## ILLINOIS POLLUTION CONTROL BOARD November 7, 1996

IN THE MATTER OF:	)	
STEEL AND FOUNDRY INDUSTRY WASTE	)	R96-3
LANDFILLS: AMENDMENTS TO 35 ILL.	)	(Rulemaking - Land)
ADM. CODE 817.309 (FACILITY LOCATION	)	,
FOR LANDFILLS ACCEPTING	)	
POTENTIALLY USABLE WASTE)	)	
Proposed Rule. Second Notice.		

OPINION AND ORDER OF THE BOARD (by R.C. Flemal):

This matter comes before the Board upon a petition for rulemaking filed by the Illinois Cast Metals Association (ICMA) on September 6, 1995, and a revised petition filed on February 26, 1996. ICMA requests that the Board's landfill regulations governing steel and foundry industry wastes be amended at 35 Ill. Adm. Code 817.309. In pertinent part, Section 817.309 establishes minimum setback distances and strata thicknesses between the waste unit and Class I and Class III groundwaters. The proposed amendments would allow the owner or operator to make a demonstration to the Illinois Environmental Protection Agency (Agency) that, the absence of natural barriers notwithstanding, the unit could be operated in a manner protective of human health and the environment.

The Board's responsibility in this matter arises from the Environmental Protection Act (Act) (415 ILCS 5/1 et seq. (1994)). The Board is charged therein to "determine, define and implement the environmental control standards applicable in the State of Illinois" (415 ILCS 5/5(b)(1994)). More generally, the Board's rulemaking charge is based on the system of checks and balances integral to Illinois environmental governance: the Board bears responsibility for the rulemaking and principal adjudicatory functions; the Agency has primary responsibility for administration of the Act and the Board's regulations, including the regulations today proposed for amendment. The Agency has indicated that it does not oppose the instant amendments. (Exh. 3.)

By today's action the Board adopts the proposed amendments for the purpose of second notice, pursuant to the Illinois Administrative Procedure Act (5 ILCS 100/1-1 et seq. (1994)). The Board makes only one minor revision today regarding use of the term "qualified geologist", as discussed below. This matter will now be filed with the Joint Committee on Administrative Rules (JCAR) for consideration by that body.

PROCEDURAL HISTORY

ICMA initially filed its proposal on September 6, 1995. By order of September 21, 1995 the Board accepted the proposal for hearing.

Hearings were scheduled on the initial proposal for November 28 and 30, 1995. However, by filing of November 22, 1995 ICMA moved the Board to postpone the hearings pending additional discussion of the proposal with the Agency.

On February 26, 1996 ICMA withdrew the initial petition and filed a revised petition. In the initial proposal, ICMA sought to effectuate the relief it desires by amendment of 35 Ill. Adm. Code 814.902<sup>1</sup>. In the revised proposal the locus of the proposed amendments was changed to 35 Ill. Adm. Code 817.309.

Public hearings were held before hearing officer Audrey Lozuk-Lawless in Chicago on June 24, 1996 and in Edwardsville on June 26, 1996. ICMA presented the testimony of Michael Slattery and Christopher Peters, both of Residuals Management Technology, Inc. The Agency presented the testimony of Kenneth W. Liss, manager of the Groundwater Unit, Permit Section, of the Agency's Bureau of Land.

In response to considerations raised at hearing, on July 18, 1996 ICMA filed revised proposed language. The Board adopted that proposal for first notice by Board order of August 15, 1996. Publication occurred at 20 Illinois Register 11554 (August 30, 1996).

Two public comments were received during the first notice public comment period. These are discussed below.

### **OVERVIEW**

The instant proposal has antecedents in two prior Board rulemakings. In the first of these, R88-7, the Board adopted a broadly-applicable and extensively-revised set of regulations governing non-hazardous waste landfills<sup>2</sup>.

The R88-7 rulemaking resulted in the establishment of several categories of waste for which waste-specific landfill standards were established. Among these, for example, are standards applicable to putrescible waste landfills. The principle underlying waste-specific landfilling standards is that different types of waste may have sufficiently different properties as to warrant distinct provisions governing their disposal. Moreover, the Board recognized at

<sup>&</sup>lt;sup>1</sup> Section 814.902 contains miscellaneous standards for operation and closure of existing landfill units that (a) accept only potentially usable steel or foundry industry waste and (b) plan to stay open for more than two years.

<sup>&</sup>lt;sup>2</sup> See, <u>In the Matter of: Development, Operating and Reporting Requirements for Non-hazardous Waste Landfills</u> R88-7, 114 PCB 483, August 17, 1990, effective September 18, 1990.

the time that the R88-7 rulemaking was finalized, that there were additional categories of wastes for which further waste-specific landfill standards might be warranted.

One such additional category explicitly identified in the R88-7 rulemaking and in the regulations themselves is "wastes generated by foundries and primary steel production facilities" (35 III. Adm. Code 811.101(b)). In the second of the two antecedent rulemakings, docketed as R90-26(A)<sup>3</sup> and R90-26(B)<sup>4</sup>, the Board adopted regulations governing the land disposal of a variety of steel and foundry industry non-hazardous wastes. Included in the R90-26 rulemakings was adoption of Part 817, which is at issue in the instant proceeding.

Today's focus is on only a small portion of Part 817<sup>5</sup>, the portion that deals with landfills that receive only potentially usable steel and foundry industry waste. Potentially usable waste (PUW) is one of the three types of steel and foundry industry wastes for which waste-specific landfilling standards were developed in the R90-26 rulemakings. "Potentially usable waste" is defined at 35 Ill. Adm. Code 810.103 as:

"Potentially usable waste" means any solid waste from the steel and foundry industries that will not decompose biologically, burn, serve as food for vectors, form a gas, cause an odor, or form a leachate that contains constituents that exceed the limits for this type of waste as specified at 35 Ill. Adm. Code 817.106.

Moreover, today's focus is only on the facility location standards for new PUW landfills and, further, only on that aspect of the location standards that concerns the positioning of the landfills with respect to Class I and Class III groundwaters<sup>6</sup>. The current regulations at Section 817.309(b) contain a prohibition against the siting of any new PUW landfill where any part of the landfill unit is within 1200 feet, vertically or horizontally, of a Class I or Class III groundwater, unless there is an intervening confining layer of specific properties:

\* \* \* \* \* \* \*

b) No part of a unit shall be located within the recharge zone or within 366 meters (1200 feet), vertically or horizontally, of that portion of a

In the Matter of: Steel and Foundry Industry Amendments to the Landfill Regulations (35 Ill. Adm. Code 810 through 815 and 817) R90-86(A), July 21, 1994.

<sup>&</sup>lt;sup>4</sup> In the Matter of: Steel and Foundry Industry Amendments to the Landfill Regulations (35 Ill. Adm. Code 810 through 815 and 817) R90-86(B), September 1, 1994.

<sup>&</sup>lt;sup>5</sup> See today's order for the full text of the table of contents of Part 817.

<sup>&</sup>lt;sup>6</sup> Class I groundwaters are groundwaters that constitute potable resources, as defined at 35 Ill. Adm. Code 620.210. Class III groundwaters are groundwaters that, pursuant to 35 Ill. Adm. Code 620.250, are explicitly designated as "Special Resources Groundwaters"; as of this date, no Class III groundwaters have been designated.

stratigraphic unit containing Class I or Class III groundwater as defined at 35 III. Adm. Code 620, unless there is a stratum between the bottom of the waste disposal unit and the top of the Class I or Class III groundwater that meets the following minimum requirements:

- 1) The stratum has a minimum thickness of 15.2 meters (50 feet);
- 2) The maximum hydraulic conductivity in both the horizontal and vertical directions is no more than  $1 \times 10^{-7}$  centimeters per second, as determined by in situ borehole or equivalent tests;
- 3) There is no indication of continuous sand or silt seams, faults, fractures or cracks within the stratum that may provide parts for migration; and
- 4) Age dating of extracted water samples from both the aquifer and the stratum indicates that the time of travel for water percolating downward through the relatively impermeable stratum is no faster than 15.2 meters (50 feet) in 100 years.

\* \* \* \* \* \* \*

Today's proposal would retain this prohibition generally, but would allow for an exception if the owner or operator of the unit successfully demonstrates to the Agency that siting of the unit will not degrade the use of any Class I groundwater or adversely impact any existing Class III groundwater.

The Board notes that, although Part 817 is titled "Requirements for <u>New Steel</u> and Foundry Industry Wastes Landfills" (emphasis added), today's proposed amendments would, through the operation of 35 Ill. Adm. Code 814.902(a), also apply to existing PUW landfills.

## **JUSTIFICATION**

### **Environmental Considerations**

The purpose of the existing Section 817.309(b) is to provide assurance that steel and foundry industry waste landfills will not be sited in such a manner as to cause or allow pollution of adjacent groundwaters. This assurance is currently provided by the requirement of a large spacial separation between the landfill and groundwater, or by the requirement of a intervening confining layer. Today's proposal offers a third assurance mechanism. That mechanism is a demonstration made to and accepted by the Agency that the landfill will not pollute the groundwater based on the site-specific character of both the landfill and the groundwater.

This third exemption would require the operator or owner of the landfill to demonstrate to the Agency that the unit will not impact any existing Class III groundwater or impact any

Class I groundwater such that treatment or further treatment will be required to allow reasonable use of such Class I groundwater for potable water supply purposes. According to Christopher Peters of ICMA, there are certain hydrogeologic situations in which existing PUW landfills pose a negligible potential for impacts to downgradient potable water supply wells or to surface water. ICMA requests that an applicant should be allowed to site or continue to operate a PUW landfill if such a technical demonstration is made.

ICMA's revised language, at the request of the Agency, proposes that this demonstration be made through the use of a site-specific groundwater model developed and evaluated by an Illinois-licensed Professional Geologist, or through other appropriate means prepared by an Illinois-licensed Professional Geologist such as historical knowledge of local conditions or regional geological and hydrogeological data. However, because the licensing program for Illinois-licensed Professional Geologists is just now developing, ICMA states that there will not be an adequate supply of licensed Professional Geologists until mid-1997. The Board finds this current shortage to be a problem, and is adverse to conditioning the exemption to become effective at some future uncertain date. Because the licensing program is not in place at this time, the Board will accordingly not require the demonstration be completed by an Illinois-licensed Professional Geologist. Additionally the Board will not use the term "qualified geologist". In the Board's experience a term such as "qualified geologist" is objectionable unless there is a specific definition of what constitutes being "qualified"; no definition has been offered. Therefore, rather than specifying any particular type of geologist, the Board believes that it is appropriate to simply rely on the Agency's expertise to review and approve the demonstration made by the owner or operator of the unit.

## **Economic Considerations**

ICMA describes the economic considerations motivating their proposal as follows:

ICMA is aware of several facilities in current operation who have the potential to benefit from this proposal. It is also believed that there are several inactive landfills which, if the rule is changed, have the potential to re-open. Finally, the proposed revision will allow new landfills to be sited in locations that are currently prohibited even though a landfill would have no reasonable likelihood of adversely impacting downgradient groundwater users.

We have prepared disposal cost estimates for an average-sized foundry who: (1) sends its waste to an offsite landfill; (2) operates a chemical waste landfill; or (3) operates a PUW landfill . . . Of interest to this rule making is the difference between offsite disposal and disposal in a PUW landfill. That difference is . . . estimated at \$1,327,560 per year per landfill.

In addition, diversion of PUW wastes to chemical waste landfills would reduce the capacity of those landfills by hundreds of thousands of tons per year. ICMA believes the limited capacity of chemical waste landfills should be used for more difficult to manage industrial wastes which create a greater threat to the environment than does PUW.

An additional benefit of this rule making is the continued segregation of PUW from chemical wastes. Since the promulgation of Part 817 in July 1994, the Illinois Cast Metals Association (ICMA) has continued to work with regulators and the foundry industry to promote beneficial use of foundry sand materials. ICMA held several seminars to promote the new rule making and educate the membership on protocol for becoming a beneficial use participant.

ICMA has additionally sought out new approaches to promote beneficial use on a statewide basis. One such approach was to meet with Illinois Department of Transportation (IDOT) officials in the Bureau of Materials and Physical Research Division to seek their participation in utilizing foundry byproduct materials for highway construction material. IDOT is considering a specification for foundry byproducts materials in construction back fill and indicated they will work with individual foundries to qualify materials for construction use.

ICMA has initiated a contract with the University of Illinois to conduct research on beneficial use of foundry materials for the potential use in improving the drainage of Illinois farm soils and the project is underway. The research proposal from the University, entitled "Use of Foundry Green Sand to Improve the Physical Properties of Poorly Drained Soils," . . . represents the scope of the project.

Substantial supplies of Potentially Useable Waste make it much easier to convince a possible purchaser to consider the use of the material. ICMA believes the current rule making effort is necessary to promote continuation of PUW sites to assure a supply of construction materials when needed.

\* \* \* \* \* \* \*

ICMA believes that the proposed revision will result in a net economic and environmental benefit to the State of Illinois. It will allow existing facilities to continue to operate and new facilities to be sited without seeking Board approval for each siting decision.

Exhibit 1 at p 4-6

## **PUBLIC COMMENTS**

Two public comments (PC) have been filed during the first notice public comment period. The first, PC #1, was filed on September 19, 1996 by Browning-Ferris Industries (BFI). BFI contends that the proposed amendments would "weaken an already insufficiently stringent set of regulations governing steel and foundry industry waste landfills". (PC #1 at 1.) BFI further contends that standards for steel and foundry industry waste landfills "are far less protective of the environment than the criteria applicable to municipal solid waste landfills". (Id.)

BFI also contends that the proposed language "is so vague and amorphous that inconsistent criteria will undoubtedly be developed and applied" to individual landfills. (PC #1 at 1.) BFI observes that "a long line of cases makes clear that the Fourteenth Amendment of the U.S. Constitution requires that a regulation or law give adequate notice to those who must conform their conduct and be sufficient definite to provide standards for enforcement and adjudications". (Id. at 2.) To address the alleged vagueness, BFI proposes certain revised language that it urges the Board to adopt in place of the first notice language. (Id.)

PC #2 was filed by ICMA on October 15, 1996. ICMA contends that the proposed amendments represent an environmentally safe strategy. (PC #2 at 1.) ICMA observes that it, along with the Agency, "expended a substantial amount of time in developing a site evaluation protocol which would be sufficiently broad in scope to apply to a variety of potential scenarios while providing IEPA with the necessary data to properly evaluate a site's suitability". (Id.) ICMA adds that "notwithstanding Commenter BFI's assertions, the proposed language does exactly that". (Id.)

ICMA also discusses the various cases cited by BFI as support for the alleged unconstitutionality of the proposal. (PC #2 at 2-4.) ICMA concludes that "none of the cases cited by BFI even remotely suggest that [the] level of flexibility [in the proposed rule] raises Constitutional vagueness concerns". (Id. at 4.)

BFI's assertions notwithstanding, the Board continues to believe that the rules as proposed for first notice provide appropriate environmental protection under the narrow range of wastes and circumstances covered by the instant proposal. The Board does not accept BFI's premise that, because the proposed rules are different from those applied to municipal solid waste landfills, the proposed rules are less protective of the environment. The Board similarly believes that BFI's contention that the proposal is unacceptably vague is without merit.

## CONCLUSION

The Board believes that ICMA has presented evidence warranting further consideration of this matter. Accordingly, we today find that the record before us justifies adopting the proposal for second notice.

### ORDER

The Board hereby directs that second notice of the following proposed amendments be submitted to the Joint Committee on Administrative Rules.

TITLE 35: ENVIRONMENTAL PROTECTION
SUBTITLE G: WASTE DISPOSAL
CHAPTER I: POLLUTION CONTROL BOARD
SUBCHAPTER i: SOLID WASTE AND SPECIAL WASTE HAULING

# REQUIREMENTS FOR NEW STEEL AND FOUNDRY INDUSTRY WASTES LANDFILLS

## SUBPART A: GENERAL REQUIREMENTS

Scope and Applicability
<b>Determination of Waste Status</b>
Sampling Frequency
Waste Classification
Waste Classification Limits
Waste Mining

## SUBPART B: STANDARDS FOR MANAGEMENT OF BENEFICIALLY USABLE STEEL AND FOUNDRY INDUSTRY WASTES

Section	
817.201	Scope and Applicability
817.202	Limitations on Use
817.203	Notification
817.204	Long-Term Storage

## SUBPART C: STEEL AND FOUNDRY INDUSTRY POTENTIALLY USABLE WASTE LANDFILLS

Section	
817.301	Scope and Applicability
817.302	Design Period
817.303	Final Cover
817.304	Final Slope and Stabilization
817.305	Leachate Sampling
817.306	Load Checking
817.307	Closure
817.308	Nuisance Precautions
817.309	Facility Location

# SUBPART D: NEW STEEL AND FOUNDRY INDUSTRY LOW RISK WASTE LANDFILLS

Section	
817.401	Scope and Applicability
817.402	Facility Location
817.403	Design Period
817.404	Foundation and Mass Stability Analysis
817.405	Foundation Construction
817.406	Liner Systems
817.407	Leachate Drainage System
817.408	Leachate Collection System
817.409	Leachate Treatment and Disposal System
817.410	Final Cover System

817.411	Hydrogeologic Site Investigations
817.412	Plugging and Sealing of Drill Holes
817.413	Groundwater Impact Assessment
817.414	Design, Construction and Operation of Groundwater Monitoring Systems
817.415	Groundwater Monitoring Programs
817.416	Groundwater Quality Standards
817.417	Waste Placement
817.418	Final Slope and Stabilization
817.419	Load Checking

## SUBPART E: CONSTRUCTION QUALITY ASSURANCE PROGRAMS

#### Section

Scope and Applicability

## Section

817. Appendix A Organic Chemical Constituents List

AUTHORITY: Implementing Sections 5, 21, 21.1, 22, 22.17, 28.1, and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111½, pars. 1005, 1021, 1021.1, 1022, 1022.17, 1028.1 and 1027 [415 ILCS 5/5, 5/21, 5/21.1, 5/22, 5/22.17, 5/28.1, and 5/27]).

SOURCE:	Adopted in R90-26(	A) at 18 Ill. Reg	. 12411,	effective August	t 1, 1994; a	ımended in
R90-26(B)	at 18 Ill. Reg. 14370	, effective Septer	mber 13	, 1994; amended	in R96-3 a	t 21 Ill.
Reg.	, effective					

## Section 817.309 Facility Location

- a) No part of a unit shall be located within a setback zone established pursuant to Section 14.2 or 14.3 of the Act.
- b) No part of a unit shall be located within the recharge zone or within 366 meters (1200 feet), vertically or horizontally, of that portion of a stratigraphic unit containing Class I or Class III groundwater as defined at 35 Ill. Adm. Code 620, unless:
  - <u>T</u>there is a stratum between the bottom of the waste disposal unit and the top of the Class I or Class III groundwater that meets the following minimum requirements:
    - A)1) The stratum has a minimum thickness of 15.2 meters (50 feet);
    - <u>B)2)</u> The maximum hydraulic conductivity in both the horizontal and vertical directions is no more than 1 x 10<sup>-7</sup> centimeters per second, as determined by in situ borehole or equivalent tests;

- <u>C)3)</u> There is no indication of continuous sand or silt seams, faults, fractures or cracks within the stratum that may provide <u>paths</u> parts for migration; and
- <u>D)4)</u> Age dating of extracted water samples from both the aquifer and the stratum indicates that the time of travel for water percolating downward through the relatively impermeable stratum is no faster than 15.2 meters (50 feet) in 100 years; or
- The owner or operator of the unit has demonstrated to the Agency, through the use of a site-specific groundwater model, or through other appropriate means, such as historical knowledge of local conditions or regional geological and hydrogeological data, that operation of the unit will not adversely impact any existing Class III groundwater or impact any Class I groundwater such that treatment or further treatment will be required to allow reasonable use of such Class I groundwater for potable water supply purposes.
  - A) Factors to be considered in evaluating whether a Class I groundwater may be reasonably used for potable supply purposes include, but are not limited to:
    - i) Physical or technological practicability of development;
    - <u>ii)</u> Existence of deed restrictions or other legal mechanisms for imposing a restriction on land use; and
    - iii) The nature of an existing use of the groundwater.
  - B) In performing groundwater modeling, the owner or operator shall:
    - i) Estimate the amount of seepage from the unit during operations assuming that the actual design standards for the unit apply;
    - ii) Determine the concentration of constituents in the leachate from actual leachate samples from the waste or similar waste, or laboratory-derived extracts;
    - <u>Collect information to develop the site-specific</u> groundwater model (e.g., hydraulic conductivity, gradients, hydrogeology, stratigraphy);

- iv) Develop a conceptual groundwater flow model of the site to determine the soil units through which leachate may migrate;
- v) If leachate from the unit is expected to contain organic constituents in excess of the MALCs for beneficial usable waste, determine the organic carbon content for soil units through which the leachate constituents may migrate; and
- vi) Determine the retardation factor for constituents of interest based on traditional hydrogeological methods.
- c) Subsection (b) shall not apply to units that accept only beneficially useable waste.
- d) A facility located within 152 meters (500 feet) of the right of way of a township or county road or State or interstate highway shall have its operations screened from view by a barrier of natural objects, fences, barricades or plants no less than 2.44 meters (8 feet) in height.
- e) No part of a unit shall be located closer than 152 meters (500 feet) from an occupied dwelling, school, or hospital that was occupied on the date when the operator first applied for a permit to develop the unit or the facility containing the unit, unless the owner of such dwelling, school, or hospital provides permission to the operator, in writing, for a closer distance.

(Source: Amended at 21 Ill. Reg. \_\_\_\_\_, effective \_\_\_\_\_.)

IT IS SO ORDERED.	
Board Member McFawn dissented and Board Member Hennessey abstained.	
I, Dorothy M. Gunn, Clerk of the Illinois Pollution Control Board, hereby certify that we opinion and order was adopted on the day of, 1990 te of	
Dorothy M. Gunn, Clerk	
Illinois Pollution Control Board	