

ATTACHMENT 2
CONTAMINANT TRANSPORT MODEL

City Water, Light & Power

CCR Impoundments – Lakeside and Dallman Ash Ponds

Springfield, Sangamon County, Illinois

Closure Alternatives Assessment - Contaminant Transport Model

October 2021



Prepared for:
City Water, Light & Power
3100 Stevenson Drive
Springfield, Illinois 62703



3300 Ginger Creek Drive, Springfield, IL 62711 | 217.787.2334

ILLINOIS | MISSOURI | INDIANA

TABLE OF CONTENTS

EXECUTIVE SUMMARY	I
1. INTRODUCTION	1
2. SURFACE IMPOUNDMENT CONSTRUCTION	3
3. SUBSURFACE CONDITIONS AT THE CCR SURFACE IMPOUNDMENTS	4
3.1 Surficial Deposits	5
3.2 Uppermost Bedrock	8
3.3 Hydrogeologic Units.....	8
3.4 Groundwater Movement.....	9
4. CONCEPTUAL MODEL	10
4.1 Conversion Assumptions	10
4.2 Transport Processes.....	11
5. MATHEMATICAL MODEL	12
5.1 Model Input and Sensitivity Analysis	13
5.1.1 Two-Dimensional Profile Setup.....	13
5.1.2 Closure-In-Place Model Input Parameters	13
5.1.2.1 Source Concentration.....	13
5.1.2.2 Base Width and Surface Width.....	14
5.1.2.3 Layer Thickness and Number of Sublayers	14
5.1.2.4 Dry Density and Distribution Coefficient	14
5.1.2.5 Effective Porosity.....	14
5.1.2.6 Darcy Velocity	15
5.1.2.7 Coefficients of Hydrodynamic Dispersion	17
5.1.2.8 Lateral Distances.....	20
5.1.2.9 Integration	21
5.1.3 Closure-By-Removal Model Input Parameters	21
6. CONTAMINANT TRANSPORT RESULTS.....	22
6.1 Closure-In-Place	22
6.2 Closure-by-Removal	24
7. CCR SURFACE IMPOUNDMENT CONTAMINANT TRANSPORT EVALUATION RESULTS.....	27
8. CONCLUSIONS	28

FIGURES

Figure 1 – Site Location

Figure 2 – Groundwater Monitoring Network

Figure 3 – 1976 Site Survey

Figure 4 – Conceptual Model

APPENDICES

Appendix A: Hydrologic Evaluation of Landfill Performance (HELP) Output

Appendix B: MIGRATE Model Input and Output Files