

# OFFICE OF THE SECRETARY OF STATE

JESSE WHITE • Secretary of State

November 13, 2009

# RECEIVED CLERK'S OFFICE

NOV 1 7 2009

STATE OF ILLINOIS Pollution Control Board

POLLUTION CONTROL BOARD JOHN THERRIAULT ASSISTANT CLERK 100 W RANDOLPH ST, STE 11-500 CHICAGO, IL 60601

## Dear JOHN THERRIAULT ASSISTANT CLERK

Your rules Listed below met our codification standards and have been published in Volume 33, Issue 47 of the Illinois Register, dated 11/20/2009.

PROPOSED RULES Organic Material Emission Standard and Limitations for the Chicago Area 35 Ill. Adm. Code 218 Point of Contact: Nancy Miller	16399
Organic Material Emission Standards and Limitations for the Metro East Area 35 Ill. Adm. Code 219 Point of Contact: Nancy Miller	16460

If you have any questions, you may contact the Administrative Code Division at (217) 782 - 7017.



## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- 1) <u>Heading of the Part</u>: Organic Material Emission Standard and Limitations for the Chicago Area
- 2) <u>Code Citation</u>: 35 Ill. Adm. Code 218

3)	Section Numbers:	Proposed Action:	RECEIVED CLERK'S OFFICE
	218.106 218.204 218.205 218.207 218.210 218.211 218.212 218.218	Amended Amended Amended Amended Amended Amended New	NOV 1 7 2009 STATE OF ILLINOIS Pollution Control Board

- 4) <u>Statutory Authority</u>: Implementing Section 10 and authorized by Sections 27, 28, and 28.5 of the Environmental Protection Act [415 ILCS 5/10, 27, 28, and 28.5]
- 5) A Complete Description of the Subjects and Issues Involved: The proposed rulemaking is intended to satisfy Illinois' obligation to submit a State Implementation Plan addressing requirements under Sections 172 and 182 of the federal Clean Air Act, 42 U.S.C. § 7401 et seq., for sources of volatile organic material (VOM) emissions in areas designated as nonattainment with respect to the ozone National Ambient Air Quality Standard. The United States Environmental Protection Agency (USEPA) issued Control Techniques Guidelines (CTGs) for the following Group III Consumer and Commercial Product Categories: Paper, Film, and Foil Coatings, Metal Furniture Coatings, and Large Appliance Coatings. In the CTGs, the USEPA recommended control measures that it believes constitute reasonably available control technology for those product categories. The Illinois EPA proposes amending Parts 218 to implement such recommendations for the Chicago nonattainment area. Generally, the proposal amends VOM content limitations and exclusions, requires that metal furniture and large appliance coating lines comply with application method limitations, and requires that subject coating lines implement specified work practices for cleaning materials and/or cleaning-related activities.
- 6) <u>Published studies or reports, and sources of underlying data, used to compose this</u> <u>rulemaking:</u> The regulatory proposal included the Illinois EPA's *Technical Support Document*, which relied on several sources. Copies of the documents the Illinois EPA relied upon are available for review with the Pollution Control Board and are listed

received

NOV - 5 2009

EOS-CODE DIV.

## POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

below:

*Control Techniques Guidelines for Paper, Film, and Foil Coatings*, United States Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 2007.

*Control Techniques Guidelines for Metal Furniture Coatings*, United States Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 2007.

*Control Techniques Guidelines for Large Appliance Coatings*, United States Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 2007.

- 7) Will this proposed amendment replace an emergency rule currently in effect? No.
- 8) <u>Does this rulemaking contain an automatic repeal date</u>? No.
- 9) Does this proposed amendment contain incorporations by reference? No.
- 10) Are there any other proposed amendments pending on this Part? No.
- Statement of Statewide Policy Objectives: This proposed rule does not create or enlarge a State mandate, as defined in Section 3(b) of the State Mandates Act. [30 ILCS 805/3(b) (2006)].
- 12) <u>Time, Place, and Manner in which interested persons may comment on this proposed</u> <u>rulemaking</u>:

Interested persons may request copies of the Board's opinion and order by calling the Clerk's office at 312-814-3620, or may download copies from the Board's Web site at <u>www.ipcb.state.il.us</u>. The Board will accept written public comment on this proposal for 45 days after the date of publication in the *Illinois Register*. Comments should reference Docket R10-10 and be addressed to:

#### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

Clerk's Office Illinois Pollution Control Board 100 W. Randolph St., Suite 11-500 Chicago, IL 60601

The Board has scheduled hearings according to the deadlines and for the purposes established by Section 28.5. Each hearing will continue from day-to-day until business is completed:

First hearing:	Wednesday, December 9, 2009 10:00 AM James R. Thompson Center 100 W. Randolph St. Pollution Control Board Conference Room 11-512 Chicago, Illinois
Second hearing: (if necessary)	Wednesday, January 6, 2010 10:00 AM Michael A. Bilandic Building 160 N. LaSalle Street Room N-505 Chicago, Illinois
Third hearing: (if necessary)	Wednesday, January 20, 2010 10:00 AM Michael A. Bilandic Building 160 N. LaSalle Street Room N-505 Chicago, Illinois

A November 5, 2009 hearing officer order contains additional details concerning participation in the rulemaking. For more information contact Hearing Officer Tim Fox at 312-814-6085 or email at foxt@ipcb.state.il.us.

- 13) Initial Regulatory Flexibility Analysis:
  - A. Types of small businesses, small municipalities and not for profit corporations affected: this rulemaking will impact any small business, small municipality, and not for profit corporation that falls within one of the Group III Product Categories

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

and meets the applicability thresholds specified in the proposal.

- B. Reporting, bookkeeping or other procedures required for compliance: the proposed rulemaking requires that the owner or operator of a subject source perform emissions monitoring, submit certifications, complete required tests, and maintain records and make reports as required.
- C. Types of Professional skills necessary for compliance: no professional skills beyond those currently required by the existing state and federal air pollution control regulations applicable to affected sources will be required.
- 14) <u>Regulatory Agenda on which this rulemaking was summarized</u>: July 2009

The full text of the Proposed Amendment(s) begins on the next page:

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

## TITLE 35: ENVIRONMENTAL PROTECTION SUBTITLE B: AIR POLLUTION CHAPTER I: POLLUTION CONTROL BOARD SUBCHAPTER c: EMISSIONS STANDARDS AND LIMITATIONS FOR STATIONARY SOURCES

## PART 218 ORGANIC MATERIAL EMISSION STANDARDS AND LIMITATIONS FOR THE CHICAGO AREA

#### SUBPART A: GENERAL PROVISIONS

Section

- 218.100 Introduction
- 218.101 Savings Clause
- 218.102 Abbreviations and Conversion Factors
- 218.103 Applicability
- 218.104 Definitions
- 218.105 Test Methods and Procedures
- 218.106 Compliance Dates
- 218.107 Operation of Afterburners
- 218.108 Exemptions, Variations, and Alternative Means of Control or Compliance Determinations
- 218.109 Vapor Pressure of Volatile Organic Liquids
- 218.110 Vapor Pressure of Organic Material or Solvent
- 218.111 Vapor Pressure of Volatile Organic Material
- 218.112 Incorporations by Reference
- 218.113 Monitoring for Negligibly-Reactive Compounds
- 218.114 Compliance with Permit Conditions

# SUBPART B: ORGANIC EMISSIONS FROM STORAGE AND LOADING OPERATIONS

## Section

- 218.119 Applicability for VOL
- 218.120 Control Requirements for Storage Containers of VOL
- 218.121 Storage Containers of VPL
- 218.122 Loading Operations
- 218.123 Petroleum Liquid Storage Tanks
- 218.124 External Floating Roofs
- 218.125 Compliance Dates

## POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

- 218.126 Compliance Plan (Repealed)
- 218.127 Testing VOL Operations
- 218.128 Monitoring VOL Operations
- 218.129 Recordkeeping and Reporting for VOL Operations

# SUBPART C: ORGANIC EMISSIONS FROM MISCELLANEOUS EQUIPMENT

Section

- 218.141 Separation Operations
- 218.142 Pumps and Compressors
- 218.143 Vapor Blowdown
- 218.144 Safety Relief Valves

#### SUBPART E: SOLVENT CLEANING

- Section
- 218.181 Solvent Cleaning in General
- 218.182 Cold Cleaning
- 218.183 Open Top Vapor Degreasing
- 218.184 Conveyorized Degreasing
- 218.185 Compliance Schedule (Repealed)
- 218.186 Test Methods

### SUBPART F: COATING OPERATIONS

Section

- 218.204 Emission Limitations
- 218.205 Daily-Weighted Average Limitations
- 218.206 Solids Basis Calculation
- 218.207 Alternative Emission Limitations
- 218.208 Exemptions from Emission Limitations
- 218.209 Exemption from General Rule on Use of Organic Material
- 218.210 Compliance Schedule
- 218.211 Recordkeeping and Reporting
- 218.212 Cross-Line Averaging to Establish Compliance for Coating Lines
- 218.213 Recordkeeping and Reporting for Cross-Line Averaging Participating Coating Lines
- 218.214 Changing Compliance Methods
- 218.215 Wood Furniture Coating Averaging Approach
- 218.216 Wood Furniture Coating Add-On Control Use
- 218.217 Wood Furniture Coating Work Practice Standards
- 218.218 Work Practice Standards for Paper Coatings, Metal Furniture Coatings, and Large

#### POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

## **Appliance Coatings**

## SUBPART G: USE OF ORGANIC MATERIAL

Section

- 218.301 Use of Organic Material
- 218.302 Alternative Standard
- 218.303 Fuel Combustion Emission Units
- 218.304 Operations with Compliance Program

### SUBPART H: PRINTING AND PUBLISHING

Section

- 218.401 Flexographic and Rotogravure Printing
- 218.402 Applicability
- 218.403 Compliance Schedule
- 218.404 Recordkeeping and Reporting
- 218.405 Lithographic Printing: Applicability
- 218.406 Provisions Applying to Heatset Web Offset Lithographic Printing Prior to March 15, 1996
- 218.407 Emission Limitations and Control Requirements for Lithographic Printing Lines On and After March 15, 1996
- 218.408 Compliance Schedule for Lithographic Printing On and After March 15, 1996
- 218.409 Testing for Lithographic Printing On and After March 15, 1996
- 218.410 Monitoring Requirements for Lithographic Printing
- 218.411 Recordkeeping and Reporting for Lithographic Printing

## SUBPART Q: SYNTHETIC ORGANIC CHEMICAL AND POLYMER MANUFACTURING PLANT

Section

- 218.421 General Requirements
- 218.422 Inspection Program Plan for Leaks
- 218.423 Inspection Program for Leaks
- 218.424 Repairing Leaks
- 218.425 Recordkeeping for Leaks
- 218.426 Report for Leaks
- 218.427 Alternative Program for Leaks
- 218.428 Open-Ended Valves
- 218.429 Standards for Control Devices
- 218.430 Compliance Date (Repealed)
- 218.431 Applicability
- 218.432 Control Requirements

## POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

- 218.433 Performance and Testing Requirements
- 218.434 Monitoring Requirements
- 218.435 Recordkeeping and Reporting Requirements
- 218.436 Compliance Date

## SUBPART R: PETROLEUM REFINING AND RELATED INDUSTRIES; ASPHALT MATERIALS

#### Section

- 218.441 Petroleum Refinery Waste Gas Disposal
- 218.442 Vacuum Producing Systems
- 218.443 Wastewater (Oil/Water) Separator
- 218.444 Process Unit Turnarounds
- 218.445 Leaks: General Requirements
- 218.446 Monitoring Program Plan for Leaks
- 218.447 Monitoring Program for Leaks
- 218.448 Recordkeeping for Leaks
- 218.449 Reporting for Leaks
- 218.450 Alternative Program for Leaks
- 218.451 Sealing Device Requirements
- 218.452 Compliance Schedule for Leaks
- 218.453 Compliance Dates (Repealed)

## SUBPART S: RUBBER AND MISCELLANEOUS PLASTIC PRODUCTS

- Section
- 218.461 Manufacture of Pneumatic Rubber Tires
- 218.462 Green Tire Spraying Operations
- 218.463 Alternative Emission Reduction Systems
- 218.464 Emission Testing
- 218.465 Compliance Dates (Repealed)
- 218.466 Compliance Plan (Repealed)

#### SUBPART T: PHARMACEUTICAL MANUFACTURING

- Section
- 218.480 Applicability
- 218.481 Control of Reactors, Distillation Units, Crystallizers, Centrifuges and Vacuum Dryers
- 218.482 Control of Air Dryers, Production Equipment Exhaust Systems and Filters
- 218.483 Material Storage and Transfer
- 218.484 In-Process Tanks
- 218.485 Leaks

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- 218.486 Other Emission Units
- 218.487 Testing
- 218.488 Monitoring for Air Pollution Control Equipment
- 218.489 Recordkeeping for Air Pollution Control Equipment

## SUBPART V: BATCH OPERATIONS AND AIR OXIDATION PROCESSES

- Section
- 218.500 Applicability for Batch Operations
- 218.501 Control Requirements for Batch Operations
- 218.502 Determination of Uncontrolled Total Annual Mass Emissions and Average Flow Rate Values for Batch Operations
- 218.503 Performance and Testing Requirements for Batch Operations
- 218.504 Monitoring Requirements for Batch Operations
- 218.505 Reporting and Recordkeeping for Batch Operations
- 218.506 Compliance Date
- 218.520 Emission Limitations for Air Oxidation Processes
- 218.521 Definitions (Repealed)
- 218.522 Savings Clause
- 218.523 Compliance
- 218.524 Determination of Applicability
- 218.525 Emission Limitations for Air Oxidation Processes
- 218.526 Testing and Monitoring
- 218.527 Compliance Date (Repealed)

## SUBPART W: AGRICULTURE

218.541 Pesticide Exception

## SUBPART X: CONSTRUCTION

#### Section

Section

- 218.561 Architectural Coatings
- 218.562 Paving Operations
- 218.563 Cutback Asphalt

## SUBPART Y: GASOLINE DISTRIBUTION

- Section 218.581 Bulk Gasoline Plants
- 218.582 Bulk Gasoline Terminals
- 218.583 Gasoline Dispensing Operations Storage Tank Filling Operations
- 218.584 Gasoline Delivery Vessels

## POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

- 218.585 Gasoline Volatility Standards
- 218.586 Gasoline Dispensing Operations Motor Vehicle Fueling Operations

#### SUBPART Z: DRY CLEANERS

## Section

- 218.601 Perchloroethylene Dry Cleaners (Repealed)
- 218.602 Applicability (Repealed)
- 218.603 Leaks (Repealed)
- 218.604 Compliance Dates (Repealed)
- 218.605 Compliance Plan (Repealed)
- 218.606 Exception to Compliance Plan (Repealed)
- 218.607 Standards for Petroleum Solvent Dry Cleaners
- 218.608 Operating Practices for Petroleum Solvent Dry Cleaners
- 218.609 Program for Inspection and Repair of Leaks
- 218.610 Testing and Monitoring
- 218.611 Applicability for Petroleum Solvent Dry Cleaners
- 218.612 Compliance Dates (Repealed)
- 218.613 Compliance Plan (Repealed)

#### SUBPART AA: PAINT AND INK MANUFACTURING

- Section
- 218.620 Applicability
- 218.621 Exemption for Waterbase Material and Heatset Offset Ink
- 218.623 Permit Conditions (Repealed)
- 218.624 Open Top Mills, Tanks, Vats or Vessels
- 218.625 Grinding Mills
- 218.626 Storage Tanks
- 218.628 Leaks
- 218.630 Clean Up
- 218.636 Compliance Schedule
- 218.637 Recordkeeping and Reporting

#### SUBPART BB: POLYSTYRENE PLANTS

- Section
- 218.640 Applicability
- 218.642 Emissions Limitation at Polystyrene Plants
- 218.644 Emissions Testing

# SUBPART CC: POLYESTER RESIN PRODUCT MANUFACTURING PROCESS

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- Section
- 218.660 Applicability
- 218.666 Control Requirements
- 218.667 Compliance Schedule
- 218.668 Testing
- 218.670 Recordkeeping and Reporting for Exempt Emission Units
- 218.672 Recordkeeping and Reporting for Subject Emission Units

## SUBPART DD: AEROSOL CAN FILLING

- Section
- 218.680 Applicability
- 218.686 Control Requirements
- 218.688 Testing
- 218.690 Recordkeeping and Reporting for Exempt Emission Units
- 218.692 Recordkeeping and Reporting for Subject Emission Units

## SUBPART FF: BAKERY OVENS (REPEALED)

- Section
- 218.720 Applicability (Repealed)
- 218.722 Control Requirements (Repealed)
- 218.726 Testing (Repealed)
- 218.727 Monitoring (Repealed)
- 218.728 Recordkeeping and Reporting (Repealed)
- 218.729 Compliance Date (Repealed)
- 218.730 Certification (Repealed)

## SUBPART GG: MARINE TERMINALS

- Section
- 218.760 Applicability
- 218.762 Control Requirements
- 218.764 Compliance Certification
- 218.766 Leaks
- 218.768 Testing and Monitoring
- 218.770 Recordkeeping and Reporting

## SUBPART HH: MOTOR VEHICLE REFINISHING

- Section
- 218.780 Emission Limitations
- 218.782 Alternative Control Requirements
- 218.784 Equipment Specifications

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- 218.786 Surface Preparation Materials
- 218.787 Work Practices
- 218.788 Testing
- 218.789 Monitoring and Recordkeeping for Control Devices
- 218.790 General Recordkeeping and Reporting (Repealed)
- 218.791 Compliance Date
- 218.792 Registration
- 218.875 Applicability of Subpart BB (Renumbered)
- 218.877 Emissions Limitation at Polystyrene Plants (Renumbered)
- 218.879 Compliance Date (Repealed)
- 218.881 Compliance Plan (Repealed)
- 218.883 Special Requirements for Compliance Plan (Repealed)
- 218.886 Emissions Testing (Renumbered)

## SUBPART PP: MISCELLANEOUS FABRICATED PRODUCT MANUFACTURING PROCESSES

## Section

- 218.920 Applicability
- 218.923 Permit Conditions (Repealed)
- 218.926 Control Requirements
- 218.927 Compliance Schedule
- 218.928 Testing
- 218.929 Cementable and Dress or Performance Shoe Leather

# SUBPART QQ: MISCELLANEOUS FORMULATION MANUFACTURING PROCESSES

## Section

- 218.940 Applicability
- 218.943 Permit Conditions (Repealed)
- 218.946 Control Requirements
- 218.947 Compliance Schedule
- 218.948 Testing

## SUBPART RR: MISCELLANEOUS ORGANIC CHEMICAL MANUFACTURING PROCESSES

- Section
- 218.960 Applicability
- 218.963 Permit Conditions (Repealed)
- 218.966 Control Requirements
- 218.967 Compliance Schedule

## POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

218.968 Testing

#### SUBPART TT: OTHER EMISSION UNITS

- Section
- 218.980 Applicability
- 218.983 Permit Conditions (Repealed)
- 218.986 Control Requirements
- 218.987 Compliance Schedule
- 218.988 Testing

## SUBPART UU: RECORDKEEPING AND REPORTING

Section		
218.990	Exempt Emis	sion Units
218.991	Subject Emiss	sion Units
218.APPEND	DIX A:	List of Chemicals Defining Synthetic Organic Chemical and Polymer Manufacturing
218.APPEND	IX B:	VOM Measurement Techniques for Capture Efficiency (Repealed)
218.APPEND	DIX C:	Reference Methods and Procedures
218.APPEND	DIX D:	Coefficients for the Total Resource Effectiveness Index (TRE) Equation
218.APPEND	IX E:	List of Affected Marine Terminals
218.APPEND	DIX G:	TRE Index Measurements for SOCMI Reactors and Distillation Units
218.APPEND	IX H:	Baseline VOM Content Limitations for Subpart F, Section 218.212 Cross-Line Averaging

AUTHORITY: Implementing Section 10 and authorized by Sections 27, 28, and 28.5 of the Environmental Protection Act [415 ILCS 5/10, 27, 29 and 28.5].

SOURCE: Adopted at R91-7 at 15 Ill. Reg. 12231, effective August 16, 1991; amended in R91-24 at 16 Ill. Reg. 13564, effective August 24, 1992; amended in R93-9 at 17 Ill. Reg. 16636, effective September 27, 1993; amended in R93-14 at 18 Ill. Reg. at 1945, effective January 24, 1994; amended in R94-12 at 18 Ill. Reg. 14973, effective September 21, 1994; amended in R94-15 at 18 Ill. Reg. 16392, effective October 25, 1994; amended in R94-16 at 18 Ill. Reg. 16950, effective November 15, 1994; amended in R94-21, R94-31 and R94-32 at 19 Ill. Reg. 6848, effective May 9, 1995; amended in R94-33 at 19 Ill. Reg. 7359, effective May 22, 1995; amended in R94-13 at 20 Ill. Reg. 14428, effective October 17, 1996; amended in R97-24 at 21 Ill. Reg. 7708, effective June 9, 1997; amended in R97-31 at 22 Ill. Reg. 3556, effective

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

February 2, 1998; amended in R98-16 at 22 Ill. Reg. 14282, effective July 16, 1998; amended in R02-20 at 27 Ill. Reg 7283, effective April 8, 2003; amended in R04-12/20 at 30 Ill. Reg. 9684, effective May 15, 2006; amended in R06-21 at 31 Ill. Reg. 7086, effective April 30, 2007; amended in R10-10 at 34 Ill. Reg. \_\_\_\_\_, effective \_\_\_\_\_.

## SUBPART A: GENERAL PROVISIONS

## Section 218.106 Compliance Dates

- a) Except as otherwise provided in this Section or as otherwise provided in a specific Subpart of this Part, compliance with the requirements of all rules is required by July 1, 1991, or September 1, 1991, for all sources located in Cook, DuPage, Kane, Lake, McHenry, or Will Counties, consistent with the appropriate provisions of Section 218.103 of this Subpart.
- Except as otherwise provided in this Section or as otherwise provided in a specific Subpart of this Part, compliance with the requirements of this Part is required by November 15, 1993, for all sources located in Aux Sable Township or Goose Lake Township in Grundy County, or in Oswego Township in Kendall County.
- c) All emission units which meet the applicability requirements of Sections 218.402(a)(2), 218.611(b), 218.620(b), 218.660(a), 218.680(a), 218.920(b), 218.940(b), 218.960(b) or 218.980(b) of this Part, including emission units at sources which are excluded from the applicability criteria of Sections 218.402(a)(1), 218.611(a), 218.620(a), 218.920(a), 218.940(a), 218.960(a), or 218.980(a) of this Part by virtue of permit conditions or other enforceable means, must comply with the requirements of Subparts H, Z, AA, CC, DD, PP, QQ, RR or TT of this Part, respectively, by March 15, 1995. Any owner or operator of an emission unit which has already met the applicability requirements of Sections 218.402(a)(1), 218.611(a), 218.620(a), 218.920(a), 218.940(a), 218.960(a) 218.980(a) of this Part on or by the effective date of this subsection is required to comply with all compliance dates or schedules found in Sections 218.106(a) or 218.106(b), as applicable.
- d) Any owner or operator of a source with an emission unit subject to the requirements of Section 218.204(m)(2) or (m)(3) of this Part shall comply with those requirements by March 25, 1995.
- e) Any owner or operator of a source subject to the requirements of Section 218.204(c)(2), 218.204(g)(2), or 218.204(h)(2) of this Part shall comply with the

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

# applicable requirements in such Section(s), as well as all applicable requirements in Sections 218.205 through 218.214 and 218.218, by May 1, 2011.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

## SUBPART F: COATING OPERATIONS

#### Section 218.204 Emission Limitations

Except as provided in Sections 218.205, 218.207, 218.208, 218.212, 218.215 and 218.216 of this Subpart, no owner or operator of a coating line shall apply at any time any coating in which the VOM content exceeds the following emission limitations for the specified coating. Except as otherwise provided in Sections 218.204(c), 218.204(g), 218.204(h), and 218.204(l), compliance with the emission limitations marked with an asterisk in this Section is required on and after March 15, 1996, and compliance with emission limitations not marked with an asterisk is required until March 15, 1996. The following emission limitations are expressed in units of VOM per volume of coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied at each coating applicator, except where noted. Compounds which are specifically exempted from the definition of VOM should be treated as water for the purpose of calculating the "less water" part of the coating composition. Compliance with this Subpart must be demonstrated through the applicable coating analysis test methods and procedures specified in Section 218.105(a) of this Part and the recordkeeping and reporting requirements specified in Section 218.211(c) of this Subpart except where noted. (Note: The equation presented in Section 218.206 of this Part shall be used to calculate emission limitations for determining compliance by add-on controls, credits for transfer efficiency, emissions trades and cross-line averaging.) The emission limitations are as follows:

- a)	Autor	nobile or Light-Duty Truck Coating	kg/l	lb/gal
	1)	Prime coat	0.14 0.14*	(1.2) (1.2)*
	2)	Primer surface coat	1.81 1.81*	(15.1) (15.1)*

(Note: The primer surface coat limitation is in units of kg (lbs) of VOM per l (gal) of coating solids deposited. Compliance with the limitation shall be based on the daily-weighted average from an entire primer surfacer operation. Compliance shall be demonstrated in accordance with the topcoat protocol referenced in Section 218.105(b) and the

#### NOTICE OF PROPOSED AMENDMENTS

recordkeeping and reporting requirements specified in Section 218.211(f). Testing to demonstrate compliance shall be performed in accordance with the topcoat protocol and a detailed testing proposal approved by the Agency and USEPA specifying the method of demonstrating compliance with the protocol. Section 218.205 does not apply to the primer surfacer limitation.)

		kg/l	lb/gal
3)	Topcoat	1.81	(15.1)
		1.81*	(15.1)*

(Note: The topcoat limitation is in units of kg (lbs) of VOM per l (gal) of coating solids deposited. Compliance with the limitation shall be based on the daily-weighted average from an entire topcoat operation. Compliance shall be demonstrated in accordance with the topcoat protocol referenced in Section 218.105(b) of this Part and the recordkeeping and reporting requirements specified in Section 218.211(f). Testing to demonstrate compliance shall be performed in accordance with the topcoat protocol and a detailed testing proposal approved by the Agency and USEPA specifying the method of demonstrating compliance with the protocol. Section 218.205 of this Part does not apply to the topcoat limitation.)

	4)	Final	repair coat	kg/l 0.58 0.58*	lb/gal (4.8) (4.8)*
b)	Can C	oating		kg/l	lb/gal
	1)	Sheet	basecoat and overvarnish		
		A)	Sheet basecoat	0.34 0.26*	(2.8) (2.2)*
		B)	Overvarnish	0.34 0.34	(2.2) (2.8) (2.8)*
	2)	Exteri	or basecoat and overvarnish	0.34 0.25*	(2.8) (2.1)*

3) Interior body spray coat

#### NOTICE OF PROPOSED AMENDMENTS

	A)	Two piece	0.51 0.44*	(4.2) (3.7)*
	B)	Three piece	0.51 0.51*	(4.2) (4.2)*
4)	Exter	ior end coat	0.51 0.51*	(4.2) (4.2)*
5)	Side s	seam spray coat	0.66 0.66*	(5.5) (5.5)*
6)	End s	ealing compound coat	0.44 0.44*	(3.7) (3.7)*
Paper	Coating	g	<del>kg/1</del> 0.35 0.28*	<del>lb/gal</del> <del>(2.9)</del> <del>(2.3)</del> *
<u>1)</u>	Prior 1	to May 1, 2011:	<u>kg/l</u> 0.28	<u>lb/gal</u> (2.3)
<u>2)</u>	<u>On an</u>	<u>d after May 1, 2011:</u>	kg VOM/kg (lb VOM/lb)	<u>kg VOM/kg</u> ( <u>Ib VOM/Ib)</u>
	<u>A)</u>	Pressure sensitive tape and label surface coatings	solids applied	<u>coatings applied</u> (0.067)
	<u>B)</u>	All other paper coatings	<u>0.40</u>	<u>(0.08)</u>

c)

(Note: The paper coating limitation shall not apply to any owner or operator of any paper coating line on which flexographic or rotogravure printing is performed if the paper coating line complies with the emissions limitations in Section 218.401 of this Part. In addition, screen printing on paper is not regulated as paper coating, but is regulated under Subpart TT of this Part. <u>On and after May 1, 2011, the paper coating limitation shall also not apply to coating performed on or in-line with any digital printing press, or to size presses and on-machine coaters</u>

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

## on papermaking machines applying sizing or water-based clays.)

d)	Coil Coating	kg/l 0.31 0.20*	lb/gal (2.6) (1.7)*
e)	Fabric Coating	0.35 0.28*	(2.9) (2.3)*
f)	Vinyl Coating	0.45 0.28*	(3.8) (2.3)*

#### Metal Furniture Coating g)

<u>i)</u>

Air Dried

<u>1)</u>

Prio	r to May 1, 2011:		
		<u>kg/1</u>	<u>lb/gal</u>
<u>A)</u>	Air dried	<u>0.34</u>	<u>(2.8)</u>
<u>B)</u>	Baked	0.28	(2.3)

<u>2)</u>	On and after May 1, 2011:				
				<u>kg/l</u> (lb/gal)	<u>kg/l (lb/gal)</u> solids applied
	<u>A)</u>	Gener	al, One-Component	<u>0.275</u> (2.3)	<u>0.40</u> (3.3)
	<u>B)</u>	General, Multi-Component			
		<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
		<u>ii)</u>	Baked	<u>0.275</u> (2.3)	<u>0.40</u> (3.3)
	<u>C)</u>	Extren	ne High Gloss		

<u>0.340</u>

<u>(2.8)</u>

<u>0.55</u>

(4.5)

# POLLUTION CONTROL BOARD

		<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
	<u>D)</u>	Extre	eme Performance		
		<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
		<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
	<u>E)</u>	<u>Heat</u>	Resistant		
		<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
		<u>ii)</u>	<u>Baked</u>	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
	<u>F)</u>	<u>Meta</u>	llic	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>G)</u>	<u>Pretr</u>	eatment Coatings	$\frac{0.420}{(3.5)}$	<u>0.80</u> (6.7)
	<u>H)</u>	<u>Sola</u>	Absorbent		
		<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
		<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<del>1)</del>	Air d	ried		<del>0.36</del> 0.34*	<del>(3.0)</del> <del>(2.8)*</del>
<del>2)</del>	Bake	ŧ		<del>0.36</del> <del>0.28*</del>	<del>(3.0)</del> <del>(2.3)*</del>

#### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

(Note: On and after May 1, 2011, these limitations shall not apply to stencil coatings, safety-indicating coatings, solid-film lubricants, electric-insulating and thermal-conducting coatings, touch-up and repair coatings, or coating applications utilizing hand-held aerosol cans.)

- 3) On and after May 1, 2011, an owner or operator of a coating line subject to the limitations in subsection (g) of this Section shall apply all coatings using one or more of the following application methods:
  - <u>A)</u> <u>Electrostatic spray:</u>
  - <u>B)</u> <u>High volume low pressure (HVLP) spray;</u>
  - <u>C)</u> Flow coating. For the purposes of this subsection (g), flow coating means a non-atomized technique of applying coating to a substrate with a fluid nozzle with no air supplied to the nozzle;
  - <u>D)</u> <u>Roll coating;</u>
  - E) Dip coating, including electrodeposition. For purposes of this subsection (g), electrodeposition means a water-borne dip coating process in which opposite electrical charges are applied to the substrate and the coating. The coating is attracted to the substrate due to the electrochemical potential difference that is created; or
  - <u>F)</u> Another coating application method capable of achieving a transfer efficiency equal to or better than that achieved by HVLP spraying, if such method is approved in writing by the Agency.
- h) Large Appliance Coating
  - <u>1)</u> Prior to May 1, 2011:

	<u>A)</u>	Air dried	<u>kg/1</u> 0.34	<u>lb/gal</u> (2.8)
	<u>B)</u>	Baked	<u>0.28</u>	<u>(2.3)</u>
<u>2)</u>	<u>On an</u>	<u>d after May 1, 2011:</u>	<u>kg/l</u> (lb/gal)	<u>kg/l (lb/gal)</u> solids applied

## POLLUTION CONTROL BOARD

<u>A)</u>	<u>Gene</u>	ral, One-Component	<u>0.275</u> (2.3)	<u>0.40</u> (3.3)
<u>B)</u>	Gene	ral, Multi-Component		
	<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
	<u>ii)</u>	Baked	<u>0.275</u> (2.3)	<u>0.40</u> (3.3)
<u>C)</u>	Extre	me High Gloss		
	<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>D)</u>	Extre	me Performance		
	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>E)</u>	<u>Heat</u>	Resistant		
	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>F)</u>	<u>Meta</u>	llic	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
<u>G)</u>	Pretre	eatment Coatings	0.420	<u>0.80</u>

#### NOTICE OF PROPOSED AMENDMENTS

				<u>(3.5)</u>	<u>(6.7)</u>
	<u>H)</u>	<u>Sola</u>	r Absorbent		
		<u>i)</u>	<u>Air Dried</u>	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
		<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<del>1)</del>	<del>Air d</del>	ried		<del>0.34</del> <del>0.34*</del>	<del>(2.8)</del> <del>(2.8)*</del>
<del>2)</del>	Bake	đ		<del>0.34</del> <del>0.28*</del>	<del>(2.8)</del> <del>(2.3)*</del>

(Note: The<u>se</u> limitation<u>s</u> shall not apply to the use of quick-drying lacquers for repair of scratches and nicks that occur during assembly, provided that the volume of coating does not exceed 0.951 (1 quart) in any one rolling eight-hour period. On and after May 1, 2011, these limitations shall also not apply to stencil coatings, safety-indicating coatings, solid-film lubricants, electric-insulating and thermal-conducting coatings, touch-up and repair coatings, or coating applications utilizing hand-held aerosol cans.)

- 3) On and after May 1, 2011, an owner or operator of a coating line subject to the limitations in subsection (h) of this Section shall apply all coatings using one or more of the following application methods:
  - <u>A)</u> <u>Electrostatic spray;</u>
  - B) High volume low pressure (HVLP) spray;
  - <u>C)</u> Flow coating. For the purposes of this subsection (h), flow coating means a non-atomized technique of applying coating to a substrate with a fluid nozzle with no air supplied to the nozzle;
  - <u>D)</u> <u>Roll coating;</u>
  - E) Brush coating;

## POLLUTION CONTROL BOARD

- <u>F</u>) Dip coating, including electrodeposition. For purposes of this subsection (h), electrodeposition means a water-borne dip coating process in which opposite electrical charges are applied to the substrate and the coating. The coating is attracted to the substrate due to the electrochemical potential difference that is created; or
- <u>G</u>) <u>Another coating application method capable of achieving a transfer</u> <u>efficiency equal to or better than that achieved by HVLP spraying,</u> <u>if such method is approved in writing by the Agency.</u>

i)	Magn	et Wire	Coating	kg/l 0.20 0.20*	lb/gal (1.7) (1.7)*
j)	Misce Coatir		s Metal Parts and Products		
	1)	Clear	coating	0.52 0.52*	(4.3) (4.3)*
	2)	Extre	ne performance coating		
		A)	Air dried	0.42 0.42*	(3.5) (3.5)*
		B)	Baked	0.42 0.40*	(3.5) (3.3)*
	3)	Steel j coatin	pail and drum interior	0.52	(4.3)
		coatin	8	0.52*	(4.3)*
	4)	All ot	her coatings		
		A)	Air Dried	0.42 0.40*	(3.5) (3.3)*
		B)	Baked	0.36 0.34*	(3.0) (2.8)*

#### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

5)	Marine engine coating						
	A)	Air Dı	ried	0.42 0.42*	(3.5) (3.5)*		
	B)	Baked					
		i)	Primer/Topcoat	0.42 0.42*	(3.5) (3.5)*		
		ii)	Corrosion resistant basecoat	0.42	(3.5)		
			busboout	0.28*	(2.3)*		
	C)	Clear	Coating	0.52 0.52*	(4.3) (4.3)*		
6)	Metall	ic Coat	ing				
	A)	Air Dr	ried	0.42 0.42*	(3.5) (3.5)*		
	B)	Baked		0.36 0.36	(3.0) (3.0)*		

#### 7) Definitions

- A) For purposes of subsection 218.204(j)(5) of this Section, the following terms are defined:
  - "Corrosion resistant basecoat" means, for purposes of subsection 218.204(j)(5)(B)(ii) of this Section, a waterborne epoxy coating applied via an electrodeposition process to a metal surface prior to spray coating, for the purpose of enhancing corrosion resistance.
  - "Electrodeposition process" means, for purposes of subsection 218.204(j)(5) of this Section, a water-borne dip coating process in which opposite electrical charges are

#### NOTICE OF PROPOSED AMENDMENTS

applied to the substrate and the coating. The coating is attracted to the substrate due to the electrochemical potential difference that is created.

- iii) "Marine engine coating" means, for purposes of subsection 218.204(j)(5) of this Section, any extreme performance protective, decorative or functional coating applied to an engine that is used to propel watercraft.
- B) For purposes of subsection 218.204(j)(6) of this Section, "metallic coating" means a coating which contains more than 1/4 lb/gal of metal particles, as applied.

k)	Heavy Coatii	v Off-Highway Vehicle Products	kg/l	lb/gal
	1)	Extreme performance prime coat	0.42 0.42*	(3.5) (3.5)*
	2)	Extreme performance topcoat (air dried)	0.42	(3.5)
			0.42*	(3.5)*
	3)	Final repair coat (air dried)	0.42 0.42*	(3.5) (3.5)*

4) All other coatings are subject to the emission limitations for miscellaneous metal parts and products coatings in subsection (j) above.

#### 1) Wood Furniture Coating

1)	Limi 1998	tations before March 15, :	kg/l	lb/gal
	A)	Clear topcoat	0.67	(5.6)
	B)	Opaque stain	0.56	(4.7)
	C)	Pigmented coat	0.60	(5.0)

## NOTICE OF PROPOSED AMENDMENTS

D)	Repair coat	0.67	(5.6)
E)	Sealer	0.67	(5.6)
F)	Semi-transparent stain	0.79	(6.6)
G)	Wash coat	0.73	(6.1)

(Note: Prior to March 15, 1998, an owner or operator of a wood furniture coating operation subject to this Section shall apply all coatings, with the exception of no more than 37.8 l (10 gal) of coating per day used for touch-up and repair operations, using one or more of the following application systems: airless spray application system, air-assisted airless spray application system, electrostatic spray application system, electrostatic bell or disc spray application system, heated airless spray application system, roller coating, brush or wipe coating application system, dip coating application system or high volume low pressure (HVLP) application system.)

 On and after March 15, 1998, wood furniture sealers and topcoats must comply with one of the limitations specified in subsections (1)(2)(A) through (E), below:

A)	Торсо	at	kg VOM/kg solids 0.8	lb VOM/lb solids (0.8)
B)		s and topcoats with lowing limits:		
	i)	Sealer other than acid-cured alkyd amino vinyl sealer	1.9	(1.9)
	ii)	Topcoat other than acid-cured alkyd amino conversion varnish topcoat	1.8	(1.8)
	iii)	Acid-cured alkyd amino vinyl sealer	2.3	(2.3)

#### POLLUTION CONTROL BOARD

- iv) Acid-cured alkyd 2.0 (2.0) amino conversion varnish topcoat
- C) Meet the provisions of Section 218.215 of this Subpart for use of an averaging approach;
- Achieve a reduction in emissions equivalent to the requirements of subsection (l)(2)(A) or (B) of this Section, as calculated using Section 218.216 of this Subpart; or
- E) Use a combination of the methods specified in subsections (1)(2)(A) through (D) of this Section.
- 3) Other wood furniture coating limitations on and after March 15, 1998:

A)	Opaque stain	kg/l 0.56	lb/gal (4.7)
B)	Non-topcoat pigmented coat	0.60	(5.0)
C)	Repair coat	0.67	(5.6)
D)	Semi-transparent stain	0.79	(6.6)
E)	Wash coat	0.73	(6.1)

- 4) Other wood furniture coating requirements on and after March 15, 1998:
  - A) No source subject to the limitations of subsection (1)(2) or (3) of this Section and utilizing one or more wood furniture coating spray booths shall use strippable spray booth coatings containing more than 0.8 kg VOM/kg solids (0.8 lb VOM/lb solids), as applied.
  - B) Any source subject to the limitations of subsection (l)(2) or (3) of this Section shall comply with the requirements of Section 218.217 of this Subpart.

## POLLUTION CONTROL BOARD

- C) Any source subject to the limitations of subsection (1)(2)(A) or (B) of this Section and utilizing one or more continuous coaters shall, for each continuous coater, use an initial coating which complies with the limitations of subsection (1)(2)(A) or (B) of this Section. The viscosity of the coating in each reservoir shall always be greater than or equal to the viscosity of the initial coating in the reservoir. The owner or operator shall:
  - i) Monitor the viscosity of the coating in the reservoir with a viscosity meter or by testing the viscosity of the initial coating and retesting the coating in the reservoir each time solvent is added;
  - ii) Collect and record the reservoir viscosity and the amount and weight of VOM per weight of solids of coating and solvent each time coating or solvent is added; and
  - iii) Maintain these records at the source for a period of three years.

,	Existing Diesel-Electric Locomotive kg/l Coating Lines in Cook County					
	1)	Extreme performance prime coat	0.42 0.42*	(3.5) (3.5)*		
	2)	Extreme performance top-coat (air	0.42	(3.5)		
		dried)	0.42*	(3.5)*		
	3)	Final repair coat (air dried)	0.42 0.42*	(3.5) (3.5)*		
	4)	High-temperature aluminum coating	0.72	(6.0)		
		coating	0.72*	(6.0)*		
	5)	All other coatings	0.36 0.36*	(3.0) (3.0)*		

# POLLUTION CONTROL BOARD

n)			Coating: Transpor	kg/l	lb/gal	
	1)	Interio	ors			
		A)	Baked			
			i) ii)	Color coat Primer	0.49* 0.46*	(4.1)* (3.8)*
		B)	Air Dı	ried		
			i) ii)	Color coat Primer	0.38* 0.42*	(3.2)* (3.5)*
	2)	Exteri flexibl		kible and non-		
		A)	Baked			
			i)	Primer	0.60*	(5.0)*
			ii)	Primer non-flexible	0.54*	(4.5)*
			iii)	Clear coat	0.52*	(4.3)*
			iv)	Color coat	0.55*	(4.6)*
		B)	Air Dr	ied		
			i)	Primer	0.66*	(5.5)*
			ii)	Clear coat	0.54*	(4.5)*
			iii)	Color coat (red & black)	0.67*	(5.6)*
			iv)	Color coat (others)	0.61*	(5.1)*

# POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

3) Specialty

0)

	A)	Vacuum metalizing basecoats, texture basecoats	0.66*	(5.5)*
	B)	Black coatings, reflective argent coatings, air bag cover coatings, and soft coatings	0.71*	(5.9)*
	C)	Gloss reducers, vacuum metalizing topcoats, and texture topcoats	0.77*	(6.4)*
	D)	Stencil coatings, adhesion primers, ink pad coatings, electrostatic prep coatings, and resist coatings	0.82*	(6.8)*
	E)	Head lamp lens coatings	0.89*	(7.4)*
Plastic Parts Coating: Business Machine			kg/l	lb/gal
1)	Primer		0.14*	(1.2)*
2)	Color coat (non-texture coat)		0.28*	(2.3)*
3)	Color coat (texture coat)		0.28*	(2.3)*
4)	freque	omagnetic interference/radio mcy interference (EMI/RFI) ing coatings	0.48*	(4.0)*
5)	Specialty Coatings			
	A)	Soft coat	0.52*	(4.3)*
	B)	Plating resist	0.71*	(5.9)*

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

C) Plating sensitizer  $0.85^*$   $(7.1)^*$ 

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

## Section 218.205 Daily-Weighted Average Limitations

No owner or operator of a coating line subject to the limitations of Section 218.204 of this Subpart and complying by means of this Section shall operate the subject coating line unless the owner or operator has demonstrated compliance with subsection (a), (b), (c), (d), (e), (f), (g), (h), or(i), or (j) of this Section (depending upon the category of coating) through the applicable coating analysis test methods and procedures specified in Section 218.105(a) of this Part and the recordkeeping and reporting requirements specified in Section 218.211(d) of this Subpart:

- a) No owner or operator of a coating line subject to only one of the limitations from among Section 218.204(a)(1), (a)(4), (c), (d), (e), (f), or (i), or, prior to May 1, 2011, (c) of this Subpart shall apply coatings on any such coating line, during any day, whose daily-weighted average VOM content exceeds the emission limitation to which the coatings are subject.
- b) No owner or operator of a miscellaneous metal parts and products coating line subject to the limitations of Section 218.204(j) of this Subpart shall apply coatings to miscellaneous metal parts or products on the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(j) during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l [3.5 lbs/gal]), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(j) of this Subpart, during the same day, the owner or operator shall have a site-specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.
- c) No owner or operator of a can coating line subject to the limitations of Section

#### NOTICE OF PROPOSED AMENDMENTS

218.204(b) of this Subpart shall operate the subject coating line using a coating with a VOM content in excess of the limitations specified in Section 218.204(b) of this Subpart unless all of the following requirements are met:

An alternative daily emission limitation shall be determined for the can coating operation, i.e. for all of the can coating lines at the source, according to subsection (c)(2) of this Section. Actual daily emissions shall never exceed the alternative daily emission limitation and shall be calculated by use of the following equation.

$$E_d = \sum_{i=1}^n V_i C_i$$

where:

- $E_d =$  Actual VOM emissions for the day in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of coatings applied in the can coating operation, i.e. all can coating lines at the source;
- V<sub>i</sub> = Volume of each coating applied for the day in units of l/day (gal/day) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- C<sub>i</sub> = The VOM content of each coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM).
- 2) The alternative daily emission limitation (A<sub>d</sub>) shall be determined for the can coating operation, i.e. for all of the can coating lines at the source, on a daily basis as follows:

$$A_d = \sum_{i=1}^n V_i L_i \left( \frac{D_i - C_i}{D_i - L_i} \right)$$

#### NOTICE OF PROPOSED AMENDMENTS

where:

- $A_d =$  The VOM emissions allowed for the day in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of surface coatings applied in the can coating operation;
- C<sub>i</sub> = The VOM content of each surface coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- D<sub>i</sub> = The density of VOM in each coating applied. For the purposes of calculating A<sub>d</sub>, the density is 0.882 kg VOM/l VOM (7.36 lbs VOM/gal VOM);
- V<sub>i</sub> = Volume of each surface coating applied for the day in units of 1 (gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- $\begin{array}{ll} L_i = & \mbox{The VOM emission limitation for each surface coating applied as} \\ & \mbox{specified in Section 218.204(b) of this Subpart in units of kg} \\ & \mbox{VOM/I (lbs VOM/gal) of coating (minus water and any} \\ & \mbox{compounds which are specifically exempted from the definition of} \\ & \mbox{VOM)}. \end{array}$
- No owner or operator of a heavy off-highway vehicle products coating line subject to the limitations of Section 218.204(k) of this Subpart shall apply coatings to heavy off-highway vehicle products on the subject coating line unless the requirements of subsection (d)(1) or (d)(2) of this Section are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(k) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l (3.5 lbs/gal)), the daily-weighted average VOM content shall not exceed the coating VOM content limit

## NOTICE OF PROPOSED AMENDMENTS

corresponding to the category of coating used, or

- 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(k) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.
- e) No owner or operator of a wood furniture coating line subject to the limitations of Section 218.204(1)(1) or (1)(3) of this Subpart shall apply coatings to wood furniture on the subject coating line unless the requirements of subsection (e)(1) or subsection (e)(2) of this Section, in addition to the requirements specified in the note to Section 218.204(1)(1) of this Subpart, are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(l)(1) or (l)(3) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.67 kg/l (5.6 lbs/gal)), the dailyweighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(l)(1) or (l)(3) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.
- f) No owner or operator of an existing diesel-electric locomotive coating line in Cook County, subject to the limitations of Section 218.204(m) of this Subpart shall apply coatings to diesel-electric locomotives on the subject coating line unless the requirements of subsection (f)(1) or (f)(2) of this Section are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(m) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l (3.5 lbs/gal)), the daily-weighted average

#### NOTICE OF PROPOSED AMENDMENTS

VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or

- 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(m) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.
- g) No owner or operator of a plastic parts coating line, subject to the limitations of Section 218.204(n) or (o) of this Subpart shall apply coatings to business machine or automotive/transportation plastic parts on the subject coating line unless the requirements of subsection (g)(1) or (g)(2) of this Section are met:
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(n) or (o) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l (3.5 lbs/gal)), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used; or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(n) or (o) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.
- h) No owner or operator of a metal furniture coating line, subject to the limitations of Section 218.204(g) of this Subpart shall apply coatings on the subject coating line unless the requirements of subsection (h)(1) or (h)(2) of this Section are met:
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(g) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.34 kg/l (2.8 lbs/gal)), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used; or

## POLLUTION CONTROL BOARD

- 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(g) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.
- i) No owner or operator of a large appliance coating line, subject to the limitations of Section 218.204(h) of this Subpart shall apply coatings on the subject coating line unless the requirements of subsection (i)(1) or (i)(2) of this Section are met:
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(h) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.34 kg/l (2.8 lbs/gal)), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(h) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.
- j) On and after May 1, 2011, no owner or operator of a paper coating line subject to the limitations of Section 218.204(c) of this Subpart shall apply coatings on the subject coating line unless the requirements in subsection (j)(1) or (j)(2) of this Section are met:
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 218.204(c) during the same day (e.g., all coatings used on the line are subject to 0.40 kg/kg solids [0.08 kg/kg coatings]), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used; or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 218.204(c) during the same day, the owner or operator shall have a site-specific proposal approved by the

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy), 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

# Section 218.207 Alternative Emission Limitations

- a) Any owner or operator of a coating line subject to Section 218.204 of this Subpart may comply with this Section, rather than with Section 218.204 of this Subpart, if a capture system and control device are operated at all times the coating line is in operation and the owner or operator demonstrates compliance with subsections (c), (d), (e), (f), (g), (h), (i), (j), or (k), or (l) of this Section (depending upon the source category) through the applicable coating analysis and capture system and control device efficiency test methods and procedures specified in Section 218.105 of this Part and the recordkeeping and reporting requirements specified in Section 218.211(e) of this Subpart; and the control device is equipped with the applicable monitoring equipment specified in Section 218.105(d) of this Part and the monitoring equipment is installed, calibrated, operated and maintained according to vendor specifications at all times the control device is in use. A capture system and control device, which does not demonstrate compliance with subsection (c), (d), (e), (f), (g), (h), (i), (i), or(k), or (l) of this Section may be used as an alternative to compliance with Section 218.204 of this Subpart only if the alternative is approved by the Agency and approved by the USEPA as a SIP revision.
- b) Alternative Add-On Control Methodologies
  - 1) The coating line is equipped with a capture system and control device that provides 81 percent reduction in the overall emissions of VOM from the coating line and the control device has a 90 percent efficiency, or
  - 2) The system used to control VOM from the coating line is demonstrated to have an overall efficiency sufficient to limit VOM emissions to no more than what is allowed under Section 218.204 of this Subpart. Use of any control system other than an afterburner, carbon adsorption, condensation, or absorption scrubber system can be allowed only if approved by the Agency and approved by the USEPA as a SIP revision. The use of transfer efficiency credits can be allowed only if approved by the Agency

#### NOTICE OF PROPOSED AMENDMENTS

and approved by the USEPA as a SIP revision. Baseline transfer efficiencies and transfer efficiency test methods must be approved by the Agency and the USEPA. Such overall efficiency is to be determined as follows:

- A) Obtain the emission limitation from the appropriate subsection in Section 218.204 of this Subpart;
- B) Calculate "S" according to the equation in Section 218.206 of this Subpart;
- C) Calculate the overall efficiency required according to Section 218.105(e) of this Part. For the purposes of calculating this value, according to the equation in Section 218.105(e)(2) of this Part, VOM<sub>1</sub> is equal to the value of "S" as determined above in subsection (b)(2)(B) of this Section.
- c) No owner or operator of a coating line subject to only one of the emission limitations from among Section 218.204(a)(1), (a)(4), (c), (d), (e), (f), or (i), or, prior to May 1, 2011, (c) of this Subpart and equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met. No owner or operator of a coating line subject to Section 218.204(a)(2) or 218.204(a)(3) and equipped with a capture system and control device shall operate the coating line unless the owner or operator demonstrates compliance with such limitation in accordance with the topcoat protocol referenced in Section 218.105(b).
- No owner or operator of a miscellaneous metal parts and products coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(j) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/1 [3.5 lbs/gal], and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- e) No owner or operator of a heavy off-highway vehicle products coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(k) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/1 [3.5 lbs/gal]), and which is equipped with a capture system and control device shall operate the

#### NOTICE OF PROPOSED AMENDMENTS

subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.

- f) No owner or operator of an existing diesel-electric locomotive coating line in Cook County which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(m) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/1 [3.5 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- g) No owner or operator of a wood furniture coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(l) of this Subpart (e.g., all coatings used on the line are subject to 0.67 kg/l [5.6 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met. If compliance is achieved by meeting the requirements in subsection (b)(2) of this Subpart must also be met.
- h) No owner or operator of a can coating line which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (h)(1) or (h)(2) of this Section are met.
  - An alternative daily emission limitation shall be determined for the can coating operation, i.e., for all of the can coating lines at the source, according to Section 218.205(c)(2) of this Subpart. Actual daily emissions shall never exceed the alternative daily emission limitation and shall be calculated by use of the following equation:

$$E_{d} = \sum_{i=1}^{n} V_{i} C_{i} \quad (1-F_{i})$$

where:

 $E_d = Actual VOM$  emissions for the day in units of kg/day (lbs/day);

i = Subscript denoting the specific coating applied;

#### POLLUTION CONTROL BOARD

- n = Total number of surface coatings as applied in the can coating operation;
- V<sub>i</sub> = Volume of each coating as applied for the day in units of l/day (gal/day) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- C<sub>i</sub> = The VOM content of each coating as applied in units of kg VOM/1 (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM); and
- $F_i$  = Fraction, by weight, of VOM emissions from the surface coating, reduced or prevented from being emitted to the ambient air. This is the overall efficiency of the capture system and control device.
- 2) The coating line is equipped with a capture system and control device that provide 75 percent reduction in the overall emissions of VOM from the coating line and the control device has a 90 percent efficiency.
- i) No owner or operator of a plastic parts coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(n) or (o) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/l [3.5 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- j) <u>Prior to May 1, 2011, noNo</u> owner or operator of a metal furniture coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(g) of this Subpart (e.g., all coatings used on the line are subject to 0.34 kg/l [2.8 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- <u>Prior to May 1, 2011, noNo</u> owner or operator of a large appliance coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 218.204(h) of this Subpart (e.g., all coatings used on the line are subject to 0.34 kg/l [2.8 lbs/gal]),

# NOTICE OF PROPOSED AMENDMENTS

and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.

- 1) On and after May 1, 2011, no owner or operator of a paper coating line, metal furniture coating line, or large appliance coating line which is equipped with a capture system and control device shall operate the subject coating line unless either:
  - 1) The capture system and control device provide at least 90 percent reduction in the overall emissions of VOM from the coating line; or
  - 2) The owner or operator complies with the applicable limitation set forth in Section 218.204 of this Subpart by utilizing a combination of low-VOM coatings and a capture system and control device.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

## Section 218.210 Compliance Schedule

Every owner or operator of a coating line (of a type included within Section 218.204 of this Subpart) shall comply with the requirements of Section 218.204, 218.205, 218.207 or 218.208 and Section 218.211 or Sections 218.212 and 218.213 of this Subpart in accordance with the appropriate compliance schedule as specified in subsection (a), (b), (c), (d), (e),  $\frac{\text{or}}{(f)}$ , or (g) below:

- a) No owner or operator of a coating line which is exempt from the limitations of Section 218.204 of this Subpart because of the criteria in Section 218.208(a) or
   (b) of this Subpart shall operate said coating line on or after a date consistent with Section 218.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Section 218.211(b) of this Subpart:
- b) No owner or operator of a coating line complying by means of Section 218.204 of this Subpart shall operate said coating line on or after a date consistent with Section 218.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Sections 218.204 and 218.211(c) of this Subpart.
- c) No owner or operator of a coating line complying by means of Section 218.205 of this Subpart shall operate said coating line on or after a date consistent with Section 218.106 of this Part, unless the owner or operator has complied with, and

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

continues to comply with, Sections 218.205 and 218.211(d) of this Subpart.

- d) No owner or operator of a coating line complying by means of Section 218.207 of this Subpart shall operate said coating line on or after a date consistent with Section 218.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Sections 218.207 and 218.211(e) of this Subpart.
- e) No owner or operator of a coating line subject to one or more of the emission limitations contained in Section 218.204 of this Subpart on or after March 15, 1996, choosing to comply by means of Section 218.204, 218.205 or 218.207 of this Subpart, shall operate said coating line on or after March 15, 1996, unless the owner or operator complies with and continues to comply with, respectively, the applicable requirements in Section 218.204, or the alternative control options in Section 218.205 or 218.207 and the requirements of Section 218.211.
- f) No owner or operator of a coating line subject to one or more of the emission limitations contained in Section 218.204 of this Subpart on or after March 15, 1996, choosing to comply by means of Section 218.212 of this Subpart, shall operate said coating line on or after March 15, 1996, unless the owner or operator complies with and continues to comply with the requirements of Sections 218.212 and 218.213 of this Subpart.
- g) No owner or operator of a coating line subject to the emission limitations in Section 218.204(c)(2), 218.204(g)(2), or 218.204(h)(2) of this Subpart shall operate said coating line on or after a date consistent with Section 218.106(e) of this Part, unless the owner or operator has complied with, and continues to comply with, Section 218.204(c)(2), 218.204(g)(2), or 218.204(h)(2), as applicable, or the alternative control options in Section 218.205 or 218.207, and all applicable requirements in Sections 218.211 and 218.218 of this Subpart.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective\_\_\_\_)

# Section 218.211 Recordkeeping and Reporting

- a) The VOM content of each coating and the efficiency of each capture system and control device shall be determined by the applicable test methods and procedures specified in Section 218.105 of this Part to establish the records required under this Section.
- b) Any owner or operator of a coating line which is exempted from the limitations of

#### NOTICE OF PROPOSED AMENDMENTS

Section 218.204 of this Subpart because of Section 218.208(a) or (b) of this Subpart shall comply with the following:

- For sources exempt under Section 218.208(a) of this Subpart, by a date consistent with Section 218.106 of this Part, the owner or operator of a coating line or a group of coating lines referenced in subsection\_(b) of this Section shall certify to the Agency that the coating line or group of coating lines is exempt under the provisions of Section 218.208(a) -of this Subpart. Such certification shall include:
  - A) A declaration that the coating line or group of coating lines is exempt from the limitations of Section 218.204 of this Subpart because of Section 218.208(a) of this Subpart; and
  - B) Calculations which demonstrate that the combined VOM emissions from the coating lines or group of coating lines never exceed 6.8 kg (15 lbs) per day before the application of capture systems and control devices. The following equation shall be used to calculate total VOM emissions:

$$T_e = \sum_{j=1}^{m} \sum_{i=1}^{n} (A_i B_i)_j$$

- T<sub>e</sub> = Total VOM emissions from coating lines each day before the application of capture systems and control devices in units of kg/day (lbs/day);
- m = Number of coating lines at the source that otherwise would be subject to the same subsection of Section 218.104 of this Part (because they belong to the same category, e.g., can coating);
- j = Subscript denoting an individual coating line;
- n = Number of different coatings as applied each day on each coating line;
- i = Subscript denoting an individual coating;

- $A_i$  = Weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line in units of kg VOM/l (lbs VOM/gal); and
- $B_i = Volume of each coating (minus water and any compounds$ which are specifically exempted from the definition ofVOM) as applied each day on each coating line in units ofl/day (gal/day). The instrument or method by which theowner or operator accurately measured or calculated thevolume of each coating as applied on each coating line eachday shall be described in the certification to the Agency.
- 2) For sources exempt under Section 218.208(b) of this Subpart, by March 15, 1998, or upon initial start-up, the owner or operator of a coating line or a group of coating lines referenced in subsection (b) of this Section shall certify to the Agency that the source is exempt under the provisions of Section 218.208(b) of this Subpart. Such certification shall include:
  - A) A declaration that the source is exempt from the limitations of Section 218.204(1) of this Subpart because of Section 218.208(b) of this Subpart; and
  - B) Calculations which demonstrate that the source meets the criteria for exemption because of Section 218.208(b) of this Subpart.
- 3) For sources exempt under Section 218.208(a) of this Subpart, on and after a date consistent with Section 218.106 of this Part, the owner or operator of a coating line or group of coating lines referenced in this subsection shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line; and
  - B) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating

#### NOTICE OF PROPOSED AMENDMENTS

line.

- 4) For sources exempt under Section 218.208(b) of this Subpart, on and after March 15, 1998, the owner or operator of a coating line or group of coating lines referenced in this subsection (b) shall collect and record all of the following information for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line; and
  - B) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied on each coating line on a monthly basis.
- 5) On and after a date consistent with Section 218.106 of this Part, the owner or operator of a coating line or group of coating lines exempted from the limitations of Section 218.204 of this Subpart because of Section 218.208(a) of this Subpart shall notify the Agency of any record showing that total VOM emissions from the coating line or group of coating lines exceed 6.8 kg (15 lbs) in any day before the application of capture systems and control devices by sending a copy of such record to the Agency within 30 days after the exceedance occurs.
- 6) On and after March 15, 1998, any owner or operator of a source exempt from the limitations of Section 218.204(l) of this Subpart because of Section 218.208(b) of this Subpart shall notify the Agency if the source's VOM emissions exceed the limitations of Section 218.208(b) of this Subpart by sending a copy of calculations showing such an exceedance within 30 days after the change occurs.
- c) Any owner or operator of a coating line subject to the limitations of Section 218.204 of this Subpart other than Section 218.204(a)(2) or (a)(3) of this Subpart and complying by means of Section 218.204 of this Subpart shall comply with the following:
  - 1) By a date consistent with Section 218.106 of this Part, or upon initial startup of a new coating line, or upon changing the method of compliance from an existing subject coating line from Section 218.205, Section

#### NOTICE OF PROPOSED AMENDMENTS

218.207, Section 218.215, or Section 218.216 of this Subpart to Section 218.204 of this Subpart; the owner or operator of a subject coating line shall certify to the Agency that the coating line will be in compliance with Section 218.204 of this Subpart on and after a date consistent with Section 218.106 of this Part, or on and after the initial startup date. Such certification shall include:

- A) The name and identification number of each coating as applied on each coating line;
- B) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line; and
- C) On and after March 15, 1998, for coating lines subject to the limitations of Section 218.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line;-
- D) For coating lines subject to the limitations of Section 218.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line; and
- E) For coating lines subject to the limitations of Section 218.204(g)(2) or 218.204(h)(2) of this Subpart, the application method(s) used to apply coatings on the subject coating line and the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line.
- 2) On and after a date consistent with Section 218.106 of this Part, or on and after the initial start-up date, the owner or operator of a subject coating line shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line;

#### POLLUTION CONTROL BOARD

- B) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line;
- C) On and after March 15, 1998, for coating lines subject to the limitations of Section 218.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line and certified product data sheets for each coating; and
- D) On and after March 15, 1998, for wood furniture coating spray booths subject to the limitations of Section 218.204(l)(4)(A) of this Subpart, the weight of VOM per weight of solids in each strippable spray booth coating as applied each day on each spray booth and certified product data sheets for each coating:-
- E) For coating lines subject to the limitations of Section 218.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line, and certified product data sheets for each coating; and
- F) For coating lines subject to the limitations of Section 218.204(g)(2) or 218.204(h)(2) of this Subpart, the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line, and certified product data sheets for each coating.
- 3) On and after a date consistent with Section 218.106 of this Part, the owner or operator of a subject coating line shall notify the Agency in the following instances:
  - A) Any record showing violation of Section 218.204 of this Subpart shall be reported by sending a copy of such record to the Agency within 30 days following the occurrence of the violation.
  - B) At least 30 calendar days before changing the method of compliance from Section 218.204 of this Subpart to Section 218.205 or Section 218.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (d)(1) or (e)(1) of

## NOTICE OF PROPOSED AMENDMENTS

this Section below, respectively. Upon changing the method of compliance from Section 218.204 of this Subpart to Section 218.205 of this Subpart or Section 218.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (d) or (e) of this Section, respectively.

- d) Any owner or operator of a coating line subject to the limitations of Section 218.204 of this Subpart and complying by means of Section 218.205 of this Subpart shall comply with the following:
  - By a date consistent with Section 218.106 of this Part, or upon initial start-up of a new coating line, or upon changing the method of compliance for an existing subject coating line from Section 218.204 or Section 218.207 of this Subpart to Section 218.205 of this Subpart; the owner or operator of the subject coating line shall certify to the Agency that the coating line will be in compliance with Section 218.205 of this Subpart on and after a date consistent with Section 218.106 of this Part, or on and after the initial start-up date. Such certification shall include:
    - A) The name and identification number of each coating line which will comply by means of Section 218.205 of this Subpart.
    - B) The name and identification number of each coating as applied on each coating line.
    - C) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
    - D) On and after March 15, 1998, for coating lines subject to the limitations of Section 218.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line.
    - E) For coating lines subject to the limitations of Section 218.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line.

## POLLUTION CONTROL BOARD

- F) For coating lines subject to the limitations of Section 218.204(g)(2) or 218.204(h)(2) of this Subpart, the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line.
- $\underline{GE}$ ) The instrument or method by which the owner or operator will accurately measure or calculate the volume of each coating as applied each day on each coating line.
- <u>H</u>F) The method by which the owner or operator will create and maintain records each day as required in subsection (d)(2) of this Section.
- $\underline{IG}$ ) An example of the format in which the records required in subsection (d)(2) of this Section will be kept.
- 2) On and after a date consistent with Section 218.106 of this Part, or on and after the initial start-up date, the owner or operator of a subject coating line shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line.
  - B) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
  - C) On and after March 15, 1998, for coating lines subject to the limitations of Section 218.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line.
  - D) For coating lines subject to the limitations of Section 218.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line.

#### POLLUTION CONTROL BOARD

- <u>For coating lines subject to the limitations of Section 218.204(g)(2)</u> or 218.204(h)(2) of this Subpart, the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line.
- $\underline{FD}$ ) The daily-weighted average VOM content of all coatings as applied on each coating line as defined in Section 218.104 of this Part.
- 3) On and after a date consistent with Section 218.106 of this Part, the owner or operator of a subject coating line shall notify the Agency in the following instances:
  - A) Any record showing violation of Section 218.205 of this Subpart shall be reported by sending a copy of such record to the Agency within 30 days following the occurrence of the violation.
  - B) At least 30 calendar days before changing the method of compliance with this Subpart from Section 218.205 of this Subpart to Section 218.204 or Section 218.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (c)(1) or (e)(1) of this Section, respectively. Upon changing the method of compliance with this subpart from Section 218.205 to Section 218.204 or Section 218.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (c) or (e) of this Section, respectively.
- e) Any owner or operator of a coating line subject to the limitations of Section 218.207 of this Subpart and complying by means of Section 218.207(c), (d), (e), (f), (g), or (h), or (l) of this Subpart shall comply with the following:
  - By a date consistent with Section 218.106 of this Part, or upon initial startup of a new coating line, or upon changing the method of compliance for an existing coating line from Section 218.204 or Section 218.205 of this Subpart to Section 218.207 of this Subpart, the owner or operator of the subject coating line shall perform all tests and submit to the Agency the results of all tests and calculations necessary to demonstrate that the subject coating line will be in compliance with Section 218.207 of this

## NOTICE OF PROPOSED AMENDMENTS

Subpart on and after a date consistent with Section 218.106 of this Part, or on and after the initial startup date.

- 2) On and after a date consistent with Section 218.106 of this Part, or on and after the initial startup date, the owner or operator of a subject coating line shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The weight of VOM per volume of coating solids as applied each day on each coating line, if complying pursuant to Section 218.207(b)(2) of this Subpart.
  - B) Control device monitoring data.
  - C) A log of operating time for the capture system, control device, monitoring equipment and the associated coating line.
  - D) A maintenance log for the capture system, control device and monitoring equipment detailing all routine and non-routine maintenance performed including dates and duration of any outages.
- 3) On and after a date consistent with Section 218.106 of this Part, the owner or operator of a subject coating line shall notify the Agency in the following instances:
  - A) Any record showing violation of Section 218.207 of this Subpart shall be reported by sending a copy of such record to the Agency within 30 days following the occurrence of the violation.
  - B) At least 30 calendar days before changing the method of compliance with this Subpart from Section 218.207 of this Subpart to Section 218.204 or Section 218.205 of this Subpart, the owner or operator shall comply with all requirements of subsection (c)(1) or (d)(1) of this Section, respectively. Upon changing the method of compliance with this subpart from Section 218.207 of this Subpart to Section 218.204 or Section 218.205 of this Subpart, the owner or operator shall comply with all requirements of subsection (c) or (d) of this Section, respectively.

## POLLUTION CONTROL BOARD

- f) Any owner or operator of a primer surfacer operation or topcoat operation subject to the limitations of Section 218.204(a)(2) or (a)(3) of this Subpart shall comply with the following:
  - By a date consistent with Section 218.106 of this Part, or upon initial startup of a new coating operation, the owner or operator of a subject coating operation shall certify to the Agency that the operation will be in compliance with Section 218.204 of this Subpart on and after a date consistent with Section 218.106 of this Part, or on and after the initial startup date. Such certification shall include:
    - A) The name and identification number of each coating operation which will comply by means of Section 218.204(a)(2) and (a)(3) of this Subpart and the name and identification number of each coating line in each coating operation.
    - B) The name and identification number of each coating as applied on each coating line in the coating operation.
    - C) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
    - D) The transfer efficiency and control efficiency measured for each coating line.
    - E) Test reports, including raw data and calculations documenting the testing performed to measure transfer efficiency and control efficiency.
    - F) The instrument or method by which the owner or operator will accurately measure or calculate the volume of each coating as applied each day on each coating line.
    - G) The method by which the owner or operator will create and maintain records each day as required in subsection (f)(2) below.
    - H) An example format for presenting the records required in subsection (f)(2) below.

- 2) On and after a date consistent with Section 218.106 of this Part, or on and after the initial startup date, the owner or operator of a subject coating operation shall collect and record all of the following information each day for each operation and maintain the information at the source for a period of three years:
  - All information necessary to calculate the daily-weighted average VOM emissions from the coating operations in kg (lbs) per 1 (gal) of coating solids deposited in accordance with the proposal submitted, and approved pursuant to Section 218.204(a)(2) or (a)(3) of this Subpart including:
    - i) The name and identification number of each coating as applied on each coating operation.
    - ii) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating operation.
  - B) If a control device(s) is used to control VOM emissions, control device monitoring data; a log of operating time for the capture system, control device, monitoring equipment and the associated coating operation; and a maintenance log for the capture system, control device and monitoring equipment, detailing all routine and non-routine maintenance performed including dates and duration of any outages.
- 3) On and after a date consistent with Section 218.106 of this Part or on and after the initial startup date, the owner or operator of a subject coating operation shall determine and record the daily VOM emissions in kg (lbs) per 1 (gal) of coating solids deposited in accordance with the proposal submitted and approved pursuant to Section 218.204(a)(2) or (a)(3) of this Subpart within 10 days from the end of the month and maintain this information at the source for a period of three years.
- 4) On and after a date consistent with Section 218.106 of this Part, the owner or operator of a subject coating operation shall notify the Agency in the following instances:

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

- A) Any record showing a violation of Section 218.204(a)(2) or (a)(3) of this Subpart shall be reported by sending a copy of such record to the Agency within 15 days from the end of the month in which the violation occurred.
- B) The owner or operator shall notify the Agency of any change to the operation at least 30 days before the change is affected. The Agency shall determine whether or not compliance testing is required. If the Agency determines that compliance testing is required, then the owner or operator shall submit a testing proposal to the Agency within 30 days and test within 30 days of the approval of the proposal by the Agency and USEPA.
- g) On and after a date consistent with Section 218.106(e) of this Part, or on and after the initial startup date, whichever is later, the owner or operator of a coating line subject to the requirements of Section 218.218 of this Subpart shall comply with the following:
  - 1) By May 1, 2011, or upon initial startup, whichever is later, submit a certification to the Agency that includes a description of the practices and procedures that the source will follow to ensure compliance with the applicable requirements in Section 218.218 of this Subpart;
  - 2) Notify the Agency of any violation of Section 218.218 of this Subpart by providing a description of the violation and copies of records documenting such violation to the Agency within 30 days following the occurrence of the violation; and
  - 3) Maintain at the source all records required by this subsection (g) for a minimum of three years from the date the document was created and make such records available to the Agency upon request.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective\_\_\_\_)

# Section 218.212 Cross-Line Averaging to Establish Compliance for Coating Lines

a) On and after March 15, 1996, any owner or operator of a coating line subject to the limitations set forth in Section 218.204 of this Subpart, <u>except coating lines</u> subject to the limitations in Section 218.204(c)(2), (g)(2), or (h)(2) of this

#### NOTICE OF PROPOSED AMENDMENTS

<u>Subpart</u>, and with coating lines in operation prior to January 1, 1991 ("preexisting coating lines"), may, for pre-existing coating lines only, elect to comply with the requirements of this Section, rather than complying with the applicable emission limitations set forth in Section 218.204, if an operational change of the type described below has been made after January 1, 1991, to one or more preexisting coating lines at the source. An operational change occurs when a preexisting coating line is replaced with a line using lower VOM coating for the same purpose as the replaced line ("replacement line"). A source electing to rely on this Section to demonstrate compliance with the requirements of this Subpart shall operate pursuant to federally enforceable permit conditions approved by the Agency and USEPA.

- b) An owner or operator of pre-existing coating lines subject to a VOM content limitation in Section 218.204 of this Subpart and electing to rely on this Section to demonstrate compliance with this Subpart must establish, by use of the equations in subsection (d) of this Section, that the calculated actual daily VOM emissions from all participating coating lines, as defined below, are less than the calculated daily allowable VOM emissions from the same group of coating lines. For any pre-existing coating line to be aggregated for the purposes of Section 218.212, 218.213, or 218.214 of this Subpart ("participating coating lines"), the source must establish that:
  - 1) All coatings applied on the participating coating line shall, at all times, have a VOM content less than or equal to the applicable VOM content limitation for such coating listed in Appendix H of this Part; and
  - 2) On the date the source elects to rely on this Section to demonstrate compliance with this Subpart, all coatings applied on the participating coating line are not already in compliance with the VOM content limitation for such coating effective on or after March 15, 1996; or the participating coating line is a replacement line, as defined in subsection (a) of this Section with an operational change occurring on or after January 1, 1991.
- c) Notwithstanding subsection (a) of this Section, any owner or operator of a coating line subject to the limitations set forth in Section 218.204 of this Subpart and electing to rely on this Section to demonstrate compliance with this Subpart, may also include as a participating coating line, until December 31, 1999, only, any replacement line that satisfies all of the following conditions:

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- 1) The replacement line is operated as a powder coating line;
- 2) The replacement line was added after July 1, 1988; and
- 3) The owner or operator also includes as a participating coating line one or more coating lines that satisfy the criteria of a replacement line, as described in subsection (a) of this Section.
- d) To demonstrate compliance with this Section, a source shall establish the following:
  - 1) An alternative daily emission limitation shall be determined for all participating coating lines at the source according to subsection (d)(2) of this Section. All participating coating lines shall be factored in each day to demonstrate compliance. Provided compliance is established pursuant to the requirements in this subsection, nothing in this Section requires daily operation of each participating line. Actual daily emissions from all participating coating lines  $(E_d)$  shall never exceed the alternative daily emission limitation  $(A_d)$  and shall be calculated by use of the following equation:

$$E_d = \sum_{i=1}^n V_i C_i$$

- $E_d$  = Actual daily VOM emissions from participating coating lines in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of coatings applied by all participating coating lines at the source;
- V<sub>i</sub> = Volume of each coating applied for the day in units of l/day (gal/day) of coating 3(minus water and any compounds which are specifically exempted from the definition of VOM); and

#### NOTICE OF PROPOSED AMENDMENTS

- $C_i$  = The VOM content of each coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM).
- 2) The alternative daily emission limitation (A<sub>d</sub>) shall be determined for all participating coating lines at the source on a daily basis as follows:

$$A_d = A_l + A_p$$

where

 $A_d$  and  $A_p$  are defined in subsections (2)(A) and (2)(B) of this Section.

A) The portion of the alternative daily emissions limitation for coating operations at a source using non-powder coating (A<sub>1</sub>) shall be determined for all such participating non-powder coating lines on a daily basis as follows:

$$\begin{array}{ccc}n\\A_{l} = \Sigma & V_{i} & (\underline{D_{i} - C_{i}})\\i = 1 & L_{i} & (D_{i} - L_{i})\end{array}$$

- A<sub>1</sub> = The VOM emissions allowed for the day in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of coatings applied in the participating coating lines;
- C<sub>i</sub> = The VOM content of each coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- D<sub>i</sub> = The density of VOM in each coating applied. For the purposes of calculating A<sub>1</sub>, the density is 0.882 kg VOM/1 VOM (7.36 lbs VOM/gal VOM);

## POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

- $V_i$  = Volume of each coating applied for the day in units of 1 (gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM); and
- L<sub>i</sub> = The VOM emission limitation for each coating applied, as specified in Section 218.204 of this Subpart, in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM).
- B) The portion of the alternative daily emission limitation for coating operations at a source using powdered coating (A<sub>p</sub>) shall be determined for all such participating powder coating lines at the source on a daily basis as follows:

$$A_{p} = \sum_{h=1}^{m} \sum_{j=1}^{n} \frac{V_{j} L_{j} D_{j} K_{h}}{(D_{j} - L_{j})}$$

- A<sub>p</sub> = The VOM emissions allowed for the day in units of kg/day (lbs/day);
- h = Subscript denoting a specific powder coating line;
- j = Subscript denoting a specific powder coating applied;
- m = Total number of participating powder coating lines;
- n = Total number of powder coatings applied in the participating coating lines;
- D<sub>j</sub> = The assumed density of VOM in liquid coating, 0.882 kg VOM/1 VOM (7.36 lbs VOM/gal VOM);
- V<sub>j</sub> = Volume of each powder coating consumed for the day in units of 1 (gal) of coating; and

# NOTICE OF PROPOSED AMENDMENTS

- L<sub>j</sub> = The VOM emission limitation for each coating applied, as specified in Section 218.204 of this Subpart, in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM); and
- K = A constant for each individual coating line representing the ratio of the volume of coating solids consumed on the liquid coating system which has been replaced to the volume of powder coating consumed on the replacement line to accomplish the same coating job. This value shall be determined by the source based on tests conducted and records maintained pursuant to the requirements of Section 218.213 of this Subpart demonstrating the amount of coating solids consumed as both liquid and powder. Test methods and recordkeeping requirements shall be approved by the Agency and USEPA and shall be contained in the source's operating permit as federally enforceable permit conditions, subject to the following restrictions:
- i) K cannot exceed 0.9 for non-recycled powder coating systems; or
- ii) K cannot exceed 2.0 for recycled powder coating systems.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective\_\_\_\_)

# Section 218.218 Work Practice Standards for Paper Coatings, Metal Furniture Coatings, and Large Appliance Coatings

- a) On and after May 1, 2011, every owner or operator of a source subject to the requirements of Section 218.204(c) of this Subpart shall:
  - 1) Store all VOM-containing cleaning materials in closed containers;
  - 2) Ensure that mixing and storage containers used for VOM-containing materials are kept closed at all times except when depositing or removing such materials:
  - 3) <u>Minimize spills of VOM-containing cleaning materials;</u>

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

- 4) <u>Convey VOM-containing cleaning materials from one location to another</u> in closed containers or pipes; and
- 5) Minimize VOM emissions from the cleaning of storage, mixing, and conveying equipment.
- b) On and after May 1, 2011, every owner or operator of a source subject to the requirements of Section 218.204(g) or 218.204(h) of this Subpart shall:
  - 1) <u>Store all VOM-containing coatings, thinners, coating-related waste</u> materials, cleaning materials, and used shop towels in closed containers;
  - 2) Ensure that mixing and storage containers used for VOM-containing coatings, thinners, coating-related waste materials, and cleaning materials are kept closed at all times except when depositing or removing such materials;
  - 3) Minimize spills of VOM-containing coatings, thinners, coating-related waste materials, and cleaning materials, and clean up spills immediately;
  - 4) <u>Convey VOM-containing coatings, thinners, coating-related waste</u> <u>materials, and cleaning materials from one location to another in closed</u> <u>containers or pipes; and</u>
  - 5) Minimize VOM emissions from the cleaning of storage, mixing, and conveying equipment.

(Source: Added at 34 Ill. Reg. \_\_\_\_, effective\_\_\_\_)



## POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

- 1) Heading of the Part: Organic Material Emission Standards and Limitations for the Metro East Area 2) Code Citation: 35 Ill. Adm. Code 219 RECEIVED CLERK'S OFFICE 3) Section Numbers: Proposed Action: NOV 172009 219.106 Amended STATE OF ILLINOIS 219.204 Amended Pollution Control Board 219.205 Amended 219.207 Amended 219.210 Amended 219.211 Amended 219.212 Amended 219.218 New
- 4) <u>Statutory Authority</u>: Implementing Section 10 and authorized by Sections 27, 28, and 28.5 of the Environmental Protection Act [415 ILCS 5/10, 27, 28, and 28.5]
- 5) A Complete Description of the Subjects and Issues Involved: The proposed rulemaking intends to satisfy Illinois' obligation to submit a State Implementation Plan addressing requirements under Sections 172 and 182 of the federal Clean Air Act, 42 U.S.C. § 7401 et seq., for sources of volatile organic material (VOM) emissions in areas designated as nonattainment with respect to the ozone National Ambient Air Quality Standard. The United States Environmental Protection Agency (USEPA) issued Control Techniques Guidelines (CTGs) for the following Group III Consumer and Commercial Product Categories: Paper, Film, and Foil Coatings, Metal Furniture Coatings, and Large Appliance Coatings. In the CTGs, the USEPA recommended control measures that it believes constitute reasonably available control technology for the product categories. The Illinois EPA proposes amending Part 219 to implement such recommendations for the Metro East nonattainment area. Generally, the proposal amends VOM content limitations and exclusions, requires that metal furniture and large appliance coating lines comply with application method limitations, and requires that subject coating lines implement specified work practices for cleaning materials and/or cleaning-related activities.
- 6) <u>Published studies or reports, and sources of underlying data, used to compose this</u> <u>rulemaking:</u> The regulatory proposal included the Illinois EPA's *Technical Support Document*, which relied on several sources. Copies of the documents the Illinois EPA relied upon are available for review with the Pollution Control Board and are listed

RECEIVED

NOV - 5 2009

SOS-CODE DIV.

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

below:

*Control Techniques Guidelines for Paper, Film, and Foil Coatings*, United States Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 2007.

*Control Techniques Guidelines for Metal Furniture Coatings*, United States Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 2007.

*Control Techniques Guidelines for Large Appliance Coatings*, United States Environmental Protection Agency, Office of Air Quality Planning and Standards, Research Triangle Park, NC, September 2007.

- 7) Will this proposed amendment replace an emergency rule currently in effect? No.
- 8) <u>Does this rulemaking contain an automatic repeal date</u>? No.
- 9) Does this proposed amendment contain incorporations by reference? No.
- 10) Are there any other proposed amendments pending on this Part? No.
- Statement of Statewide Policy Objectives: This proposed rule does not create or enlarge a State mandate, as defined in Section 3(b) of the State Mandates Act. [30 ILCS 805/3(b) (2006)].
- 12) <u>Time, Place, and Manner in which interested persons may comment on this proposed</u> <u>rulemaking</u>:

Interested persons may request copies of the Board's opinion and order by calling the Clerk's office at 312-814-3620, or may download copies from the Board's Web site at <u>www.ipcb.state.il.us</u>. The Board will accept written public comment on this proposal for 45 days after the date of publication in the *Illinois Register*. Comments should refer to Docket R10-10 and be addressed to:

## POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

Clerk's Office Illinois Pollution Control Board 100 W. Randolph St., Suite 11-500 Chicago, IL 60601

The Board has scheduled hearings according to the deadlines and for the purposes established by Section 28.5. Each hearing will continue from day-to-day until business is completed:

First hearing:	Wednesday, December 9, 2009 10:00 AM James R. Thompson Center 100 W. Randolph St. Pollution Control Board Conference Room 11-512 Chicago, Illinois
Second hearing: (if necessary)	Wednesday, January 6, 2010 10:00 AM Michael A. Bilandic Building 160 N. LaSalle Street Room N-505 Chicago, Illinois
Third hearing: (if necessary)	Wednesday, January 20, 2010 10:00 AM Michael A. Bilandic Building 160 N. LaSalle Street Room N-505 Chicago, Illinois

A November 5, 2009 hearing officer order contains additional details concerning participation in the rulemaking. For more information contact Hearing Officer Tim Fox at 312-814-6085 or email at foxt@ipcb.state.il.us.

- 13) Initial Regulatory Flexibility Analysis:
  - A. Types of small businesses, small municipalities and not for profit corporations affected: This rulemaking will impact any small business, small municipality, and not-for-profit corporation that falls within one of the Group III Product

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

Categories and meets the applicability thresholds specified in the proposal.

- B. Reporting, bookkeeping or other procedures required for compliance: The proposed rulemaking requires that the owner or operator of a subject source perform emissions monitoring, submit certifications, complete required tests, and maintain records and make reports as required.
- C. Types of Professional skills necessary for compliance: No professional skills beyond those currently required by the existing state and federal air pollution control regulations applicable to affected sources will be required.
- 14) <u>Regulatory Agenda on which this rulemaking was summarized</u>: July 2009

The full text of the Proposed Amendment(s) begins on the next page:

#### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

# TITLE 35: ENVIRONMENTAL PROTECTION SUBTITLE B: AIR POLLUTION CHAPTER I: POLLUTION CONTROL BOARD SUBCHAPTER c: EMISSIONS STANDARDS AND LIMITATIONS FOR STATIONARY SOURCES

## PART 219 ORGANIC MATERIAL EMISSION STANDARDS AND LIMITATIONS FOR THE METRO EAST AREA

#### SUBPART A: GENERAL PROVISIONS

Sectio	n

- 219.100 Introduction
- 219.101 Savings Clause
- 219.102 Abbreviations and Conversion Factors
- 219.103 Applicability
- 219.104 Definitions
- 219.105 Test Methods and Procedures
- 219.106 Compliance Dates
- 219.107 Operation of Afterburners
- 219.108 Exemptions, Variations, and Alternative Means of Control or Compliance Determinations
- 219.109 Vapor Pressure of Volatile Organic Liquids
- 219.110 Vapor Pressure of Organic Material or Solvent
- 219.111 Vapor Pressure of Volatile Organic Material
- 219.112 Incorporations by Reference
- 219.113 Monitoring for Negligibly-Reactive Compounds

# SUBPART B: ORGANIC EMISSIONS FROM STORAGE AND LOADING OPERATIONS

- Section
- 219.119 Applicability for VOL
- 219.120 Control Requirements for Storage Containers of VOL
- 219.121 Storage Containers of VPL
- 219.122 Loading Operations
- 219.123 Petroleum Liquid Storage Tanks
- 219.124 External Floating Roofs
- 219.125 Compliance Dates
- 219.126 Compliance Plan (Repealed)
- 219.127 Testing VOL Operations

## POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- 219.128 Monitoring VOL Operations
- 219.129 Recordkeeping and Reporting for VOL Operations

## SUBPART C: ORGANIC EMISSIONS FROM MISCELLANEOUS EQUIPMENT

Section

- 219.141 Separation Operations
- 219.142 Pumps and Compressors
- 219.143 Vapor Blowdown
- 219.144 Safety Relief Valves

## SUBPART E: SOLVENT CLEANING

Section

- 219.181 Solvent Cleaning in General
- 219.182 Cold Cleaning
- 219.183 Open Top Vapor Degreasing
- 219.184 Conveyorized Degreasing
- 219.185 Compliance Schedule (Repealed)
- 219.186 Test Methods

#### SUBPART F: COATING OPERATIONS

- Section
- 219.204 Emission Limitations
- 219.205 Daily-Weighted Average Limitations
- 219.206 Solids Basis Calculation
- 219.207 Alternative Emission Limitations
- 219.208 Exemptions From Emission Limitations
- 219.209 Exemption From General Rule on Use of Organic Material
- 219.210 Compliance Schedule
- 219.211 Recordkeeping and Reporting
- 219.212 Cross-Line Averaging to Establish Compliance for Coating Lines
- 219.213 Recordkeeping and Reporting for Cross-Line Averaging Participating Coating Lines
- 219.214 Changing Compliance Methods
- 219.215 Wood Furniture Coating Averaging Approach
- 219.216 Wood Furniture Coating Add-On Control Use
- 219.217 Wood Furniture Coating Work Practice Standards
- 219.218 Work Practice Standards for Paper Coatings, Metal Furniture Coatings, and Large Appliance Coatings

# POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

## SUBPART G: USE OF ORGANIC MATERIAL

- Section
- 219.301 Use of Organic Material
- 219.302 Alternative Standard
- 219.303 Fuel Combustion Emission Units
- 219.304 Operations with Compliance Program

## SUBPART H: PRINTING AND PUBLISHING

- Section
- 219.401 Flexographic and Rotogravure Printing
- 219.402 Applicability
- 219.403 Compliance Schedule
- 219.404 Recordkeeping and Reporting
- 219.405 Lithographic Printing: Applicability
- 219.406 Provisions Applying to Heatset Web Offset Lithographic Printing Prior to March 15, 1996
- 219.407 Emission Limitations and Control Requirements for Lithographic Printing Lines On and After March 15, 1996
- 219.408 Compliance Schedule for Lithographic Printing On and After March 15, 1996
- 219.409 Testing for Lithographic Printing On and After March 15, 1996
- 219.410 Monitoring Requirements for Lithographic Printing
- 219.411 Recordkeeping and Reporting for Lithographic Printing

# SUBPART Q: SYNTHETIC ORGANIC CHEMICAL AND POLYMER MANUFACTURING PLANT

- Section
- 219.421 General Requirements
- 219.422 Inspection Program Plan for Leaks
- 219.423 Inspection Program for Leaks
- 219.424 Repairing Leaks
- 219.425 Recordkeeping for Leaks
- 219.426 Report for Leaks
- 219.427 Alternative Program for Leaks
- 219.428 Open-Ended Valves
- 219.429 Standards for Control Devices
- 219.430 Compliance Date (Repealed)
- 219.431 Applicability
- 219.432 Control Requirements
- 219.433 Performance and Testing Requirements
- 219.434 Monitoring Requirements

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

- 219.435 Recordkeeping and Reporting Requirements
- 219.436 Compliance Date

# SUBPART R: PETROLEUM REFINING AND RELATED INDUSTRIES; ASPHALT MATERIALS

Section

- 219.441 Petroleum Refinery Waste Gas Disposal
- 219.442 Vacuum Producing Systems
- 219.443 Wastewater (Oil/Water) Separator
- 219.444 Process Unit Turnarounds
- 219.445 Leaks: General Requirements
- 219.446 Monitoring Program Plan for Leaks
- 219.447 Monitoring Program for Leaks
- 219.448 Recordkeeping for Leaks
- 219.449 Reporting for Leaks
- 219.450 Alternative Program for Leaks
- 219.451 Sealing Device Requirements
- 219.452 Compliance Schedule for Leaks
- 219.453 Compliance Dates (Repealed)

# SUBPART S: RUBBER AND MISCELLANEOUS PLASTIC PRODUCTS

- Section
- 219.461 Manufacture of Pneumatic Rubber Tires
- 219.462 Green Tire Spraying Operations
- 219.463 Alternative Emission Reduction Systems
- 219.464 Emission Testing
- 219.465 Compliance Dates (Repealed)
- 219.466 Compliance Plan (Repealed)

# SUBPART T: PHARMACEUTICAL MANUFACTURING

- Section
- 219.480 Applicability
- 219.481 Control of Reactors, Distillation Units, Crystallizers, Centrifuges and Vacuum Dryers
- 219.482 Control of Air Dryers, Production Equipment Exhaust Systems and Filters
- 219.483 Material Storage and Transfer
- 219.484 In-Process Tanks
- 219.485 Leaks
- 219.486 Other Emission Units
- 219.487 Testing

## POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

- 219.488 Monitoring for Air Pollution Control Equipment
- 219.489 Recordkeeping for Air Pollution Control Equipment

## SUBPART V: BATCH OPERATIONS AND AIR OXIDATION PROCESSES

# Section

219.500	Applicability fo	or Batch Operations
---------	------------------	---------------------

- 219.501 Control Requirements for Batch Operations
- 219.502 Determination of Uncontrolled Total Annual Mass Emissions and Actual Weighted Average Flow Rate Values for Batch Operations
- 219.503 Performance and Testing Requirements for Batch Operations
- 219.504 Monitoring Requirements for Batch Operations
- 219.505 Reporting and Recordkeeping for Batch Operations
- 219.506 Compliance Date
- 219.520 Emission Limitations for Air Oxidation Processes
- 219.521 Definitions (Repealed)
- 219.522 Savings Clause
- 219.523 Compliance
- 219.524 Determination of Applicability
- 219.525 Emission Limitations for Air Oxidation Processes (Renumbered)
- 219.526 Testing and Monitoring
- 219.527 Compliance Date (Repealed)

#### SUBPART W: AGRICULTURE

Section

219.541 Pesticide Exception

## SUBPART X: CONSTRUCTION

Section

- 219.561 Architectural Coatings
- 219.562 Paving Operations
- 219.563 Cutback Asphalt

#### SUBPART Y: GASOLINE DISTRIBUTION

Section

- 219.581 Bulk Gasoline Plants
- 219.582 Bulk Gasoline Terminals
- 219.583 Gasoline Dispensing Operations Storage Tank Filling Operations
- 219.584 Gasoline Delivery Vessels
- 219.585 Gasoline Volatility Standards
- 219.586 Gasoline Dispensing Operations Motor Vehicle Fueling Operations (Repealed)

## NOTICE OF PROPOSED AMENDMENTS

## SUBPART Z: DRY CLEANERS

- 219.601 Perchloroethylene Dry Cleaners (Repealed)
- 219.602 Exemptions (Repealed)
- 219.603 Leaks (Repealed)
- 219.604 Compliance Dates (Repealed)
- 219.605 Compliance Plan (Repealed)
- 219.606 Exception to Compliance Plan (Repealed)
- 219.607 Standards for Petroleum Solvent Dry Cleaners
- 219.608 Operating Practices for Petroleum Solvent Dry Cleaners
- 219.609 Program for Inspection and Repair of Leaks
- 219.610 Testing and Monitoring
- 219.611 Exemption for Petroleum Solvent Dry Cleaners
- 219.612 Compliance Dates (Repealed)
- 219.613 Compliance Plan (Repealed)

## SUBPART AA: PAINT AND INK MANUFACTURING

Section

Section

- 219.620 Applicability
- 219.621 Exemption for Waterbase Material and Heatset-Offset Ink
- 219.623 Permit Conditions
- 219.624 Open-Top Mills, Tanks, Vats or Vessels
- 219.625 Grinding Mills
- 219.626 Storage Tanks
- 219.628 Leaks
- 219.630 Clean Up
- 219.636 Compliance Schedule
- 219.637 Recordkeeping and Reporting

#### SUBPART BB: POLYSTYRENE PLANTS

- Section 219.640 Applicability
- 219.642 Emissions Limitation at Polystyrene Plants
- 219.644 Emissions Testing

#### SUBPART FF: BAKERY OVENS

- Section
- 219.720 Applicability (Repealed)
- 219.722 Control Requirements (Repealed)

#### POLLUTION CONTROL BOARD

## NOTICE OF PROPOSED AMENDMENTS

- 219.726 Testing (Repealed)
- 219.727 Monitoring (Repealed)
- 219.728 Recordkeeping and Reporting (Repealed)
- 219.729 Compliance Date (Repealed)
- 219.730 Certification (Repealed)

## SUBPART GG: MARINE TERMINALS

- Section
- 219.760 Applicability
- 219.762 Control Requirements
- 219.764 Compliance Certification
- 219.766 Leaks
- 219.768 Testing and Monitoring
- 219.770 Recordkeeping and Reporting

#### SUBPART HH: MOTOR VEHICLE REFINISHING

- Section
- 219.780 Emission Limitations
- 219.782 Alternative Control Requirements
- 219.784 Equipment Specifications
- 219.786 Surface Preparation Materials
- 219.787 Work Practices
- 219.788 Testing
- 219.789 Monitoring and Recordkeeping for Control Devices
- 219.790 General Recordkeeping and Reporting (Repealed)
- 219.791 Compliance Date
- 219.792 Registration
- 219.875 Applicability of Subpart BB (Renumbered)
- 219.877 Emissions Limitation at Polystyrene Plants (Renumbered)
- 219.879 Compliance Date (Repealed)
- 219.881 Compliance Plan (Repealed)
- 219.883 Special Requirements for Compliance Plan (Repealed)
- 219.886 Emissions Testing (Renumbered)

## SUBPART PP: MISCELLANEOUS FABRICATED PRODUCT MANUFACTURING PROCESSES

Section

- 219.920 Applicability
- 219.923 Permit Conditions
- 219.926 Control Requirements

# POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

- 219.927 **Compliance Schedule**
- 219.928 Testing

### SUBPART QQ: MISCELLANEOUS FORMULATION MANUFACTURING PROCESSES

### Section

- 219.940 Applicability
- 219.943 Permit Conditions
- **Control Requirements** 219.946
- **Compliance Schedule** 219.947
- 219.948 Testing

### SUBPART RR: MISCELLANEOUS ORGANIC CHEMICAL MANUFACTURING PROCESSES

- Section
- 219.960 Applicability
- Permit Conditions 219.963
- 219.966 **Control Requirements**
- **Compliance Schedule** 219.967
- 219.968 Testing

#### SUBPART TT: OTHER EMISSION UNITS

- Section
- 219.980 Applicability
- Permit Conditions 219.983
- **Control Requirements** 219.986
- **Compliance Schedule** 219.987
- 219.988 Testing

# SUBPART UU: RECORDKEEPING AND REPORTING

Section

- 219.990 **Exempt Emission Units**
- 219.991 Subject Emission Units
- 219.APPENDIX A: List of Chemicals Defining Synthetic Organic Chemical and Polymer Manufacturing 219.APPENDIX B:
- VOM Measurement Techniques for Capture Efficiency (Repealed)
- **Reference** Methods and Procedures 219.APPENDIX C:
- 219.APPENDIX D: Coefficients for the Total Resource Effectiveness Index (TRE) Equation
- 219.APPENDIX E: List of Affected Marine Terminals

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

# 219.APPENDIX G: TRE Index Measurements for SOCMI Reactors and Distillation Units 219.APPENDIX H: Baseline VOM Content Limitations for Subpart F, Section 219.212 Cross-Line Averaging

AUTHORITY: Implementing Section 10 and authorized by Sections 27, 28 and 28.5 of the Environmental Protection Act [415 ILCS 5/10, 27, 28, and 28.5].

SOURCE: Adopted in R91-8 at 15 Ill. Reg. 12491, effective August 16, 1991; amended in R91-24 at 16 Ill. Reg. 13597, effective August 24, 1992; amended in R91-30 at 16 Ill. Reg. 13883, effective August 24, 1992; emergency amendment in R93-12 at 17 Ill. Reg. 8295, effective May 24, 1993, for a maximum of 150 days, amended in R93-9 at 17 Ill. Reg. 16918, effective September 27, 1993 and October 21, 1993; amended in R93-28 at 18 Ill. Reg. 4242, effective March 3, 1994; amended in R94-12 at 18 Ill. Reg. 14987, effective September 21, 1994; amended in R94-15 at 18 Ill. Reg. 16415, effective October 25, 1994; amended in R94-16 at 18 Ill. Reg. 16980, effective November 15, 1994; emergency amendment in R95-10 at 19 Ill. Reg. 3059, effective February 28, 1995, for a maximum of 150 days; amended in R94-21, R94-31 and R94-32 at 19 Ill. Reg. 6958, effective May 9, 1995; amended in R94-33 at 19 Ill. Reg. 7385, effective May 22, 1995; amended in R96-2 at 20 Ill. Reg. 3848, effective February 15, 1996; amended in R96-13 at 20 Ill. Reg. 14462, effective October 28, 1996; amended in R97-24 at 21 Ill. Reg. 7721, effective June 9, 1997; amended in R97-31 at 22 Ill. Reg. 3517, effective February 2, 1998; amended in R04-12/20 at 30 Ill. Reg. 9799, effective May 15, 2006; amended in R06-21 at 31 Ill. Reg. 7110, effective April 30, 2007; amended in R10-10 at 34 Ill. Reg. effective \_\_\_\_\_.

# SUBPART A: GENERAL PROVISIONS

#### Section 219.106 Compliance Dates

- a) Except as provided in subsection (b) below, compliance with the requirements of this Part is required by May 15, 1992, consistent with the provisions of Section 219.103 of this Part.
- b) As this Part is amended from time to time, compliance dates included in the specific Subparts supersede the requirements of this Section except as limited by Section 219.101(b) of this Subpart.
- c) Any owner or operator of a source subject to the requirements of Section 219.204(c)(2), 219.204(g)(2), or 219.204(h)(2) of this Part shall comply with the applicable requirements in such Section(s), as well as all applicable requirements in Sections 219.205 through 219.214 and 219.218, by May 1, 2011.

### POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

### SUBPART F: COATING OPERATIONS

#### Section 219.204 Emission Limitations

a)

Except as provided in Sections 219.205, 219.207, 219.208, 219.212, 219.215 and 219.216 of this Subpart, no owner or operator of a coating line shall apply at any time any coating in which the VOM content exceeds the following emission limitations for the specified coating. Except as otherwise provided in Sections 219.204(c), 219.204(g), 219.204(h), and 219.204(l), compliance with the emission limitations marked with an asterisk in this Section is required on and after March 15, 1996, and compliance with emission limitations not marked with an asterisk is required until March 15, 1996. The following emission limitations are expressed in units of VOM per volume of coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied at each coating applicator, except where noted. Compounds which are specifically exempted from the definition of VOM should be treated as water for the purpose of calculating the "less water" part of the coating composition. Compliance with this Subpart must be demonstrated through the applicable coating analysis test methods and procedures specified in Section 219.105(a) of this Part and the recordkeeping and reporting requirements specified in Section 219.211(c) of this Subpart except where noted. (Note: The equation presented in Section 219.206 of this Part shall be used to calculate emission limitations for determining compliance by add-on controls, credits for transfer efficiency, emissions trades and cross-line averaging.) The emission limitations are as follows:

Autor	nobile or Light-Duty Truck Coating	kg/l	lb/gal
1)	Prime coat	0.14 0.14*	(1.2) (1.2)*
2)	Primer surface coat	1.81 1.81*	(15.1) (15.1)*

(Note: The primer surface coat limitation is in units of kg (lbs) of VOM per l (gal) of coating solids deposited. Compliance with the limitation shall be based on the daily-weighted average from an entire primer surface operation. Compliance shall be demonstrated in accordance with the topcoat protocol referenced in Section 219.105(b) and the recordkeeping and reporting requirements specified in Section 219.211(f). Testing to demonstrate compliance shall be performed in accordance with the topcoat

#### NOTICE OF PROPOSED AMENDMENTS

protocol and a detailed testing proposal approved by the Agency and USEPA specifying the method of demonstrating compliance with the protocol. Section 219.205 does not apply to the primer surface limitation.)

		kg/l	lb/gal
3)	Topcoat	1.81	(15.1)
		1.81*	(15.1)*

(Note: The topcoat limitation is in units of kg (lbs) of VOM per l (gal) of coating solids deposited. Compliance with the limitation shall be based on the daily-weighted average from an entire topcoat operation. Compliance shall be demonstrated in accordance with the topcoat protocol referenced in Section 219.105(b) of this Part and the recordkeeping and reporting requirements specified in Section 219.211(f). Testing to demonstrate compliance shall be performed in accordance with the topcoat protocol and a detailed testing proposal approved by the Agency and USEPA specifying the method of demonstrating compliance with the protocol. Section 219.205 of this Part does not apply to the topcoat limitation.)

	4)	Final 1	repair coat	kg/l 0.58 0.58*	lb/gal (4.8) (4.8)*
b)	Can C	Can Coating <ol> <li>Sheet basecoat and overvarnish</li> </ol>		kg/l	lb/gal
	1)				
		A)	Sheet basecoat	0.34 0.26*	(2.8) (2.2)*
		B)	Overvarnish	0.20 0.34 0.34	(2.8)
				0.54	(2.8)*
	2)	Exteri	or basecoat and overvarnish	0.34 0.25*	(2.8) (2.1)*
	3)	Interio	or body spray coat		
		A)	Two piece	0.51	(4.2)
		B)	Three piece	0.44* 0.51	(3.7)* (4.2)

# POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

			0.51*	(4.2)*
4)	Exter	ior end coat	0.51 0.51*	(4.2) (4.2)*
5)	Side s	seam spray coat	0.66 0.66*	(5.5) (5.5)*
6)	End s	ealing compound coat	0.44 0.44*	(3.7) (3.7)*
Paper	Coating	g	<del>kg/l</del> 0.35 0.28*	<del>lb/gal</del> <del>(2.9)</del> <del>(2.3)</del> *
<u>1)</u>	Prior 1	<u>to May 1, 2011:</u>	<u>kg/1</u> 0.28	<u>lb/gal</u> (2.3)
<u>2)</u>	<u>On an</u> <u>A)</u>	<u>d after May 1, 2011:</u> Pressure sensitive	<u>kg VOM/kg</u> ( <u>lb VOM/lb)</u> solids applied	<u>kg VOM/kg</u> ( <u>lb VOM/lb)</u> coatings applied
		tape and label surface coatings	<u>0.20</u>	<u>(0.067)</u>
	<u>B)</u>	All other paper coatings	<u>0.40</u>	<u>(0.08)</u>

c)

(Note: The paper coating limitation shall not apply to any owner or operator of any paper coating line on which flexographic or rotogravure printing is performed if the paper coating line complies with the emissions limitations in Section 219.401 of this Part. In addition, screen printing on paper is not regulated as paper coating, but is regulated under Subpart TT of this Part. <u>On and after May 1, 2011, the paper coating limitation shall also not apply to coating performed on or in-line with any digital printing press, or to size presses and on-machine coaters on papermaking machines applying sizing or water-based clays.)</u>

		kg/l	lb/gal
d)	Coil Coating	0.31	(2.6)

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

					0.20*	(1.7)*
e)	Fabri	ic Coati	ng		0.35 0.28*	(2.9) (2.3)*
f)	Viny	l Coatir	ıg		0.45 0.28*	(3.8) (2.3)*
g)	Meta	l Furnit	ture Coa	ating		
	<u>1)</u>	<u>Prior</u>	to May	<u>1, 2011:</u>		
		<u>A)</u>	<u>Air d</u>	ried	<u>kg/1</u> 0.34	<u>lb/gal</u> (2.8)
		<u>B)</u>	Bake	<u>d</u>	<u>0.28</u>	<u>(2.3)</u>
	<u>2)</u>	<u>On a</u>	nd after	<u>May 1, 2011:</u>	<u>kg/l</u> (lb/gal)	<u>kg/l (lb/gal)</u> solids applied
		<u>A)</u>	<u>Gene</u>	ral, One Component	<u>0.275</u> (2.3)	$\frac{0.40}{(3.3)}$
		<u>B)</u>	Gene	ral, Multi-Component		
			<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
			<u>ii)</u>	Baked	<u>0.275</u> (2.3)	<u>0.40</u> (3.3)
		<u>C)</u>	Extre	me High Gloss		
			<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
			<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
			Entro	ma Doutours ou oo		

<u>D)</u> <u>Extreme Performance</u>

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>E)</u>	<u>Heat</u>	Resistant		
	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>F)</u>	Meta	llic	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
<u>G)</u>	Pretr	eatment Coatings	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
<u>H)</u>	<u>Sola</u>	Absorbent		
	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<del>Air d</del>	lried		<del>0.36</del> <del>0.34*</del>	<del>(3.0)</del> <del>(2.8)*</del>
Bake	d		<del>0.36</del> <del>0.28*</del>	<del>(3.0)</del> <del>(2.3)*</del>

1

<del>2)</del>

(Note: On and after May 1, 2011, these limitations shall not apply to stencil coatings, safety-indicating coatings, solid-film lubricants, electric-insulating and thermal-conducting coatings, touch-up and repair coatings, or coating applications utilizing hand-held aerosol cans.)

#### POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

- 3) On and after May 1, 2011, an owner or operator of a coating line subject to the limitations in subsection (g) of this Section shall apply all coatings using one or more of the following application methods:
  - <u>A)</u> <u>Electrostatic spray;</u>
  - <u>B)</u> <u>High volume low pressure (HVLP) spray;</u>
  - <u>C)</u> <u>Flow coating.</u> For the purposes of this subsection (g), flow coating means a non-atomized technique of applying coating to a substrate with a fluid nozzle with no air supplied to the nozzle;
  - D) Roll coating;
  - E) Dip coating, including electrodeposition. For purposes of this subsection (g), electrodeposition means a water-borne dip coating process in which opposite electrical charges are applied to the substrate and the coating. The coating is attracted to the substrate due to the electrochemical potential difference that is created; or
  - <u>F)</u> Another coating application method capable of achieving a transfer efficiency equal to or better than that achieved by HVLP spraying, if such method is approved in writing by the Agency.
- h) Large Appliance Coating

<u>1)</u>	<u>Prior</u>	rior to May 1, 2011:				
	<u>A)</u>	Air dried	<u>kg/1</u> 0.34	<u>lb/gal</u> (2.8)		
	<u>B)</u>	Baked	<u>0.28</u>	<u>(2.3)</u>		
<u>2)</u>	<u>On ar</u>	<u>nd after May 1, 2011:</u>	<u>kg/l</u> (1b/gal)	<u>kg/l (lb/gal)</u> solids applied		
	<u>A)</u>	General, One Component	<u>0.275</u> (2.3)	$\frac{0.40}{(3.3)}$		
	<u>B)</u>	General, Multi-Component				

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

	<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
	<u>ii)</u>	Baked	<u>0.275</u> (2.3)	$\frac{0.40}{(3.3)}$
<u>C)</u>	Extrer	ne High Gloss		
	<u>i)</u>	Air Dried	<u>0.340</u> (2.8)	<u>0.55</u> (4.5)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>D)</u>	Extrer	ne Performance		
	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>E)</u>	<u>Heat F</u>	Resistant		
	<u>i)</u>	Air Dried	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
<u>F)</u>	<u>Metall</u>	ic	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
<u>G)</u>	Pretrea	atment Coatings	<u>0.420</u> (3.5)	<u>0.80</u> (6.7)
<u>H)</u>	Solar 4	Absorbent		
	<u>i)</u>	Air Dried	<u>0.420</u>	<u>0.80</u>

### NOTICE OF PROPOSED AMENDMENTS

			<u>(3.5)</u>	<u>(6.7)</u>
	<u>ii)</u>	Baked	<u>0.360</u> (3.0)	<u>0.61</u> (5.1)
1)	Air dried		<del>0.3</del> 4 <del>0.34*</del>	<del>(2.8)</del> <del>(2.8)*</del>
<del>2)</del>	Baked		<del>0.34</del> <del>0.28*</del>	<del>(2.8)</del> <del>(2.3)*</del>

(Note: The<u>se</u> limitation<u>s</u> shall not apply to the use of quick-drying lacquers for repair of scratches and nicks that occur during assembly, provided that the volume of coating does not exceed 0.951 (1 quart) in any one rolling eight-hour period. On and after May 1, 2011, these limitations shall also not apply to stencil coatings, safety-indicating coatings, solid-film lubricants, electric-insulating and thermal-conducting coatings, touch-up and repair coatings, or coating applications utilizing hand-held aerosol cans.)

- 3) On and after May 1, 2011, an owner or operator of a coating line subject to the limitations in subsection (h) of this Section shall apply all coatings using one or more of the following application methods:
  - A) Electrostatic spray;
  - B) High volume low pressure (HVLP) spray;
  - <u>C)</u> <u>Flow coating</u>. For the purposes of this subsection (h), flow coating means a non-atomized technique of applying coating to a substrate with a fluid nozzle with no air supplied to the nozzle;
  - <u>D)</u> <u>Roll coating;</u>
  - <u>E)</u> Brush coating;
  - F) Dip coating, including electrodeposition. For purposes of this subsection (h), electrodeposition means a water-borne dip coating process in which opposite electrical charges are applied to the

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

substrate and the coating. The coating is attracted to the substrate due to the electrochemical potential difference that is created; or

<u>G</u> )	Another coating application method capable of achieving a transfer
	efficiency equal to or better than that achieved by HVLP spraying,
	if such method is approved in writing by the Agency.

i)	Magne	et Wire	Coating	kg/l 0.20 0.20*	lb/gal (1.7) (1.7)*	
j)	Miscellaneous Metal Parts and Products Coating					
	1)	Clear	coating	0.52 0.52*	(4.3) (4.3)*	
	2)	Extreme performance coating				
		A)	Air dried	0.42 0.42*	(3.5) (3.5)*	
		B)	Baked	0.42 0.40*	(3.5) (3.3)*	
	3)	Steel pail and drum interior coating		0.52	(4.3)	
				0.52*	(4.3)*	
	4)	All other coatings				
		A)	Air Dried	0.42 0.40*	(3.5) (3.3)*	
		B)	Baked	0.36 0.34*	(3.0) (2.8)*	
	5)	Metall	ic Coating			
		A)	Air Dried	0.42	(3.5)	

# NOTICE OF PROPOSED AMENDMENTS

		0.42*	(3.5)*
B)	Baked	0.36 0.36	(3.0) (3.0)*

6) For purposes of subsection 219.204(j)(5) of this Section, "metallic coating" means a coating which contains more than 1/4 lb/gal of metal particles, as applied.

k)	Heav Coati	y Off-Highway Vehicle Products ng	kg/l	lb/gal
	1)	Extreme performance prime coat	0.42 0.42*	(3.5) (3.5)*
	2)	Extreme performance topcoat (air dried)	0.42	(3.5)
			0.42*	(3.5)*
	3)	Final repair coat (air dried)	0.42 0.42*	(3.5) (3.5)*

4) All other coatings are subject to the emission limitations for miscellaneous metal parts and products coatings in subsection (j) above.

# 1) Wood Furniture Coating

.

1)	Limi 1998	tations before March 15, :	kg/l	lb/gal
	A)	Clear topcoat	0.67	(5.6)
	B)	Opaque stain	0.56	(4.7)
	C)	Pigmented coat	0.60	(5.0)
	D)	Repair coat	0.67	(5.6)
	E)	Sealer	0.67	(5.6)

# POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

F)	Semi-transparent stain	0.79	(6.6)

G) Wash coat 0.73 (6.1)

(Note: Prior to March 15, 1998, an owner or operator of a wood furniture coating operation subject to this Section shall apply all coatings, with the exception of no more than 37.8 l (10 gal) of coating per day used for touch-up and repair operations, using one or more of the following application systems: airless spray application system, air-assisted airless spray application system, electrostatic spray application system, electrostatic bell or disc spray application system, heated airless spray application system, roller coating, brush or wipe coating application system, dip coating application system or high volume low pressure (HVLP) application system.)

2) On and after March 15, 1998, wood furniture sealers and topcoats must comply with one of the limitations specified in subsections (l)(2)(A) through (E), below:

A)	Торсо	at	kg VOM/kg solids 0.8	lb VOM/lb solids (0.8)
B)	Sealers and topcoats with the following limits:			
	i)	Sealer other than acid-cured alkyd amino vinyl sealer	1.9	(1.9)
	ii)	Topcoat other than acid-cured alkyd amino conversion varnish topcoat	1.8	(1.8)
	iii)	Acid-cured alkyd amino vinyl sealer	2.3	(2.3)
	iv)	Acid-cured alkyd	2.0	(2.0)

#### NOTICE OF PROPOSED AMENDMENTS

amino conversion varnish topcoat

- C) Meet the provisions of Section 219.215 of this Subpart for use of an averaging approach;
- Achieve a reduction in emissions equivalent to the requirements of Section 219.204(1)(2)(A) or (B) of this Subpart, as calculated using Section 219.216 of this Subpart; or
- E) Use a combination of the methods specified in Section 219.204(1)(2)(A) through (D) of this Subpart.
- 3) Other wood furniture coating limitations on and after March 15, 1998:

A)	Opaque stain	kg/l 0.56	lb/gal (4.7)
B)	Non-topcoat pigmented coat	0.60	(5.0)
C)	Repair coat	0.67	(5.6)
D)	Semi-transparent stain	0.79	(6.6)
E)	Wash coat	0.73	(6.1)

- 4) Other wood furniture coating requirements on and after March 15, 1998:
  - A) No source subject to the limitations of subsection (1)(2) or (3) of this Section and utilizing one or more wood furniture coating spray booths shall use strippable spray booth coatings containing more than 0.8 kg VOM/kg solids (0.8 lb VOM/lb solids), as applied.
  - B) Any source subject to the limitations of subsection (l)(2) or (3) of this Section shall comply with the requirements of Section 219.217 of this Subpart.
  - C) Any source subject to the limitations of subsection (1)(2)(A) or (B) of this Section and utilizing one or more continuous coaters, shall

#### NOTICE OF PROPOSED AMENDMENTS

for each continuous coater, use an initial coating which complies with the limitations of subsection (1)(2)(A) or (B) of this Section. The viscosity of the coating in each reservoir shall always be greater than or equal to the viscosity of the initial coating in the reservoir. The owner or operator shall:

- i) Monitor the viscosity of the coating in the reservoir with a viscosity meter or by testing the viscosity of the initial coating and retesting the coating in the reservoir each time solvent is added;
- ii) Collect and record the reservoir viscosity and the amount and weight of VOM per weight of solids of coating and solvent each time coating or solvent is added; and
- iii) Maintain these records at the source for a period of three years.

m)		e Parts C notive/T	-		kg/l	lb/gal		
	1)	Interio	ors					
		A)	Baked					
			i) ii)	Color coat Primer	0.49* 0.46*	(4.1)* (3.8)*		
		B)	Air Dr	ried				
			i) ii)	Color coat Primer	0.38* 0.42*	(3.2)* (3.5)*		
	2)	Exterio flexibl		kible and non-				
		A)	Baked					
			i)	Primer	0.60*	(5.0)*		

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

	ii)	Primer non-flexible	0.54*	(4.5)*
	iii)	Clear coat	0.52*	(4.3)*
	iv)	Color coat	0.55*	(4.6)*
B)	Air D	ried		
	i)	Primer	0.66*	(5.5)*
	ii)	Clear coat	0.54*	(4.5)*
	iii)	Color coat (red & black)	0.67*	(5.6)*
	iv)	Color coat (others)	0.61*	(5.1)*
Specia	alty			
A)		um metalizing pats, texture pats	0.66*	(5.5)*
B)	argent	coatings, reflective coatings, air bag coatings, and soft gs	0.71*	(5.9)*
C)	metali	reducers, vacuum zing topcoats, and e topcoats	0.77*	(6.4)*
D)	primer electro	l coatings, adhesion rs, ink pad coatings, ostatic prep coatings, sist coatings	0.82*	(6.8)*
E)	Head	amp lens coatings	0.89*	(7.4)*

3)

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

n)	Plastic	e Parts (	Coating: Business Machine	kg/l	lb/gal
	1)	Prime	0.14*	(1.2)*	
	2) Color coat (non-texture coat)				(2.3)*
	3)	Color	coat (texture coat)	0.28*	(2.3)*
	4)	freque	omagnetic interference/radio ency interference (EMI/RFI) ing coatings	0.48*	(4.0)*
	5)	Specia	alty Coatings		
		A)	Soft coat	0.52*	(4.3)*
		B)	Plating resist	0.71*	(5.9)*
		C)	Plating sensitizer	0.85*	(7.1)*
(Source: Amended at 34 Ill. Reg, effective)					

# Section 219.205 Daily-Weighted Average Limitations

No owner or operator of a coating line subject to the limitations of Section 219.204 of this Subpart and complying by means of this Section shall operate the subject coating line unless the owner or operator has demonstrated compliance with subsection (a), (b), (c), (d), (e), (f), (g),  $\Theta T$ (h), or (i) of this Section (depending upon the category of coating) through the applicable coating analysis test methods and procedures specified in Section 219.105(a) of this Part and the recordkeeping and reporting requirements specified in Section 219.211(d) of this Subpart:

- a) No owner or operator of a coating line subject to only one of the limitations from among Section 219.204(a)(1), (a)(4), (c), (d), (e), (f), or (i), or, prior to May 1, 2011, (c) of this Subpart shall apply coatings on any such coating line, during any day, whose daily-weighted average VOM content exceeds the emission limitation to which the coatings are subject.
- b) No owner or operator of a miscellaneous metal parts and products coating line subject to the limitations of Section 219.204(j) of this Subpart shall apply coatings to miscellaneous metal parts or products on the subject coating line unless the

# NOTICE OF PROPOSED AMENDMENTS

requirements in subsection (b)(1) or (b)(2) of this Section are met.

- For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(j) of this Subpart during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l (3.5 lbs/gal), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
- 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(j) of this Subpart, during the same day, the owner or operator shall have a site-specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.
- No owner or operator of a can coating line subject to the limitations of Section 219.204(b) of this Subpart shall operate the subject coating line using a coating with a VOM content in excess of the limitations specified in Section 219.204(b) of this Subpart unless all of the following requirements are met:
  - An alternative daily emission limitation for the can coating operation, i.e. for all of the can coating lines at the source, shall be determined according to subsection (c)(2) of this Section. Actual daily emissions shall never exceed the alternative daily emission limitation and shall be calculated by use of the following equation.

$$E_b = \sum_{i=1}^n V_i C_i$$

- $E_d = Actual VOM$  emissions for the day in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of coatings applied in the can coating operation, i.e. all can coating lines at the source;

### NOTICE OF PROPOSED AMENDMENTS

- $V_i$  = Volume of each coating applied for the day in units of l/day (gal/day) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- $C_i$  = The VOM content of each coating as applied in units of kg VOM/1 (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM).
- 2) The alternative daily emission limitation (A<sub>d</sub>) shall be determined for the can coating operation, i.e. for all of the can coating lines at the source, on a daily basis as follows:

$$A_d = \sum_{i=1}^n V_i L_i \frac{\left(D_i - C_i\right)}{\left(D_i - L_i\right)}$$

- A<sub>d</sub> = The VOM emissions allowed for the day in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of surface coatings applied in the can coating operation;
- C<sub>i</sub> = The VOM content of each surface coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- D<sub>i</sub> = The density of VOM in each coating applied. For the purposes of calculating A<sub>d</sub>, the density is 0.882 kg VOM/l VOM (7.36 lbs VOM/gal VOM);
- V<sub>i</sub> = Volume of each surface coating applied for the day in units of 1 (gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- $L_i =$  The VOM emission limitation for each surface coating applied as

# NOTICE OF PROPOSED AMENDMENTS

specified in Section 219.204(b) of this Subpart in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM).

- No owner or operator of a heavy off-highway vehicle products coating line subject to the limitations of Section 219.204(k) of this Subpart shall apply coatings to heavy off-highway vehicle products on the subject coating line unless the requirements of subsection (d)(1) or (d)(2) of this Section are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(k) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l (3.5 lbs/gal), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(k) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.
- e) No owner or operator of a wood furniture coating line subject to the limitations of Section 219.204(l)(1) or (l)(3) of this Subpart shall apply coatings to wood furniture on the subject coating line unless the requirements of subsection (e)(1) or (e)(2) of this Section, in addition to the requirements specified in the note to Section 219.204(l)(1) of this Subpart, are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(l)(1) or (l)(3) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.67 kg/l (5.6 lbs/gal), the dailyweighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(l)(1) or (l)(3) of this

#### NOTICE OF PROPOSED AMENDMENTS

Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.

- f) No owner or operator of a plastic parts coating line subject to the limitations of Section 219.204(m) or (n) of this Subpart shall apply coatings to business machine or automotive/transportation plastic parts on the subject coating line unless the requirements of subsection (f)(1) or (f)(2) of this Section are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(m) or (n) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.42 kg/l (3.5 lbs/gal), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(m) or (n) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.
- g) No owner or operator of a metal furniture coating line subject to the limitations of Section 219.204(g) of this Subpart shall apply coatings on the subject coating line unless the requirements of subsection (g)(1) or (g)(2) of this Section are met:
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(g) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.34 kg/l (2.8 lbs/gal)), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(g) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and USEPA as a SIP revision. To

#### NOTICE OF PROPOSED AMENDMENTS

receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.

- h) No owner or operator of a large appliance coating line subject to the limitations of Section 219.204(h) of this Subpart shall apply coatings on the subject coating line unless the requirements of subsection (h)(1) or (h)(2) of this Section are met.
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(h) of this Subpart, during the same day (e.g., all coatings used on the line are subject to 0.34 kg/l (2.8 lbs/gal)), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used, or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(h) of this Subpart, during the same day, the owner or operator shall have a site specific proposal approved by the Agency and USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy) must be satisfied.
- i) On and after May 1, 2011, no owner or operator of a paper coating line subject to the limitations of Section 219.204(c) of this Subpart shall apply coatings on the subject coating line unless the requirements in subsection (i)(1) or (i)(2) of this Section are met:
  - For each coating line which applies multiple coatings, all of which are subject to the same numerical emission limitation within Section 219.204(c) during the same day (e.g., all coatings used on the line are subject to 0.40 kg/kg solids [0.08 kg/kg coatings]), the daily-weighted average VOM content shall not exceed the coating VOM content limit corresponding to the category of coating used; or
  - 2) For each coating line which applies coatings subject to more than one numerical emission limitation in Section 219.204(c) during the same day, the owner or operator shall have a site-specific proposal approved by the Agency and approved by the USEPA as a SIP revision. To receive approval, the requirements of USEPA's Emissions Trading Policy Statement (and related policy), 51 Fed. Reg. 43814 (December 4, 1986), must be satisfied.

### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

#### Section 219.207 Alternative Emission Limitations

a) Any owner or operator of a coating line subject to Section 219.204 of this Subpart may comply with this Section, rather than with Section 219.204 of this Subpart, if a capture system and control device are operated at all times the coating line is in operation and the owner or operator demonstrates compliance with subsection (c), (d), (e), (f), (g), (h), (i), or (j), or (k) of this Section (depending upon the source category) through the applicable coating analysis and capture system and control device efficiency test methods and procedures specified in Section 219.105 of this Part and the recordkeeping and reporting requirements specified in Section 219.211(e) of this Subpart; and the control device is equipped with the applicable monitoring equipment specified in Section 219.105(d) of this Part and the monitoring equipment is installed, calibrated, operated and maintained according to vendor specifications at all times the control device is in use. A capture system and control device, which does not demonstrate compliance with subsection (c), (d), (e), (f), (g), (h), (i), (j), or (k) of this Section may be used as an alternative to compliance with Section 219.204 of this Subpart only if the alternative is approved by the Agency and approved by the USEPA as a SIP revision.

#### b) Alternative Add-On Control Methodologies

- 1) The coating line is equipped with a capture system and control device that provides 81 percent reduction in the overall emissions of VOM from the coating line and the control device has a 90 percent efficiency, or
- 2) The system used to control VOM from the coating line is demonstrated to have an overall efficiency sufficient to limit VOM emissions to no more than what is allowed under Section 219.204 of this Subpart. Use of any control system other than an afterburner, carbon adsorption, condensation, or absorption scrubber system can be allowed only if approved by the Agency and approved by the USEPA as a SIP revision. The use of transfer efficiency credits can be allowed only if approved by the Agency and approved by the USEPA as a SIP revision. Baseline transfer efficiencies and transfer efficiency test methods must be approved by the Agency and the USEPA. Such overall efficiency is to be determined as follows:

### POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

- A) Obtain the emission limitation from the appropriate subsection in Section 219.204 of this Subpart;
- B) Calculate "S" according to the equation in Section 219.206 of this Subpart;
- C) Calculate the overall efficiency required according to Section 219.105(e) of this Part. For the purposes of calculating this value, according to the equation in Section 219.105(e)(2) of this Part,  $VOM_1$  is equal to the value of "S" as determined above in subsection (b)(2)(B) of this Section.
- c) No owner or operator of a coating line subject to only one of the emission limitations from among Section 219.204(a)(1), (a)(4), (c), (d), (e), (f), or (i), or, prior to May 1, 2011, (c) of this Subpart and equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met. No owner or operator of a coating line subject to Section 219.204(a)(2) or (a)(3) of this Part and equipped with a capture system and control device shall operate the coating line unless the owner or operator demonstrates compliance with such limitation in accordance with the topcoat protocol referenced in Section 219.105(b) of this Part.
- d) No owner or operator of a miscellaneous metal parts and products coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 219.204(j) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/1 [3.5 lbs/gal], and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- e) No owner or operator of a heavy off-highway vehicle products coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 219.204(k) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/1 [3.5 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- f) No owner or operator of a wood furniture coating line which applies one or more coatings during the same day, all of which are subject to the same numerical

### NOTICE OF PROPOSED AMENDMENTS

emission limitation within Section 219.204(l) of this Subpart (e.g., all coatings used on the line are subject to 0.67 kg/l [5.6 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met. If compliance is achieved by meeting the requirements in subsection (b)(2) of this Section (b)(2) of this Section, then the provisions in the note to Section 219.204(l) of this Subpart must also be met.

- g) No owner or operator of a can coating line and equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (g)(1) or (g)(2) of this Section are met.
  - An alternative daily emission limitation for the can coating operation, i.e. for all of the can coating lines at the source, shall be determined according to Section 219.205(c)(2) of this Subpart. Actual daily emissions shall never exceed the alternative daily emission limitation and shall be calculated by use of the following equation:

$$E_d = \sum_{i=1}^{n} V_i C_i (1-F_i)$$

- E<sub>d</sub>= Actual VOM emissions for the day in units of kg/day (lbs/day);
- i= Subscript denoting the specific coating applied;
- n= Total number of surface coatings as applied in the can coating operation;
- V<sub>i</sub>= Volume of each coating as applied for the day in units of l/day (gal/day) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- C<sub>i</sub>= The VOM content of each coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any

#### NOTICE OF PROPOSED AMENDMENTS

compounds which are specifically exempted from the definition of VOM) and

- F<sub>i</sub>= Fraction, by weight, of VOM emissions from the surface coating, reduced or prevented from being emitted to the ambient air. This is the overall efficiency of the capture system and control device.
- 2) The coating line is equipped with a capture system and control device that provide 75 percent reduction in the overall emissions of VOM from the coating line and the control device has a 90 percent efficiency.
- h) No owner or operator of a plastic parts coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 219.204(m) or (n) of this Subpart (e.g., all coatings used on the line are subject to 0.42 kg/l [3.5 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- i) <u>Prior to May 1, 2011, no No</u> owner or operator of a metal furniture coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 219.204(g) of this Subpart (e.g., all coatings used on the line are subject to 0.34 kg/l [2.8 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- j) <u>Prior to May 1, 2011, no No</u> owner or operator of a large appliance coating line which applies one or more coatings during the same day, all of which are subject to the same numerical emission limitation within Section 219.204(h) of this Subpart (e.g., all coatings used on the line are subject to 0.34 kg/l [2.8 lbs/gal]), and which is equipped with a capture system and control device shall operate the subject coating line unless the requirements in subsection (b)(1) or (b)(2) of this Section are met.
- k) On and after May 1, 2011, no owner or operator of a paper coating line, metal furniture coating line, or large appliance coating line which is equipped with a capture system and control device shall operate the subject coating line unless either:

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

- 1) The capture system and control device provide at least 90 percent reduction in the overall emissions of VOM from the coating line; or
- 2) The owner or operator complies with the applicable limitation set forth in Section 219.204 of this Subpart by utilizing a combination of low-VOM coatings and a capture system and control device.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective\_\_\_\_)

# Section 219.210 Compliance Schedule

Every owner or operator of a coating line (of a type included within Section 219.204 of this Subpart) shall comply with the requirements of Section 219.204, 219.205, 219.207 or 219.208 and Section 219.211 or Sections 219.212 and 219.213 of this Subpart in accordance with the appropriate compliance schedule as specified in subsection (a), (b), (c), (d), (e),  $\frac{\text{or}}{(f)}$ , or (g) below:

- a) No owner or operator of a coating line which is exempt from the limitations of Section 219.204 of this Subpart because of the criteria in Section 219.208(a) or
   (b) of this Subpart shall operate said coating line on or after a date consistent with Section 219.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Section 219.211(b) of this Subpart.
- b) No owner or operator of a coating line complying by means of Section 219.204 of this Subpart shall operate said coating line on or after a date consistent with Section 219.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Sections 219.204 and 219.211(c) of this Subpart.
- c) No owner or operator of a coating line complying by means of Section 219.205 of this Subpart shall operate said coating line on or after a date consistent with Section 219.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Sections 219.205 and 219.211(d) of this Subpart.
- d) No owner or operator of a coating line complying by means of Section 219.207 of this Subpart shall operate said coating line on or after a date consistent with Section 219.106 of this Part, unless the owner or operator has complied with, and continues to comply with, Sections 219.207 and 219.211(e) of this Subpart.
- e) No owner or operator of a coating line subject to one or more of the emission

# NOTICE OF PROPOSED AMENDMENTS

limitations contained in Section 219.204 of this Subpart on or after March 15, 1996, choosing to comply by means of Section 219.204, 219.205 or 219.207 of this Subpart, shall operate said coating line on or after March 15, 1996, unless the owner or operator complies with and continues to comply with, respectively, the applicable requirements in Section 219.204, or the alternative control options in Sections 219.205 or 219.207 and the requirements of Section 219.211.

- f) No owner or operator of a coating line subject to one or more of the emission limitations contained in Section 219.204 of this Subpart on or after March 15, 1996, choosing to comply by means of Section 219.212 of this Subpart, shall operate said coating line on or after March 15, 1996, unless the owner or operator complies with and continues to comply with the requirements of Sections 219.212 and 219.213 of this Subpart.
- g) No owner or operator of a coating line subject to the emission limitations in Section 219.204(c)(2), 219.204(g)(2), or 219.204(h)(2) of this Subpart shall operate said coating line on or after a date consistent with Section 219.106(c) of this Part, unless the owner or operator has complied with, and continues to comply with, Section 219.204(c)(2), 219.204(g)(2), or 219.204(h)(2), as applicable, or the alternative control options in Section 219.205 or 219.207, and all applicable requirements in Sections 219.211 and 219.218 of this Subpart.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective\_\_\_\_)

# Section 219.211 Recordkeeping and Reporting

- a) The VOM content of each coating and the efficiency of each capture system and control device shall be determined by the applicable test methods and procedures specified in Section 219.105 of this Part to establish the records required under this Section.
- b) Any owner or operator of a coating line which is exempted from the limitations of Section 219.204 of this Subpart because of Section 219.208(a) or (b) of this Subpart shall comply with the following:
  - For sources exempt from Section 219.208(a) of this Subpart, by a date consistent with Section 219.106 of this Part, the owner or operator of a coating line or group of coating lines referenced in subsection (b) of this Section shall certify to the Agency that the coating line or group of coating lines is exempt under the provisions of Section 219.208(a) of this Subpart.

#### NOTICE OF PROPOSED AMENDMENTS

Such certification shall include:

- A) A declaration that the coating line is exempt from the limitations of Section 219.204 of this Subpart because of Section 219.208(a) of this Subpart; and
- B) Calculations which demonstrate that the combined VOM emissions from the coating line and all other coating lines in the same category never exceed 6.8 kg (15 lbs) per day before the application of capture systems and control devices. The following equation shall be used to calculate total VOM emissions:

$$T_e = \sum_{j=1}^m \sum_{i=1}^n \left( A_i B_i \right)_j$$

- T<sub>e</sub> = Total VOM emissions from coating lines each day before the application of capture systems and control devices in units of kg/day (lbs/day);
- m = Number of coating lines at the source that otherwise would be subject to the same subsection of Section 219.104 of this Part (because they belong to the same category, e.g., can coating);
- j = Subscript denoting an individual coating line;
- n = Number of different coatings as applied each day on each coating line;
- i = Subscript denoting an individual coating;
- A<sub>i</sub> = Weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line in units of kg VOM/l (lbs VOM/gal);
- $B_i$  = Volume of each coating (minus water and any compounds which are specifically exempted from the definition of

#### NOTICE OF PROPOSED AMENDMENTS

VOM) as applied each day on each coating line in units of l/day (gal/day). The instrument or method by which the owner or operator accurately measured or calculated the volume of each coating as applied on each coating line each day shall be described in the certification to the Agency.

- 2) For sources exempt under Section 219.208(b) of this Subpart, by March 15, 1998, or upon initial start-up, the owner or operator of a coating line or a group of coating lines referenced in subsection (b) of this Section shall certify to the Agency that the source is exempt under the provisions of Section 219.208(b) of this Subpart. Such certification shall include:
  - A) A declaration that the source is exempt from the limitations of Section 219.204(l) of this Subpart because of Section 219.208(b) of this Subpart; and
  - B) Calculations which demonstrate that the source meets the criteria of exemption because of Section 219.208(b) of this Subpart.
- 3) For sources exempt under Section 219.208(a) of this Subpart, on and after a date consistent with Section 219.106 of this Part, the owner or operator of a coating line or group of lines referenced in this subsection shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line; and
  - B) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
- 4) For sources exempt under Section 219.208(b) of this Subpart, on and after March 15, 1998, the owner or operator of a coating line or group of coating lines referenced in this subsection (b) shall collect and record all of the following information for each coating line and maintain the information at the source for a period of three years:

# NOTICE OF PROPOSED AMENDMENTS

- A) The name and identification number of each coating as applied on each coating line; and
- B) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied on each coating line on a monthly basis.
- 5) On and after a date consistent with Section 219.106 of this Part, the owner or operator of a coating line or group of coating lines exempted from the limitations of Section 219.204 of this Subpart because of Section 219.208(a) of this Subpart shall notify the Agency of any record showing that total VOM emissions from the coating line or group of coating lines exceed 6.8 kg (15 lbs) in any day before the application of capture systems and control devices by sending a copy of such record to the Agency within 30 days after the exceedance occurs.
- 6) On and after March 15, 1998, any owner or operator of a source exempt from the limitations of Section 219.204(l) of this Subpart because of Section 219.208(b) of this Subpart shall notify the Agency if the source's VOM emissions exceed the limitations of Section 219.208(b) of this Subpart by sending a copy of calculations showing such an exceedance within 30 days after the change occurs.
- c) Any owner or operator of a coating line subject to the limitations of Section 219.204 of this Subpart other than Section 219.204(a)(2) and (a)(3) of this Subpart and complying by means of Section 219.204 of this Subpart shall comply with the following:
  - By a date consistent with Section 219.106 of this Part, or upon initial start-up of a new coating line, or upon changing the method of compliance from an existing subject coating line from Section 219.205, Section 219.207, Section 219.215, or Section 219.216 of this Subpart to Section 219.204 of this Subpart; the owner or operator of a subject coating line shall certify to the Agency that the coating line will be in compliance with Section 219.204 of this Subpart on and after a date consistent with Section 219.106 of this Part, or on and after the initial start-up date. Such certification shall include:
    - A) The name and identification number of each coating as applied on

#### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

each coating line;

- B) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line;-and
- C) On and after March 15, 1998, for coating lines subject to the limitations of Section 219.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line;-
- <u>D</u> For coating lines subject to the limitations of Section 219.204(c)(2)
   of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line; and
- E) For coating lines subject to the limitations of Section 219.204(g)(2) or 219.204(h)(2) of this Subpart, the application method(s) used to apply coatings on the subject coating line and the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line.
- 2) On and after a date consistent with Section 219.106 of this Part, or on and after the initial startup date, the owner or operator of a subject coating line shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line;
  - B) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line;
  - C) On and after March 15, 1998, for coating lines subject to the limitations of Section 219.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line and certified product data sheets for

# NOTICE OF PROPOSED AMENDMENTS

each coating; and

- D) On and after March 15, 1998, for wood furniture coating spray booths subject to the limitation of Section 219.204(l)(4)(A) of this Subpart, the weight of VOM per weight of solids in each strippable spray booth coating as applied each day on each spray booth and certified product data sheets for each coating:-
- E) For coating lines subject to the limitations of Section 219.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line, and certified product data sheets for each coating; and
- F) For coating lines subject to the limitations of Section 219.204(g)(2) or 219.204(h)(2) of this Subpart, the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line, and certified product data sheets for each coating.
- 3) On and after a date consistent with Section 219.106 of this Part, the owner or operator of a subject coating line shall notify the Agency in the following instances:
  - A) Any record showing violation of Section 219.204 of this Subpart shall be reported by sending a copy of such record to the Agency within 30 days following the occurrence of the violation.
  - B) At least 30 calendar days before changing the method of compliance from Section 219.204 to Section 219.205 or Section 219.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (d)(1) or (e)(1) below, respectively. Upon changing the method of compliance from Section 219.204 to Section 219.205 or Section 219.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (d) or (e) of this Section, respectively.
- d) Any owner or operator of a coating line subject to the limitations of Section 219.204 of this Subpart and complying by means of Section 219.205 of this Subpart shall comply with the following:

### NOTICE OF PROPOSED AMENDMENTS

- By a date consistent with Section 219.106 of this Part, or upon initial start-up of a new coating line, or upon changing the method of compliance for an existing subject coating line from Section 219.204 or Section 219.207 to Section 219.205 of this Subpart; the owner or operator of the subject coating line shall certify to the Agency that the coating line will be in compliance with Section 219.205 on and after a date consistent with Section 219.106 of this Part, or on and after the initial start-up date. Such certification shall include:
  - A) The name and identification number of each coating line which will comply by means of Section 219.205 of this Subpart.
  - B) The name and identification number of each coating as applied on each coating line.
  - C) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
  - D) On and after March 15, 1998, for coating lines subject to the limitations of Section 219.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line.
  - <u>E</u>) For coating lines subject to the limitations of Section 219.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line.
  - F) For coating lines subject to the limitations of Section 219.204(g)(2) or 219.204(h)(2) of this Subpart, the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line.
  - $\underline{GE}$ ) The instrument or method by which the owner or operator will accurately measure or calculate the volume of each coating as applied each day on each coating line.

#### NOTICE OF PROPOSED AMENDMENTS

- <u>H</u>F) The method by which the owner or operator will create and maintain records each day as required in subsection (d)(2) of this Section.
- $\underline{IG}$  An example of the format in which the records required in subsection (d)(2) of this Section will be kept.
- 2) On and after a date consistent with Section 219.106 of this Part, or on and after the initial start-up date, the owner or operator of a subject coating line shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - A) The name and identification number of each coating as applied on each coating line.
  - B) The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
  - C) On and after March 15, 1998, for coating lines subject to the limitations of Section 219.204(l)(2)(A) or (B) of this Subpart, the weight of VOM per weight of solids in each coating as applied each day on each coating line.
  - D) For coating lines subject to the limitations of Section 219.204(c)(2) of this Subpart, the weight of VOM per weight of solids (or the weight of VOM per weight of coatings, as applicable) in each coating as applied each day on each coating line.
  - E) For coating lines subject to the limitations of Section 219.204(g)(2) or 219.204(h)(2) of this Subpart, the weight of VOM per volume of each coating (or the weight of VOM per volume of solids in each coating, as applicable) as applied each day on each coating line.
  - $\underline{FD}$  The daily-weighted average VOM content of all coatings as applied on each coating line as defined in Section 219.104 of this

# NOTICE OF PROPOSED AMENDMENTS

Part.

- 3) On and after a date consistent with Section 219.106 of this Part, the owner or operator of a subject coating line shall notify the Agency in the following instances:
  - A) Any record showing violation of Section 219.205 of this Subpart shall be reported by sending a copy of such record to the Agency within 30 days following the occurrence of the violation.
  - B) At least 30 calendar days before changing the method of compliance with this Subpart from Section 219.205 to Section 219.204 or Section 219.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (c)(1) or (e)(1) of this Section, respectively. Upon changing the method of compliance with this Subpart from Section 219.205 to Section 219.204 or Section 219.207 of this Subpart, the owner or operator shall comply with all requirements of subsection (c) or (e) of this Section, respectively.
- e) Any owner or operator of a coating line subject to the limitations of Section 219.207 and complying by means of Section 219.207(c), (d), (e), (f), (g), or (h), or (k) of this Subpart shall comply with the following:
  - 1) By a date consistent with Section 219.106 of this Part, or upon initial start-up of a new coating line, or upon changing the method of compliance for an existing coating line from Section 219.204 or Section 219.205 to Section 219.207 of this Subpart, the owner or operator of the subject coating line shall perform all tests and submit to the Agency the results of all tests and calculations necessary to demonstrate that the subject coating line will be in compliance with Section 219.207 of this Subpart on and after a date consistent with Section 219.106 of this Part, or on and after the initial start-up date.
  - 2) On and after a date consistent with Section 219.106 of this Part, or on and after the initial start-up date, the owner or operator of a subject coating line shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:

#### POLLUTION CONTROL BOARD

#### NOTICE OF PROPOSED AMENDMENTS

- A) The weight of VOM per volume of coating solids as applied each day on each coating line, if complying pursuant to Section 219.207(b)(2) of this Subpart.
- B) Control device monitoring data.
- C) A log of operating time for the capture system, control device, monitoring equipment and the associated coating line.
- D) A maintenance log for the capture system, control device and monitoring equipment detailing all routine and non-routine maintenance performed including dates and duration of any outages.
- 3) On and after a date consistent with Section 219.106 of this Part, the owner or operator of a subject coating line shall notify the Agency in the following instances:
  - A) Any record showing violation of Section 219.207 of this Subpart shall be reported by sending a copy of such record to the Agency within 30 days following the occurrence of the violation.
  - B) At least 30 calendar days before changing the method of compliance with this Subpart from Section 219.207 to Section 219.204 or Section 219.205 of this Subpart, the owner or operator shall comply with all requirements of subsection (c)(1) or (d)(1) of this Section, respectively. Upon changing the method of compliance with this Subpart Part from Section 219.207 to Section 219.204 or Section 219.205 of this Subpart, the owner or operator shall comply with all requirements of subsection (c) or (d) of this Section, respectively.
- f) Any owner or operator of a primer surfacer operation or topcoat operation subject to the limitations of Section 219.204(a)(2) or (a)(3) of this Subpart shall comply with the following:
  - 1) By a date consistent with Section 219.106 of this Part, or upon initial startup of a new coating operation, the owner or operator of a subject coating operation shall certify to the Agency that the operation will be in compliance with Section 219.204 of this Subpart on and after a date

#### NOTICE OF PROPOSED AMENDMENTS

consistent with Section 219.106 of this Part, or on and after the initial startup date. Such certification shall include:

- A) The name and identification number of each coating operation which will comply by means of Section 219.204(a)(2) and (a)(3) of this Subpart and the name and identification number of each coating line in each coating operation.
- B) The name and identification number of each coating as applied on each coating line in the coating operation.
- C) The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
- D) The transfer efficiency and control efficiency measured for each coating line.
- E) Test reports, including raw data and calculations documenting the testing performed to measure transfer efficiency and control efficiency.
- F) The instrument or method by which the owner or operator will accurately measure or calculate the volume of each coating as applied each day on each coating line.
- G) The method by which the owner or operator will create and maintain records each day as required in subsection (f)(2) below.
- H) An example format for presenting the records required in subsection (f)(2) below.
- 2) On and after a date consistent with Section 219.106 of this Part, or on and after the initial start-up date, the owner or operator of a subject coating operation shall collect and record all of the following information each day for each topcoat or primer surfacer coating operation and maintain the information at the source for a period of three years:
  - A) All information necessary to calculate the daily-weighted average VOM emissions from the coating operations in kg (lbs) per 1 (gal)

#### NOTICE OF PROPOSED AMENDMENTS

of coating solids deposited in accordance with the proposal submitted, and approved pursuant to Section 219.204(a)(2) or (a)(3) of this Subpart including:

- i) The name and identification number of each coating as applied on each coating operation.
- The weight of VOM per volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating operation.
- B) If a control device(s) is used to control VOM emissions, control device monitoring data; a log of operating time for the capture system, control device, monitoring equipment and the associated coating operation; and a maintenance log for the capture system, control device and monitoring equipment, detailing all routine and non-routine maintenance performed including dates and duration of any outages.
- 3) On and after a date consistent with Section 219.106 of this Part or on and after the initial startup date, the owner or operator of a subject coating operation shall determine and record the daily VOM emissions in kg (lbs) per 1 (gal) of coating solids deposited in accordance with the proposal submitted and approved pursuant to Section 219.204(a)(2) or (a)(3) of this Subpart within 10 days from the end of the month and maintain this information at the source for a period of three years.
- 4) On and after a date consistent with Section 219.106 of this Part, the owner or operator of a subject coating operation shall notify the Agency in the following instances:
  - A) Any record showing a violation of Section 219.204(a)(2) or (a)(3) of this Subpart shall be reported by sending a copy of such record to the Agency within 15 days from the end of the month in which the violation occurred.
  - B) The owner or operator shall notify the Agency of any change to the operation at least 30 days before the change is affected. The Agency shall determine whether or not compliance testing is

# POLLUTION CONTROL BOARD

# NOTICE OF PROPOSED AMENDMENTS

required. If the Agency determines that compliance testing is required, then the owner or operator shall submit a testing proposal to the Agency within 30 days and test within 30 days of the approval of the proposal by the Agency and USEPA.

- g) On and after a date consistent with Section 219.106(c) of this Part, or on and after the initial start-up date, whichever is later, the owner or operator of a coating line subject to the requirements of Section 219.218 of this Subpart shall comply with the following:
  - 1) By May 1, 2011, or upon initial start-up, whichever is later, submit a certification to the Agency that includes a description of the practices and procedures that the source will follow to ensure compliance with the applicable requirements in Section 219.218 of this Subpart;
  - 2) Notify the Agency of any violation of Section 219.218 of this Subpart by providing a description of the violation and copies of records documenting such violation to the Agency within 30 days following the occurrence of the violation; and
  - 3) Maintain at the source all records required by this subsection (g) for a minimum of three years from the date the document was created and make such records available to the Agency upon request.

(Source: Amended at 34 Ill. Reg. \_\_\_\_\_, effective \_\_\_\_\_)

# Section 219.212 Cross-Line Averaging to Establish Compliance for Coating Lines

a) On and after March 15, 1996, any owner or operator of a coating line subject to the limitations set forth in Section 219.204 of this Subpart, <u>except coating lines</u> <u>subject to the limitations in Section 219.204(c)(2), (g)(2), or (h)(2) of this</u> <u>Subpart, and with coating lines in operation prior to January 1, 1991 ("pre-existing coating lines")</u>, may, for pre-existing coating lines only, elect to comply with the requirements of this Section, rather than complying with the applicable emission limitations set forth in Section 219.204, if an operational change of the type described below has been made after January 1, 1991, to one or more pre-existing coating lines at the source. An operational change occurs when a pre-existing coating line is replaced with a line using lower VOM coating for the same purpose as the replaced line ("replacement line"). A source electing to rely on this Section to demonstrate compliance with the requirements of this Subpart compliance with the requirements of this Subpart ("replacement line").

# NOTICE OF PROPOSED AMENDMENTS

shall operate pursuant to federally enforceable permit conditions approved by the Agency and USEPA.

- b) An owner or operator of pre-existing coating lines subject to a VOM content limitation in Section 219.204 of this Subpart and electing to rely on this Section to demonstrate compliance with this Subpart must establish, by use of the equations in subsection (d) of this Section, that the calculated actual daily VOM emissions from all participating coating lines, as defined below, are less than the calculated daily allowable VOM emissions from the same group of coating lines. For any pre-existing coating line to be aggregated for the purposes of Section 219.212, 219.213, or 219.214 of this Subpart ("participating coating lines"), the source must establish that:
  - 1) All coatings applied on the participating coating line shall, at all times, have a VOM content less than or equal to the applicable VOM content limitation for such coating listed in Appendix H of this Part; and
  - 2) On the date the source elects to rely on this Section to demonstrate compliance with this Subpart, all coatings applied on the participating coating line are not already in compliance with the VOM content limitation for such coating effective on or after March 15, 1996; or the participating coating line is a replacement line, as defined in subsection (a) of this Section with an operational change occurring on or after January 1, 1991.
- c) Notwithstanding subsection (a) of this Section, any owner or operator of a coating line subject to the limitations set forth in Section 219.204 of this Subpart and electing to rely on this Section to demonstrate compliance with this Subpart, may also include as a participating coating line, until December 31, 1999, only, any replacement line that satisfies all of the following conditions:
  - 1) The replacement line is operated as a powder coating line;
  - 2) The replacement line was added after July 1, 1988; and
  - 3) The owner or operator also includes as a participating coating line one or more coating lines that satisfy the criteria of a replacement line, as described in subsection (a) of this Section.

#### NOTICE OF PROPOSED AMENDMENTS

- d) To demonstrate compliance with this Section, a source shall establish the following:
  - 1) An alternative daily emission limitation shall be determined for all participating coating lines at the source according to subsection (d)(2) of this Section. All participating coating lines shall be factored in each day to demonstrate compliance. Provided compliance is established pursuant to the requirements in this subsection, nothing in this Section requires daily operation of each participating line. Actual daily emissions from all participating coating lines  $(E_d)$  shall never exceed the alternative daily emission limitation  $(A_d)$  and shall be calculated by use of the following equation:

$$E_{d} = \sum_{i=1}^{\Pi} V_{i} C_{i}$$

- E<sub>d</sub> = Actual daily VOM emissions from participating coating lines in units of kg/day (lbs/day);
- i = Subscript denoting a specific coating applied;
- n = Total number of coatings applied by all participating coating lines at the source;
- V<sub>i</sub> = Volume of each coating applied for the day in units of l/day (gal/day) of coating (minus water and any compounds which are specifically exempted from the definition of VOM); and
- C<sub>i</sub> = The VOM content of each coating as applied in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM).
- 2) The alternative daily emission limitation (A<sub>d</sub>) shall be determined for all participating coating lines at the source on a daily basis as follows:

#### NOTICE OF PROPOSED AMENDMENTS

 $A_d = A_l + A_p$ 

where A<sub>1</sub> and A<sub>p</sub> are defined in subsections (2)(A) and (2)(B) of this subsection.

A) The portion of the alternative daily emissions limitation for coating operations at a source using non-powder coating (A<sub>1</sub>) shall be determined for all such participating non-powder coating lines on a daily basis as follows:

$$A_i = \sum_{i=1}^{n} V_i L_i (\underline{D_i - C_i})$$

- A<sub>i</sub> = The VOM emissions allowed for the day in units of kg/day (lbs/day);
- I = Subscript denoting a specific coating applied;
- n = Total number of coatings applied in the participating coating lines;
- C<sub>i</sub> = The VOM content of each coating as applied in units of kg VOM/l(lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM);
- $D_i$  = The density of VOM in each coating applied. For the purposes of calculating A<sub>1</sub>, the density is 0.882 kg VOM/1 VOM (7.36 lbs VOM/gal VOM);
- V<sub>i</sub> = Volume of each coating applied for the day in units of l (gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM); and
- L<sub>i</sub> = The VOM emission limitation for each coating applied, as specified in Section 219.204 of this Subpart, in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any

#### NOTICE OF PROPOSED AMENDMENTS

compounds which are specifically exempted from the definition of VOM).

B) The portion of the alternative daily emission limitation for coating operations at a source using powdered coating (A<sub>p</sub>) shall be determined for all such participating powder coating lines at the source on a daily basis as follows:

$$A_{p} = \sum_{h=1}^{m} \sum_{j=1}^{n} \frac{V_{j} L_{j} D_{j} K_{h}}{(D_{j} - L_{j})}$$

- A<sub>p</sub> = The VOM emissions allowed for the day in units of kg/day (lbs/day);
- h = Subscript denoting a specific powder coating line;
- j = Subscript denoting a specific powder coating applied;
- m = Total number of participating powder coating lines;
- n = Total number of powder coatings applied in the participating coating lines;
- D<sub>j</sub> = The assumed density of VOM in liquid coating, 0.882 kg VOM/l VOM (7.36 lbs VOM/gal VOM);
- $V_j$  = Volume of each powder coating consumed for the day in units of 1 (gal) of coating;
- L<sub>j</sub> = The VOM emission limitation for each coating applied, as specified in Section 219.204 of this Subpart, in units of kg VOM/l (lbs VOM/gal) of coating (minus water and any compounds which are specifically exempted from the definition of VOM); and
- K = A constant for each individual coating line representing the ratio of the volume of coating solids consumed on the liquid coating system which has been replaced to the

### POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

volume of powder coating consumed on the replacement line to accomplish the same coating job. This value shall be determined by the source based on tests conducted and records maintained pursuant to the requirements of Section 219.213 of this Subpart demonstrating the amount of coating solids consumed as both liquid and powder. Tests methods and recordkeeping requirements shall be approved by the Agency and USEPA and contained in the source's operating permit as federally enforceable permit conditions, subject to the following restrictions:

- i) K cannot exceed 0.9 for non-recycled powder coating systems; or
- ii) K cannot exceed 2.0 for recycled powder coating systems.

(Source: Amended at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)

# Section 219.218 Work Practice Standards for Paper Coatings, Metal Furniture Coatings, and Large Appliance Coatings

- a) On and after May 1, 2011, every owner or operator of a source subject to the requirements of Section 219.204(c) of this Subpart shall:
  - 1) Store all VOM-containing cleaning materials in closed containers;
  - 2) Ensure that mixing and storage containers used for VOM-containing materials are kept closed at all times except when depositing or removing such materials:
  - 3) <u>Minimize spills of VOM-containing cleaning materials;</u>
  - 4) <u>Convey VOM-containing cleaning materials from one location to another</u> in closed containers or pipes; and
  - 5) Minimize VOM emissions from the cleaning of storage, mixing, and conveying equipment.
- b) On and after May 1, 2011, every owner or operator of a source subject to the requirements of Section 219.204(g) or 219.204(h) of this Subpart shall:

# POLLUTION CONTROL BOARD

### NOTICE OF PROPOSED AMENDMENTS

- 1) Store all VOM-containing coatings, thinners, coating-related waste materials, cleaning materials, and used shop towels in closed containers;
- 2) Ensure that mixing and storage containers used for VOM-containing coatings, thinners, coating-related waste materials, and cleaning materials are kept closed at all times except when depositing or removing such materials;
- 3) Minimize spills of VOM-containing coatings, thinners, coating-related waste materials, and cleaning materials, and clean up spills immediately;
- 4) <u>Convey VOM-containing coatings, thinners, coating-related waste</u> <u>materials, and cleaning materials from one location to another in closed</u> <u>containers or pipes; and</u>
- 5) Minimize VOM emissions from the cleaning of storage, mixing, and conveying equipment.

(Source: Added at 34 Ill. Reg. \_\_\_\_, effective \_\_\_\_)