

OFFICE OF THE SECRETARY OF STATE

JESSE WHITE • Secretary of State

May 11, 2012

CLERK'S OFFICE

MAY 1 4 2012

STATE OF ILLINOIS Pollution Control Board

POLLUTION CONTROL BOARD JOHN THERRIAULT ASSISTANT CLERK 100 W RANDOLPH ST, STE 11-500 CHICAGO, IL 60601

Dear JOHN THERRIAULT ASSISTANT CLERK

Your rules Listed below met our codification standards and have been published in Volume 36, Issue 20 of the Illinois Register, dated 5/18/2012.

ADOPTED RULES Standards and Limitations for Organic Material Emissions for Area Sources 35 Ill. Adm. Code 223 Point of Contact: Nancy Miller PROPOSED RULES Tired Approach to Corrective Action Objectives 35 Ill. Adm. Code 742 Point of Contact: Nancy Miller If you have any questions, you may contact the Administrative Code Division at (217) 782 - 7017.

Index Department - Administrative Code Division - 111 East Monroe Springfield, IL 62756

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 1) Heading of the Part: Tiered Approach to Corrective Action Objectives
- 2) Code Citation: 35 Ill. Adm. Code 742

3)

Section Numbers: **Proposed Action:** 742.105 Amend 742.110 Amend 742.115 Amend 742.200 Amend 742.210 Amend 742.220 Amend 742.222 New 742.225 Amend 742.227 New 742.305 Amend 742.310 Amend 742.312 New 742.405 Amend 742.500 Amend 742.505 Amend 742.510 Amend 742.515 New 742.600 Amend 742.605 Amend 742.610 Amend 742.700 Amend 742.705 Amend 742.710 Amend 742.712 New 742.715 Amend 742.717 New 742.805 Amend 742.810 Amend 742.812 New 742.900 Amend 742.920 Amend 742.925 Amend 742.935 New 742.1000 Amend



in grad

Pollution Control during

RECEIVED MAY 4 2012 SOS-CODE DIV.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

543 1010	4 1
742.1010	Amend
742.1015	Amend
742.1105	Amend
742.1200	New
742.1205	New
742.1210	New
742.Appendix A	
Table A	Amend
Table E	Amend
Table F	Amend
Table J	New
Table K	New
742.Appendix B	
Table G	New
Table H	New
Table I	New
742.Appendix C	
Table A	Amend
Table B	Amend
Table E	Amend
Table F	Amend
Table L	New
Table M	New
742.Appendix F	Amend

- 4) <u>Statutory Authority</u>: Authorized by Section 27 of the Environmental Protection Act [415 ILCS 5/27].
- 5) <u>A Complete Description of the Subjects and Issues Involved</u>: On April 19, 2012, the Illinois Pollution Control Board (Board) adopted an opinion and order proposing first-notice amendments to the Tiered Approach to Corrective Action Objectives (TACO) rules (35 Ill. Adm. Code 742). The rulemaking is docketed Tiered Approach to Corrective Action Objectives (TACO) (Indoor Inhalation): Amendments to 35 Ill. Adm. Code 742, R11-9. Since 1997, the TACO rules have provided procedures for developing remediation objectives based upon risks posed to human health by environmental conditions at a variety of sites. TACO is used at sites being remediated under any one of several regulatory programs: Leaking Underground Storage Tank (UST) Program; Site Remediation Program (SRP); and Resource Conservation and Recovery Act (RCRA) Part B Permits and Closure Plans.

NOTICE OF PROPOSED AMENDMENTS

The first-notice amendments include the addition of a new exposure route under TACO: the indoor inhalation exposure route. To protect building occupants, this exposure route addresses the potential for vapors to migrate into buildings from underlying volatile chemicals in soil or groundwater, a process commonly known as "vapor intrusion" or "VI." The Board also proposed adding 13 chemicals to the TACO tables based upon the Board's pending rulemaking on groundwater quality standards, Proposed Amendments to Groundwater Quality Standards (35 Ill. Adm. Code 620), R08-18. Further, the first-notice amendments to TACO update physical and chemical parameters and revise toxicity values in accordance with the new United States Environmental Protection Agency hierarchy for selecting human health toxicity values.

The R11-9 rulemaking was initiated when the Illinois Environmental Protection Agency (IEPA) filed a proposal with the Board on November 9, 2010, under Section 27 of the Environmental Protection Act [415 ILCS 5/27]. After conducting two public hearings and receiving public comments, the Board has adopted, for first notice, the amendments proposed or agreed to by IEPA, with minor clarifying changes. In addition, the Board proposed requiring that IEPA be notified if an indoor inhalation building control technology at a school is rendered inoperable. The Board also proposed that the entire set of amendments would become effective on a date certain 60 days after their final adoption. For further information, please refer to the Board's first-notice opinion and order of April 19, 2012, which is available through the Clerk's Office On-Line (COOL) on the Board's Web site at www.ipcb.state.il.us.

6) <u>Published studies or reports and sources of underlying data used to compose this</u> <u>rulemaking</u>:

Abreu, L.D.V., Ettinger, R., McAlary, T. 2009. "Simulated Soil Vapor Intrusion Attenuation Factors Including Bidegradation for Petroleum Hydrocarbons." *Ground Water Monitoring and Remediation* 29(1):105-117.

Agency for Toxic Substances and Disease Registry. (Jan. 2004). Health Consultation: Active Soil Gas Data Review, Chillum Perc site, Chillum, Prince Georges County, Maryland. <u>http://www.atsdr.cdc.gov/hac/PHA/chillumperc/cps_p1.html</u>

Agency for Toxic Substances and Disease Registry. (November 2007). Minimal Risk Levels (MRLs).

Agency for Toxic Substances and Disease Registry. (December 2006). Minimal Risk Levels (MRLs).

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

American Petroleum Institute (Nov. 2005). A Practical Strategy for Assessing the Subsurface Vapor-to-Indoor-Air Migration Pathway at Petroleum Hydrocarbon Sites. API Publication 4741. <u>http://www.itrcweb.org/Documents/VI-1.pdf</u>

Bibler, G. & Mason, E. (Nov. 2005). Scrutiny of Indoor Air Pathway Affects Standards for Investigation and Cleanup. Daily Environment Report, 11-10-05. http://net2.gph.com/~/media/64E898D7D8F042379F78727C1EC07A43.ashx

California EPA, Department of Toxic Substances Control (Feb. 2005). Interim Final Guidance for the Evaluation and Mitigation of Subsurface Vapor Intrusion to Indoor Air. <u>http://www.dtsc.ca.gov/assessingrisk/upload/herd_pol_eval_subsurface_vapor_intrusion_interim_final.pdf</u>

California EPA, Department of Toxic Substances Control (Jan. 2003). Advisory on Active Soil Gas Investigations. <u>http://www.dtsc.ca.gov/lawsregspolicies/policies/SiteCleanup/upload/SMBR_ADV_activ</u>esoilgasinvst.pdf

California EPA, Department of Toxic Substances Control. 2010. Advisory-Active Soil Gas Investigation. <u>http://www.dtsc.ca.gov/SiteCleanup/upload/SAG_Review_Drft.pdf</u>

California EPA. Office of Environmental Health Hazard Assessment. Toxicity Criteria Database. <u>http://www.oehha.ca.gov/risk/ChemicalDB/index.asp</u>

Colorado Department of Public Health and Environment (Sept. 2004). Draft Indoor Air Guidance. <u>http://www.cdphe.state.co.us/HM/indoorair.pdf</u>

Davis, G.B., Patterson, B.M., Trefry, M.G. 2009. "Evidence for Instantaneous Oxygen-Limited Biodegradation of Petroleum Hydrocarbon Vapors in the Subsurface." *Ground Water Monitoring and Remediation* 29(1):126-137.

Davis, R.V. 2009. "Update on Recent Studies and Proposed Screening Criteria for the Vapor-Intrusion Pathway." *LUSTLine Bulletin* 61:11-14.

Dawson, H.E., McAlary, T. 2009. "A Compilation of Statistics for VOCs from Post 1990 Indoor Air Concentration Studies in North American Residences Unaffected by Subsurface Vapor Intrusion." *Ground Water Monitoring and Remediation* 29(1):60-69.

Department of the Army, U.S. Army Corps of Engineers (Sept. 1993). Indoor Radon Prevention and Mitigation. Technical Letter No. 1110-3-438.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

http://www.wbdg.org/ccb/DOD/UFC/ufc 3 490 04a.pdf

Fetter, C.W. (1994). Applied Hydrogeology, 3rd Edition. Available at the Illinois EPA library, Call Number: 551.48 FETT 1994

Fitzpatrick, N.A., Fitzgerald, J.J. 2002. "An Evaluation of Vapor Intrusion Into Buildings Through a Study of Field Data." *Soil and Sediment Contamination* 11(4):603-623.

Folkes, D. (Dec. 2002). Design, Effectiveness, and Reliability of Sub-Slab Depressurization Systems for Mitigation of Chlorinated Solvent Vapor Intrusion. EnviroGroup Limited. Presented at the U.S. EPA Seminar on Indoor Air Vapor Intrusion, San Francisco. http://www.envirogroup.com/publications/folkes epa seminar.pdf

Folkes, D., Wertz, W., Kurtz, J., Kuehster, T. 2009. "Observed Spatial and Temporal Distributions of CVOCs at Colorado and New York Vapor Intrusion Sites." *Ground Water Monitoring and Remediation* 29(1):70-80.

Geoprobe Systems. 2006. Direct Push Installation of Devices for Active Soil Gas Sampling and Monitoring. Technical Bulletin No. MK3098.

Grimsrud, D.T., Sherman, M.H., Sonderegger, R.C. 1982. "Calculating Infiltration: Implications for a Construction Quality Standard." *Thermal Performance of the Exterior Envelopes of Buildings II; Proceedings of the ASHRAE/DOE Conference, Dec. 6-9* SP38:422-452.

Hartman, B. 2002. How to Collect Reliable Soil Gas Data for Risk-Based Applications, Part 1: Active Soil-Gas Method. *LUSTLine Bulletin* 42:17-22.

Hartman, B. 2004. How to Collect Reliable Soil Gas Data for Risk-Based Applications, Part 3: Answers to Frequently Asked Questions. *LUSTLine Bulletin* 48:12-17.

Hartman, B. (Sept. 2006). How to Collect Reliable Soil-Gas Data for Risk-Based Applications, Specifically Vapor Intrusion: Part Four, Updates on Soil-Gas Collection and Analytical Procedures. *LUSTLine Bulletin* #53. http://www.handpmg.com/lustline53-soil-gas-part-4.htm

Heath, Ralph C. (1983). <u>Basic Ground-Water Hydrology</u>. United States Geological Survey Water-Supply Paper 2220. <u>http://pubs.er.usgs.gov/djvu/WSP/wsp_2220.pdf</u>

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Hers, I., Zapf-Gilje, R. 1998. "Canadian Consortium Research Project-Filed Validation of Soil Gas Transport to Indoor Air Pathway." In *Proceedings of 1998 Petrol. Hydro.and Chem. In Ground Water;* API/NGWA, Houston, TX, November 11-13; pp 251-266.

Hers, I., Atwater, J., Li, L., Zapf-Gilje, R. 2000. "Evolution of Vadose Zone Biodegradation of BTX Vapors." *Journal of Contaminant Hydrology* 46(2000): 233-264.

Hers, I., Zapf-Gilje, R., Li, L., Atwater, J. 2001. "The Use of Indoor Air Measurements To Evaluate Intrusion of Subsurface VOC Vapors into Buildings." *Journal of the Air & Waste Management Association* 51:1318-1331.

Hers, I., Evans, D., Zapf-Gilje, R., Li, L. 2002. "Comparison, Validation and Use of Models for Predicting Indoor Air Quality from Soil and Groundwater Contamination." *Soil & Sediment Contamination*. 11(4):491-527.

Hers, I., Zapf-Gilje, R., Johnson, P.C., Li, L. 2003. "Evaluation of the Johnson and Ettinger Model for Prediction of Indoor Air Quality." *Ground Water Monitoring and Remediation* 23(1):62-76.

Howard, Philip H., W.F. Jarvis, W.M. Meylan, and E.M. Michalenko. (1991). Handbook of Environmental Degradation Rates. Lewis Publishers, Inc. Chelsea, Michigan. Available at the Illinois EPA Library, Call Number: 363.7384 HOWA2

International Building Code (2006). Available at the Illinois EPA Library upon request.

Johnson, P.C. 2005. "Identification of Application-Specific Critical Inputs for the 1991 Johnson and Ettinger Vapor Intrusion Algorithm." *Ground Water Monitoring and Remediation* 25(1):63-78.

Johnson, P.C., Ettinger, R.A. 1991. "Heuristic Model for Predicting the Intrusion Rate of Contaminant Vapors into Buildings." *Environmental Science and Technology* 25(8):1445-1452.

Johnson, P.C., Kemblowski, W., Johnson, R.L. 1998. "Assessing the Significance of Subsurface Contamination Migration to Enclosed Spaces- Site Specific Alternatives to Generic Estimates." *API Publication 4674*. American Petroleum Institute: Washington, D.C., December 1998.

Johnson, P.C., Ettinger, R.A., Kurtz, J., Bryan, R., Dester, J.E. 2002. Migration of Soil

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Gas Vapors to Indoor Air: Determining Vapor Attenuation Factors Using a Screening-Level Model and Field Data from the CDOT-MTL Denver, Colorado Site. American Petroleum Institute. No. 16.

Kremesec, V., Hopkins, H. and Thun, R. (Feb. 2005). A View of the Evaluation of the Vapor Intrusion Pathway from Within the Petroleum Industry. EM Magazine, Air and Waste Management Association.

http://www.astswmo.org/files/publications/tanks/2005SoilVaporMonitoringWorkshop/Ev aluation-of-Vapor-Intrusion-Pathway-Kremesec.pdf

Lyman, W. and Reehl, W. (1990). Handbook of Chemical Property Estimation Methods. Available at the Illinois EPA Library, Call Number: 547.3 LYMA 1990.

McAlary, T., R. Ettinger, P. Johnson, B. Eklund, H. Hayes, D.B. Chadwick, and I. Rivera-Duarte. 2009. *Review of Best Practices, Knowledge and Data Gaps, and Research Opportunities for the U.S. Department of Navy Vapor Intrusion Focus Areas.* Technical Report 1982. SSC Pacific, San Diego, CA.

McHugh, T.E., Connor, J.A., Ahmad, F. 2004. "An Empirical Analysis of the Groundwater-to-Indoor-Air Exposure Pathway: The Role of Background Concentrations in Indoor Air." *Environmental Forensics* 5:33-44.

McHugh, T., Connor, J., & Ahmad, F. (Mar. 2005). An Empirical Analysis of the Groundwater-to-Indoor-Air Exposure Pathway: The Role of Background Concentrations in Indoor Air. Environmental Forensics, Vol. 5, No. 2. <u>http://www.gsi-net.com/Publications/McHugh GW-Air 2004.pdf</u>

McHugh, T.E., De Blanc, P.C., Pokluda, R.J. 2006. "Indoor Air as a Source of VOC Contamination in Shallow Soils Below Buildings." *Soil & Sediment Contamination* 15:103-122.

Missouri Department of Natural Resources (April 2005). Missouri Risk-Based Corrective Action for Petroleum Storage Tanks: Soil Gas Sampling Protocol. <u>http://www.dnr.mo.gov/env/hwp/tanks/docs/soil-gas-protocol-2005-04-21.pdf</u>

National Institute for Occupational Safety and Health (NIOSH). (2005). NIOSH Pocket Guide to Chemical Hazards. <u>http://www.cdc.gov/niosh/npg/default.html</u>

Nazaroff, W.W. 1988. "Predicting the Rate of ²²²Rn Entry from Soil into the Basement of a Dwelling Due to Pressure-Driven Air Flow." *Radiation Protection Dosimetry*

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

24(1/4):199-202.

Nazaroff, W.W., Feustel, H., Nero, A.V., Revzan, K.L., Grimsrud, D.T., Essling, M.A., Toohey, R.E. 1985. "Radon Transport into a Detached One-Story House with a Basement." *Atmosphere & Environment* 19(1):31-46.

Nelson, D., Lapara, T., Novak, P. 2010. "Effects of Ethanol-Based Fuel Contamination: Microbial Community Changes, Production of Regulated Compounds and Methane Generation." *Environmental Science and Technology* 44(12):4525-4530.

New Hampshire Department of Environmental Services (April 2005). Draft Vapor Intrusion Guidance. <u>http://www.des.state.nh.us/ORCB/doclist/pdf/vapor_intrusion.pdf</u>

New Jersey Department of Environmental Protection (June 2005). Draft Vapor Intrusion Guidance. <u>http://www.state.nj.us/dep/srp/guidance/vaporintrusion/vig.htm</u>

New York Department of Environmental Conservation (Nov. 2004). Evaluating the Potential for Vapor Intrusion at Past, Current and Future Sites, Draft. <u>http://www.ny-brownfields.com/PDF_Files/Draft_Policy.pdf</u>

Ohio EPA. 2010. Guidance Document for Sample Collection and Evaluation of Vapor Intrusion to Indoor Air for Remedial Response and Voluntary Action Programs. http://www.epa.state.oh.us/portals/30/rules/VI%20guidance.pdf

Patterson, B.M., Davis, G.B. 2009. "Quantification of Vapor Intrusion Pathways into a Slab-on-Ground Building under Varying Environmental Conditions." *Environmental Science and Technology* 43:650-656.

Pennsylvania Department of Environmental Protection (June 2004). Land Recycling Program Technical Guidance Manual Section IV.A.4 Vapor Intrusion into Buildings from Groundwater and Soil Under the Act 2 Statewide Health Standard. <u>http://164.156.71.80/VWRQ.asp?docid=2087d8407c0e00000000051100000511&context</u> =2&backlink=WXOD.aspx%3ffs%3d2087d8407c0e00008000051000000510%26ff%3d1

Persily, A. (March 1999). Myths About Building Envelopes. ASHRAE Journal. http://www.argonair.com/pdf/Myth%20About%20Bldg%20Env.pdf

Provoost, J., Bosman, A., Reijnders, L., Bronders, J., Touchant, K., Swartjes, F. 2010. "Vapor Intrusion from the Vadose Zone- Seven Algorithms Compared." *Journal of Soils and Sediments* 10:473-483.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Ririe, G.T., Sweeney, R., Hartman, B. 2009. *BP Standard Operating Procedures for Petroleum Hydrocarbon Vapor Intrusion Sampling*. Draft document, not published.

Roggemans, S., Bruce, C., Johnson, P.C., Johnson, R.L. 2001. Vadose Zone Natural Attenuation of Hydrocarbon Vapors. American Petroleum Institute. No. 15.

Siegel, L. (April 2005). A Community View of Vapor Intrusion. Center for Public Environmental Oversight. <u>http://www.cpeo.org/pubs/CommunityView-V12.doc</u>

Stanin, F. (March 2006). Vapor Intrusion: Breaking Through the Roadblocks to Progress. Superfund and Natural Resource Damages Litigation Committee Newsletter. Vol. 3, No. 1.

http://www.abanet.org/environ/committees/superfundnatresdamages/newsletter/mar06/superfund0306.pdf

The Star-Ledger (Aug. 12, 2006). DEP to review sites after day-care fiasco. Newark, New Jersey. Available from the Illinois EPA library upon request.

Syracuse Research Corporation (SRC). CHEMFATE Database. SRC. Syracuse, NY. <u>http://www.srcinc.com/what-we-do/databaseforms.aspx?id=381</u>

Syracuse Research Corporation (SRC). PHYSPROP Database. SRC. Syracuse, NY. <u>http://www.srcinc.com/what-we-do/databaseforms.aspx?id=386</u>

The Tri-Service Environmental Risk Assessment Workgroup (U.S. Air Force, U.S. Navy, U.S. Army). 2008. *Tri-Services Handbook for the Assessment of the Vapor Intrusion Pathway*.

http://portal.navfac.navy.mil/portal/page/portal/navfac/navfac_ww_pp/navfac_nfesc_pp/e nvironmental/erb/resourceerb/dod%20vi%20guidance%20handbook_dftfinal.pdf

Tilman, F.D., Weaver, J.W. 2005. *Review of Recent Research on Vapor Intrusion*. U.S. Environmental Protection Agency Office of Research and Development, Washington, DC. EPA/600/R-05/106.

United States Geological Survey. <u>Water Basics Glossary of Terms.</u> <u>http://capp.water.usgs.gov/GIP/h2o_gloss/</u> Last modified January 13, 2009.

U.S. Department of Agriculture, Natural Resources Conservation Service. 1992. *Proposed Illinois State Soil*. <u>http://www.il.nrcs.usda.gov/technical/soils/soildrum.html</u>

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

U.S. EPA (Mar. 2008). Brownfields Technical Primer: Vapor Intrusion Considerations for Redevelopment. EPA 542-R-08-001. http://www.brownfieldstsc.org/pdfs/BTSC%20Vapor%20Intrustion%20Considerations% 20for%20Redevelopment%20EPA%20542-R-08-001.pdf

U.S. EPA. (July 1997). Health Effects Assessment Summary Tables. FY 1997 Update. EPA Publication No. EPA 540/R-97-036. Available at <u>http://nepis.epa.gov</u>

U.S. EPA. Integrated Risk Information System. http://cfpub.epa.gov/ncea/iris/index.cfm

U.S. EPA, Office of Inspector General. 2009. Evaluation Report: Lack of Final Guidance on Vapor Intrusion Impedes Efforts to Address Indoor Air Risks. Report No. 10-P-0042.

U.S. EPA, Office of Underground Storage Tanks. 2010. *Petroleum Vapor Intrusion Workgroup Information Paper*. Draft document, not published.

U.S. EPA. Provisional Peer Reviewed Toxicity Values. Superfund Health Risk Technical Support Center. National Center for Environmental Assessment, Office of Research and Development. Cincinnati, OH 45268, (513) 569-7300.

U.S. EPA. (January 2004). Superfund Chemical Data Matrix. http://www.epa.gov/superfund/sites/npl/hrsres/tools/scdm.htm

U.S. EPA. (July 2004). Water9, Version 2.0. http://www.epa.gov/ttn/chief/software/water/

Weaver, J.W., Tilman, F.D. 2005. Uncertainty and the Johnson-Ettinger Model for Vapor Intrusion Calculations. U.S. Environmental Protection Agency Office of Research and Development, Washington, DC. EPA/600/R-05/110

- 7) <u>Will these proposed amendments replace an emergency rule currently in effect?</u> No.
- 8) <u>Do these amendments contain an automatic repeal date?</u> No.
- 9) Do these proposed amendments contain incorporations by reference? Yes.
- 10) Are there any other proposed amendments pending on this Part? No.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- Statement of Statewide Policy Objectives: These proposed amendments do not create or enlarge a State mandate as defined in Section 3(b) of the State Mandates Act. [30 ILCS 805/3(b)].
- 12) <u>Time, Place, and Manner in which interested persons may comment on this proposed</u> <u>rulemaking</u>: The Board will accept written public comments on this proposal for a period of 45 days after the date of publication in the Illinois Register. Public comments should refer to docket R11-9 and must be filed with the Clerk of the Board. Public comments may be filed at the following address:

Pollution Control Board John Therriault, Assistant Clerk JRTC 100 W. Randolph Street, Suite 11-500 Chicago, IL 60601

In addition, public comments may be filed electronically through COOL on the Board's Web site at <u>www.ipcb.state.il.us</u>. Persons interested in obtaining copies of Board opinions and orders in R11-9 may do so by contacting the Clerk's office at (312) 814-3620 or by download from COOL on the Board's Web site. For more information, please contact Hearing Officer Richard McGill by telephone at (312) 814-6983 or by email at mcgillr@ipcb.state.il.us.

- 13) Initial Regulatory Flexibility Analysis:
 - A) <u>Types of small businesses, small municipalities, and not-for-profit corporations</u> <u>affected</u>: This rulemaking could impact any small business, small municipality, and not-for-profit corporation in a regulatory program subject to TACO remediation objectives (*e.g.*, Leaking UST Program or SRP). The amendments are proposed to become effective on a date certain 60 days after their final adoption by the Board. The delayed effective date would help to accommodate those entities with sites near closure who wish to submit remediation completion documentation to IEPA in order to receive a No Further Remediation (NFR) letter in accordance with the existing TACO regulations.
 - B) <u>Reporting, bookkeeping, or other procedures required for compliance</u>: This rulemaking does not impose additional bookkeeping requirements beyond those already required by the existing rules. Under the proposed amendments, where a school receives an NFR letter based upon the use of an indoor inhalation building

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

control technology, the site owner/operator must notify IEPA upon the building control technology being rendered inoperable.

- C) <u>Types of Professional skills necessary for compliance</u>: In addition to the professional skills currently necessary to comply with the existing TACO regulations, compliance with the amendments may involve addressing the indoor inhalation exposure route through the sampling/analysis of soil gas and the design/installation of building control technologies, such as sub-slab depressurization (SSD) systems or vented raised floors.
- 14) <u>Regulatory Agenda in which these amendments were summarized</u>: January 2012

The full text of the proposed amendments begins on the next page:

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

TITLE 35: ENVIRONMENTAL PROTECTION SUBTITLE G: WASTE DISPOSAL CHAPTER I: POLLUTION CONTROL BOARD SUBCHAPTER f: RISK BASED CLEANUP OBJECTIVES

PART 742 TIERED APPROACH TO CORRECTIVE ACTION OBJECTIVES

SUBPART A: INTRODUCTION

Section

- 742.100 Intent and Purpose
- 742.105 Applicability
- 742.110 Overview of Tiered Approach

742.115 Key Elements

742.120 Site Characterization

SUBPART B: GENERAL

- 742.200 Definitions
- 742.205 Severability
- 742.210 Incorporations by Reference
- 742.215 Determination of Soil Attenuation Capacity
- 742.220 Determination of Soil Saturation Limit
- 742.222 Determination of Soil Vapor Saturation Limit
- 742.225 Demonstration of Compliance with <u>Soil and Groundwater</u> Remediation Objectives
- 742.227Demonstration of Compliance with Soil Gas Remediation Objectives for the
Outdoor and Indoor Inhalation Exposure Routes
- 742.230 Agency Review and Approval

SUBPART C: EXPOSURE ROUTE EVALUATIONS

Section

742.300	Exclusion of	f Exposure Route

- 742.305 Contaminant Source and Free Product Determination
- 742.310 <u>Outdoor</u> Inhalation Exposure Route
- 742.312 Indoor Inhalation Exposure Route
- 742.315 Soil Ingestion Exposure Route
- 742.320 Groundwater Ingestion Exposure Route

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

SUBPART D: DETERMINING AREA BACKGROUND

Section	
742.400	Area Background

Section

- 742.405 Determination of Area Background for Soil
- 742.410 Determination of Area Background for Groundwater
- 742.415 Use of Area Background Concentrations

SUBPART E: TIER 1 EVALUATION

Section	
742.500	Tier 1 Evaluation Overview
742.505	Tier 1 Soil, Soil Gas and Groundwater Remediation Objectives
742.510	Tier 1 Remediation Objectives Tables for the Ingestion, Outdoor Inhalation, and
	Soil Component of the Groundwater Ingestion Exposure Routes
740 515	Tion 1 Demodiation Objectives Tables for the Indeen Inheletion Exposure Devite

742.515 Tier 1 Remediation Objectives Tables for the Indoor Inhalation Exposure Route

SUBPART F: TIER 2 GENERAL EVALUATION

Section

- 742.600 Tier 2 Evaluation Overview
- 742.605 Land Use
- 742.610 Chemical and Site Properties

SUBPART G: TIER 2 SOIL AND SOIL GAS EVALUATION

Section	
742.700	Tier 2 Soil Evaluation Overview
742.705	Parameters for Soil Remediation Objective Equations
742.710	SSL Soil Equations
<u>742.712</u>	SSL Soil Gas Equation for the Outdoor Inhalation Exposure Route
742.715	RBCA Soil Equations
<u>742.717</u>	J&E Soil Gas Equations for the Indoor Inhalation Exposure Route
742.720	Chemicals with Cumulative Noncarcinogenic Effects

SUBPART H: TIER 2 GROUNDWATER EVALUATION

Section	
742.800	Tier 2 Groundwater Evaluation Overview
742.805	Tier 2 Groundwater Remediation Objectives

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 742.810 <u>RBCA</u> Calculations to Predict Impacts from Remaining Groundwater Contamination
- 742.812 J&E Groundwater Equations for the Indoor Inhalation Exposure Route

SUBPART I: TIER 3 EVALUATION

Section

742.900	Tier 3 Evaluation Overview
742.905	Modifications of Parameters
742.910	Alternative Models
742.915	Formal Risk Assessments
742.920	Impractical Remediation
742.925	Exposure Routes
742.930	Derivation of Toxicological Data
742 025	Indoor Inholation Exposure Doute

742.935Indoor Inhalation Exposure Route

SUBPART J: INSTITUTIONAL CONTROLS

Section

- 742.1000 Institutional Controls
- 742.1005 No Further Remediation Letters
- 742.1010 Environmental Land Use Controls
- 742.1012 Federally Owned Property: Land Use Control Memoranda of Agreement
- 742.1015 Ordinances
- 742.1020 Highway Authority Agreements and Highway Authority Agreement Memoranda of Agreement

SUBPART K: ENGINEERED BARRIERS

Section

- 742.1100 Engineered Barriers
- 742.1105 Engineered Barrier Requirements

SUBPART L: BUILDING CONTROL TECHNOLOGIES

Section 1997	
742.1200	Building Control Technologies
742.1205	Building Control Technology Proposals
742.1210	Building Control Technology Requirements

742.APPENDIX A General

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

ILLUSTRATION A	Developing Soil Remediation Objectives Under the Tiered
	Approach
ILLUSTRATION B	Developing Groundwater Remediation Objectives Under the
	Tiered Approach
TABLE A	Soil Saturation Limits (C _{sat}) for Chemicals Whose Melting Point is
	Less than 30°C
TABLE B	Tolerance Factor (K)
TABLE C	Coefficients $\{A_{N-I+1}\}$ for W Test of Normality, for N=2(1)50
TABLE D	Percentage Points of the W Test for $n=3(1)50$
TABLE E	Similar-Acting Noncarcinogenic Chemicals
TABLE F	Similar-Acting Carcinogenic Chemicals
TABLE G	Concentrations of Inorganic Chemicals in Background Soils
TABLE H	Concentrations of Polynuclear Aromatic Hydrocarbon Chemicals in Background Soils
TABLE I	Chemicals Whose Tier 1 Class I Groundwater Remediation
	Objective Exceeds the 1 in 1,000,000 Cancer Risk Concentration
TABLE J	List of TACO Volatile Chemicals for the Indoor Inhalation
<u></u>	Exposure Route
<u>TABLE K</u>	Soil Vapor Saturation Limits (C_v^{sat}) for Volatile Chemicals
	$\underline{\text{bon}}$ + upor sutaration $\underline{\text{binne}}$ ($\underline{\text{binne}}$) for $\underline{\text{binne}}$ or $\underline{\text{binne}}$
742.APPENDIX B Tier 1	Illustrations and Tables
ILLUSTRATION A	Tier 1 Evaluation
TABLE A	Tier 1 Soil Remediation Objectives for Residential Properties
TABLE B	Tier 1 Soil Remediation Objectives for Industrial/Commercial
	Properties
TABLE C	pH Specific Soil Remediation Objectives for Inorganics and
	Ionizing Organics for the Soil Component of the Groundwater
	Ingestion Route (Class I Groundwater)
TABLE D	pH Specific Soil Remediation Objectives for Inorganics and
	Ionizing Organics for the Soil Component of the Groundwater
	Ingestion Route (Class II Groundwater)
TABLE E	Tier 1 Groundwater Remediation Objectives for the Groundwater
	Component of the Groundwater Ingestion Route
TABLE F	Values Used to Calculate the Tier 1 Soil Remediation Objectives
	for the Soil Component of the Groundwater Ingestion Route
TABLE G	Soil Gas Remediation Objectives for the Outdoor Inhalation
	Exposure Route
TABLE H	Tier 1 Soil Gas and Groundwater Remediation Objectives for the
	Indoor Inhalation Exposure Route – Diffusion and Advection
TABLE I	Tier 1 Soil Gas and Groundwater Remediation Objectives for the
	Indoor Inhalation Exposure Route – Diffusion Only

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

742.APPENDIX C Tier 2	Illustrations and Tables
ILLUSTRATION A	Tier 2 Evaluation for Soil
ILLUSTRATION B	Tier 2 Evaluation for Groundwater
ILLUSTRATION C	US Department of Agriculture Soil Texture Classification
TABLE A	SSL Equations
TABLE B	SSL Parameters
TABLE C	RBCA Equations
TABLE D	RBCA Parameters
TABLE E	Default Physical and Chemical Parameters
TABLE F	Methods for Determining Physical Soil Parameters
TABLE G	Error Function (erf)
TABLE H	Q/C Values By Source Area
TABLE I	K_{oc} Values for Ionizing Organics as a Function of pH (cm ³ /g or
	$L/kg \text{ or } cm^{3}_{water}/g_{soil})$
TABLE J	Values to be Substituted for kd or ks when Evaluating Inorganics
	as a Function of pH (cm ³ /g or L/kg or cm ³ _{water} /g _{soil})
TABLE K	Parameter Estimates for Calculating Water-Filled Soil Porosity θ_w)
TABLE L	<u>J&E Equations</u>
TABLE M	J&E Parameters

- 742. APPENDIX E Highway Authority Agreement Memorandum of Agreement
- 742.APPENDIX F Environmental Land Use Control
- 742.APPENDIX G Model Ordinance
- 742.APPENDIX H Memorandum of Understanding

AUTHORITY: Implementing Sections 22.4, 22.12, Title XVI, and Title XVII and authorized by Sections 27 and 58.5 of the Environmental Protection Act [415 ILCS 5/22.4, 22.12, 27, and 58.5 and Title XVI and Title XVII].

SOURCE: Adopted in R97-12(A) at 21 Ill. Reg. 7942, effective July 1, 1997; amended in R97-12(B) at 21 Ill. Reg. 16391, effective December 8, 1997; amended in R97-12(C) at 22 Ill. Reg. 10847, effective June 8, 1998; amended in R00-19(A) at 25 Ill. Reg. 651, effective January 6, 2001; amended in R00-19(B) at 25 Ill. Reg. 10374, effective August 15, 2001; amended in R00-19(C) at 26 Ill. Reg. 2683, effective February 5, 2002; amended in R06-10 at 31 Ill. Reg. 4063, effective February 23, 2007; amended in R06-10 at 31 Ill. Reg. 4063 effective March 9, 2007; amended in R11-09 at 36 Ill. Reg. _____, effective _____.

NOTE: Italics indicates statutory language.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

SUBPART A: INTRODUCTION

Section 742.105 Applicability

- a) Any person, including a person required to perform an investigation pursuant to the Illinois Environmental Protection Act [415 ILCS 5] (Act), may elect to proceed under this Part to the extent allowed by State or federal law and regulations and the provisions of this Part and subject to the exceptions listed in subsection (h) below. A person proceeding under this Part may do so to the extent such actions are consistent with the requirements of the program under which site remediation is being addressed.
- b) This Part is to be used in conjunction with the procedures and requirements applicable to the following programs:
 - 1) Leaking Underground Storage Tanks (35 Ill. Adm. Code 731, 732, and 734);
 - 2) Site Remediation Program (35 Ill. Adm. Code 740); and
 - 3) RCRA Part B Permits and Closure Plans (35 Ill. Adm. Code 724 and 725).
- c) The procedures in this Part may not be used if their use would delay response action to address imminent and substantial threats to human health and the environment. This Part may only be used after actions to address such threats have been completed.
- d) This Part may be used to develop remediation objectives to protect surface waters, sediments or ecological concerns, when consistent with the regulations of other programs, and as approved by the Agency.
- e) A no further remediation determination issued by the Agency prior to July 1, 1997 pursuant to Section 4(y) of the Act or one of the programs listed in subsection (b) of this Section that approves completion of remedial action relative to a release shall remain in effect in accordance with the terms of that determination.
- f) Site specific groundwater remediation objectives determined under this Part for contaminants of concern may exceed the groundwater quality standards established pursuant to the rules promulgated under the Illinois Groundwater Protection Act [415 ILCS 55] as long as done in accordance with Sections 742.805 and 742.900(c)(9). (See 415 ILCS 5/58.5(d)(4)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- g) Where contaminants of concern include polychlorinated byphenyls (PCBs), a person may need to evaluate the applicability of regulations adopted under the Toxic Substances Control Act (15 U.S.C. 2601).
- h) This Part may not be used in lieu of the procedures and requirements applicable to landfills under 35 Ill. Adm. Code 807 or 811 through 814.
- <u>An evaluation of the indoor inhalation exposure route under this Part addresses</u> the potential of contaminants present in soil gas or groundwater to reach human receptors within buildings. This Part does not address the remediation or mitigation of any contamination within a building from a source other than soil gas or groundwater, such as the building structure itself and products within the building.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.110 Overview of Tiered Approach

- a) This Part presents an approach for developing remediation objectives (see Appendix A, Illustrations A and B) that include an option for exclusion of pathways from further consideration, use of area background concentrations as remediation objectives and three tiers for selecting applicable remediation objectives. An understanding of human exposure routes is necessary to properly conduct an evaluation under this approach. In some cases, applicable human exposure route(s) can be excluded from further consideration prior to any tier evaluation. Selecting which tier or combination of tiers to be used to develop remediation objectives is dependent on the site-specific conditions and remediation goals. Tier 1 evaluations and Tier 2 evaluations are not prerequisites to conducting Tier 3 evaluations.
- b) A Tier 1 evaluation compares the concentration of contaminants detected at a site to the corresponding remediation objectives for residential and industrial/commercial properties contained in Appendix B, Tables A, B, C, D and E, G, H and I. To complete a Tier 1 evaluation, the extent and concentrations of the contaminants of concern, the groundwater class, the land use classification, human exposure routes at the site, and, if appropriate, soil pH, must be known. If remediation objectives are developed based on industrial/commercial property use, then institutional controls under Subpart J are required.

NOTICE OF PROPOSED AMENDMENTS

- c) A Tier 2 evaluation uses the risk based equations from the Soil Screening Level (SSL Model) and Risk Based Corrective Action (RBCA Model) and modified Johnson and Ettinger Model (J&E Model) documents listed in Appendix C, Tables A, and C, and L respectively. In addition to the information that is required for a Tier 1 evaluation, site-specific information is used to calculate Tier 2 remediation objectives. As in Tier 1, Tier 2 evaluates residential and industrial/commercial properties only. If remediation objectives are developed based on industrial/commercial property use, then institutional controls under Subpart J are required.
- d) A Tier 3 evaluation allows alternative parameters and factors, not available under a Tier 1 or Tier 2 evaluation, to be considered when developing remediation objectives. Remediation objectives developed for conservation and agricultural properties can only be developed under Tier 3.
- e) Remediation objectives may be developed using area background concentrations or any of the three tiers if the evaluation is conducted in accordance with applicable requirements in Subparts D through I. When contaminant concentrations do not exceed remediation objectives developed under one of the tiers or area background procedures under Subpart D, further evaluation under any of the other tiers is not required.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.115 Key Elements

To develop remediation objectives under this Part, the following key elements shall be addressed.

- a) Exposure Routes
 - 1) This Part identifies the following as potential exposure routes to be addressed:
 - A) <u>Outdoor</u> Inhalation;
 - <u>B)</u> <u>Indoor Inhalation;</u>
 - $\underline{C} \underline{B}$) Soil ingestion;
 - $\underline{D} \in$) Groundwater ingestion; and

NOTICE OF PROPOSED AMENDMENTS

- $\underline{E} \mathbf{D}$) Dermal contact with soil.
- 2) The evaluation of exposure routes under subsections (a)(1)(A),(a)(1)(B), and (a)(1)(C) and (a)(1)(D) of this Section is required for all sites when developing remediation objectives or excluding exposure pathways. Evaluation of the dermal contact exposure route is required for use of RBCA equations in Appendix C, Table C or use of formal risk assessment under Section 742.915.
- 3) The groundwater ingestion exposure route is comprised of two components:
 - A) Migration from soil to groundwater (soil component); and
 - B) Direct ingestion of groundwater (groundwater component).
- 4) The outdoor inhalation route is comprised of two components:
 - <u>A)</u> <u>Migration from soil through soil gas to outdoor air (soil component); and</u>
 - B) <u>Migration from soil gas to outdoor air (soil gas component).</u>
- 5) The indoor inhalation exposure route is comprised of two components:
 - A) Migration from soil gas to indoor air (soil gas component); and
 - B) Migration from groundwater through soil gas to indoor air (groundwater component).
- b) Contaminants of Concern

The contaminants of concern to be remediated depend on the following:

- 1) The materials and wastes managed at the site;
- 2) The extent of the no further remediation determination being requested from the Agency pursuant to a specific program; and

NOTICE OF PROPOSED AMENDMENTS

- 3) The requirements applicable to the specific program, as listed at Section 742.105(b) under which the remediation is being performed.
- c) Land Use

The present and post-remediation uses of the site where exposures may occur shall be evaluated. The land use of a site, or portion thereof, shall be classified as one of the following:

- 1) Residential property;
- 2) Conservation property;
- 3) Agricultural property; or
- 4) Industrial/commercial property.
- <u>d)</u> Environmental Media of Concern

This Part provides procedures for developing remediation objectives for the following environmental media:

- <u>1)</u> <u>Soil;</u>
- 2) Soil gas;
- <u>3)</u> <u>Groundwater.</u>

(Source: Amended at 36 Ill. Reg. ____, effective ____)

SUBPART B: GENERAL

Section 742.200 Definitions

Except as stated in this Section, or unless a different meaning of a word or term is clear from the context, the definition of words or terms in this Part shall be the same as that applied to the same words or terms in the Act.

"Act" means the Illinois Environmental Protection Act [415 ILCS 5].

NOTICE OF PROPOSED AMENDMENTS

"ADL" means Acceptable Detection Limit, which is the detectable concentration of a substance that is equal to the lowest appropriate Practical Quantitation Limit (PQL) as defined in this Section.

"Agency" means the Illinois Environmental Protection Agency.

"Agricultural Property" means any real property for which its present or postremediation use is for growing agricultural crops for food or feed either as harvested crops, cover crops or as pasture. This definition includes, but is not limited to, properties used for confinement or grazing of livestock or poultry and for silviculture operations. Excluded from this definition are farm residences, farm outbuildings and agrichemical facilities.

"Aquifer" means saturated (with groundwater) soils and geologic materials which are sufficiently permeable to readily yield economically useful quantities of water to wells, springs, or streams under ordinary hydraulic gradients. (Illinois Groundwater Protection Act [415 ILCS 55/3(a)])

"Area Background" means concentrations of regulated substances that are consistently present in the environment in the vicinity of a site that are the result of natural conditions or human activities, and not the result solely of releases at the site. [415 ILCS 5/58.2]

"ASTM" means the American Society for Testing and Materials.

"Board" means the Illinois Pollution Control Board.

"Building" means a man-made structure with an enclosing roof and enclosing walls, except for windows and doors, that is fit for any human occupancy for at least six consecutive months.

"Building Control Technology" means any technology or barrier that affects air flow or air pressure within a building for purposes of reducing contaminant migration to the indoor air.

"Cancer Risk" means a unitless probability of an individual developing cancer from a defined exposure rate and frequency.

"Cap" means a barrier designed to prevent the infiltration of precipitation or other surface water, or impede the ingestion or inhalation of contaminants.

NOTICE OF PROPOSED AMENDMENTS

"Capillary Fringe" means the zone above the water table in which water is held by surface tension. Water in the capillary fringe is under a pressure less than atmospheric.

"Carcinogen" means a contaminant that is classified as a category A1 or A2 carcinogen by the American Conference of Governmental Industrial Hygienists; a category 1 or 2A/2B carcinogen by the World Health Organization's International Agency for Research on Cancer; a "human carcinogen" or "anticipated human carcinogen" by the United States Department of Health and Human Service National Toxicological Program; or a category A or B1/B2 carcinogen or as "carcinogenic to humans" or "likely to be carcinogenic to humans" by the United States Environmental Protection Agency in the integrated risk information system or a final rule issued in a Federal Register notice by the USEPA. [415 ILCS 5/58.2]

"Class I Groundwater" means groundwater that meets the Class I: Potable Resource Groundwater criteria set forth in 35 Ill. Adm. Code 620.

"Class II Groundwater" means groundwater that meets the Class II: General Resource Groundwater criteria set forth in 35 Ill. Adm. Code 620.

"Conservation Property" means any real property for which present or postremediation use is primarily for wildlife habitat.

"Construction Worker" means a person engaged on a temporary basis to perform work involving invasive construction activities including, but not limited to, personnel performing demolition, earth-moving, building, and routine and emergency utility installation or repair activities.

"Contaminant of Concern" or "Regulated Substance of Concern" means *any* contaminant that is expected to be present at the site based upon past and current land uses and associated releases that are known to the person conducting a remediation based upon reasonable inquiry [415 ILCS 5/58.2]

"County highway" means county highway as defined in the Illinois Highway Code, [605 ILCS 5].

"District road" means district road as defined in the Illinois Highway Code, [605 ILCS 5].

NOTICE OF PROPOSED AMENDMENTS

"Engineered Barrier" means a barrier designed or verified using engineering practices that limits exposure to or controls migration of the contaminants of concern.

"Environmental Land Use Control" means an instrument that meets the requirements of this Part and is placed in the chain of title to real property that limits or places requirements upon the use of the property for the purpose of protecting human health or the environment, is binding upon the property owner, heirs, successors, assigns, and lessees, and runs in perpetuity or until the Agency approves, in writing, removal of the limitation or requirement from the chain of title.

"Exposure Route" means the transport mechanism by which a contaminant of concern reaches a receptor.

"Federally Owned Property" means real property owned in fee by the United States of America on which institutional controls are sought to be placed in accordance with this Subpart.

"Federal Landholding Entity" means that federal department, agency, or instrumentality with the authority to occupy and control the day-to-day use, operation and management of Federally Owned Property.

"Free Product" means a contaminant that is present as a non-aqueous phase liquid for chemicals whose melting point is less than 30° C (e.g., liquid not dissolved in water).

"GIS" means Geographic Information System.

"GPS" means Global Positioning System.

"Groundwater" means underground water which occurs within the saturated zone and geologic materials where the fluid pressure in the pore space is equal to or greater than atmospheric pressure. [415 ILCS 5/3.64]

"Groundwater Quality Standards" means the standards for groundwater as set forth in 35 Ill. Adm. Code 620.

"Hazard Quotient" means the ratio of a single substance exposure level during a specified time period to a reference dose for that substance derived from a similar exposure period.

NOTICE OF PROPOSED AMENDMENTS

"Highway" means any public way for vehicular travel which has been laid out in pursuance of any law of this State, or of the Territory of Illinois, or which has been established by dedication, or used by the public as a highway for 15 years, or which has been or may be laid out and connect a subdivision or platted land with a public highway and which has been dedicated for the use of the owners of the land included in the subdivision or platted land where there has been an acceptance and use under such dedication by such owners, and which has not been vacated in pursuance of law. The term "highway" includes rights of way, bridges, drainage structures, signs, guard rails, protective structures and all other structures and appurtenances necessary or convenient for vehicular traffic. A highway in a rural area may be called a "road", while a highway in a municipal area may be called a "street". (Illinois Highway Code [605 ILCS 5/2-202])

"Highway Authority" means the Department of Transportation with respect to a State highway; the Illinois State Toll Highway with respect to a toll highway; the County Board with respect to a county highway or a county unit district road if a discretionary function is involved and the County Superintendent of Highways if a ministerial function is involved; the Highway Commissioner with respect to a township or district road not in a county unit road district; or the corporate authorities of a municipality with respect to a municipal street. (Illinois Highway Code [605 ILCS 5/2-213])

"Human Exposure Pathway" means a physical condition which may allow for a risk to human health based on the presence of all of the following: contaminants of concern; an exposure route; and a receptor activity at the point of exposure that could result in contaminant of concern intake.

"Industrial/Commercial Property" means any real property that does not meet the definition of residential property, conservation property or agricultural property.

"Infiltration" means the amount of water entering into the ground as a result of precipitation.

"Institutional Control" means a legal mechanism for imposing a restriction on land use, as described in Subpart J.

"Land Use Control Memoranda of Agreement" mean agreements entered into between one or more agencies of the United States and the Illinois Environmental Protection Agency that limit or place requirements upon the use of Federally Owned Property for the purpose of protecting human health or the environment.

NOTICE OF PROPOSED AMENDMENTS

"Man-Made Pathways" means *constructed* physical conditions *that may allow for the transport of regulated substances including, but not limited to, sewers, utility lines, utility* <u>or elevator</u> *vaults, building foundations, basements, crawl spaces, drainage ditches,* or *previously excavated and filled areas,* <u>or sumps</u>. [415 ILCS 5/58.2]

"Natural Pathways" means *natural* physical conditions that may allow *for the transport of regulated substances including, but not limited to, soil, groundwater, sand seams and lenses, and gravel seams and lenses.* [415 ILCS 5/58.2]

"Person" means an *individual*, *trust*, *firm*, *joint stock company*, *joint venture*, consortium, commercial entity, corporation (including a government corporation), partnership, association, state, municipality, commission, political subdivision of a state, or any interstate body including the United States government and each department, agency, and instrumentality of the United States. [415 ILCS 5/58.2]

"Point of Human Exposure" means the points at which human exposure to a contaminant of concern may reasonably be expected to occur. The point of human exposure is at the source, unless an institutional control limiting human exposure for the applicable exposure route has been or will be in place, in which case the point of human exposure will be the boundary of the institutional control. Point of human exposure may be at a different location than the point of compliance.

"Populated Area" means

an area within the boundaries of a municipality that has a population of 10,000 or greater based on the year 2000 or most recent census; or

an area less than three miles from the boundary of a municipality that has a population of 10,000 or greater based on the year 2000 or most recent census.

"Potable" means generally fit for human consumption in accordance with accepted water supply principles and practices. (Illinois Groundwater Protection Act [415 ILCS 55/3(h)])

"PQL" means practical quantitation limit or estimated quantitation limit, which is the lowest concentration that can be reliably measured within specified limits of

NOTICE OF PROPOSED AMENDMENTS

precision and accuracy for a specific laboratory analytical method during routine laboratory operating conditions in accordance with "Test Methods for Evaluating Solid Wastes, Physical/Chemical Methods", EPA Publication No. SW-846, incorporated by reference in Section 742.210. When applied to filtered water samples, PQL includes the method detection limit or estimated detection limit in accordance with the applicable method revision in: "Methods for the Determination of Organic Compounds in Drinking Water", Supplement II", EPA Publication No. EPA/600/4-88/039; "Methods for the Determination of Organic Compounds in Drinking Water, Supplement III", EPA Publication No. EPA/600/R-95/131, all of which are incorporated by reference in Section 742.210.

"Q_{soil}" means the volumetric flow rate of soil gas from the subsurface into the enclosed building space.

"RBCA" means Risk Based Corrective Action as defined in ASTM E-1739-95, as incorporated by reference in Section 742.210.

"RCRA" means the Resource Conservation and Recovery Act of 1976 (42 U.S.C. 6921).

"Reference Concentration" or "RfC" means an estimate of a daily exposure, in units of milligrams of chemical per cubic meter of air (mg/m(3)), to the human population (including sensitive subgroups) that is likely to be without appreciable risk of deleterious effects during a portion of a lifetime (up to approximately seven years, subchronic) or for a lifetime (chronic).

"Reference Dose" or "RfD" means an estimate of a daily exposure, in units of milligrams of chemical per kilogram of body weight per day (mg/kg/d), to the human population (including sensitive subgroups) that is likely to be without appreciable risk of deleterious effects during a portion of a lifetime (up to approximately seven years, subchronic) or for a lifetime (chronic).

"Regulated Substance" means any hazardous substance as defined under Section 101(14) of the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (P.L. 96-510) and petroleum products including crude oil or any fraction thereof, natural gas, natural gas liquids, liquefied natural gas, or synthetic gas usable for fuel (or mixtures of natural gas and such synthetic gas). [415 ILCS 5/58.2]

NOTICE OF PROPOSED AMENDMENTS

"Residential Property" *means any real property that is used for habitation by individuals, or* where children have the opportunity for exposure to contaminants through soil ingestion or inhalation (indoor or outdoor) at educational facilities, health care facilities, child care facilities or outdoor recreational areas. [415 ILCS 5/58.2]

"Right of Way" means the land, or interest therein, acquired for or devoted to a highway. (Illinois Highway Code [605 ILCS 5/2-217])

"Saturated Zone" means a subsurface zone in which all the interstices or voids are filled with water under pressure greater than that of the atmosphere.

"Similar-Acting Chemicals" are chemical substances that have toxic or harmful effect on the same specific organ or organ system (see Appendix A.Tables E and F for a list of similar-acting chemicals with noncarcinogenic and carcinogenic effects).

"Site" means any single location, place, tract of land or parcel of property, or portion thereof, including contiguous property separated by a public right-of-way. 415 ILCS 5/58.2]

"Slurry Wall" means a man-made barrier made of geologic material which is constructed to prevent or impede the movement of contamination into a certain area.

"Soil Gas" means the air existing in void spaces in the soil between the groundwater table and the ground surface.

"Soil Saturation Limit" or " C_{sat} " means the contaminant concentration at which soil pore air and pore water are saturated with the chemical and the adsorptive limits of the soil particles have been reached. the contaminant concentration at which the absorptive limits of the soil particles, the solubility limits of the available soil moisture, and saturation of soil pore air have been reached. Above the soil saturation concentration, the assumptions regarding vapor transport to air and/or dissolved phase transport to groundwater (for chemicals which are liquid at ambient soil temperatures) do not apply, and alternative modeling approaches are required.

"Soil Vapor Saturation Limit" or " $C_v^{\text{sat,"}}$ means the maximum vapor concentration that can exist in the soil pore air at a given temperature and pressure.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

"Solubility" means a chemical specific maximum amount of solute that can dissolve in a specific amount of solvent (groundwater) at a specific temperature.

"SPLP" means Synthetic Precipitation Leaching Procedure (Method 1312) as published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", USEPA Publication No. SW-846, as incorporated by reference in Section 742.210.

"SSL" means Soil Screening Levels as defined in USEPA's Soil Screening Guidance: User's Guide and Technical Background Document, as incorporated by reference in Section 742.210.

"State highway" means state highway as defined in the Illinois Highway Code [605 ILCS 5].

"Stratigraphic Unit" means a site-specific geologic unit of native deposited material and/or bedrock of varying thickness (e.g., sand, gravel, silt, clay, bedrock, etc.). A change in stratigraphic unit is recognized by a clearly distinct contrast in geologic material or a change in physical features within a zone of gradation. For the purposes of this Part, a change in stratigraphic unit is identified by one or a combination of differences in physical features such as texture, cementation, fabric, composition, density, and/or permeability of the native material and/or bedrock.

"Street" means street as defined in the Illinois Highway Code [605 ILCS 5].

"TCLP" means Toxicity Characteristic Leaching Procedure (Method 1311) as published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", USEPA Publication No. SW-846, as incorporated by reference in Section 742.210.

"Toll highway" means toll highway as defined in the Illinois Highway Code [605 ILCS 5].

"Total Petroleum Hydrocarbon (TPH)" means the additive total of all petroleum hydrocarbons found in an analytical sample.

"Township road" means township road as defined in the Illinois Highway Code [605 ILCS 5].

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

"Unconfined Aquifer" means an aquifer whose upper surface is a water table free to fluctuate under atmospheric pressure.

"Volatile Chemicals" means chemicals with a Dimensionless Henry's Law Constant of greater than 1.9×10^{-2} or a vapor pressure greater than 0.1 Torr (mmHg) at 25°C. For purposes of the indoor inhalation exposure route, elemental mercury is included in this definition.

"Volatile Organic Compounds (VOCs)" means organic chemical analytes identified as volatiles as published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", USEPA Publication No. SW-846 (incorporated by reference in Section 742.210), method numbers 8011, 8015B, 8021B, 8031, 8260B, 8315A, and 8316. For analytes not listed in any category in those methods, those analytes which have a boiling point less than 200° C and a vapor pressure greater than 0.1 Torr (mm Hg) at 20° C.

"Water Table" means the top water surface of an unconfined aquifer at atmospheric pressure.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.210 Incorporations by Reference

a) The Board incorporates the following material by reference:

Agency for Toxic Substances and Disease Registry (ATSDR) Minimal Risk Levels (MRLs), U.S. Environmental Protection Agency, 1600 Clifton Road, Mailstop F32, Atlanta, Georgia 30333, (770) 488-3357 (November 2007).

ASTM. American Society for Testing and Materials International, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959. (610) 832-9585.

ASTM D 2974-00, Standard Test Methods for Moisture, Ash and Organic Matter of Peat and Other Organic Soils, approved August 10, 2000.

ASTM D 2488-00, Standard Practice for Description and Identification of Soils (Visual-Manual Procedure), approved February 10, 2000.

ASTM D 1556-00, Standard Test Method for Density and Unit Weight of Soil in Place by the Sand-Cone Method, approved March 10, 2000.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

ASTM D 2167-94, Standard Test Method for Density and Unit Weight of Soil in Place by the Rubber Balloon Method, approved March 15, 1994.

ASTM D 2922-01, Standard Test Methods for Density of Soil and Soil-Aggregate in Place by Nuclear Methods (Shallow Depth), approved June 10, 2001.

ASTM D 2937-00e1, Standard Test Method for Density of Soil in Place by the Drive-Cylinder Method, approved June 10, 2000.

ASTM D 854-02, Standard Test Methods for Specific Gravity of Soil Solids by Water Pycnometer, approved July 10, 2002.

ASTM D 2216-98, Standard Test Method for Laboratory Determination of Water (Moisture) Content of Soil and Rock by Mass, approved February 10, 1998.

ASTM D 4959-00, Standard Test Method for Determination of Water (Moisture) Content of Soil by Direct Heating, approved March 10, 2000.

ASTM D 4643-00, Standard Test Method for Determination of Water (Moisture) Content of Soil by the Microwave Oven Method, approved February 10, 2000.

ASTM D 5084-03, Standard Test Methods for Measurement of Hydraulic Conductivity of Saturated Porous Materials Using a Flexible Wall Permeameter, approved November 1, 2003.

ASTM D 422-63 (2002), Standard Test Method for Particle-Size Analysis of Soils, approved November 10, 2002.

ASTM D 1140-00, Standard Test Methods for Amount of Material in Soils Finer than the No. 200 (75 μ m) Sieve, approved June 10, 2000.

ASTM D 3017-01, Standard Test Method for Water Content of Soil and Rock in Place by Nuclear Methods (Shallow Depth), approved June 10, 2001.

ASTM D 4525-90 (2001), Standard Test Method for Permeability of Rocks by Flowing Air, approved May 25, 1990.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

ASTM D 2487-00, Standard Classification of Soils for Engineering Purposes (Unified Soil Classification System), approved March 10, 2000.

ASTM D 1945-03, Standard Test Method for Analysis of Natural Gas by Gas Chromatography, approved May 10, 2003.

ASTM D 1946-90, Standard Practice for Analysis of Reformed Gas by Gas Chromatography, approved June 1, 2006.

ASTM E 1527-00, Standard Practice for Environmental Site Assessments: Phase I Environmental Site Assessment Process, approved May 10, 2000. Vol. 11.04.

ASTM E 1739-95 (2002), Standard Guide for Risk-Based Corrective Action Applied at Petroleum Release Sites, approved September 10, 1995.

ASTM E 2121-09, Standard Practice for Installing Radon Mitigation Systems in Existing Low-Rise Residential Buildings, approved November 1, 2009.

<u>ASTM E 2600-08, Standard Practice for Assessment for Vapor Intrusion</u> into Structures on Property Involved in Real Estate Transactions, approved March 1, 2008.

API. American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005-4070 (202) 682-8000.

"BIOVAPOR-A 1-D Vapor Intrusion Model with Oxygen-Limited Aerobic Biodegradation, Version 2.0 (January 2010)"

Barnes, Donald G. and Dourson, Michael. (1988). Reference Dose (RfD): Description and Use in Health Risk Assessments. Regulatory Toxicology and Pharmacology. 8, 471-486.

EPRI. Electric Power Research Institute. 3420 Hillview Avenue, Palo Alto, California 94304. (650) 855-2121.

Polycyclic Aromatic Hydrocarbons (PAHs) in Surface Soil in Illinois: Background PAHs, EPRI, Palo Alto, CA, We Energies, Milwaukee, WI, and IEPA, Springfield, IL: 2004. 1011376.

NOTICE OF PROPOSED AMENDMENTS

"Reference Handbook for Site-Specific Assessment of Subsurface Vapor Intrusion to Indoor Air," Electric Power Research Institute (EPRI), Inc., Program No. 1008492, (March 2005).

GPO. Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20401, (202) 783-3238.

USEPA Guidelines for Carcinogenic Risk Assessment, 51 Fed. Reg. 33992-34003 (September 24, 1986).

"Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", USEPA Publication number SW-846 (Third Edition, Final Update IIIA, April 1998), as amended by Updates I, IIA, III, and IIIA (Document No. 955-001-00000-1).

"Methods for the Determination of Organic Compounds in Drinking Water", EPA Publication No. EPA/600/4-88/039 (December 1988 (Revised July 1991)).

"Methods for the Determination of Organic Compounds in Drinking Water, Supplement I", EPA Publication No. EPA/600/4-90/020 (July 1990).

"Methods for the Determination of Organic Compounds in Drinking Water, Supplement II", EPA Publication No. EPA/600/R-92/129 (August 1992).

"Methods for the Determination of Organic Compounds in Drinking Water, Supplement III", EPA Publication No. EPA/600/R-95/131 (August 1995).

"Guidance for Data Quality Assessment, Practical Methods for Data Analysis, EPA QA/G-9, QAOO Update," EPA/600/R-96/084 (July 2000). Available at www.epa.gov/quality/qs-docs/g9-final.pdf.

"Assessment of Vapor Intrusion in Homes Near the Raymark Superfund Site Using Basement and Sub-Slab Air Samples", EPA Publication No. EPA/600/R-05/147 (March 2006).

"Model Standards and Techniques for Control of Radon in New Residential Buildings" EPA Publication No. EPA/402/R-94/009 (March 1994).

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

"Radon Reduction Techniques for Existing Detached Houses: Technical Guidance (Third Edition) for Active Soil Depressurization Systems" EPA Publication No. EPA/625/R-93/011 (October 1993).

Illinois Environmental Protection Agency, 1021 N. Grand Ave East, Springfield, IL 62701 (217) 785-0830.

"A Summary of Selected Background Conditions for Inorganics in Soil", Publication No. IEPA/ENV/94-161, August 1994.

IRIS. Integrated Risk Information System, National Center for Environmental Assessment, U.S. Environmental Protection Agency, 26 West Martin Luther King Drive, MS-190, Cincinnati, OH 45268, (513) 569-7254.

"Reference Dose (RfD): Description and Use in Health Risk Assessments", Background Document 1A (March 15, 1993).

"EPA Approach for Assessing the Risks Associated with Chronic Exposures to Carcinogens", Background Document 2 (January 17, 1992).

Johnson, Paul C. (2005). Identification of Application Specific Critical Inputs for the 1991 Johnson and Ettinger Vapor Intrusion Algorithm. Ground Water Monitoring and Remediation. 25(1), 63-78.

Murray, Donald M. and Burmaster, David E. (1995). Residential Air Exchange Rates in the United States: Empirical and Estimated Parametric Distributions by Season and Climatic Region. Risk Analysis. 15(4), 459-465.

Nelson, D.W., and L.E. Sommers (1982). Total carbon, organic carbon, and organic matter. In: A.L. Page (ed.), Methods of Soil Analysis. Part 2. Chemical and Microbiological Properties. 2nd Edition, pp. 539-579, American Society of Agronomy. Madison, WI.

NTIS. National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161, (703) 487-4600.

"Calculating Upper Confidence Limits for Exposure Point Concentrations at Hazardous Waste Sites," USEPA Office of Emergency and Remedial Response, OSWER 9285.6-10 (December 2002), PB 2003-104982.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

<u>"Evaluating the Vapor Intrusion to Indoor Air Pathway from Groundwater</u> and Soils," OSWER Draft Guidance. EPA Publication No. EPA/530D-02/004 (November 2002).

"Exposures Factors Handbook, Vol. I: General Factors", EPA Publication No. EPA/600/P-95/002Fa (August 1997).

"Exposures Factors Handbook, Vol. II: Food Ingestion Factors", EPA Publication No. EPA/600/P-95/002Fb (August 1997).

"Exposures Factors Handbook, Vol. III: Activity Factors", EPA Publication No. EPA/600/P-95/002Fc (August 1997).

"Risk Assessment Guidance for Superfund, Vol. I: ; Human Health Evaluation Manual, Supplemental Guidance: Standard Default Exposure Factors", OSWER Directive 9285.6-03 (March 1991).

"Rapid Assessment of Exposure to Particulate Emissions from Surface Contamination Sites," EPA Publication No. EPA/600/8-85/002 (February 1985), PB 85-192219.

"Risk Assessment Guidance for Superfund, Volume I; Human Health Evaluation Manual (Part A)", Interim Final, EPA Publication No. EPA/540/1-89/002 (December 1989).

"Risk Assessment Guidance for Superfund, Volume I; Human Health Evaluation Manual, Supplemental Guidance, Dermal Risk Assessment Interim Guidance", Draft (August 18, 1992).

"Risk Assessment Guidance for Superfund, Vol. I: Human Health Evaluation Manual (Part E, Supplemental Guidance for Dermal Risk Assessment) Interim Final", EPA Publication No. EPA/540/R/99/005 (September 2001 July 2004).

"Risk Assessment Guidance for Superfund, Vol. 1: Human Health Evaluation Manual (Part F, Supplemental Guidance for Inhalation Risk Assessment) Final" EPA Publication No. 540-R-070-002 (January 2009).

"Soil Screening Guidance: Technical Background Document", EPA Publication No. EPA/540/R-95/128, PB 96-963502 (May 1996).

NOTICE OF PROPOSED AMENDMENTS

"Soil Screening Guidance: User's Guide", EPA Publication No. EPA/540/R-96/018, PB 96-963505 (April 1996).

"Superfund Exposure Assessment Manual", EPA Publication No. EPA/540/1-88/001 (April 1988).

"Supplemental Guidance for Developing Soil Screening Levels for Superfund Sites", OSWER Directive 9355.4-24 (December 2002).

<u>"Users Guide for Evaluating Subsurface Vapor Intrusion into Buildings,"</u> <u>EPA. EPA/68/W-02/33, (February 2004).</u>

Polynuclear Aromatic Hydrocarbon Background Study City of Chicago, Tetra Tech Em Inc., 200 E. Randolph Drive, Suite 4700, Chicago, IL 60601, February 24, 2003.

Polycyclic Aromatic Hydrocarbons (PAHs) in Surface Soil in Illinois: Background PAHs, EPRI, Palo Alto, CA, We Energies, Milwaukee, WI, and IEPA, Springfield, IL: 2004. 1011376. EPRI, 3412 Hillview Avenue, Palo Alto, CA 94304, (800) 313-3774.

RCRA Facility Investigation Guidance, Interim Final, developed by USEPA (EPA 530/SW-89-031), 4 volumes (May 1989).

United States Environmental Protection Agency, Office of Environmental Information (2000). "Guidance for Data Quality Assessment, Practical Methods for Data Analysis," EPA QA/G-9, QAOO update. EPA Publication No. EPA/600/R-96-084. (Available online at www.epa.gov/oswer/riskassessment/pdf/ucl.pdf).

United States Environmental Protection Agency, Office of Solid Waste and Emergency Response (2003). "Human Health Toxicity Values in Superfund Risk Assessments," OSWER Directive 9285.7-53. (Available online at http://www.epa.gov/oswer/riskassessment/pdf/hhmemo.pdf).

United States Environmental Protection Agency, Compendium of Methods for Determination of Toxic Organic Compounds in Ambient Air, Second Edition, EPA Publication No. EPA/625/R-96/010b, January 1999 available at http://www.epa.gov/ttnamti1/files/ambient/airtox/tocomp99.pdf.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

United States Environmental Protection Agency, Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, SW-846 through Revision IVB (February 2007) available at http://www.epa.gov/sw-846/main.htm.

<u>United States Environmental Protection Agency, CFR Promulgated Test Methods</u>, <u>Methods 3C and 16, Technology Transfer Network, Emission Measurement</u> <u>Center, (2007) available at http://www.epa.gov/ttn/emc/promgate.html.</u>

United States Environmental Protection Agency (2005). "Guidelines for Carcinogen Risk Assessment (2005)". U. S. Environmental Protection Agency, Washington, DC, EPA Publication No. EPA/630/P-03/001F, 2005. (Available online at http://cfpub.epa.gov/ncea/raf/recordisplay.cfm?deid=116283).

"Vapor Intrusion Pathway: A Practical Guide," Technical and Regulatory Guidance. Interstate Technology and Regulatory Council (January 2007).

b) CFR (Code of Federal Regulations). Available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402 (202)783-3238:

40 CFR 761 (1998).

c) This Section incorporates no later editions or amendments.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.220 Determination of Soil Saturation Limit

- a) For any organic contaminant that has a melting point below 30°C, the remediation objective for the <u>outdoor</u> inhalation exposure route developed under Tier 2 shall not exceed the soil saturation limit, as determined under subsection (c) of this Section.
- b) For any organic contaminant that has a melting point below 30°C, the remediation objective under Tier 2 for the soil component of the groundwater ingestion exposure route shall not exceed the soil saturation limit, as determined under subsection (c) of this Section.
- c) The soil saturation limit shall be:
 - 1) The value listed in Appendix A, Table A for that specific contaminant;.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 2) A value derived from Equation S29 in Appendix C, Table A; or
- 3) A value derived from another method approved by the Agency.

(Source: Amended at 36 Ill. Reg. ____, effective _____)

Section 742.222 Determination of Soil Vapor Saturation Limit

- a) For any volatile chemical, the soil gas remediation objective for the indoor and outdoor inhalation exposure routes developed under Tier 2 shall not exceed the soil vapor saturation limit, as determined under subsection (b) of this Section.
- b) The soil vapor saturation limit shall be:
 - 1) The value listed in Appendix A, Table K for that specific contaminant;
 - 2) A value derived from Equation J&E5 in Appendix C, Table L; or
 - 3) A value derived from another method approved by the Agency.

(Source: Added at 36 Ill. Reg. ____, effective _____)

Section 742.225 Demonstration of Compliance with <u>Soil and Groundwater</u> Remediation Objectives

Compliance <u>with soil and groundwater remediation objectives</u> is achieved if each sample result does not exceed that respective remediation objective unless a person elects to proceed under subsections (c), (d) and (e) of this Section.

- a) Compliance with groundwater remediation objectives developed under Subparts D through F and H through I shall be demonstrated by comparing the contaminant concentrations of discrete samples at each sample point to the applicable groundwater remediation objective. Sample points shall be determined by the program under which remediation is performed.
- b) Unless the person elects to composite samples or average sampling results as provided in subsections (c) and (d) of this Section, compliance with soil remediation objectives developed under Subparts D through G and I shall be demonstrated by comparing the contaminant concentrations of discrete samples to the applicable soil remediation objective.

- 1) Except as provided in subsections (c) and (d) of this Section, compositing of samples is not allowed.
- 2) Except as provided in subsections (c) and (d) of this Section, averaging of sample results is not allowed.
- 3) Notwithstanding subsections (c) and (d) of this Section, compositing of samples and averaging of sample results is not allowed for the construction worker population.
- 4) The number of sampling points required to demonstrate compliance is determined by the requirements applicable to the program under which remediation is performed.
- c) If a person chooses to composite soil samples or average soil sample results to demonstrate compliance relative to the soil component of the groundwater ingestion exposure route, the following requirements apply:
 - A minimum of two sampling locations for every 0.5 acre of contaminated area is required, with discrete samples at each sample location obtained at every two feet of depth, beginning at six inches below the ground surface for surface contamination and at the upper limit of contamination for subsurface contamination and continuing through the zone of contamination. Alternatively, a sampling method may be approved by the Agency based on an appropriately designed site-specific evaluation. Samples obtained at or below the water table shall not be used in compositing or averaging.
 - 2) For contaminants of concern other than volatile organic contaminants chemicals:
 - A) Discrete samples from the same boring may be composited; or
 - B) Discrete sample results from the same boring may be averaged.
 - 3) For volatile organic contaminants chemicals:
 - A) Compositing of samples is not allowed.
 - B) Discrete sample results from the same boring may be averaged.

POLLUTION CONTROL BOARD

- 4) Composite samples may not be averaged. An arithmetic average may be calculated for discrete samples collected at every two feet of depth through the zone of contamination as specified above in Section 742.225(c)(1) of this Section.
- d) If a person chooses to composite soil samples or average soil sample results to demonstrate compliance relative to the <u>outdoor inhalation</u> exposure route or ingestion exposure routes, the following requirements apply:
 - 1) A person shall submit a sampling plan for Agency approval, based upon a site-specific evaluation;
 - 2) For volatile organic compounds chemicals, compositing of samples is not allowed; and
 - 3) All samples shall be collected within the contaminated area.
 - 4) Composite samples may not be averaged. Procedures specified in "Calculating Upper Confidence Limits for Exposure Point Concentrations at Hazardous Waste Sites", USEPA Office of Emergency and Remedial Response, OSWER 9285.6-10 (December 2002), as incorporated by reference in Section 742.210, or an alternative procedure approved by the Agency, shall be used to determine sample averages.
- e) When averaging under this Section, if no more than 15% of sample results are reported as "non-detect", "no contamination", "below detection limits", or similar terms, such results shall be included in the averaging calculations as one-half the reported analytical detection limit for the contaminant. However, when performing a test for normal or lognormal distribution for the purpose of calculating a 95% Upper Confidence Limit of the mean for a contaminant, a person may substitute for each non-detect value a randomly generated value between, but not including, zero and the reported analytical detection limit. If more than 15% of sample results are "non-detect", procedures specified in "Guidance for Data Quality Assessment, Practical Methods for Data Analysis, EPA QA/G-9, QA00 Update", EPA/600/R-96/084 (July 2000), as incorporated by reference in Section 742.210, or an alternative procedure approved by the Agency shall be used to address the non-detect values, or another statistically valid procedure approved by the Agency may be used to determine an average.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

f) All soil samples collected after August 15, 2001, shall be reported on a dry weight basis for the purpose of demonstrating compliance, with the exception of the TCLP and SPLP and the property pH.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

<u>Section 742.227</u> <u>Demonstration of Compliance with Soil Gas Remediation Objectives for</u> the Outdoor and Indoor Inhalation Exposure Routes

Compliance shall be demonstrated by comparing the contaminant concentrations of discrete samples at each sample point to the applicable soil gas remediation objective. As specified in Section 742.510(c), the soil gas remediation objectives for the outdoor inhalation exposure route are contained in Appendix B, Table G. As specified in Section 742.515, the soil gas remediation objectives for the indoor inhalation exposure route are contained in Appendix B, Tables H and I. Section 742.227 applies to exterior soil gas samples or near-slab samples collected outside a building. Proposals to use sub-slab soil gas data for the indoor inhalation exposure route shall follow Section 742.935(c).

- a) Sample points shall be determined by the program under which remediation is <u>performed.</u>
- b) When collecting soil gas samples:
 - 1) Use rigid-wall tubing made of nylon or Teflon® or other material approved by the Agency;
 - <u>Use gas-tight, inert containers to hold the sample. For light sensitive or</u> halogenated volatile chemicals, these containers shall be opaque or darkcolored;
 - 3) Purge three volumes before obtaining each discrete soil gas sample;
 - 4) Use a helium tracer or other leak apparatus detection system approved by the Agency; and
 - 5) Limit the flow rate to 200 ml/min.
- c) Soil gas samples shall be analyzed using a National Environmental Laboratory Accreditation Program (NELAP) certified laboratory.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

<u>d)</u> Soil gas remediation objectives shall be compared to concentrations of soil gas collected at a depth at least 3 feet below ground surface and above the saturated zone.

(Source: Added at 36 Ill. Reg. ____, effective ____)

SUBPART C: EXPOSURE ROUTE EVALUATIONS

Section 742.305 Contaminant Source and Free Product Determination

No exposure route shall be excluded from consideration relative to a contaminant of concern unless the following requirements are met:

- a) The sum of the concentrations of all organic contaminants of concern shall not exceed the attenuation capacity of the soil as determined under Section 742.215;
- b) The concentrations of any organic contaminants of concern remaining in the soil shall not exceed the soil saturation limit as determined under Section 742.220;
- c) Any soil which contains contaminants of concern shall not exhibit any of the characteristics of reactivity for hazardous waste as determined under 35 Ill. Adm. Code 721.123;
- Any soil which contains contaminants of concern shall not exhibit a pH less than or equal to 2.0 or greater than or equal to 12.5, as determined by SW-846 Method 9040B: pH Electrometric for soils with 20% or greater aqueous (moisture) content or by SW-846 Method 9045C: Soil pH for soils with less than 20% aqueous (moisture) content as incorporated by reference in Section 742.210;
- e) Any soil which contains contaminants of concern in the following list of inorganic chemicals or their salts shall not exhibit any of the characteristics of toxicity for hazardous waste as determined by 35 Ill. Adm. Code 721.124: arsenic, barium, cadmium, chromium, lead, mercury, selenium or silver; and
- f) If contaminants of concern include polychlorinated biphenyls (PCBs), the concentration of any PCBs in the soil shall not exceed 50 parts per million as determined by SW-846 Methods; and
- g) The concentration of any contaminant of concern in soil gas shall not exceed 10% of its Lower Explosive Limit (LEL) as measured by a hand held combustible gas indicator that has been calibrated to manufacturer specifications.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.310 <u>Outdoor</u> Inhalation Exposure Route

The <u>outdoor</u> inhalation exposure route may be excluded from consideration if:

- <u>a)</u> The following requirements in subsections (a)(1) or (a)(2) are met:
 - 1) An approved engineered barrier is in place that meets the requirements of Subpart K; or
 - 2) The only contaminants of concern are benzene, toluene, ethylbenzene, and total xylenes, and a demonstration of active biodegradation has been made for benzene, toluene, ethylbenzene, and total xylenes such that no outdoor inhalation exposure will occur. This demonstration shall be submitted to the Agency for review and approval;
- <u>ba</u>) The requirements of Sections 742.300 and 742.305 are met;
- b) An approved engineered barrier is in place that meets the requirements of Subpart K;
- c) Safety worker precautions for the construction worker are taken if the Tier 1 construction remediation objectives are exceeded; and
- d) An institutional control, in accordance with Subpart J, will be placed on the property.

(Source: Amended at 36 Ill. Reg. _____, effective _____)

Section 742.312 Indoor Inhalation Exposure Route

The indoor inhalation exposure route may be excluded from consideration if:

- a) None of the contaminants of concern are listed on Appendix A, Table J and none of the contaminants of concern are volatile chemicals, as defined in Section 742.200; or
- b) The following requirements in subsections (b)(1)(A) or (B) or (C), and (b)(2) and (b)(3) are met:

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 1) Exclusion options when the contaminants of concern are volatile chemicals:
 - A) No building or man-made pathway exists or will be placed above the contaminated soil gas or groundwater; or
 - <u>B)</u> An approved building control technology is in place or will be placed that meets the requirements of Subpart L; or
 - C) If the contaminants of concerns are benzene, toluene, ethylbenzene, and total xylenes only, a demonstration of active biodegradation has been made for benzene, toluene, ethylbenzene, and total xylenes such that no indoor inhalation exposure will occur. This demonstration shall be submitted to the Agency for review and approval;
- 2) The requirements of Sections 742.300 and 742.305 are met; and
- 3) An institutional control, in accordance with Subpart J, will be placed on the property.

(Source: Added at 36 Ill. Reg. ____, effective _____)

SUBPART D: DETERMINING AREA BACKGROUND

Section 742.405 Determination of Area Background for Soil

- a) Soil sampling results shall be obtained for purposes of determining area background levels in accordance with the following procedures:
 - 1) For volatile organic contaminants chemicals, sample results shall be based on discrete samples;
 - 2) Unless an alternative method is approved by the Agency, for contaminants other than volatile organic contaminants chemicals, sample results shall be based on discrete samples or composite samples. If a person elects to use composite samples, each 0.5 acre of the area to be sampled shall be divided into quadrants and 5 aliquots of equal volume per quadrant shall be composited into 1 sample;

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 3) Samples shall be collected from similar depths and soil types, which shall be consistent with the depths and soil types in which maximum levels of contaminants are found in the areas of known or suspected releases; and
- 4) Samples shall be collected from areas of the site or adjacent to the site that are unaffected by known or suspected releases at or from the site. If the sample results show an impact from releases at or from the site, then the sample results shall not be included in determining area background levels under this Part.
- b) Area background shall be determined according to one of the following approaches:
 - 1) Statewide Area Background Approach:
 - A) The concentrations of inorganic chemicals in background soils listed in Appendix A, Table G may be used as the upper limit of the area background concentration for the site. The first column to the right of the chemical name presents inorganic chemicals in background soils for counties within Metropolitan Statistical Areas. Counties within Metropolitan Statistical Areas are identified in Appendix A, Table G, Footnote a. Sites located in counties outside Metropolitan Statistical Areas shall use the concentrations of inorganic chemicals in background soils shown in the second column to the right of the chemical name.
 - B) Soil area background concentrations determined according to this statewide area background approach shall be used as provided in Section 742.415(b) of this Part. For each parameter whose sampling results demonstrate concentrations above those in Appendix A, Table G, the person shall develop appropriate soil remediation objectives in accordance with this Part, or may determine area background in accordance with subsection (b)(2) of this Section.
 - 2) A statistically valid approach for determining area background concentrations appropriate for the characteristics of the data set, and approved by the Agency.

(Source: Amended at 36 Ill. Reg. ____, effective _____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

SUBPART E: TIER 1 EVALUATION

Section 742.500 Tier 1 Evaluation Overview

- a) A Tier 1 evaluation compares the concentration of each contaminant of concern detected at a site to the baseline remediation objectives provided in Appendix B, Tables A, B, C, D, and E. G, H and I. Use of Tier 1 remediation objectives requires only limited site-specific information: concentrations of contaminants of concern, groundwater classification, land use classification, and, if appropriate, soil pH. (See Appendix B, Illustration A.)
- Although Tier 1 allows for differentiation between residential and industrial/commercial property use of a site, an institutional control under Subpart J is required where remediation objectives are based on an industrial/commercial property use.
- c) Any given exposure route is not a concern if the concentration of each contaminant of concern detected at the site is below the Tier 1 value of that given route. In such a case, no further evaluation of that route is necessary.

(Source: Amended at 36 Ill. Reg. _____, effective _____)

Section 742.505 Tier 1 Soil, Soil Gas and Groundwater Remediation Objectives

- a) Soil
 - 1) <u>Outdoor</u> Inhalation Exposure Route
 - A) The Tier 1 soil remediation objectives for this exposure route based upon residential property use are listed in Appendix B, Table A.
 - B) The Tier 1 soil remediation objectives for this exposure route based upon industrial/commercial property use are listed in Appendix B, Table B. Soil remediation objective determinations relying on this table require use of institutional controls in accordance with Subpart J.
 - <u>C)</u> For this exposure route, it is acceptable to determine compliance by meeting either the soil or soil gas remediation objectives.

POLLUTION CONTROL BOARD

- 2) Ingestion Exposure Route
 - A) The Tier 1 soil remediation objectives for this exposure route based upon residential property use are listed in Appendix B, Table A.
 - B) The Tier 1 soil remediation objectives for this exposure route based upon industrial/commercial property use are listed in Appendix B, Table B. Soil remediation objective determinations relying on this table require use of institutional controls in accordance with Subpart J.
- 3) Soil Component of the Groundwater Ingestion Route
 - A) The Tier 1 soil remediation objectives for this exposure route based upon residential property use are listed in Appendix B, Table A.
 - B) The Tier 1 soil remediation objectives for this exposure route based upon industrial/commercial property use are listed in Appendix B, Table B.
 - C) The pH-dependent Tier 1 soil remediation objectives for identified ionizable organics or inorganics for the soil component of the groundwater ingestion exposure route (based on the total amount of contaminants present in the soil sample results and groundwater classification) are provided in Appendix B, Tables C and D.
 - D) Values used to calculate the Tier 1 soil remediation objectives for this exposure route are listed in Appendix B, Table F.
- 4) Evaluation of the dermal contact with soil exposure route is not required under Tier 1.
- b) <u>Soil Gas</u>
 - 1) Outdoor Inhalation Exposure Route
 - <u>A)</u> The Tier 1 soil gas remediation objectives for this exposure route based upon residential property use are listed in Appendix B, Table <u>G</u>.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- B) The Tier 1 soil gas remediation objectives for this exposure route based upon industrial/commercial property use, including the construction worker population, are listed in Appendix B, Table G. Soil gas remediation objective determinations relying on an industrial/commercial scenario require use of institutional controls in accordance with Subpart J.
- <u>C)</u> For this exposure route, it is acceptable to determine compliance by meeting either the soil or soil gas remediation objectives.

2) Indoor Inhalation Exposure Route

- A) The Tier 1 soil gas remediation objectives for this exposure route are listed in Appendix B, Tables H and I.
- <u>C)</u> <u>Appendix B, Table H shall be used when soil or groundwater</u> <u>contamination is within 5 feet, vertically or horizontally, of an</u> <u>existing or potential building or man-made pathway. In this</u> <u>scenario, the mode of contaminant transport is both diffusion and</u> <u>advection, which sets the Q_{soil} value at 83.33 cm³/sec.</u>
- D) Appendix B, Table I shall be used when soil and groundwater contamination are more than 5 feet, vertically and horizontally, from an existing or potential building or man-made pathway. In this scenario, the mode of contaminant transport is diffusion only, which sets the Q_{soil} value at 0.0 cm³/sec. Soil gas remediation objective determinations relying on this table require use of institutional controls in accordance with Subpart J.
- <u>E</u>) To determine whether the Q_{soil} value can be set at 0.0 cm³/sec, the site evaluator shall demonstrate that soil and groundwater within 5 feet, vertically and horizontally, of an existing or potential building or man-made pathway meet the Tier 1 remediation objectives for residential property listed in Appendix B, Table A, and the Tier 1 remediation objectives for Class I groundwater listed in Appendix B, Table E, respectively.

NOTICE OF PROPOSED AMENDMENTS

b c) Groundwater

- 1) The Tier 1 groundwater remediation objectives for the groundwater component of the groundwater ingestion route are listed in Appendix B, Table E.
- 2) The Tier 1 groundwater remediation objectives for this exposure route are given for Class I and Class II groundwaters, respectively.
- 3) The evaluation of 35 Ill. Adm. Code 620.615 regarding mixtures of similar-acting chemicals shall be considered satisfied for Class I groundwater at the point of human exposure if:
 - A) No more than one similar-acting noncarcinogenic chemical as listed in Appendix A, Table E is detected in the groundwater at the site; and
 - B) No carcinogenic contaminant of concern as listed in Appendix A, Table I is detected in any groundwater sample associated with the site, using analytical procedures capable of achieving either the 1 in 1,000,000 cancer risk concentration or the ADL, whichever is greater.
- If the conditions of subsection (c)(3)(b)(3) of this Section are not met, the Class I groundwater remediation objectives set forth in Appendix B, Table E shall be corrected for the cumulative effect of mixtures of similar-acting chemicals using the following methodologies:
 - A) For noncarcinogenic chemicals, the methodologies set forth at Section 742.805(c) or Section 742.915(h) shall be used; and
 - B) For carcinogenic chemicals, the methodologies set forth at Section 742.805(d) or Section 742.915(h) shall be used.
- 5) For the groundwater component of the indoor inhalation exposure route, the Tier 1 groundwater remediation objectives are listed in Appendix B, Tables H and I.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- <u>A)</u> The Tier 1 groundwater remediation objectives for this exposure route are based on a default water-filled soil porosity value of 0.15 cm³/cm³.
- B) Appendix B, Table H shall be used when soil or groundwater contamination is within 5 feet, vertically and horizontally, of an existing or potential building or man-made pathway. In this scenario, the mode of contaminant transport is both diffusion and advection, which sets the Q_{soil} value at 83.33 cm³/sec.
- C) Appendix B, Table I shall be used when soil and groundwater contamination are more than 5 feet, vertically and horizontally, from an existing or potential building or man-made pathway. In this scenario, the mode of contaminant transport is diffusion only, which sets the Q_{soil} value at 0.0 cm³/sec. Groundwater remediation objective determinations relying on this table require use of institutional controls in accordance with Subpart J.
- D) To determine whether the Q_{soil} value can be set at 0.0 cm³/sec, the site evaluator shall demonstrate that soil and groundwater within 5 feet, vertically and horizontally, of an existing or potential building or man-made pathway meet the Tier 1 remediation objectives for residential property listed in Appendix B, Table A, and the Tier 1 remediation objectives for Class I groundwater listed in Appendix B, Table E, respectively.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.510 Tier 1 Remediation Objectives Tables <u>for the Ingestion, Outdoor</u> Inhalation and Soil Component of the Groundwater Ingestion Exposure Routes

- a) Soil remediation objectives are listed in Appendix B, Tables A, B, C and D.
 - 1) Appendix B, Table A is based upon residential property use.
 - A) The first column to the right of the chemical name lists soil remediation objectives for the soil ingestion exposure route.
 - B) The second column lists the soil remediation objectives for the <u>outdoor</u> inhalation exposure route.

POLLUTION CONTROL BOARD

- C) The third and fourth columns list soil remediation objectives for the soil component of the groundwater ingestion exposure route for the respective classes of groundwater:
 - i) Class I groundwater; and
 - ii) Class II groundwater.
- D) The final column lists the Acceptable Detection Limit (ADL), only where applicable.
- 2) Appendix B, Table B is based upon industrial/commercial property use.
 - A) The first and third columns to the right of the chemical name list the soil remediation objectives for the soil ingestion exposure route based on two receptor populations:
 - i) Industrial/commercial; and
 - ii) Construction worker.
 - B) The second and fourth columns to the right of the chemical name list the soil remediation objectives for the <u>outdoor</u> inhalation exposure route based on two receptor populations:
 - i) Industrial/commercial; and
 - ii) Construction worker.
 - C) The fifth and sixth columns to the right of the chemical name list the soil remediation objectives for the soil component of the groundwater ingestion exposure route for two classes of groundwater:
 - i) Class I groundwater; and
 - ii) Class II groundwater.
 - D) The final column lists the acceptable detection limit (ADL), only where applicable.

- 3) Appendix B, Tables C and D set forth pH specific soil remediation objectives for inorganic and ionizing organic chemicals for the soil component of the groundwater ingestion route.
 - A) Table C sets forth remediation objectives based on Class I groundwater and Table D sets forth remediation objectives based on Class II groundwater.
 - B) The first column in Tables C and D lists the chemical names.
 - C) The second through ninth columns to the right of the chemical names list the pH based soil remediation objectives.
- 4) For the inorganic chemicals listed in Appendix B, Tables A and B, the soil component of the groundwater ingestion exposure route shall be evaluated using TCLP (SW-846 Method 1311) or SPLP (SW-846 Method 1312), incorporated by reference at Section 742.210 unless a person chooses to evaluate the soil component on the basis of the total amount of contaminant in a soil sample result in accordance with subsection (a)(5) of this Section.
- 5) For those inorganic and ionizing organic chemicals listed in Appendix B, Tables C and D, if a person elects to evaluate the soil component of the groundwater ingestion exposure route based on the total amount of contaminant in a soil sample result (rather than TCLP or SPLP analysis), the person shall determine the soil pH at the site and then select the appropriate soil remediation objectives based on Class I and Class II groundwaters from Tables C and D, respectively. If the soil pH is less than 4.5 or greater than 9.0, then Tables C and D cannot be used.
- 6) Unless one or more exposure routes are excluded from consideration under Subpart C, the most stringent soil remediation objective of the exposure routes (i.e., soil ingestion exposure route, <u>outdoor</u> inhalation exposure route, and soil component of the groundwater ingestion exposure route) shall be compared to the concentrations of soil contaminants of concern measured at the site. When using Appendix B, Table B to select soil remediation objectives for the ingestion exposure route and <u>outdoor</u> inhalation exposure routes, the remediation objective shall be the more stringent soil remediation objective of the industrial/commercial populations and construction worker populations.

- 7) Confirmation sample results may be averaged or soil samples may be composited in accordance with Section 742.225.
- 8) If a soil remediation objective for a chemical is less than the ADL, the ADL shall serve as the soil remediation objective.
- b) Groundwater remediation objectives for the groundwater component of the groundwater ingestion exposure route are listed in Appendix B, Table E. However, Appendix B, Table E must be corrected for cumulative effect of mixtures of similar-acting noncarcinogenic chemicals as set forth in Section Sections 742.505(c)(3) and (c)(4).
 - 1) The first column to the right of the chemical name lists groundwater remediation objectives for Class I groundwater, and the second column lists the groundwater remediation objectives for Class II groundwater.
 - 2) To use Appendix B, Table E of this Part, the 35 Ill. Adm. Code 620 classification for groundwater at the site shall be determined. The concentrations of groundwater contaminants of concern at the site are compared to the applicable Tier 1 groundwater remediation objectives for the groundwater component of the groundwater ingestion exposure route in Appendix B, Table E.
- c) Soil gas remediation objectives for the outdoor inhalation exposure route are listed in Appendix B, Table G.
 - 1) The first column to the right of the chemical name lists the soil gas remediation objectives for residential populations.
 - 2) The second and third columns to the right of the chemical names list the soil gas remediation objectives for the outdoor inhalation exposure route based on two receptor populations:
 - A) Industrial/commercial; and
 - B) Construction worker.
- ed) For contaminants of concern not listed in Appendix B, Tables A, B and , E, and <u>G</u>, a person may request site-specific remediation objectives from the Agency or propose site-specific remediation objectives in accordance with 35 Ill. Adm. Code 620, Subpart I of this Part, or both.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.515 <u>Tier 1 Remediation Objectives Tables for the Indoor Inhalation Exposure</u> <u>Route</u>

- a) When the mode of contaminant transport is both diffusion and advection as described in Section 742.505 (i.e., soil or groundwater contamination is within 5 feet of an existing or potential building or man-made pathway), the remediation objectives for soil gas and groundwater listed in Appendix B, Table H shall be used.
 - 1) The first column to the right of the chemical name lists the soil gas remediation objectives for residential receptors.
 - 2) The second column lists the soil gas remediation objectives for industrial/commercial receptors.
 - 3) The third column lists the groundwater remediation objectives for residential receptors.
 - 4) The fourth column lists the groundwater remediation objectives for industrial/commercial receptors.
- b) When the mode of contaminant transport is diffusion only as described in Section 742.505 (i.e., soil and groundwater contamination are more than 5 feet from an existing or potential building or man-made pathway), the remediation objectives for soil gas and groundwater listed in Appendix B, Table I shall be used. Remediation objectives relying on this table require use of institutional controls in accordance with Subpart J.
 - 1) The first column to the right of the chemical name lists the soil gas remediation objectives for residential receptors.
 - 2) The second column lists the soil gas remediation objectives for industrial/commercial receptors.
 - 3) The third column lists the groundwater remediation objectives for residential receptors.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 4) The fourth column lists the groundwater remediation objectives for industrial/commercial receptors.
- c) If using Appendix B, Table H, compliance is determined by meeting either the soil gas remediation objectives or the groundwater remediation objectives.
- <u>d)</u> If using Appendix B, Table I, compliance is determined by meeting both the soil gas remediation objectives and the groundwater remediation objectives.
- e) For volatile chemicals not listed in Appendix B, Table H or I, a person may request site-specific remediation objectives from the Agency or propose sitespecific remediation objectives in accordance with Subpart I of this Part, or both.

(Source: Added at 36 Ill. Reg. ____, effective _____)

SUBPART F: TIER 2 GENERAL EVALUATION

Section 742.600 Tier 2 Evaluation Overview

- a) Tier 2 remediation objectives are developed through the use of equations which allow site-specific data to be used. (See Appendix C, Illustrations A and B.) The equations, identified in Appendix C, Tables A, and C, and L may be used to develop Tier 2 remediation objectives.
- b) Tier 2 evaluation is only required for contaminants of concern and corresponding exposure routes (except where excluded from further consideration under Subpart C) exceeding the Tier 1 remediation objectives. When conducting Tier 2 evaluations, the values used in the calculations must have the appropriate units of measure as identified in Appendix C, Tables B, and D, and M.
- c) Any development of remediation objectives using site-specific information or equations outside the Tier 2 framework shall be evaluated under Tier 3.
- d) Any development of a remediation objective under Tier 2 shall not use a target hazard quotient greater than one at the point of human exposure or a target cancer risk greater than 1 in 1,000,000 at the point of human exposure.
- e) In conducting a Tier 2 evaluation, the following conditions shall be met:

- 1) For each discrete sample, the total soil contaminant concentration of either a single contaminant or multiple contaminants of concern shall not exceed the attenuation capacity of the soil as provided in Section 742.215.
- 2) Remediation objectives for noncarcinogenic compounds which affect the same target organ, organ system or similar mode of action shall meet the requirements of Section 742.720.
- 3) The soil remediation objectives based on the <u>outdoor inhalation exposure</u> <u>route</u> and the soil component of the groundwater ingestion exposure routes shall not exceed the soil saturation limit as provided in Section 742.220.
- 4) The soil gas remediation objectives based on the indoor and outdoor inhalation exposure routes shall not exceed the soil vapor saturation limit as provided in Section 742.222.
- $\frac{f}{1} \qquad \frac{\text{Tier 2 remediation objectives for the indoor inhalation exposure route shall be calculated for either soil gas or groundwater if a Q_{soil} value of 83.33 cm³/sec is used.}$
- g) Tier 2 remediation objectives for the indoor inhalation exposure route shall be calculated for both soil gas and groundwater if a Q_{soil} value of 0.0 cm³/sec is used.
- f)h) If the calculated Tier 2 soil remediation objective for an applicable exposure route is more stringent than the corresponding Tier 1 remediation objective, then the Tier 1 remediation objective applies.
- <u>g)i)</u> If the calculated Tier 2 soil remediation objective for an exposure route is more stringent than the Tier 1 soil remediation objective(s) for the other exposure routes, then the Tier 2 calculated soil remediation objective applies and Tier 2 soil remediation objectives for the other exposure routes are not required.
- h)j) If the calculated Tier 2 soil remediation objective is less stringent than one or more of the soil remediation objectives for the remaining exposure routes, then the Tier 2 values are calculated for the remaining exposure route(s) and the most stringent Tier 2 calculated value applies.
- <u>k</u>) If a contaminant has both carcinogenic and noncarcinogenic effects for any applicable exposure route or receptor, remediation objectives shall be calculated for each effect and the more stringent remediation objective shall apply. The toxicological-specific information is described in Section 742.705(d).

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.605 Land Use

- a) Present and post-remediation land use is evaluated in a Tier 2 evaluation. Acceptable exposure factors for the Tier 2 evaluation for residential, industrial/commercial, and construction worker populations are provided in the far right column of Appendix C, Tables B, and D, and M. Use of exposure factors different from those in Appendix C, Tables B, and D, and M must be approved by the Agency as part of a Tier 3 evaluation.
- b) If a Tier 2 evaluation is based on an industrial/commercial property use, then:
 - 1) Construction worker populations shall also be evaluated, except for the indoor inhalation exposure route; and
 - 2) Institutional controls are required in accordance with Subpart J.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.610 Chemical and Site Properties

a) Physical and Chemical Properties of Contaminants

Tier 2 evaluations require information on the physical and chemical properties of the contaminants of concern. The physical and chemical properties used in a Tier 2 evaluation are contained in Appendix C, Table E. If the site has contaminants not included in this table, a person may request the Agency to provide the applicable physical and chemical input values or may propose input values under Subpart I. If a person proposes to apply values other than those in Appendix C, Table E, or those provided by the Agency, the evaluation shall be considered under Tier 3.

- b) Soil and Groundwater Parameters
 - A Tier 2 evaluation requires examination of soil and groundwater parameters. The parameters that may be varied, and the conditions under which these parameters are determined as part of Tier 2, are summarized in Appendix C, Tables B, and D, and M. If a person proposes to vary site-

NOTICE OF PROPOSED AMENDMENTS

specific parameters outside of the framework of these tables, the evaluation shall be considered under Tier 3.

- 2) To determine site-specific physical soil parameters, a minimum of one boring per 0.5 acre of contamination shall be collected. This boring must be deep enough to allow the collection of the required field measurements. The site-specific physical soil parameters must be determined from the portion of the boring representing the stratigraphic unit(s) being evaluated. For example, if evaluating the soil component of the groundwater ingestion exposure route, two samples from the boring will be required:
 - A) A sample of the predominant soil type for the vadose zone; and
 - B) A sample of the predominant soil type for the saturated zone.
- 3) A site-specific SSL dilution factor (used in developing soil remediation objectives based upon the protection of groundwater) may be determined by substituting site information in Equation S22 in Appendix C, Table A. To make this demonstration, a minimum of three monitoring wells shall be used to determine the hydraulic gradient. As an alternative, the default dilution factor value listed in Appendix C, Table B may be used. If monitoring wells are used to determine the hydraulic gradient, the soil taken from the borings shall be visually inspected to ensure there are no significant differences in the stratigraphy. If there are similar soil types in the field, one boring shall be used to determine the site-specific physical soil parameters. If there are significant differences, all of the borings shall be evaluated before determining the site-specific physical soil parameters for the site.
- 4) Not all of the parameters identified in Appendix C, Tables B, and D, and <u>M</u> need to be determined on a site-specific basis. A person may choose to collect partial site-specific information and use default values as listed in Appendix C, Tables B, and D, and M for the rest of the parameters.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

SUBPART G: TIER 2 SOIL AND SOIL GAS EVALUATION

Section 742.700 Tier 2 Soil Evaluation Overview

POLLUTION CONTROL BOARD

- a) Tier 2 remediation objectives are developed through the use of models which allow site-specific data to be considered. Appendix C, Tables A, and C, and L list equations that shall be used under a Tier 2 evaluation to calculate soil remediation objectives prescribed by SSL, and RBCA, and the modified J&E models, respectively. (See also Appendix C, Illustration A.)
- b) Appendix C, Table A lists equations that are used under the SSL model. (See also Appendix C, Illustration A.) The SSL model has equations to evaluate the following human exposure routes:
 - 1) Soil ingestion exposure route;
 - 2) <u>Outdoor</u> Inhalation exposure route for:; and
 - A) Organic contaminants;
 - B) Fugitive dust; and
 - 3) Soil component of the groundwater ingestion exposure route.
- c) Evaluation of the dermal exposure route is not required under the SSL model.
- d) Appendix C, Table C lists equations that are used under the RBCA model. (See also Appendix C, Illustration A.) The RBCA model has equations to evaluate human exposure based on the following:
 - 1) The combined exposure routes of <u>outdoor</u> inhalation of vapors and particulates, soil ingestion and dermal contact with soil;
 - 2) The ambient vapor inhalation (outdoor) <u>outdoor inhalation exposure</u> route from subsurface soils;
- e) Appendix C, Table L lists equations that are used under the modified J&E model. The modified J&E model has equations to evaluate human exposure by the indoor inhalation exposure route. The modified model allows for the development of soil gas remediation objectives.
- <u>f</u>) e) The equations in either Appendix C, Table A, or C, or L may be used to calculate remediation objectives for each contaminant of concern under Tier 2, if the following requirements are met:

- λ= first order degradation constant obtained from AppendixC, Table E or from measured groundwater data
- $S_w =$ width of planar groundwater source in the y direction
- $S_d =$ depth of planar groundwater source in the z direction
- The following parameters are determined through field measurements: U, K, I, θT, Sw, Sd.
 - A) The determination of values for U, K, I and θ_T can be obtained through the appropriate laboratory and field techniques;
 - B) From the immediate down-gradient edge of the source of the groundwater contamination values for Sw and Sd shall be determined. Sw is defined as the width of groundwater at the source which exceeds the Tier 1 groundwater remediation objective. Sd is defined as the depth of groundwater at the source which exceeds the Tier 1 groundwater remediation objective; and
 - C) Total soil porosity can also be calculated using Equation R23.
- b) Once values are obtained for all the input parameters identified in subsection (a) of this Section, the contaminant concentration Cx along the centerline of the plume at a distance X from the source shall be calculated so that X is the distance from the down-gradient edge of the source of the contamination at the site to the point where the contaminant concentration is equal to the Tier 1 groundwater remediation objective or concentration determined according to the procedures specified in 35 Ill. Adm. Code 620, Subpart F.
 - If there are any potable water supply wells located within the calculated distance X, then the Tier 1 groundwater remediation objective or concentration shall be met at the edge of the minimum or designated maximum setback zone of the nearest potable water supply down-gradient of the source. To demonstrate that a minimum or maximum setback zone of a potable water supply well will not be impacted above the applicable Tier 1 groundwater remediation objective or concentration determined according to the procedures specified in 35 Ill. Adm. Code 620, Subpart F, X shall be the distance from the Csource location to the edge of the setback zone.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 1) The Tier 2 soil <u>or soil gas</u> remediation objectives for the ingestion and <u>outdoor</u> inhalation exposure routes shall use the applicable equations from the same approach (i.e., SSL equations in Appendix C, Table C). For the indoor inhalation exposure route, only the J&E equations can be used.
- 2) The equations used to calculate soil remediation objectives for the soil component of the groundwater ingestion exposure route are not dependent on the approach utilized to calculate soil remediation objectives for the other exposure routes. For example, it is acceptable to use the SSL equations for calculating Tier 2 soil remediation objectives for the ingestion and <u>outdoor</u> inhalation exposure routes, and the RBCA equations for calculating Tier 2 soil remediation objectives for the soil component of the groundwater ingestion exposure route.
- 3) Combining equations from Appendix C, Tables A, and C, and L to form a new model is not allowed. In addition, Appendix C, Tables A, and C, and L must use their own applicable parameters identified in Appendix C, Tables B, and D, and M, respectively.
- g) f) In calculating soil or soil gas remediation objectives for industrial/commercial property use, applicable calculations shall be performed twice: once using industrial/commercial population default values and once using construction worker population default values. The more stringent soil or soil gas remediation objectives derived from these calculations must be used for further Tier 2 evaluations. The indoor inhalation exposure route does not apply to the construction worker population.
- h) g) Tier 2 data sheets provided by the Agency shall be used to present calculated Tier 2 remediation objectives, if required by the particular program for which remediation is being performed.
- i) h) The RBCA equations which rely on the parameter Soil Water Sorption Coefficient (k_s) can only be used for ionizing organics and inorganics by substituting values for k_s from Appendix C, Tables I and J, respectively. This will also require the determination of a site-specific value for soil pH.
- j) For the outdoor inhalation exposure route, it is acceptable to use either 742.710 to develop a soil remediation objective or 742.712 to develop a soil gas remediation objective to determine compliance with the pathway.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

NOTICE OF PROPOSED AMENDMENTS

Section 742.705 Parameters for Soil Remediation Objective Equations

- a) Appendix C, Tables B, and D, and M list the input parameters for the SSL, and RBCA, and J&E equations, respectively. The first column lists each symbol as it is presented in the equation. The next column defines the parameters. The third column shows the units for the parameters. The fourth column identifies where information on the parameters can be obtained (i.e., field measurement, applicable equation(s), reference source, or default value). The last column identifies how the parameters can be generated.
- b) Default Values

Default values are numerical values specified for use in the Tier 2 equations. The fourth column of Appendix C, Tables B, and D, and M denotes if the default values are from the SSL model, RBCA model, the modified J&E model or some other source. The last column of Appendix C, Tables B, and D, and M lists the numerical values for the default values used in the SSL, and RBCA, and J&E equations, respectively.

c) Site-specific Information

Site-specific information is a parameter measured, obtained, or determined from the site to calculate Tier 2 remediation objectives. The fourth column of Appendix C, Tables B, and D, and M identifies those site-specific parameters that may require direct field measurement. For some parameters, numerical default inputs have been provided in the last column of Appendix C, Tables B, and D, and M to substitute for site-specific information. In some cases, information on the receptor or soil type is required to select the applicable numerical default inputs. Site-specific information includes:

- Physical soil parameters identified in Appendix C, Table F. The second column identifies the location where the sample is to be collected. Acceptable methods for measuring or calculating these soil parameters are identified in the last column of Appendix C, Table F;
- 2) Institutional controls or engineered barriers, pursuant to Subparts J and K, describe applicable institutional controls and engineered barriers under a Tier 2 evaluation; and
- 3) Land use classification

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

d) Toxicological-specific Information

- 1) Toxicological-specific information is used to calculate Tier 2 remediation objectives for the following parameters, if applicable:
 - A) Oral Chronic Reference Dose (RfD_o, expressed in mg/kg-d);
 - B) Oral Subchronic Reference Dose (RfD_s, expressed in mg/kg-d, shall be used for construction worker remediation objective calculations);
 - C) Oral Slope Factor (SF_o, expressed in $(mg/kg-d)^{-1}$);
 - D) Inhalation Unit Risk Factor (URF expressed in $(\mu g/m^3)^{-1}$);
 - E) Inhalation Chronic Reference Concentration (RfC, expressed in mg/m³);
 - F) Inhalation Subchronic Reference Concentration (RfC_s, expressed in mg/m³, shall be used for construction worker remediation objective calculations);
 - G) Inhalation Chronic Reference Dose (RfD_i, expressed in mg/kg-d);
 - H) Inhalation Subchronic Reference Dose (RfD_{is}, expressed in mg/kgd, shall be used for construction worker remediation objective calculations); and
 - I) Inhalation Slope Factor $(SF_i, expressed in (mg/kg-d)^{-1});$
- 2) Toxicological information can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210, or the program under which the remediation is being performed.
- e) Chemical-specific Information

Chemical-specific information used to calculate Tier 2 remediation objectives is listed in Appendix C, Table E.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

f) Calculations

Calculating numerical values for some parameters requires the use of equations listed in Appendix C, Table A, Θr C, and L. The parameters that are calculated are listed in Appendix C, Tables B, and D, and M.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.710 SSL Soil Equations

- a) This Section sets forth the equations and parameters used to develop Tier 2 soil remediation objectives for the three exposure routes using the SSL approach.
- b) Soil Ingestion Exposure Route
 - Equations S1 through S3 form the basis for calculating Tier 2 remediation objectives for the soil ingestion exposure route using the SSL approach. Equation S1 is used to calculate soil remediation objectives for noncarcinogenic contaminants. Equations S2 and S3 are used to calculate soil remediation objectives for carcinogenic contaminants for residential populations and industrial/commercial and construction worker populations, respectively.
 - 2) For Equations S1 through S3, the SSL default values cannot be modified with site-specific information.
- c) <u>Outdoor</u> Inhalation Exposure Route
 - Equations S4 through S16, S26 and S27 are used to calculate Tier 2 soil remediation objectives for the <u>outdoor</u> inhalation exposure route using the SSL approach. To address this exposure route, organic contaminants and mercury must be evaluated separately from fugitive dust using their own equations set forth in subsections (c)(2) and (c)(3) of this Section, respectively.
 - 2) Organic Contaminants
 - A) Equations S4 through S10 are used to calculate Tier 2 soil remediation objectives for organic contaminants and mercury based on the <u>outdoor</u> inhalation exposure route. Equation S4 is used to calculate soil remediation objectives for noncarcinogenic

NOTICE OF PROPOSED AMENDMENTS

organic contaminants in soil for residential and industrial/commercial populations. Equation S5 is used to calculate soil remediation objectives for noncarcinogenic organic contaminants and mercury in soil for construction worker populations. Equation S6 is used to calculate soil remediation objectives for carcinogenic organic contaminants in soil for residential and industrial/commercial populations. Equation S7 is used to calculate soil remediation objectives for carcinogenic organic contaminants in soil for construction worker populations. Equations S8 through S10, S27 and S28 are used for calculating numerical values for some of the parameters in Equations S4 through S7.

- B) For Equation S4, a numerical value for the Volatilization Factor (VF) can be calculated in accordance with subsection (c)(2)(F) of this Section. The remaining parameters in Equation S4 have either SSL default values listed in Appendix C, Table B or toxicologicalspecific information (i.e., RfC), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- C) For Equation S5, a numerical value for the Volatilization Factor adjusted for Agitation (VF') can be calculated in accordance with subsection (c)(2)(G) of this Section. The remaining parameters in Equation S5 have either SSL default values listed in Appendix C, Table B or toxicological-specific information (i.e., RfC), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- D) For Equation S6, a numerical value for VF can be calculated in accordance with subsection (c)(2)(F) of this Section. The remaining parameters in Equation S6 have either default values listed in Appendix C, Table B or toxicological-specific information (i.e., URF), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.

- E) For Equation S7, a numerical value for VF' can be calculated in accordance with subsection (c)(2)(G) of this Section. The remaining parameters in Equation S7 have either default values listed in Appendix C, Table B or toxicological-specific information (i.e., URF), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- F) The VF can be calculated for residential and industrial/commercial populations using one of the following equations based on the information known about the contaminant source and receptor population:
 - i) Equation S8, in conjunction with Equation S10, is used to calculate VF assuming an infinite source of contamination; or
 - ii) If the area and depth of the contaminant source are known or can be estimated reliably, mass limit considerations may be used to calculate VF using Equation S26.
- G) The VF' can be calculated for the construction worker populations using one of the following equations based on the information known about the contaminant source:
 - i) Equation S9 is used to calculate VF' assuming an infinite source of contamination; or
 - ii) If the area and depth of the contaminant source are known or can be estimated reliably, mass limit considerations may be used to calculate VF' using Equation S27.
- 3) Fugitive Dust
 - A) Equations S11 through S16 are used to calculate Tier 2 soil remediation objectives using the SSL fugitive dust model for the <u>outdoor</u> inhalation exposure route. Equation S11 is used to calculate soil remediation objectives for noncarcinogenic contaminants in fugitive dust for residential and industrial/commercial populations. Equation S12 is used to

NOTICE OF PROPOSED AMENDMENTS

calculate soil remediation objectives for noncarcinogenic contaminants in fugitive dust for construction worker populations. Equation S13 is used to calculate soil remediation objectives for carcinogenic contaminants in fugitive dust for residential and industrial/commercial populations. Equation S14 is used to calculate soil remediation objectives for carcinogenic contaminants in fugitive dust for construction worker populations. Equations S15 and S16 are used for calculating numerical quantities for some of the parameters in Equations S11 through S14.

- B) For Equation S11, a numerical value can be calculated for the Particulate Emission Factor (PEF) using Equation S15. This equation relies on various input parameters from a variety of sources. The remaining parameters in Equation S11 have either SSL default values listed in Appendix C, Table B or toxicologicalspecific information (i.e., RfC), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- C) For Equation S12, a numerical value for the Particulate Emission Factor for Construction Worker (PEF') can be calculated using Equation S16. The remaining parameters in Equation S12 have either SSL default values listed in Appendix C, Table B or toxicological-specific information (i.e., RfC), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- D) For Equation S13, a numerical value for PEF can be calculated using Equation S15. The remaining parameters in Equation S13 have either default values listed in Appendix C, Table B or toxicological-specific information (i.e., URF), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- E) For Equation S14, a numerical value for PEF' can be calculated using Equation S16. The remaining parameters in Equation S14

NOTICE OF PROPOSED AMENDMENTS

have either default values listed in Appendix C, Table B or toxicological-specific information (i.e., URF), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.

d) Soil Component of the Groundwater Ingestion Exposure Route

The Tier 2 remediation objective for the soil component of the groundwater ingestion exposure route can be calculated using one of the following equations based on the information known about the contaminant source and receptor population:

- 1) Equation S17 is used to calculate the remediation objective assuming an infinite source of contamination.
 - A) The numerical quantities for four parameters in Equation S17, the Target Soil Leachate Concentration (C_w), Soil-Water Partition Coefficient (K_d) for non-ionizing organics, Water-Filled Soil Porosity Theta w (θ_w) and Air-Filled Soil Porosity Theta a (θ_a), are calculated using Equations S18, S19, S20 and S21, respectively. Equations S22, S23, S24 and S25 are also needed to calculate numerical values for Equations S18 and S21. The pH-dependent K_d values for ionizing organics can be calculated using Equation S19 and the pH-dependent Koc values in Appendix C, Table I.
 - B) The remaining parameters in Equation S17 are Henry's Law Constant (H'), a chemical specific value listed in Appendix C, Table E and Dry Soil Bulk Density (ρ_b), a site-specific based value listed in Appendix C, Table B.
 - C) The default value for GW_{obj} is the Tier 1 groundwater objective. For chemicals for which there is no Tier 1 groundwater remediation objective, the value for GW_{obj} shall be the concentration determined according to the procedures specified in 35 Ill. Adm. Code 620, Subpart F. As an alternative to using Tier 1 groundwater remediation objectives or concentrations determined according to the procedures specified in 35 Ill. Adm. Code 620, Subpart F₋₂ GW_{obj} may be developed using Equations

NOTICE OF PROPOSED AMENDMENTS

R25 and R26, if approved institutional controls are in place as required in Subpart J.

2) If the area and depth of the contaminant source are known or can be estimated reliably, mass limit considerations may be used to calculate the remediation objective for this exposure route using Equation S28. The parameters in Equation S28 have default values listed in Appendix C, Table B.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.712 SSL Soil Gas Equation for the Outdoor Inhalation Exposure Route

- a) This section sets forth the equation and parameters used to develop Tier 2 soil gas remediation objectives for the outdoor inhalation exposure route using the SSL approach.
- b) Equation S30 is used to calculate Tier 2 soil gas remediation objectives for the outdoor inhalation exposure route for residential, industrial/commercial, and construction worker populations.
- c) Equations S4 through S16, S26 and S27, which calculate Tier 2 soil remediation objectives as described in Section 742.710(c), form the basis for developing the Tier 2 soil gas remediation objectives for the outdoor inhalation exposure route using the SSL model.
- <u>d)</u> The remaining parameters used to calculate Equation S30 are listed in Appendix C, Table B, except for Dimensionless Henry's Law Constant (25° C), a chemical specific value listed in Appendix C, Table E.

(Source: Added at 36 Ill. Reg. ____, effective ____)

Section 742.715 RBCA Soil Equations

- a) This Section presents the RBCA model and describes the equations and parameters used to develop Tier 2 soil remediation objectives.
- b) Ingestion, <u>Outdoor</u> Inhalation, and Dermal Contact
 - 1) The two sets of equations in subsections (b)(2) and (b)(3) of this Section shall be used to generate Tier 2 soil remediation objectives for the

NOTICE OF PROPOSED AMENDMENTS

combined ingestion, <u>outdoor</u> inhalation, and dermal contact with soil exposure routes.

- 2) Combined Exposure Routes of Soil Ingestion, <u>Outdoor</u> Inhalation of Vapors and Particulates, and Dermal Contact with Soil
 - A) Equations R1 and R2 form the basis for deriving Tier 2 remediation objectives for the set of equations that evaluates the combined exposure routes of soil ingestion, outdoor inhalation of vapors and particulates, and dermal contact with soil using the RBCA approach. Equation R1 is used to calculate soil remediation objectives for carcinogenic contaminants. Equation R2 is used to calculate soil remediation objectives for noncarcinogenic contaminants. Soil remediation objectives for the ambient vapor inhalation (outdoor) outdoor inhalation exposure route from subsurface soils must also be calculated in accordance with the procedures outlined in subsection (b)(3) of this Section and compared to the values generated from Equations R1 or R2. The smaller value (i.e., R1 and R2 compared to R7 and R8, respectively) from these calculations is the Tier 2 soil remediation objective for the combined exposure routes of soil ingestion, outdoor inhalation, and dermal contact with soil.
 - B) In Equation R1, numerical values are calculated for two parameters:
 - i) The volatilization factor for surficial soils (VF_{ss}) using Equations R3 and R4; and
 - ii) The volatilization factor for subsurface surficial soils regarding particulates (VF_p) using Equation R5.
 - C) VF_{ss} uses Equations R3 and R4 to derive a numerical value. Equation R3 requires the use of Equation R6. Both equations must be used to calculate the VF_{ss}. The lowest calculated value from these equations must be substituted into Equation R1.
 - D) The remaining parameters in Equation R1 have either default values listed in Appendix C, Table D or toxicological-specific information (i.e., SF_o, SF_i), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as

NOTICE OF PROPOSED AMENDMENTS

incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.

- E) For Equation R2, the parameters VF_{ss} and VF_p are calculated. The remaining parameters in Equation R2 have either default values listed in Appendix C, Table D or toxicological-specific information (i.e., RfD_o , RfD_i), which can be obtained from IRIS by following the guidelines in OSWER Directive 9285.7-53, as incorporated by reference in Section 742.210 or requested from the program under which the remediation is being performed.
- F) For chemicals other than inorganics which do not have default values for the dermal absorption factor (RAF_d) in Appendix C, Table D, a dermal absorption factor of 0.5 shall be used for Equations R1 and R2. For inorganics, dermal absorption may be disregarded (i.e., $RAF_d = 0$).
- 3) Ambient Vapor Inhalation (outdoor) Outdoor Inhalation Exposure Route from Subsurface Soils (soil below one meter)
 - A) Equations R7 and R8 form the basis for deriving Tier 2 remediation objectives for the ambient vapor inhalation (outdoor) outdoor inhalation exposure route from subsurface soils using the RBCA approach. Equation R7 is used to calculate soil remediation objectives for carcinogenic contaminants. Equation R8 is used to calculate soil remediation objectives for noncarcinogenic contaminants.
 - B) For Equation R7, the carcinogenic risk-based screening level for air (RBSL_{air}) and the volatilization factor for soils below one meter to ambient air (VF_{samb}) have numerical values that are calculated using Equations R9 and R11, respectively. Both equations rely on input parameters from a variety of sources.
 - C) The noncarcinogenic risk-based screening level for air (RBSL_{air}) and the volatilization factor for soils below one meter to ambient air (VF_{samb}) in Equation R8 have numerical values that can be calculated using Equations R10 and R11, respectively.
- c) Soil Component of the Groundwater Ingestion Exposure Route

NOTICE OF PROPOSED AMENDMENTS

- Equation R12 forms the basis for deriving Tier 2 remediation objectives for the soil component of the groundwater ingestion exposure route using the RBCA approach. The parameters, groundwater at the source (GW_{source}) and Leaching Factor (LF_{sw}), have numerical values that are calculated using Equations R13 and R14, respectively.
- 2) Equation R13 requires numerical values that are calculated using Equation R15.
- Equation R14 requires numerical values that are calculated using Equations R21, R22, and R24. For non-ionizing organics, the Soil Water Sorption Coefficient k_s shall be calculated using Equation R20. For ionizing organics and inorganics, the values for (k_s) are listed in Appendix C, Tables I and J, respectively. The pH-dependent k_s values for ionizing organics can be calculated using Equation R20 and the pH-dependent K_{oc} values in Appendix C, Table I. The remaining parameters in Equation R14 are field measurements or default values listed in Appendix C, Table D.
- d) The default value for GW_{comp} is the Tier 1 groundwater remediation objective. For chemicals for which there is no Tier 1 groundwater remediation objective, the value for GW_{comp} shall be the concentration determined according to the procedures specified in 35 Ill. Adm. Code 620, Subpart F. As an alternative to using the above concentrations, GW_{comp} may be developed using Equations R25 and R26, if approved institutional controls are in place as may be required in Subpart J.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.717 J&E Soil Gas Equations for the Indoor Inhalation Exposure Route

- a) This Section sets forth the equations and parameters to be used to develop Tier 2 soil gas remediation objectives for the indoor inhalation exposure route using the modified J&E model.
- b) Equations J&E1 and J&E2 calculate, for carcinogens and noncarcinogens respectively, an acceptable concentration of the contaminant of concern in indoor air that adequately protects humans who inhale this air. Equation J&E3 converts indoor air concentrations from parts per million volume to milligrams per cubic meter.

POLLUTION CONTROL BOARD

- <u>Equation J&E4 calculates an acceptable concentration of the contaminant of concern in the soil gas at the source of contamination. This calculation is made using: (1) an attenuation factor developed in accordance with Equations J&E7 through 18; and (2) the acceptable concentration of the contaminant of concern in indoor air calculated in accordance with Equation J&E1 (for carcinogens) or J&E2 (for noncarcinogens).</u>
- <u>d)</u> The attenuation factor (Equation J&E7 or J&E8) accounts for the following processes:
 - 1) Migration of contaminants from the source upwards through the vadose zone;
 - 2) Migration of contaminants through the earthen filled cracks in the slab-ongrade or basement floor and walls; and
 - 3) Mixing of the contaminants with air inside the building.
- e) Equation J&E7 is used where the mode of contaminant transport is both diffusion and advection. In this scenario, the Q_{soil} value equals 83.33 cm³/sec as described in Section 742.505.
- g) Equations J&E9a through J&E18 calculate input parameters for either Equation J&E7 or J&E8 (the equations used to calculate an attenuation factor). These equations assume there are "n" different soil layers between the source of the contamination and the floor of the building. Equations J&E11, 16, 17 and 18 shall be used to calculate the needed parameters for each of the n layers (the general soil layer is referred to as soil layer "i" and i = 1, 2, ...n). Equations J&E16, 17, and 18 shall also be used to calculate needed parameters for the soil in the cracks of the floor of the building (it is through these cracks that contaminants flow from the subsurface and into the building).
- <u>h)</u> The default representative subsurface temperature for Henry's Law Constant is 13°C. This value shall be used, as appropriate, in all calculations needed to represent the system by which contaminants migrate through the subsurface.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- i) The calculated soil gas remediation objective shall be compared with the saturated vapor concentration (C_v^{sat} , Equation J&E6b) for each volatile chemical. The calculated C_v^{sat} shall use the default representative subsurface temperature specified in 742.717(g). If the calculated soil gas remediation objective is greater than C_v^{sat} , then C_v^{sat} is used as the soil gas remediation objective.
- j) The calculated soil gas remediation objective shall be compared to concentrations of soil gas collected at a depth at least 3 feet below ground surface and above the saturated zone. If a valid sample cannot be collected, a soil gas sampling plan shall be approved by the Agency under Tier 3.

(Source: Added at 36 Ill. Reg. ____, effective ____)

SUBPART H: TIER 2 GROUNDWATER EVALUATION

Section 742.805 Tier 2 Groundwater Remediation Objectives

- a) To develop a groundwater remediation objective under this Section that exceeds the applicable Tier 1 groundwater remediation objective, or for which there is no Tier I groundwater remediation objective, a person may request approval from the Agency if the person has performed the following:
 - 1) Identified the horizontal and vertical extent of groundwater for which the Tier 2 groundwater remediation objective is sought;
 - 2) Taken corrective action, to the maximum extent practicable to remove any free product;
 - 3) Using Equation R26 in accordance with Section 742.810, demonstrated that the concentration of any contaminant of concern in groundwater will meet:
 - A) The applicable Tier 1 groundwater remediation objective at the point of human exposure; or
 - B) For any contaminant of concern for which there is no Tier 1 groundwater remediation objective, the concentration determined according to the procedures specified in 35 Ill. Adm. Code 620 at the point of human exposure. A person may request the Agency to provide these concentrations or may propose these concentrations under Subpart I;

- 4) Using Equation R26 in accordance with Section 742.810, demonstrated that the concentration of any contaminant of concern in groundwater within the minimum or designated maximum setback zone of an existing potable water supply well will meet the applicable Tier 1 groundwater remediation objective or, if there is no Tier 1 groundwater remediation objective, the concentration determined according to the procedures specified in 35 Ill. Adm. Code 620. A person may request the Agency to provide these concentrations or may propose these concentrations under Subpart I;
- 5) Using Equation R26 in accordance with Section 742.810, demonstrated that the concentration of any contaminant of concern in groundwater discharging into a surface water will meet the applicable water quality standard under 35 Ill. Adm. Code 302;
- 6) Demonstrated that the source of the release is not located within the minimum or designated maximum setback zone or within a regulated recharge area of an existing potable water supply well; and
- 7) If the selected corrective action includes an engineered barrier as set forth in Subpart K to minimize migration of contaminants of concern from the soil to the groundwater, demonstrated that the engineered barrier will remain in place for post-remediation land use through an institutional control as set forth in Subpart J.
- b) A groundwater remediation objective that exceeds the water solubility of that chemical (refer to Appendix C, Table E for solubility values) is not allowed.
- c) The contaminants of concern for which a Tier 1 remediation objective has been developed shall be included in any mixture of similar-acting chemicals under consideration in Tier 2. The evaluation of 35 Ill. Adm. Code 620.615 regarding mixtures of similar-acting chemicals shall be considered satisfied for Class I groundwater at the point of human exposure if either of the following requirements are achieved:
 - 1) Calculate the weighted average using the following equations:

$$W_{ave} = \frac{x_1}{CUOx_1} + \frac{x_2}{CUOx_2} + \frac{x_3}{CUOx_3} + \dots + \frac{x_a}{CUOx_a}$$

NOTICE OF PROPOSED AMENDMENTS

where:

W_{ave} = Weighted Average

x_1 through $x_a =$	Concentration of each individual contaminant at the location of concern. Note that, depending on the target organ, the actual number of contaminants will range from 2 to 33.
CUOx _a =	A Tier 1 or Tier 2 remediation objective must be developed for each x_a .

- A) If the value of the weighted average calculated in accordance with the equations above is less than or equal to 1.0, then the remediation objectives are met for those chemicals.
- B) If the value of the weighted average calculated in accordance with the equations above is greater than 1.0, then additional remediation must be carried out until the level of contaminants remaining in the remediated area has a weighted average calculated in accordance with the equation above less than or equal to one; or
- 2) Divide each individual chemical's remediation objective by the number of chemicals in that specific target organ group that were detected at the site. Each of the contaminant concentrations at the site is then compared to the remediation objectives that have been adjusted to account for this potential additivity.
- d) The evaluation of 35 Ill. Adm. Code 620.615 regarding mixtures of similar-acting chemicals are considered satisfied if the cumulative risk from any contaminant(s) of concern listed in Appendix A, Table I, plus any other contaminant(s) of concern detected in groundwater and listed in Appendix A, Table F as affecting the same target organ/organ system as the contaminant(s) of concern detected from Appendix A, Table I, does not exceed 1 in 10,000.
- e) Groundwater remediation objectives for the indoor inhalation exposure route shall be developed in accordance with Section 742.812.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742.810 <u>RBCA</u> Calculations to Predict Impacts from Remaining Groundwater Contamination

- a) Equation R26 predicts the contaminant concentration along the centerline of a groundwater plume emanating from a vertical planar source in the aquifer (dimensions S_w wide and S_d deep). This model accounts for both three-dimensional dispersion (x is the direction of groundwater flow, y is the other horizontal direction, and z is the vertical direction) and biodegradation.
 - 1) The parameters in this equation are:
 - X = distance from the planar source to the location of concern, along the centerline of the groundwater plume (i.e., y=0, z=0)
 - $C_x =$ the concentration of the contaminant at a distance X from the source, along the centerline of the plume
 - C_{source} = the greatest potential concentration of the contaminant of concern in the groundwater at the source of the contamination, based on the concentrations of contaminants in groundwater due to the release and the projected concentration of the contaminant migrating from the soil to the groundwater. As indicated above, the model assumes a planar source discharging groundwater at a concentration equal to C_{source} .
 - α_x = dispersivity in the x direction (i.e., Equation R16)
 - α_y = dispersivity in the y direction (i.e., Equation R17)
 - α_z = dispersivity in the z direction (i.e., Equation R18)
 - U = specific discharge (i.e., actual groundwater flow velocity through a porous medium; takes into account the fact that the groundwater actually flows only through the pores of the subsurface materials) where the aquifer hydraulic conductivity (K), the hydraulic gradient (I) and the total soil porosity θ_T must be known (i.e., Equation R19)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

2) To demonstrate that no surface water is adversely impacted, X shall be the distance from the down-gradient edge of the source of the contamination site to the nearest surface water body. This calculation must show that the contaminant in the groundwater at this location (Cx) does not exceed the applicable water quality standard.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.812 J&E Groundwater Equations for the Indoor Inhalation Exposure Route

Groundwater remediation objectives for the indoor inhalation exposure route are calculated using the modified J&E model as described in Section 742.717, except as follows:

- a) In Equation J&E9a, the total number of layers of soil that contaminants migrate through from the source to the building shall include a capillary fringe layer.
- b) The thickness of the capillary fringe layer is 37.5 cm.
- c) The volumetric water content of the capillary fringe shall be 90 % of the total porosity of the soil that comprises the capillary fringe.
- d) Equations J&E7 and J&E8 calculate an acceptable groundwater remediation objective. This calculation is made using: (1) the soil gas remediation objective calculated in accordance with Equation J&E4, and (2) the assumption that this gas is in equilibrium with any contamination in the groundwater.
 - 1) Equation J&E7 is used where the mode of contaminant transport is both diffusion and advection. In this scenario, the Q_{soil} value equals 83.33 cm³/sec as described in Section 742.505.
 - 2) Equation J&E8 is used where the mode of contaminant transport is diffusion only. In this scenario, the Q_{soil} value equals 0.0 cm³/sec as described in Section 742.505.
- e) A groundwater remediation objective that exceeds the water solubility of that chemical (refer to Appendix C, Table E for solubility values) is not allowed.

(Source: Added at 36 Ill. Reg. ____, effective ____)

SUBPART I: TIER 3 EVALUATION

NOTICE OF PROPOSED AMENDMENTS

Section 742.900 Tier 3 Evaluation Overview

- a) Tier 3 sets forth a flexible framework to develop remediation objectives outside of the requirements of Tiers 1 and 2. Although Tier 1 and Tier 2 evaluations are not prerequisites to conduct Tier 3 evaluations, data from Tier 1 and Tier 2 can assist in developing remediation objectives under a Tier 3 evaluation.
- b) The level of detail required to adequately characterize a site depends on the particular use of Tier 3. Tier 3 can require additional investigative efforts beyond those described in Tier 2 to characterize the physical setting of the site. However, in situations where remedial efforts have simply reached a physical obstruction additional investigation may not be necessary for a Tier 3 submittal.
- c) Situations that can be considered for a Tier 3 evaluation include, but are not limited to:
 - 1) Modification of parameters not allowed under Tier 2;
 - 2) Use of models different from those used in Tier 2;
 - Use of additional site data, such as results of indoor air sampling, to improve or confirm predictions of exposed receptors to contaminants of concern;
 - 4) Analysis of site-specific risks using formal risk assessment, probabilistic data analysis, and sophisticated fate and transport models (e.g., requesting a target hazard quotient greater than 1 or a target cancer risk greater than 1 in 1,000,000);
 - 5) Requests for site-specific remediation objectives because an assessment indicates further remediation is not practical;
 - 6) Incomplete human exposure pathway(s) not excluded under Subpart C;
 - 7) Use of toxicological-specific information not available from the sources listed in Tier 2;
 - 8) Land uses which are substantially different from the assumed residential or industrial/commercial property uses of a site (e.g., a site will be used for recreation in the future and cannot be evaluated in Tier 1 or 2); and

NOTICE OF PROPOSED AMENDMENTS

- 9) Requests for site-specific remediation objectives that exceed Tier 1 groundwater remediation objectives so long as the following is demonstrated:
 - A) To the extent practical, the exceedance of the groundwater quality standard has been minimized and beneficial use appropriate to the groundwater that was impacted has been returned; and
 - B) Any threat to human health or the environment has been minimized. [415 ILCS 5/58.5(d)(4)(A)]; and
- 10) Use of building control technologies, other than those described in Subpart L, to prevent completion of the indoor inhalation exposure route.
- d) For requests of a target cancer risk ranging between 1 in 1,000,000 and 1 in 10,000 at the point of human exposure or a target hazard quotient greater than 1 at the point of human exposure, the requirements of Section 742.915 shall be followed. Requests for a target cancer risk exceeding 1 in 10,000 at the point of human exposure are not allowed.
- e) Requests for approval of a Tier 3 evaluation must be submitted to the Agency for review under the specific program under which remediation is performed. When reviewing a submittal under Tier 3, the Agency shall consider *whether the interpretations and conclusions reached are supported by the information gathered.* [415 ILCS 58.7(e)(1)]. The Agency shall approve a Tier 3 evaluation if the person submits the information required under this Part and establishes through such information that public health is protected and that specified risks to human health and the environment have been minimized.
- f) If contaminants of concern include polychlorinated biphenyls (PCBs), requests for approval of a Tier 3 evaluation must additionally address the applicability of 40 CFR 761.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.920 Impractical Remediation

Any request for site-specific remediation objectives due to impracticality of remediation shall be submitted to the Agency for review and approval. <u>Any request for site-specific remediation</u> <u>objectives due to impracticality of remediation that involves the indoor inhalation exposure route</u>

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

shall follow Section 742.935 in lieu of this Section. A submittal under this Section shall include the following information:

- a) The reason(s) why the remediation is impractical;
- b) The extent of contamination;
- c) Geology, including soil types;
- d) The potential impact to groundwater;
- e) Results and locations of sampling events;
- f) Map of the area, including all utilities and structures; and
- g) Present and post-remediation uses of the area of contamination, including human receptors at risk.

(Source: Amended at 36 Ill. Reg. ____, effective _____)

Section 742.925 Exposure Routes

Technical information may demonstrate that there is no actual or potential impact of contaminants of concern to receptors from a particular exposure route. In these instances, a demonstration excluding an exposure route shall be submitted to the Agency for review and approval. <u>A demonstration that involves the indoor inhalation exposure route shall follow</u> <u>Section 742.935 in lieu of this Section.</u> A submittal under this Section shall include the following information:

- a) A description of the route evaluated;
- b) A description of the site and physical site characteristics;
- c) A discussion of the result and possibility of the route becoming active in the future; and
- d) Technical support that may include, but is not limited to, the following:
 - 1) a discussion of the natural or man-made barriers to that exposure route;
 - 2) calculations and modeling;

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 3) physical and chemical properties of contaminants of concern; and
- 4) contaminant migration properties.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.935 Indoor Inhalation Exposure Route

<u>a)</u> Exclusion of Exposure Route

Site information may demonstrate that there is no actual or potential impact of contaminants of concern to receptors from the indoor inhalation exposure route. In such instances, a demonstration excluding the exposure route shall be submitted to the Agency for review and approval. A submittal under this Section shall include the following information:

- 1) A description of the site, physical site characteristics, existing and planned buildings, and existing and planned manmade pathways; and
- 2) A discussion of the possibility of the route becoming active in the future.
- b) Exclusion of Exposure Route Using Building Control Technologies

Any proposals to use building control technologies as a means to prevent or mitigate human exposures under the indoor inhalation exposure route that differ from the requirements of Subpart L shall be submitted to the Agency for review and approval. A submittal under this Section shall include the following information:

- 1) A description of the site and physical site characteristics;
- <u>2)</u> <u>The current extent of contamination;</u>
- 3) <u>Geology, including soil parameters;</u>
- <u>4)</u> <u>Results and locations of sampling events;</u>
- 5) Scaled map of the area, including all buildings and man-made pathways;

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 6) A description of building characteristics and methods of construction, including a description of man-made pathways;
- 7) Present and post-remediation uses of the land above the area of contamination, including human receptors at risk;
- 8) A description of any building control technologies currently in place or proposed for installation that can reduce or eliminate the potential for completion of the exposure route, including design and construction specifications;
- 9) Information regarding the effectiveness of any building control technologies currently in place or proposed for installation and a schedule for performance testing to show the effectiveness of the control technology. For buildings not yet constructed, an approved building control technology shall be in place and operational prior to human occupancy;
- 10) Identification of documents reviewed and the criteria used in the documents for determining whether building control technologies are effective and how those criteria compare to existing or potential buildings or man-made pathways at the site; and
- 11) <u>A description as to how the effectiveness of the building control</u> technologies will be operated and maintained for the life of the buildings and man-made pathways, or until soil gas and groundwater contaminant concentrations have reached remediation objectives that are approved by the Agency. This includes provisions for potential extended system inoperability due to power failure or other disruption.
- c) Calculations and Modeling Used to Establish Soil Gas Remediation Objectives

The calculations and modeling shall account for contaminant transport through the mechanisms of diffusion and advection. Proposals to use soil gas data, including subslab samples, to establish remediation objectives for the indoor inhalation exposure route that differ from the requirements of Section 742.227 shall be submitted to the Agency for review and approval. A submittal under this Section shall include the following information:

1) Scaled map of the area, showing all buildings and man-made pathways (current and planned);

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- <u>2)</u> <u>The current extent of contamination;</u>
- 3) <u>Geology, including soil parameters:</u>
- 4) Depth to groundwater (including seasonal variation) and flow direction;
- 5) Location of soil gas sampling points; and
- 6) <u>A discussion of soil gas sampling procedures that, at a minimum, addresses the following:</u>
 - A) sampling equipment;
 - <u>B)</u> soil gas collection protocol, including field tests and weather conditions; and
 - <u>C)</u> <u>laboratory analytical methods.</u>
- d) Calculations and Modeling Used to Establish Soil Remediation Objectives

The calculations and modeling shall account for contaminant transport through the mechanisms of diffusion and advection. Any proposals to use soil data in lieu of soil gas data to establish remediation objectives for the indoor inhalation exposure route shall be submitted to the Agency for review and approval. A submittal under this Section shall include the following information:

- 1) Scaled map of the area, showing all buildings and man-made pathways (current and planned);
- <u>2)</u> <u>The current extent of contamination;</u>
- 3) Geology, including soil parameters:
- 4) Location of soil sampling points; and
- 5) A discussion of soil sampling procedures that, at a minimum, addresses the following:
 - <u>A)</u> sampling equipment;

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- <u>B)</u> soil collection protocol, including field tests and weather conditions; and
- <u>C)</u> <u>laboratory analytical methods.</u>
- 6) Mathematical and technical justification for the model proposed; and
- 7) Demonstration that the model was correctly applied.
- e) Calculations and Modeling Used to Establish Groundwater Remediation Objectives

The calculations and modeling shall account for contaminant transport through the mechanisms of diffusion and advection. Proposals to use groundwater data to establish remediation objectives for the indoor inhalation exposure route that differ from the requirements of Section 742.805 and Section 742.812 shall be submitted to the Agency for review and approval. A submittal under this Section shall include the following information.

- 1) Scaled map of the area, showing all buildings and man-made pathways (current and planned);
- <u>2)</u> <u>The current extent of contamination;</u>
- 3) Geology, including soil parameters and the thickness of the capillary fringe:
- 4) Depth to groundwater (including seasonal variation) and flow direction;
- 5) Results and locations of groundwater sampling events;
- 6) Mathematical and technical justification for the model proposed; and
- 7) Demonstration that the model was correctly applied.

(Source: Added at 36 Ill. Reg. ____, effective ____)

SUBPART J: INSTITUTIONAL CONTROLS

Section 742.1000 Institutional Controls

- a) Institutional controls in accordance with this Subpart must be placed on the property when remediation objectives are based on any of the following assumptions:
 - 1) Industrial/Commercial property use;
 - 2) Target cancer risk greater than 1 in 1,000,000;
 - 3) Target hazard quotient greater than 1;
 - 4) Engineered barriers;
 - 5) The point of human exposure is located at a place other than at the source;
 - 6) Exclusion of exposure routes; or
 - 7) Use of remediation objectives based on a diffusion only mode of contaminant transport for the indoor inhalation exposure route;
 - 8) Use of an indoor inhalation building control technology; or
 - 9) 7) Any combination of the above.
- b) The Agency shall not approve any remediation objective under this Part that is based on the use of institutional controls unless the person has proposed institutional controls meeting the requirements of this Subpart and the requirements of the specific program under which the institutional control is proposed. A proposal for approval of institutional controls shall provide identification of the selected institutional controls from among the types recognized in this Subpart.
- c) The following instruments may be institutional controls subject to the requirements of this Subpart J and the requirements of the specific program under which the institutional control is proposed:
 - 1) No Further Remediation Letters;
 - 2) Environmental Land Use Controls;
 - 3) Land Use Control Memoranda of Agreement;

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- 4) Ordinances adopted and administered by a unit of local government;
- 5) Agreements between a property owner (or, in the case of a petroleum leaking underground storage tank, the owner or operator of the tank) and a highway authority with respect to any contamination remaining under highways; and
- 6) Agreements between a highway authority, which is also the property owner (or, in the case of a petroleum leaking underground storage tank, the owner or operator of the tank) and the Agency with respect to any contamination remaining under the highways.
- d) No Further Remediation Letters and Environmental Land Use Controls that meet the requirements of this Subpart and the recording requirements of the program under which remediation is being performed are transferred with the property.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.1010 Environmental Land Use Controls

- a) An Environmental Land Use Control (ELUC) is an institutional control that may be used under this Part to impose land use limitations or requirements related to environmental contamination. ELUCs are only effective when approved by the Agency in accordance with this Part. Activities or uses that may be limited or required include, but are not limited to, prohibition of use of groundwater for potable purposes, restriction to industrial/commercial uses, operation or maintenance of engineered barriers, <u>indoor inhalation building control</u> <u>technologies</u>, or worker safety plans. ELUCs may be used in the following circumstances:
 - 1) When No Further Remediation Letters are not available, including but not limited to when contamination has migrated off-site or outside the remediation site; or
 - 2) When No Further Remediation Letters are not issued under the program for which a person is undergoing remediation.
- b) Recording requirements:
 - 1) An ELUC approved by the Agency pursuant to this Section must be recorded in the Office of the Recorder or Registrar of Titles for the county

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

in which the property that is the subject of the ELUC is located. A copy of the ELUC demonstrating that it has been recorded must be submitted to the Agency before the Agency will issue a no further remediation determination.

- 2) An ELUC approved under this Section will not become effective until officially recorded in the chain of title for the property that is the subject of the ELUC in accordance with subsection (b)(1) of this Section.
- 3) Reference to the recorded ELUC must be made in the instrument memorializing the Agency's no further remediation determination. Recording of the no further remediation determination and confirmation of recording must be in accordance with the requirements of the program under which the determination was issued.
- 4) The requirements of this Section do not apply to Federally Owned Property for which the Federal Landholding Entity does not have the authority under federal law to record land use limitations on the chain of title.
- 5) The requirements of this Section apply only to those sites for which a request for a no further remediation determination has not yet been made to the Agency by January 6, 2001.
- c) Duration:
 - 1) Except as provided in this subsection (c), an ELUC shall remain in effect in perpetuity.
 - 2) At no time shall any site for which an ELUC has been imposed as a result of remediation activities under this Part be used in a manner inconsistent with the land use limitation unless attainment of objectives appropriate for the new land use is achieved and a new no further remediation determination has been obtained and recorded in accordance with the program under which the ELUC was first imposed or the Site Remediation Program (35 Ill. Adm. Code 740). [415 ILCS 58.8(c)]. In addition, the appropriate release or modification of the ELUC must be prepared by the Agency and filed on the chain of title for the property that is the subject of the ELUC.

- A) For a Leaking Underground Storage Tank (LUST) site under 35 Ill. Adm. Code 731, or 732, or 734 or a Site Remediation Program site under 35 Ill. Adm. Code 740, an ELUC may be released or modified only if the NFR Letter is also modified under the Site Remediation Program to reflect the change;
- B) For a RCRA site under 35 Ill. Adm. Code 721-730, an ELUC may be released or modified only if there is also an amended certification of closure or a permit modification.
- 3) In addition to any other remedies that may be available, a failure to comply with the limitations or requirements of an ELUC may result in voidance of an Agency no further remediation determination in accordance with the program under which the determination was made. The failure to comply with the limitations or requirements of an ELUC may also be grounds for an enforcement action pursuant to Title VIII of the Act.
- d) An ELUC submitted to the Agency must match the form and contain the same substance, except for variable elements (e.g., name of property owner), as the model in Appendix F and must contain the following elements:
 - 1) Name of property owners and declaration of property ownership;
 - 2) Identification of the property to which the ELUC applies by common address, legal description, and Real Estate Tax Index/Parcel Index Number;
 - 3) A reference to the Bureau of Land LPC numbers or 10-digit identification numbers under which the remediation was conducted;
 - 4) A statement of the reason for the land use limitation or requirement relative to protecting human health and the surrounding environment from soil, groundwater, and/or other environmental contamination;
 - 5) The language instituting such land use limitations or requirements;
 - 6) A statement that the limitations or requirements apply to the current owners, occupants, and all heirs, successors, assigns, and lessees;

- 7) A statement that the limitations or requirements apply in perpetuity or until:
 - A) The Agency determines that there is no longer a need for the ELUC;
 - B) The Agency, upon written request, issues to the site that received the no further remediation determination that relies on the ELUC a new no further remediation determination approving modification or removal of the limitations or requirements;
 - C) The new no further remediation determination is filed on the chain of title of the site subject to the no further remediation determination; and
 - D) A release or modification of the land use limitation is filed on the chain of title for the property that is the subject of the ELUC;
- 8) Scaled site maps showing:
 - A) The legal boundary of the property to which the ELUC applies;
 - B) The horizontal and vertical extent of contaminants of concern above applicable remediation objectives for soil, and groundwater, and soil gas to which the ELUC applies;
 - C) Any physical features to which an ELUC applies (e.g., engineered barriers, monitoring wells, caps, indoor inhalation building control technologies); and
 - D) The nature, location of the source, and direction of movement of the contaminants of concern;
- 9) A statement that any information regarding the remediation performed on the property for which the ELUC is necessary may be obtained from the Agency through a request under the Freedom of Information Act [5 ILCS 140] and rules promulgated thereunder; and
- 10) The dated, notarized signatures of the property owners or authorized agent.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

(Source: Amended at 36 Ill. Reg. ____, effective ____)

Section 742.1015 Ordinances

- a) An ordinance adopted by a unit of local government that effectively prohibits the installation of potable water supply wells (and the use of such wells) may be used as an institutional control to meet the requirements of Section 742.320(d) or 742.805(a)(3) if the requirements of this Section are met. A model ordinance is found in Appendix G. Ordinances prohibiting the installation of potable water supply wells (and the use of such wells) by units of local government may be acceptable as institutional controls if the requirements of this Section are met and a Memorandum of Understanding (MOU) is entered into under subsection (i) of this Section. For purposes of this Section, a unit of local government is considered to be expressly prohibited from installing and using potable water supply wells only if the unit of local government is included in the prohibition provision by name. The prohibition required by this Section shall satisfy the following requirements at a minimum:
 - 1) The prohibition shall not allow exceptions for potable water well installation and use other than for the adopting unit of local government;
 - 2) The prohibition shall apply at all depths and shall not be limited to particular aquifers or other geologic formations;
 - 3) If the prohibition does not apply everywhere within the boundaries of the unit of local government, the limited area to which the prohibition applies shall be easily identifiable and clearly defined by the ordinance (e.g., narrative descriptions accompanied by maps with legends or labels showing prohibition boundaries, narrative descriptions using fixed, common reference points such as street names). Boundaries of prohibitions limited by area shall be fixed by the terms of the ordinance and shall not be subject to change without amending the ordinance in which the prohibition has been adopted (e.g., no boundaries defined with reference to zoning districts or the availability of the public water supply); and
 - 4) The prohibition shall not in any way restrict or limit the Agency's approval of the use of the ordinance as an institutional control pursuant to this Part (e.g., no restrictions based on remediation program participation,

NOTICE OF PROPOSED AMENDMENTS

no restrictions on persons performing remediation within the prohibition area who may use the ordinance).

- b) A request for approval of a local ordinance as an institutional control shall provide the following:
 - A copy of the ordinance restricting groundwater use certified by an official of the unit of local government in which the site is located that it is a true and accurate copy of the ordinance, unless the Agency and the unit of local government have entered an agreement under subsection (i) of this Section, in which case the request may alternatively reference the MOU. The ordinance must demonstrate that potable use of groundwater from potable water supply wells is prohibited;
 - A scaled map(s) delineating the area and extent of groundwater contamination modeled above the applicable remediation objectives including any measured data showing concentrations of contaminants of concern in which the applicable remediation objectives are exceeded;
 - 3) A scaled map delineating the boundaries of all properties under which groundwater is located which exceeds the applicable groundwater remediation objectives;
 - 4) Information identifying the current owner(s) of each property identified in subsection (b)(3) of this Section; and
 - 5) A copy of the proposed written notification to the unit of local government that adopted the ordinance and to the current owners identified in subsection (b)(4) of this Section that includes the following information:
 - A) The name and address of the unit of local government that adopted the ordinance;
 - B) The ordinance's citation;
 - C) A description of the property being sent notice by adequate legal description, reference to a plat showing the boundaries of the property, or by accurate street address;
 - D) Identification of the party requesting to use the groundwater ordinance as an institutional control, and a statement that the party

NOTICE OF PROPOSED AMENDMENTS

has requested approval from the Agency to use the ordinance as an institutional control;

- E) A statement that use of the ordinance as an institutional control allows contamination above groundwater ingestion remediation objectives to remain in groundwater beneath the affected properties, and that the ordinance strictly prohibits human and domestic consumption of the groundwater;
- F) A statement as to the nature of the release and response action with the site name, site address, and Agency site number or Illinois inventory identification number; and
- G) A statement that more information about the remediation site may be obtained by contacting the party requesting the use of the groundwater ordinance as an institutional control or by submitting a FOIA request to the Agency.
- c) Written notification proposed pursuant to subsection (b)(5) of this Section must be sent to the unit of local government that adopted the ordinance as well as all current property owners identified in subsection (b)(4). Written proof that the notification was sent to the unit of local government and the property owners shall be submitted to the Agency within 45 days from the date the Agency's no further remediation determination is recorded. Such proof may consist of the return card from certified mail, return receipt requested, a notarized certificate of service, or a notarized affidavit.
- d) Unless the Agency and the unit of local government have entered into a MOU under subsection (i) of this Section, the current owner or successors in interest of a site who have received approval of use of an ordinance as an institutional control under this Section shall:
 - Monitor activities of the unit of local government relative to variance requests or changes in the ordinance relative to the use of potable groundwater at properties identified in subsection (b)(3) of this Section; and
 - 2) Notify the Agency of any approved variance requests or ordinance changes within 30 days after the date such action has been approved.

POLLUTION CONTROL BOARD

- e) The information required in subsections (b)(1) through (b)(5) of this Section and the Agency letter approving the groundwater remediation objective shall be submitted to the unit of local government. Proof that the information has been filed with the unit of local government shall be provided to the Agency.
- f) Any ordinance or MOU used as an institutional control pursuant to this Section shall be recorded in the Office of the Recorder or Registrar of Titles of the county in which the site is located together with the instrument memorializing the Agency's no further remediation determination pursuant to the specific program within 45 days after receipt of the Agency's no further remediation determination.
- g) An institutional control approved under this Section shall not become effective until officially recorded in accordance with subsection (f) of this Section. The person receiving the approval shall obtain and submit to the Agency within 30 days after recording a copy of the institutional control demonstrating that it has been recorded.
- h) The following shall be grounds for voidance of the ordinance as an institutional control and the instrument memorializing the Agency's no further remediation determination:
 - 1) Modification of the ordinance by the unit of local government to allow potable use of groundwater;
 - 2) Approval of a site-specific request, such as a variance, to allow potable use of groundwater at a site identified in subsection (b)(3) of this Section;
 - 3) Violation of the terms of an institutional control recorded under Section 742.1005 or Section 742.1010; or
 - 4) Failure to provide notification and proof of such notification pursuant to subsection (c) of this Section.
- The Agency and a unit of local government may enter into a MOU under this Section if the unit of local government has adopted an ordinance satisfying subsection (a) of this Section and if the requirements of this subsection are met. The MOU submitted to the Agency must match the form and contain the same substance as the model in Appendix H and shall include the following:
 - 1) Identification of the authority of the unit of local government to enter the MOU;

NOTICE OF PROPOSED AMENDMENTS

- 2) Identification of the legal boundaries, or equivalent, under which the ordinance is applicable;
- 3) A certified copy of the ordinance;
- 4) A commitment by the unit of local government to notify the Agency of any variance requests or proposed ordinance changes at least 30 days prior to the date the local government is scheduled to take action on the request or proposed change;
- 5) A commitment by the unit of local government to maintain a registry of all sites within the unit of local government that have received no further remediation determinations pursuant to specific programs; and
- 6) If the ordinance does not expressly prohibit the installation of potable water supply wells (and the use of such wells) by units of local government, a commitment by the unit of local government:
 - A) To review the registry of sites established under subsection (i)(5) of this Section prior to siting potable water supply wells within the area covered by the ordinance;
 - B) To determine whether the potential source of potable water may be or has been affected by contamination left in place at those sites; and
 - C) To take whatever steps are necessary to ensure that the potential source of potable water is protected from the contamination or treated before it is used as a potable water supply.
- j) <u>A groundwater ordinance may not be used to exclude the indoor inhalation</u> <u>exposure route.</u>

(Source: Amended at 36 Ill. Reg. ____, effective _____)

SUBPART K: ENGINEERED BARRIERS

Section 742.1105 Engineered Barrier Requirements

- a) Natural attenuation, access controls, and point of use treatment shall not be considered engineered barriers. Engineered barriers may not be used to prevent direct human exposure to groundwater without the use of institutional controls.
- b) For purposes of determining remediation objectives under Tier 1, engineered barriers are not recognized.
- c) The following engineered barriers are recognized for purposes of calculating remediation objectives that exceed residential remediation objectives:
 - 1) For the soil component of the groundwater ingestion exposure route, the following engineered barriers are recognized if they prevent completion of the exposure pathway:
 - A) Caps or walls constructed of compacted clay, asphalt, concrete or other material approved by the Agency; and
 - B) Permanent structures such as buildings and highways.
 - 2) For the soil ingestion exposure route, the following engineered barriers are recognized if they prevent completion of the exposure pathway:
 - A) Caps or walls constructed of compacted clay, asphalt, concrete, or other material approved by the Agency;
 - B) Permanent structures such as buildings and highways; and
 - C) Soil, sand, gravel, or other geologic materials that:
 - i) Cover the contaminated media;
 - ii) Meet the soil remediation objectives under Subpart E for residential property for contaminants of concern; and
 - iii) Are a minimum of three feet in depth.
 - 3) For the <u>outdoor</u> inhalation exposure route, the following engineered barriers are recognized if they prevent completion of the exposure pathway:

NOTICE OF PROPOSED AMENDMENTS

- A) Caps or walls constructed of compacted clay, asphalt, concrete, or other material approved by the Agency;
- B) Permanent structures such as buildings and highways; and
- C) Soil, sand, gravel, or other geologic materials that:
 - i) Cover the contaminated media;
 - ii) Meet the soil remediation objectives under Subpart E for residential property for contaminants of concern; and
 - iii) Are a minimum of ten feet in depth and not within ten feet of any manmade pathway.
- 4) For the ingestion of groundwater exposure route, the following engineered barriers are recognized if they prevent completion of the exposure pathway:
 - A) Slurry walls; and
 - B) Hydraulic control of groundwater.
- d) Unless otherwise prohibited under Section 742.1100, any other type of engineered barrier may be proposed if it will be as effective as the options listed in subsection (c) of this Section.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

SUBPART L: BUILDING CONTROL TECHNOLOGIES

Section 742.1200 Building Control Technologies

- a) Any person who develops remediation objectives under this Part based on building control technologies shall meet the requirements of this Subpart and the requirements of Subpart J relative to institutional controls.
- b) The Agency shall not approve any remediation objective under this Part that is based on the use of building control technologies unless the person has proposed building control technologies meeting the requirements of this Subpart or Subpart I and Subpart J relative to institutional controls.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- c) The use of building control technologies can be recognized in determining remediation objectives only if the building control technologies are intended for use as part of the final corrective action.
- <u>d)</u> <u>An approved building control technology shall be in place and operational prior to human occupancy.</u>
- e) Any no further remediation determination based upon the use of building control technologies shall require effective maintenance of the building control technology. The maintenance requirements shall be included in an institutional control under Subpart J. This institutional control shall address provisions for inoperability by requiring the following if the building control technology is rendered inoperable:
 - 1) The site owner/operator shall notify building occupants and workers in advance of intrusive activities. Such notification shall enumerate the contaminant of concern known to be present;
 - 2) The site owner/operator shall require building occupants and workers to implement protective measures consistent with good industrial hygiene practice; and
 - 3) For a school, the site owner/operator shall notify the Agency upon any building control technology being rendered inoperable. For the purposes of this subsection (e)(3), the term "school" means any public educational facility in Illinois, including grounds and/or campus, consisting of students, comprising one or more grade groups or other identifiable groups, organized as one unit with one or more teachers to give instruction of a defined type. Public educational facility includes, but is not limited to, primary and secondary (kindergarten 12th grade), charter, vocational, alternative, and special education schools. Public educational facility does not include junior colleges, colleges, or universities.
- <u>f</u>) Failure to install or maintain a building control technology in accordance with a no further remediation determination shall be grounds for voidance of the determination and the instrument memorializing the Agency's no further remediation determination.

(Source: Added at 36 Ill. Reg. ____, effective ____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742.1205 Building Control Technology Proposals

A proposal to use a building control technology under this Subpart shall include the following information:

- a) A description of the site and physical site characteristics;
- b) The current extent and modeled migration of contamination;
- c) <u>Geology, including soil types;</u>
- d) Results and locations of sampling events;
- e) Scaled map of the area, including all buildings and man-made pathways;
- <u>f)</u> <u>A description of building characteristics and methods of construction, including a description of man-made pathways; and</u>
- g) Present and post-remediation uses of the land above the area of contamination, including human receptors at risk.

(Source: Added at 36 Ill. Reg. ____, effective _____)

Section 742.1210 Building Control Technology Requirements

- a) Natural attenuation, access controls, and point of use treatment shall not be considered building control technologies.
- b) For purposes of determining compliance with remediation objectives under Tier 1, building control technologies are not recognized.
- <u>c)</u> <u>The following building control technologies are recognized for purposes of pathway exclusion under Section 742.312.</u>
 - 1) Sub-slab depressurization (SSD) systems meeting the following requirements:
 - <u>A</u>) <u>A suction pit is installed that is at least two cubic feet and extends at least 6 inches below the slab (larger suction pits may be</u>

NOTICE OF PROPOSED AMENDMENTS

excavated as needed to achieve the performance criteria in Section 742.1210(c)(1)(B));

- B) <u>A PVC pipe of at least 3 inches in diameter extends from the</u> suction pit to the intake side of an in-line fan capable of achieving a static vacuum of at least 0.25 inches water column (wc) at the suction point and measureable vacuum at the furthest edges of the area served by the suction pit under worst case conditions (all exhaust fans and heating systems running, during cold weather) as determined by a differential pressure reading of at least -0.003 inches wc below the slab or visible downward flow of air at test holes using chemical or smoke sticks;
- <u>C)</u> <u>All visible cracks and joints in the slab (including the place where the pipe exits the slab) and foundation walls are sealed;</u>
- D) The pipe exhausts outside the building at least 10 feet above ground and at least 10 feet from any door or window; and
- <u>Additional suction pits meeting the requirements of Section</u> 742.1210(c)(1)(A) shall be installed as necessary to achieve measureable vacuum below the slab in all areas, including in any area where subsurface or foundation conditions (e.g., a sub-slab grade beam) prevent adequate suction field extension.</u>
- 2) <u>Sub-membrane depressurization (SMD) systems meeting the following</u> requirements:
 - A) <u>A non-woven geotextile is installed on the exposed earthen</u> <u>material</u>;
 - B) A cross-laminated polyethylene membrane liner at least 0.10 mm (or 4 mil) thick is placed over the geotextile and sealed to foundation walls using a low volatile adhesive that is recommended by the liner manufacturer (e.g., acrylic latex adhesive);
 - <u>C)</u> <u>A 3 inch diameter PVC pipe extends from a hole cut in the liner to</u> <u>the intake side of an in-line fan capable of achieving a static</u> <u>vacuum of at least 0.25 inches water column (wc) at the riser pipe</u>

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

and measureable vacuum at the furthest edges of the liner under worst case conditions (all exhaust fans running during cold weather) as determined by a differential pressure reading of at least -0.003 inches we below the liner or visible downward flow of air in test holes using chemical or smoke sticks;

- D) The pipe is sealed to the liner;
- <u>E)</u> The pipe exhausts outside the building at least 10 feet above ground and at least 10 feet from any door or window; and
- F) No leaks based on smoke stick tests along the entire perimeter of the liner (i.e., at all sealed edges) with the fan running. Where leaks are identified, appropriate repairs are undertaken and smoke stick testing repeated until no leaks are detected.
- 3) Membrane barrier systems when placed below concrete slabs meeting the following requirements:
 - <u>A)</u> The membrane is impermeable to volatile chemicals and is not less than 1.5 mm (or 60 mil) thick;
 - B) The membrane is sealed to foundation walls and any penetrating pipes according to membrane manufacturer/installer recommendations:
 - <u>C)</u> The membrane is installed in accordance with the manufacturer's requirements and by an applicator trained and approved by the manufacturer;
 - D) A smoke test of the membrane system (where smoke is injected below the installed liner prior to slab installation), in accordance with the manufacturer's requirements, is performed to ensure no leaks exist. Where leaks are identified, appropriate repairs are undertaken and smoke testing repeated until no leaks are detected;
 - <u>E)</u> The membrane is puncture resistant to slab installation construction activities and protected by sand layers or geotextiles as recommended by the manufacturer; and

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

- <u>F)</u> <u>Construction activities following membrane installation do not</u> <u>damage, puncture or tear the membrane or otherwise compromise</u> <u>its ability to prevent the migration of volatile chemicals.</u>
- 4) Vented raised floors meeting the following requirements:
 - <u>A)</u> An interconnected void system below the slab sufficient to allow free movement of air and communication of negative pressures to all points below the slab;
 - B) Sealing of all construction joints, open cracks, and penetrations through the slab (e.g., for utilities and riser pipes) with a low volatile caulk; and
 - C) At least one 3 inch diameter riser pipe venting to the atmosphere above the roof line (at least 10 feet from any doors or windows) for each 5000 square feet of membrane area, with the capability of converting passively vented floor systems to actively vented or SSD systems meeting the performance requirements of Section 742.1210(c)(1).

(Source: Added at 36 Ill. Reg. ____, effective ____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742. APPENDIX A: General

Section 742.TABLE A: Soil Saturation Limits (C_{sat}) for Chemicals Whose Melting Point is Less than 30° C

CAS No.	Chemical Name	C _{sat} (mg/kg)
67-64-1	Acetone	100,000
71-43-2	Benzene	870
111-44-4	Bis(2-chloroethyl)ether	3,300
117-81-7	Bis(2-ethylhexyl)phthalate	31,000
75-27-4	Bromodichloromethane (Dichlorobromomethane)	3,000
75-25-2	Bromoform	1,900
71-36-3	Butanol	10,000
85-68-7	Butyl benzyl phthalate	930
75-15-0	Carbon disulfide	720
56-23-5	Carbon tetrachloride	1,100
108-90-7	Chlorobenzene (Monochlorobenzene)	680
124-48-1	Chlorodibromomethane (Dibromochloromethane)	1,300
67-66-3	Chloroform	2,900
96-12-8	1,2-Dibromo-3-chloropropane	1,400
106-93-4	1,2-Dibromoethane (Ethylene dibromide)	2,800
84-74-2	Di- <i>n</i> -butyl phthalate	2,300
95-50-1	1,2-Dichlorobenzene (o-Dichlorobenzene)	560
75-34-3	1,1-Dichloroethane	1,700
107-06-2	1,2-Dichloroethane (Ethylene dichloride)	1,800
75-35-4	1,1-Dichloroethylene	1,500
156-59-2	<i>eis-</i> 1,2-Dichloroethylene	1,200
156-60-5	trans-1,2-Dichloroethylene	3,100
7 8-87-5	1,2-Dichloropropane	1,100

POLLUTION CONTROL BOARD

542-75-6	1,3-Dichloropropene (1,3-Dichloropropylene, <i>cis</i> + trans)	1,400
84-66-2	Diethyl phthalate	2,000
117-84-0	Di-n-octyl phthalate	10,000
100-41-4	Ethylbenzene	400
77-47-4	Hexachlorocyclopentadiene	2,200
78-59-1	Isophorone	4,600
74-83-9	Methyl bromide (Bromomethane)	3,200
1634-04-4	Methyl-tertiary-butyl ether	8,800
75-09-2	Methylene chloride (Dichloromethane)	2,400
98-95-3	Nitrobenzene	1,000
100-42-5	Styrene	1,500
127-18-4	Tetrachloroethylene (Perchloroethylene)	2 40
108-88-3	Toluene	650
120-82-1	1,2,4-Trichlorobenzene	3,200
71-55-6	1,1,1-Trichloroethane	1,200
79-00-5	1,1,2-Trichloroethane	1,800
79-01-6	Trichloroethylene	1,300
108-05-4	Vinyl acetate	2,700
75-01-4	Vinyl chloride	1,200
108-38-3	m-Xylene	4 20
95-47-6	o-Xylene	410
106-42-3	p-Xylene	4 60
1330-20-7	Xylenes (total)	320
	Ionizable Organics	
95-57-8	2-Chlorophenol	53,000

POLLUTION CONTROL BOARD

		For the Outdoor Inhalation	For the Soil Component of <u>the</u> Groundwater Ingestion
CAS No.	Chemical Name	Exposure Route ^a C _{sat} (mg/kg)	<u>Exposure</u> <u>Route^b C_{sat} (mg/kg)</u>
<u>67-64-1</u>	Acetone	<u>1.00E+05</u>	<u>2.00E+05</u>
<u>71-43-2</u>	Benzene	<u>8.00E+02</u>	<u>5.80E+02</u>
111-44-4	Bis(2-chloroethyl)ether	<u>3.00E+03</u>	<u>3.90E+03</u>
<u>117-81-7</u>	Bis(2-ethylhexyl)phthalate	<u>2.00E+02</u>	<u>6.80E+01</u>
75-27-4	Bromodichloromethane (Dichlorobromomethane)	<u>2.80E+03</u>	<u>2.00E+03</u>
75-25-2	Bromoform	<u>2.00E+03</u>	<u>1.20E+03</u>
<u>71-36-3</u>	Butanol	<u>1.00E+04</u>	<u>1.60E+04</u>
<u>78-93-3</u>	2-Butanone (MEK)	<u>2.50E+04</u>	<u>4.50E+04</u>
<u>85-68-7</u>	Butyl benzyl phthalate	<u>1.00E+03</u>	<u>3.40E+02</u>
<u>75-15-0</u>	Carbon disulfide	<u>8.50E+02</u>	<u>5.20E+02</u>
<u>56-23-5</u>	Carbon tetrachloride	<u>1.20E+03</u>	<u>5.60E+02</u>
<u>108-90-7</u>	Chlorobenzene (Monochlorobenzene)	<u>6.20E+02</u>	<u>2.90E+02</u>
<u>124-48-1</u>	<u>Chlorodibromomethane</u> (Dibromochloromethane)	<u>1.40E+03</u>	<u>8.90E+02</u>
<u>67-66-3</u>	<u>Chloroform</u>	<u>3.40E+03</u>	<u>2.50E+03</u>
<u>95-57-8</u>	2-Chlorophenol ^c (ionizable organic)	<u>1.00E+04</u>	<u>7.10E+03</u>
<u>75-99-0</u>	<u>Dalapon</u>	<u>1.20E+05</u>	<u>1.90E+05</u>
<u>96-12-8</u>	1,2-Dibromo-3-chloropropane	<u>6.90E+02</u>	<u>4.30E+02</u>
<u>106-93-4</u>	1,2-Dibromoethane (Ethylene dibromide)	<u>1.60E+03</u>	<u>1.20E+03</u>

POLLUTION CONTROL BOARD

		For the Outdoor Inhalation	For the Soil Component of the Groundwater Ingestion
CAS No.	Chemical Name	Exposure Route ^a C _{sat} (mg/kg)	<u>Exposure</u> <u>Route^b <u>C_{sat} (mg/kg)</u></u>
<u>84-74-2</u>	Di-n-butyl phthalate	<u>2.60E+03</u>	<u>8.80E+02</u>
<u>95-50-1</u>	1,2-Dichlorobenzene (o-Dichlorobenzene)	<u>5.60E+02</u>	<u>2.10E+02</u>
<u>75-71-8</u>	Dichlorodifluoromethane	<u>8.70E+02</u>	<u>4.30E+02</u>
75-34-3	<u>1,1-Dichloroethane</u>	<u>1.70E+03</u>	<u>1.40E+03</u>
107-06-2	1,2-Dichloroethane (Ethylene dichloride)	<u>1.90E+03</u>	<u>2.10E+03</u>
<u>75-35-4</u>	1,1-Dichloroethylene	<u>1.40E+03</u>	<u>9.10E+02</u>
<u>156-59-2</u>	cis-1,2-Dichloroethylene	<u>1.30E+03</u>	<u>1.00E+03</u>
<u>156-60-5</u>	trans-1,2-Dichloroethylene	<u>3.00E+03</u>	<u>2.10E+03</u>
<u>78-87-5</u>	1,2-Dichloropropane	<u>1.20E+03</u>	<u>8.70E+02</u>
<u>542-75-6</u>	$\frac{1,3-\text{Dichloropropene} (1,3-\text{Dichloropropylene},}{cis + trans)}$	<u>1.00E+03</u>	<u>8.50E+02</u>
84-66-2	Diethyl phthalate	<u>2.20E+03</u>	<u>9.20E+02</u>
<u>105-67-9</u>	2,4-Dimethylphenol	<u>1.00E+04</u>	<u>4.70E+03</u>
<u>117-84-0</u>	Di-n-octyl phthalate	<u>1.60E+01</u>	<u>5.20E+00</u>
<u>123-91-1</u>	<u>p-Dioxane</u>	<u>1.00E+05</u>	<u>2.00E+05</u>
100-41-4	Ethylbenzene	<u>3.50E+02</u>	<u>1.50E+02</u>
<u>77-47-4</u>	<u>Hexachlorocyclopentadiene</u>	<u>1.30E+02</u>	<u>4.40E+01</u>
<u>78-59-1</u>	Isophorone	<u>3.00E+03</u>	<u>3.00E+03</u>
<u>98-82-8</u>	Isopropylbenzene (Cumene)	<u>9.40E+02</u>	<u>4.00E+02</u>
<u>7439-97-6</u>	Mercury (elemental)	<u>3.10E+00</u>	<u>N/A</u>
<u>74-83-9</u>	Methyl bromide (Bromomethane)	<u>3.10E+03</u>	<u>3.60E+03</u>

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

		For the Outdoor Inhalation	For the Soil Component of the Groundwater Ingestion
CAS No.	Chemical Name	Exposure Route ^a C _{sat} (mg/kg)	<u>Exposure</u> <u>Route^b <u>C_{sat} (mg/kg)</u></u>
1634-04-4	Methyl tertiary-butyl ether	<u>8.40E+03</u>	<u>1.10E+04</u>
<u>75-09-2</u>	Methylene chloride (Dichloromethane)	<u>2.50E+03</u>	<u>3.00E+03</u>
<u>98-95-3</u>	Nitrobenzene	<u>7.10E+02</u>	<u>5.90E+02</u>
<u>621-64-7</u>	n-Nitrosodi-n-propylamine	<u>1.90E+03</u>	<u>2.30E+03</u>
100-42-5	Styrene	<u>6.30E+02</u>	<u>2.60E+02</u>
127-18-4	Tetrachloroethylene (Perchloroethylene)	<u>8.00E+02</u>	<u>3.10E+02</u>
108-88-3	Toluene	<u>5.80E+02</u>	<u>2.90E+02</u>
120-82-1	<u>1,2,4-Trichlorobenzene</u>	<u>3.40E+02</u>	<u>1.20E+02</u>
<u>71-55-6</u>	1,1,1-Trichloroethane	<u>1.30E+03</u>	<u>6.70E+02</u>
<u>79-00-5</u>	1,1,2-Trichloroethane	<u>1.80E+03</u>	<u>1.30E+03</u>
<u>79-01-6</u>	Trichloroethylene	<u>1.20E+03</u>	<u>6.50E+02</u>
<u>75-69-4</u>	Trichlorofluoromethane	<u>1.80E+03</u>	<u>8.90E+02</u>
108-05-4	Vinyl acetate	<u>2.60E+03</u>	<u>4.20E+03</u>
<u>75-01-4</u>	Vinyl chloride	<u>2.60E+03</u>	<u>2.90E+03</u>
<u>108-38-3</u>	m-Xylene	<u>4.10E+02</u>	<u>1.60E+02</u>
<u>95-47-6</u>	<u>o-Xylene</u>	<u>3.70E+02</u>	<u>1.50E+02</u>
106-42-3	<u>p-Xylene</u>	<u>3.30E+02</u>	<u>1.40E+02</u>
1330-20-7	Xylenes (total)	<u>2.80E+02</u>	<u>1.10E+02</u>

<u>a</u> Soil Saturation Limits calculated using an foc of 0.006 g/g and a system temperature of 25°C.
 <u>b</u> Soil Saturation Limits calculated using an foc of 0.002 g/g and a system temperature of 25°C.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

$\frac{c}{C_{sat}}$ for pH of 6.8. If soil pH is other than 6.8, a site-specific C_{sat} should be calculated using equations S19 and S29 and the pH-specific Koc values in Appendix C Table I.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742. APPENDIX A General

Ethylbenzene

Fluoranthene

Nitrobenzene Picloram

2,4,5-TP (Silvex)

Styrene (Ingestion only)

Toluene (Ingestion only)

2,4,5-Trichlorophenol

Methyl tertiary-butyl ether (Inhalation only)

1,2,4-Trichlorobenzene (Inhalation only)

Section 742.TABLE E Similar-Acting Noncarcinogenic Chemicals

Adrenal Gland	Central Nervous System
Nitrobenzene	Butanol (Ingestion only)
1,2,4-Trichlorobenzene (Ingestion only)	Cyanide (amenable)
	2,4-Dimethylphenol
Kidney	Endrin
Acetone (Ingestion only)	Manganese
Cadmium (Ingestion only)	2-Methylphenol
Chlorobenzene	Mercury (Inhalation only)
Dalapon	Styrene (Inhalation only)
1,1-Dichloroethane	Toluene (Inhalation only)
Di-n-octyl-phthalate (Ingestion only)	Xylenes (Ingestion only)
Endosulfan	
Ethylbenzene	Circulatory System
Fluoranthene	Antimony
Methyl tertiary-butyl ether (Inhalation only)	Barium (Ingestion only)
Nitrobenzene	2,4-D
Pyrene	cis-1,2-Dichloroethylene (Ingestion only)
Toluene (Ingestion only)	Nitrobenzene
2,4,5-Trichlorophenol	trans-1,2-Dichloroethylene (Ingestion only)
Vinyl acetate (Ingestion only)	2,4-Dimethylphenol
	Fluoranthene
Liver	Fluorene
Acenaphthene	Styrene (Ingestion only)
Acetone (Ingestion only)	Zine
Butylbenzyl phthalate (Ingestion only)	
Chlorobenzene (Ingestion only)	Gastrointestinal System
1,1-Dichloroethylene (Ingestion only)	Beryllium (Ingestion only)
Di-n-octyl phthalate (Ingestion only)	Endothall
Endrin	Hexachlorocyclopentadiene (Ingestion only)

Hexachlorocyclopentadiene (Ingestion only) Methyl bromide (Ingestion only)

Methyl tertiary butyl ether (Ingestion only)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Immune System

2,4-Dichlorophenol p-Chloroaniline Mercury (Ingestion only)

Reproductive System

Barium (Inhalation only) Boron (Ingestion only) Carbon disulfide 2-Chlorophenol (Ingestion only) 1,2 Dibromo-3-Chloropropane (Inhalation only) Dinoseb Ethylbenzene (Inhalation only) Methoxychlor Phenol

Respiratory System

1,2-Dichloropropane (Inhalation only) 1,3-Dichloropropylene (Inhalation only) Hexachlorocyclopentadiene (Inhalation only) Methyl bromide (Inhalation only) Naphthalene (Inhalation only) Toluene (Inhalation only) Vinyl acetate (Inhalation only)

Cholinesterase Inhibition Aldicarb Carbofuran

Decreased Body Weight Gains

and Circulatory System Effects Atrazine Simazine

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Adrenal Gland

Isopropylbenzene

Cholinesterase Inhibition

<u>Aldicarb</u> <u>Carbofuran</u>

Circulatory System

Alachlor Antimony (ingestion only) Benzene Cobalt (ingestion only) 2.4-D cis-1,2-Dichloroethylene (ingestion only) 2,4-Dimethylphenol 2,4-Dinitrotoluene 2,6-Dinitrotoluene Ensosulfan Fluoranthene Fluorene Methylene Chloride (inhalation only) Nickel (Res. & I/C only) (inhalation only) Nitrate as N Nitrobenzene (ingestion only) Selenium Simazine Styrene (ingestion only) 1,3,5-Trinitrobenzene Zinc

Decreased Body Weight Gain

<u>Atrazine</u> <u>Bis(2-chloroethyl)ether</u> <u>Cyanide</u> <u>1,2-Dichlorobenzene (inhalation only)</u> <u>Diethyl phthalate (ingestion only)</u>

Immune System

4-Chloroaniline

Decreased Body Weight Gain (continued)

Ensosulfan 2-Methylphenol (o-cresol) Naphthalene (ingestion only) Nickel (ingestion only) n-Nitrosodiphenylamine Phenol (ingestion only) Simazine Tetrachloroethylene (ingestion only) 1,1,1-Trichloroethane (ingestion only) Vinyl acetate (ingestion only) Xylenes (Res. & I/C only) (ingestion only)

Endocrine System

<u>Cyanide</u> 1,2-Dibromoethane (ingestion only) <u>Di-n-octyl phthalate (ingestion only)</u> <u>Nitrobenzene</u> 1,2,4-Trichlorobenzene (ingestion only)

Eye

2.4-Dinitrophenol n-Nitrosodiphenylamine Polychlorinated biphenyls (PCBs) Trichloroethylene

Gastrointestinal System

Beryllium (ingestion only) <u>Copper</u> 1,3-Dichloropropene (cis + trans) (ingestion only) <u>Endothall</u> <u>Fluoride</u> <u>Hexachlorocyclopentadiene (ingestion only)</u> <u>Iron</u> <u>Methyl bromide (ingestion only)</u> Methyl tertiary-butyl ether (ingestion only)

Liver (continued) Chlorobenzene (ingestion only)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

2,4-Dichlorophenol Mercury (ingestion only) Polychlorinated biphenyls (PCBs) Kidney Acetone (ingestion only) Aldrin (CW only) Barium Bromodichloromethane (ingestion only) Cadmium 2.4-D Dalapon 1,1-Dichloroethane 1,2-Dichloroethane (CW only) (ingestion only) Ensosulfan Ethylbenzene (ingestion only) Fluoranthene gamma-HCH (gamma-BHC) Hexachloroethane (ingestion only) Isopropylbenzene Mecoprop (MCPP) Methyl tertiary-butyl ether (inhalation only) Pentachlorophenol Pvrene Toluene (ingestion only) 2,4,5-Trichlorophenol Vinyl acetate (ingestion only)

<u>Liver</u>

Acenaphthene Aldrin (Res. & I/C only) Bis(2-ethylhexyl)phthalate (Res. & I/C only) (ingestion only) Bromoform Butyl Benzyl Phthalate (ingestion only) Carbon Tetrachloride Chlordane

Liver (continued) 1,2,4-Trichlorobenzene (inhalation only) Chlorodibromomethane (ingestion only) Chloroform 2.4-D DDT 1,2-Dibromoethane (ingestion only) 1,2-Dichlorobenzene (CW only) (ingestion only) 1,4-Dichlorobenzene Dichlorodifluoromethane 1.2-Dichloroethane (inhalation only) 1,1-Dichloroethylene trans-1,2-Dichloroethylene 1,2-Dichloropropane (ingestion only) Dieldrin (Res. & I/C only) 2.4-Dinitrotoluene 2,6-Dinitrotoluene Di-n-octyl phthalate (ingestion only) p-Dioxane Endrin Ethylbenzene (ingestion only) Fluoranthene Heptachlor Heptachlor epoxide Hexachlorobenzene alpha-HCH (alpha-BHC) gamma-HCH (gamma-BHC) High Melting Exlosive, Octogen (HMX) Isophorone (inhalation only) Methyl tertiary-butyl ether Methylene Chloride (ingestion only) Pentachlorophenol Phenol (inhalation only)

<u>Picloram</u> <u>Styrene (ingestion only)</u> <u>Tetrachloroethylene (ingestion only)</u> <u>Toxaphene (CW only)</u> <u>2,4,5-TP (Silvex)</u>

Reproductive System (continued) Carbofuran

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

1,1,1-Trichloroethane (inhalation only) 1,1,2-Trichloroethane (ingestion only) 2,4,5-Trichlorophenol 2,4,6-Trinitrotoluene (TNT) Vinyl Chloride

Mortality

<u>Di-n-butyl phthalate (ingestion only)</u> Xylenes (Res. & I/C only) (ingestion only)

Nervous System

Butanol (ingestion only) Carbon disulfide (inhalation only) Cvanide Dieldrin (CW only) 2.4-Dimethylphenol 2,4-Dinitrotoluene 2,6-Dinitrotoluene Endrin Hexachloroethane (inhalation only) (CW only) Manganese Mercury (inhalation only) 2-Methylphenol (o-cresol) Phenol (inhalation only) Selenium Styrene (inhalation only) Tetrachloroethylene (inhalation only) Toluene (inhalation only) Trichloroethylene Xylenes (CW only) (ingestion only) Xylenes (inhalation only)

Reproductive System

Arsenic (inhalation only) Bis(2-ethylhexyl)phthalate (CW only) (ingestion only) Boron 2-Butanone Spleen 1,3-Dinotrobenzene Carbon disulfide (ingestion only) 2-Chlorophenol 1,2-Dibromo-3-chloropropane 1,2-Dibromoethane (ingestion only) Dicamba Dinoseb Ethylbenzene (inhalation only) Isophorone (inhalation only)

Reproductive System (continued)

<u>Methoxychlor</u> <u>Royal Demolition Explosive, Cyclonite (RDX)</u> <u>2,4,6-Trichlorophenol</u>

Respiratory System

Antimony (inhalation only) Benzoic Acid (inhalation only) Beryllium (inhalation only) Cadmium (inhalation only) Chromium (hex) (inhalation only) Cobalt (inhalation only) 1,2-Dibromoethane (inhalation only) trans-1,2-Dichloroethylene (inhalation only) 1,2-Dichloropropane (inhalation only) 1.3-Dichloropropene (cis + trans)(inhalation only) Hexachlorocyclopentadiene (inhalation only) Methyl bromide (inhalation only) Naphthalene (inhalation only) Nickel (inhalation only) Nitrobenezene (inhalation only) Vinyl acetate (inhalation only)

<u>Skin</u>

Arsenic (ingestion only)

Polychlorinated biphenyls (PCBs) Selenium Silver

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

1,3,5-Trinitrobenzene

Notes:

 $\frac{\text{Res.} = \text{Residential receptor}}{\text{I/C} = \text{Industrial Commercial receptor}}$ $\frac{\text{CW} = \text{Construction Worker receptor}}{\text{Worker receptor}}$

(Source: Amended at 36 Ill. Reg. ____, effective ____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742. APPENDIX A: General

Section 742.TABLE F: Similar-Acting Carcinogenic Chemicals

Kidney Bromodichloromethane (Ingestion only) Chloroform (Ingestion only) 1,2-Dibromo-3-chloropropane (Ingestion only) 2,4-Dinitrotoluene 2,6-Dinitrotoluene Hexachlorobenzene Liver Aldrin Bis(2-chloroethyl)ether Bis(2-ethylhexyl)phthalate (Ingestion only) Carbazole Carbon tetrachloride Chlordane Chloroform (Inhalation only) DDD DDE DDT 1,2-Dibromo-3-chloropropane (Ingestion only) 1,2-Dibromoethane(Ingestion only) 3,3'-Dichlorobenzidine 1.2-Dichloroethane 1,2-Dichloropropane (Ingestion only) 1,3-Dichloropropylene (Ingestion only) Dieldrin 2.4-Dinitrotoluene 2,6-Dinitrotoluene Heptachlor Heptachlor epoxide Hexachlorobenzene alpha-HCH gamma-HCH (Lindane) Methylene chloride **N-Nitrosodiphenylamine** N-Nitrosodi-n-propylamine **Pentachlorophenol**

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Tetrachloroethylene Trichloroethylene 2,4,6-Trichlorophenol Toxaphene Vinyl chloride

<u>Circulatory System</u> Benzene 2,4,6-Trichlorophenol

Gastrointestinal-System Benzo(a)anthracene Benzo(b)fluoranthene Benzo(k)fluoranthene Benzo(a)pyrene Chrysene Dibenzo(a,h)anthracene Indeno(1,2,3-c,d)pyrene Bromodichloromethane (Ingestion only) Bromoform 1,2-Dibromo-3-chloropropane (Ingestion only) 1,2-Dibromoethane (Ingestion only) 1,3-Dichloropropylene (Ingestion only)

Lung

Arsenic (Inhalation only) Beryllium (Inhalation only) Cadmium (Inhalation only) Chromium, hexavalent (Inhalation only) 1,3-Dichloropropylene (Inhalation only) Methylene chloride (Inhalation only) N-Nitrosodi-n-propylamine Nickel (Inhalation only) Vinyl chloride

<u>Nasal Cavity</u> 1,2-Dibromo-3-chloropropane (Inhalation only) 1,2-Dibromoethane (Inhalation only) N-Nitrosodi-n-propylamine

Bladder

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

3,30-Dichlorobenzidine 1,3-Dichloropropylene (Ingestion only) N-Nitrosodiphenylamine

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Bladder

<u>1,3-Dichloropropene (cis + trans) (ingestion only)</u> <u>n-Nitrosodiphenylamine</u>

<u>Circulatory System</u>

Benzene 1,2-Dibromoethane 1,2-Dichloroethane Pentachlorophenol 2,4,6-Trichlorophenol

<u>Gall Bladder</u> p-Dioxane (inhalation only)

Gastrointestinal System

Benzo(a)anthracene (ingestion only) Benzo(b)fluoranthene (ingestion only) Benzo(k)flouranthene (ingestion only) Benzo(a)pyrene (ingestion only) Bromoform Chrysene (ingestion only) Dibenzo(a,h)anthracene (ingestion only) 1,2-Dibromoethane (ingestion only) Indeno(1,2,3-cd)pyrene (ingestion only)

<u>Kidney</u>

Bromodichloromethane (ingestion only) Chloroform (ingestion only) 1,2-Dibromo-3-chloropropane (ingestion only) Nitrobenzene

Liver

<u>Aldrin</u> <u>Bis(2-chloroethyl)ether</u> <u>Bis(2-ethylhexyl)phthalate</u> <u>Carbazole</u> Carbon Tetrachloride Liver (continued) Chlordane Chloroform DDD DDE DDT 1,2-Dichloropropane Dieldrin 2.4-Dinitrotoluene 2,6-Dinitrotoluene p-Dioxane Heptachlor Heptachlor epoxide Hexachlorobenzene alpha-HCH (alpha-BHC) gamma-HCH (gamma-BHC) Methylene Chloride Nitrobenzene n-Nitrosodiphenylamine (inhalation only) n-Nitrosodi-n-propylamine Pentachlorophenol Polychlorinated biphenyls (PCBs) Tetrachloroethylene Toxaphene Trichloroethylene Vinyl Chloride (I/C & CW) Vinyl Chloride (Res.)

Mammary Gland

3,3'-Dichlorobenzidine 2,4-Dinitrotoluene 2,6-Dinitrotoluene

Respiratory System

Arsenic (inhalation only) Benzo(a)anthracene (inhalation only) Benzo(b)fluoranthene (inhalation only)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Respiratory System (continued)

Benzo(k)flouranthene (inhalation only) Benzo(a)pyrene (inhalation only) Beryllium Cadmium Chromium (hexavalent ion) Chrysene (inhalation only) Cobalt Dibenzo(a,h)anthracene (inhalation only) 1,2-Dibromo-3-chloropropane (inhalation only) 1,2-Dibromoethane (inhalation only) 1,3-Dichloropropene (*cis* + *trans*) (inhalation only) p-Dioxane (inhalation only) Trichloroethylene

Notes:

 $\frac{\text{Res.} = \text{Residential receptor}}{\text{I/C} = \text{Industrial Commercial receptor}}$ $\frac{\text{CW} = \text{Construction Worker receptor}}{\text{Worker receptor}}$

(Source: Amended at 36 Ill. Reg. _____, effective _____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742. APPENDIX A: General

<u>Section 742.Table J: List of TACO Volatile Chemicals for the Indoor Inhalation</u> <u>Exposure Route</u>

CAS No.	Chemical
<u>67-64-1</u>	Acetone
71-43-2	Benzene
111-44-4	Bis(2-chloroethyl)ether
75-27-4	Bromodichloromethane
75-25-2	Bromoform
71-36-3	Butanol
78-93-3	2-Butanone (MEK)
75-15-0	Carbon disulfide
56-23-5	Carbon tetrachloride
108-90-7	Chlorobenzene
124-48-1	Chlorodibromomethane
67-66-3	Chloroform
<u>95-57-8</u>	2-Chlorophenol
75-99-0	Dalapon
<u>96-12-8</u>	1,2-dibromo-3-chloropropane
106-93-4	1,2-Dibromoethane
<u>95-50-1</u>	1,2-Dichlorobenzene
106-46-7	1,4-Dichlorobenzene
75-71-8	Dichlorodifluoromethane
<u>75-34-3</u>	1,1-Dichloroethane
<u>107-06-2</u>	1,2-Dichloroethane
<u>75-35-4</u>	1,1-Dichloroethylene
<u>156-59-2</u>	cis-1,2-Dichloroethylene
<u>156-60-5</u>	Trans-1,2-Dichloroethylene
78-87-5	1,2-Dichloropropane
<u>542-75-6</u>	1,3-Dichloropropylene (cis + trans)
123-91-1	p-Dioxane
100-41-4	Ethylbenzene
76-44-8	Heptachlor
118-74-1	Hexachlorobenzene
77-47-4	Hexachlorocyclopentadiene
<u>67-72-1</u>	Hexachloroethane
<u>78-59-1</u>	Isophorone
<u>98-82-8</u>	Isopropylbenzene (Cumene)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

CAS No.	Chemical
7439-97-6	Mercury
74-83-9	Methyl bromide
1634-04-4	Methyl tertiary-butyl ether
75-09-2	Methylene chloride
93-65-2	2-Methylnaphthalene
95-48-7	2-Methylphenol (o-cresol)
<u>91-20-3</u>	Naphthalene
<u>98-95-3</u>	Nitrobenzene
<u>621-64-7</u>	n-Nitrosodi-n-propylamine
108-95-2	Phenol
1336-36-3	Polychlorinated biphenyls (PCBs)
100-42-5	Styrene
127-18-4	Tetrachloroethylene
108-88-3	Toluene
<u>120-82-1</u>	1,2,4-Trichlorobenzene
<u>71-55-6</u>	1,1,1-Trichloroethane
<u>79-00-5</u>	1,1,2-Trichloroethane
<u>79-01-6</u>	Trichloroethylene
<u>75-69-4</u>	Trichlorofluoromethane
<u>108-05-4</u>	Vinyl acetate
75-01-4	Vinyl chloride
108-38-3	<u>m-Xylene</u>
<u>95-47-6</u>	<u>o-Xylene</u>
106-42-3	<u>p-Xylene</u>
<u>1330-20-7</u>	Xylenes (total)

(Source: Added at 36 Ill. Reg. ____, effective ____)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742. APPENDIX A: General

Section 742.TABLE K: Soil Vapor Saturation Limits (C_v^{sat}) for Volatile Chemicals

CAS No.	Chemical Name	$\underline{C_v^{sat} (mg/m^3)}$
<u>67-64-1</u>	Acetone	<u>7.50E+05</u>
<u>71-43-2</u>	Benzene	<u>4.20E+05</u>
111-44-4	Bis(2-chloroethyl)ether	<u>1.20E+04</u>
<u>75-27-4</u>	Bromodichloromethane	<u>4.50E+05</u>
<u>75-25-2</u>	Bromoform	<u>7.80E+04</u>
<u>71-36-3</u>	Butanol	<u>2.90E+04</u>
<u>78-93-3</u>	2-Butanone (MEK)	<u>3.80E+05</u>
<u>75-15-0</u>	Carbon disulfide	<u>1.50E+06</u>
<u>56-23-5</u>	Carbon tetrachloride	<u>1.00E+06</u>
<u>108-90-7</u>	Chlorobenzene	<u>7.40E+04</u>
<u>124-48-1</u>	Chlorodibromomethane	<u>5.70E+04</u>
<u>67-66-3</u>	<u>Chloroform</u>	<u>1.30E+06</u>
<u>95-57-8</u>	2-Chlorophenol (ionizable organic)	<u>1.70E+04</u>
<u>75-99-0</u>	Dalapon	<u>1.50E+03</u>
<u>96-12-8</u>	1,2-Dibromo-3-chloropropane	<u>7.80E+03</u>
<u>106-93-4</u>	<u>1,2-Dibromoethane</u>	<u>1.40E+05</u>
<u>95-50-1</u>	1,2-Dichlorobenzene	<u>1.10E+04</u>
106-46-7	<u>1,4-Dichlorobenzene</u>	<u>8.40E+03</u>
<u>75-71-8</u>	Dichlorodifluoromethane	<u>3.30E+07</u>
75-34-3	1,1-Dichloroethane	<u>1.30E+06</u>
107-06-2	1.2-Dichloroethane	<u>4.40E+05</u>
75-35-4	1,1-Dichloroethylene	<u>3.30E+06</u>

POLLUTION CONTROL BOARD

CAS No.	Chemical Name	$\frac{C_v^{sat} (mg/m^3)}{m^3}$
156-59-2	cis-1,2-Dichloroethylene	<u>1.10E+06</u>
<u>156-60-5</u>	trans-1,2-Dichloroethylene	<u>1.80E+06</u>
78-87-5	1,2-Dichloropropane	<u>3.20E+05</u>
<u>542-75-6</u>	1,3-Dichloropropylene (cis + trans)	<u>2.10E+05</u>
<u>123-91-1</u>	<u>p-Dioxane</u>	<u>1.90E+05</u>
100-41-4	Ethylbenzene	<u>5.90E+04</u>
76-44-8	Heptachlor	<u>8.30E+00</u>
<u>118-74-1</u>	Hexachlorobenzene	<u>2.80E-01</u>
77-47-4	Hexachlorocyclopentadiene	<u>9.10E+02</u>
<u>67-72-1</u>	Hexachloroethane	<u>2.80E+03</u>
<u>78-59-1</u>	Isophorone	<u>3.40E+03</u>
<u>98-82-8</u>	Isopropylbenzene (Cumene)	<u>3.00E+04</u>
7439-97-6	Mercury (elemental)	<u>2.20E+01</u>
74-83-9	Methyl bromide	<u>8.60E+06</u>
1634-04-4	Methyl tertiary-butyl ether	<u>1.20E+06</u>
<u>75-09-2</u>	Methylene chloride	<u>2.00E+06</u>
<u>93-65-2</u>	2-Methylnaphthalene	<u>5.30E+02</u>
1634-04-4	2-Methylphenol (o-cresol)	<u>1.80E+03</u>
<u>91-20-3</u>	Naphthalene	<u>6.20E+02</u>
<u>98-95-3</u>	Nitrobenzene	<u>1.70E+03</u>
<u>621-64-7</u>	n-Nitrosodi-n-propylamine	<u>9.50E+02</u>
108-95-2	Phenol	<u>1.50E+03</u>
1336-36-3	Polychlorinated biphenyls (PCBs)	<u>9.00E+00</u>
100-42-5	Styrene	<u>3.40E+04</u>

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

CAS No.	Chemical Name	$\underline{C_v}^{sat}$ (mg/m ³)
127-18-4	Tetrachloroethylene	<u>1.80E+05</u>
108-88-3	Toluene	<u>1.40E+05</u>
120-82-1	<u>1,2,4-Trichlorobenzene</u>	<u>4.30E+03</u>
<u>71-55-6</u>	1,1,1-Trichloroethane	<u>8.70E+05</u>
<u>79-00-5</u>	1,1,2-Trichloroethane	<u>1.70E+05</u>
<u>79-01-6</u>	Trichloroethylene	<u>5.30E+05</u>
75-69-4	Trichlorofluoromethane	<u>6.30E+06</u>
108-05-4	Vinyl acetate	<u>4.30E+05</u>
<u>75-01-4</u>	Vinyl chloride	<u>1.10E+07</u>
108-38-3	<u>m-Xylene</u>	<u>5.20E+04</u>
<u>95-47-6</u>	<u>o-Xylene</u>	<u>4.10E+04</u>
106-42-3	<u>p-Xylene</u>	<u>5.50E+04</u>
1330-20-7	Xylenes (total)	<u>4.90E+04</u>

(Source: Added at 36 Ill. Reg. ____, effective ____)

Section 742. APPENDIX B: Tier 1 Illustrations and Tables

Section 742.TABLE G: Tier 1 Soil Gas Remediation Objectives for the Outdoor Inhalation Exposure Route^a

		1	107	ГIC	ЕC)F F	PRC	OPC	SE	D A	AM]	ENI	DM	EN	TS							
Construction Worker (mg/m ³)	750,000 ^e	$1,100^{\circ}$	<u>3.4°</u>	450,000 ^e	$4,900^{\circ}$	$29,000^{\circ}$	<u>15,000^b</u>	$48,000^{b}$	<u>770°</u>	3.700^{b}	<u>150^b</u>	290°	$17,000^{e}$	1.500°	<u>0.38^c</u>	<u>7.9°</u>	$6,700^{b}$	6.400^{b}	$92,000^{b}$	90,000 ^b	180°	$5,300^{\mathrm{b}}$
Industrial/Commercial (mg/m ³)	750,000 ^c	<u>800</u> ^c	2.4 ^c	$450,000^{e}$	$3,500^{\circ}$	$29,000^{\circ}$	<u>380,000[¢]</u>	$1.500,000^{\circ}$	<u>550°</u>	<u>57,000^b</u>	<u>57,000^e</u>	200°	$17,000^{\circ}$	1.500°	<u>0.27^c</u>	<u>5.6°</u>	$11,000^{\circ}$	$8,400^{\circ}$	$1,400,000^{\rm b}$	$1,300,000^{\circ}$	<u>130^c</u>	820,000 ^b
<u>Residential</u> (mg/m ³)	750,000 ^e	420°	<u>1.3^c</u>	$450,000^{\circ}$	$1,800^{c}$	29,000 ^e	<u>380,000^e</u>	$1,500,000^{e}$	290°	<u>36,000^b</u>	$\overline{57,000^{e}}$	110°	$17,000^{e}$	$1,500^{\circ}$	0.14°	2.9 ^c	$11,000^{e}$	$8,400^{\circ}$	<u>890,000^b</u>	<u>870,000^b</u>	<u>67^c</u>	$520,000^{\rm b}$
Chemical Name	Acetone	Benzene	Bis(2-chloroethyl)ether	Bromodichloromethane	Bromoform	<u>Butanol</u>	2-Butanone (MEK)	Carbon disulfide	Carbon tetrachloride	Chlorobenzene	<u>Chlorodibromomethane</u>	<u>Chloroform</u>	<u>2-Chlorophenol</u>	Dalapon	<u>1,2-Dibromo-3-</u> <u>chloropropane</u>	1,2-Dibromoethane	1,2-Dichlorobenzene	<u>1,4-Dichlorobenzene</u>	Dichlorodifluoromethane	1,1-Dichloroethane	<u>1,2-Dichloroethane</u>	<u>1,1-Dichloroethylene</u>
CAS No.	<u>67-64-1</u>	71-43-2	111-44-4	75-27-4	75-25-2	71-36-3	78-93-3	75-15-0	56-23-5	108-90-7	124-48-1	67-66-3	95-57-8	75-99-0	<u>96-12-8</u>	106-93-4	<u>95-50-1</u>	106-46-7	75-71-8	75-34-3	107-06-2	75-35-4

POLLUTION CONTROL BOARD

ILLINOIS REGISTER

	,						-			-														
<u>Construction Worker</u> (<u>mg/m³</u>)	$1,100,000^{\circ}$	$12,000^{b}$	<u>110°</u>	$1,400^{\circ}$	<u>42°</u>	$8,500^{b}$	1.1 ^c	0.28 ^e	440^{b}	$2,800^{\circ}$	1.500^{b}	$30,000^{\circ}$	<u>0.62^b</u>	$2,400^{b}$	$23,000^{b}$	$5,100^{b}$	<u>530^e</u>	<u>410^b</u>	<u>5.8^b</u>	10^{b}	<u>0.15^c</u>	$\overline{46L}$	p	$16,000^{b}$
<u>Industrial/Commercial</u> (<u>mg/m³</u>)	$1,100,000^{\circ}$	<u>190,000^b</u>	<u>470^c</u>	<u>3,700°</u>	<u>30^c</u>	<u>59,000^e</u>	<u>0.76°</u>	<u>0.28^e</u>	140^{b}	$2,800^{\circ}$	$3,400^{\circ}$	<u>30,000</u> €	<u>22^e</u>	$19,000^{b}$	$1,200,000^{e}$	$12,000^{c}$	<u>530°</u>	$1,800^{\circ}$	<u>620^e</u>	<u>12^c</u>	<u>0.11^c</u>	1.500°	p	$34,000^{\circ}$
<u>Residential</u> (mg/m ³)	$1,100,000^{\circ}$	<u>120,000^b</u>	240°	1.900°	<u>16^c</u>	<u>59,000^e</u>	<u>0.40^c</u>	<u>0.26°</u>	<u>85^b</u>	$2,800^{\circ}$	$3,400^{\circ}$	$30,000^{\circ}$	<u>22^e</u>	<u>12,000^b</u>	$1,200,000^{e}$	<u>6,100^c</u>	<u>530^e</u>	$1,800^{\circ}$	<u>560^b</u>	<u>6.5°</u>	<u>0.056^c</u>	$1,500^{e}$	d	<u>34,000^e</u>
<u>Chemical Name</u>	cis-1,2-Dichloroethylene	trans-1,2-Dichloroethylene	1,2-Dichloropropane	<u>1,3-Dichloropropylene (cis</u> + trans)	p-Dioxane	Ethylbenzene	<u>Heptachlor</u>	Hexachlorobenzene	Hexachlorocyclopentadiene	<u>Hexachloroethane</u>	Isophorone	Isopropylbenzene (Cumene)	<u>Mercury^f</u>	<u>Methyl bromide</u>	Methyl tertiary-butyl ether	Methylene chloride	2-Methylnaphthalene	2-Methylphenol (o-cresol)	<u>Naphthalene</u>	Nitrobenzene	n-Nitrosodi-n-propylamine	Phenol	<u>Polychlorinated biphenyls</u> (PCBs)	Styrene
<u>CAS No.</u>	<u>156-59-2</u>	156-60-5	78-87-5	<u>542-75-6</u>	123-91-1	100-41-4	76-44-8	<u>118-74-1</u>	77-47-4	<u>67-72-1</u>	78-59-1	98-82-8	7439-97-6	74-83-9	1634-04-4	75-09-2	<u>91-57-6</u>	<u>95-48-7</u>	<u>91-20-3</u>	<u>98-95-3</u>	<u>621-64-7</u>	108-95-2	1336-36-3	<u>100-42-5</u>

POLLUTION CONTROL BOARD

[1	1	1	NC		CE	OF	PR	OP	OS	ED	
Construction Worker (mg/m ³)	<u>970°</u>	$50,000^{b}$	<u>110^b</u>	89,000 ^b	$170,000^{\circ}$	$1,500^{b}$	$220,000^{b}$	$1,600^{b}$	$3,000^{\mathrm{b}}$	$3,100^{\rm b}$	$2,600^{b}$	$3,300^{\rm b}$	$2,900^{\rm b}$	<u>leeting either the soil or so</u> oute are located in
Industrial/Commercial (mg/m ³)	<u>690°</u>	$140,000^{\circ}$	$1,600^{b}$	870,000 ^e	<u>170,000^e</u>	$3,300^{\circ}$	$3,400,000^{\rm b}$	250,000 ^b	$3,000^{\circ}$	$52,000^{\circ}$	$41,000^{\circ}$	$55,000^{\circ}$	<u>49,000^e</u>	in Objective Notations (posure route, it is acceptable to determine compliance by meeting either the s The soil remediation objectives for the outdoor inhalation route are located in s.
<u>Residential</u> (mg/m ³)	<u>360°</u>	$140,000^{\circ}$	$1,000^{b}$	<u>870,000^e</u>	$170,000^{e}$	$1,700^{c}$	<u>2,100,000^b</u>	<u>160,000^b</u>	<u>780^c</u>	<u>52,000^e</u>	$41,000^{\circ}$	$55,000^{\circ}$	$49,000^{\circ}$	e Notations te, it is acceptable to nediation objectives f
Chemical Name	<u>Tetrachloroethylene</u>	Toluene	1,2,4-Trichlorobenzene	1,1,1-Trichloroethane	1,1,2-Trichloroethane	<u>Trichloroethylene</u>	Trichlorofluoromethane	Vinyl acetate	Vinyl chloride	<u>m-Xylene</u>	o-Xylene	p-Xylene	Xylenes (total)	Chemical Name and Remediation Objective Notations Events in the outdoor inhalation exposure route, it is acceptable to determine compliance by meeting either the soil or soil gas remediation objectives. The soil remediation objectives for the outdoor inhalation route are located in Appendix B, Tables A and B.
CAS No.	127-18-4	108-88-3	120-82-1	71-55-6	79-00-5	79-01-6	75-69-4	108-05-4	75-01-4	108-38-3	<u>95-47-6</u>	106-42-3	1330-20-7	Chemical Nan Ever the ou gas remed Appendix

- For the outdoor inhalation exposure route, it is acceptable to determine compliance by meeting either the soil or soil gas remediation objectives. The soil remediation objectives for the outdoor inhalation route are located in Appendix B, Tables A and B. cal
 - Calculated values correspond to a target hazard quotient of 1. اھ.
- Calculated values correspond to a cancer risk level of 1 in 1,000,000 ပ၊
- PCBs are a mixture of different congeners. The appropriate values to use for the physical/chemical and toxicity parameters depend on the congeners present at the site. Persons remediating sites should consult with BOL if calculation of Tier 2 or 3 remediation objectives is desired q
- objective if the calculated value exceeds the C_v^{sat} value or if there are no toxicity criteria available for the inhalation The value shown is the C_v^{sat} value of the chemical in soil gas. The C_v^{sat} of the chemical becomes the remediation route of exposure. o

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

7439-97-6). Inhalation remediation objectives only apply at sites where elemental Mercury is a contaminant of Value for the inhalation exposure route is based on Reference Concentration for elemental Mercury (CAS No. concern. 4---1

(Source: Added at 36 Ill. Reg. ____, effective _____

POLLUTION CONTROL BOARD

Section 742. APPENDIX B: Tier 1 Illustrations and Tables

<u>Section 742.TABLE H:</u> <u>Tier 1 Soil Gas and Groundwater Remediation Objectives for the Indoor Inhalation</u> <u>Exposure Route – Diffusion and Advection</u>

Q _{soil} equals 8	Q _{soil} equals 83.33 cm ³ /sec ^a					
			Soil Gas		Groundwater	
CAS No.	Chemical Name	Residential (mg/m ³)	Industrial/Commercial (mg/m ³)	Residential (mg/L)	Industrial/Commercial (mg/L)	Ν
<u>67-64-1</u>	Acetone	750,000 ^f	750,000 ^f	$1,000,000^{g}$	$1,000,000^{\$}$	OT
71-43-2	<u>Benzene</u>	<u>0.37^c</u>	2.8 ^c	<u>0.11^c</u>	<u>0.41^c</u>	ICE
111-44-4	Bis(2-chloroethyl)ether	<u>0.014^c</u>	<u>0.087^c</u>	<u>0.083°</u>	<u>0.43°</u>	E OI
75-27-4	Bromodichloromethane	$450,000^{f}$	<u>450,000^f</u>	$\underline{6,700^{g}}$	<u>6,700^g</u>	F PI
75-25-2	Bromoform	<u>11^c</u>	<u>52°</u>	<u>3.1°</u>	<u>12°</u>	ROI
71-36-3	<u>Butanol</u>	$29,000^{f}$	<u>29,000^f</u>	$74,000^{g}$	$74,000^{g}$	205
78-93-3	2-Butanone (MEK)	$6,400^{b}$	$40,000^{b}$	<u>10,000^b</u>	48,000 ^b	SED
75-15-0	<u>Carbon disulfide</u>	<u>780^b</u>	$5,300^{b}$	<u>67^b</u>	210 ^b) A]
56-23-5	Carbon tetrachloride	<u>0.21^c</u>	<u>1.5^c</u>	<u>0.020^c</u>	<u>0.076^c</u>	ME
108-90-7	<u>Chlorobenzene</u>	<u>69</u> ^b	420^{b}	26^{b}	<u>82^b</u>	ND
124-48-1	Chlorodibromomethane	<u>57,000^f</u>	<u>57,000^f</u>	$2,600^{g}$	$2,600^{g}$	ME
<u>67-66-3</u>	<u>Chloroform</u>	<u>0.11^c</u>	<u>0.92^c</u>	0.07^{i}	<u>0.15^c</u>	ENT
<u>95-57-8</u>	<u>2-Chlorophenol</u>	$17,000^{f}$	<u>17,000^f</u>	$22,000^{g}$	$22,000^{g}$	ſS
75-99-0	<u>Dalapon^e</u>	$1,500^{f}$	$1,500^{\mathrm{f}}$	$900,000^{g}$	900,000 ^g	
<u>96-12-8</u>	<u>1,2-Dibromo-3-</u> <u>chloropropane^e</u>	<u>0.0012^c</u>	<u>0.0062°</u>	<u>0.00065°</u>	<u>0.0027^c</u>	
106-93-4	<u>1,2-Dibromoethane</u>	<u>0.0078°</u>	0.048°	<u>0.0035^c</u>	<u>0.014^c</u>	
<u>95-50-1</u>	1,2-Dichlorobenzene	<u>290^b</u>	$1,700^{b}$	<u>140^b</u>	<u>160^g</u>	
106-46-7	<u>1,4-Dichlorobenzene</u>	$1,200^{b}$	$6.800^{\rm b}$	<u>79⁸</u>	<u>79^g</u>	
75-71-8	Dichlorodifluoromethane	<u>270^b</u>	$1,700^{b}$	<u>3.0^b</u>	<u>9.2^b</u>	

POLLUTION CONTROL BOARD

ILLINOIS REGISTER

	rcial																								
Groundwater	Industrial/Commercial (mg/L)	<u>580</u> ^b	<u>0.22^c</u>	74 ^b	$3,500^{g}$	<u>51^b</u>	<u>0.48^c</u>	<u>0.52^c</u>	25 ^c	<u>1.4°</u>	<u>0.0096°</u>	0.0062^{g}	<u>0.26^b</u>	$\overline{50^g}$	$\underline{12,000^g}$	<u>8.4^b</u>	$\underline{0.060^{g}}$	<u>4.8^b</u>	<u>6,800^b</u>	<u>8.2</u> ^c	<u>25^g</u>	$26,000^{g}$	<u>0.32^c</u>	<u>2.0°</u>	
	Residential (mg/L)	<u>180^b</u>	<u>0.054^c</u>	$\frac{24^{b}}{24}$	$3,500^{g}$	16^{b}	<u>0.12^c</u>	<u>0.14^c</u>	<u>2.9°</u>	0.37^{c}	<u>0.0025^c</u>	<u>0.0059°</u>	0.084^{b}	$\overline{50^{g}}$	$12,000^{g}$	$\frac{2.7^{b}}{2.7}$	<u>0.053^b</u>	$\frac{1.5^{b}}{2}$	$1,900^{b}$	<u>2.1^c</u>	<u>25^g</u>	$26,000^{g}$	<u>0.075^c</u>	0.34°	0,10,0
Soil Gas	<u>Industrial/Commercial</u> (mg/m ³)	$4,200^{b}$	<u>0.81^c</u>	$1,600^{b}$	$1,100,000^{f}$	<u>510^b</u>	<u>2.3^c</u>	<u>6.2°</u>	<u>2.3</u> ^c	<u>9.3°</u>	<u>0.032^c</u>	<u>0.057^c</u>	2.6^{b}	$2,800^{f}$	$\underline{3,400^{f}}$	$3,500^{\rm b}$	<u>2.5^b</u>	<u>42^b</u>	$24,000^{b}$	<u>45°</u>	<u>530^f</u>	$1,800^{\mathrm{f}}$	<u>0.75^c</u>	0.57°	0 01 00
	<u>Residential</u> (mg/m ³)	<u>690^b</u>	<u>0.099°</u>	240^{b}	$1,100,000^{f}$	<u>85^b</u>	$0.31^{\rm c}$	<u>0.90^c</u>	<u>0.22°</u>	<u>1,3</u> ^c	<u>0.0063°</u>	<u>0.0087^c</u>	0.58^{b}	$2,800^{\mathrm{f}}$	$2,900^{b}$	<u>600^b</u>	0.42^{b}	$\overline{6.9^{b}}$	$3,700^{b}$	<u>5.6^c</u>	$\overline{530^{f}}$	<u>600^b</u>	0.11^{c}	<u>0.077^c</u>	
	Chemical Name	1,1-Dichloroethane	1,2-Dichloroethane	<u>1,1-Dichloroethylene</u>	cis-1,2-Dichloroethylene	trans-1,2-Dichloroethylene	1,2-Dichloropropane	<u>1,3-Dichloropropylene (cis</u> + trans]	p-Dioxane	Ethylbenzene	Heptachlor	Hexachlorobenzene	Hexachlorocyclopentadiene	<u>Hexachloroethane</u>	Isophorone	Isopropylbenzene (Cumene)	Mercury ^h	<u>Methyl bromide</u>	Methyl tertiary-butyl ether	<u>Methylene chloride</u>	2-Methylnaphthalene	2-Methylphenol (o-cresol)	Naphthalene	Nitrobenzene	AT'. 1
	CAS No.	75-34-3	107-06-2	75-35-4	156-59-2	<u>156-60-5</u>	78-87-5	542-75-6	123-91-1	100-41-4	76-44-8	118-74-1	77-47-4	<u>67-72-1</u>	78-59-1	<u>98-82-8</u>	7439-97-6	74-83-9	1634-04-4	75-09-2	<u>91-57-6</u>	95-48-7	<u>91-20-3</u>	<u>98-95-3</u>	

POLLUTION CONTROL BOARD

			<u>Soil Gas</u>		Groundwater
CAS No.	Chemical Name	<u>Residential</u> (mg/m ³)	Industrial/Commercial (mg/m ³)	Residential (mg/L)	Industrial/Commercial (mg/L)
108-95-2	Phenol	140^{b}	$1,300^{b}$	<u>28,000^b</u>	<u>83,000^g</u>
1336-36-3	Polychlorinated biphenyls (PCBs)	p	p	p	p
100-42-5	Styrene	$1,400^{b}$	$8,500^{b}$	310^{g}	310^{g}
127-18-4	<u>Tetrachloroethylene</u>	<u>0.55°</u>	<u>4.0^c</u>	<u>0.091^c</u>	<u>0.34°</u>
108-88-3	Toluene	$6,200^{b}$	$40,000^{b}$	530 ^g	530 ^g
120-82-1	1,2,4-Trichlorobenzene	<u>5.4^b</u>	<u>25^b</u>	<u>1.8</u>	<u>5.9^b</u>
71-55-6	1,1,1-Trichloroethane	<u>6,600^b</u>	$41,000^{b}$	$1,000^{b}$	$1,300^{\sharp}$
79-00-5	1,1,2-Trichloroethane	<u>170,000^f</u>	<u>170,000^f</u>	$4,400^{8}$	$4,400^{g}$
79-01-6	Trichloroethylene	<u>1.5°</u>	<u>12^c</u>	<u>0.34</u> °	<u>1.3^c</u>
75-69-4	Trichlorofluoromethane	<u>860^b</u>	$5,600^{b}$	26^{b}	<u>82^b</u>
108-05-4	Vinyl acetate	250 ^b	$1,600^{b}$	<u>160^b</u>	<u>550^b</u>
75-01-4	Vinyl chloride	<u>0.29°</u>	<u>4.8</u> ^c	<u>0.028°</u>	<u>0.21^c</u>
108-38-3	<u>m-Xylene</u>	140^{b}	<u>850^b</u>	<u>43^b</u>	130^{b}
95-47-6	o-Xylene	120^{b}	<u>م067</u>	40 ^b	<u>130^b</u>
106-42-3	p-Xylene	<u>130^b</u>	$\underline{820^{b}}$	$\overline{38^{b}}$	<u>120^b</u>
1330-20-7	<u>Xylenes (total)^e</u>	140^{b}	$\underline{840^{b}}$	$\overline{30^{b}}$	$\overline{93^{b}}$
<u>Chemical Na</u> <u>^a Compliar</u>	Chemical Name and Remediation Objective Notations Compliance is determined by meeting either the soil gas remediation objectives or the groundwater remediation	e Notations ither the soil g	as remediation objectives o	or the ground	water remediation
01	objectives. See Sections 742.505 and 742.515	<u>12.515.</u>			
² Calculate	Calculated values correspond to a target hazard quotient of 1. Calculated values correspond to a cancer risk level of 1 in 1 000 000	<u>: hazard quotie</u> r risk level of	<u>mt of 1.</u> 1 in 1 000 000		
d PCBs are	PCBs are a mixture of different congeners. The appropriate values to use for the physical/chemical and toxicity	ers. The appro	priate values to use for the	e physical/che	mical and toxicity
paramete	parameters depend on the congeners present at the site. Persons remediating sites should consult with BOL if	sent at the site	e. Persons remediating site	es should cons	ult with BOL if
•		•	-		

calculation of Tier 2 or 3 remediation objectives is desired.

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

7439-97-6). Inhalation remediation objectives only apply at sites where elemental Mercury is a contaminant of Value for the inhalation exposure route is based on Reference Concentration for elemental Mercury (CAS No. route of exposure. concern. Ч

The value shown is the Groundwater Remediation Objective listed in Appendix B, Table E. • ----1

(Source: Added at 36 Ill. Reg. ____, effective

POLLUTION CONTROL BOARD

Section 742. APPENDIX B: Tier 1 Illustrations and Tables

Section 742.TABLE I: Tier 1 Soil Gas and Groundwater Remediation Objectives for the Indoor Inhalation **Exposure Route – Diffusion Only**

Q_{soil} equals 0.0 cm³/sec^{a,b}

		lercial				E O	F P	RO	PO	SE	D A	MI	ENI		EN	TS						
	Groundwater	Industrial/Commercial	(mg/L)	$1,000,000^{h}$	2.6^{d}	<u>48^d</u>	<u>6,700^h</u>	$1,300^{d}$	$74,000^{h}$	<u>220,000^h</u>	<u>820^c</u>	0.31^{d}	470 ^h	$2,600^{h}$	<u>1.1^d</u>	22,000 ^h	<u>4000'006</u>	<u>0.21^d</u>	<u>0.52^d</u>	160^{h}	$\frac{1}{4}$	200
	5	Residential	(mg/L)	$1,000,000^{\rm h}$	<u>0.41^d</u>	<u>6.6^d</u>	$6,700^{h}$	<u>170^d</u>	$74,000^{h}$	<u>220,000^h</u>	<u>170^c</u>	<u>0.052^d</u>	<u>130^c</u>	$2,600^{h}$	0.17^{d}	<u>22,000^h</u>	$900,000^{h}$	<u>0.029^d</u>	<u>0.073^d</u>	<u>160^h</u>	<u>79^h</u>	1 00
	Soil Gas	Industrial/Commercial	(mg/m^3)	$750,000^{g}$	<u>300^d</u>	<u>14^d</u>	$\underline{450,000^{\sharp}}$	$13,000^{d}$	$29,000^{g}$	$380,000^{\text{g}}$	$500,000^{\circ}$	<u>180^d</u>	$51,000^{\circ}$	$\overline{57,000^{g}}$	<u>87^d</u>	$\underline{17,000^{\tt g}}$	1.500^{g}	<u>1.3^d</u>	<u>7.9^d</u>	$\underline{11,000^{g}}$	$8,400^{g}$	000 000
		Residential	(mg/m^3)	$750,000^{g}$	<u>41^d</u>	1.9^{d}	$450,000^{g}$	$1,800^{d}$	$29,000^{g}$	$380,000^{g}$	$81,000^{c}$	24^{d}	$\underline{8,300^{c}}$	$57,000^{g}$	12^{d}	$17,000^{g}$	$1,500^{g}$	0.17^{d}	<u>1.1^d</u>	$11,000^{g}$	$8,400^{g}$	<u>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</u>
$.0 \text{ cm}^3/\text{sec}^{4,0}$		Chaminel Mamo	CIRCUITCAL INALLIC	Acetone	Benzene	Bis(2-chloroethyl)ether	Bromodichloromethane	<u>Bromoform</u>	<u>Butanol</u>	2-Butanone (MEK)	<u>Carbon disulfide</u>	Carbon tetrachloride	<u>Chlorobenzene</u>	<u>Chlorodibromomethane</u>	<u>Chloroform</u>	2-Chlorophenol	<u>Dalapon^f</u>	<u>1,2-Dibromo-3-</u> chloropropane ^f	1,2-Dibromoethane	<u>1,2-Dichlorobenzene</u>	<u>1,4-Dichlorobenzene</u>	N: 11 1.0
Q_{soil} equals 0.0 cm ² /sec ^{4,0}			CAD INU.	<u>67-64-1</u>	71-43-2	111-44-4	75-27-4	75-25-2	71-36-3	78-93-3	75-15-0	56-23-5	108-90-7	124-48-1	67-66-3	95-57-8	75-99-0	96-12-8	106-93-4	95-50-1	<u>106-46-7</u>	75 71 0

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

			Soil Gas		Groundwater
CAS No.	Chemical Name	Residential (mg/m ³)	Industrial/Commercial	Residential	Industrial/Commercial
75-34-3	1,1-Dichloroethane	<u>81,000^c</u>	<u>500,000^c</u>	750 ^c	$4,100^{\circ}$
107-06-2	1,2-Dichloroethane	10^{d}	<u>76^d</u>	<u>0.50^d</u>	<u>3.5^d</u>
75-35-4	1,1-Dichloroethylene	<u>27,000^c</u>	$160,000^{\circ}$	<u>61°</u>	300°
156-59-2	cis-1,2-Dichloroethylene	$1,100,000^{B}$	$1,100,000^{g}$	$3,500^{\rm h}$	$3,500^{h}$
<u>156-60-5</u>	trans-1,2-Dichloroethylene	$10,000^{\circ}$	$63,000^{\circ}$	<u>58</u> °	<u>310^c</u>
78-87-5	1.2-Dichloropropane	36^{d}	260^{d}	<u>0.67^d</u>	<u>4.5^d</u>
<u>542-75-6</u>	<u>1,3-Dichloropropylene (cis</u> + trans)	$\frac{110^{d}}{10}$	<u>830^d</u>	<u>0.42^d</u>	<u>2.6^d</u>
123-91-1	p-Dioxane	<u>15</u> ^d	<u>110^d</u>	<u>140^d</u>	$1,000^{d}$
100-41-4	Ethylbenzene	<u>150^d</u>	$1,100^{d}$	<u>1.3^d</u>	<u>8.1^d</u>
76-44-8	<u>Heptachlor</u>	$\overline{0.97^{d}}$	7.1 ^d	<u>0.058^d</u>	0.18^{h}
118-74-1	<u>Hexachlorobenzene</u>	<u>0.28^g</u>	<u>0.28^g</u>	<u>0.0062^h</u>	<u>0.0062^h</u>
77-47-4	<u>Hexachlorocyclopentadiene</u>	<u>86°</u>	<u>530^c</u>	<u>0.29^c</u>	<u>1.5^c</u>
<u>67-72-1</u>	<u>Hexachloroethane</u>	$2,800^{g}$	$2,800^{\text{B}}$	<u>50</u> ^h	<u>50^h</u>
78-59-1	Isophorone	$3,400^{B}$	$3,400^{B}$	<u>12,000^h</u>	<u>12,000^h</u>
<u>98-82-8</u>	Isopropylbenzene (Cumene)	<u>30,000^g</u>	$30,000^{g}$	<u>6.2</u> ^c	<u>30°</u>
7439-97-6	<u>Mercury</u> ⁱ	<u>22^g</u>	<u>22^B</u>	0.060^{h}	<u>0.060^h</u>
74-83-9	<u>Methyl bromide</u>	<u>830^c</u>	$\overline{5,100^{c}}$	<u>6.1^c</u>	<u>33°</u>
<u>1634-04-4</u>	Methyl tertiary-butyl ether	<u>420,000°</u>	$1,200,000^{g}$	$30,000^{\circ}$	<u>51,000^h</u>
75-09-2	Methylene chloride	$\overline{590^{d}}$	$4,400^{d}$	<u>12^d</u>	<u>84^d</u>
<u>91-57-6</u>	<u>2-Methylnaphthalene</u>	<u>530^g</u>	<u>530^g</u>	25^{h}	<u>25^h</u>
<u>95-48-7</u>	2-Methylphenol (o-cresol)	$1,800^{g}$	$1,800^{\text{B}}$	<u>26,000^h</u>	$26,000^{h}$
<u>91-20-3</u>	<u>Naphthalene</u>	<u>14</u> d	<u>100^d</u>	<u>1.8</u> ^d	<u>13^d</u>
<u>98-95-3</u>	<u>Nitrobenzene</u>	9.0^{d}	<u>66^d</u>	<u>23^d</u>	<u>170^d</u>
<u>621-64-7</u>	<u>n-Nitrosodi-n-propylamine</u>	0.18^{d}	<u>1.3^d</u>	<u>3.3^d</u>	24 ^d

POLLUTION CONTROL BOARD

		Τ	1			T												
Groundwater	Industrial/Commercial (mg/L)	$83,000^{h}$	ບ 	$\frac{310^{\text{h}}}{310^{\text{h}}}$	1.6^{d}	<u>530^h</u>	$35^{\rm h}$	$1,300^{\mathrm{h}}$	$4,400^{h}$	<u>6.7^d</u>	300°	$15,000^{\circ}$	0.75^{d}	<u>160^h</u>	<u>180^h</u>	<u>160^h</u>	<u>110^h</u>	
5	Residential (mg/L)	83,000 ^h	e 	$\frac{310^{\text{h}}}{310^{\text{h}}}$	<u>0.26^d</u>	<u>530^h</u>	$\overline{35^{h}}$	$1,300^{h}$	$4,400^{h}$	<u>1.1^d</u>	<u>62</u> °	2.500°	<u>0.065^d</u>	160°	<u>170^c</u>	140°	$\overline{96^{\circ}}$	
Soil Gas	Industrial/Commercial (mg/m ³)	$1,500^{g}$	ຍ 	$34,000^{\text{g}}$	490 ^d	$\underline{140,000^{\$}}$	$4,300^{\mathrm{g}}$	$870,000^{\ell}$	$170,000^{g}$	$1,300^{d}$	$\overline{600,000^{\circ}}$	$170,000^{\circ}$	440^{d}	$52,000^{\circ}$	$41,000^{\circ}$	$55,000^{\circ}$	$49,000^{\circ}$	
	<u>Residential</u> (mg/m ³)	$1,500^{g}$	0	$34,000^{g}$	<u>66^d</u>	$\underline{140,000^{g}}$	<u>800°</u>	$770,000^{\circ}$	$170,000^{g}$	180^{d}	<u>97,000°</u>	$28,000^{\circ}$	$\overline{30^{d}}$	$17,000^{d}$	<u>14,000^d</u>	<u>16,000^d</u>	<u>17,000^d</u>	
	Chemical Name	Phenol	Polychlorinated biphenyls (PCBs)	Styrene	Tetrachloroethylene	Toluene	1,2,4-Trichlorobenzene	1,1,1-Trichloroethane	<u>1,1,2-Trichloroethane</u>	Trichloroethylene	Trichlorofluoromethane	Vinyl acetate	<u>Vinyl chloride</u>	<u>m-Xylene</u>	<u>o-Xylene</u>	p-Xylene	<u>Xylenes (total)^f</u>	
	CAS No.	108-95-2	1336-36-3	100-42-5	127-18-4	108-88-3	120-82-1	71-55-6	79-00-5	79-01-6	75-69-4	108-05-4	75-01-4	108-38-3	95-47-6	106-42-3	<u>1330-20-7</u>	

Chemical Name and Remediation Objective Notations

- Compliance is determined by meeting both the soil gas remediation objectives and the groundwater remediation objectives. See Sections 742.505 and 742.515. ଟା
 - Remediation objectives relying on this table require use of institutional controls in accordance with Subpart J. a.
 - Calculated values correspond to a cancer risk level of 1 in 1,000,000. Calculated values correspond to a target hazard quotient of 1. u u

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

<u>ченирегание (т.с.) ани синцару от уароплацон ан цие понциа роциц (п.ч.о.) аге пот available. For Aylenes</u> (total), the enthalpy of vaporization at the normal boiling point (Hv,b) is not available. 50

objective if the calculated value exceeds the Cv^{at} value or if there are no toxicity criteria available for the inhalation The value shown is the C_v^{sat} value of the chemical in soil gas. The C_v^{sat} of the chemical becomes the remediation route of exposure.

The value shown is the solubility of the chemical in water. The solubility of the chemical becomes the remediation objective if the calculated value exceeds the solubility or if there are no toxicity criteria available for the inhalation route of exposure. ı ع • ----

Value for the inhalation exposure route is based on Reference Concentration for elemental Mercury (CAS No. 7439-97-6). Inhalation remediation objectives only apply at sites where elemental Mercury is a contaminant of concern.

(Source: Added at 36 Ill. Reg. _____, effective _____

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

S S3 **S**4 5 $-\bullet 10^{-6} \frac{kg}{M} \bullet EF \bullet ED \bullet IR_{soil}$ $SF_o \bullet 10^{-6} \frac{kg}{mc} \bullet EF \bullet ED \bullet IR_{soil}$ $SF_o \bullet 10^{-6} \frac{kg}{m\sigma} \bullet EF \bullet IF_{soil-adj}$ yr $THQ \bullet BW \bullet AT \bullet 365 \stackrel{d}{--}$ Vr $TR \bullet BW \bullet AT_c \bullet 365 \frac{d}{d}$ \overline{VF} γľ $TR \bullet AT_c \bullet 365 \frac{d}{d}$ vr $THQ \bullet AT \bullet 365 \stackrel{d}{--}$ <u>RfC</u> Вш вш $EF \bullet ED \bullet$ Вш RfD_{o} Noncarcinogenic Noncarcinogenic Contaminants -Contaminants -Contaminants -Objectives for Objectives for Objectives for Objectives for Contaminants Carcinogenic Carcinogenic Remediation Remediation Remediation Commercial, Construction Remediation Commercial Residential, Residential Industrial/ Industrial/ (mg/kg) (mg/kg) (mg/kg) Worker (mg/kg) Soil Ingestion Contaminants Equations for Equations for and Mercury) Inhalation Exposure Exposure (Organic Route Route

Section 742.APPENDIX C: Tier 2 Illustrations and Tables

Section 742. Table A: SSL Equations

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

POLLUTION CONTROL BOARD

SS	S6	S7	S8	S9
$THQ \bullet AT \bullet 365 \frac{d}{yr}$ $EF \bullet ED \bullet \left(\frac{1}{RfC} \bullet \frac{1}{VF'}\right)$	$TR \bullet AT_c \bullet 365 \frac{d}{yr}$ $URF \bullet 1,000 \frac{ug}{mg} \bullet EF \bullet ED \bullet \frac{1}{VF}$	$TR \bullet AT_c \bullet 365 \frac{d}{yr}$ $URF \bullet 1,000 \frac{ug}{mg} \bullet EF \bullet ED \bullet \frac{1}{VF'}$	$VF = \frac{Q}{C} \bullet \frac{\left(3.14 \bullet D_A \bullet T\right)^{1/2}}{\left(2 \bullet \rho_b \bullet D_A\right)} \bullet 10^{-4} \frac{m^2}{cm^2}$	$VF' = \frac{VF}{10}$
Remediation Objectives for Noncarcinogenic Contaminants - Construction Worker (mg/kg)	Remediation Objectives for Carcinogenic Contaminants - Residential, Industrial/ Commercial (mg/kg)	Remediation Objectives for Carcinogenic Contaminants - Construction Worker (mg/kg)	Equation for Equation of the Derivation of the Volatilization Factor - Residential, Industrial/ Commercial, VF (m ³ /kg)	Equation for Derivation of the

POLLUTION CONTROL BOARD

	Volatilization Factor - Construction Worker, VF' (m ³ /kg)		
	Equation for Derivation of Apparent Diffusivity, D _A (cm ² /s)	$D_{A} = \frac{\left(\theta_{a}^{3.33} \bullet D_{i} \bullet H\right) + \left(\theta_{w}^{3.33} \bullet D_{w}\right)}{\mathfrak{n}^{2}} \bullet \frac{1}{\left(\rho_{b} \bullet K_{d}\right) + \theta_{w} + \left(\theta_{a} \bullet H\right)}$	S10
Equations for Inhalation Exposure Route (Fugitive Dusts)	Remediation Objectives for Noncarcinogenic Contaminants - Residential, Industrial/Comm ercial (mg/kg)	$THQ \bullet AT \bullet 365 \frac{d}{yr}$ $EF \bullet ED \bullet \left(\frac{1}{RfC} \bullet \frac{1}{PEF}\right)$	S11
	Remediation Objectives for Noncarcinogenic Contaminants - Construction Worker (mg/kg)	$THQ \bullet AT \bullet 365 \frac{d}{yr}$ $EF \bullet ED \bullet \left(\frac{1}{RfC} \bullet \frac{1}{PEF'}\right)$	S12
	Remediation Objectives for Carcinogenic Contaminants - Residential, Industrial/ Commercial (mg/kg)	$TR \bullet AT_{C} \bullet 365 \frac{d}{yr}$ $URF \bullet 1,000 \frac{ug}{mg} \bullet EF \bullet ED \bullet \frac{1}{PEF}$	S13

POLLUTION CONTROL BOARD

		OF FROFOSED AM	I	I
S14	S15	S16	S17	S18
$TR \bullet AT_{c} \bullet 365 \frac{d}{yr}$ $URF \bullet 1,000 \frac{ug}{mg} \bullet EF \bullet ED \bullet \frac{1}{PEF^{1}}$	$PEF = \frac{Q}{C} \bullet \frac{3,600 \frac{S}{hr}}{0.036 \bullet (1 - V) \bullet \left(\frac{U_m}{U_t}\right)^3} \bullet F(x)$	$PEF^{1} = \frac{PEF}{10}$ NOTE: PEF must be the industrial/commercial value	$C_{w} \bullet \left[K_{d} + \frac{(\theta_{w} + \theta_{a} \bullet H')}{\rho_{b}} \right]$ NOTE: This equation can only be used to model contaminant migration not in the water bearing unit.	$C_{w} = DF \bullet GW_{obj}$
Remediation Objectives for Carcinogenic Contaminants - Construction Worker (mg/kg)	Equation for Derivation of Particulate Emission Factor, PEF (m ³ /kg)	Equation for Derivation of Particulate Emission Factor, PEF' - Construction Worker (m ³ /kg)	Remediation Objective (mg/kg)	Target Soil Leachate Concentration, C _w (mg/L)
			Equations for the Soil Component of the Groundwater Ingestion Exposure Route	

POLLUTION CONTROL BOARD


$K_{d} = K_{oc} \bullet f_{oc}$ $\theta_{w} = \eta \bullet \left(\frac{I}{K_{s}}\right)^{1/(2b+3)}$ $\theta_{w} = \eta - \theta_{w}$ $\theta_{a} = \eta - \theta_{w}$ $DF = 1 + \frac{K \bullet i \bullet d}{I \bullet L}$ $DF = 1 + \frac{K \bullet i \bullet d}{I \bullet L}$ $TR \bullet BW \bullet AT_{c} \bullet 36S \frac{d}{yT}$ $TR \bullet BW \bullet AT_{c} \bullet 36S \frac{d}{yT}$ $\frac{TR \bullet BW \bullet AT_{c} \bullet 36S \frac{d}{yT}}{SF_{o} \bullet IR_{w} \bullet EF \bullet ED}$ $\eta = 1 - \frac{\rho_{b}}{\rho_{s}}$ $d = (0.0112 \bullet L^{2})^{0.5} + d_{a} \left[1 - \exp\left(\frac{(-L \bullet I)}{K \bullet i \bullet d_{a}}\right)\right]$	S19	S20	S21	S22	S23	S24	S25
	$K_d = K_{oc} \bullet f_{oc}$	$ heta_w = \eta ullet \left(rac{I}{K_s} ight)^{1/(2b+3)}$	$\theta_a = \eta - \theta_W$	$DF = 1 + \frac{K \bullet i \bullet d}{I \bullet L}$	$TR \bullet BW \bullet AT_c \bullet 365 \frac{d}{yr}$ $SF_o \bullet IR_w \bullet EF \bullet ED$	$\eta = 1 - \frac{\rho_b}{\rho_s}$	$d = (0.0112 \bullet L^2)^{0.5} + d_a \left[1 - \exp \frac{(-L \bullet I)}{(K \bullet i \bullet d_a)} \right]$
Soil-Water Partition Coefficient, K _d (cm ³ /g) Water-Filled Soil Porosity, θ _w (L _{water} /L _{soil}) Air-Filled Soil Porosity, θ _a (L _{uir} /L _{soil}) DF (unitless) DF (unitless) DF (unitless) DF (unitless) Contaminants, GW ^{obj} (mg/L) Total Soil Porosity, η (L _{pore} /L _{soil}) Equation for Estimation of Mixing Zone	Soil-Water Partition Coefficient, K _d (cm ³ /g)	Water-Filled Soil Porosity, θ_w (L _{water} /L _{soil})	Air-Filled Soil Porosity, θ _a (L _{air} /L _{soil})	Dilution Factor, DF (unitless)	Groundwater Remediation Objective for Carcinogenic Contaminants, GW ^{obj} (mg/L)	Total Soil Porosity, η (L _{pore} /L _{soil})	Equation for Estimation of Mixing Zone Depth, d (m)

S26 S28 S29 S27 NOTE: This equation may be used when vertical thickness is known or NOTE: This equation may be used when vertical thickness of $C_{sat} = \frac{S}{\rho_b} \bullet \Big[\Big(K_d \bullet \rho_b \Big) + \theta_w + \Big(H' \bullet \theta_a \Big) \Big]$ $\rho_b \bullet d_s \bullet 10^6 \frac{\operatorname{cm}^3}{}$ $T_{M-L} \bullet \left(3.15 \bullet 10^7 \right)^{-S}$ contamination is known or can be estimated reliably. 71 $(C_W \bullet I_{M-L} \bullet ED_{M-L})$ $VF_{M-L} = \frac{VF_{M-L}}{}$ $\rho_b \bullet d_s$ $VF_{M-L} = Q_{\bullet}L$ \mathcal{O} can be estimated reliably. Commercial, VF **Exposure Route Exposure Route** Soil Component **Exposure Route** - Construction Volatilization Worker, VF' -Volatilization Factor for the Equation for Derivation of the Soil Saturation Limit, C_{sat} - Residential, Objective for Remediation Groundwater Mass-Limit Mass-Limit Mass-Limit Inhalation Industrial/ Inhalation Factor for Ingestion (mg/kg) (m³/kg) (m^{3}/kg) of the Component of Equations for Groundwater Mass-Limit Inhalation Route and Exposure Ingestion Exposure Route Soil the

POLLUTION CONTROL BOARD

ILLINOIS REGISTER

POLLUTION CONTROL BOARD



Symbol	Parameter	Units	Source	Parameter Value(s)
АТ	Averaging Time for Noncarcinogens in Ingestion Equation	yr		Residential = 6 Industrial/Commercial = 25 Construction Worker = 0.115
АТ	Averaging Time for Noncarcinogens in Inhalation Equation	yr		Residential = 30 Industrial/Commercial = 25 Construction Worker = 0.115
AT _c	Averaging Time for Carcinogens	уг	SSL	70
BW	Body Weight	kg		Residential = 15, noncarcinogens 70, carcinogens Industrial/Commercial = 70 Construction Worker = 70
Csat	Soil Saturation Concentration	mg/kg	Appendix A, Table A or Equation S29 in Appendix C, Table A	Chemical-Specific or Calculated Value
s v	Target Soil Leachate Concentration	mg/L	Equation S18 in Appendix C, Table A	Groundwater Standard, Health Advisory concentration, or Calculated Value

NOTICE OF PROPOSED AMENDMENTS

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

Section 742. Table B: SSL Parameters

			NOT	TICE OF I	PROPC	SED A	MENI	MENT	<u>S</u>	
Parameter Value(s)	2 m or Calculated Value	Site-Specific	Site-Specific		Calculated Value	Chemical-Specific	Chemical-Specific	20 or Calculated Value	Industrial/Commercial = 25 Construction Worker = 1	Residential = 30 Industrial/Commercial = 25 Construction Worker = 1
Source	SSL or Equation S25 in Appendix C, Table A	Field Measurement	Field Measurement or Estimation		Equation S10 in Appendix C, Table A	Appendix C, Table E	Appendix C, Table E	Equation S22 in Appendix C, Table A		
Units	m	m	H		cm^2/s	cm^2/s	cm^2/s	unitless	yr	yr
Parameter	Mixing Zone Depth	Aquifer Thickness	Depth of Source	(Vertical thickness of contamination)	Apparent Diffusivity	Diffusivity in Air	Diffusivity in Water	Dilution Factor	Exposure Duration for Ingestion of Carcinogens	Exposure Duration for Inhalation of Carcinogens
Symbol	đ	$d_{\rm a}$	ds		D_A	Di	D_{w}	DF	ED	ED

POLLUTION CONTROL BOARD

				POSED AMENDN			
Parameter Value(s)	Residential = 6 Industrial/Commercial = 25 Construction Worker = 1	Residential = 30 Industrial/Commercial = 25 Construction Worker = 1	Residential = 30 Industrial/Commercial = 25 Construction Worker = 1	70	Residential = 350 Industrial/Commercial = 250 Construction Worker = 30	0.194	Surface Soil = 0.006 Subsurface soil = 0.002, or Site-Specific
Source				SSL		SSL	SSL or Field Measurement (See Appendix C, Table F)
Units	ут	уг	ут	yr	d/yr	unitless	g/g
Parameter	Exposure Duration for Ingestion of Noncarcinogens	Exposure Duration for Inhalation of Noncarcinogens	Exposure Duration for the Direct Ingestion of Groundwater	Exposure Duration for Migration to Groundwater Mass-Limit Equation S28	Exposure Frequency	Function dependent on U _m /U _t	Organic Carbon Content of Soil
Symbol	ED	ED	ED	ED _{M-L}	EF	F(x)	foc

NOTICE OF PROPOSED AMENDMENTS

POLLUTION CONTROL BOARD

[[NOTICE	OF PR	OPOSED AME	NDMENTS		
Parameter Value(s)	Chemical-Specific or Calculated	Chemical-Specific	Site-Specific	0.3	0.18	114	Residential = 200 Industrial/Commercial = 50 Construction Worker = 480	Residential = 2 Industrial/Commercial = 1
Source	Appendix B, Table E, 35 IAC 620.Subpart F, or Equation S23 in Appendix C, Table A	Appendix C, Table E	Field Measurement (See Appendix C, Table F)	TSS	TSS	SSL		
Units	mg/L	unitless	m/m	m/yr	m/yr	(mg-yr)/(kg-d)	mg/d	L/d
Parameter	Groundwater Remediation Remediation Objective	Henry's Law Constant	Hydraulic Gradient	Infiltration Rate	Infiltration Rate for Migration to Groundwater Mass-Limit Equation S28	Age Adjusted Soil Ingestion Factor for Carcinogens	Soil Ingestion Rate	Daily Water Ingestion Rate
Symbol	GW _{obj}	H'	i	I	Im-L	IF _{soil-adj} (residential)	IR _{soil}	IRw

POLLUTION CONTROL BOARD

		NOTICE (OF PROPO	DSED AM	IENDMEN	NTS	
Site-Specific	Calculated Value	Chemical and pH-Specific (see Appendix C, Table I)	Chemical and pH-Specific	Chemical-Specific	Site-Specific	Site-Specific	Residential = $1.32 \bullet 10^9$ or Site- Specific Industrial/Commercial = $1.24 \bullet 10^9$ or Site-Specific
Field Measurement (See Appendix C, Table F)	Equation S19 in Appendix C, Table A	Equation S19 in Appendix C, Table A	Appendix C, Table J	Appendix C, Table E or Appendix C, Table I	Appendix C, Table K Appendix C, Illustration C	Field Measurement	SSL or Equation S15 in Appendix C, Table A
m/yr	cm³/g or L/kg	cm3/g or L/kg	cm3/g or L/kg	cm³/g or L/kg	m/yr	ш	m³/kg
Aquifer Hydraulic Conductivity	Soil-Water Partition Coefficient	Soil-Water Partition Coefficient	Soil-Water Partition Coefficient	Organic Carbon Partition Coefficient	Saturated Hydraulic Conductivity	Source Length Parallel to Groundwater Flow	Particulate Emission Factor
K	K _d (Non- ionizing organics)	K _d (Ionizing organics)	K _d (Inorganics)	${ m K}_{ m oc}$	Ks	L	PEF

POLLUTION CONTROL BOARD

(Note: for Construction Workers use subchronic reference concentrations) Note: for Construction Worker use Industrial/Commercial = 85.81 Industrial/Commercial = 85.81 Construction Worker = 85.81Construction Worker = 85.81subchronic reference doses) 1.24 • 10⁸ or Site-Specific Toxicological-Specific Toxicological-Specific Residential = 68.81Residential = 90.80Calculated value industrial/commercial) http://www.epa.state.il. http://www.epa.state.il. IEPA (IRIS/HEAST^a) EPA (IRIS/HEAST^a) Appendix C, Table H Appendix C, Table A Appendix C, Table A us/land/taco/toxicityus/land/taco/toxicity-SSL or Appendix C, Equation S30 in Equation S16 in Illinois EPA: Illinois EPA: using PEF values.xls values.xls **Table H** $(g/m^2-s)/(kg/m^3)$ $(g/m^2-s)/(kg/m^3)$ mg/(kg-d) mg/m³ m³/kg mg/kg concentration at concentration at Oral Reference Factor adjusted the center of a the center of a Inverse of the Concentration Inverse of the square source square source for Agitation (construction remediation Particulate Inhalation Reference Emission objective worker) mean mean Dose Soil (used in VF equations) equations) (used in RO_{soil} PEF RfD。 PEF' Q/C Q/C RfC

NOTICE OF PROPOSED AMENDMENTS

POLLUTION CONTROL BOARD

				POSED AMENDM			
Calculated value	Chemical-Specific	Toxicological-Specific	Residential = $9.5 \bullet 10^8$ Industrial/Commercial = $7.9 \bullet 10^8$ Construction Worker = $3.6 \bullet 10^6$	30	1	Residential = 10^{-6} at the point of human exposure Industrial/Commercial = 10^{-6} at the point of human exposure Construction Worker = 10^{-6} at the point of human exposure	4.69
Equation S30 in Appendix C, Table A	Appendix C, Table E	HEPA (IRIS/HEAST ^a) Illinois EPA: http://www.epa.state.il. us/land/taco/toxicity- values.xls		SSL	TSS		TSS
mg/m³	mg/L	(mg/kg-d) ⁻¹	S	yr	unitless	unitless	s/m
Soil gas remediation objective	Solubility in Water	Oral Slope Factor	Exposure Interval	Exposure Interval for Mass-Limit Volatilization Factor Equation S26	Target Hazard Quotient	Target Cancer Risk	Mean Annual Windspeed
RO _{soil gas}	S	SFo	Т	Тм-г	ТНQ	TR	U _m

NOTICE OF PROPOSED AMENDMENTS

POLLUTION CONTROL BOARD

	NOTI	CE OF PR	OPOSI	ED AMEN	IDMENT:	8
Toxicological-Specific	11.32	0.5 or Site-Specific	Calculated Value	Calculated Value	Calculated Value	Calculated Value
HEPA (IRIS/HEAST ^a) Illinois EPA: http://www.epa.state.il. us/land/taco/toxicity- values.xls	SSL	SSL or Field Measurement	Equation S8 in Appendix C, Table A	Equation S9 in Appendix C, Table A	Equation S26 in Appendix C, Table A	Equation S27 in Appendix C, Table A
(ug/m ³) ⁻¹	III/S	unitless	m³/kg	m ³ /kg	m³/kg	m³/kg
Inhalation Unit Risk Factor	Equivalent Threshold Value of Windspeed at 7 m	Fraction of Vegetative Cover	Volatilization Factor	Volatilization Factor adjusted for Agitation	Mass-Limit Volatilization Factor	Mass-Limit Volatilization Factor adjusted for Agitation
URF	'n	V	VF	VF′	VF _{M-L}	VF' _{M-L}

POLLUTION CONTROL BOARD

			NOTICE C	OF PROPOSEI	D Al	MENDMEN	NTS	
0.43, or	Gravel = 0.25 Sand = 0.32 Silt = 0.40 Clay = 0.36 , or	Calculated Value	Surface Soil (top 1 meter) = 0.28 Subsurface Soil (below 1 meter) = 0.13, or	Gravel = 0.05 Sand = 0.14 Silt - 0.24 Clay = 0.19, or	Calculated Value	Surface Soil (top 1 meter) = 0.15 Subsurface Soil (below 1 meter) = 0.30, or	Gravel = 0.20 Sand = 0.18 Silt = 0.16 Clay = 0.17, or	Calculated Value
SSL or Fauation S24 in	Appendix C, Table A		SSL or Equation S21 in Appendix C, Table A			SSL or Equation S20 in Appendix C, Table A		
Lpore/Lsoil			Lair/Lsoil			Lwater/Lsoil		
Total Soil Porosity			Air-Filled Soil Porosity			Water-Filled Soil Porosity		
u			θ_{a}			θ		

POLLUTION CONTROL BOARD

	NOTICE	OF	PROPOSEI
1.5, or Gravel = 2.0 Sand = 1.8 Silt = 1.6 Clay = 1.7, or Site-Specific	2.65, or Site-Specific	1	Site-Specific
SSL or Field Measurement (See Appendix C, Table F)	SSL or Field Measurement (See Appendix C, Table F)	TSS	Appendix C, Table K Appendix C, Illustration C
kg/L or g/cm ³	g/cm ³	g/cm ³	unitless
Dry Soil Bulk Density	Soil Particle Density	Water Density	Exponential in Equation S20
ę	Ъs	ρ	1/(2b+3)

AMENDMENTS HEAST - Health Effects Assessment Summary Tables. USEPA, Office of Solid Waste and Emergency Response. EPA/SQO/R 95/036. Updated Quarterly.

effective (Source: Amended at 36 Ill. Reg.

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S)	Diffusivity in Air (Di) (cm ² /s)	Diffusivity in Water (Dw)	Dimensionless Henry's Law Constant (H') (25°C)	Organic Carbon Partition Coefficient	Firrst Order Degradation Constant
		(mg/L)		(em ² /s)		(K _{oe}) (L/kg)	(∖,) (d ⁻¹)
Neutral Organics							
<u>83 32 9</u>	Acenaphthene	4.24	0.0421	7.69E-6	0.00636	7,080	<u>0.0034</u>
67-64-1	Acetone	1,000,000	0.124	1.14E-5	0.00159	0.575	0.0495
15972-60- 8	Alachlor	242	0.0198	5.69E-6	0.00000132	394	No Data
116 06 3	Aldicarb	6,000	0.0305	7.19E-6	0.000000574	<u>12</u>	<u>0.00109</u>
<u>309-00-2</u>	Aldrin	0.18	0.0132	4.86E-6	0.00697	2,450,000	0.00059
120-12-7	Anthracene	0.0434	0.0324	7.74E-6	0.00267	29,5 00	0.00075
1912 24 9	Atrazine	02	0.0258	6.69E-6	0.0000005	4 51	No Data
71 43 2	Benzene	1,750	0.088	<u>9.80E-6</u>	0.228	58.9	0.0009

NOTICE OF PROPOSED AMENDMENTS

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

Section 742.APPENDIX C: Tier 2 Illustrations and Tables

Section 742. Table E: Default Physical and Chemical Parameters^e

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (cm ² /s)	Diffusivity in Water (Dw) (em ² /s)	Dimensionless Henry's Law Constant (H) (25°C)	Organie Carbon Partition Coefficient (Kee) (L/kg)	First Order Degradation Constant (λ) (d^{+})
56-55-3	Benzo(a)anthracene	0.0094	0.0510	<u>9.00E-6</u>	0.000137	398,000	0.00051
205 99 2	Benzo(b)fluoranthene	0.0015	0.0226	5.56E-6	0.00455	1,230,000	0.00057
<u>207 08 9</u>	Benzo(k)fluoranthene	0.0008	0.0226	5.56E-6	0.000034	1,230,000	0.00016
65 85 0	Benzoic Acid	3,5 00	0.0536	7.97E-6	<u>0.0000631</u>	0.600	No Data
50 32 8	Benzo(a)pyrene	0.00162	0.043	<u>9.00E-6</u>	0.0000463	<u>1,020,000</u>	0.00065
111-44-4	Bis(2 chloroethyl)ether	17,200	0.0692	7 .53E-6	0.000738	15.5	0.0019
117-81-7	Bis(2- ethylhexyl)phthalate	0.3 4	<u>0.0351</u>	3.66E-6	0.00000418	15,100,000	0.0018
75 27 4	Bromodichloromethane	6,740	0.0298	1.06E-5	<u>0.0656</u>	55.0	No Data
75 25 2	Bromoform	3,100	0.0149	1.03E-5	0.0219	87.1	0.0019
71 36 3	Butanol	74,000	0.0800	<u>9.30E-6</u>	0.000361	6.92	0.01283
85 68 7	Butyl Benzyl Phthalate	<u>2.69</u>	0.0174	4.83E-6	0.0000517	57,500	0.00385
86-74-8	Carbazole	7.48	0.0390	7.03E-6	0.00000626	3,3 90	No Data

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (cm ² /s)	Diffusivity in Water (D _w) (cm ² /s)	Dimensionless Henry's Law Constant (H') (25°C)	Organic Carbon Partition Coefficient (Koe)	First Order Degradation Constant (A)
1563-66-2	Carbofuran	320	0.0249	6.63E-6	<u>.00377</u>	37	No Data
75-15-0	Carbon Disulfide	1,190	0.104	1.00E-5	1.24	45.7	No Data
56-23-5	Carbon Tetrachloride	793	0.0780	8.80E-6	1.25	174	0.0019
57-74-9	Chlordane	0.056	0.0118	4.37E-6	0.00199	<u>120,000</u>	0.00025
106-47-8	p Chloroaniline	5,3 00	0.0483	1.01E-5	0.0000136	66.1	No Data
108-90-7	Chlorobenzene	472	0.0730	<u>8.70E-6</u>	0.152	219	0.0023
124 48 1	Chlorodibromomethane	2,600	0.0196	1.05E-5	<u>0.0321</u>	63.1	0.00385
67-66-3	<u>Chloroform</u>	7,920	0.104	1.00E-5	0.15	39.8	0.00039
95-57-8	2 Chlorophenol	22,000	0.0501	<u>9.46E-6</u>	0.016	388	No Data
218-01-9	Chrysene	0.0016	0.0248	6.21E-6	0.00388	398,000	0.00035
<u>94-75-7</u>	2,4 D	680	0.0231	7.31E-6	0.00000041	4 51	0.00385
72 54 8	4,4' DDD	0.09	0.0169	4.76E-6	0.000164	1,000,000	0.000062

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (em ² /s)	Diffusivity in Water (Dw) (em ² /s)	Dimensionless Henry's Law Constant (H ⁻) (25°C)	Organic Carbon Partition Coefficient (Kee) (L/kg)	First Order Degradation Constant (\)
72 55 9	4,4'-DDE	0.12	0.0144	5.87E-6	0.000861	4,470,000	0.000062
50 29 3	4,4'-DDT	0.025	0.0137	4. 95E-6	0.000332	2,630,000	0.000062
75-99-0	Dalapon	900,000	0.0414	<u>9.46E-6</u>	0.0000264	5.8	0.005775
53-70-3	Dibenzo(a,h)anthracene	0.00249	0.0202	5.18E-6	0.00000603	3,800,000	0.00037
96 12 8	1,2 Dibromo 3- ehloropropane	1,2 00	0.0212	7.02E-6	0.00615	<u>182</u>	0.001925
106-93-4	1,2 Dibromoethane	4,200	0.0287	<u>8.06E-6</u>	0.0303	93	0.005775
84-74-2	Di n butyl Phthalate	11.2	0.0438	7.86E-6	0.000000385	33,900	0.03013
95-50-1	1,2 Dichlorobenzene	156	0.0690	7.90E-6	0.0779	617	0.0019
106-46-7	1,4 Dichlorobenzene	73.8	0.0690	7.90E-6	0.0996	617	0.0019
91-94-1	3,3-Dichlorobenzidine	3.11	0.0194	6.74E-6	0.00000164	724	0.0019

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (cm ² /s)	Diffusivity in Water (Dw) (cm ² /s)	Dimensionless Henry's Law Constant (H ¹) (25°C)	Organie Carbon Partition Coefficient (K) (L/kg)	Firrst Order Degradation Constant (λ) (d^{-1})
75 34 3	1,1-Dichloroethane	5,060	0.0742	1.05E-5	0.23	31.6	0.0019
<u>107-06-2</u>	1,2 Dichloroethane	8 ,5 20	0.104	<u>9.90E-6</u>	<u>0.0401</u>	17.4	0.0019
75-35-4	1,1 Dichloroethylene	2,250	0060.0	1.04E-5	1.07	58.9	0.0053
156-59-2	Cis 1,2 Dichloroethylene	3,500	0.0736	1.13E-5	0.167	35.5	0.00024
156 60 5	Trans 1,2- Dichloroethylene	6,300	0.0707	<u>1.19E-5</u>	0.385	52.5	0.00024
120 83 2	2,4-Dichlorophenol	4,500	0.0346	<u>8.77E-6</u>	0.00013	147	0.00027
78 87 5	1,2-Dichloropropane	2,800	0.0782	<u>8.73E 6</u>	0.115	43.7	0.00027
542-75-6	1,3-Dichloropropylene (cis + trans)	2,800	0.0626	1.00E-5	0.726	4 5.7	0.061
60-57-1	Dieldrin	0.195	0.0125	4.74E 6	0.000619	21,400	0.00032
84 66 2	Diethyl Phthalate	1,080	0.0256	<u>6.35E-6</u>	0.0000185	288	0.00619
105-67-9	2,4 Dimethylphenol	7,870	0.0584	<u>8.69E-6</u>	0.000082	209	0.0495
51 28 5	2,4 Dinitrophenol	2,790	0.0273	<u>9.06E-6</u>	0.0000182	0.01	0.00132

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (em ² /s)	Diffusivity in Water (Dw) (em ² /s)	Dimensionless Henry's Law Constant (H') (25°C)	Organie Carbon Partition Coefficient (K) (L/kg)	First Order Degradation Constant (λ) (d^{+})
121-14-2	2,4 Dinitrotoluene	270	<u>0.203</u>	7.06E-6	0.000038	95.5	0.00192
606 20 2	2,6 Dinitrotoluene	<u>182</u>	0.0327	7.26E-6	0.0000306	69.2	0.00192
88 85 7	Dinoseb	52	0.0215	6.62E-6	0.0000189	<u>1,120</u>	0.002817
117-84-0	Di n octyl Phthalate	0.02	0.0151	3.58E-6	0.00274	83,200,000	0.0019
115 29 7	Endosulfan	<u>0.51</u>	0.0115	4 .55E-6	0.000459	2,140	0.07629
145 73 3	Endothall	21,000	0.0291	<u>8.07E-6</u>	0.000000107	<u>0.29</u>	No Data
72-20-8	Endrin	0.25	0.0125	4.74E-6	0.000308	12,300	0.00032
100-41-4	Ethylbenzene	169	0.0750	7.80E-6	0.323	363	0.003
206 44 0	Fluoranthene	0.206	0.0302	6.35E-6	0.00066	107,000	0.00019
<u>86 73 7</u>	Fluorene	1.98	0.0363	7.88E-6	<u>0.00261</u>	13,800	0.000691
76-44-8	Heptachlor	0.18	0.0112	5.69E-6	60.7	1,410,000	0.13
1024-57-3	Heptachlor epoxide	0.2	0.0132	4.23E-6	0.00039	83,200	0.00063

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (em ² /6)	Diffusivity in Water (Dw) (em ² /s)	Dimensionless Henry's Law Constant (H') (25°C)	Organic Carbon Partition Coefficient (K _{ee}) (L/kg)	First Order Degradation Constant (A) (d ⁺)
118-74-1	<u>Hexachlorobenzene</u>	6.2	0.0542	5.91E-6	0.0541	55,000	0.00017
319 84 6	Alpha HCH (alpha- BHC)	2.0	0.0142	7.34E-6	0.000435	1,2 30	0.0025
58 89 9	Gamma-HCH (Lindane)	6.8	0.0142	7.34E-6	0.000574	1,070	0.0029
77-47-4	H exachlorocyclo- P entadiene	1.8	<u>0.0161</u>	7.21E-6	1.11	200,000	<u>0.012</u>
67-72-1	Hexachloroethane	50	0.0025	<u>6.80E-6</u>	0.159	1,780	0.00192
<u>193 39 5</u>	Indeno(1,2,3 c,d)pyrene	0.000022	0.0190	5.66E-6	0.0000656	3,470,000	0.00047
78-59-1	Isophorone	12,000	0.0623	6.76E-6	0.000272	46.8	0.01238
7439-97-6	Mercury		0.0307	6.30E-6	0.467		No Data
72 43 5	Methoxychlor	<u>0.045</u>	0.0156	4.46E-6	0.000648	<u>97,700</u>	0.0019
74 83 9	Methyl Bromide	15,200	0.0728	1.21E-5	0.256	10.5	0.01824
<u>1634 04 4</u>	Methyl tertiary butyl ether	51,000	0.102	1.10E-5	0.0241	11.5	No Data
75-09-2	Methylene Chloride	13,000	0.101	1.17E-5	0.0898	11.7	0.012

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (em ² /9)	Diffusivity in Water (D*) (em ² /s)	Dimensionless Henry's Law Constant (H') (25°C)	Organic Carbon Partition (K _{oe}) (L/kg)	Firrst Order Degradation Constant (A) (d ⁺)
95 48 7	<u>2-Methylphenol (o-</u> eresol)	26,000	0.0740	<u>8.30E-6</u>	0.0000492	91.2	0.0495
<u>91-20-3</u>	Naphthalene	31.0	0.0590	7.50E-6	0.0198	2,000	0.0027
<u>98 95 3</u>	Nitrobenzene	2,090	0.0760	<u>8.60E-6</u>	0.000984	64.6	<u>0.00176</u>
86-30-6	N- Nitrosodiphenylamine	35.1	0.0312	6.35E-6	0.000205	1,2 90	0.01
<u>621 64 7</u>	N Nitrosodi n- propylamine	0,890	0.0545	<u>8.17E-6</u>	0.0000923	24.0	0.0019
87 86 5	Pentachlorophenol	1,950	0.0560	<u>6.10E-6</u>	0.000001	5 92	0.00045
108 95 2	Phenol	82,800	0.0820	9.10E-6	0.0000163	<u>28.8</u>	660:0
<u>1918-02-1</u>	Picloram	430	0.0255	5.28E 6	0.000000016 6	1.98	No Data
<u>1336 36 3</u>	Polychlorinated biphenyls (PCBs)	0.7	53 	69	G5 	309,000	No Data
<u>129-00-0</u>	Pyrene	0.135	0.0272	7.24E-6	0.000451	<u>105,000</u>	0.00018
122 34 9	Simazine	£	0.027	7.36E-6	0.0000000133	133	No Data
100-42-5	Styrene	310	0.0710	8.00E-6	0.113	<i>3</i> 76	0.0033

POLLUTION CONTROL BOARD

CAS No.	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (em ² /s)	Diffusivity in Water (Dw) (em ² /s)	Dimensionless Henry's Law Constant (H ⁻) (25°C)	Organie Carbon Partition Coefficient (K) (L/kg)	First Order Degradation Constant (A) (d ⁻¹)
93-72-1	2,4,5 TP (Silvex)	31	0.0194	5.83E-6	0.000000032	5,440	No Data
127-18-4	Tetrachloroethylene	2 00	0.0720	8.20E-6	0.754	155	0.00096
108 88 3	Toluene	<u>526</u>	0.0870	<u>8.60E-6</u>	0.272	182	0.011
8001 35 2	Toxaphene	0.74	0.0116	4.34E-6	0.000246	257,000	No Data
120 82 1	1,2,4 Trichlorobenzene	300	0.0300	<u>8.23E-6</u>	0.0582	1,780	0.0019
71-55-6	1,1,1 Trichloroethane	1,330	0.0780	8.80E-6	0.705	110	0.0013
79-00-5	1,1,2 Trichloroethane	4,420	0.0780	8.80E-6	0.0374	50.1	0.00095
79-01-6	Trichloroethylene	1,100	0.0790	<u>9.10E-6</u>	0.422	166	0.00042
<u>95 95 4</u>	2,4,5 Trichlorophenol	1,200	0.0291	7.03E-6	0.000178	1,600	0.00038
<u>88 06 2</u>	2,4,6 Trichlorophenol	800	0.0318	6.25E-6	0.000319	381	0.00038
108 05 4	Vinyl Acetate	20,000	0.0850	<u>9.20E-6</u>	<u>0.021</u>	5.25	No Data
57-01-4	Vinyl Chloride	2,760	0.106	1.23E-6	1.11	<u>18.6</u>	0.00024
108 38 3	m Xylene	161	0.070	7.80E-6	0.301	407	0.0019

	N	OTIC	CE OI
First Order Degradation Constant (Å) (d ⁻¹)	<u>0.0019</u>	<u>0.0019</u>	0.0019
Organie Carbon Partition Coefficient (LAg)	363	380	260
Dimensionless Henry's Law Constant (H') (25°C)	0.213	0.31 4	0.25
Diffusivity in Water (D _w) (cm ² /s)	1.00E-5	<u>8.44E-6</u>	<u>9.34E 6</u>
Diffusivity in Air (Di) (em ² /s)	0.087	0.0769	0.0720
Solubility in Water (S) (mg/L)	178	185	<u>186</u>
Chemical	e Xylene	p Xylene	1330-20-7 Xylenes (total)
CAS No.	95-47-6 o-Xylene	106 42 3 p Xylene	1330-20-7

Chemical Abstracts Service (CAS) registry number. This number in the format xxx xx x, is unique for each chemical and allows efficient searching on computerized data bases.

^{a-Soil} Remediation objectives are determined pursuant to 40 CFR 761, as incorporated by reference at Section 732.104 (the USEPA "PCB Spill Cleanup Policy"), for most sites;

persons remediating sites should consult with BOL if calculation of Tier 2 soil remediation objectives is desired.

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

PROPOSED AMENDMENTS

POLLUTION CONTROL BOARD

6.30E+03 3.40E-03 6.30E+03 3.40E-03 7.80E-01 4.95E-02 7.80E-01 4.95E-02 3.20E+03 No Data 1.29E+01 1.09E-03 2.50E+05 5.90E-04 2.50E+04 7.50E-04 3.63E+02 No Data 3.60E+04 7.50E-04 3.63E+02 No Data 3.63E+02 5.90E-04 1.09E+04 7.50E-04 1.05E+04 9.00E-04 1.05E+06 5.70E-04 1.05E+06 5.70E-04 1.00E+06 1.60E-04 1.00E+06 1.60E-04 1.012E+00 ^d No Data	 <u>Chemical</u>	<u>Solubility</u> in Water (S) (mg/L)	Diffusivity in Air (Di) (cm ² /s)	Diffusivity in Water (<u>C</u> ^w) (cm ² /s)	Dimensionless Henry's Law Constant (H') (25°C)	Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route	Organic Carbon Coefficient (K _{so}) (L/kg)	$\frac{First}{Order}$ $\frac{Order}{Degradation}$ $\frac{(\lambda)}{(d^{-1})}$	<u>Vapor</u> <u>Pressure</u> (mm/Hg)
amphtheme 3.60 ± -00 4.76 ± -02 7.69 ± -06 5.60 ± -03 $\ldots-1^{\circ}$ $6.30\pm+03$ 3.40 ± -03 tome $1.00\pm+06$ 1.24 ± -01 1.14 ± -05 1.60 ± -03 9.73 ± -04 2.80 ± -01 4.95 ± -02 thome $2.40\pm+02$ 2.13 ± 02 5.28 ± -06 3.40 ± -06 3.40 ± -06 $3.20\pm+03$ 4.95 ± -02 thome $2.40\pm+02$ 2.13 ± 02 5.28 ± -06 3.40 ± -06 3.40 ± -06 $3.20\pm+03$ $2.00\pm+03$ thome $2.40\pm+02$ 2.13 ± 02 2.24 ± -06 5.90 ± -08 $\ldots-1^{\circ}$ $2.50\pm+04$ 1.09 ± -03 thome 1.70 ± -02 1.96 ± -02 4.86 ± -06 2.00 ± -03 $\ldots-1^{\circ}$ $2.50\pm+04$ 2.90 ± -04 the 1.70 ± -02 2.95 ± -02 2.40 ± -02 2.00 ± -03 $\ldots-1^{\circ}$ $2.50\pm+04$ 2.50 ± -04 the 1.70 ± -02 2.95 ± -02 2.70 ± -03 $\ldots-1^{\circ}$ $2.50\pm+04$ 2.50 ± -04 the 2.00 ± -03 2.00 ± -03 $\ldots-1^{\circ}$ $2.50\pm+04$ 2.50 ± -04 the 2.00 ± -03 2.00 ± -03 2.00 ± -03 2.00 ± -04 $2.50\pm+04$ the 2.00 ± -03 2.00 ± -03 2.00 ± -03 2.00 ± -04 $2.50\pm+04$ the 2.00 ± -03 2.00 ± -03 2.00 ± -03 2.00 ± -04 $2.50\pm+04$ the 2.00 ± -04 2.50 ± -04 2.50 ± -04 2.50 ± -04 the 2.00 ± -04 2.20 ± -03 2.00 ± -04 2.00 ± -04 the 2.00 ± -03 2.00 ± -03 2.00 ± -04 2.00 ± -04 the 2.00 ± -04 2.20 ± -02 $2.0\pm$									
tone $1.00\pm+06$ 1.24 ± 0.1 1.14 ± -05 1.60 ± -03 2.73 ± 0.4 2.80 ± -01 4.95 ± -02 thot $2.40\pm+02$ 2.13 ± 0.2 5.28 ± 0.6 3.40 ± 0.6 3.40 ± 0.6 $3.20\pm+0.1$ 4.95 ± -0.2 thot $2.40\pm+02$ 2.13 ± 0.2 5.28 ± 0.6 $3.20\pm+0.1$ 2.90 ± -0.1 1.09 ± -0.3 thut 1.70 ± -02 1.96 ± 0.2 4.86 ± 0.6 5.90 ± 0.6 3.00 ± -0.7 2.90 ± -0.1 1.09 ± -0.3 thut 1.70 ± 0.2 2.35 ± 0.2 7.24 ± 0.6 5.00 ± 0.7 2.90 ± -0.7 2.90 ± -0.7 2.90 ± -0.7 thut 1.70 ± 0.2 2.35 ± 0.2 7.74 ± 0.6 2.70 ± -0.3 $2.50\pm+0.7$ 2.90 ± -0.7 thut 1.70 ± 0.2 2.35 ± 0.2 2.74 ± 0.6 2.70 ± -0.7 $2.50\pm+0.7$ 2.90 ± -0.7 thut 1.70 ± 0.2 2.35 ± 0.2 2.74 ± 0.6 2.70 ± -0.7 $2.50\pm+0.7$ 2.90 ± -0.7 thut 1.70 ± 0.2 2.35 ± 0.2 2.74 ± 0.6 2.70 ± -0.7 $2.50\pm+0.7$ 2.90 ± -0.7 thut $2.00\pm+0.7$ 2.55 ± 0.2 2.70 ± -0.7 $2.50\pm+0.7$ 2.00 ± -0.7 thut $2.00\pm+0.7$ 2.50 ± -0.7 $2.50\pm+0.7$ 2.00 ± -0.7 2.00 ± -0.7 thut $2.00\pm+0.7$ 2.50 ± -0.7 2.50 ± -0.7 2.50 ± -0.7 2.50 ± -0.7 2.50 ± -0.7 thut 2.00 ± -0.7 2.23 ± -0.7 2.00 ± -0.7 2.00 ± -0.7 2.00 ± -0.7 2.00 ± -0.7 thut 2.00 ± -0.7 2.23 ± -0.7 2.56 ± -0.7 2.56 ± -0.7 2.50 ± -0.7 2.00 ± -0.7 thut 2.00 ± -0.7 2.0	Acenaphthene	<u>3.60E+00</u>	<u>4.76E-02</u>	<u>7.69E-06</u>	<u>6.60E-03</u>	q	<u>6.30E+03</u>	<u>3.40E-03</u>	<u>2.50E-03</u>
thlor2.40E+022.13E-025.28E-063.40E-06b3.20E+03No Datacarb6.03E+033.18E-022.24E-065.90E-08b1.29E+011.09E-03ciarb1.70E-021.96E-024.86E-065.90E-03b2.50E+055.90E-04ciarb1.70E-021.96E-024.86E-067.00E-03b2.50E+047.50E-04ciarb1.70E-023.85E-022.74E-062.70E-03b2.50E+047.50E-04hracene4.30E-023.85E-026.67E-062.66E-03b2.50E+047.50E-04ciarb1.00E+012.59E-026.67E-062.30E-011.34E-012.00E+012.00E-04ciarb1.80E+038.80E-021.02E-052.30E-011.34E-012.00E+012.00E-04ciarb1.80E+038.80E-021.02E-052.30E-011.34E-012.00E+012.00E-04ciarb1.80E+038.80E-021.02E-052.30E-011.34E-012.00E+012.00E-04ciarb1.80E+038.80E-021.02E-052.30E-011.34E-012.00E+012.00E-04ciarb1.50E-032.23E-022.55E-062.30E-011.34E-032.00E+062.00E-04ciarb1.50E-032.23E-022.55E-062.55E-062.55E-062.55E-062.00E-032.00E+06colohuoranth8.00E-042.03E-022.55E-062.55E-062.55E-062.55E-062.55E-062.55E-062.55E-062.55E-06 <td>Acetone</td> <td><u>1.00E+06</u></td> <td><u>1.24E-01</u></td> <td><u>1.14E-05</u></td> <td><u>1.60E-03</u></td> <td><u>9.73E-04</u></td> <td>7.80E-01</td> <td>4.95E-02</td> <td><u>2.30E+02</u></td>	Acetone	<u>1.00E+06</u>	<u>1.24E-01</u>	<u>1.14E-05</u>	<u>1.60E-03</u>	<u>9.73E-04</u>	7.80E-01	4.95E-02	<u>2.30E+02</u>
icarb $6.03\pm+03$ 3.18 ± -02 7.24 ± -06 5.90 ± -08 \ldots^{-b} $1.29\pm+01$ 1.09 ± -03 in 1.70 ± -02 1.96 ± -02 4.86 ± -06 2.00 ± -03 \ldots^{-b} $2.50\pm+04$ 5.90 ± -04 in 1.70 ± -02 3.85 ± -02 4.86 ± -06 2.70 ± -03 \ldots^{-b} $2.50\pm+04$ 7.50 ± -04 inacene 4.30 ± -02 3.85 ± -02 2.74 ± -06 2.70 ± -03 \ldots^{-b} $2.50\pm+04$ 7.50 ± -04 inacene 4.30 ± -02 2.56 ± -06 2.66 ± -06 2.66 ± -06 1.34 ± -01 $3.63\pm+02$ 8.00 ± -04 izine $1.80\pm+03$ 8.80 ± -02 1.02 ± 02 2.30 ± -01 1.34 ± -01 9.00 ± -04 izine $1.80\pm+03$ 8.80 ± -02 2.00 ± -04 3.00 ± -04 9.00 ± -04 izine $1.80\pm+03$ 8.80 ± -02 2.30 ± -01 1.34 ± -01 $9.00\pm+02$ izine $2.00\pm+01$ 2.23 ± -02 5.56 ± -06 4.55 ± -03 \ldots^{-b} $1.05\pm+06$ 5.10 ± -04 izine 8.00 ± -04 2.23 ± -02 5.56 ± -06 3.40 ± -05 \ldots^{-b} $1.00\pm+06$ 5.10 ± -04 izine 8.00 ± -04 2.23 ± -02 5.56 ± -06 3.40 ± -05 \ldots^{-b} $1.00\pm+06$ 5.10 ± -04 izine 8.00 ± -04 2.23 ± -02 5.56 ± -06 3.40 ± -05 $5.00\pm+06$ 5.00 ± -04 izine 8.00 ± -04 2.23 ± -02 5.56 ± -06 5.56 ± -06 5.56 ± -06 5.56 ± -06 5.56 ± -06 izine 8.00 ± -04 2.23 ± -02 5.56 ± -06 5.56 ± -06 5.56 ± -06 5.56 ± -06 5.5	Alachlor	<u>2.40E+02</u>	2.13E-02	<u>5.28E-06</u>	<u>3.40E-06</u>	q	<u>3.20E+03</u>	<u>No Data</u>	<u>2.20E-05</u>
in $1.70E-02$ $1.96E-02$ $4.86E-06$ $7.00E-03$ \dots $2.50E+05$ $5.90E-04$ hracene $4.30E-02$ $3.85E-02$ $2.74E-06$ $2.70E-03$ \dots $2.50E+04$ $7.50E-04$ kracene $4.30E-02$ $2.59E-02$ $6.67E-06$ $9.68E-08$ \dots $2.50E+04$ $7.50E-04$ kracene $1.00E+01$ $2.59E-02$ $6.67E-06$ $9.68E-08$ \dots $0.62+01$ $9.00E-04$ kracene $1.80E+03$ $8.80E-02$ $1.02E-05$ $2.30E-01$ $1.34E-01$ $5.00E+01$ $9.00E-04$ zo(a) anthracen $9.40E-03$ $5.10E-02$ $9.00E-06$ $1.39E-04$ $0.0E-04$ $9.00E-04$ zo(a) anthracen $9.40E-03$ $5.10E-02$ $2.02E-06$ $1.39E-04$ $0.00E+06$ $5.10E-04$ zo(b) fluoranth $1.50E-03$ $2.23E-02$ $5.56E-06$ $4.55E-03$ \dots $1.00E+06$ $5.70E-04$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ $0.00E+06$ $0.00E+06$ $0.00E+06$ $0.00E+06$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $2.56E-06$ $3.40E-05$ $0.00E+06$ $0.00E+06$ $0.00E+06$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $2.90E-06$ $0.00E+06$ $0.00E+06$ $0.00E+06$ $0.00E+06$ zo(b) fluoranth $8.00E-04$ $2.02E-02$ $2.90E-06$ $0.00E+06$ <td>Aldicarb</td> <td><u>6.03E+03</u></td> <td><u>3.18E-02</u></td> <td><u>7.24E-06</u></td> <td><u>5.90E-08</u></td> <td>q</td> <td><u>1.29E+01</u></td> <td>1.09E-03</td> <td><u>3.47E-05</u></td>	Aldicarb	<u>6.03E+03</u>	<u>3.18E-02</u>	<u>7.24E-06</u>	<u>5.90E-08</u>	q	<u>1.29E+01</u>	1.09E-03	<u>3.47E-05</u>
hracene $4.30E-02$ $3.85E-02$ $7.74E-06$ $2.70E-03$ \dots^{-b} $2.50E+04$ $7.50E-04$ value $7.00E+01$ $2.59E-02$ $6.67E-06$ $9.68E-08$ \dots^{-b} $3.63E+02$ $No Data$ zene $1.00E+01$ $2.59E-02$ $6.67E-06$ $9.68E-08$ $1.34E-01$ $3.63E+02$ $No Data$ zene $1.80E+03$ $8.80E-02$ $1.02E-05$ $2.30E-01$ $1.34E-01$ $5.00E+01$ $9.00E-04$ zo(a) anthracen $9.40E-03$ $5.10E-04$ $1.39E-04$ \dots^{-b} $4.00E+02$ $5.10E-04$ zo(a) anthracen $9.40E-03$ $5.10E-02$ $9.00E-06$ $1.39E-04$ \dots^{-b} $9.00E+04$ zo(b) fluoranth $1.50E-03$ $2.23E-02$ $5.56E-06$ $3.40E-03$ $1.05E+06$ $5.70E-04$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ $1.00E+06$ $1.60E-04$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ $1.00E+06$ $1.60E-06$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ $1.00E+06$ $1.60E-06$ zo(b) fluoranth $8.00E-04$ $2.23E-02$ $2.70E-06$ $3.40E-05$ $1.00E+06$ $1.00E+06$ zo(b) fluoranth $3.40E+03$ $2.02E-02$ $2.97E-06$ $1.56E-06$ $1.56E-06$ $1.56E-06$ zo(b) fluoranth $3.40E+03$ $2.02E-02$ $2.97E-06$ $1.56E-06$ $1.56E-06$ $1.00E+06$	Aldrin	<u>1.70E-02</u>	<u>1.96E-02</u>	<u>4.86E-06</u>	<u>7.00E-03</u>	q	<u>2.50E+05</u>	<u>5.90E-04</u>	<u>6.00E-06</u>
zine $7.00E+01$ $2.59E-02$ $6.67E-06$ $9.68E-08$ \dots^{-b} $3.63E+02$ $No Data$ zene $1.80E+03$ $8.80E-02$ $1.02E-05$ $2.30E-01$ $1.34E-01$ $5.00E+01$ $9.00E-04$ zo(a)anthracen $9.40E-03$ $5.10E-02$ $9.00E-06$ $1.39E-04$ \dots^{-b} $4.00E+05$ $5.10E-04$ zo(a)anthracen $9.40E-03$ $5.10E-02$ $9.00E-06$ $1.39E-04$ \dots^{-b} $4.00E+05$ $5.10E-04$ zo(b)fluoranth $1.50E-03$ $2.23E-02$ $5.56E-06$ $4.55E-03$ \dots^{-b} $1.05E+06$ $5.70E-04$ zo(b)fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-03$ \dots^{-b} $1.00E+06$ $5.70E-04$ zo(b)fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ \dots^{-b} $1.00E+06$ $5.70E-04$ zo(b)fluoranth $8.00E-04$ $2.23E-02$ $7.97E-06$ $3.40E-05$ \dots^{-b} $1.00E+06^{4}$ $No Data$ zoic Acid $3.40E+03$ $7.02E-02$ $7.97E-06$ $1.56E-06$ \dots^{-b} $1.21E+00^{4}$ $No Data$	Anthracene	4.30E-02	<u>3.85E-02</u>	<u>7.74E-06</u>	<u>2.70E-03</u>		2.50E+04	7.50E-04	<u>2.70E-06</u>
zene $1.80E+03$ $8.80E-02$ $1.02E-05$ $2.30E-01$ $1.34E-01$ $5.00E+01$ $9.00E-04$ zo(a)anthracen $9.40E-03$ $5.10E-02$ $9.00E-06$ $1.39E-04$ \dots $4.00E+05$ $5.10E-04$ zo(b)fluoranth $1.50E-03$ $2.23E-02$ $5.56E-06$ $4.55E-03$ \dots $1.05E+06$ $5.70E-04$ zo(k)fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ $3.40E-05$ $1.05E+06$ $5.70E-04$ zo(k)fluoranth $8.00E-04$ $2.23E-02$ $5.56E-06$ $3.40E-05$ $3.40E-06$ $1.05E+06$ $1.60E+06$ zoic Acid $3.40E+03$ $7.02E-02$ $7.97E-06$ $1.56E-06$ $1.56E-06$ $1.56E-06$ $1.00E+00^4$ $1.00E+00^4$	Atrazine	7.00E+01	<u>2.59E-02</u>	<u>6.67E-06</u>	<u>9.68E-08</u>	۹	<u>3.63E+02</u>	<u>No Data</u>	<u>2.70E-07</u>
zo(a)anthracen 9.40E-03 5.10E-02 9.00E-06 1.39E-04 ^b 4.00E+05 5.10E-04 zo(b)fluoranth 1.50E-03 2.23E-02 5.56E-06 4.55E-03 ^b 1.05E+06 5.70E-04 zo(k)fluoranth 8.00E-04 2.23E-02 5.56E-06 3.40E-05 ^b 1.05E+06 5.70E-04 zo(k)fluoranth 8.00E-04 2.23E-02 5.56E-06 3.40E-05 ^b 1.00E+06 1.60E-04 zoic Acid 3.40E+03 7.02E-02 7.97E-06 1.56E-06 ^b 1.21E+00 ^d No Data	Benzene	<u>1.80E+03</u>	<u>8.80E-02</u>	<u>1.02E-05</u>	<u>2.30E-01</u>	<u>1.34E-01</u>	<u>5.00E+01</u>	<u>9.00E-04</u>	<u>9.50E+01</u>
zo(b)fluoranth 1.50E-03 2.23E-02 5.56E-06 4.55E-03 b 1.05E+06 5.70E-04 zo(k)fluoranth 8.00E-04 2.23E-02 5.56E-06 3.40E-05 1.40E+06 1.60E+06 1.60E-04 zoic Acid 3.40E+03 7.02E-02 7.97E-06 1.56E-06 b 1.21E+00 ^d No Data	<u>Benzo(a)anthracen</u> <u>e</u>	<u>9.40E-03</u>	<u>5.10E-02</u>	<u>9.00E-06</u>	<u>1.39E-04</u>	pp	<u>4.00E+05</u>	<u>5.10E-04</u>	<u>1.10E-07</u>
zo(k)fluoranth 8.00E-04 2.23E-02 5.56E-06 3.40E-05 3.40E-05 1.00E+06 1.60E+06 1.60E-04 zoic Acid 3.40E+03 7.02E-02 7.97E-06 1.56E-06 ^b 1.21E+00 ^d No Data	 <u>Benzo(b)fluoranth</u> ene	<u>1.50E-03</u>	<u>2.23E-02</u>	<u>5.56E-06</u>	<u>4.55E-03</u>	pb	<u>1.05E+06</u>	<u>5.70E-04</u>	<u>5.00E-07</u>
<u>3.40E+03</u> 7.02E-02 7.97E-06 1.56E-06 1.56E-06 1.21E+00 ^d No Data	 <u>Benzo(k)fluoranth</u> ene	<u>8.00E-04</u>	<u>2.23E-02</u>	<u>5.56E-06</u>	<u>3.40E-05</u>	٩ 	<u>1.00E+06</u>	<u>1.60E-04</u>	<u>2.00E-09</u>
	Benzoic Acid	<u>3.40E+03</u>	<u>7.02E-02</u>	<u>7.97E-06</u>	<u>1.56E-06</u>	q	<u>1.21E+00^d</u>	<u>No Data</u>	7.00E-04

POLLUTION CONTROL BOARD

Chemical	<u> iical</u>	<u>Solubility</u> in Water (S) (mg/L)	<u>Diffusivity</u> in Air (Di) (cm ² /s)	<u>Diffusivity</u> in Water (D _w) (cm ² /s)	<u>Dimensionless</u> <u>Henry's Law</u> <u>Constant (H')</u> (25°C)	Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route	Organic Carbon Partition Coefficient (K _{oc}) (L/kg)	First Order Degradation Constant (Å) (d ⁻¹)	<u>Vapor</u> <u>Pressure</u> (mm/Hg)
<u> </u>	Benzo(a)pyrene	<u>1.60E-03</u>	<u>4.30E-02</u>	<u>9.49E-06</u>	<u>4.50E-05</u>	q	<u>7.90E+05</u>	<u>6.50E-04</u>	<u>5.50E-09</u>
	<u>Bis(2-</u> <u>chloroethyl)ether</u>	<u>1.72E+04</u>	<u>4.13E-02</u>	<u>7.53E-06</u>	7.40E-04	<u>2.94E-04</u>	<u>1.26E+01</u>	<u>1.90E-03</u>	<u>1.55E+00</u>
	<u>Bis(2-</u> <u>ethylhexyl)phthalat</u> <u>e</u>	<u>3.40E-01</u>	<u>3.51E-02</u>	<u>3.66E-06</u>	<u>4.10E-06</u>	۹ <mark> </mark>	<u>1.00E+05</u>	<u>1.80E-03</u>	<u>6.80E-08</u>
	<u>Bromodichloromet</u> <u>hane</u>	<u>6.70E+03</u>	<u>5.61E-02</u>	<u>1.06E-05</u>	<u>6.60E-02</u>	<u>3.71E-02</u>	<u>5.00E+01</u>	<u>No Data</u>	<u>5.00E+01</u>
	<u>Bromoform</u>	<u>3.10E+03</u>	<u>1.49E-02</u>	<u>1.03E-05</u>	<u>2.19E-02</u>	<u>1.06E-02</u>	<u>9.12E+01</u>	<u>1.90E-03</u>	<u>5.51E+00</u>
	<u>Butanol</u>	7.40E+04	<u>8.00E-02</u>	<u>9.30E-06</u>	<u>3.61E-04</u>	<u>1.55E-04</u>	<u>6.00E+00</u>	<u>1.28E-02</u>	7.00E+00
	<u>2-Butanone</u> (MEK)	<u>2.20E+05</u>	<u>8.08E-02</u>	<u>9.8E-06</u>	<u>2.30E-03</u>	<u>1.32E-03</u>	<u>2.00E+00</u>	<u>4.95E-02</u>	<u>9.50E+01</u>
	<u>Butyl Benzyl</u> Phthalate	<u>2.70E+00</u>	<u>1.99E-02</u>	<u>4.89E-06</u>	<u>5.30E-05</u>	q	<u>6.30E+04</u>	<u>3.85E-03</u>	<u>8.30E-06</u>
	<u>Carbazole</u>	<u>1.20E+00</u>	<u>4.17E-02</u>	<u>7.45E-06</u>	<u>3.60E-06</u>		<u>4.00E+03</u>	<u>No Data</u>	7.00E-04
	<u>Carbofuran</u>	<u>3.20E+02</u>	<u>2.37E-02</u>	<u>5.95E-06</u>	<u>1.27E-07</u>	q	<u>1.91E+02</u>	<u>No Data</u>	<u>4.85E-06</u>
	Carbon Disulfide	<u>1.20E+03</u>	<u>1.04E-01</u>	<u>1.00E-05</u>	<u>1.23E+00</u>	<u>8.06E-01</u>	<u>6.30E+01</u>	<u>No Data</u>	<u>3.60E+02</u>
	<u>Carbon</u> <u>Tetrachloride</u>	<u>7.90E+02</u>	<u>7.80E-02</u>	<u>8.80E-06</u>	<u>1.23E+00</u>	<u>7.48E-01</u>	<u>2.00E+02</u>	<u>1.90E-03</u>	<u>1.20E+02</u>
	Chlordane	<u>5.60E-02</u>	<u>1.79E-02</u>	<u>4.37E-06</u>	<u>2.00E-03</u>	۹ 	<u>2.50E+05</u>	<u>2.50E-04</u>	<u>9.80E-06</u>

POLLUTION CONTROL BOARD

<u>No.</u>	<u>Chemical</u>	<u>Solubility</u> in Water (S) (mg/L)	<u>Diffusivity</u> in Air (Di) (cm ² /s)	Diffusivity in Water (D _w) (cm ² /s)	<u>Dimensionless</u> <u>Henry's Law</u> <u>Constant (H')</u> (25°C)	Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exnosure route	Organic Carbon Partition Coefficient (L/kg)	First Order Degradation Constant (d ⁻¹)	<u>Vapor</u> <u>Pressure</u> (mm/Hg)
<u>106-47-</u> <u>8</u>	p-Chloroaniline	<u>5.30E+03</u>	<u>6.99E-02</u>	<u>1.01E-05</u>	<u>4.76E-05</u>	_م	<u>6.31E+01</u>	<u>No Data</u>	<u>1.23E-02</u>
<u>108-90-</u>	Chlorobenzene	<u>4.70E+02</u>	7.30E-02	<u>8.70E-06</u>	<u>1.50E-01</u>	7.93E-02	<u>2.00E+02</u>	<u>2.30E-03</u>	<u>1.20E+01</u>
<u>124-48-</u> <u>1</u>	<u>Chlorodibromomet</u> <u>hane</u>	<u>2.60E+03</u>	<u>3.66E-02</u>	<u>1.05E-05</u>	<u>3.20E-02</u>	<u>2.07E-02</u>	<u>6.92E+01</u>	<u>3.85E-03</u>	4.90E+00
<u>67-66-3</u>	<u>Chloroform</u>	7.90E+03	<u>1.04E-01</u>	<u>1.00E-05</u>	<u>1.50E-01</u>	<u>9.18E-02</u>	5.00E+01	<u>3.90E-04</u>	2.00E+02
<u>95-57-8</u>	2-Chlorophenol	<u>2.20E+04</u>	<u>6.61E-02</u>	<u>9.46E-06</u>	<u>1.60E-02</u>	<u>7.28E-03</u>	<u>5.93E+01^d</u>	<u>No Data</u>	<u>2.34E+00</u>
<u>218-01-</u> <u>9</u>	<u>Chrysene</u>	<u>6.30E-03</u>	<u>2.44E-02</u>	<u>6.21E-06</u>	<u>3.90E-03</u>	q	<u>4.00E+05</u>	<u>3.50E-04</u>	<u>6.20E-09</u>
<u>94-75-7</u>	<u>2,4-D</u>	<u>6.77E+02</u>	<u>5.88E-02</u>	<u>6.49E-06</u>	<u>4.18E-07</u>		<u>5.75E+02</u>	<u>3.85E-03</u>	6.00E-07
72-54-8	<u>4,4'-DDD</u>	<u>9.00E-02</u>	<u>2.27E-02</u>	<u>5.79E-06</u>	<u>1.60E-04</u>		7.90E+05	<u>6.20E-05</u>	<u>6.70E-07</u>
<u>72-55-9</u>	<u>4,4'-DDE</u>	<u>1.20E-01</u>	<u>2.38E-02</u>	<u>5.87E-06</u>	<u>8.60E-04</u>	9	<u>4.00E+05</u>	<u>6.20E-05</u>	<u>6.00E-06</u>
<u>50-29-3</u>	<u>4,4'-DDT</u>	<u>2.50E-02</u>	<u>1.99E-02</u>	<u>4.95E-06</u>	<u>3.30E-04</u>	9	2.00E+06	<u>6.20E-05</u>	<u>1.60E-07</u>
75-99-0	<u>Dalapon</u>	<u>9.00E+05</u>	<u>6.08E-02</u>	<u>9.45E-06</u>	<u>2.64E-06</u>	NA	<u>4.80E+00</u>	<u>5.78E-03</u>	1.90E-01
<u>53-70-3</u>	<u>Dibenzo(a,h)anthra</u> cene	<u>2.50E-03</u>	<u>2.11E-02</u>	<u>5.24E-06</u>	<u>6.10E-07</u>	q	<u>2.50E+06</u>	<u>3.70E-04</u>	<u>1.00E-10</u>
<u>96-12-8</u>	<u>1,2-Dibromo-3-</u> <u>chloropropane</u>	<u>1.20E+03</u>	<u>2.68E-02</u>	7.02E-06	<u>6.20E-03°</u>	NA	7.90E+01	<u>1.93E-03</u>	5.80E-01
<u>106-93-</u>	<u>1.2-</u> Dibromoethane	<u>4.00E+03</u>	<u>4.37E-02</u>	<u>8.44E-06</u>	<u>3.00E-02</u>	<u>1.54E-02</u>	<u>5.00E+01</u>	<u>5.78E-03</u>	<u>1.30E+01</u>

POLLUTION CONTROL BOARD

POLLUTION CONTROL BOARD

<u>CAS</u> <u>No.</u>	Chemical	Solubility in Water (S) (mg/L)	Diffusivity in Air (Di) (cm ² /s)	Diffusivity in Water (D _w) (cm ² /s)	<u>Dimensionless</u> <u>Henry's Law</u> <u>Constant (H')</u> (25°C)	Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route	Organic Carbon Partition Coefficient (L/kg)	First Order Degradation Constant (Å) (d ⁻¹)	<u>Vapor</u> <u>Pressure</u> (mm/Hg)
	Dichloropropane								
<u>542-75-</u> <u>6</u>	<u>1,3-</u> <u>Dichloropropylene</u> (cis + trans)	<u>2.80E+03</u>	<u>6.26E-02</u>	<u>1.00E-05</u>	7.40E-01	<u>3.98E-01</u>	<u>2.00E+01</u>	<u>6.10E-02</u>	<u>3.40E+01</u>
<u>60-57-1</u>	<u>Dieldrin</u>	<u>2.00E-01</u>	<u>1.92E-02</u>	<u>4.74E-06</u>	<u>6.2E-04</u>	a	<u>2.50E+04</u>	<u>3.20E-04</u>	<u>5.9E-06</u>
84-66-2	Diethyl Phthalate	<u>1.10E+03</u>	<u>2.49E-02</u>	<u>6.35E-06</u>	<u>1.80E-05</u>		<u>3.20E+02</u>	<u>6.19E-03</u>	1.60E-03
<u>105-67-</u> <u>9</u>	<u>2,4-</u> <u>Dimethylphenol</u>	<u>7.90E+03</u>	<u>6.43E-02</u>	<u>8.69E-06</u>	<u>8.20E-05</u>	aa	<u>2.00E+02</u>	<u>4.95E-02</u>	<u>9.80E-02</u>
75-71-8	1,3-Dinitrobenzene	<u>8.60E+02</u>	<u>4.55E-02</u>	<u>8.46E-06</u>	<u>2.30E-07</u>	8	<u>3.20E+01</u>	<u>1.92E-03</u>	<u>9.00E-04</u>
51-28-5	2,4-Dinitrophenol	<u>2.79E+03</u>	<u>2.73E-02</u>	<u>9.06E-06</u>	<u>1.82E-05</u>	a	<u>3.24E+01</u>	<u>1.32E-03</u>	<u>5.10E-03</u>
<u>121-14-</u> 2	2,4-Dinitrotoluene	<u>2.70E+02</u>	<u>2.03E-01</u>	<u>7.06E-06</u>	<u>3.80E-06</u>	8	<u>8.90E+01</u>	<u>1.92E-03</u>	<u>1.47E-04</u>
<u>606-20-</u> 2	2,6-Dinitrotoluene	<u>1.82E+02</u>	<u>3.70E-02</u>	7.76E-06	<u>3.06E-05</u>	8	<u>4.90E+01</u>	<u>1.92E-03</u>	<u>5.67E-04</u>
<u>88-85-7</u>	<u>Dinoseb</u>	<u>5.20E+01</u>	<u>2.45E-02</u>	<u>6.25E-06</u>	<u>1.87E-05</u>		<u>9.17E+01^d</u>	<u>2.82E-03</u>	<u>7.50E-05</u>
<u>117-84-</u> <u>0</u>	<u>Di-n-octyl</u> <u>Phthalate</u>	<u>2.00E-02</u>	<u>1.73E-02</u>	<u>4.17E-06</u>	<u>2.74E-03</u>	8	<u>1.30E+05</u>	<u>1.90E-03</u>	<u>2.60E-06</u>
<u>123-91-</u> <u>1</u>	p-Dioxane	<u>1.00E+06</u>	<u>2.29E-01</u>	<u>1.02E-05</u>	<u>1.97E-04</u>	<u>1.07E-04</u>	<u>7.20E-01</u>	<u>1.92E-03</u>	<u>3.81E+01</u>
<u>115-29-</u> 7	<u>Endosulfan</u>	<u>5.10E-01</u>	<u>1.85E-02</u>	<u>4.55E-06</u>	<u>4.51E-04</u>	ю	<u>5.00E+03</u>	<u>7.63E-02</u>	<u>1.00E-05</u>

POLLUTION CONTROL BOARD

5	Chemical	Solubility in Water (S) (mg/L)	<u>Diffusivity</u> in Air (Di) (cm ² /s)	<u>Diffusivity</u> in Water (<u>D_w</u>) (cm ² /s)	<u>Dimensionless</u> <u>Henry's Law</u> <u>Constant (H')</u> (25°C)	Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route	Organic Carbon Partition Coefficient (L/kg)	First Order Degradation (A) (d ⁻¹)	<u>Vapor</u> <u>Pressure</u> (mm/Hg)
ŭ	Endothall	<u>2.10E+04</u>	<u>2.91E-02</u>	<u>8.07E-06</u>	<u>1.58E-14</u>	67 	<u>7.59E+01</u>	<u>No Data</u>	<u>1.57E-10</u>
Enc	Endrin	<u>2.50E-01</u>	<u>1.92E-02</u>	<u>4.74E-6</u>	<u>3.08E-04</u>		<u>3.20E+04</u>	<u>3.20E-04</u>	<u>3.00E-06</u>
Eth	Ethylbenzene	<u>1.70E+02</u>	<u>7.50E-02</u>	<u>7.80E-06</u>	<u>3.24E-01</u>	<u>1.64E-01</u>	<u>3.20E+02</u>	<u>3.00E-03</u>	<u>9.60E+00</u>
Flu	Fluoranthene	<u>2.06E-01</u>	<u>2.51E-02</u>	<u>6.35E-06</u>	<u>6.60E-04</u>	9 	7.40E+04	<u>1.90E-04</u>	<u>1.23E-08</u>
Flu	Fluorene	<u>2.00E+00</u>	<u>4.40E-02</u>	<u>7.88E-06</u>	<u>2.62E-03</u>	3	<u>1.30E+04</u>	<u>6.91E-04</u>	<u>6.30E-04</u>
He	<u>Heptachlor</u>	<u>1.80E-01</u>	<u>2.23E-02</u>	<u>5.69E-06</u>	<u>6.07E-02</u>	<u>1.73E-02</u>	<u>3.00E+03</u>	<u>1.30E-01</u>	<u>4.00E-04</u>
Hel epc	<u>Heptachlor</u> <u>epoxide</u>	<u>2.00E-01</u>	<u>2.19E-02</u>	<u>5.57E-06</u>	<u>3.90E-04</u>	8	<u>2.00E+05</u>	<u>6.30E-04</u>	<u>1.90E-05</u>
e He	<u>Hexachlorobenzen</u> <u>e</u>	<u>6.20E-03</u>	<u>5.42E-02</u>	<u>5.91E-06</u>	<u>5.33E-02</u>	<u>1.35E-02</u>	<u>2.00E+04</u>	<u>1.70E-04</u>	<u>1.80E-05</u>
Alt (alt	Alpha-HC <u>H</u> (alpha-BHC)	<u>2.00E+00</u>	<u>2.04E-02</u>	<u>5.04E-06</u>	<u>4.51E-04</u>	R 	<u>5.00E+03</u>	<u>2.50E-03</u>	<u>4.50E-05</u>
<u>(Li</u>	<u>Gamma-HCH</u> (Lindane)	7.30E+00	<u>2.75E-02</u>	<u>7.34E-06</u>	<u>5.74E-04</u>	۲۵ 	<u>3.00E+03</u>	<u>2.90E-03</u>	<u>4.10E-04</u>
No IEI HI	<u>High Melting</u> <u>Explosive,</u> <u>Octogen (HMX)</u>	<u>5.00E+00</u>	<u>2.69E-02</u>	<u>7.15E-06</u>	<u>8.67E-10</u>	<u>3.55E-08</u>	<u>1.40E+00</u>	<u>No Data</u>	<u>3.30E-14</u>
He. Per	<u>Hexachlorocyclo-</u> <u>Pentadiene</u>	<u>1.80E+00</u>	<u>2.79E-02</u>	<u>7.21E-06</u>	<u>1.11E+00</u>	<u>4.22E-01</u>	<u>1.20E+04</u>	<u>1.20E-02</u>	<u>5.96E-02</u>
He	<u>Hexachloroethane</u>	<u>5.00E+01</u>	<u>2.50E-03</u>	<u>6.80E-06</u>	<u>1.59E-01</u>	<u>7.26E-02</u>	<u>1.50E+03</u>	<u>1.92E-03</u>	<u>2.10E-01</u>

POLLUTION CONTROL BOARD

POLLUTION CONTROL BOARD

	1	1						Ϋ́			1		T
<u>Vapor</u> <u>Pressure</u> (mm/Hg)		<u>1.30E-01</u>	<u>3.20E-05</u>	<u>2.80E-01</u>	7.21E-11	a a	<u>4.60E-06</u>	4.10E-09	<u>2.21E-08</u>	<u>6.10E+00</u>	<u>9.97E-06</u>	<u>1.90E+01</u>	2.80E+01
$\frac{First}{Order}$ $\frac{Order}{Degradation}$ $\frac{(\lambda)}{(d^{-1})}$		<u>1.90E-03</u>	<u>4.50E-04</u>	<u>9.90E-02</u>	<u>No Data</u>	8	<u>1.80E-04</u>	No Data	<u>No Data</u>	<u>3.30E-03</u>	No Data	<u>9.60E-04</u>	<u>1.10E-02</u>
Organic Carbon Partition Coefficient (K _{oc}) (L/kg)		<u>1.45E+01</u>	2.77E+03 ^d	2.00E+01	2.00E+00	8	<u>6.31E+04</u>	7.20E+00	<u>1.32E+02</u>	<u>3.16E+02</u>	<u>5.50E+03</u>	<u>6.31E+02</u>	<u>1.58E+02</u>
Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route		<u>5.48E-05</u>	3	<u>6.67E-06</u>	3	8 1 1 1 1 1 1 1 1 1 1 1 1 1		ся 	aa	<u>5.48E-03</u>	a	<u>4.00E-01</u>	<u>1.49E-01</u>
Dimensionless Henry's Law Constant (H') (25°C)		<u>9.20E-05</u>	<u>9.84E-07</u>	<u>1.64E-05</u>	<u>2.19E-12</u>	a	<u>4.51E-04</u>	<u>2.01E-11</u>	<u>3.80E-08</u>	1.11E-01	<u>3.71E-07</u>	7.38E-01	2.71E-01
<u>Diffusivity</u> in Water (<u>D_w</u>) (cm ² /s)		<u>8.17E-06</u>	<u>6.10E-06</u>	<u>9.10E-06</u>	<u>5.64E-06</u>	e	<u>7.24E-06</u>	<u>8.49E-06</u>	<u>6.28E-06</u>	<u>8.00E-06</u>	<u>5.83E-06</u>	<u>8.20E-06</u>	<u>8.60E-06</u>
<u>Diffusivity</u> in Air (Di) (cm ² /s)		<u>5.87E-02</u>	<u>5.60E-02</u>	<u>8.20E-02</u>	<u>2.26E-02</u>	a	<u>2.77E-02</u>	<u>3.11E-02</u>	<u>2.48E-02</u>	7.10E-02	<u>2.30E-02</u>	<u>7.20E-02</u>	<u>8.70E-02</u>
<u>Solubility</u> in Water (S) (mg/L)		<u>9.89E+03</u>	<u>2.00E+03</u>	<u>8.30E+04</u>	<u>4.30E+02</u>	ت ا	<u>1.40E+00</u>	5.97E+01	<u>6.20E+00</u>	<u>3.10E+02</u>	7.10E+01	<u>2.00E+02</u>	<u>5.30E+02</u>
Chemical	ine	<u>N-Nitrosodi-n-</u> propylamine	Pentachlorophenol	Phenol	<u>Picloram</u>	<u>Polychlorinated</u> <u>biphenyls (PCBs)</u>	<u>Pyrene</u>	<u>Royal Demolition</u> <u>Explosive</u> , <u>Cyclonite (RDX)</u>	Simazine	Styrene	2,4,5-TP (Silvex)	<u>Tetrachloroethylen</u> <u>e</u>	Toluene
<u>CAS</u> <u>No.</u>		<u>621-64-</u> <u>7</u>	<u>87-86-5</u>	<u>108-95-</u> 2	<u>1918-</u> 02-1	<u>1336-</u> <u>36-3</u>	<u>129-00-</u> 0	<u>121-82-</u> <u>4</u>	<u>122-34-</u> <u>9</u>	<u>100-42-</u> <u>5</u>	<u>93-72-1</u>	<u>127-18-</u> <u>4</u>	108-88-

POLLUTION CONTROL BOARD


		r						[<u> </u>		
<u>Vapor</u> <u>Pressure</u> (mm/Hg)		<u>9.80E-07</u>	<u>4.30E-01</u>	<u>1.20E+02</u>	<u>2.30E+01</u>	7.30E+01	<u>8.00E+02</u>	<u>2.40E-02</u>	<u>2.00E-02</u>	<u>9.00E+01</u>	<u>6.40E-06</u>	<u>2.02E-06</u>	3.00E+03
$\frac{First}{Order}$ $\frac{Order}{Degradation}$ $\frac{(\Delta)}{(d^{-1})}$		<u>No Data</u>	<u>1.90E-03</u>	1.30E-03	<u>9.50E-04</u>	4.20E-04	<u>9.63E-04</u>	<u>3.80E-04</u>	<u>3.80E-04</u>	<u>No Data</u>	No Data	<u>1.92E-03</u>	2.40E-04
Organic Carbon Partition Coefficient (<u>K_{oc}</u>) (<u>L/kg</u>)		<u>5.01E+04</u>	<u>1.58E+03</u>	<u>1.26E+02</u>	5.01E+01	<u>1.00E+02</u>	<u>1.30E+02</u>	<u>2.68E+03^d</u>	8.78E+02 ^d	<u>4.57E+00</u>	<u>1.60E+01</u>	<u>3.72E+01</u>	<u>1.58E+01</u>
Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route			2.38E-02	<u>4.21E-01</u>	<u>1.98E-02</u>	<u>2.41E-01</u>	<u>2.69E+00</u>	5	8	<u>1.18E-02</u>	a	3	<u>8.14E-01</u>
Dimensionless Henry's Law Constant (H') (25°C)		<u>2.46E-04</u>	<u>5.74E-02</u>	<u>6.97E-01</u>	<u>3.73E-02</u>	<u>4.10E-01</u>	<u>3.98E+00</u>	<u>1.78E-04</u>	<u>3.53E-04</u>	<u>2.09E-02</u>	<u>3.30E-10</u>	<u>4.87E-09</u>	1.11E+00
<u>Diffusivity</u> in Water (D _w) (cm ² /s)		<u>5.51E-06</u>	<u>8.23E-06</u>	<u>8.80E-06</u>	<u>8.80E-06</u>	9.10E-06	<u>9.70E-06</u>	<u>7.03E-06</u>	<u>6.36E-06</u>	<u>9.20E-06</u>	<u>6.08E-06</u>	7.90E-06	<u>1.23E-06</u>
<u>Diffusivity</u> in Air (Di) (cm ^{2/s})		<u>2.16E-02</u>	<u>3.00E-02</u>	<u>7.80E-02</u>	<u>7.80E-02</u>	7.90E-02	<u>8.70E-02</u>	<u>2.91E-02</u>	<u>2.61E-02</u>	<u>8.50E-02</u>	<u>2.41E-02</u>	<u>2.94E-02</u>	<u>1.06E-01</u>
<u>Solubility</u> in Water (S) (mg/L)		<u>7.40E-01</u>	<u>3.50E+01</u>	<u>1.30E+03</u>	<u>4.40E+03</u>	<u>1.50E+03</u>	<u>1.10E+03</u>	<u>1.20E+03</u>	<u>8.00E+02</u>	2.00E+04	<u>2.80E+02</u>	<u>1.24E+02</u>	<u>8.80E+03</u>
Chemical		Toxaphene	<u>1.2.4-</u> <u>Trichlorobenzene</u>	<u>1,1,1-</u> Trichloroethane	<u>1,1,2-</u> Trichloroethane	Trichloroethylene	<u>Trichlorofluoromet</u> <u>hane</u>	<u>2,4,5-</u> Trichlorophenol	<u>2,4,6-</u> <u>Trichlorophenol</u>	Vinyl Acetate	<u>1,3,5-</u> Trinitrobenzene	<u>2,4,6-</u> Trinitrotoluene (TNT)	Vinyl Chloride
<u>CAS</u> <u>No.</u>	3	<u>8001-</u> 35-2	<u>120-82-</u> <u>1</u>	71-55-6	79-00-5	<u>79-01-6</u>	75-69-4	<u>95-95-4</u>	<u>88-06-2</u>	<u>108-05-</u> 4	<u>99-35-4</u>	<u>118-96-</u> <u>7</u>	<u>57-01-4</u>

	N	OTIC	E OF	PROP	OSED AMENDMENTS
<u>Vapor</u> <u>Pressure</u> (mm/Hg)	<u>8.50E+00</u>	<u>6.60E+00</u>	<u>8.90E+00</u>	<u>8.00E+00</u>	<u>chemical</u> sult with ters. The
$\frac{First}{Order}$ $\frac{Order}{Degradation}$ $\frac{(\Lambda)}{(d^{-1})}$	<u>1.90E-03</u>	<u>1.90E-03</u>	<u>1.90E-03</u>	<u>1.90E-03</u>	que for each nce at Section es should con ferent conger t the site
Organic Carbon Partition Coefficient (<u>K_{oc}</u>) (<u>L/kg</u>)	<u>3.98E+02</u>	<u>3.16E+02</u>	<u>3.16E+02</u>	<u>3.98E+02</u>	- <u>xx-x</u> , is uni ed by refere lediating site ixture of dif ers present a
Dimensionless Henry's Law Constant (H') (13°C) For the indoor inhalation exposure route	<u>1.52E-01</u>	<u>1.07E-01</u>	<u>1.59E-01</u>	NA	the format xxx. 1, as incorporates; persons rem PCBs are a m end on congene
<u>Dimensionless</u> <u>Henry's Law</u> Constant (H') (25°C)	<u>2.99E-01</u>	<u>2.13E-01</u>	<u>3.16E-01</u>	<u>2.71E-01</u>	This number in pases. t to 40 CFR 76 "), for most sit tives is desired. parameters dep
<u>Diffusivity</u> in Water (D _w) (cm ² /s)	<u>7.80E-06</u>	<u>1.00E-05</u>	<u>8.44E-06</u>	<u>9.23E-06</u>	S) registry number. This r i computerized data bases. e determined pursuant to 4 Spill Cleanup Policy"), fo 3 remediation objectives le physical/chemical paran
<u>Diffusivity</u> in Air (Di) (cm ² /s)	7.00E-02	<u>8.70E-02</u>	<u>7.69E-02</u>	<u>7.35E-02</u>	CAS) registi 2 on compute are determi CB Spill Cle 2 or 3 remed r the physic
<u>Solubility</u> in Water (S) (mg/L)	<u>1.60E+02</u>	<u>1.80E+02</u>	<u>1.60E+02</u>	<u>1.10E+02</u>	ts Service (ant searching n objectives USEPA "P ion of Tier 2 aes to use fo Henry's Law
Chemical	<u>m-Xylene</u>	<u>o-Xylene</u>	p-Xylene	Xylenes (total)	Chemical Abstracts Service (CAS) registry number. This number in the format xxx-xx-x, is unique for each chemical and allows efficient searching on computerized data bases. ^a Soil remediation objectives are determined pursuant to 40 CFR 761, as incorporated by reference at Section 742.210(b) (the USEPA "PCB Spill Cleanup Policy"), for most sites; persons remediating sites should consult with BOL if calculation of Tier 2 or 3 remediation objectives is desired. PCBs are a mixture of different congeners. The appropriate values to use for the physical/chemical parameters depend on congeners present at the site.
<u>CAS</u> <u>No.</u>	<u>108-38-</u> <u>3</u>	<u>95-47-6</u>	<u>106-42-</u> <u>3</u>	<u>1330-</u> 20-7	

- The 742.210(b) (the USEPA "PCB Spill Cleanup Policy"), for most sites; persons remediating sites should consult with BOL if calculation of Tier 2 or 3 remediation objectives is desired. PCBs are a mixture of different congeners. Soil remediation objectives are determined pursuant to 40 CFR 761, as incorporated by reference at Section appropriate values to use for the physical/chemical parameters depend on congeners present at the site. ст)
 - Dimensionless Henry's Law Constant at 13°C is not calculated because the chemical is not volatile and does not require evaluation under the indoor inhalation exposure route. ച
- ^{ε} Dimensionless Henry's Law Constant = 20°C
- ^d These chemicals are ionizing and its K_{oc} value will change with pH. The K_{oc} values listed in this table is the effective K_{oc} at pH of 6.8. If the site-specific pH is values other than 6.8, the K_{oc} value listed in Section 742, Appendix C, Table I should be used.
- The values in this table were taken from the following sources (in order of preference): SCDMS online database (http://www.epa.gov/superfund/sites/npl/hrsres/tools/scdm.htm); CHEMFATE online database (http://www.srcinc.com/what-we-do/databaseforms.aspx?id=381); PhysProp online database e)

ILLINOIS REGISTER

POLLUTION CONTROL BOARD



(Source: Amended at 36 Ill. Reg. ____, effective _____

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

Section 742. APPENDIX C: Tier 2 Illustrations and Tables

Section 742. Table F: Methods for Determining Physical Soil Parameters

Methods for Determining Physical Soil Parameters							
Parameter	Sampling Location ^a	Method					
$\rho_{\rm b}$ (soil bulk density)	Surface	ASTM - D 1556-90 Sand Cone Method ^b					
		ASTM - D 2167-94 Rubber Balloon Method ^b					
		ASTM - D 2922-91 Nuclear Method ^b					
	Subsurface	ASTM - D 2937-94 Drive Cylinder Method ^b					
ρ_{s} (soil particle density)	Surface or Subsurface	ASTM - D 854-92 Specific Gravity of Soil ^b					
w (moisture content)	Surface or Subsurface	ASTM - D 4959-89 (Reapproved 1994) Standard ^b					
		ASTM - D 4643-93 Microwave Oven ^b					
		ASTM - D2216-92 Laboratory Determination ^b					
		ASTM - D3017-88 (Reapproved 1993) Nuclear Method ^b					
		Equivalent USEPA Method (e.g., sample preparation procedures described in methods 3541 or 3550)					
f _{oc} (fraction organic carbon content)	Surface or Subsurface	ASTM - D 2974-00 Moisture, Ash, and Organic Matter ^b appropriately adjusted to estimate the fraction of organic carbon as stated in Nelson and Sommers (1982) ^b					

Methods	Methods for Determining Physical Soil Parameters								
Parameter	Sampling Location ^a	Method							
η or $θ_T$ (total soil porosity)	Surface or Subsurface (calculated)	Equation S24 in Appendix C, Table A for SSL Model, or Equation R23 in Appendix C, Table C for RBCA Model, <u>or</u> <u>Equation J&E 16 in Appendix</u> <u>C, Table L for J&E Model</u>							
θ_a or θ_{as} (air-filled soil porosity)	Surface or Subsurface (calculated)	Equation S21 in Appendix C, Table A for SSL Model, or Equation R21 in Appendix C, Table C for RBCA Model, <u>or</u> Equation J&E 18 in Appendix C, Table L for J&E Model							
θ_w or θ_{ws} (water-filled soil porosity)	Surface or Subsurface (calculated)	Equation S20 in Appendix C, Table A for SSL Model, or Equation R22 in Appendix C, Table C for RBCA Model, <u>or</u> Equation J&E 17 in Appendix C, Table L for J&E Model							
K (hydraulic conductivity)	Surface or Subsurface	ASTM - D 5084-90 Flexible Wall Permeameter ^b Pump Test Slug Test							
i (hydraulic gradient)	Surface or Subsurface	Field Measurement							

^a This is the location where the sample is collected ^b As incorporated by reference in Section 742.120.

(Source: Amended at 36 Ill. Reg. ____, effective ____)

J&E3 J&E4 J&E5 J&E6 J&E2 J&E1 Note: 24.45 equals the molar volume of air in liters at normal $THQ \times AT_{uc} \times 365 \frac{days}{\dots} \times RfC$ gm $ED \times EF \times URF \times 1000 \frac{\mu g}{M}$ $TR \times AT_c \times 365 \frac{\text{days}}{2}$ ¥ yr $\underline{R \times T} \times 10^6$ $mg/m^3 = \frac{ppmv \times MW}{mg/m^3}$ $H_{TS}^{'} \times 1000 \frac{L}{m^3}$ $ED \times EF$ RO indoor-air temperature (25°C) and pressure (760 mm Hg). RO soilg as 24.45 8 $P \times MW$ $RO_{soilg\,as} = C_v^{sat} = \frac{1}{2}$ RO_{gw} = - $RO_{indoor-air} = .$ İ RO indoor-air For carcinogenic noncarcinogenic contaminants contaminants For Groundwater mg/m² from remediation **remediation** remediation (mg/m³-air) To convert Soil Vapor objectives Saturation objectives Indoor air objective parts per (mg/m^3) (mg/m³) Soil gas million volume Limit

NOTICE OF PROPOSED AMENDMENTS

POLLUTION CONTROL BOARD

Section 742. APPENDIX C: Tier 2 Tables

Section 742. Table L: J&E Equations

POLLUTION CONTROL BOARD

J&ET	J&E8
$\alpha = \frac{\left[\left(\frac{D_T^{eff} \times A_B}{Q_{bidg} \times L_T} \right) \times \exp \left(\frac{Q_{soil} \times L_{crack}}{D_{crack}^{eff} \times A_{crack}} \right) \right]}{\left[\exp \left(\frac{Q_{soil} \times L_{crack}}{D_{crack}^{eff} \times A_{crack}} \right) + \left(\frac{D_T^{eff} \times A_B}{Q_{bidg} \times L_T} \right) + \left(\frac{D_T^{eff} \times A_B}{Q_{soil} \times L_T} \right) \left[\exp \left(\frac{Q_{soil} \times L_{crack}}{D_{crack} \times A_{crack}} \right) - 1 \right] \right]}$	$\alpha = \frac{\left(\frac{D_T^{eff} \times A_B}{Q_{bldg} \times L_T}\right)}{\left[1 + \left(\frac{D_T^{eff} \times A_B}{Q_{bldg} \times L_T}\right) + \left(\frac{D_T^{eff} \times A_B \times L_{cuck}}{L_T \times D_{cuck}^{eff} \times A_{cuck}}\right)\right]}$
Attenuationfactor when themode ofcontaminanttransport is bothdiffusion andadvection $Q_{soil} = 83.33$ cm ³ /sec	<u>Attenuation</u> <u>factor when the</u> <u>mode of</u> <u>contaminant</u> <u>transport is</u> <u>diffusion only</u> Q _{soij} = 0 cm ³ /sec
lation	lactor

POLLUTION CONTROL BOARD

<u>J&E9a</u>	<u>J&E9b</u>	J&E10	<u>J&E11</u>	<u>J&E12a</u>	J&E12b
$D_T^{eff} = \frac{L_T}{\sum\limits_{i=1}^n L_i / D_i^{eff}}$	$\sum_{i=1}^{n} L_i = L_T$	$L_T = D_{source} - L_F$	$D_i^{ ext{eff}} = D_i iggl(egin{array}{c} 3.33 \ heta_{i,j} \ heta_{T,i} \ het$	$A_B = (L_B \times W_B)$	$A_B = (L_B \times W_B) + (2 \times L_F \times L_B) + (2 \times L_F \times W_B)$
	<u>In Equation</u> <u>J&E9a, the</u> <u>following</u> <u>condition must</u> <u>be satisfied:</u>			<u>For a slab-on-</u> grade building	For a building with a basement
<u>Total overall</u> <u>effective</u> <u>diffusion</u> <u>coefficient for</u> <u>vapor</u>	<u>transport in</u> <u>porous media</u> <u>for multiple</u> <u>soil layers</u> (cm ² /s)	<u>Source to</u> <u>building</u> <u>separation</u> (cm)	<u>Effective</u> <u>diffusion</u> <u>coefficient for</u> <u>each soil</u> <u>layer (cm²/s)</u>	Surface area of enclosed space at or below grade (cm ²)	Surface are of enclosed space at or below grade (cm ²)

POLLUTION CONTROL BOARD

<u>J&E13</u>	J&E14	J&E15	<u>J&E16</u>	<u>J&E17</u>	<u>J&E18</u>
$Q_{bldg} = \left(\frac{L_B \times W_B \times H_B \times ER}{3600 \frac{\text{sec}}{\text{hr}}} \right)$	$A_{crack} = 2 \times (L_B + W_B) \times W$	$D_{arack}^{eff} = D_i \Biggl(rac{ heta_{a,crack}}{ heta_{T,crack}} \Biggr) + \Biggl(rac{D_w}{H_T^{'}} \Biggr) \Biggl(rac{ heta_{3,33}}{ heta_{T,crack}^2} \Biggr)$	$\theta_{Ti} = 1 - \frac{\rho_{bi}}{\rho_s}$	$\theta_w = \left(W\right) \left(\frac{\rho_b}{\rho_w}\right)$	$\underline{\theta_a = \theta_T - \theta_w}$
<u>Building</u> <u>ventilation</u> <u>rate (cm³/s)</u>	<u>Area of total</u> cracks (cm ²)	<u>Effective</u> <u>diffusion</u> <u>coefficient</u> <u>through the</u> <u>cracks (cm²/s)</u>	Total porosity	<u>Water-filled</u> soil porosity	<u>Air-filled soil</u> porosity

NOTICE OF PROPOSED AMENDMENTS

(Source: Added at 36 Ill. Reg. ____, effective _

Section 742. APPENDIX C: Tier 2 Tables

Section 742. Table M: J&E Parameters

	NOTICE OF PROPOSED AMENDMENTS						
Tier 1 or Calculated Value	$\frac{\text{Residential} = 1 \text{ x } 10^{6}}{\text{Industrial/Commercial} = 4.0 \text{ x } 10^{6}}$	Calculated Value	70	<u>Residential = 30</u> <u>Industrial/Commercial = 25</u>	<u>Chemical-Specific or Calculated</u> <u>Value</u>	Calculated Value	Chemical-Specific
Source	Equation J&E 12a or 12b, Appendix C, Table L	<u>Equation J&E 14,</u> Appendix C, Table L	<u>SSL, May 1996</u>	<u>AT_{nc}=ED</u>	<u>Equation J&E 5,</u> Appendix C, Table L	Equation J&E 15, Appendix C, Table L	Appendix C, Table E
<u>Units</u>	<u>cm²</u>	$\overline{cm^2}$	<u>year</u>	<u>year</u>	<u>mg/m³-air</u>	<u>cm² /s</u>	<u>cm² /s</u>
Parameter	Surface area of enclosed space at or below grade	Area of total cracks	<u>Averaging time for</u> carcinogens	<u>Averaging time for</u> <u>noncarcinogens</u>	<u>Soil vapor saturation</u> <u>limit</u>	<u>Effective diffusion</u> <u>coefficient through the</u> <u>cracks</u>	Diffusivity in air
<u>Symbol</u>	$\underline{A}_{\overline{B}}$	$\underline{\mathbf{A}}_{\mathrm{crack}}$	$\overline{\mathrm{AT}_{\mathrm{c}}}$	$\overline{\mathrm{AT}_{\mathrm{nc}}}$	$\underline{C}_{v}^{\underline{sat}}$	<u>D_{crack} eff</u>	<u>D</u> i

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

	1			SED AMENDI		
Calculated Value	Soil Contamination = 152.4 Groundwater Contamination = <u>304.8</u> Site-Specific	Calculated Value	Chemical-Specific	<u>Residential = 30</u> Industrial/Commercial = 25	<u>Residential = 350</u> Industrial/Commercial = 250	<u>Residential = 0.53</u> Industrial/Commercial = 0.93
Equation J&E 11, Appendix C, Table L	Field Measurement	<u>Equation J&E 9a.</u> Appendix C, Table <u>L</u>	Appendix C, Table E	<u>Residential: SSL, May</u> <u>1996</u> <u>Industrial/Commercial:</u> <u>SSL 2002</u>	Residential: SSL, May <u>1996</u> Industrial/Commercial: <u>SSL 2002</u>	<u>Illinois EPA</u>
<u>cm²/s</u>	cm	$\overline{\mathrm{cm}^2/\mathrm{S}}$	$\frac{\mathrm{cm}^2/\mathrm{S}}{\mathrm{S}}$	<u>year</u>	<u>day/year</u>	<u>exchanges per</u> <u>hour</u>
<u>Effective diffusion</u> <u>coefficient for each soil</u> <u>layer</u>	<u>Distance from ground</u> <u>surface to top of</u> <u>contamination</u>	<u>Total overall effective</u> <u>diffusion coefficient</u>	Diffusivity in water	Exposure duration	Exposure frequency	<u>Air exchange rate</u>
Di ^{eff}	Dsource	$\underline{\mathrm{D}}_{\overline{\mathrm{I}}}$	$\underline{D}_{\underline{w}}$	ED	Ξ	ER

POLLUTION CONTROL BOARD

		I	,	
0.002 or Site-Specific	Slab on Grade <u>Residential = 244</u> <u>Industrial/Commercial = 305</u> <u>or Site-Specific in Tier 3</u> <u>Basement</u> <u>Residential = 427</u> <u>Industrial/Commercial = 488</u> or Site-Specific in Tier 3	Chemical-Specific	<u>Residential = 1000</u> <u>Industrial/Commercial = 2000</u> <u>or Site-Specific in Tier 3</u>	<u>10</u>
<u>SSL, May 1996, or Field</u> <u>Measurement</u> <u>Appendix C, Table F</u>	Illinois EPA	<u>Appendix C, Table E</u>	Illinois EPA	<u>US EPA, Users Guide</u> 2004
5/8	cu	unitless	cm	<u>cm</u>
Fraction organic carbon content	<u>Height of building</u>	<u>Dimensionless Henry's</u> law constant at the <u>system (soil)</u> temperature 13°C	Length of building	Slab thickness
<u>f</u> oc	HB	$\underline{\mathrm{H}}_{\mathrm{TS}}$	<u>L</u> B	L <u>crack</u>

POLLUTION CONTROL BOARD

POLLUTION CONTROL BOARD

Ľ	<u>Distance from ground</u> surface to bottom of <u>slab</u>	CII	<u>US EPA, Users Guide</u> 2004	<u>10 (slab on grade)</u> 200 (basement)
Ľ.	<u>Thickness of soil layer</u> <u>i</u>	cm	Field Measurement For capillary fringe, USEPA, 2004	<u>Site-Specific</u> For capillary fringe, 37.5 cm
$\underline{L_{T}}$	<u>Distance from bottom</u> <u>of slab to top of</u> <u>contamination</u>	cm	Field Measurement or Equation J&E 10, Appendix C, Table L	142.4 or Site-Specific
<u>MW</u>	<u>Molecular weight</u>	<u>g/mole</u>	Illinois EPA	Chemical-Specific
ц	<u>Total number of layers</u> <u>of different types of</u> <u>soil vapors migrate</u> <u>through from source to</u> <u>building</u> (if source is <u>groundwater, include a</u> <u>capillary fringe layer of</u> <u>37.5 cm as one of the</u> <u>layers)</u>	unitless	Field measurement	Site-Specific
4	Vapor Pressure	<u>atm</u>	<u>Appendix C, Table E</u>	Chemical-Specific

Industrial/Commercial = 3.15×10^{5} Industrial/Commercial = $5.04 \text{ x} 10^5$ If L_T is 5 feet (152 cm) or greater, An input value of zero requires an If L_T is less than 5 feet (152 cm), institutional control. See Section Chemical-Specific or Calculated or Site-Specific in Tier 3 or Site-Specific in Tier 3 Residential = 3.59×10^4 Residential = 6.28×10^4 Toxicological-Specific 742.505(b) and (c). Qsoil equals 83.33 Q_{soil} equals zero Slab on Grade Basement 0.08206 Value US EPA, Users Guide for http://www.epa.state.il.us Appendix B, Table E, or **Evaluating Subsurface** US EPA, Users Guide Appendix C, Table L Appendix C, Table L Vapor Intrusion into /land/taco/toxicity-Equation J&E 13, Equation J&E 6, **Buildings 2004** Illinois EPA: values.xls 2004 atm-L/mol-K ug/m³ cm³/s cm³/s <u>mg/L</u> Volumetric flow rate of remediation objective Building ventilation Ideal gas constant soil gas into the enclosed space concentration Groundwater Reference rate ROgw Q_{bldg} RfC Q_{soil} 2

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

Industrial/Commercial = 10^{-6} at the Residential = 10^{-6} at the point of 286 (converted from 13°C) point of human exposure Toxicological-Specific Chemical-Specific Calculated Value Calculated Value human exposure 0.1 -1 http://www.epa.state.il.us Equations J&E 1 and 2, US EPA, Users Guide US EPA, Users Guide Appendix C, Table L Appendix C, Table E Appendix C, Table L /land/taco/toxicity-Equation J&E 4, SSL, May 1996 SSL, May 1996 Illinois EPA: values.xls 2004 2004 $(ug/m^3)^{-1}$ unitless <u>mg/m³</u> <u>mg/m³</u> unitless <u>mg/L</u> cm \mathbf{M} developing cancer over exposure to a chemical Target hazard quotient Indoor air remediation Soil gas remediation Floor-wall seam gap increased chance of Solubility in water Target risk or the a lifetime due to Unit risk factor for a chemical Temperature objective objective <u>RO</u>soilgas <u>ROindoor</u> THQ URF TR -air ≥| 2 H

ILLINOIS REGISTER

POLLUTION CONTROL BOARD

	r		JF PROPOSEI				
<u>Site-Specific</u>	<u>Residential = 1000</u> <u>Industrial/Commercial = 2000</u> or Site-Specific in Tier <u>3</u>	<u>Site-Specific</u>	0.28 or Calculated Value	<u>0.13</u>	<u>0.13 or Calculated Value</u> For capillary fringe, $\theta_{a,i} = 0.1 \ \theta_{T,i}$	0.43	0.43 or Calculated Value
<u>Field Measurement,</u> <u>Appendix C, Table F</u>	<u>Illinois EPA</u>	<u>Equations J&E 7 or 8,</u> <u>Appendix C, Table L</u>	<u>SSL, May 1996 or</u> <u>Equation J&E 18,</u> <u>Appendix C, Table L</u>	SSL, May 1996 or Equation J&E 18, Appendix C, Table L	<u>SSL, May 1996 or</u> <u>Equation J&E 18,</u> <u>Appendix C, Table L</u>	<u>SSL, May 1996 or</u> <u>Equation J&E 16,</u> <u>Appendix C, Table L</u>	SSL, May 1996 or Equation J&E 16, Appendix C, Table L
g of water/g of soil	cm	<u>unitless</u>	$\frac{\mathrm{cm}^3/\mathrm{cm}^3}{\mathrm{cm}^3}$	cm^3/cm^3	$\mathrm{cm}^3/\mathrm{cm}^3$	$\frac{\mathrm{cm}^3/\mathrm{cm}^3}{\mathrm{cm}^3}$	$\overline{\mathrm{cm}^3/\mathrm{cm}^3}$
Moisture content	Width of building	Attenuation factor	Air-filled soil porosity	<u>Air-filled porosity for</u> soil in cracks	<u>Air-filled porosity of soil layer i</u>	<u>Total porosity for soil</u> in cracks	<u>Total porosity of soil</u> <u>layer i</u>
B	$\underline{W}_{\mathbf{B}}$	ß	$\overline{\Theta}_{a}$	<u> </u>	$\underline{\theta}_{a,i}$	$\underline{\Theta}_{T, crack}$	$\underline{\theta}_{\mathrm{T,i}}$

POLLUTION CONTROL BOARD

	NOTICE OF PROPOSED AMENDMENTS				
0.15 or Calculated Value	0.15	$\frac{0.15 \text{ or Calculated Value}}{\text{For capillary fringe} = 0.375 \text{ or } 0.9}$	1.5 or Calculated Value	2.65 or Calculated Value	1
<u>SSL, May 1996 or</u> Equation J&E 17, Appendix C, Table L	<u>SSL, May 1996 or</u> Equation J&E 17, Appendix C, Table L	SSL, May 1996 or Equation J&E 17, Appendix C, Table L For capillary fringe, US EPA, Users Guide 2004	<u>SSL, May 1996 or</u> <u>Field Measurement,</u> <u>Appendix C, Table F</u>	<u>SSL, May 1996 or</u> <u>Field Measurement,</u> <u>Appendix C, Table F</u>	Illinois EPA
cm ³ /cm ³	cm ³ /cm ³	<u>cm³/cm³</u>	g/cm ³	<u>g/cm³</u>	g/cm ³
<u>Water-filled soil</u> porosity	<u>Water-filled porosity</u> <u>for soil in cracks</u>	<u>Water-filled porosity of</u> soil layer <u>i</u>	Dry soil bulk density	Soil particle density	Density of water
$\overline{\Theta}_{\overline{w}}$	<u> 0 w.crack</u>	<u> 0 w.i</u>	$\overline{\Theta}_{\overline{D}}$	$\underline{\theta}_{s,i}$	$\underline{\Theta}_{\underline{w}}$

POLLUTION CONTROL BOARD

NOTICE OF BROROED ANTENIDAENTO

_____ effective _____ (Source: Added at 36 Ill. Reg.

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Section 742. APPENDIX F: Environmental Land Use Control

PREPARED BY:

Name: _____

Address:

RETURN TO:

Name: _____

Address: _____

THE ABOVE SPACE FOR RECORDER'S OFFICE

Model Environmental Land Use Control

THIS ENVIRONMENTAL LAND USE	E CONTROL ("ELUC"), is made this
day of, 20, by	, ("Property Owner") of the real
property located at the common address	("Property").

WHEREAS, 415 ILCS 5/58.17 and 35 Ill. Adm. Code 742 provide for the use of an ELUC as an institutional control in order to impose land use limitations or requirements related to environmental contamination so that persons conducting remediation can obtain a No Further Remediation determination from the Illinois Environmental Protection Agency ("IEPA"). The reason for an ELUC is to ensure protection of human health and the environment. The limitations and requirements contained herein are necessary in order to protect against exposure to contaminated soil, or groundwater, or soil gas both, that may be present on the property as a result of [VARIABLE] activities. Under 35 Ill. Adm. Code 742, the use of risk-based, site-specific remediation objectives may require the use of an ELUC on real property, and the ELUC may apply to certain physical features (e.g., engineered barriers, indoor inhalation building control technologies, monitoring wells, caps, etc.).

WHEREAS, _____ [the party performing remediation] intends to request risk-based, site specific soil, and groundwater, or soil gas remediation objectives from IEPA under 35 Ill. Adm. Code 742 to obtain risk-based closure of the site, identified by Bureau of Land [10-digit LPC or Identification number] ______, utilizing an ELUC.

NOW, THEREFORE, the recitals set forth above are incorporated by reference as if fully set forth herein, and the Property Owner agrees as follows:

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

Date:

By:

Director

Section One. Property Owner does hereby establish an ELUC on the real estate, situated in the County of ______, State of Illinois and further described in Exhibit A attached hereto and incorporated herein by reference (the "Property").

Attached as Exhibit B are site maps that show the legal boundary of the Property, any physical features to which the ELUC applies, the horizontal and vertical extent of the contaminants of concern above the applicable remediation objectives for soil, or groundwater, or <u>soil gas both</u>, and the nature, location of the source, and direction of movement of the contaminants of concern, as required under 35 Ill. Adm. Code 742.

Section Two. Property Owner represents and warrants **he/she** is the current owner of the Property and has the authority to record this ELUC on the chain of title for the Property with the Office of the Recorder or Registrar of Titles in _____ County, Illinois.

Section Three. The Property Owner hereby agrees, for **himself/herself**, and **his/her** heirs, grantees, successors, assigns, transferees and any other owner, occupant, lessee, possessor or user of the Property or the holder of any portion thereof or interest therein, that **[INSERT RESTRICTION** (e.g. the groundwater under the Property shall not be used as a potable supply of water, and any contaminated groundwater or soil that is removed, excavated, or disturbed from the Property described in Exhibit A herein must be handled in accordance with all applicable laws and regulations)].

Section Four. This ELUC is binding on the Property Owner, **his/her** heirs, grantees, successors, assigns, transferees and any other owner, occupant, lessee, possessor or user of the Property or the holder of any portion thereof or interest therein. This ELUC shall apply in perpetuity against the Property and shall not be released until the IEPA determines there is no longer a need for this ELUC as an institutional control; until the IEPA, upon written request, issues to the site that received the no further remediation determination a new no further remediation determination (s) or requirement(s); the new no further remediation determination is filed on the chain of title of the site subject to the no further remediation determination; and until a release or modification of the land use limitation or requirement is filed on the chain of title for the Property.

Section Five. Information regarding the remediation performed on the Property may be obtained from the IEPA through a request under the Freedom of Information Act (5 ILCS 140)

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

and rules promulgated thereunder by providing the IEPA with the [10-digit LPC or identification number] listed above.

Section Six. The effective date of this ELUC shall be the date that it is officially recorded in the chain of title for the Property to which the ELUC applies.

WITNESS the following signatures:

Property Owner(s)

By:		
Its:		

Date:

STATE OF ILLINOIS)	
)	SS:
COUNTY OF)	

I, _______the undersigned, a Notary Public for said County and State, DO HEREBY CERTIFY, that _______ and ______, personally known to me to be the Property Owner(s) of _______, and personally known to me to be the same persons whose names are subscribed to the foregoing instrument, appeared before me this day in person and severally acknowledged that in said capacities they signed and delivered the said instrument as their free and voluntary act for the uses and purposes therein set forth.

Given under my hand and official seal, this _____ day of _____, 20___.

Notary Public

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

 STATE OF ______)
)

 OUNTY OF _____)
 S.S.

I, _____, a notary public, do hereby certify that before me this day in person appeared ______, personally known to me to be the Property Owner(s), of ______, each severally acknowledged that they signed and delivered the foregoing instrument as the Property Owner(s) herein set forth, and as their own free and voluntary act, for the uses and purposes herein set forth.

Given under my hand and seal this _____ day of _____, 20__.

Notary Public

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

PIN NO. XX-XX-XXX-XXX-XXXX (Parcel Index Number)

Exhibit A

The subject property is located in the City of ______, _____, County, State of Illinois, commonly known as ______, ____, Illinois and more particularly described as: LIST THE COMMON ADDRESS; LEGAL DESCRIPTION; AND REAL ESTATE TAX INDEX OR PARCEL # (PURSUANT TO SECTION 742. 1010(D)(2))

POLLUTION CONTROL BOARD

NOTICE OF PROPOSED AMENDMENTS

PIN NO. XX-XX-XXX-XXX-XXXX

Exhibit B

IN ACCORDANCE WITH SECTION 742.1010(<u>d</u>)(D)(8)(A)-(D), PROVIDE ALL THE FOLLOWING ELEMENTS. ATTACH SEPARATE SHEETS, LABELED AS EXHIBIT B, WHERE NECESSARY.

- (A) A scaled map showing the legal boundary of the property to which the ELUC applies.
- (B) Scaled maps showing the horizontal and vertical extent of contaminants of concern above the applicable remediation objectives for soil, and groundwater, and soil gas to which the ELUC applies.
- (C) Scaled maps showing the physical features to which an ELUC applies (e.g., engineered barriers, <u>indoor inhalation building control technologies</u>, monitoring wells, caps, etc.).
- (D) Scaled maps showing the nature, location of the source, and direction of movement of the contaminants of concern.

(Source: Amended at 36 Ill. Reg.____, effective _____)