

ILLINOIS POLLUTION CONTROL BOARD
June 23, 1994

IN THE MATTER OF:)
) R94-7
RCRA UPDATE, USEPA REGULATIONS) (Identical in Substance Rules)
(7-1-93 THROUGH 12-31-93))

Adopted Rule. Final Order.

ORDER OF THE BOARD (by E. Dunham):


Pursuant to Section 22.4(a) of the Environmental Protection Act (Act), the Board adopts amendments to the RCRA hazardous waste (RCRA) regulations.

Section 22.4(a) provides for quick adoption of regulations that are "identical in substance" to federal regulations adopted by U.S. EPA to implement Sections 3001 through 3005 of the Resource Conservation and Recovery Act of 1976 (RCRA, 42 U.S.C. §§ 6921-6925) and that Title VII of the Act and Section 5 of the Administrative Procedure Act (APA) shall not apply. Because this rulemaking is not subject to Section 5 of the APA, it is not subject to first notice or to second notice review by the Joint Committee on Administrative Rules (JCAR). The federal RCRA Subtitle C regulations are found at 40 CFR 260 through 268, 270 through 271, and, more recently, 279.

This order is supported by an opinion adopted on the same day. The Board will file the adopted amendments 30 days after the date of this order. The complete text of the adopted rules follows.

IT IS SO ORDERED.

I, Dorothy M. Gunn, Clerk of the Illinois Pollution Control Board, hereby certify that the above order was adopted on the 23rd day of June, 1994, by a vote of 6-0.


Dorothy M. Gunn, Clerk
Illinois Pollution Control Board

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE G: WASTE DISPOSAL
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER b: PERMITS

PART 703
 RCRA PERMIT PROGRAM

SUBPART A: GENERAL PROVISIONS

Section
 703.100 Scope and Relation to Other Parts
 703.101 Purpose
 703.110 References

SUBPART B: PROHIBITIONS

Section
 703.120 Prohibitions in General
 703.121 RCRA Permits
 703.122 Specific Inclusions in Permit Program
 703.123 Specific Exclusions from Permit Program
 703.124 Discharges of Hazardous Waste
 703.125 Reapplications
 703.126 Initial Applications
 703.127 Federal Permits (Repealed)

SUBPART C: AUTHORIZATION BY RULE AND INTERIM STATUS

Section
 703.140 Purpose and Scope
 703.141 Permits by Rule
 703.150 Application by Existing HWM Facilities and Interim Status
 Qualifications
 703.151 Application by New HWM Facilities
 703.152 Amended Part A Application
 703.153 Qualifying for Interim Status
 703.154 Prohibitions During Interim Status
 703.155 Changes During Interim Status
 703.156 Interim Status Standards
 703.157 Grounds for Termination of Interim Status
 703.158 Permits for Less Than an Entire Facility
 703.159 Closure by Removal
 703.160 Procedures for Closure Determination

SUBPART D: APPLICATIONS

Section
 703.180 Applications in General
 703.181 Contents of Part A
 703.182 Contents of Part B
 703.183 General Information
 703.184 Facility Location Information
 703.185 Groundwater Protection Information
 703.186 Exposure Information
 703.187 Solid Waste Management Units
 703.188 Other Information
 703.200 Specific Information
 703.201 Containers
 703.202 Tank Systems
 703.203 Surface Impoundments
 703.204 Waste Piles
 703.205 Incinerators
 703.206 Land Treatment
 703.207 Landfills
 703.208 Specific Part B Information Requirements for Boilers and

703.209 Industrial Furnaces
 703.210 Miscellaneous Units
 703.211 Process Vents
 703.212 Equipment
 703.212 Drip Pads

SUBPART E: SHORT TERM AND PHASED PERMITS

Section
 703.221 Emergency Permits
 703.222 Incinerator Conditions Prior to Trial Burn
 703.223 Incinerator Conditions During Trial Burn
 703.224 Incinerator Conditions After Trial Burn
 703.225 Trial Burns for Existing Incinerators
 703.230 Land Treatment Demonstration
 703.231 Research, Development and Demonstration Permits
 703.232 Permits for Boilers and Industrial Furnaces Burning Hazardous Waste

SUBPART F: PERMIT CONDITIONS OR DENIAL

Section
 703.240 Permit Denial
 703.241 Establishing Permit Conditions
 703.242 Noncompliance Pursuant to Emergency Permit
 703.243 Monitoring
 703.244 Notice of Planned Changes
 703.245 Twenty-four Hour Reporting
 703.246 Reporting Requirements
 703.247 Anticipated Noncompliance

SUBPART G: CHANGES TO PERMITS

Section
 703.260 Transfer
 703.270 Modification
 703.271 Causes for Modification
 703.272 Causes for Modification or Reissuance
 703.273 Facility Siting
 703.280 Permit Modification at the Request of the Permittee
 703.281 Class 1 Modifications
 703.282 Class 2 Modifications
 703.283 Class 3 Modifications

703.Appendix A Classification of Permit Modifications

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111 $\frac{1}{2}$, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R82-19, 53 PCB 131, at 7 Ill. Reg. 14289, effective October 12, 1983; amended in R83-24 at 8 Ill. Reg. 206, effective December 27, 1983; amended in R84-9 at 9 Ill. Reg. 11899, effective July 24, 1985; amended in R85-22 at 10 Ill. Reg. 1110, effective January 2, 1987; amended in R85-23 at 10 Ill. Reg. 13284, effective July 28, 1986; amended in R86-1 at 10 Ill. Reg. 14093, effective August 12, 1986; amended in R86-19 at 10 Ill. Reg. 20702, effective December 2, 1986; amended in R86-28 at 11 Ill. Reg. 6121, effective March 24, 1987; amended in R86-46 at 11 Ill. Reg. 13543, effective August 4, 1987; amended in R87-5 at 11 Ill. Reg. 19383, effective November 12, 1987; amended in R87-26 at 12 Ill. Reg. 2584, effective January 15, 1988; amended in R87-39 at 12 Ill. Reg. 13069, effective July 29, 1988; amended in R88-16 at 13 Ill. Reg. 447, effective December 27, 1988; amended in R89-1 at 13 Ill. Reg. 18477, effective November 13, 1989; amended in R89-9 at 14 Ill. Reg. 6278, effective April 16, 1990; amended in R90-2 at 14 Ill. Reg. 14492, effective August 22, 1990; amended in R90-11 at 15 Ill. Reg. 9616, effective

June 17, 1991; amended in R91-1 at 15 Ill. Reg. 14554, effective September 30, 1991; amended in R91-13 at 16 Ill. Reg. 9767, effective June 9, 1992; amended in R92-10 at 17 Ill. Reg. 5774, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20794, effective November 22, 1993; amended in R93-16 at 18 Ill. Reg. 6898, effective April 26, 1994; amended in R94-7 at _____ Ill. Reg. _____, effective _____.

SUBPART A: GENERAL PROVISIONS

Section 703.110 References

- a) When used in this Part the following publications are incorporated by reference:

~~"Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW-846 (Second Edition, 1982 as amended by Update I (April, 1984) and Update II (April, 1985)). The second edition of SW-846 and Updates I and II are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20401 (202) 782-3238, on a subscription basis. (See 35 Ill. Adm. Code 720.111.)~~

- b) The references listed in paragraph subsection (a) above are also available for inspection at the offices of the Pollution Control Board. This incorporation includes no later amendments or editions.

(BOARD NOTE: Derived from 40 CFR 270.6 (1992), as amended at 58 Fed. Reg. 46051 (Aug. 31, 1993).

(Source: Amended at 18 Ill. Reg. _____, effective _____)

SUBPART D: APPLICATIONS

Section 703.205 Incinerators

For facilities that incinerate hazardous waste, except as 35 Ill. Adm. Code 724.440 provides otherwise, the applicant must fulfill the requirements of paragraph subsections (a), (b) or (c) below in completing the Part B application:

- a) When seeking exemption under 35 Ill. Adm. Code 724.440(b) or (c) (ignitable, corrosive or reactive wastes only):
- 1) Documentation that the waste is listed as a hazardous waste in 35 Ill. Adm. Code 721____Subpart D solely because it is ignitable (Hazard Code I), corrosive (Hazard Code C), or both; or
 - 2) Documentation that the waste is listed as a hazardous waste in 35 Ill. Adm. Code 721____Subpart D solely because it is reactive (Hazard Code R) for characteristics other than those listed in 35 Ill. Adm. Code 721.123(a)(4) and (a)(5), and will not be burned when other hazardous wastes are present in the combustion zone; or
 - 3) Documentation that the waste is a hazardous waste solely because it possesses the characteristic of ignitability or corrosivity, or both, as determined by the tests for

characteristics of hazardous wastes under 35 Ill. Adm. Code 721~~7~~ Subpart C; or

- 4) Documentation that the waste is a hazardous waste solely because it possesses the reactivity characteristics listed in 35 Ill. Adm. Code 721.123 (a)(1)~~7~~ ~~(2)~~, through (a)(3), or (a)(6), ~~(7)~~ ~~or through (a)(8)~~, and that it will not be burned when other hazardous wastes are present in the combustion zone; or
- b) Submit a trial burn plan or the results of a trial burn, including all required determinations, in accordance with Section 703.222 et seq.; or
- c) In lieu of a trial burn, the applicant may submit the following information:
 - 1) An analysis of each waste or mixture of wastes to be burned including:
 - A) Heat value of the waste in the form and composition in which it will be burned;
 - B) Viscosity (if applicable), or description of physical form of the waste;
 - C) An identification of any hazardous organic constituents listed in 35 Ill. Adm. Code 721~~7~~ Appendix H, ~~which that~~ are present in the waste to be burned, except that the applicant need not analyze for constituents listed in 35 Ill. Adm. Code 721~~7~~ Appendix H ~~which that~~ would reasonably not be expected to be found in the waste. The constituents excluded from analysis must be identified and the basis for their exclusion stated. The waste analysis must rely on analytical techniques specified in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as ~~incorporated by reference, see at 35 Ill. Adm. Code 720.111 and Section 703.110 and referenced in 35 Ill. Adm. Code 721, Appendix G~~, or their equivalent;
 - D) An approximate quantification of the hazardous constituents identified in the waste, within the precision produced by the analytical methods specified in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as ~~incorporated by reference, see at 35 Ill. Adm. Code 720.111 and Section 703.110~~;
 - E) A quantification of those hazardous constituents in the waste ~~which that~~ may be designated as POHCs based on data submitted from other trial or operational burns ~~which that~~ demonstrate compliance with the performance standard in 35 Ill. Adm. Code 724.443;
 - 2) A detailed engineering description of the incinerator, including:
 - A) Manufacturer's name and model number of incinerator;
 - B) Type of incinerator;

- C) Linear dimension of incinerator unit including cross sectional area of combustion chamber;
 - D) Description of auxiliary fuel system (type/feed);
 - E) Capacity of prime mover;
 - F) Description of automatic waste feed cutoff system(s);
 - G) Stack gas monitoring and pollution control monitoring system;
 - H) Nozzle and burner design;
 - I) Construction materials;
 - J) Location and description of temperature, pressure and flow indicating devices and control devices;
- 3) A description and analysis of the waste to be burned compared with the waste for which data from operational or trial burns are provided to support the contention that a trial burn is not needed. The data should include those items listed in paragraph subsection (c)(1) above. This analysis should specify the POHCs ~~which~~that the applicant has identified in the waste for which a permit is sought, and any differences from the POHCs in the waste for which burn data are provided;
- 4) The design and operating conditions of the incinerator unit to be used, compared with that for which comparative burn data are available;
- 5) A description of the results submitted from any previously conducted trial burn(s) including:
- A) Sampling and analysis techniques used to calculate performance standards in 35 Ill. Adm. Code 724.443;
 - B) Methods and results of monitoring temperatures, waste feed rates, carbon monoxide and an appropriate indicator of combustion gas velocity (including a statement concerning the precision and accuracy of this measurement);
 - C) The certification and results required by paragraph subsection (b) above;
- 6) The expected incinerator operation information to demonstrate compliance with 35 Ill. Adm. Code 724.443 and 724.445 including:
- A) Expected carbon monoxide (CO) level in the stack exhaust gas;
 - B) Waste feed rate;
 - C) Combustion zone temperature;
 - D) Indication of combustion gas velocity;
 - E) Expected stack gas volume, flow rate and temperature;

- F) Computed residence time for waste in the combustion zone;
 - G) Expected hydrochloric acid removal efficiency;
 - H) Expected fugitive emissions and their control procedures;
 - I) Proposed waste feed cut-off limits based on the identified significant operating parameters;
- 7) The Agency may, pursuant to 35 Ill. Adm. Code 705.122, request such additional information as may be necessary for the Agency to determine whether the incinerator meets the requirements of 35 Ill. Adm. Code 724.443 Subpart 0, and what conditions are required by that Subpart and Section 39(d) of the Environmental Protection Act;
 - 8) Waste analysis data, including that submitted in ~~paragraph~~ subsection (c)(1) above, sufficient to allow the Agency to specify as permit Principal Organic Hazardous Constituents (permit POHCs) those constituents for which destruction and removal efficiencies will be required;
- d) The Agency shall approve a permit application without a trial burn if it finds that:
 - 1) The wastes are sufficiently similar; and
 - 2) The incinerator units are sufficiently similar, and the data from other trial burns are adequate to specify (under 35 Ill. Adm. Code 724.445) operating conditions that will ensure that the performance standards in 35 Ill. Adm. Code 724.443 will be met by the incinerator.

(BOARD NOTE: Derived from 40 CFR 270.19 (1992), as amended at 58 Fed. Reg. 46051 (Aug. 31, 1993). See 40 CFR 122.25(b)(5).)

(Source: Amended at 18 Ill. Reg. _____, effective _____)

SUBPART E: SHORT TERM AND PHASED PERMITS

Section 703.223 Incinerator Conditions During Trial Burn

For the purposes of determining feasibility of compliance with the performance standards of 35 Ill. Adm. Code 724.443 and of determining adequate operating conditions under 35 Ill. Adm. Code 724.445, the Agency shall establish conditions in the permit to a new hazardous waste incinerator to be effective during the trial burn.

- a) Applicants shall propose a trial burn plan, prepared under subsection (b) below with Part B of the permit application;
- b) The trial burn plan must include the following information:
 - 1) An analysis of each waste or mixture of wastes to be burned ~~which~~ that includes:
 - A) Heat value of the waste in the form and composition in

which it will be burned;

- B) Viscosity (if applicable), or description of physical form of the waste;
 - C) An identification of any hazardous organic constituents listed in 35 Ill. Adm. Code 721. Appendix H, ~~which that~~ are present in the waste to be burned, ~~except that the applicant need not analyze for constituents listed in 35 Ill. Adm. Code 721. Appendix H which that~~ would reasonably not be expected to be found in the waste. The constituents excluded from analysis must be identified, and the basis for their exclusion stated. The waste analysis must rely on analytical techniques specified in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, ~~as~~ ~~incorporated by reference, see at 35 Ill. Adm. Code 720.111 and Section 703.110~~, or their equivalent;
 - D) An approximate quantification of the hazardous constituents identified in the waste, within the precision produced by the analytical methods specified in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, ~~as~~ ~~incorporated by reference, see at 35 Ill. Adm. Code 720.111 and Section 703.110~~, or their equivalent;
- 2) A detailed engineering description of the incinerator for which the permit is sought including:
- A) Manufacturer's name and model number of incinerator (if available);
 - B) Type of incinerator;
 - C) Linear dimensions of the incinerator unit including the cross sectional area of combustion chamber;
 - D) Description of the auxiliary fuel system (type/feed);
 - E) Capacity of prime mover;
 - F) Description of automatic waste feed cut-off system(s);
 - G) Stack gas monitoring and pollution control equipment;
 - H) Nozzle and burner design;
 - I) Construction materials;
 - J) Location and description of temperature, pressure and flow indicating and control devices;
- 3) A detailed description of sampling and monitoring procedures, including sampling and monitoring locations in the system, the equipment to be used, sampling and monitoring frequency and planned analytical procedures for sample analysis;
- 4) A detailed test schedule for each waste for which the trial

burn is planned including date(s), duration, quantity of waste to be burned and other factors relevant to the Agency's decision under subsection (e) below;

- 5) A detailed test protocol, including, for each waste identified, the ranges of temperature, waste feed rate, combustion gas velocity, use of auxiliary fuel and any other relevant parameters that will be varied to affect the destruction and removal efficiency of the incinerator;
 - 6) A description of, and planned operating conditions for, any emission control equipment ~~which~~that will be used;
 - 7) Procedures for rapidly stopping waste feed, shutting down the incinerator and controlling emissions in the event of an equipment malfunction;
 - 8) Such other information as the Agency reasonably finds necessary to determine whether to approve the trial burn plan in light of the purposes of this ~~paragraph~~subsection and the criteria in subsection (e) below. Such information must be requested by the Agency pursuant to 35 Ill. Adm. Code 705.123.
- c) The Agency, in reviewing the trial burn plan, shall evaluate the sufficiency of the information provided and shall require the applicant, pursuant to 35 Ill. Adm. Code 705.123, to supplement this information, if necessary, to achieve the purposes of this ~~paragraph~~subsection;
- d) Based on the waste analysis data in the trial burn plan, the Agency shall specify as trial Principal Organic Hazardous Constituents (POHCs), those constituents for which destruction and removal efficiencies must be calculated during the trial burn. These trial POHCs must be specified by the Agency based on its estimate of the difficulty of incineration of the constituents identified in the waste analysis, their concentration or mass in the waste feed, and, for wastes listed in 35 Ill. Adm. Code 721.Subpart D, the hazardous waste organic constituent of constituents identified in 35 Ill. Adm. Code 721.Appendix G or H as the basis for listing;
- e) The Agency shall approve a trial burn plan if it finds that:
- 1) The trial burn is likely to determine whether the incinerator performance standard required by 35 Ill. Adm. Code 724.443 can be met;
 - 2) The trial burn itself will not present an imminent hazard to human health or the environment;
 - 3) The trial burn will help the Agency to determine operating requirements to be specified under 35 Ill. Adm. Code 724.445; and
 - 4) The information sought in subsections (e)(1) and (e)(3) above cannot reasonably be developed through other means;
- f) During each approved trial burn (or as soon after the burn as is practicable), the applicant shall make the following determinations:

- 1) A quantitative analysis of the trial POHCs, in the waste feed to the incinerator;
 - 2) A quantitative analysis of the exhaust gas for the concentration and mass emissions of the trial POHC's, molecular oxygen and hydrogen chloride (HCl);
 - 3) A quantitative analysis of the scrubber water (if any), ash residues and other residues, for the purpose of estimating the fate of the trial POHCs;
 - 4) A computation of destruction and removal efficiency (DRE), in accordance with the DRE formula specified in 35 Ill. Adm. Code 724.443(a);
 - 5) If the HCl (hydrogen chloride) emission rate exceeds 1.8 kilograms of HCl per hour (4 pounds per hour), a computation of HCl removal efficiency in accordance with 35 Ill. Adm. Code 724.443(b);
 - 6) A computation of particulate emissions, in accordance with 35 Ill. Adm. Code 724.443(c);
 - 7) An identification of sources of fugitive emissions and their means of control;
 - 8) A measurement of average, maximum and minimum temperatures and combustion gas velocity;
 - 9) A continuous measurement of carbon monoxide (CO) in the exhaust gas;
 - 10) Such other information as the Agency specifies as necessary to ensure that the trial burn will determine compliance with the performance standards in 35 Ill. Adm. Code 724.443 and to establish the operating conditions required by 35 Ill. Adm. Code 724.445 as necessary to meet that performance standard.
- g) The applicant shall submit to the Agency a certification that the trial burn has been carried out in accordance with the approved trial burn plan, and shall submit the results of all the determinations required in subsection (f) above. This submission must be made within 90 days of completion of the trial burn, or later if approved by the Agency;
- h) All data collected during any trial burn must be submitted to the Agency following the completion of the trial burn;
- i) All submissions required by this ~~paragraph~~ subsection must be certified on behalf of the applicant by the signature of a person authorized to sign a permit application or a report under 35 Ill. Adm. Code 702.126;
- j) Based on the results of the trial burn, the Agency shall set the operating requirements in the final permit according to 35 Ill. Adm. Code 724.445. The permit modification must proceed as a minor modification according to Section 703.280.

BOARD NOTE: Derived from 40 CFR 270.62(a) (198892), as amended at 538 Fed. Reg. 37934, ~~September 28, 1988~~ 46051 (Aug. 31, 1993).

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 703.232 Permits for Boilers and Industrial Furnaces Burning Hazardous Waste

- a) **General.** Owners and operators of new boilers and industrial furnaces (those not operating under the interim status standards of 35 Ill. Adm. Code 726.203) are subject to subsection (b) through (f) below. Boilers and industrial furnaces operating under the interim status standards of 35 Ill. Adm. Code 726.203 are subject to subsection (g) below.
- b) **Permit operating periods for new boilers and industrial furnaces.** A permit for a new boiler or industrial furnace must specify appropriate conditions for the following operating periods:
 - 1) **Pretrial burn period.** For the period beginning with initial introduction of hazardous waste and ending with initiation of the trial burn, and only for the minimum time required to bring the boiler or industrial furnace to a point of operation readiness to conduct a trial burn, not to exceed 720 hours operating time when burning hazardous waste, the Agency shall establish in the Pretrial Burn Period of the permit conditions, including but not limited to allowable hazardous waste feed rates and operating conditions. The Agency shall extend the duration of this operational period once, for up to 720 additional hours, at the request of the applicant when good cause is shown. The permit must be modified to reflect the extension according to Section 703.280 et seq.
 - A) Applicants must submit a statement, with part B of the permit application, that suggests the conditions necessary to operate in compliance with the standards of 35 Ill. Adm. Code 726.204 through 726.207 during this period. This statement should include, at a minimum, restrictions on the applicable operating requirements identified in 35 Ill. Adm. Code 726.202 (e).
 - B) The Agency shall review this statement and any other relevant information submitted with part B of the permit application and specify requirements for this period sufficient to meet the performance standards of 35 Ill. Adm. Code 726.204 through 726.207 based on the Agency's engineering judgment.
 - 2) **Trial burn period.** For the duration of the trial burn, the Agency shall establish conditions in the permit for the purposes of determining feasibility of compliance with the performance standards of 35 Ill. Adm. Code 726.204 through 726.207 and determining adequate operating conditions under 35 Ill. Adm. Code 726.202(e). Applicants shall propose a trial burn plan, prepared under subsection (c) below, to be submitted with part B of the permit application.
 - 3) **Post-trial burn period.**
 - A) For the period immediately following completion of the trial burn, and only for the minimum period sufficient to allow sample analysis, data computation and submission of the trial burn results by the applicant,

and review of the trial burn results and modification of the facility permit by the Agency to reflect the trial burn results, the Agency shall establish the operating requirements most likely to ensure compliance with the performance standards of 35 Ill. Adm. Code 726.204 through 726.207 based on the Agency's engineering judgment.

- B) Applicants shall submit a statement, with part B of the application, that identifies the conditions necessary to operate during this period in compliance with the performance standards of 35 Ill. Adm. Code 726.204 through 726.207. This statement should include, at a minimum, restrictions on the operating requirements provided by 35 Ill. Adm. Code 726.202 (e).
 - C) The Agency shall review this statement and any other relevant information submitted with part B of the permit application and specify requirements of this period sufficient to meet the performance standards of 35 Ill. Adm. Code 726.204 through 726.207 based on the Agency's engineering judgment.
- 4) Final permit period. For the final period of operation the Agency shall develop operating requirements in conformance with 35 Ill. Adm. Code 726.202-(e) that reflect conditions in the trial burn plan and are likely to ensure compliance with the performance standards of 35 Ill. Adm. Code 726.204 through 726.207. Based on the trial burn results, the Agency shall make any necessary modifications to the operating requirements to ensure compliance with the performance standards. The permit modification must proceed according to Section 703.280 et seq.
- c) Requirements for trial burn plans. The trial burn plan must include the following information. The Agency, in reviewing the trial burn plan, shall evaluate the sufficiency of the information provided and may require the applicant to supplement this information, if necessary, to achieve the purposes of this subsection.
- 1) An analysis of each feed stream, including hazardous waste, other fuels, and industrial furnace feed stocks, as fired, that includes:
 - A) Heating value, levels of antimony, arsenic, barium, beryllium, cadmium, chromium, lead, mercury, silver, thallium, total chlorine/chloride and ash;
 - B) Viscosity or description of the physical form of the feed stream;
 - 2) An analysis of each hazardous waste, as fired, including:
 - A) An identification of any hazardous organic constituents listed in 35 Ill. Adm. Code 721. Appendix H that are present in the feed stream, except that the applicant need not analyze for constituents listed in ~~Appendix H which that~~ would reasonably not be expected to be found in the hazardous waste. The constituents excluded from analysis must be identified as the basis

for this exclusion explained. The analysis must be conducted in accordance with analytical techniques specified in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as ~~incorporated by reference, see at 35 Ill. Adm. Code 720.111 and Section 703.110, or their equivalent.~~

- B) An approximate quantification of the hazardous constituents identified in the hazardous waste, within the precision produced by the analytical methods specified in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference at 35 Ill. Adm. Code 720.111 and Section 703.110, or other equivalent.
 - C) A description of blending procedures, if applicable, prior to firing the hazardous waste, including a detailed analysis of the hazardous waste prior to blending, an analysis of the material with which the hazardous waste prior to blending, an analysis of the material with which the hazardous waste is blended, and blending ratios.
- 3) A detailed engineering description of the boiler or industrial furnace, including:
- A) Manufacturer's name and model number of the boiler or industrial furnace;
 - B) Type of boiler or industrial furnace;
 - C) Maximum design capacity in appropriate units;
 - D) Description of the Feed system for the hazardous waste, and as appropriate, other fuels and industrial furnace feedstocks;
 - E) Capacity of hazardous waste feed system;
 - F) Description of automatic hazardous waste feed cutoff system(s); and
 - G) Description of any pollution control system; and
 - H) Description of stack gas monitoring and any pollution control monitoring systems.
- 4) A detailed description of sampling and monitoring procedures including sampling and monitoring locations in the system, the equipment to be used, sampling and monitoring frequency and sample analysis.
- 5) A detailed test schedule for each hazardous waste for which the trial burn is planned, including date(s), duration, quantity of hazardous waste to be burned, and other factors relevant to the Agency's decision under subsection (b)(2) above.
- 6) A detailed test protocol, including, for each hazardous waste identified, the ranges of hazardous waste feed rate,

and, as appropriate, the feed rates of other fuels and industrial furnace feedstocks, and any other relevant parameters that may affect the ability of the boiler or industrial furnace to meet the performance standards in 35 Ill. Adm. Code 726.204 through 726.207.

- 7) A description of and planned operating conditions for any emission control equipment that will be used.
 - 8) Procedures for rapidly stopping ;the hazardous waste feed and controlling emissions in the event of an equipment malfunction.
 - 9) Such other information as the Agency finds necessary to determine whether to approve the trial burn plan in light of the purposes of this subsection and the criteria in subsection (b)(2) above.
- d) Trial burn procedures.
- 1) A trial burn must be conducted to demonstrate conformance with the standards of 35 Ill. Adm. Code 726.104 through 726.107.
 - 2) The Agency shall approve a trial burn plan if the Agency finds that:
 - A) The trial burn is likely to determine whether the boiler or industrial furnace can meet the performance standards of 35 Ill. Adm. Code 726.104 through 726.107.
 - B) The trial burn itself will not present an imminent hazard to human health and the environment;
 - C) The trial burn will help the Agency to determine operating requirements to be specified under 35 Ill. Adm. Code 726.102-(e); and
 - D) The information sought in the trial burn cannot reasonably be developed through other means.
 - 3) The applicant shall submit to the Agency a certification that the trial burn has been carried out in accordance with the approved trial burn plan, and submit the results of all the determinations required in subsection (c) above. The Agency shall, in the trial burn plan, require that the submission be made within 90 days after completion of the trial burn, or later if the Agency determines that a later date is acceptable.
 - 4) All data collected during any trial burn must be submitted to the Agency following completion of the trial burn.
 - 5) All submissions required by this subsection must be certified on behalf of the applicant by the signature of a person authorized to sign a permit application or a report under 35 Ill. Adm. Code 702.126.
- e) Special procedures for DRE trial burns. When a DRE trial burn is required under 35 Ill. Adm. Code 726.104, the Agency shall specify (based on the hazardous waste analysis data and other information

in the trial burn plan) as trial Principal Organic Hazardous Constituents (POHCs) those compounds for which destruction and removal efficiencies must be calculated during the trial burn. These trial POHCs will be specified by the Agency based on information including the Agency's estimate of the difficulty of destroying the constituents identified in the hazardous waste analysis, their concentrations or mass in the hazardous waste feed, and, for hazardous waste containing or derived from wastes listed in 35 Ill. Adm. Code 721.Subpart D, the hazardous waste organic constituent(s) identified in 35 Ill. Adm. Code 721.Appendix G as the basis for listing.

- f) Determinations based on trial burn. During each approved trial burn (or as soon after the burn as is practicable), the applicant shall make the following determinations:
- 1) A quantitative analysis of the levels of antimony, arsenic, barium, beryllium, cadmium, chromium, lead, mercury, thallium, silver, and chlorine/chloride, in the feed streams (hazardous waste, other fuels, and industrial furnace feedstocks);
 - 2) When a DRE trial burn is required under 35 Ill. Adm. Code 726.204-(a):
 - A) A quantitative analysis of the trial POHCs in the hazardous waste feed;
 - B) A quantitative analysis of the stack gas for the concentration and mass emissions of the trial POHCs; and
 - C) A computation of (DRE), in accordance with the DRE formula specified in 35 Ill. Adm. Code 726.204-(a).
 - 3) When a trial burn for chlorinated dioxins and furans is required under 35 Ill. Adm. Code 726.204-(e), a quantitative analysis of the stack gas for the concentration and mass emission rate of the 2-,3-,7-,8-chlorinated tetra-octa congeners of chlorinated dibenzo-p-dioxins and furans, and a computation showing conformance with the emission standard.
 - 4) When a trial burn for PM, metals, or HCl/Chlorine gas is required under 35 Ill. Adm. Code 726.205, 726.206-(c) or (d) or 726.207-(b)-(2) or (c), a quantitative analysis of the stack gas for the concentrations and mass emissions of PM, metals, or HCl and chlorine gas and computations showing conformance with the applicable emission performance standards;
 - 5) When a trial burn for DRE, metals, and HCl/Chlorine gas is required under 35 Ill. Adm. Code 726.204-(a), 726.206-(c) or (d), or 726.207-(b)-(2) or (c), a quantitative analysis of the scrubber water (if any), ash residues, other residues, and products for the purpose of estimating the fate of the trial POHCs, metals, and chlorine/chloride;
 - 6) An identification of sources of fugitive emissions and their means of control;
 - 7) A continuous measurement of carbon monoxide (CO), oxygen, and where required, hydrocarbons (HC), in the stack gas; and

- 8) Such other information as the Agency specifies as necessary to ensure that the trial burn will determine compliance with the performance standards 35 Ill. Adm. Code 726.204 through 726.207 and to establish the operating conditions required by 35 Ill. Adm. Code 726.204 through 726.207 and of determining adequate operating conditions under 35 Ill. Adm. Code 726.203, and to establish the operating conditions required by 35 Ill. Adm. Code 726.202(e) as necessary to meet those performance standards.
- g) Interim status boilers and industrial furnaces. for the purpose of determining feasibility of compliance with the performance standards of 35 Ill. Adm. Code 726.204 through 726.207 and of determining adequate operating conditions under 35 Ill. Adm. Code 726.203, applicants owning or operating existing boilers or industrial furnaces operated under the interim status standards of 35 Ill. Adm. Code 726.203 shall either prepare and submit a trial burn plan and perform a trial burn in accordance with the requirements of the Section or submit other information as specified in Section 703.208(a)(6). Applicants ~~whethat~~ submit a trial burn plan and receive approval before submission of the part B permit application shall complete the trial burn and submit the results specified in subsection (f) above, with the part B permit application. If completion of this process conflicts with the date set for submission of the part B application, the applicant shall contact the Agency to establish a later date for submission of the part B application or the trial burn results. If the applicant submits a trial burn plan with part B of the permit application, the trial burn must be conducted and the results submitted within a time period prior to permit issuance to be specified by the Agency.

BOARD NOTE: Derived from 40 CFR 270.66 (1992), as amended at 58 Fed. Reg. 46051 (Aug. 31, 1993).

(Source: Amended at 18 Ill. Reg. _____, effective _____)

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE G: WASTE DISPOSAL
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER c: HAZARDOUS WASTE OPERATING REQUIREMENTS

PART 720
 HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL

SUBPART A: GENERAL PROVISIONS

Section
 720.101 Purpose, Scope and Applicability
 720.102 Availability of Information; Confidentiality of Information
 720.103 Use of Number and Gender

SUBPART B: DEFINITIONS

Section
 720.110 Definitions
 720.111 References

SUBPART C: RULEMAKING PETITIONS AND OTHER PROCEDURES

Section
 720.120 Rulemaking
 720.121 Alternative Equivalent Testing Methods
 720.122 Waste Delisting

720.130	Procedures for Solid Waste Determinations
720.131	Solid Waste Determinations
720.132	Boiler Determinations
720.133	Procedures for Determinations
720.140	Additional regulation of certain hazardous waste Recycling Activities on a case-by-case Basis
720.141	Procedures for case-by-case regulation of hazardous waste Recycling Activities

720.Appendix A Overview of 40 CFR, Subtitle C Regulations

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111½, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R81-22, 43 PCB 427, at 5 Ill. Reg. 9781, effective as noted in 35 Ill. Adm. Code 700.106; amended and codified in R81-22, 45 PCB 317, at 6 Ill. Reg. 4828, effective as noted in 35 Ill. Adm. Code 700.106; amended in R82-19 at 7 Ill. Reg. 14015, effective October 12, 1983; amended in R84-9, 53 PCB 131 at 9 Ill. Reg. 11819, effective July 24, 1985; amended in R85-22 at 10 Ill. Reg. 968, effective January 2, 1986; amended in R86-1 at 10 Ill. Reg. 13998, effective August 12, 1986; amended in R86-19 at 10 Ill. Reg. 20630, effective December 2, 1986; amended in R86-28 at 11 Ill. Reg. 6017, effective March 24, 1987; amended in R86-46 at 11 Ill. Reg. 13435, effective August 4, 1987; amended in R87-5 at 11 Ill. Reg. 19280, effective November 12, 1987; amended in R87-26 at 12 Ill. Reg. 2450, effective January 15, 1988; amended in R87-39 at 12 Ill. Reg. 12999, effective July 29, 1988; amended in R88-16 at 13 Ill. Reg. 362, effective December 27, 1988; amended in R89-1 at 13 Ill. Reg. 18278, effective November 13, 1989; amended in R89-2 at 14 Ill. Reg. 3075, effective February 20, 1990; amended in R89-9 at 14 Ill. Reg. 6225, effective April 16, 1990; amended in R90-10 at 14 Ill. Reg. 16450, effective September 25, 1990; amended in R90-17 at 15 Ill. Reg. 7934, effective May 9, 1991; amended in R90-11 at 15 Ill. Reg. 9323, effective June 17, 1991; amended in R91-1 at 15 Ill. Reg. 14446, effective September 30, 1991; amended in R91-13 at 16 Ill. Reg. 9489, effective June 9, 1992; amended in R92-1 at 16 Ill. Reg. 17636, effective November 6, 1992; amended in R92-10 at 17 Ill. Reg. 5625, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20545, effective November 22, 1993; amended in R93-16 at 18 Ill. Reg. 6720, effective April 26, 1994; amended in R94-7 at _____ Ill. Reg. _____, effective _____.

SUBPART B: DEFINITIONS

Section 720.111 References

a) The following publications are incorporated by reference:

ANSI. Available from the American National Standards Institute, 1430 Broadway, New York, New York 10018, (212) 354-3300:

ANSI B31.3 and B31.4. See ASME/ANSI B31.3 and B31.4

ACI. Available from the American Concrete Institute, Box 19150, Redford Station, Detroit, Michigan 48219:

ACI 318-83: "Building Code Requirements for Reinforced Concrete", adopted September, 1983.

API. Available from the American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005, (202) 682-8000:

"Guide for Inspection of Refinery Equipment, Chapter XIII, Atmospheric and Low Pressure Storage Tanks," 4th Edition, 1981, reaffirmed December, 1987.

"Cathodic Protection of Underground Petroleum Storage Tanks and Piping Systems," API Recommended Practice 1632, Second Edition, December, 1987.

"Installation of Underground Petroleum Storage Systems," API Recommended Practice 1615, Fourth Edition, November, 1987.

APTI. Available from the Air and Waste Management Association, Box 2861, Pittsburgh, PA 15230, (412) 232-3444:

APTI Course 415: Control of Gaseous Emissions, U.S. EPA Publication EPA-450/2-81-005, December, 1981.

ASME. Available from the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017, (212) 705-7722:

"Chemical Plant and Petroleum Refinery Piping", ASME/ANSI B31.3-1987, as supplemented by B31.3a-1988 and B31.3b-1988. Also available from ANSI.

"Liquid Transportation Systems for Hydrocarbons, Liquid Petroleum Gas, Anhydrous Ammonia, and Alcohols", ASME/ANSI B31.4-1986, as supplemented by B31.4a-1987. Also available from ANSI.

ASTM. Available from American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103, (215) 299-5400:

ASTM C94-90, Standard Specification for Ready-Mixed Concrete, approved March 30, 1990.

ASTM D88-87, Standard Test Method for Saybolt Viscosity, April 24, 1981, reapproved January, 1987.

ASTM D93-85, Standard Test Methods for Flash Point by Pensky-Martens Closed Tester, approved October 25, 1985.

ASTM D1946-90, Standard Practice for Analysis of Reformed Gas by Gas Chromatography, Approved March 30, 1990.

ASTM D2161-87, Standard Practice for Conversion of Kinematic Viscosity to Saybolt Universal or to Saybolt Furol Viscosity, March 27, 1987.

ASTM D2267-88, Standard Test Method for Aromatics in Light Naphthas and Aviation Gasolines by Gas Chromatography, approved November 17, 1988.

ASTM D2382-88, Standard Test Method for Heat of Combustion of Hydrocarbon Fuels by Bomb Calorimeter (High Precision Method), approved October 31, 1988.

ASTM D2879-86, Standard Test Method for Vapor Pressure-Temperature Relationship and Initial Decomposition Temperature of Liquids by Isoteniscope, approved October 31, 1986.

ASTM D3828-87, Standard Test Methods for Flash Point of Liquids by Setaflash Closed Tester, approved December 14, 1988.

ASTM E168-88, Standard Practices for General Techniques of Infrared Quantitative Analysis, approved May 27, 1988.

ASTM E169-87, Standard Practices for General Techniques of Ultraviolet-Visible Quantitative Analysis, approved February 1, 1987.

ASTM E260-85, Standard Practice for Packed Column Gas Chromatography, approved June 28, 1985.

ASTM E926-88 C, Standard Test Methods for Preparing Refuse-Derived Fuel (RDF) Samples for Analysis of Metals, Bomb-Acid Digestion Method, approved March 25, 1988.

ASTM Method G21-70 (1984a) -- Standard Practice for Determining Resistance of Synthetic Polymer Materials to Fungi

ASTM Method G22-76 (1984b) -- Standard Practice for Determining Resistance of Plastics to Bacteria.

GPO. Available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402, (202) 783-3238:

Standard Industrial Classification Manual (1972), and 1977 Supplement, republished in 1983

"Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," U.S. EPA Publication number SW-846 (Third Edition, September 1986), as amended by Update I (July 1992) (Document Number 955-001-00000-1).

NACE. Available from the National Association of Corrosion Engineers, 1400 South Creek Dr., Houston, TX 77084, (713) 492-0535:

"Control of External Corrosion on Metallic Buried, Partially Buried, or Submerged Liquid Storage Systems", NACE Recommended Practice RP0285-85, approved March, 1985.

NFPA. Available from the National Fire Protection Association, Batterymarch Park, Boston, MA 02269, (617) 770-3000 or (800) 344-3555:

"Flammable and Combustible Liquids Code" NFPA 30, issued July 17, 1987. Also available from ANSI.

NTIS. Available from the U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal

Road, Springfield, VA 22161, (703) 487-4600:

"Generic Quality Assurance Project Plan for Land Disposal Restrictions Program", EPA/530-SW-87-011, March 15, 1987. (Document number PB 88-170766.)

"Guidance on Air Quality Models", Revised 1986. (Document number PB86-245-248 (Guideline) and PB88-150-958 (Supplement)).

"Methods for Chemical Analysis of Water and Wastes", Third Edition, March, 1983. (Document number PB 84-128677).

"Methods Manual for Compliance with BIF Regulations", December, 1990. (Document number PB91-120-006).

"Petitions to Delist Hazardous Wastes -- A Guidance Manual", EPA/530-SW-85-003, April, 1985. (Document Number PB 85-194488).

"Procedures Manual for Ground Water Monitoring at Solid Waste Disposal Facilities", EPA-530/SW-611, 1977. (Document number PB 84-174820).

"Screening Procedures for Estimating the Air Quality Impact of Stationary Sources", ~~August~~ October, 1988 92, ~~(Document number PB89-159296)~~ EPA-450/R-92-019.

~~"Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication number SW-846 (Second Edition, 1982 as amended by Update I (April, 1984) and Update II (April, 1985)) (Document number PB 87-120291).~~

~~"Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication number SW-846 (Third Edition, September 1986 (Document number PB88-239223) as amended by Revision I (December 1987) and First Update, January, 1988) (Document Number PB89-148076)).~~

STI. Available from the Steel Tank Institute, 728 Anthony Trail, Northbrook, IL 60062, (312) 498-1980:

"Standard for Dual Wall Underground Steel Storage Tanks" (1986).

U.S. EPA. Available from United States Environmental Protection Agency, Office of Drinking Water, State Programs Division, WH 550 E, Washington, D.C. 20460:

"Technical Assistance Document: Corrosion, Its Detection and Control in Injection Wells", EPA 570/9-87-002, August, 1987.

U.S. EPA. Available from U.S. EPA, Number F-90-WPWF-FFFFF, Room M2427, 401 M Street SW, Washington, D.C. 20460, (202) 475-9327:

"Test Method 8290: Procedures for the Detection and

Measurement of PCDDs and PCDFs", EPA/530-SW-91-019
(January, 1991)

U.S. EPA. Available from Receptor Analysis Branch, U.S. EPA
(MD-14), Research Triangle Park, NC 27711:

"Screening Procedures for Estimating the Air Quality
Impact of Stationary Sources, Revised", October, 1992,
Publication Number EPA-450/R-92-019.

- b) Code of Federal Regulations. Available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20401, (202) 783-3238:

10 CFR 20, Appendix B (1992)

40 CFR 51.100(ii) (1992)

40 CFR 51, Subpart W, as added at 58 Fed. Reg. 38822 (July
20, 1993)

40 CFR 60 (1992~~3~~)

40 CFR 61, Subpart V (1992~~3~~)

40 CFR 136 (1992~~3~~)

40 CFR 142 (1992~~3~~)

40 CFR 220 (1992)

40 CFR 260.20 (1992)

40 CFR 264 (1992)

40 CFR 268.Appendix IX (1992)

40 CFR 302.4, 302.5 and 302.6 (1992)

40 CFR 761 (1991~~3~~)

- c) Federal Statutes

Section 3004 of the Resource Conservation and Recovery Act (42 U.S.C. 6901 et seq.), as amended through December 31, 1987.

- d) This Section incorporates no later editions or amendments.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

SUBPART C: RULEMAKING PETITIONS AND OTHER PROCEDURES

Section 720.122 Waste Delisting

- a) Any person seeking to exclude a waste from a particular generating facility from the lists in 35 Ill. Adm. Code 721.Subpart D may file a petition, as specified in subsection (n) below. The Board will grant the petition if:

- 1) The petitioner demonstrates that the waste produced by a particular generating facility does not meet any of the

criteria under which the waste was listed as a hazardous or acute hazardous waste; and

- 2) If the Board determines that there is a reasonable basis to believe that factors (including additional constituents) other than those for which the waste was listed could cause the waste to be a hazardous waste, that such factors do not warrant retaining the waste as a hazardous waste. A Board determination under the preceding sentence must be made by reliance on, and in a manner consistent with, "Petitions to Delist--A Guidance Manual", incorporated by reference in Section 720.111. A waste ~~which~~that is so excluded, however, still may be a hazardous waste by operation of 35 Ill. Adm. Code 721.Subpart C.
- b) Listed wastes and mixtures. A person may also petition the Board to exclude from 35 Ill. Adm. Code 721.103(a)(2)(B) or (a)(2)(C), a waste ~~which~~that is described in these Sections and is either a waste listed in 35 Ill. Adm. Code 721.Subpart D, or is derived from a waste listed in that Subpart. This exclusion may only be granted for a particular generating, storage, treatment or disposal facility. The petitioner shall make the same demonstration as required by subsection (a) above. Where the waste is a mixture of a solid waste and one or more listed hazardous wastes or is derived from one or more listed hazardous wastes, the demonstration must be made with respect to the waste mixture as a whole; analyses must be conducted for not only those constituents for which the listed waste contained in the mixture was listed as hazardous, but also for factors (including additional constituents) that could cause the waste mixture to be a hazardous waste. A waste ~~which~~that is so excluded may still be a hazardous waste by operation of 35 Ill. Adm. Code 721.Subpart C.
 - c) Ignitable, corrosive, reactive and toxicity characteristic wastes. If the waste is listed in codes "I", "C", "R" or "E" in 35 Ill. Adm. Code 721.Subpart D:
 - 1) The petitioner shall demonstrate that the waste does not exhibit the relevant characteristic for which the waste was listed, as defined in 35 Ill. Adm. Code 721.121, 721.122, 721.123 or 721.124, using any applicable methods prescribed in those Sections. The petitioner shall also show that the waste does not exhibit any of the other characteristics, defined in those Sections, using any applicable methods prescribed in those Sections;
 - 2) Based on a complete petition, the Board will determine, if it has a reasonable basis to believe that factors (including additional constituents) other than those for which the waste was listed could cause the waste to be hazardous waste, that such factors do not warrant retaining the waste as a hazardous waste. A Board determination under the preceding sentence must be made by reliance on, and in a manner consistent with, "Petitions to Delist--A Guidance Manual", incorporated by reference in Section 720.111. A waste ~~which~~that is so excluded, however, may still be a hazardous waste by operation of 35 Ill. Adm. Code 721.Subpart C.
 - d) Toxic waste. If the waste is listed in code "T" in 35 Ill. Adm. Code 721.Subpart D:

- 1) The petitioner shall demonstrate that the waste:
 - A) Does not contain the constituent or constituents (as defined in 35 Ill. Adm. Code 721. Appendix G) that caused U.S. EPA to list the waste, using the appropriate test methods prescribed in ~~35 Ill. Adm. Code 721. Appendix C~~ "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in Section 720.111; or
 - B) Although containing one or more of the hazardous constituents (as defined in 35 Ill. Adm. Code 721. Appendix G) that caused U.S. EPA to list the waste, does not meet the criterion of 35 Ill. Adm. Code 721.111(a)(3) when considering the factors used in 35 Ill. Adm. Code 721.111(a)(3)(A) through (K) under which the waste was listed as hazardous; and
 - 2) Based on a complete petition, the Board will determine, if it has a reasonable basis to believe that factors (including additional constituents) other than those for which the waste was listed could cause the waste to be hazardous waste, that such factors do not warrant retaining the waste as a hazardous waste.
 - 3) The petitioner shall demonstrate that the waste does not exhibit any of the characteristics, defined in 35 Ill. Adm. Code 721.121, 721.122, 721.123 or 721.124, using any applicable methods prescribed in those Sections.
 - 4) A waste ~~which~~that is so excluded, however, may still be a hazardous waste by operation of 35 Ill. Adm. Code 721. Subpart C.
- e) Acute hazardous waste. If the waste is listed with the code "H" in 35 Ill. Adm. Code 721. Subpart D:
- 1) The petitioner shall demonstrate that the waste does not meet the criterion of 35 Ill. Adm. Code 721.111(a)(2); and
 - 2) Based on a complete petition, the Board will determine, if it has a reasonable basis to believe that factors (including additional constituents) other than those for which the waste was listed could cause the waste to be hazardous waste, that such factors do not warrant retaining the waste as a hazardous waste. A Board determination under the preceding sentence must be made by reliance on, and in a manner consistent with, "Petitions to Delist--A Guidance Manual", incorporated by reference in Section 720.111.
 - 3) The petitioner shall demonstrate that the waste does not exhibit any of the characteristics, defined in 35 Ill. Adm. Code 721.121, 721.122, 721.123 or 721.124, using any applicable methods prescribed in those Sections.
 - 4) A waste ~~which~~that is so excluded, however, may still be a hazardous waste by operation of 35 Ill. Adm. Code 721. Subpart C.
- h) Demonstration samples must consist of enough representative samples, but in no case less than four samples, taken over a

period of time sufficient to represent the variability or the uniformity of the waste.

- i) Each petition must include, in addition to the information required by subsection (n) below:
- 1) The name and address of the laboratory facility performing the sampling or tests of the waste;
 - 2) The names and qualifications of the persons sampling and testing the waste;
 - 3) The dates of sampling and testing;
 - 4) The location of the generating facility;
 - 5) A description of the manufacturing processes or other operations and feed materials producing the waste and an assessment of whether such processes, operations or feed materials can or might produce a waste ~~which~~that is not covered by the demonstration;
 - 6) A description of the waste and an estimate of the average and maximum monthly and annual quantities of waste covered by the demonstration;
 - 7) Pertinent data on and discussion of the factors delineated in the respective criterion for listing a hazardous waste, where the demonstration is based on the factors in 35 Ill. Adm. Code 721.111(a)(3);
 - 8) A description of the methodologies and equipment used to obtain the representative samples;
 - 9) A description of the sample handling and preparation techniques, including techniques used for extraction, containerization and preservation of the samples;
 - 10) A description of the tests performed (including results);
 - 11) The names and model numbers of the instruments used in performing the tests; and
 - 12) The following statement signed by the generator or the generator's authorized representative:

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this demonstration and all attached documents, and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.
- j) After receiving a petition, the Board may request any additional information ~~which~~that the Board needs to evaluate the petition.
- k) An exclusion will only apply to the waste generated at the individual facility covered by the demonstration and will not

apply to waste from any other facility.

- 1) The Board will exclude only part of the waste for which the demonstration is submitted if the Board determines that variability of the waste justifies a partial exclusion.

BOARD NOTE: See "Petitions to Delist Hazardous Wastes -- A Guidance Manual", incorporated by reference in Section 720.111.

- m) Delisting of specific wastes from specific sources ~~which that~~ have been adopted by U.S. EPA may be proposed as State regulations ~~which that~~ are identical in substance pursuant to Section 720.120(a).
- n) Delistings ~~which that~~ have not been adopted by U.S. EPA may be proposed to the Board pursuant to a petition for adjusted standard pursuant to 35 Ill. Adm. Code 106.Subpart G. The justification for the adjusted standard is as specified in subsections (a) ~~et seq. through (g) above~~, as applicable to the waste in question. The petition must be clearly labeled as a RCRA delisting adjusted standard petition.
- 1) In accordance with 35 Ill. Adm. Code 106.710, the petitioner shall serve copies of the petition, and any other documents filed with the Board, on U.S. EPA at the following addresses:
- U.S. EPA
Office of Solid Waste and Emergency Response
Washington, D.C. 20460
- U.S. EPA, Region V
230 S. Dearborn Street
Chicago, IL 60604
- 2) The Board will mail copies of all opinions and orders to U.S. EPA at the above addresses.
- 3) In conjunction with the normal updating of the RCRA regulations, the Board will maintain, in 35 Ill. Adm. Code 721.Appendix I, a listing of all adjusted standards granted by the Board.
- o) The Agency may determine in a permit or a letter directed to a generator that, based on 35 Ill. Adm. Code 721, a waste from a particular source is not subject to these regulations. Such a finding is evidence against the Agency in any subsequent proceedings but shall not be conclusive with reference to other persons or the Board.
- p) Any petition to delist directed to the Board or request for determination directed to the Agency must include a showing that the waste will be generated or managed in Illinois.
- q) The Board will not grant any petition ~~which that~~ would render the Illinois RCRA program less stringent than if the decision were made by U.S. EPA.
- r) Delistings apply only within Illinois. Generators shall comply with 35 Ill. Adm. Code 722 for waste ~~which that~~ is hazardous in any state to which it is to be transported.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE G: WASTE DISPOSAL
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER c: HAZARDOUS WASTE OPERATING REQUIREMENTS

PART 721
 IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

SUBPART A: GENERAL PROVISIONS

Section	
721.101	Purpose and Scope
721.102	Definition of Solid Waste
721.103	Definition of Hazardous Waste
721.104	Exclusions
721.105	Special Requirements for Hazardous Waste Generated by Small Quantity Generators
721.106	Requirements for Recyclable Materials
721.107	Residues of Hazardous Waste in Empty Containers
721.108	PCB Wastes Regulated under TSCA

SUBPART B: CRITERIA FOR IDENTIFYING THE CHARACTERISTICS
 OF HAZARDOUS WASTE AND FOR LISTING HAZARDOUS WASTES

Section	
721.110	Criteria for Identifying the Characteristics of Hazardous Waste
721.111	Criteria for Listing Hazardous Waste

SUBPART C: CHARACTERISTICS OF HAZARDOUS WASTE

Section	
721.120	General
721.121	Characteristic of Ignitability
721.122	Characteristic of Corrosivity
721.123	Characteristic of Reactivity
721.124	Toxicity Characteristic

SUBPART D: LISTS OF HAZARDOUS WASTE

Section	
721.130	General
721.131	Hazardous Wastes From Nonspecific Sources
721.132	Hazardous Waste from Specific Sources
721.133	Discarded Commercial Chemical Products, Off-Specification Species, Container Residues and Spill Residues Thereof
721.135	Wood Preserving Wastes

721.Appendix A	Representative Sampling Methods
721.Appendix B	Method 1311 Toxicity Characteristic Leaching Procedure (TCLP)
721.Appendix C	Chemical Analysis Test Methods
Table A	Analytical Characteristics of Organic Chemicals (Repealed)
Table B	Analytical Characteristics of Inorganic Species (Repealed)
Table C	Sample Preparation/Sample Introduction Techniques (Repealed)
721.Appendix G	Basis for Listing Hazardous Wastes
721.Appendix H	Hazardous Constituents
721.Appendix I	Wastes Excluded under Section 720.120 and 720.122
Table A	Wastes Excluded from Non-Specific Sources
Table B	Wastes Excluded from Specific Sources
Table C	Wastes Excluded From Commercial Chemical Products, Off-Specification Species, Container Residues, and Soil Residues Thereof
Table D	Wastes Excluded by Adjusted Standard

- 721.Appendix J Method of Analysis for Chlorinated Dibenzo-p-Dioxins and Dibenzofurans (Repealed)
 721.Appendix Z Table to Section 721.102

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111½, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R81-22, 43 PCB 427, at 5 Ill. Reg. 9781, effective as noted in 35 Ill. Adm. Code 700.106; amended and codified in R81-22, 45 PCB 317, at 6 Ill. Reg. 4828, effective as noted in 35 Ill. Adm. Code 700.106; amended in R82-18, 51 PCB 31, at 7 Ill. Reg. 2518, effective February 22, 1983; amended in R82-19, 53 PCB 131, at 7 Ill. Reg. 13999, effective October 12, 1983; amended in R84-34, 61 PCB 247, at 8 Ill. Reg. 24562, effective December 11, 1984; amended in R84-9, at 9 Ill. Reg. 11834, effective July 24, 1985; amended in R85-22 at 10 Ill. Reg. 998, effective January 2, 1986; amended in R85-2 at 10 Ill. Reg. 8112, effective May 2, 1986; amended in R86-1 at 10 Ill. Reg. 14002, effective August 12, 1986; amended in R86-19 at 10 Ill. Reg. 20647, effective December 2, 1986; amended in R86-28 at 11 Ill. Reg. 6035, effective March 24, 1987; amended in R86-46 at 11 Ill. Reg. 13466, effective August 4, 1987; amended in R87-32 at 11 Ill. Reg. 16698, effective September 30, 1987; amended in R87-5 at 11 Ill. Reg. 19303, effective November 12, 1987; amended in R87-26 at 12 Ill. Reg. 2456, effective January 15, 1988; amended in R87-30 at 12 Ill. Reg. 12070, effective July 12, 1988; amended in R87-39 at 12 Ill. Reg. 13006, effective July 29, 1988; amended in R88-16 at 13 Ill. Reg. 382, effective December 27, 1988; amended in R89-1 at 13 Ill. Reg. 18300, effective November 13, 1989; amended in R90-2 at 14 Ill. Reg. 14401, effective August 22, 1990; amended in R90-10 at 14 Ill. Reg. 16472, effective September 25, 1990; amended in R90-17 at 15 Ill. Reg. 7950, effective May 9, 1991; amended in R90-11 at 15 Ill. Reg. 9332, effective June 17, 1991; amended in R91-1 at 15 Ill. Reg. 14473, effective September 30, 1991; amended in R91-12 at 16 Ill. Reg. 2155, effective January 27, 1992; amended in R91-26 at 16 Ill. Reg. 2600, effective February 3, 1992; amended in R91-13 at 16 Ill. Reg. 9519, effective June 9, 1992; amended in R92-1 at 16 Ill. Reg. 17666, effective November 6, 1992; amended in R92-10 at 17 Ill. Reg. 5650, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20568, effective November 22, 1993; amended in R93-16 at 18 Ill. Reg. 6741, effective April 26, 1994; amended in R94-7 at Ill. Reg. , effective _____.

SUBPART C: CHARACTERISTICS OF HAZARDOUS WASTE

Section 721.122 Characteristic of Corrosivity

- a) A solid waste exhibits the characteristic of corrosivity if a representative sample of the waste has either of the following properties:
- 1) It is aqueous and has a pH less than or equal to 2 or greater than or equal to 12.5, as determined by a pH meter using ~~either an EPA test method or an equivalent test method (35 Ill. Adm. Code 720.121). The EPA test methods for pH are specified as Methods 9040, 9041 or 9045 in "Test Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", incorporated by reference in 35 Ill. Adm. Code 720.111.~~
 - 2) It is a liquid and corrodes steel (SAE 1020) at a rate greater than 6.35 mm (0.250 inch) per year at a test temperature of 55° C (130° F) as determined by the test method specified in NACE (National Association of Corrosion Engineers) Standard TM-01-69 as standardized in "Test

Methods for the Evaluation of Solid Waste, Physical/Chemical Methods", incorporated by reference in 35 Ill. Adm. Code 720.111, ~~or an equivalent test method (35 Ill. Adm. Code 720.121).~~

BOARD NOTE: The corrosivity characteristic determination currently does not apply to non-liquid wastes, as discussed by U.S. EPA at 45 Fed. Reg. 33109, May 19, 1980 and at 55 Fed. Reg. 22549, June 1, 1990.

- b) A solid waste that exhibits the characteristic of corrosivity has the U.S. EPA Hazardous Waste Number of D002.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 721.124 Toxicity Characteristic

- a) A solid waste exhibits the characteristic of toxicity if, using the ~~test methods described in Appendix B or equivalent test methods approved by the Agency under the procedures set forth in Sections 720.120 and 720.121~~ Toxicity Characteristic Leaching Procedure (TCLP), test Method 1311 in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111, the extract from a representative sample of the waste contains any of the contaminants listed in the table in subsection (b) below at a concentration equal to or greater than the respective value given in that table. Where the waste contains less than 0.5 percent filterable solids, the waste itself, after filtering using the methodology outlined in ~~Appendix B Method 1311,~~ is considered to be the extract for the purpose of this Section.

BOARD NOTE: ~~Generators are required to use the TCLP test for the hazardous waste determination under 35 Ill. Adm. Code 722.120 as of September 25, 1990. Provided, however, that, as specified at 55 Fed. Reg. 11850, March 29, 1990, small quantity generators of 100 to 1000 kg/ month, as defined in 35 Ill. Adm. Code 721.105, may continue to use the EP toxicity test until March 29, 1991. The EP toxicity test is Method 1310 in SW 846, "Test Methods for Evaluating Solid Wastes, Physical/Chemical Methods", incorporated by reference in 35 Ill. Adm. Code 720.111. The reference to the "EP toxicity test" in 35 Ill. Adm. Code 808.410(b)(4) is to be understood as referencing the test required by this Section.~~

- b) A solid waste that exhibits the characteristic of toxicity has the U.S. EPA Hazardous Waste Number specified in the following table ~~which~~ that corresponds to the toxic contaminant causing it to be hazardous.

MAXIMUM CONCENTRATION OF CONTAMINANTS FOR THE TOXICITY CHARACTERISTIC

U.S. EPA Hazardous Waste No.	Contaminant	CAS Number	Note	Regulatory Level(mg/L)
D004	Arsenic	7440-38-2		5.0
D005	Barium	7440-39-3		100.0
D018	Benzene	71-43-2		0.5
D006	Cadmium	7440-43-9		1.0
D019	Carbon tetra- chloride	56-23-5		0.5

D020	Chlordane	57-74-9		0.03
D021	Chlorobenzene	108-90-7		100.0
D022	Chloroform	67-66-3		6.0
D007	Chromium	7440-47-3		5.0
D023	o-Cresol	95-48-7	4	200.0
D024	m-Cresol	108-39-4	4	200.0
D025	p-Cresol	106-44-5	4	200.0
D026	Cresol		4	200.0
D016	2,4-D	94-75-7		10.0
D027	1,4-Dichlorobenzene	106-46-7		7.5
D028	1,2-Dichloroethane	107-06-2		0.5
D029	1,1-Dichloro- ethylene	75-35-4		0.7
D030	2,4-Dinitrotoluene	121-14-2	3	0.13
D012	Endrin	72-20-8		0.02
D031	Heptachlor (and its epoxide)	76-44-8		0.008
D032	Hexachlorobenzene	118-74-1	3	0.13
D033	Hexachlorobutadiene	87-68-3		0.5
D034	Hexachloroethane	67-72-1		3.0
D008	Lead	7439-92-1		5.0
D013	Lindane	58-89-9		0.4
D009	Mercury	7439-97-6		0.2
D014	Methoxychlor	72-43-5		10.0
D035	Methyl ethyl ketone	78-93-3		200.0
D036	Nitrobenzene	98-95-3		2.0
D037	Pentachlorophenol	87-86-5		100.0
D038	Pyridine	110-86-1	3	5.0
D010	Selenium	7782-49-2		1.0
D011	Silver	7440-22-4		5.0
D039	Tetrachloroethylene	127-18-4		0.7
D015	Toxaphene	8001-35-2		0.5
D040	Trichloroethylene	79-01-6		0.5
D041	2,4,5-Trichloro- phenol	95-95-4		400.0
D042	2,4,6-Trichloro- phenol	88-06-2		2.0
DQ17	2,4,5-TP (Silvex)	93-72-1		1.0
D043	Vinyl chloride	75-01-4		0.2

Notes to Table:

- 3 Quantitation limit is greater than the calculated regulatory level. The quantitation limit therefore becomes the regulatory level.
- 4 If o-, m-, p-cresol concentrations cannot be differentiated, the total cresol (D026) concentration is used. The regulatory level of total cresol is 200.0 mg/L.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 721. Appendix B+ Method 1311 Toxicity Characteristic Leaching Procedure (TCLP)

~~The Board incorporates by reference 40 CFR 261, Appendix II, as amended at 57 Fed. Reg. 55114-55117, November 24, 1992 and 58 Fed. Reg. 6854. This Section incorporates no future editions or modifications.~~

NOTE: The TCLP (Method 1311) is published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111.

724.134 Access to Communications or Alarm System
 724.135 Required Aisle Space
 724.137 Arrangements with Local Authorities

SUBPART D: CONTINGENCY PLAN AND EMERGENCY PROCEDURES

Section
 724.150 Applicability
 724.151 Purpose and Implementation of Contingency Plan
 724.152 Content of Contingency Plan
 724.153 Copies of Contingency Plan
 724.154 Amendment of Contingency Plan
 724.155 Emergency Coordinator
 724.156 Emergency Procedures

SUBPART E: MANIFEST SYSTEM, RECORDKEEPING AND REPORTING

Section
 724.170 Applicability
 724.171 Use of Manifest System
 724.172 Manifest Discrepancies
 724.173 Operating Record
 724.174 Availability, Retention and Disposition of Records
 724.175 Annual Report
 724.176 Unmanifested Waste Report
 724.177 Additional Reports

SUBPART F: RELEASES FROM SOLID WASTE MANAGEMENT UNITS

Section
 724.190 Applicability
 724.191 Required Programs
 724.192 Groundwater Protection Standard
 724.193 Hazardous Constituents
 724.194 Concentration Limits
 724.195 Point of Compliance
 724.196 Compliance Period
 724.197 General Groundwater Monitoring Requirements
 724.198 Detection Monitoring Program
 724.199 Compliance Monitoring Program
 724.200 Corrective Action Program
 724.201 Corrective Action for Solid Waste Management Units

SUBPART G: CLOSURE AND POST-CLOSURE

Section
 724.210 Applicability
 724.211 Closure Performance Standard
 724.212 Closure Plan; Amendment of Plan
 724.213 Closure; Time Allowed For Closure
 724.214 Disposal or Decontamination of Equipment, Structures and Soils
 724.215 Certification of Closure
 724.216 Survey Plat
 724.217 Post-closure Care and Use of Property
 724.218 Post-closure Plan; Amendment of Plan
 724.219 Post-closure Notices
 724.220 Certification of Completion of Post-closure Care

SUBPART H: FINANCIAL REQUIREMENTS

Section
 724.240 Applicability
 724.241 Definitions of Terms As Used In This Subpart
 724.242 Cost Estimate for Closure
 724.243 Financial Assurance for Closure
 724.244 Cost Estimate for Post-closure Care
 724.245 Financial Assurance for Post-closure Care

724.246 Use of a Mechanism for Financial Assurance of Both Closure and Post-closure Care
 724.247 Liability Requirements
 724.248 Incapacity of Owners or Operators, Guarantors or Financial Institutions
 724.251 Wording of the Instruments

SUBPART I: USE AND MANAGEMENT OF CONTAINERS

Section
 724.270 Applicability
 724.271 Condition of Containers
 724.272 Compatibility of Waste With Container
 724.273 Management of Containers
 724.274 Inspections
 724.275 Containment
 724.276 Special Requirements for Ignitable or Reactive Waste
 724.277 Special Requirements for Incompatible Wastes
 724.278 Closure

SUBPART J: TANK SYSTEMS

Section
 724.290 Applicability
 724.291 Assessment of Existing Tank System's Integrity
 724.292 Design and Installation of New Tank Systems or Components
 724.293 Containment and Detection of Releases
 724.294 General Operating Requirements
 724.295 Inspections
 724.296 Response to Leaks or Spills and Disposition of Leaking or unfit-for-use Tank Systems
 724.297 Closure and Post-Closure Care
 724.298 Special Requirements for Ignitable or Reactive Waste
 724.299 Special Requirements for Incompatible Wastes
 724.300 Special Requirements for Hazardous Wastes F020, F021, F022, F023, F026 and F027

SUBPART K: SURFACE IMPOUNDMENTS

Section
 724.320 Applicability
 724.321 Design and Operating Requirements
 724.322 Action Leakage Rate
 724.324₃ Response Actions
 724.326 Monitoring and Inspection
 724.327 Emergency Repairs; Contingency Plans
 724.328 Closure and Post-closure Care
 724.329 Special Requirements for Ignitable or Reactive Waste
 724.330 Special Requirements for Incompatible Wastes
 724.331 Special Requirements for Hazardous Wastes F020, F021, F022, F023, F026 and F027

SUBPART L: WASTE PILES

Section
 724.350 Applicability
 724.351 Design and Operating Requirements
 724.352 Action Leakage Rate
 724.353 Response Action Plan
 724.354 Monitoring and Inspection
 724.356 Special Requirements for Ignitable or Reactive Waste
 724.357 Special Requirements for Incompatible Wastes
 724.358 Closure and Post-closure Care
 724.359 Special Requirements for Hazardous Wastes F020, F021, F022, F023, F026 and F027

SUBPART M: LAND TREATMENT

Section
 724.370 Applicability
 724.371 Treatment Program
 724.372 Treatment Demonstration
 724.373 Design and Operating Requirements
 724.376 Food-chain Crops
 724.378 Unsaturated Zone Monitoring
 724.379 Recordkeeping
 724.380 Closure and Post-closure Care
 724.381 Special Requirements for Ignitable or Reactive Waste
 724.382 Special Requirements for Incompatible Wastes
 724.383 Special Requirements for Hazardous Wastes F020, F021, F022, F023, F026 and F027

SUBPART N: LANDFILLS

Section
 724.400 Applicability
 724.401 Design and Operating Requirements
 724.402 Action Leakage Rate
 724.403 Monitoring and Inspection
 724.404 Response Actions
 724.409 Surveying and Recordkeeping
 724.410 Closure and Post-closure Care
 724.412 Special Requirements for Ignitable or Reactive Waste
 724.413 Special Requirements for Incompatible Wastes
 724.414 Special Requirements for Bulk and Containerized Liquids
 724.415 Special Requirements for Containers
 724.416 Disposal of Small Containers of Hazardous Waste in Overpacked Drums (Lab Packs)
 724.417 Special Requirements for Hazardous Wastes F020, F021, F022, F023, F026 and F027

SUBPART O: INCINERATORS

Section
 724.440 Applicability
 724.441 Waste Analysis
 724.442 Principal Organic Hazardous Constituents (POHCs)
 724.443 Performance Standards
 724.444 Hazardous Waste Incinerator Permits
 724.445 Operating Requirements
 724.447 Monitoring and Inspections
 724.451 Closure

SUBPART S: CORRECTIVE ACTION FOR SOLID WASTE MANAGEMENT UNITS

Section
 724.652 Corrective Action Management Units
 724.653 Temporary Units

SUBPART W: DRIP PADS

Section
 724.670 Applicability
 724.671 Assessment of existing drip pad integrity
 724.672 Design and installation of new drip pads
 724.673 Design and operating requirements
 724.674 Inspections
 724.675 Closure

SUBPART X: MISCELLANEOUS UNITS

Section
 724.700 Applicability
 724.701 Environmental Performance Standards

- 724.702 Monitoring, Analysis, Inspection, Response, Reporting and
Corrective Action
724.703 Post-closure Care

SUBPART AA: AIR EMISSION STANDARDS FOR PROCESS VENTS

Section

- 724.930 Applicability
724.931 Definitions
724.932 Standards: Process Vents
724.933 Standards: Closed-vent Systems and Control Devices
724.934 Test methods and procedures
724.935 Recordkeeping requirements
724.936 Reporting Requirements

SUBPART BB: AIR EMISSION STANDARDS FOR EQUIPMENT LEAKS

Section

- 724.950 Applicability
724.951 Definitions
724.952 Standards: Pumps in Light Liquid Service
724.953 Standards: Compressors
724.954 Standards: Pressure Relief Devices in Gas/Vapor Service
724.955 Standards: Sampling Connecting Systems
724.956 Standards: Open-ended Valves or Lines
724.957 Standards: Valves in Gas/Vapor or Light Liquid Service
724.958 Standards: Pumps, Valves, Pressure Relief Devices and Other
Connectors
724.959 Standards: Delay of Repair
724.960 Standards: Closed-vent Systems and Control Devices
724.961 Alternative Percentage Standard for Valves
724.962 Skip Period Alternative for Valves
724.963 Test Methods and Procedures
724.964 Recordkeeping Requirements
724.965 Reporting Requirements

SUBPART DD: CONTAINMENT BUILDINGS

Section

- 724.1100 Applicability
724.1101 Design and operating standards
724.1102 Closure and post-closure care

724.Appendix A Recordkeeping Instructions
724.Appendix B EPA Report Form and Instructions (Repealed)
724.Appendix D Cochran's Approximation to the Behrens-Fisher Student's T-
Test
724.Appendix E Examples of Potentially Incompatible Waste
724.Appendix I Groundwater Monitoring List

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111½, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R82-19, 53 PCB 131, at 7 Ill. Reg. 14059, effective October 12, 1983; amended in R84-9 at 9 Ill. Reg. 11964, effective July 24, 1985; amended in R85-22 at 10 Ill. Reg. 1136, effective January 2, 1986; amended in R86-1 at 10 Ill. Reg. 14119, effective August 12, 1986; amended in R86-28 at 11 Ill. Reg. 6138, effective March 24, 1987; amended in R86-28 at 11 Ill. Reg. 8684, effective April 21, 1987; amended in R86-46 at 11 Ill. Reg. 13577, effective August 4, 1987; amended in R87-5 at 11 Ill. Reg. 19397, effective November 12, 1987; amended in R87-39 at 12 Ill. Reg. 13135, effective July 29, 1988; amended in R88-16 at 13 Ill. Reg. 458, effective December 28, 1988; amended in R89-1 at 13 Ill. Reg. 18527, effective November

13, 1989; amended in R90-2 at 14 Ill. Reg. 14511, effective August 22, 1990; amended in R90-10 at 14 Ill. Reg. 16658, effective September 25, 1990; amended in R90-11 at 15 Ill. Reg. 9654, effective June 17, 1991; amended in R91-1 at 15 Ill. Reg. 14572, effective October 1, 1991; amended in R91-13 at 16 Ill. Reg. 9833, effective June 9, 1992; amended in R92-1 at 16 Ill. Reg. 17666, effective November 6, 1992; amended in R92-10 at 17 Ill. Reg. 5806, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20830, effective November 22, 1993; amended in R93-16 at 18 Ill. Reg. 6973, effective April 26, 1994; amended in R94-7 at _____ Ill. Reg. _____, effective _____.

SUBPART J: TANK SYSTEMS

Section 724.290 Applicability

The requirements of this Subpart apply to owners and operators of facilities that use tank systems for storing or treating hazardous waste, except as otherwise provided in subsections (a), (b) or (c) below or in Section 724.101.

- a) Tank systems that are used to store or treat hazardous waste ~~which~~that contains no free liquids and are situated inside a building with an impermeable floor are exempted from the requirements in Section 724.293. To demonstrate the absence or presence of free liquids in the stored or treated waste, the following test must be used: U.S. EPA Method 9095 (Paint Filter Liquids Test), as described in "Test Methods for Evaluating Solid Wastes Physical/Chemical Methods" U.S. EPA Publication No. SW-846), incorporated by reference in 35 Ill. Adm. Code 720.111, must be used.
- b) Tank systems, including sumps, are defined in 35 Ill. Adm. Code 720.110, that serve as part of a secondary containment system to collect or contain releases of hazardous wastes are exempted from the requirements in Section 724.293(a).
- c) Tanks, sumps and other such collection devices or systems used in conjunction with drip pads, as defined in 35 Ill. Adm. Code 720.110 and regulated under Subpart W of this Part, must meet the requirements of this Subpart.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

SUBPART N: LANDFILLS

Section 724.414 Special Requirements for Bulk and Containerized Liquids

- a) This subsection corresponds with 40 CFR 264.314(a), which pertains to pre May 8, 1985 actions, a date long since passed. This statement maintains structural consistency with U.S. EPA rules.
- b) The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.
- c) To demonstrate the absence or presence of free liquids in either a containerized or a bulk waste, the following test must be used: Method 9095 (Paint Filter Liquids Test) as described in "Test Methods for Evaluating Solid Wastes, Physical/Chemical Methods", ~~U.S. EPA Publication No. SW-846, incorporated by reference in 35 Ill. Adm. Code 724~~0.111.

- d) Containers holding free liquids must not be placed in a landfill unless;
- 1) All free-standing liquid:
 - A) has been removed by decanting or other methods;
 - B) has been mixed with sorbent or solidified so that free-standing liquid is no longer observed; or
 - C) has been otherwise eliminated; or
 - 2) The container is very small, such as an ampule; or
 - 3) The container is designed to hold free liquids for use other than storage, such as a battery or capacitor; or
 - 4) The container is a lab pack as defined in Section 724.416 and is disposed of in accordance with Section 724.416.
- e) Sorbents used to treat free liquids to be disposed of in landfills must be nonbiodegradable. Nonbiodegradable sorbents are: materials listed or described in subsection (e)(1) below; materials that pass one of the tests in subsection (e)(2) below; or materials that are determined by the Board to be nonbiodegradable through the 35 Ill. Adm. Code 106 adjusted standard process.
- 1) Nonbiodegradable sorbents are:
 - A) Inorganic minerals, other inorganic materials, and elemental carbon (e.g., aluminosilicates, clays, smectites, Fuller's earth, bentonite, calcium bentonite, montmorillonite, calcined montmorillonite, kaolinite, micas (illite), vermiculites, zeolites; calcium carbonate (organic free limestone); oxides/hydroxides, alumina, lime, silica (sand), diatomaceous earth; perlite (volcanic glass); expanded volcanic rock; volcanic ash; cement kiln dust; fly ash; rice hull ash; activated charcoal (activated carbon)); or
 - B) High molecular weight synthetic polymers (e.g., polyethylene, high density polyethylene (HDPE), polypropylene, polystyrene, poly urethane, polycrylate, polynorborene, polyisobutylene, ground synthetic rubber, cross-linked allylstrene and tertiary butyl copolymers). This does not include polymers derived from biological material or polymers specifically designed to be degradable; or
 - C) Mixtures of these nonbiodegradable materials.
 - 2) Tests for nonbiodegradable sorbents:
 - A) The sorbent material is determined to be nonbiodegradable under ASTM Method G21-70 (1984a)-- "Standard Practice for Determining Resistance of Synthetic Polymer Materials to Fungi", incorporated by reference in 35 Ill. Adm. Code 720.111; or
 - B) The sorbent material is determined to be nonbiodegradable under ASTM Method G22-76 (1984b)--

"Standard Practice for Determining Resistance of
Plastics to Bacteria", incorporated by reference in 35
Ill. Adm. Code 720.111.

- f) The placement of any liquids ~~which~~that is not a hazardous waste in a landfill is prohibited (35 Ill. Adm. Code 729.311).

(Source: Amended at 18 Ill. Reg. _____, effective _____)

TITLE 35: ENVIRONMENTAL PROTECTION
SUBTITLE G: WASTE DISPOSAL
CHAPTER I: POLLUTION CONTROL BOARD
SUBCHAPTER c: HAZARDOUS WASTE OPERATING REQUIREMENTS

PART 725
INTERIM STATUS STANDARDS FOR OWNERS AND OPERATORS OF HAZARDOUS
WASTE TREATMENT, STORAGE AND DISPOSAL FACILITIES

SUBPART A: GENERAL PROVISIONS

Section
725.101 Purpose, Scope and Applicability
725.104 Imminent Hazard Action

SUBPART B: GENERAL FACILITY STANDARDS

Section
725.110 Applicability
725.111 USEPA Identification Number
725.112 Required Notices
725.113 General Waste Analysis
725.114 Security
725.115 General Inspection Requirements
725.116 Personnel Training
725.117 General Requirements for Ignitable, Reactive or Incompatible
Wastes
725.118 Location Standards
725.119 Construction Quality Assurance Program

SUBPART C: PREPAREDNESS AND PREVENTION

Section
725.130 Applicability
725.131 Maintenance and Operation of Facility
725.132 Required Equipment
725.133 Testing and Maintenance of Equipment
725.134 Access to Communications or Alarm System
725.135 Required Aisle Space
725.137 Arrangements with Local Authorities

SUBPART D: CONTINGENCY PLAN AND EMERGENCY PROCEDURES

Section
725.150 Applicability
725.151 Purpose and Implementation of Contingency Plan
725.152 Content of Contingency Plan
725.153 Copies of Contingency Plan
725.154 Amendment of Contingency Plan
725.155 Emergency Coordinator
725.156 Emergency Procedures

SUBPART E: MANIFEST SYSTEM, RECORDKEEPING AND REPORTING

Section
725.170 Applicability
725.171 Use of Manifest System

725.172 Manifest Discrepancies
 725.173 Operating Record
 725.174 Availability, Retention and Disposition of Records
 725.175 Annual Report
 725.176 Unmanifested Waste Report
 725.177 Additional Reports

SUBPART F: GROUNDWATER MONITORING

Section
 725.190 Applicability
 725.191 Groundwater Monitoring System
 725.192 Sampling and Analysis
 725.193 Preparation, Evaluation and Response
 725.194 Recordkeeping and Reporting

SUBPART G: CLOSURE AND POST-CLOSURE

Section
 725.210 Applicability
 725.211 Closure Performance Standard
 725.212 Closure Plan; Amendment of Plan
 725.213 Closure; Time Allowed for Closure
 725.214 Disposal or Decontamination of Equipment, Structures and Soils
 725.215 Certification of Closure
 725.216 Survey Plat
 725.217 Post-closure Care and Use of Property
 725.218 Post-closure Plan; Amendment of Plan
 725.219 Post-Closure Notices
 725.220 Certification of Completion of Post-Closure Care

SUBPART H: FINANCIAL REQUIREMENTS

Section
 725.240 Applicability
 725.241 Definitions of Terms as Used in this Subpart
 725.242 Cost Estimate for Closure
 725.243 Financial Assurance for Closure
 725.244 Cost Estimate for Post-closure Care
 725.245 Financial Assurance for Post-closure Monitoring and Maintenance
 725.246 Use of a Mechanism for Financial Assurance of Both Closure and Post-closure Care
 725.247 Liability Requirements
 725.248 Incapacity of Owners or Operators, Guarantors or Financial Institutions
 725.251 Promulgation of Forms (Repealed)

SUBPART I: USE AND MANAGEMENT OF CONTAINERS

Section
 725.270 Applicability
 725.271 Condition of Containers
 725.272 Compatibility of Waste with Container
 725.273 Management of Containers
 725.274 Inspections
 725.276 Special Requirements for Ignitable or Reactive Waste
 725.277 Special Requirements for Incompatible Wastes

SUBPART J: TANK SYSTEMS

Section
 725.290 Applicability
 725.291 Assessment of Existing Tank System's Integrity
 725.292 Design and Installation of New Tank Systems or Components
 725.293 Containment and Detection of Releases
 725.294 General Operating Requirements
 725.295 Inspections

725.296 Response to leaks or spills and disposition of Tank Systems
 725.297 Closure and Post-Closure Care
 725.298 Special Requirements for Ignitable or Reactive Waste
 725.299 Special Requirements for Incompatible Wastes
 725.300 Waste Analysis and Trial Tests
 725.301 Generators of 100 to 1000 kg/mo.

SUBPART K: SURFACE IMPOUNDMENTS

Section
 725.320 Applicability
 725.321 Design and Operating Requirements
 725.322 Action Leakage Rate
 725.323 Response Actions
 725.324 Containment System
 725.325 Waste Analysis and Trial Tests
 725.326 Monitoring and Inspections
 725.328 Closure and Post-Closure Care
 725.329 Special Requirements for Ignitable or Reactive Waste
 725.330 Special Requirements for Incompatible Wastes

SUBPART L: WASTE PILES

Section
 725.350 Applicability
 725.351 Protection from Wind
 725.352 Waste Analysis
 725.353 Containment
 725.354 Design and Operating Requirements
 725.355 Action Leakage Rates
 725.356 Special Requirements for Ignitable or Reactive Waste
 725.357 Special Requirements for Incompatible Wastes
 725.358 Closure and Post-Closure Care
 725.359 Response Actions
 725.360 Monitoring and Inspection

SUBPART M: LAND TREATMENT

Section
 725.370 Applicability
 725.372 General Operating Requirements
 725.373 Waste Analysis
 725.376 Food Chain Crops
 725.378 Unsaturated Zone (Zone of Aeration) Monitoring
 725.379 Recordkeeping
 725.380 Closure and Post-closure
 725.381 Special Requirements for Ignitable or Reactive Waste
 725.382 Special Requirements for Incompatible Wastes

SUBPART N: LANDFILLS

Section
 725.400 Applicability
 725.401 Design Requirements
 725.402 Action Leakage Rate
 725.403 Response Actions
 725.404 Monitoring and Inspection
 725.409 Surveying and Recordkeeping
 725.410 Closure and Post-Closure
 725.412 Special Requirements for Ignitable or Reactive Waste
 725.413 Special Requirements for Incompatible Wastes
 725.414 Special Requirements for Liquid Wastes
 725.415 Special Requirements for Containers
 725.416 Disposal of Small Containers of Hazardous Waste in Overpacked Drums (Lab Packs)

SUBPART O: INCINERATORS

Section
 725.440 Applicability
 725.441 Waste Analysis
 725.445 General Operating Requirements
 725.447 Monitoring and Inspection
 725.451 Closure
 725.452 Interim Status Incinerators Burning Particular Hazardous Wastes

SUBPART P: THERMAL TREATMENT

Section
 725.470 Other Thermal Treatment
 725.473 General Operating Requirements
 725.475 Waste Analysis
 725.477 Monitoring and Inspections
 725.481 Closure
 725.482 Open Burning; Waste Explosives
 725.483 Interim Status Thermal Treatment Devices Burning Particular Hazardous Waste

SUBPART Q: CHEMICAL, PHYSICAL AND BIOLOGICAL TREATMENT

Section
 725.500 Applicability
 725.501 General Operating Requirements
 725.502 Waste Analysis and Trial Tests
 725.503 Inspections
 725.504 Closure
 725.505 Special Requirements for Ignitable or Reactive Waste
 725.506 Special Requirements for Incompatible Wastes

SUBPART R: UNDERGROUND INJECTION

Section
 725.530 Applicability

SUBPART W: DRIP PADS

Section
 725.540 Applicability
 725.541 Assessment of existing drip pad integrity
 725.542 Design and installation of new drip pads
 725.543 Design and operating requirements
 725.544 Inspections
 725.545 Closure

SUBPART AA: AIR EMISSION STANDARDS FOR PROCESS VENTS

Section
 725.930 Applicability
 725.931 Definitions
 725.932 Standards: Process Vents
 725.933 Standards: Closed-vent Systems and Control Devices
 725.934 Test methods and procedures
 725.935 Recordkeeping Requirements

SUBPART BB: AIR EMISSION STANDARDS FOR EQUIPMENT LEAKS

Section
 725.950 Applicability
 725.951 Definitions
 725.952 Standards: Pumps in Light Liquid Service
 725.953 Standards: Compressors
 725.954 Standards: Pressure Relief Devices in Gas/Vapor Service
 725.955 Standards: Sampling Connecting Systems
 725.956 Standards: Open-ended Valves or Lines
 725.957 Standards: Valves in Gas/Vapor or Light Liquid Service

725.958	Standards: Pumps, Valves, Pressure Relief Devices, Flanges and Other Connectors
725.959	Standards: Delay of Repair
725.960	Standards: Closed-vent Systems and Control Devices
725.961	Percent Leakage Alternative for Valves
725.962	Skip Period Alternative for Valves
725.963	Test Methods and Procedures
725.964	Recordkeeping Requirements

SUBPART DD: CONTAINMENT BUILDINGS

Section	
725.1100	Applicability
725.1101	Design and operating standards
725.1102	Closure and post-closure care
725.Appendix A	Recordkeeping Instructions
725.Appendix B	EPA Report Form and Instructions (Repealed)
725.Appendix C	EPA Interim Primary Drinking Water Standards
725.Appendix D	Tests for Significance
725.Appendix E	Examples of Potentially Incompatible Waste

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111½, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R81-22, 43 PCB 427, at 5 Ill. Reg. 9781, effective as noted in 35 Ill. Adm. Code 700.106; amended and codified in R81-22, 45 PCB 317, at 6 Ill. Reg. 4828, effective as noted in 35 Ill. Adm. Code 700.106; amended in R82-18, 51 PCB 831, at 7 Ill. Reg. 2518, effective February 22, 1983; amended in R82-19, 53 PCB 131, at 7 Ill. Reg. 14034, effective October 12, 1983; amended in R84-9, at 9 Ill. Reg. 11869, effective July 24, 1985; amended in R85-22 at 10 Ill. Reg. 1085, effective January 2, 1986; amended in R86-1 at 10 Ill. Reg. 14069, effective August 12, 1986; amended in R86-28 at 11 Ill. Reg. 6044, effective March 24, 1987; amended in R86-46 at 11 Ill. Reg. 13489, effective August 4, 1987; amended in R87-5 at 11 Ill. Reg. 19338, effective November 10, 1987; amended in R87-26 at 12 Ill. Reg. 2485, effective January 15, 1988; amended in R87-39 at 12 Ill. Reg. 13027, effective July 29, 1988; amended in R88-16 at 13 Ill. Reg. 437, effective December 28, 1988; amended in R89-1 at 13 Ill. Reg. 18354, effective November 13, 1989; amended in R90-2 at 14 Ill. Reg. 14447, effective August 22, 1990; amended in R90-10 at 14 Ill. Reg. 16498, effective September 25, 1990; amended in R90-11 at 15 Ill. Reg. 9398, effective June 17, 1991; amended in R91-1 at 15 Ill. Reg. 14534, effective October 1, 1991; amended in R91-13 at 16 Ill. Reg. 9578, effective June 9, 1992; amended in R92-1 at 16 Ill. Reg. 17672, effective November 6, 1992; amended in R92-10 at 17 Ill. Reg. 5681, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20620, effective November 22, 1993; amended in R93-16 at 18 Ill. Reg. 6771, effective April 26, 1994; amended in R94-7 at Ill. Reg. , effective .

SUBPART J: TANK SYSTEMS

Section 725.290 Applicability

The regulations of this Subpart apply to owners and operators of facilities that use tank systems for storing or treating hazardous waste, except as otherwise provided in subsections (a), (b) or (c) below, or in Section 725.101.

- a) Tank systems that are used to store or treat hazardous waste ~~which~~that contains no free liquids and that are situated inside a

building with an impermeable floor are exempted from the requirements in Section 725.293. To demonstrate the absence or presence of free liquids in the stored/ or treated waste, the following test must be used: U.S. EPA Method 9095 (Paint Filter Liquids Test), as described in "Test Methods for Evaluating Solid Wastes, Physical/Chemical Methods", U.S. EPA Publication No. SW-846, incorporated by reference in 35 Ill. Adm. Code 720.111, ~~must be used.~~

- b) Tank systems, including sumps, as defined in 35 Ill. Adm. Code 720.110, that serve as part of a secondary containment system to collect or contain releases of hazardous wastes are exempted from the requirements in Section 725.293(a).
- c) Tanks, sumps and other collection devices used in conjunction with drip pads, as defined in 35 Ill. Adm. Code 720.110 and regulated under Subpart W of this Part, must meet the requirements of this Subpart.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

SUBPART N: LANDFILLS

Section 725.414 Special Requirements for Liquid Wastes

- a) This subsection corresponds with 40 CFR 265.314(a), which pertains to the placement of bulk or non-containerized liquid waste or waste containing free liquids in a landfill prior to May 8, 1985. This statement maintains structural consistency with U.S. EPA rules.
- b) The placement of bulk or non-containerized liquid hazardous waste or hazardous waste containing free liquids (whether or not sorbents have been added) in any landfill is prohibited.
- c) Containers holding free liquids must not be placed in a landfill unless;
 - 1) All free-standing liquid:
 - A) has been removed by decanting or other methods;
 - B) has been mixed with sorbent or solidified so that free-standing liquid is no longer observed; or
 - C) has been otherwise eliminated; or
 - 2) The container is very small, such as an ampule; or
 - 3) The container is designed to hold free liquids for use other than storage, such as a battery or capacitor; or
 - 4) The container is a lab pack as defined in Section 724.416 and is disposed of in accordance with Section 724.416.
- d) To demonstrate the absence or presence of free liquids in either a containerized or a bulk waste, the following test must be used: Method 9095 (Paint Filter Liquids Test), as described in "Test Methods for Evaluating Solid Wastes, Physical/Chemical Methods", U.S. EPA Publication No. SW-846, incorporated by reference in 35 Ill. Adm. Code 720.111.

- e) The placement of any liquids ~~which~~that is not a hazardous waste in a landfill is prohibited (35 Ill. Adm. Code 729.311).
- f) Sorbents used to treat free liquids to be disposed of in landfills must be nonbiodegradable. Nonbiodegradable sorbents are:
 materials listed or described in subsection (f)(1) below;
 materials that pass one of the tests in subsection (f)(2) below;
 or materials that are determined by Board to be nonbiodegradable through the 35 Ill. Adm. Code 106 adjusted standard process.
- 1) Nonbiodegradable sorbents are:
- A) Inorganic minerals, other inorganic materials, and elemental carbon (e.g., aluminosilicates, clays, smectites, Fuller's earth, bentonite, calcium bentonite, montmorillonite, calcined montmorillonite, kaolinite, micas (illite), vermiculites, zeolites; calcium carbonate (organic free limestone); oxides/hydroxides, alumina, lime, silica (sand), diatomaceous earth; perlite (volcanic glass); expanded volcanic rock; volcanic ash; cement kiln dust; fly ash; rice hull ash; activated charcoal/activated carbon); or
- B) High molecular weight synthetic polymers (e.g., polyethylene, high density polyethylene (HDPE), polypropylene, polystyrene, polyurethane, polyacrylate, polynorborene, polysobutylene, ground synthetic rubber, cross-linked allylstyrene and tertiary butyl copolymers). This does not include polymers derived from biological material or polymers specifically designed to be degradable; or
- C) Mixtures of these nonbiodegradable materials.
- 2) Tests for nonbiodegradable sorbents.
- A) The sorbent material is determined to be nonbiodegradable under ASTM Method G21-70 (1984a)--
"Standard Practice for Determining Resistance of Synthetic Polymer Materials to Fungi", incorporated by reference in 35 Ill. Adm. Code 720.111; or
- B) The sorbent material is determined to be nonbiodegradable under ASTM Method G22-76 (1984b)--
"Standard Practice for Determining Resistance of Plastics to Bacteria", incorporated by reference in 35 Ill. Adm. Code 720.111.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE G: WASTE DISPOSAL
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER c: HAZARDOUS WASTE OPERATING REQUIREMENTS

PART 726
 STANDARDS FOR THE MANAGEMENT OF SPECIFIC HAZARDOUS WASTE
 AND SPECIFIC TYPES OF HAZARDOUS WASTE MANAGEMENT FACILITIES

SUBPART C: RECYCLABLE MATERIALS USED IN A MANNER
 CONSTITUTING DISPOSAL

Section
 726.120 Applicability
 726.121 Standards applicable to generators and transporters of materials used in a manner that constitutes disposal
 726.122 Standards applicable to storers, who are not the ultimate users, of materials that are to be used in a manner that constitutes disposal
 726.123 Standards applicable to users of materials that are used in a manner that constitutes disposal

SUBPART D: HAZARDOUS WASTE BURNED FOR ENERGY RECOVERY

Section
 726.130 Applicability (Repealed)
 726.131 Prohibitions (Repealed)
 726.132 Standards applicable to generators of hazardous waste fuel (Repealed)
 726.133 Standards applicable to transporters of hazardous waste fuel (Repealed)
 726.134 Standards applicable to marketers of hazardous waste fuel (Repealed)
 726.135 Standards applicable to burners of hazardous waste fuel (Repealed)
 726.136 Conditional exemption for spent materials and by-products exhibiting a characteristic of hazardous waste (Repealed)

SUBPART E: USED OIL BURNED FOR ENERGY RECOVERY (Repealed)

Section
 726.140 Applicability (Repealed)
 726.141 Prohibitions (Repealed)
 726.142 Standards applicable to generators of used oil burned for energy recovery (Repealed)
 726.143 Standards applicable to marketers of used oil burned for energy recovery (Repealed)
 726.144 Standards applicable to burners of used oil burned for energy recovery (Repealed)

SUBPART F: RECYCLABLE MATERIALS UTILIZED FOR PRECIOUS METAL RECOVERY

Section
 726.170 Applicability and requirements

SUBPART G: SPENT LEAD-ACID BATTERIES BEING RECLAIMED

Section
 726.180 Applicability and requirements

SUBPART H: HAZARDOUS WASTE BURNED IN BOILERS AND INDUSTRIAL FURNACES

Section
 726.200 Applicability
 726.201 Management prior to Burning
 726.202 Permit standards for Burners
 726.203 Interim ~~s~~Status ~~s~~Standards for Burners
 726.204 Standards to ~~c~~ontrol Organic Emissions
 726.205 Standards to control PM
 726.206 Standards to ~~c~~ontrol Metals Emissions
 726.207 Standards to control HCl and Chlorine Gas Emissions
 726.208 Small quantity On-site Burner Exemption
 726.209 Low risk waste Exemption
 726.210 Waiver of DRE trial burn for Boilers
 726.211 Standards for direct Transfer
 726.212 Regulation of Residues
 726.219 Extensions of Time

726.Appendix A	Tier I and Tier II Feed Rate and Emissions Screening Limits for Metals
726.Appendix B	Tier I Feed Rate Screening Limits for Total Chlorine
726.Appendix C	Tier II Emission Rate Screening Limits for Free Chlorine and Hydrogen Chloride
726.Appendix D	Reference Air Concentrations
726.Appendix E	Risk Specific Doses
726.Appendix F	Stack Plume Rise
726.Appendix G	Health-Based Limits for Exclusion of Waste-Derived Residues
726.Appendix H	Potential PICs for Determination of Exclusion of Waste-Derived Residues
726.Appendix I	Methods Manual for Compliance with BIF Regulations
726.Appendix J	Guideline on Air Quality Models
726.Appendix K	Lead-Bearing Materials That May be Processed in Exempt Lead Smelters
726.Appendix L	Nickel or Chromium-Bearing Materials that may be Processed in Exempt Nickel-Chromium Recovery Furnaces
726.Table A	Exempt Quantities for Small Quantity Burner Exemption

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111 $\frac{1}{2}$, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R85-22 at 10 Ill. Reg. 1162, effective January 2, 1986; amended in R86-1 at 10 Ill. Reg. 14156, effective August 12, 1986; amended in R87-26 at 12 Ill. Reg. 2900, effective January 15, 1988; amended in R89-1 at 13 Ill. Reg. 18606, effective November 13, 1989; amended in R90-2 at 14 Ill. Reg. 14533, effective August 22, 1990; amended in R90-11 at 15 Ill. Reg. 9727, effective June 17, 1991; amended in R91-13 at 16 Ill. Reg. 9858, effective June 9, 1992; amended in R92-10 at 17 Ill. Reg. 5865, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20904, effective November 22, 1993; amended in R94-7 at Ill. Reg. , effective

SUBPART H: HAZARDOUS WASTE BURNED IN BOILERS AND INDUSTRIAL FURNACES

Section 726.203 Interim ~~s~~Status ~~s~~Standards for Burners

a) Purpose, scope, applicability.

1) General.

- A) The purpose of this Section is to establish minimum national standards for owners and operators of "existing" BIFs that burn hazardous waste where such standards define the acceptable management of hazardous waste during the period of interim status. The standards of this Section apply to owners and operators of existing facilities until either a permit is issued under Section 726.202(d) or until closure responsibilities identified in this Section are fulfilled.
- B) "Existing" or "in existence" means a BIF for which the owner or operator filed a certification of precompliance with U.S. EPA pursuant to 40 CFR 266.103(b), incorporated by reference in subsection (b) below; provided, however, that U.S. EPA has not determined that the certification is invalid.
- C) If a BIF is located at a facility that already has a

RCRA permit or interim status, then the owner or operator shall comply with the applicable regulations dealing with permit modifications in 35 Ill. Adm. Code 703.280 or changes in interim status in 35 Ill. Adm. Code 703.155.

- 2) Exemptions. The requirements of this Section do not apply to hazardous waste and facilities exempt under Sections 726.200(b) or 726.208.
- 3) Prohibition on burning dioxin-listed wastes. The following hazardous waste listed for dioxin and hazardous waste derived from any of these wastes must not be burned in a BIF operating under interim status: U.S. EPA Hazardous Waste Numbers F020, F021, F022, F023, F026 and F027.
- 4) Applicability of 35 Ill. Adm. Code 725 standards. Owners and operators of BIFs that burn hazardous waste and are operating under interim status are subject to the following provisions of 35 Ill. Adm. Code 725, except as provided otherwise by this Section:
 - A) In Subpart A of this Part (General), 35 Ill. Adm. Code 725.104;
 - B) In Subpart B of this Part (General facility standards), 35 Ill. Adm. Code 725.111 through 725.117;
 - C) In Subpart C of this Part (Preparedness and prevention), 35 Ill. Adm. Code 725.131 through 725.137;
 - D) In Subpart D of this Part (Contingency plan and emergency procedures), 35 Ill. Adm. Code 725.151 through 725.156;
 - E) In Subpart E of this Part (Manifest system, recordkeeping and reporting), 35 Ill. Adm. Code 725.171 through 725.177, except that 35 Ill. Adm. Code 725.171, 725.172 and 725.176 do not apply to owners and operators of on-site facilities that do not receive any hazardous waste from off-site sources;
 - F) In Subpart G of this Part (Closure and post-closure), 35 Ill. Adm. Code 725.211 through 725.215;
 - G) In Subpart H of this Part (Financial requirements), 35 Ill. Adm. Code 725.241, 725.242, 725.243 and 725.247 through 725.251, except that the State of Illinois and the Federal government are exempt from the requirements of 35 Ill. Adm. Code 725.Subpart H; and
 - H) In Subpart BB of this Part (Air emission standards for equipment leaks), except 35 Ill. Adm. Code 725.950(a).
- 5) Special requirements for furnaces. The following controls apply during interim status to industrial furnaces (e.g., kilns, cupolas) that feed hazardous waste for a purpose other than solely as an ingredient (see subsection (a)(5)(B) above) at any location other than the hot end where products are normally discharged or where fuels are normally fired:

A) Controls.

- i) The hazardous waste must be fed at a location where combustion gas temperatures are at least 1800-°_F;
- ii) The owner or operator shall determine that adequate oxygen is present in combustion gases to combust organic constituents in the waste and retain documentation of such determination in the facility record;
- iii) For cement kiln systems, the hazardous waste must be fed into the kiln; and
- iv) The HC controls of Section 726.204(f) or subsection (c)(5) below apply upon certification of compliance under subsection (c) below, irrespective of the CO level achieved during the compliance test.

B) Burning hazardous waste solely as an ingredient. A hazardous waste is burned for a purpose other than "solely as an ingredient" if it meets either of these criteria:

- i) The hazardous waste has a total concentration of nonmetal compounds listed in 35 Ill. Adm. Code 721.Appendix H, exceeding 500 ppm by weight, as fired and so is considered to be burned for destruction. The concentration of nonmetal compounds in a waste as-generated may be reduced to the 500 ppm limit by bona fide treatment that removes or destroys nonmetal constituents. Blending for dilution to meet the 500 ppm limit is prohibited and documentation that the waste has not been impermissibly diluted must be retained in the facility record; or
 - ii) The hazardous waste has a heating value of 5,000 Btu/lb or more, as fired, and so is considered to be burned as fuel. The heating value of a waste as-generated may be reduced to below the 5,000 Btu/lb limit by bona fide treatment that removes or destroys organic constituents. The heating value of a waste as-generated may be reduced to below the 5,000 Btu/lb limit by bona fide treatment that removes or destroys organic constituents. Blending to augment the heating value to meet the 5,000 Btu/lb limit is prohibited and documentation that the waste has not been impermissibly blended must be retained in the facility record.
- 6) Restrictions on burning hazardous waste that is not a fuel. Prior to certification of compliance under subsection (c) below, owners and operators shall not feed hazardous waste that has a heating value less than 5000 Btu/lb, as generated, (except that the heating value of a waste as-generated may be increased to above the 5,000 Btu/lb limit by bona fide treatment; however blending to augment the heating value to meet the 5,000 Btu/lb limit is prohibited

and records must be kept to document that impermissible blending has not occurred) in a BIF, except that:

- A) Hazardous waste may be burned solely as an ingredient; or
 - B) Hazardous waste may be burned for purposes of compliance testing (or testing prior to compliance testing) for a total period of time not to exceed 720 hours; or
 - C) Such waste may be burned if the Agency has documentation to show that, prior to August 21, 1991:
 - i) The BIF was operating under the interim status standards for incinerators or thermal treatment units, 35 Ill. Adm. Code 725.Subparts O or P; and
 - ii) The BIF met the interim status eligibility requirements under 35 Ill. Adm. Code 703.153 for 35 Ill. Adm. Code 725.Subparts O or P; and
 - iii) Hazardous waste with a heating value less than 5,000 Btu/lb was burned prior to that date; or
 - D) Such waste may be burned in a halogen acid furnace if the waste was burned as an excluded ingredient under 35 Ill. Adm. Code 721.102(e) prior to February 21, 1991, and documentation is kept on file supporting this claim.
- 7) Direct transfer to the burner. If hazardous waste is directly transferred from a transport vehicle to a BIF without the use of a storage unit, the owner or operator shall comply with Section 726.211.
- b) Certification of precompliance.
- 1) The Board incorporates by reference 40 CFR 266.103(b) (1992) ; amended at 57 Fed. Reg. 38564, August 25, 1992. This Section incorporates no later editions or amendments.
 - 2) Certain owners and operators were required to file a certification of precompliance with U.S. EPA by August 21, 1991, pursuant to 40 CFR 266.103(b). No separate filing is required with the Agency.
- c) Certification of compliance. The owner or operator shall conduct emissions testing to document compliance with the emissions standards of Sections 726.204(b) through (e), 726.205, 726.206, 726.207, and subsection (a)(5)(A)(iv) above under the procedures prescribed by this subsection, except under extensions of time provided by subsection (c)(7) below. Based on the compliance test, the owner or operator shall submit to the Agency, on or before August 21, 1992, a complete and accurate "certification of compliance" (under subsection (c)(4) below) with those emission standards establishing limits on the operating parameters specified in subsection (c)(1) below.
- 1) Limits on operating conditions. The owner or operator shall establish limits on the following parameters based on

operations during the compliance test (under procedures prescribed in subsection (c)(4)(D) below) or as otherwise specified and include these limits with the certification of compliance. The BIF must be operated in accordance with these operating limits and the applicable emissions standards of Section 726.204(b) through (e), 726.205, 726.206, 726.207 and subsection (a)(5)(A)(iv) above at all times when there is hazardous waste in the unit.

- A) Feed rate of total hazardous waste and (unless complying the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e)), pumpable hazardous waste;
- B) Feed rate of each metal in the following feedstreams:
 - i) Total feedstreams, except that industrial furnaces that must comply with the alternative metals implementation approach under subsection (c)(3)(B) below must specify limits on the concentration of each metal in collected PM in lieu of feed rate limits for total feedstreams; and facilities that comply with Tier I or Adjusted Tier I metals feed rate screening limits may set their operating limits at the metal feed rate screening limits determined under subsection 726.206(b) or (e).

BOARD NOTE: Federal subsections 266.103(c)(1)(ii)(A)(1) and (c)(1)(ii)(A)(2) are condensed into the above subsection.
 - ii) Total hazardous waste feed (unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e)); and
 - iii) Total pumpable hazardous waste feed (unless complying with Tier I or Adjusted Tier I metals feed rate screening limits under subsection 726.206 (b) or (e)).
- C) Total feed rate of total chlorine and chloride in total feed streams, except that facilities that comply with Tier I or Adjusted Tier I feed rate screening limits may set their operating limits at the total chlorine and chloride feed rate screening limits determined under subsection 726.207(b)(1) or (e);
- D) Total feed rate of ash in total feed streams, except that the ash feed rate for cement kilns and light-weight aggregate kilns is not limited;
- E) CO concentration, and where required, HC concentration in stack gas. When complying with the CO controls of Section 726.204(b), the CO limit is 100 ppmv, and when complying with the HC controls of Section 726.204(c), the HC limit is 20 ppmv. When complying with the CO controls of Section 726.204(c), the CO limit is established based on the compliance test;
- F) Maximum production rate of the device in appropriate

units when producing normal product unless complying with Tier I or Adjusted Tier I feed rate screening limits for chlorine under subsection 726.207(b)(1) or (e) and for all metals under subsection 726.207(b) or (e), and the uncontrolled particulate emissions do not exceed the standard under subsection 726.205;

- G) Maximum combustion chamber temperature where the temperature measurement is as close to the combustion zone as possible and is upstream of any quench water injection, (unless complying with the Tier I adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e));
- H) Maximum flue gas temperature entering a PM control device (unless complying with Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e));
- I) For systems using wet scrubbers, including wet ionizing scrubbers (unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e) and the total chlorine and chloride feed rate screening limits under Section 726.207(b)(1) or (e)):
 - i) Minimum liquid to flue gas ratio;
 - ii) Minimum scrubber blowdown from the system or maximum suspended solids content of scrubber water; and
 - iii) Minimum pH level of the scrubber water;
- J) For systems using venturi scrubbers, the minimum differential gas pressure across the venturi (unless complying the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e) and the total chlorine and chloride feed rate screening limits under Section 726.207(b)(1) or (e));
- K) For systems using dry scrubbers (unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e) and the total chlorine and chloride feed rate screening limits under Section 726.207(b)(1) or (e)):
 - i) Minimum caustic feed rate; and
 - ii) Maximum flue gas flow rate:
- L) For systems using wet ionizing scrubbers or electrostatic precipitators (unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e) and the total chlorine and chloride feed rate screening limits under Section 726.207(b)(1) or (e)):
 - i) Minimum electrical power in kVA to the precipitator plates; and
 - ii) Maximum flue gas flow rate;

- M) For systems using fabric filters (baghouses), the minimum pressure drop (unless complying with the Tier I or adjusted Tier I metals feed rate screening limits under Section 726.206(b) or (e) and the total chlorine and chloride feed rate screening limits under Section 726.207(b)(1) or (e)).
- 2) Prior notice of compliance testing. At least 30 days prior to the compliance testing required by subsection (c)(3) below, the owner or operator shall notify the Agency and submit the following information:
- A) General facility information including:
 - i) U.S. EPA facility ID number;
 - ii) Facility name, contact person, telephone number and address;
 - iii) Person responsible for conducting compliance test, including company name, address and telephone number, and a statement of qualifications;
 - iv) Planned date of the compliance test;
 - B) Specific information on each device to be tested including:
 - i) A Description of BIF;
 - ii) A scaled plot plan showing the entire facility and location of the BIF;
 - iii) A description of the APCS;
 - iv) Identification of the continuous emission monitors that are installed, including: CO monitor; Oxygen monitor; HC monitor, specifying the minimum temperature of the system and, if the temperature is less than 150°C, an explanation of why a heated system is not used (see subsection (c)(5) below) and a brief description of the sample gas conditioning system;
 - v) Indication of whether the stack is shared with another device that will be in operation during the compliance test;
 - vi) Other information useful to an understanding of the system design or operation.
 - C) Information on the testing planned, including a complete copy of the test protocol and QA/QC plan, and a summary description for each test providing the following information at a minimum:
 - i) Purpose of the test (e.g., demonstrate compliance with emissions of PM); and
 - ii) Planned operating conditions, including levels

for each pertinent parameter specified in subsection (c)(1) above.

3) Compliance testing.

- A) General. Compliance testing must be conducted under conditions for which the owner or operator has submitted a certification of precompliance under subsection (b) above, and under conditions established in the notification of compliance testing required by subsection (c)(2) above. The owner or operator may seek approval on a case-by-case basis to use compliance test data from one unit in lieu of testing a similar on-site unit. To support the request, the owner or operator shall provide a comparison of the hazardous waste burned and other feedstreams, and the design, operation, and maintenance of both the tested unit and the similar unit. The Agency shall provide a written approval to use compliance test data in lieu of testing a similar unit if the Agency finds that the hazardous wastes, devices and the operating conditions are sufficiently similar, and the data from the other compliance test is adequate to meet the requirements of this subsection (c).
- B) Special requirements for industrial furnaces that recycle collected PM. Owners and operators of industrial furnaces that recycle back into the furnace PM from the APCS shall comply with one of the following procedures for testing to determine compliance with the metals standards of Section 726.206(c) or (d):
- i) The special testing requirements prescribed in "Alternative Method for Implementing Metals Controls" in Section 726.Appendix I-~~("eye")~~; or
 - ii) Stack emissions testing for a minimum of 6 hours each day while hazardous waste is burned during interim status. The testing must be conducted when burning normal hazardous waste for that day at normal feed rates for that day and when the APCS is operated under normal conditions. During interim status, hazardous waste analysis for metals content must be sufficient for the owner or operator to determine if changes in metals content affect the ability of the unit to meet the metals emissions standards established under Section 726.206(c) or (d). Under this option, operating limits (under subsection (c)(1) above) must be established during compliance testing under this subsection (c)(3) only on the following parameters: Feed rate of total hazardous waste; Total feed rate of total chlorine and chloride in total feed streams; Total feed rate of ash in total feed streams, except that the ash feed rate for cement kilns and light-weight aggregate kilns is not limited; CO concentration, and where required, HC concentration in stack gas; Maximum production rate of the device in appropriate units when

producing normal product; or

- iii) Conduct compliance testing to determine compliance with the metals standards to establish limits on the operating parameters of subsection (c)(1) above, only after the kiln system has been conditioned to enable it to reach equilibrium with respect to metals fed into the system and metals emissions. During conditioning, hazardous waste and raw materials having the same metals content as will be fed during the compliance test must be fed at the feed rates that will be fed during the compliance test.

C) Conduct of compliance testing.

- i) If compliance with all applicable emissions standards of Sections 726.204 through 726.207 is not demonstrated simultaneously during a set of test runs, the operating conditions of additional test runs required to demonstrate compliance with remaining emissions standards must be as close as possible to the original operating conditions.
 - ii) Prior to obtaining test data for purposes of demonstrating compliance with the applicable emissions standards of Sections 726.204 through 726.207 or establishing limits on operating parameters under this Section, the facility must operate under compliance test conditions for a sufficient period to reach steady-state operations. Industrial furnaces that recycle collected PM back into the furnace and that comply with subsections (c)(3)(B)(i) or (c)(3)(B)(ii) above, however, need not reach steady state conditions with respect to the flow of metals in the system prior to beginning compliance testing for metals.
 - iii) Compliance test data on the level of an operating parameter for which a limit must be established in the certification of compliance must be obtained during emissions sampling for the pollutant(s) (i.e., metals, PM, HCl/chlorine gas, organic compounds) for which the parameter must be established as specified by subsection (c)(1) above.
- 4) Certification of compliance. Within 90 days of completing compliance testing, the owner or operator shall certify to the Agency compliance with the emissions standards of Sections 726.204(b), (c) and (e), 726.205, 726.206, 726.207, and subsection (a)(5)(A)(iv) above. The certification of compliance must include the following information:
- A) General facility and testing information including:
 - i) U.S. EPA facility ID number;
 - ii) Facility name, contact person, telephone number

and address;

- iii) Person responsible for conducting compliance testing, including company name, address and telephone number, and a statement of qualifications;
- iv) Date(s) of each compliance test;
- v) Description of BIF tested;
- vi) Person responsible for QA/QC, title and telephone number, and statement that procedures prescribed in the QA/QC plan submitted under Section 726.203(c)(2)(C) have been followed, or a description of any changes and an explanation of why changes were necessary.
- vii) Description of any changes in the unit configuration prior to or during testing that would alter any of the information submitted in the prior notice of compliance testing under subsection (c)(2) above, and an explanation of why the changes were necessary;
- viii) Description of any changes in the planned test conditions prior to or during the testing that alter any of the information submitted in the prior notice of compliance testing under subsection (c)(2) above, and an explanation of why the changes were necessary; and
- ix) The complete report on results of emissions testing.

B) Specific information on each test including:

- i) Purpose(s) of test (e.g., demonstrate conformance with the emissions limits for PM, metals, HCl, chlorine gas and CO)
- ii) Summary of test results for each run and for each test including the following information: Date of run; Duration of run; Time-weighted average and highest hourly rolling average CO level for each run and for the test; Highest hourly rolling average HC level, if HC monitoring is required for each run and for the test; If dioxin and furan testing is required under Section 726.204(e), time-weighted average emissions for each run and for the test of chlorinated dioxin and furan emissions, and the predicted maximum annual average ground level concentration of the toxicity equivalency factor (defined in Section 726.200(g)); Time-weighted average PM emissions for each run and for the test; Time-weighted average HCl and chlorine gas emissions for each run and for the test; Time-weighted average emissions for the metals subject to regulation under Section 726.206 for each run and for the test; and QA/QC results.

- C) Comparison of the actual emissions during each test with the emissions limits prescribed by Sections 726.204(b), (c) and (e), 726.205, 726.206 and 726.207 and established for the facility in the certification of precompliance under subsection (b) above.
- D) Determination of operating limits based on all valid runs of the compliance test for each applicable parameter listed in subsection (c)(1) above using either of the following procedures:
- i) Instantaneous limits. A parameter must be measured and recorded on an instantaneous basis (i.e., the value that occurs at any time) and the operating limit specified as the time-weighted average during all runs of the compliance test; or
 - ii) Hourly rolling average basis. The limit for a parameter must be established and continuously monitored on an hourly rolling average basis, as defined in Section 726.200(g). The operating limit for the parameter must be established based on compliance test data as the average over all test runs of the highest hourly rolling average value for each run.
 - iii) Rolling average limits for carcinogenic metals and lead. Feed rate limits for the carcinogenic metals and lead must be established either on an hourly rolling average basis as prescribed by subsection (c)(4)(D)(ii) above or on (up to) a 24 hour rolling average basis. If the owner or operator elects to use an averaging period from 2 to 24 hours: The feed rate of each metal must be limited at any time to ten times the feed rate that would be allowed on a hourly rolling average basis; The continuous monitor is as defined in Section 726.200(g). And the operating limit for the feed rate of each metal must be established based on compliance test data as the average over all test runs of the highest hourly rolling average feed rate for each run.
 - iv) Feed rate limits for metals, total chlorine and chloride and ash. Feed rate limits for metals, total chlorine and chloride and ash are established and monitored by knowing the concentration of the substance (i.e., metals, chloride/chlorine and ash) in each feedstream and the flow rate of the feedstream. To monitor the feed rate of these substances, the flow rate of each feedstream must be monitored under the continuous monitoring requirements of subsections (c)(4)(D)(i) through (c)(4)(D)(iii) above.
- E) Certification of compliance statement. The following statement must accompany the certification of compliance:

"I certify under penalty of law that this information was prepared under my direction or supervision in accordance with a system designed to ensure that qualified personnel properly gathered and evaluated the information and supporting documentation. Copies of all emissions tests, dispersion modeling results and other information used to determine conformance with the requirements of 35 Ill. Adm. Code 726.203(c) are available at the facility and can be obtained from the facility contact person listed above. Based on my inquiry of the person or persons who manages the facility, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

I also acknowledge that the operating limits established pursuant to 35 Ill. Adm. Code 726.203(c)(4)(D) are enforceable limits at which the facility can legally operate during interim status until a revised certification of compliance is submitted."

- 5) Special requirements for HC monitoring systems. When an owner or operator is required to comply with the HC controls provided by Sections 726.204(c) or subsection (a)(5)(A)(iv) above, a conditioned gas monitoring system may be used in conformance with specifications provided in Section 726. Appendix I—~~"eye"~~ provided that the owner or operator submits a certification of compliance without using extensions of time provided by subsection (c)(7) below. However, owners or operators of facilities electing to comply with the alternative hydrocarbon provision of Section 726.204(f) and requesting a time extension under Section 726.219(b) may establish the baseline HC level and comply with the interim HC limit established by the time extension using a conditioned gas monitoring system if the Board determines that the owner or operator has also demonstrated a good faith effort to operate a heated monitoring system but found it to be impracticable.
- 6) Special operating requirements for industrial furnaces that recycle collected PM. Owners and operators of industrial furnaces that recycle back into the furnace PM from the APCS must:
 - A) When complying with the requirements of subsection (c)(3)(B)(i) above, comply with the operating requirements prescribed in "Alternative Method to Implement the Metals Controls" in Section 726. Appendix I—~~"eye"~~; and
 - B) When complying with the requirements of subsection (c)(3)(B)(ii) above, comply with the operating requirements prescribed by that subsection.
- 7) Extensions of time.

- A) If the owner or operator does not submit a complete certification of compliance for all of the applicable emissions standards of Sections 726.204, 726.205, 726.206 and 726.207 by August 21, 1992, the owner or operator shall either:
- i) Stop burning hazardous waste and begin closure activities under subsection (1) below for the hazardous waste portion of the facility; or
 - ii) Limit hazardous waste burning only for purposes of compliance testing (and pretesting to prepare for compliance testing) a total period of 720 hours for the period of time beginning August 21, 1992, submit a notification to the Agency by August 21, 1992 stating that the facility is operating under restricted interim status and intends to resume burning hazardous waste, and submit a complete certification of compliance by August 23, 1993; or
 - iii) Obtain a case-by-case extension of time under subsection (c)(7)(B) below.
- B) Case-by-case extensions of time. See Section 726.219.
- 8) Revised certification of compliance. The owner or operator may submit at any time a revised certification of compliance (recertification of compliance) under the following procedures:
- A) Prior to submittal of a revised certification of compliance, hazardous waste must not be burned for more than a total of 720 hours under operating conditions that exceed those established under a current certification of compliance, and such burning must be conducted only for purposes of determining whether the facility can operate under revised conditions and continue to meet the applicable emissions standards of Sections 726.204, 726.205, 726.206 and 726.207;
 - B) At least 30 days prior to first burning hazardous waste under operating conditions that exceed those established under a current certification of compliance, the owner or operator shall notify the Agency and submit the following information:
 - i) U.S. EPA facility ID number, and facility name, contact person, telephone number and address;
 - ii) Operating conditions that the owner or operator is seeking to revise and description of the changes in facility design or operation that prompted the need to seek to revise the operating conditions;
 - iii) A determination that, when operating under the revised operating conditions, the applicable emissions standards of Sections 726.204, 726.205, 726.206 and 726.207 are not likely to be exceeded. To document this determination,

the owner or operator shall submit the applicable information required under subsection (b)(2) above; and

- iv) Complete emissions testing protocol for any pretesting and for a new compliance test to determine compliance with the applicable emissions standards of Sections 726.204, 726.205, 726.206 and 726.207 when operating under revised operating conditions. The protocol shall include a schedule of pre-testing and compliance testing. If the owner or operator revises the scheduled date for the compliance test, the owner or operator shall notify the Agency in writing at least 30 days prior to the revised date of the compliance test;
 - C) Conduct a compliance test under the revised operating conditions and the protocol submitted to the Agency to determine compliance with the applicable emissions standards of Sections 726.204, 726.205, 726.206 and 726.207; and
 - D) Submit a revised certification of compliance under subsection (c)(4) above.
- d) **Periodic Recertifications.** The owner or operator shall conduct compliance testing and submit to the Agency a recertification of compliance under provisions of subsection (c) above within three years from submitting the previous certification or recertification. If the owner or operator seeks to recertify compliance under new operating conditions, the owner or operator shall comply with the requirements of subsection (c)(8) above.
- e) **Noncompliance with certification schedule.** If the owner or operator does not comply with the interim status compliance schedule provided by subsections (b), (c) and (d) above, hazardous waste burning must terminate on the date that the deadline is missed, closure activities must begin under subsection (1) below, and hazardous waste burning must not resume except under an operating permit issued under 35 Ill. Adm. Code 703.232. For purposes of compliance with the closure provisions of subsection (1) below and 35 Ill. Adm. Code 725.212(d)(2) and 725.213, the BIF has received "the known final volume of hazardous waste" on the date the deadline is missed.
- f) **Start-up and shut-down.** Hazardous waste (except waste fed solely as an ingredient under the Tier I (or adjusted Tier I) feed rate screening limits for metals and chloride/chlorine) must not be fed into the device during start-up and shut-down of the BIF, unless the device is operating within the conditions of operation specified in the certification of compliance.
- g) **Automatic waste feed cutoff.** During the compliance test required by subsection (c)(3) above and upon certification of compliance under subsection (c) above, a BIF must be operated with a functioning system that automatically cuts off the hazardous waste feed when the applicable operating conditions specified in subsections (c)(1)(A) and (c)(1)(E) through (c)(1)(M) above deviate from those established in the certification of compliance. In addition:

- 1) To minimize emissions of organic compounds, the minimum combustion chamber temperature (or the indicator of combustion chamber temperature) that occurred during the compliance test must be maintained while hazardous waste or hazardous waste residues remain in the combustion chamber, with the minimum temperature during the compliance test defined as either:
 - A) If compliance with the combustion chamber temperature limit is based on a hourly rolling average, the minimum temperature during the compliance test is considered to be the average over all runs of the lowest hourly rolling average for each run; or
 - B) If compliance with the combustion chamber temperature limit is based on an instantaneous temperature measurement, the minimum temperature during the compliance test is considered to be the time-weighted average temperature during all runs of the test; and
 - 2) Operating parameters limited by the certification of compliance must continue to be monitored during the cutoff, and the hazardous waste feed must not be restarted until the levels of those parameters comply with the limits established in the certification of compliance.
- h) Fugitive emissions. Fugitive emissions must be controlled by:
- 1) Keeping the combustion zone totally sealed against fugitive emissions; or
 - 2) Maintaining the combustion zone pressure lower than atmospheric pressure; or
 - 3) An alternate means of control that the owner or operator demonstrates provides fugitive emissions control equivalent to maintenance of combustion zone pressure lower than atmospheric pressure. Support for such demonstration must be included in the operating record.
- i) Changes. A BIF must cease burning hazardous waste when combustion properties, or feed rates of the hazardous waste, other fuels or industrial furnace feedstocks, or the BIF design or operating conditions deviate from the limits specified in the certification of compliance.
- j) Monitoring and Inspections.
- 1) The owner or operator shall monitor and record the following, at a minimum, while burning hazardous waste:
 - A) Feed rates and composition of hazardous waste, other fuels and industrial furnace feed stocks, and feed rates of ash, metals, and total chlorine and chloride as necessary to ensure conformance with the certification of precompliance or certification of compliance;
 - B) CO, oxygen and, if applicable, HC, on a continuous basis at a common point in the BIF downstream of the combustion zone and prior to release of stack gases to the atmosphere in accordance with the operating limits

specified in the certification of compliance. CO, HC and oxygen monitors must be installed, operated and maintained in accordance with methods specified in Section 726. Appendix I-~~"eye"~~.

- C) Upon the request of the Agency, sampling and analysis of the hazardous waste (and other fuels and industrial furnace feed stocks as appropriate) and the stack gas emissions must be conducted to verify that the operating conditions established in the certification of precompliance or certification of compliance achieve the applicable standards of Sections 726.204, 726.205, 726.206 and 726.207.
- 2) The BIF and associated equipment (pumps, valves, pipes, fuel storage tanks, etc.) must be subjected to thorough visual inspection when they contain hazardous waste, at least daily for leaks, spills, fugitive emissions and signs of tampering.
- 3) The automatic hazardous waste feed cutoff system and associated alarms must be tested at least once every 7 days when hazardous waste is burned to verify operability, unless the owner or operator can demonstrate that weekly inspections will unduly restrict or upset operations and that less frequent inspections will be adequate. Support for such demonstration must be included in the operating record. At a minimum, operational testing must be conducted at least once every 30 days.
- 4) These monitoring and inspection data must be recorded and the records must be placed in the operating log.
- k) Recordkeeping. The owner or operator shall keep in the operating record of the facility all information and data required by this Section until closure of the BIF unit.
- l) Closure. At closure, the owner or operator shall remove all hazardous waste and hazardous waste residues (including, but not limited to, ash, scrubber waters and scrubber sludges) from the BIF and shall comply with 35 Ill. Adm. Code 725.211 through 725.215.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 726.204 Standards to eControl Organic Emissions

- a) DRE standard.
- 1) General. Except as provided in subsection (a)(3) below, a BIF burning hazardous waste must achieve a DRE of 99.99% for all organic hazardous constituents in the waste feed. To demonstrate conformance with this requirement, 99.99% DRE must be demonstrated during a trial burn for each principal organic hazardous constituent (POHC) designated (under subsection (a)(2) below) in its permit for each waste feed. DRE is determined for each POHC from the following equation:

$$DRE = 100(I - O)/I$$

where:

I = Mass feed rate of one POHC in the hazardous waste fired to the BIF; and

O = Mass emission rate of the same POHC present in stack gas prior to release to the atmosphere.

- 2) Designation of POHCs. POHCs are those compounds for which compliance with the DRE requirements of this Section must be demonstrated in a trial burn in conformance with procedures prescribed in 35 Ill. Adm. Code 703.232. One or more POHCs must be designated by the Agency for each waste feed to be burned. POHCs must be designated based on the degree of difficulty of destruction of the organic constituents in the waste and on their concentrations or mass in the waste feed considering the results of waste analyses submitted with Part B of the permit application. POHCs are most likely to be selected from among those compounds listed in 35 Ill. Adm. Code 721.Appendix H that are also present in the normal waste feed. However, if the applicant demonstrates to the Agency that a compound not listed in 35 Ill. Adm. Code 721.Appendix H or not present in the normal waste feed is a suitable indicator of compliance with the DRE requirements of this Section, that compound must be designated as a POHC. Such POHCs need not be toxic or organic compounds.
 - 3) Dioxin-listed waste. A BIF burning hazardous waste containing (or derived from) U.S. EPA Hazardous Wastes Nos. F020, F021, F022, F023, F026 or F027 must achieve a destruction and removal efficiency (DRE) of 99.9999% for each POHC designated (under subsection (a)(2)_T above) in its permit. This performance must be demonstrated on POHCs that are more difficult to burn than tetra-, penta- and hexachlorodibenzo-p-dioxins and dibenzofurans. DRE is determined for each POHC from the equation in subsection (a)(1)_T above. In addition, the owner or operator of the BIF shall notify the Agency of intent to burn U.S. EPA Hazardous Waste Nos. F020, F021, F022, F023, F026 or F027.
 - 4) Automatic waiver of DRE trial burn. Owners and operators of boilers operated under the special operating requirements provided by Section 726.210 are considered to be in compliance with the DRE standard of subsection (a)(1)_T above_T and are exempt from the DRE trial burn.
 - 5) Low risk waste. Owners and operators of BIFs that burn hazardous waste in compliance with the requirements of Section 726.209(a) are considered to be in compliance with the DRE standard of subsection (a)(1)_T above_T and are exempt from the DRE trial burn.
- b) CO standard.
- 1) Except as provided in subsection (c)_T below, the stack gas concentration of CO from a BIF burning hazardous waste cannot exceed 100 ppmv on an hourly rolling average basis (i.e., over any 60 minute period), continuously corrected to 7 percent oxygen, dry gas basis.
 - 2) CO and oxygen must be continuously monitored in conformance with "Performance Specifications for Continuous Emission Monitoring of Carbon Monoxide and Oxygen for Incinerators, Boilers, and Industrial Furnaces Burning Hazardous Waste" in

Section 726. Appendix I—(“eye”).

- 3) Compliance with the 100 ppmv CO limit must be demonstrated during the trial burn (for new facilities or an interim status facility applying for a permit) or the compliance test (for interim status facilities). To demonstrate compliance, the highest hourly rolling average CO level during any valid run of the trial burn or compliance test must not exceed 100 ppmv.
- c) Alternative CO standard.
- 1) The stack gas concentration of CO from a BIF burning hazardous waste may exceed the 100 ppmv limit provided that stack gas concentrations of HCs do not exceed 20 ppmv, except as provided by subsection (f) below for certain industrial furnaces.
 - 2) HC limits must be established under this Section on an hourly rolling average basis (i.e., over any 60 minute period), reported as propane, and continuously corrected to 7 percent oxygen, dry gas basis.
 - 3) HC must be continuously monitored in conformance with “Performance Specifications for Continuous Emission Monitoring of Hydrocarbons for Incinerators, Boilers, and Industrial Furnaces Burning Hazardous Waste” in Section 726. Appendix I—(“eye”). CO and oxygen must be continuously monitored in conformance with subsection (b)(2) above.
 - 4) The alternative CO standard is established based on CO data during the trial burn (for a new facility) and the compliance test (for an interim status facility). The alternative CO standard is the average over all valid runs of the highest hourly average CO level for each run. The CO limit is implemented on an hourly rolling average basis, and continuously corrected to 7 percent oxygen, dry gas basis.
- d) Special requirements for furnaces. Owners and operators of industrial furnaces (e.g., kilns, cupolas) that feed hazardous waste for a purpose other than solely as an ingredient (see Section 726.203(a)(5)(B)) at any location other than the end where products are normally discharged and where fuels are normally fired must comply with the HC limits provided by subsections (c) above or (f) below irrespective of whether stack gas CO concentrations meet the 100 ppmv limit of subsection (b) above.
- e) Controls for dioxins and furans. Owners and operators of BIFs that are equipped with a dry PM control device that operates within the temperature range of 450 through 750°F, and industrial furnaces operating under an alternative HC limit established under subsection (f) below shall conduct a site-specific risk assessment as follows to demonstrate that emissions of chlorinated dibenzo-p-dioxins and dibenzofurans do not result in an increased lifetime cancer risk to the hypothetical maximum exposed individual (MEI) exceeding ~~1E-05~~ 1×10^{-5} (1 in 100,000):
- 1) During the trial burn (for new facilities or an interim status facility applying for a permit) or compliance test (for interim status facilities), determine emission rates of the tetra-octa congeners of chlorinated dibenzo-p-dioxins

- (PCDDs) and dibenzofurans (CDDs/CDFs) using Method 23, "Determination of Polychlorinated Dibenzop-Dioxins and Polychlorinated Dibenzofurans (PCDFs) from Stationary Sources", in Section 726. Appendix I-~~("eye")~~;
- 2) Estimate the 2,3,7,8-TCDD toxicity equivalence of the tetra-octa CDDs/CDFs congeners using "Procedures for Estimating the Toxicity Equivalence of Chlorinated Dibenzop-Dioxin and Dibenzofuran Congeners" in Section 726. Appendix I-~~("eye")~~. Multiply the emission rates of CDD/CDF congeners with a toxicity equivalence greater than zero (see the procedure) by the calculated toxicity equivalence factor to estimate the equivalent emission rate of 2,3,7,8-TCDD;
 - 3) Conduct dispersion modeling using methods recommended in 40 CFR 51, Appendix W, as incorporated by reference at 35 Ill. Adm. Code 720.111 ("Guideline on Air Quality Models (Revised)" (1986) and its supplements), ~~or the "Hazardous Waste Combustion Air Quality Screening Procedure", which are provided in Appendices I and J, respectively, or "EPA SCREEN Screening Procedure" as described in "Screening Procedures for Estimating Air Quality Impact of Stationary Sources, Revised" (incorporated by reference in 35 Ill. Adm. Code 720.111)~~ to predict the maximum annual average off-site ground level concentration of 2,3,7,8-TCDD equivalents determined under subsection (e)(2)~~7~~ above. The maximum annual average on-site concentration must be used when a person resides on-site; and
 - 4) The ratio of the predicted maximum annual average ground level concentration of 2,3,7,8-TCDD equivalents to the risk-specific dose (RSD) for 2,3,7,8-TCDD provided in Section 726. Appendix E ($2.2E-07 \times 10^3$) must not exceed 1.0.
- f) Alternative HC limit for furnaces with organic matter in raw material. For industrial furnaces that cannot meet the 20 ppmv HC limit because of organic matter in normal raw material, the Agency shall establish an alternative HC limit on a case-by-case basis (under a Part B permit proceeding) at a level that ensures that flue gas HC (and CO) concentrations when burning hazardous waste are not greater than when not burning hazardous waste (the baseline HC level) provided that the owner or operator complies with the following requirements. However, cement kilns equipped with a by-pass duct meeting the requirements of subsection (g)~~7~~ below~~7~~ are not eligible for an alternative HC limit.
- 1) The owner or operator shall demonstrate that the facility is designed and operated to minimize HC emissions from fuels and raw materials, and that the facility is producing normal products under normal operating conditions feeding normal feedstocks and fuels when the baseline HC (and CO) level is determined. The baseline HC level is defined as the average over all valid test runs of the highest hourly rolling average value for each run when the facility does not burn hazardous waste, adjusted as appropriate to consider the variability of hydrocarbon levels under good combustion operating conditions. The baseline CO level is determined based on the test runs used to establish the baseline HC level and is defined as the average over all test runs of the highest hourly rolling average CO value for each run. More than one baseline level must be determined if the facility operates under different modes that generate

significantly different HC (and CO) levels;

- 2) The owner or operator shall develop an approach to monitor over time changes in the operation of the facility that could reduce the baseline HC level;
- 3) The owner or operator shall conduct emissions testing during the trial burn to:
 - A) Determine the baseline HC (and CO) level;
 - B) Demonstrate that, when hazardous waste is burned, HC (and CO) levels do not exceed the baseline level; and
 - C) Identify the types and concentrations of organic compounds listed in 35 Ill. Adm. Code 721. Appendix H, that are emitted and conduct dispersion modeling to predict the maximum annual average ground level concentration of each organic compound. On-site ground level concentrations must be considered for this evaluation if a person resides on site.
 - i) Sampling and analysis of organic emissions must be conducted using procedures prescribed by the Agency pursuant to 35 Ill. Adm. Code 703.208(a).
 - ii) Dispersion modeling must be conducted according to procedures provided by subsection (e)(2) above; and
 - D) Demonstrate that maximum annual average ground level concentrations of the organic compounds identified in subsection (f)(3)(C) above do not exceed the following levels:
 - i) For the noncarcinogenic compounds listed in Section 726. Appendix D, the levels established in that Section 726. Appendix D;
 - ii) For the carcinogenic compounds listed in Section 726. Appendix E, the sum for all compounds of the ratios of the actual ground level concentration to the level established in that Section 726. Appendix E cannot exceed 1.0. To estimate the health risk from chlorinated dibenzo-p-dioxins and dibenzofuran congeners, use the procedures prescribed by subsection (e)(3) above to estimate the 2,3,7,8-TCDD toxicity equivalence of the congeners.
 - iii) For compounds not listed in Section 726. Appendix D or 726. Appendix E, 0.1 $\mu\text{g}/\text{cu-m}^3$ (micrograms per cubic meter).
- 4) All HC levels specified under this subsection are to be monitored and reported as specified in subsections (c)(1) and (c)(2) above.
- g) Monitoring CO and HC in the by-pass duct of a cement kiln. Cement kilns may comply with the CO and HC limits provided by subsections (b), (c) and (d) above by monitoring in the by-pass duct provided that:

- 1) Hazardous waste is fired only into the kiln and not at any location downstream from the kiln exit relative to the direction of gas flow; and
 - 2) The by-pass duct diverts a minimum of 10% of kiln off-gas into the duct.
- h) Use of emissions test data to demonstrate compliance and establish operating limits. Compliance with the requirements of this Section must be demonstrated simultaneously by emissions testing or during separate runs under identical operating conditions. Further, data to demonstrate compliance with the CO and HC limits of this Section or to establish alternative CO or HC limits under this Section must be obtained during the time that DRE testing, and where applicable, CDD/CDF testing under subsection (e) above and comprehensive organic emissions testing under subsection (f) above is conducted.
- i) Enforcement. For the purposes of permit enforcement, compliance with the operating requirements specified in the permit (under Section 726.202) will be regarded as compliance with this Section. However, evidence that compliance with those permit conditions is insufficient to ensure compliance with the requirements of this Section is "information" justifying modification or revocation and re-issuance of a permit under 35 Ill. Adm. Code 703.270 et seq.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 726.206 Standards to Control Metals Emissions

- a) General. The owner or operator shall comply with the metals standards provided by subsections (b), (c), (d), (e) or (f) below for each metal listed in subsection (b) below that is present in the hazardous waste at detectable levels using analytical procedures specified in Test Methods for Evaluating Solid Waste, Physical/Chemical Methods, (SW-846), incorporated by reference in 35 Ill. Adm. Code 720.111.
- b) Tier I feed rate screening limits. Feed rate screening limits for metals are specified in Section 726.Appendix A as a function of terrain-adjusted effective stack height (TESH) and terrain and land use in the vicinity of the facility. Criteria for facilities that are not eligible to comply with the screening limits are provided in subsection (b)(7) below.
 - 1) Noncarcinogenic metals. The feed rates of the noncarcinogenic metals in all feed streams, including hazardous waste, fuels and industrial furnace feed stocks must not exceed the screening limits specified in Section 726.Appendix A.
 - A) The feed rate screening limits for antimony, barium, mercury, thallium and silver are based on either:
 - i) An hourly rolling average as defined in Sections 726.200(g) and 726.202(e)(6)(A)(ii); or
 - ii) An instantaneous limit not to be exceeded at any time.
 - B) The feed rate screening limit for lead is based on one of the following:

- i) An hourly rolling average as defined in Sections 726.200(g) and 726.202(e)(6)(A)(ii);
- ii) An averaging period of 2 to 24 hours as defined in Section 726.202(e)(6)(B) with an instantaneous feed rate limit not to exceed 10 times the feed rate that would be allowed on an hourly rolling average basis; or
- iii) An instantaneous limit not to be exceeded at any time.

2) Carcinogenic metals.

- A) The feed rates of carcinogenic metals in all feed streams, including hazardous waste, fuels and industrial furnace feed stocks must not exceed values derived from the screening limits specified in Section 726.Appendix A. The feed rate of each of these metals is limited to a level such that the sum of the ratios of the actual feed rate to the feed rate screening limit specified in Section 726.Appendix A must not exceed 1.0, as provided by the following equation:

$$\sum_{i=1}^n \frac{A_i}{F_i} \leq 1.0$$

~~$$\text{SUM}(A_i/F_i) \leq 1.0$$~~

where:

~~$\text{SUM}(X_i) \sum A_i/F_i$~~ means the sum of the values of ~~X_i~~ A_i/F_i for each metal "i", from i = 1 to n.

n = number of carcinogenic metals

A_i = the actual feed rate to the device for metal "i"

F_i = the feed rate screening limit provided by Section 726.Appendix A for metal "i".

- B) The feed rate screening limits for the carcinogenic metals are based on either:
- i) An hourly rolling average; or
 - ii) An averaging period of 2 to 24 hours, as defined in Section 726.202(e)(6)(B), with an instantaneous feed rate limit not to exceed 10 times the feed rate that would be allowed on an hourly rolling average basis.

3) TESH (terrain adjusted effective stack height).

- A) The TESH is determined according to the following equation:

$$\text{TESH} = H + P - T$$

where:

H = Actual physical stack height (m)

P = Plume rise (in m) as determined from Section 726. Appendix F as a function of stack flow rate and stack gas exhaust temperature.

T = Terrain rise (in m) within five kilometers of the stack.

- B) The stack height (H) must not exceed good engineering practice stack height, as defined in Section 726.200(g).
- C) If the TESH calculated pursuant to subsection (b)(3)(A), above, is not listed in Sections 726. Appendixes A through 726. Appendix C, the values for the nearest lower TESH listed in the table must be used. If the TESH is four meters or less, a value based on four meters must be used.
- 4) Terrain type. The screening limits are a function of whether the facility is located in noncomplex or complex terrain. A device located where any part of the surrounding terrain within 5 kilometers of the stack equals or exceeds the elevation of the physical stack height (H) is considered to be in complex terrain and the screening limits for complex terrain apply. Terrain measurements are to be made from U.S. Geological Survey 7.5-minute topographic maps of the area surrounding the facility.
- 5) Land use. The screening limits are a function of whether the facility is located in an area where the land use is urban or rural. To determine whether land use in the vicinity of the facility is urban or rural, procedures provided in Section 726. Appendixes I ("eye") or Section 726. Appendix J shall be used.
- 6) Multiple stacks. Owners and operators of facilities with more than one on-site stack from a BIF, incinerator or other thermal treatment unit subject to controls of metals emissions under a RCRA permit or interim status controls shall comply with the screening limits for all such units assuming all hazardous waste is fed into the device with the worst-case stack based on dispersion characteristics. The stack with the lowest value of K is the worst-case stack. K is determined from the following equation as applied to each stack:

$$K = H^{\frac{1}{4}} \times V^{\frac{1}{4}} \times T$$

Where:

K = a parameter accounting for relative influence of stack height and plume rise;

H = physical stack height (meters);

V = stack gas flow rate (~~cu~~-m³/sec (cubic meters per second)); and

T = exhaust temperature (degrees K).

- 7) Criteria for facilities not eligible for screening limits. If any criteria below are met, the Tier I (and Tier II) screening limits do not apply. Owners and operators of such facilities shall comply with either the Tier III standards provided by subsection (d) below or with the adjusted Tier I feed rate screening limits provided by subsection (e) below.
- A) The device is located in a narrow valley less than one kilometer wide;
 - B) The device has a stack taller than 20 meters and is located such that the terrain rises to the physical height within one kilometer of the facility;
 - C) The device has a stack taller than 20 meters and is located within five kilometers of a shoreline of a large body of water such as an ocean or large lake;
 - D) The physical stack height of any stack is less than 2.5 times the height of any building within five building heights or five projected building widths of the stack and the distance from the stack to the closest boundary is within five building heights or five projected building widths of the associated building; or
- 8) Implementation. The feed rate of metals in each feedstream must be monitored to ensure that the feed rate screening limits are not exceeded.
- c) Tier II emission rate screening limits. Emission rate screening limits are specified in Section 726. Appendix A as a function of TESH and terrain and land use in the vicinity of the facility. Criteria for facilities that are not eligible to comply with the screening limits are provided in subsection (b)(7) above.
- 1) Noncarcinogenic metals. The emission rates of noncarcinogenic metals must not exceed the screening limits specified in Section 726. Appendix A.
 - 2) Carcinogenic metals. The emission rates of carcinogenic metals must not exceed values derived from the screening limits specified in Section 726. Appendix A. The emission rate of each of these metals is limited to a level such that the sum of the ratios of the actual emission rate to the emission rate screening limit specified in Section 726. Appendix A must not exceed 1.0, as provided by the following equation:

$$\sum_{i=1}^n \frac{A_i}{E_i} \leq 1.0$$

$$\text{SUM}(A_i/E_i) \leq 1.0$$

where:

$\sum_{i=1}^n A_i/E_i$ means the sum of the values of A_i/E_i for each metal "i", from i = 1 to n.

n = number of carcinogenic metals

A_i = the actual emission rate to the device for metal "i"

E_i = the emission rate screening limit provided by Section 726.Appendix A for metal "i".

- 3) Implementation. The emission rate limits must be implemented by limiting feed rates of the individual metals to levels during the trial burn (for new facilities or an interim status facility applying for a permit) or the compliance test (for interim status facilities). The feed rate averaging periods are the same as provided by subsections (b)(1)(A), and (b)(1)(B), and (b)(2)(B) above. The feed rate of metals in each feedstream must be monitored to ensure that the feed rate limits for the feedstreams specified under Sections 726.202 or 726.203 are not exceeded.
- 4) Definitions and limitations. The definitions and limitations provided by subsection (b) above and 726.200(g) for the following terms also apply to the Tier II emission rate screening limits provided by this subsection (c): TESH, good engineering practice stack height, terrain type, land use and criteria for facilities not eligible to use the screening limits.
- 5) Multiple stacks.
 - A) Owners and operators of facilities with more than one on-site stack from a BIF, incinerator or other thermal treatment unit subject to controls on metals emissions under a RCRA permit or interim status controls shall comply with the emissions screening limits for any such stacks assuming all hazardous waste is fed into the device with the worst-case stack based on dispersion characteristics.
 - B) The worst-case stack is determined by procedures provided in subsection (b)(6) above.
 - C) For each metal, the total emissions of the metal from those stacks must not exceed the screening limit for the worst-case stack.
- d) Tier III site-specific risk assessment. The requirements of this subsection apply to facilities complying with either the Tier III or Adjusted Tier I except where specified otherwise.
 - 1) General. Conformance with the Tier III metals controls must be demonstrated by emissions testing to determine the emission rate for each metal. In addition, conformance with either Tier III or Adjusted Tier I metals controls must be demonstrated by air dispersion modeling to predict the maximum annual average off-site ground level concentration

for each metal and a demonstration that acceptable ambient levels are not exceeded.

- 2) Acceptable ambient levels. Sections 726. Appendices D and 726. Appendix E list the acceptable ambient levels for purposes of this Subpart. Reference air concentrations (RACs) are listed for the noncarcinogenic metals and 1×10^{-5} RSDs are listed for the carcinogenic metals. The RSD for a metal is the acceptable ambient level for that metal provided that only one of the four carcinogenic metals is emitted. If more than one carcinogenic metal is emitted, the acceptable ambient level for the carcinogenic metals is a fraction of the RSD as described in subsection (d)(3) below.
- 3) Carcinogenic metals. For the carcinogenic metals the sum of the ratios of the predicted maximum annual average off-site ground level concentrations (except that on-site concentrations must be considered if a person resides on site) to the RSD for all carcinogenic metals emitted must not exceed 1.0 as determined by the following equation:

$$\sum_{i=1}^n \frac{P_i}{R_i} \leq 1.0$$

$$\text{SUM}(P_i/R_i) \leq 1.0$$

where:

$\text{SUM}(P_i/R_i) = \sum P_i/R_i$ means the sum of the values of P_i/R_i for each metal "i", from $i = 1$ to n .

n = number of carcinogenic metals

P_i = the predicted ambient concentration for metal i .

R_i = the RSD for metal i .

- 4) Noncarcinogenic metals. For the noncarcinogenic metals, the predicted maximum annual average off-site ground level concentration for each metal must not exceed the RAC.
- 5) Multiple stacks. Owners and operators of facilities with more than one on-site stack from a BIF, incinerator or other thermal treatment unit subject to controls on metals emissions under a RCRA permit or interim status controls shall conduct emissions testing (except that facilities complying with Adjusted Tier I controls need not conduct emissions testing) and dispersion modeling to demonstrate that the aggregate emissions from all such on-site stacks do not result in an exceedance of the acceptable ambient levels.
- 6) Implementation. Under Tier III, the metals controls must be implemented by limiting feed rates of the individual metals to levels during the trial burn (for new facilities or an interim status facility applying for a permit) or the

compliance test (for interim status facilities). The feed rate averaging periods are the same as provided by subsections (b)(1)(A), ~~and (b)(1)(B)~~, and (b)(2)(B) above. The feed rate of metals in each feedstream must be monitored to ensure that the feed rate limits for the feedstreams specified under Sections 726.202 or 726.203 are not exceeded.

- e) Adjusted Tier I feed rate screening limits. The owner or operator may adjust the feed rate screening limits provided by Section 726.Appendix A to account for site-specific dispersion modeling. Under this approach, the adjusted feed rate screening limit for a metal is determined by back-calculating from the acceptable ambient levels provided by Sections 726.Appendixes D and 726.Appendix E using dispersion modeling to determine the maximum allowable emission rate. This emission rate becomes the adjusted Tier I feed rate screening limit. The feed rate screening limits for carcinogenic metals are implemented as prescribed in subsection (b)(2) above.
- f) Alternative implementation approaches.
- 1) Pursuant to subsection (f)(2) below, the Agency shall approve on a case-by-case basis approaches to implement the Tier II or Tier III metals emission limits provided by subsections (c) or (d) above, alternative to monitoring the feed rate of metals in each feedstream.
 - 2) The emission limits provided by subsection (d) above must be determined as follows:
 - A) For each noncarcinogenic metal, by back-calculating from the RAC provided in Section 726.Appendix D to determine the allowable emission rate for each metal using the dilution factor for the maximum annual average ground level concentration predicted by dispersion modeling in conformance with subsection (h) below; and
 - B) For each carcinogenic metal by:
 - i) Back-calculating from the RSD provided in Section 726.Appendix E to determine the allowable emission rate for each metal if that metal were the only carcinogenic metal emitted using the dilution factor for the maximum annual average ground level concentration predicted by dispersion modeling in conformance with subsection (h) below; and
 - ii) If more than one carcinogenic metal is emitted, selecting an emission limit for each carcinogenic metal not to exceed the emission rate determined by subsection (f)(2)(B)(i) above, such that the sum for all carcinogenic metals of the ratios of the selected emission limit to the emission rate determined by that subsection does not exceed 1.0.
- g) Emission testing.
- 1) General. Emission testing for metals must be conducted

using the Multiple Metals Train as described in Section 726. Appendix I (~~"eye"~~).

- 2) Hexavalent chromium. Emissions of chromium are assumed to be hexavalent chromium unless the owner or operator conducts emissions testing to determine hexavalent chromium emissions using procedures prescribed in Section 726. Appendix I (~~"eye"~~).
- h) Dispersion modeling. Dispersion modeling required under this Section must be conducted according to methods recommended in ~~Section 726. Appendix J~~ 40 CFR 51, appendix W ("Guideline on Air Quality Models (Revised)" (1986) and its supplements), the "Hazardous Waste Combustion Air Quality Screening Procedure" described in Section 726. Appendix I (~~"eye"~~), or in "EPA SCREEN Screening Procedure" as described in Screening Procedures for Estimating the Air Quality Impact of Stationary Sources, Revised" (~~the latter document is incorporated by reference, see in~~ 35 Ill. Adm. Code 720.111) to predict the maximum annual average off-site ground level concentration. However, on-site concentrations must be considered when a person resides on-site.
- i) Enforcement. For the purposes of permit enforcement, compliance with the operating requirements specified in the permit (under Section 726.202) will be regarded as compliance with this Section. However, evidence that compliance with those permit conditions is insufficient to ensure compliance with the requirements of this Section is "information" justifying modification or revocation and re-issuance of a permit under 35 Ill. Adm. Code 703.270 et seq.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 726.212 Regulation of Residues

A residue derived from the burning or processing of hazardous waste in a BIF is not excluded from the definition of a hazardous waste under 35 Ill. Adm. Code 721.104(b)(4), (b)(7) or (b)(8) unless the device and the owner or operator meet the following requirements:

- a) The device meets the following criteria:
 - 1) Boilers. Boilers must burn at least 50% coal on a total heat input or mass basis, whichever results in the greater mass feed rate of coal;
 - 2) Ore or mineral furnaces. Industrial furnaces subject to 35 Ill. Adm. Code 721.104(b)(7) must process at least 50% by weight normal, nonhazardous raw materials;
 - 3) Cement kilns. Cement kilns must process at least 50% by weight normal cement-production raw materials;
- b) The owner or operator demonstrates that the hazardous waste does not significantly affect the residue by demonstrating conformance with either of the following criteria:
 - 1) Comparison of waste-derived residue with normal residue. The waste-derived residue must not contain 35 Ill. Adm. Code 721. Appendix H constituents (toxic constituents) that could reasonably be attributable to the hazardous waste at concentrations significantly higher than in residue generated without burning or processing of hazardous waste,

using the following procedure. Toxic compounds that could reasonably be attributable to burning or processing the hazardous waste (constituents of concern) include toxic constituents in the hazardous waste, and the organic compounds listed in 35 Ill. Adm. Code 721. Appendix H that may be PICs. Sampling and analyses must be in conformance with procedures prescribed in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, incorporated by reference in 35 Ill. Adm. Code 720.111(a).

- A) Normal residue. Concentrations of toxic constituents of concern in normal residue must be determined based on analyses of a minimum of 10 samples representing a minimum of 10 days of operation. Composite samples may be used to develop a sample for analysis provided that the compositing period does not exceed 24 hours. The upper tolerance limit (at 95% confidence with a 95% proportion of the sample distribution) of the concentration in the normal residue shall be considered the statistically-derived concentration in the normal residue. If changes in raw materials or fuels reduce the statistically-derived concentrations of the toxic constituents of concern in the normal residue, the statistically-derived concentrations must be revised or statistically-derived concentrations of toxic constituents in normal residue must be established for a new mode of operation with the new raw material or fuel. To determine the upper tolerance limit in the normal residue, the owner or operator shall use statistical procedures prescribed in "Statistical Methodology for Beville Residue Determinations" in Section 726. Appendix I-("eye").
 - B) Waste-derived residue. Waste derived residue must be sampled and analyzed as often as necessary to determine whether the residue generated during each 24-hour period has concentrations of toxic constituents that are higher than the concentrations established for the normal residue under subsection (b)(1)(A) above. If so, hazardous waste burning has significantly affected the residue and the residue is not excluded from the definition of "hazardous waste". Concentrations of toxic constituents in waste-derived residue must be determined based on analysis of one or more samples obtained over a 24-hour period. Multiple samples may be analyzed, and multiple samples may be taken to form a composite sample for analysis provided that the sampling period does not exceed 24 hours. If more than one sample is analyzed to characterize waste-derived residues generated over a 24-hour period, the concentration of each toxic constituent must be the arithmetic mean of the concentrations in the samples. No results can be disregarded; or
- 2) Comparison of waste-derived residue concentrations with health-based limits.
 - A) Nonmetal constituents. The concentrations of each nonmetal toxic constituents of concern (specified in subsection (b)(1) above) in the waste-derived residue must not exceed the health-based levels specified in

Section 726.Appendix G, or the level of detection (using analytical procedures prescribed in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, incorporated by reference in 35 Ill. Adm. Code 720.111), whichever is higher. If a health-based limit for a constituent of concern is not listed in Section 726.Appendix G, then a limit of 0.002 $\mu\text{g}/\text{kg}$ or the level of detection (using analytical procedures prescribed in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, incorporated by reference in 35 Ill. Adm. Code 720.111), whichever is higher, must be used. The levels specified in Section 726.Appendix G (and the default level of 0.002 $\mu\text{g}/\text{kg}$ or the level of detection for constituents, as identified in Note 1 of Section 726.Appendix G) are administratively stayed under the condition, for those constituents specified in subsection (b)(1) above, that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in 35 Ill. Adm. Code 728.143 and 728.Table B for F039 nonwastewaters. In complying with those alternative levels, if an owner or operator is unable to detect a constituent despite documenting use of the best good-faith efforts, as defined by applicable U.S. EPA guidance and standards, the owner or operator is deemed to be in compliance for that constituent. Until U.S. EPA develops new guidance or standards, the owner or operator may demonstrate such good-faith efforts by achieving a detection limit for the constituent that does not exceed an order of magnitude above (ten times) the level provided by 35 Ill. Adm. Code 728.143 and 728.Table B for F039 nonwastewaters. The stay will remain in effect until further rule-making action is taken; and

- B) Metal constituents. The concentration of metals in an extract obtained using the TCLP test must not exceed the levels specified in Section 726.Appendix G; and
 - C) Sampling and analysis. Wastewater-derived residue must be sampled and analyzed as often as necessary to determine whether the residue generated during each 24 hour period has concentrations of toxic constituents ~~which~~that are higher than the health-based levels. Concentrations of concern in the wastewater-derived residue must be determined based on analysis of one or more samples obtained over a 24-hour period. Multiple samples may be analyzed, and multiple samples may be taken to form a composite for analysis provided that the sampling period does not exceed 24 hours. If more than one sample is analyzed to characterize wastewater-derived residues generated over a 24 hour period, the concentration of each toxic constituent is the arithmetic mean of the concentrations of the samples. No results can be disregarded; and
- c) Records sufficient to document compliance with the provisions of this Section must be retained until closure of the BIF unit. At a minimum, the following must be recorded:

- 1) Levels of constituents in 35 Ill. Adm. Code 721.Appendix H that are present in waste-derived residues;
- 2) If the waste-derived residue is compared with normal residue under subsection (b)(1) above:
 - A) The levels of constituents in 35 Ill. Adm. Code 721.Appendix H that are present in normal residues; and
 - B) Data and information, including analyses of samples as necessary, obtained to determine if changes in raw materials or fuels would reduce the concentration of toxic constituents of concern in the normal residue.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 726.Appendix G Health-Based Limits for Exclusion of Waste-Derived Residues

BOARD NOTE 1: Under Section 726.212(b)(2)(A), the health-based concentration limits for 35 Ill. Adm. Code 721.Appendix H constituents for which a health-based concentration is not provided below is 0.002 µg/kg (0.000002E-06 mg/kg).

NOTE 2: The levels specified in this Section and the default level of 0.002 µg/kg (0.000002 mg/kg) or the level of detection for constituents, as identified in Note 1, are administratively stayed under the condition, for those constituents specified in Section 726.212(b)(1), that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in 35 Ill. Adm. Code 728.143 and 728.Table B for F039 nonwastewaters. See Section 726.212(b)(2)(A).

Metals-TCLP Extract Concentration Limits

Constituent	CAS No.	Concentration limits (mg/L)
Antimony	7440-36-0	1.E+00
Arsenic	7440-38-2	5.E+00
Barium	7440-39-3	100.E+02
Beryllium	7440-41-7	0.007E-03
Cadmium	7440-43-9	1.E+00
Chromium	7440-47-3	5.E+00
Lead	7439-92-1	5.E+00
Mercury	7439-97-6	0.2E-01
Nickel	7440-02-0	70.E+01
Selenium	7782-49-2	1.E+00
Silver	7440-22-4	5.E+00
Thallium	7440-28-0	7.E+00

Nonmetals-Residue Concentration Limits

Constituent	CAS No.	Concentration limits for residues (mg/kg)
Acetonitrile	75-05-8	0.2E-01
Acetophenone	98-86-2	4.E+00
Acrolein	107-02-8	0.5E-01

Acrylamide	79-06-1	0.0002E-04
Acrylonitrile	107-13-1	0.0007E-04
Aldrin	309-00-2	0.00002E-
		05
Allyl alcohol	107-18-6	0.2E-01
Aluminum phosphide	20859-73-8	0.01E-02
Aniline	62-53-3	0.06E-02
Barium cyanide	542-62-1	1.E+00
Benz(a)anthracene	56-55-3	0.0001E-04
Benzene	71-43-2	0.005E-03
Benzidine	92-87-5	0.000001E-
		06
Bis(2-chloroethyl) ether	111-44-4	0.0003E-04
Bis(chloromethyl) ether	542-88-1	0.000002E-
		06
Bis(2-ethylhexyl) phthalate	117-81-7	30.E+01
Bromoform	75-25-2	0.7E-01
Calcium cyanide	592-01-8	0.000001E-
		06
Carbon disulfide	75-15-0	4.E+00
Carbon tetrachloride	56-23-5	0.005E-03
Chlordane	57-74-9	0.0003E-04
Chlorobenzene	108-90-7	1.E+00
Chloroform	67-66-3	0.06E-02
Copper cyanide	544-92-3	0.2E-01
Cresols (Cresylic acid)	1319-77-3	2.E+00
Cyanogen	460-19-5	1.E+00
DDT	50-29-3	0.001E-03
Dibenz(a, h)-anthracene	53-70-3	0.000007E-
		06
1,2-Dibromo-3-chloropropane	96-12-8	0.00002E-
		05
p-Dichlorobenzene	106-46-7	0.07.5E-02
Dichlorodifluoromethane	75-71-8	7.E+00
1,1-Dichloroethylene	75-35-4	0.005E-03
2,4-Dichlorophenol	120-83-2	0.1E-01
1,3-Dichloropropene	542-75-6	0.001E-03
Dieldrin	60-57-1	0.00002E-
		05
Diethyl phthalate	84-66-2	30.E+01
Diethylstilbestrol	56-53-1	
		0.0000007E-07
Dimethoate	60-51-5	0.03E-02
2,4-Dinitrotoluene	121-14-2	0.0005E-04
Diphenylamine	122-39-4	0.9E-01
1,2-Diphenylhydrazine	122-66-7	0.0005E-04
Endosulfan	115-29-7	0.002E-03
Endrin	72-20-8	0.0002E-04
Epichlorohydrin	106-89-8	0.04E-02
Ethylene dibromide	106-93-4	
		0.0000004E-07
Ethylene oxide	75-21-8	0.0003E-04
Fluorine	7782-41-4	4.E+00
Formic acid	64-18-6	70.E+01
Heptachlor	76-44-8	0.00008E-
		05
Heptachlor epoxide	1024-57-3	0.00004E-
		05
Hexachlorobenzene	118-74-1	0.0002E-04
Hexachlorobutadiene	87-68-3	0.005E-03
Hexachlorocyclopentadiene	77-47-4	0.2E-01
Hexachlorodibenzo-p-dioxins	19408-74-3	

		<u>0.00000006E-</u>
		08
Hexachloroethane	67-72-1	<u>0.03E-02</u>
Hydrazine	302-01-1	<u>0.0001E-04</u>
Hydrogen cyanide	74-90-8	<u>0.00007E-</u>
		05
Hydrogen sulfide	7783-06-4	<u>0.000001E-</u>
		06
Isobutyl alcohol	78-83-1	<u>10.E+01</u>
Methomyl	16752-77-5	<u>1.E+00</u>
Methoxychlor	72-43-5	<u>0.1E-01</u>
3-Methylcholanthrene	56-49-5	<u>0.00004E-</u>
		05
4,4'-Methylenebis (2-chloroaniline)	101-14-4	<u>0.002E-03</u>
Methylene chloride	75-09-2	<u>0.05E-02</u>
Methyl ethyl ketone (MEK)	78-93-3	<u>2.E+00</u>
Methyl hydrazine	60-34-4	<u>0.0003E-04</u>
Methyl parathion	298-00-0	<u>0.02E-02</u>
Naphthalene	91-20-3	<u>10.E+01</u>
Nickel cyanide	557-19-7	<u>0.7E-01</u>
Nitric oxide	10102-43-9	<u>4.E+00</u>
Nitrobenzene	98-95-3	<u>0.02E-02</u>
N-Nitrosodi-n-butylamine	924-16-3	<u>0.00006E-</u>
		05
N-Nitrosodiethylamine	55-18-5	<u>0.000002E-</u>
		06
N-Nitroso-N-methylurea	684-93-5	
		<u>0.0000001E-07</u>
N-Nitrosopyrrolidine	930-55-2	<u>0.0002E-04</u>
Pentachlorobenzene	608-93-5	<u>0.03E-02</u>
Pentachloronitrobenzene (PCNB)	82-68-8	<u>0.1E-01</u>
Pentachlorophenol	87-86-5	<u>1.E+00</u>
Phenol	108-95-2	<u>1.E+00</u>
Phenylmercury acetate	62-38-4	<u>0.003E-03</u>
Phosphine	7803-51-2	<u>0.01E-02</u>
Polychlorinated biphenyls, N.O.S	1336-36-3	<u>0.00005E-</u>
		05
Potassium cyanide	151-50-8	<u>2.E+00</u>
Potassium silver cyanide	506-61-6	<u>7.E+00</u>
Pronamide	23950-58-5	<u>3.E+00</u>
Pyridine	110-86-1	<u>0.04E-02</u>
Reserpine	50-55-5	<u>0.00003E-</u>
		05
Selenourea	630-10-4	<u>0.2E-01</u>
Silver cyanide	506-64-9	<u>4.E+00</u>
Sodium cyanide	143-33-9	<u>1.E+00</u>
Strychnine	57-24-9	<u>0.01E-02</u>
1,2,4,5-Tetrachlorobenzene	95-94-3	<u>0.01E-02</u>
1,1,2,2-tetrachloroethane	79-34-5	<u>0.002E-03</u>
Tetrachloroethylene	127-18-4	<u>0.7E-01</u>
2,3,4,6-Tetrachlorophenol	58-90-2	<u>0.01E-02</u>
Tetraethyl lead	78-00-2	<u>0.000004E-</u>
		06
Thiourea	62-56-6	<u>0.0002E-04</u>
Toluene	108-88-3	<u>10.E+01</u>
Toxaphene	8001-35-2	<u>0.005E-03</u>
1,1,2-Trichloroethane	79-00-5	<u>0.006E-03</u>
Trichloroethylene	79-01-6	<u>0.005E-03</u>
Trichloromonofluoromethane	75-69-4	<u>10.E+01</u>
2,4,5-Trichlorophenol	95-95-4	<u>4.E+00</u>
2,4,6-Trichlorophenol	88-06-2	<u>4.E+00</u>
Vanadium pentoxide	1314-62-1	<u>0.7E-01</u>

Vinyl chloride

75-01-4

0.002E-03

(Source: Amended at 18 Ill. Reg. _____, effective _____)

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE G: WASTE DISPOSAL
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER c: HAZARDOUS WASTE OPERATING REQUIREMENTS

PART 728
 LAND DISPOSAL RESTRICTIONS

SUBPART A: GENERAL

Section	
728.101	Purpose, Scope and Applicability
728.102	Definitions
728.103	Dilution Prohibited as a Substitute for Treatment
728.104	Treatment Surface Impoundment Exemption
728.105	Procedures for case-by-case Extensions to an Effective Date
728.106	Petitions to Allow Land Disposal of a Waste Prohibited under Subpart C
728.107	Waste Analysis and Recordkeeping
728.108	Landfill and Surface Impoundment Disposal Restrictions (Repealed)
728.109	Special Rules for Characteristic Wastes

SUBPART B: SCHEDULE FOR LAND DISPOSAL PROHIBITION
 AND ESTABLISHMENT OF TREATMENT STANDARDS

Section	
728.110	First Third
728.111	Second Third
728.112	Third Third
728.113	Newly Listed Wastes
728.114	Surface Impoundment exemptions

SUBPART C: PROHIBITION ON LAND DISPOSAL

Section	
728.130	Waste Specific Prohibitions -- Solvent Wastes
728.131	Waste Specific Prohibitions -- Dioxin-Containing Wastes
728.132	Waste Specific Prohibitions -- California List Wastes
728.133	Waste Specific Prohibitions -- First Third Wastes
728.134	Waste Specific Prohibitions -- Second Third Wastes
728.135	Waste Specific Prohibitions -- Third Third Wastes
728.136	Waste Specific Prohibitions -- Newly Listed Wastes
728.137	Waste Specific Prohibitions -- Ignitable and Corrosive Characteristic Wastes Whose Treatment Standards Were Vacated
728.139	Statutory Prohibitions

SUBPART D: TREATMENT STANDARDS

Section	
728.140	Applicability of Treatment Standards
728.141	Treatment Standards Expressed as Concentrations in Waste Extract
728.142	Treatment Standards Expressed as Specified Technologies
728.143	Treatment Standards expressed as Waste Concentrations
728.144	Adjustment of Treatment Standard
728.145	Treatment Standards for Hazardous Debris
728.146	Alternative Treatment Standards Based on HTMR

SUBPART E: PROHIBITIONS ON STORAGE

Section	
728.150	Prohibitions on Storage of Restricted Wastes

728.Appendix A	Toxicity Characteristic Leaching Procedure (TCLP)
728.Appendix B	Treatment Standards (As concentrations in the Treatment Residual Extract)
728.Appendix C	List of Halogenated Organic Compounds
728.Appendix D	Organometallic Lab Packs
728.Appendix E	Organic Lab Packs
728.Appendix F	Technologies to Achieve Deactivation of Characteristics
728.Appendix G	Federal Effective Dates
728.Appendix H	National Capacity LDR Variances for UIC Wastes
728.Appendix I	EP Toxicity Test Method and Structural Integrity Test
728.Table A	Constituent Concentrations in Waste Extract (CCWE)
728.Table B	Constituent Concentrations in Wastes (CCW)
728.Table C	Technology Codes and Description of Technology-Based Standards
728.Table D	Technology-Based Standards by RCRA Waste Code
728.Table E	Standards for Radioactive Mixed Waste
728.Table F	Alternative Treatment Standards for Hazardous Debris
728.Table G	Alternative Treatment Standards Based on HMTR
728.Table H	Wastes Excluded from CCW Treatment Standards

AUTHORITY: Implementing Section 22.4 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1991, ch. 111½, pars. 1022.4 and 1027 [415 ILCS 5/22.4 and 27]).

SOURCE: Adopted in R87-5 at 11 Ill. Reg. 19354, effective November 12, 1987; amended in R87-39 at 12 Ill. Reg. 13046, effective July 29, 1988; amended in R89-1 at 13 Ill. Reg. 18403, effective November 13, 1989; amended in R89-9 at 14 Ill. Reg. 6232, effective April 16, 1990; amended in R90-2 at 14 Ill. Reg. 14470, effective August 22, 1990; amended in R90-10 at 14 Ill. Reg. 16508, effective September 25, 1990; amended in R90-11 at 15 Ill. Reg. 9462, effective June 17, 1991; amended in R92-10 at 17 Ill. Reg. 5727, effective March 26, 1993; amended in R93-4 at 17 Ill. Reg. 20692, effective November 22, 1993; amended in R93-16 at 18 Ill. Reg. 6799, effective April 26, 1994; amended in R94-7 at _____ Ill. Reg. _____, effective _____.

SUBPART A: GENERAL

Section 728.107 Waste Analysis and Recordkeeping

- a) Except as specified in Section 728.132, where a generator's waste is listed in 35 Ill. Adm. Code 721.Subpart D, the generator shall test its waste, or test an extract using the ~~test method described in 35 Ill. Adm. Code 721.Appendix B~~ Toxicity Characteristic Leaching Procedure, Method 1311, in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111, or use knowledge of the waste, to determine if the waste is restricted from land disposal under this Part. Except as specified in Section 728.132, if a generator's waste exhibits one or more of the characteristics set out at 35 Ill. Adm. Code 721.Subpart C, the generator shall test an extract using the ~~test method described in Section 728.Appendix I~~ EP Toxicity Test, Method 1310, in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111, or use knowledge of the waste, to determine if the waste is restricted from land disposal under this Part. If the generator determines that its waste displays the characteristic of ignitability (D001) (and is not in the High TOC Ignitable Liquids Subcategory or is not treated by INCIN, FSUBS, or RORGS of Section 728.Table C of this Part), or

the characteristic or corrosivity (D002), and is prohibited under Section 728.137, the generator shall determine what underlying hazardous constituents (as defined in Section 728.102 of this Part), are reasonably expected to be present in the D001 or D002 waste.

- 1) If a generator determines that the generator is managing a restricted waste under this Part and determines that the waste does not meet the applicable treatment standards set forth in Subpart D of this Part or exceeds the applicable prohibition levels set forth in Section 728.132 or 728.139, with each shipment of waste the generator shall notify the treatment or storage facility in writing of the appropriate treatment standard set forth in Subpart D of this Part and any applicable prohibition levels set forth in Section 728.132 or 728.139. The notice must include the following information:
 - A) U.S. EPA hazardous waste number;
 - B) The corresponding treatment standards for wastes F001 through F005, F039, wastes prohibited pursuant to Section 728.132 or Section 3004(d) of the Resource Conservation and Recovery Act, referenced in Section 728.139. Treatment standards for all other restricted wastes must either be included, or be referenced by including on the notification the applicable wastewater (as defined in Section 728.102(f)) or nonwastewater (as defined in Section 728.102(d)) category, the applicable subcategory made within a waste code based on waste-specific criteria (such as D003 reactive cyanides), and the Sections and subsections where the applicable treatment standard appears. Where the applicable treatment standards are expressed as specified technologies in Section 728.142, the applicable five-letter treatment code found in Section 728.Table C (e.g., INCIN, WETOX) also must be listed on the notification.
 - C) The manifest number associated with the shipment of waste; and
 - D) For hazardous debris, the contaminants subject to treatment as provided by Section 728.145(b) and the following statement: "This hazardous debris is subject to the alternative treatment standards of 35 Ill. Adm. Code 728.145; and
 - E) Waste analysis data, where available.
- 2) If a generator determines that the generator is managing a restricted waste under this Part, and determines that the waste can be land disposed without further treatment, with each shipment of waste the generator shall submit, to the treatment, storage or land disposal facility, a notice and a certification stating that the waste meets the applicable treatment standards set forth in Subpart D of this Part and the applicable prohibition levels set forth in Section 728.132 or 728.139. Generators of hazardous debris that is excluded from the definition of hazardous waste under 35 Ill. Adm. Code 721.103(c), 35 Ill. Adm. Code 728.103(f)(2) and 35 Ill. Adm. Code 720.122 (i.e. debris that is

delisted), however are not subject to these notification and certification requirements.

- A) The notice must include the following information:
- i) U.S. EPA hazardous waste number;
 - ii) The corresponding treatment standards for wastes F001 through F005, F039 and wastes prohibited pursuant to Section 728.132 or Section 3004(d) of the Resource Conservation and Recovery Act, referenced in Section 728.139. Treatment standards for all other restricted wastes must either be included or referenced by including on the notification the applicable wastewater or nonwastewater (as defined in Section 728.102) category, the applicable subdivisions made within a waste code based on waste-specific criteria (such as D003, reactive cyanides), and the Section and subsection where the applicable treatment standard appears. Where the applicable treatment standards are expressed as specified technologies in Section 728.142, the applicable five-letter treatment code found in Section 728.Table C (e.g., INCIN, WETOX) also must be listed on the notification.
 - iii) The manifest number associated with the shipment of waste;
 - iv) Waste analysis data, where available
- B) The certification must be signed by an authorized representative and must state the following:

I certify under penalty of law that I personally have examined and am familiar with the waste through analysis and testing or through knowledge of the waste to support this certification that the waste complies with the treatment standards specified in 35 Ill. Adm. Code 728.Subpart D and all applicable prohibitions set forth in 35 Ill. Adm. Code 728.132, 728.139 or Section 3004(d) of the Resource Conservation and Recovery Act. I believe that the information I submitted is true, accurate and complete. I am aware that there are significant penalties for submitting a false certification, including the possibility of a fine and imprisonment.

- 3) If a generator's waste is subject to an exemption from a prohibition on the type of land disposal method utilized for the waste (such as, but not limited to, a case-by-case extension under Section 728.105, an exemption under Section 728.106, an extension under Section 728.101(c)(3) or a nationwide capacity variance under 40 CFR 268.Subpart C (19892), with each shipment of waste, the generator shall submit a notice with the waste to the facility receiving the generator's waste, stating that the waste is not prohibited from land disposal. The notice must include the following information:

- A) U.S. EPA hazardous waste number:
 - B) The corresponding treatment standards for wastes F001 through F005, F039 and wastes prohibited pursuant to Section 728.132 or Section 3004(d) of the Resource Conservation and Recovery Act, referenced in Section 728.139. Treatment standards for all other restricted wastes must either be included or be referenced by including on the notification the , and the Section and subsection where the applicable treatment standard appears. Where the applicable treatment standards are expressed as specified technologies in Section 728.142, the applicable five-letter treatment code found in Section 728.Table C (e.g., INCIN, WETOX) also must be listed on the notification.
 - C) The manifest number associated with the shipment of waste;
 - D) Waste analysis data, where available;
 - E) For hazardous debris, the contaminants subject to treatment as provided by Section 728.145(b) and the following statement: "This hazardous debris is subject to the alternative treatment standards of 35 Ill. Adm. Code 728.145"; and
 - F) The date the waste is subject to the prohibitions.
- 4) If a generator is managing a prohibited waste in tanks or containers regulated under 35 Ill. Adm. Code 722.134, and is treating such waste in such tanks, containers or containment buildings to meet applicable treatment standards under Subpart D of this Part, the generator shall develop and follow a written waste analysis plan ~~which that~~ describes the procedures the generator will carry out to comply with the treatment standards. The plan must be kept on-site in the generator's records, and the following requirements must be met:
- A) The waste analysis plan must be based on a detailed chemical and physical analysis of a representative sample of the prohibited wastes being treated, and contain all information necessary to treat the wastes in accordance with the requirements of this Part, including the selected testing frequency.
 - B) Such plan must be filed with the Agency a minimum of 30 days prior to the treatment activity, with delivery verified.
 - C) Wastes shipped off-site pursuant to this subsection must comply with the notification requirements of Section 728.107(a)(2).
- 5) If a generator determines whether the waste is restricted based solely on the generator's knowledge of the waste, the generator shall retain all supporting data used to make this determination on-site in the generator's files. If a generator determines whether the waste is restricted based on testing the waste or an extract developed using the test method described in Section 728.Appendix A, the generator

shall retain all waste analysis data on site in the generator's files.

- 6) If a generator determines, subsequent to the time of generation, that the generator is managing a restricted waste ~~which~~that is excluded from the definition of hazardous or solid waste or exempt from regulation as a RCRA hazardous waste under 35 Ill. Adm. Code 721.102 through 721.106, the generator shall place, in the facility's file, a one-time notice stating such generation, subsequent exclusion from the definition of hazardous or solid waste or exemption from regulation as a RCRA hazardous waste, and the disposition of the waste.
- 7) Generators shall retain on-site a copy of all notices, certifications, demonstrations, waste analysis data and other documentation produced pursuant to this Section for at least five years from the date that the waste that is the subject of such documentation was last sent to on-site or off-site treatment storage or disposal. The five year record retention period is automatically extended during the course of any unresolved enforcement action regarding the regulated activity or as requested by the Agency. The requirements of this subsection apply to solid wastes even when the hazardous characteristic is removed prior to disposal, or when the waste is excluded from the definition of hazardous or solid waste under 35 Ill. Adm. Code 721.102 through 721.106, or exempted from regulation as a RCRA hazardous waste subsequent to the point of generation.
- 8) If a generator is managing a lab pack that contains wastes identified in Section 728.Appendix D and wishes to use the alternative treatment standard under Section 728.142, with each shipment of waste the generator shall submit a notice to the treatment facility in accordance with subsection (a)(1) above. The generator shall also comply with the requirements in subsections (a)(5) and (a)(6) above, and shall submit the following certification, which must be signed by an authorized representative:

I certify under penalty of law that I personally have examined and am familiar with the waste and that the lab pack contains only the wastes specified in 35 Ill. Adm. Code 728.Appendix D or solid wastes not subject to regulation under 35 Ill. Adm. Code 721. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine or imprisonment.

- 9) If a generator is managing a lab pack that contains organic wastes specified in Section 728.Appendix E and wishes to use the alternate treatment standards under Section 728.142, with each shipment of waste the generator shall submit a notice to the treatment facility in accordance with subsection (a)(1) above. The generator also shall comply with the requirements in subsections (a)(5) and (a)(6) above, and shall submit the following certification ~~which~~that must be signed by an authorized representative:

I certify under penalty of law that I personally have examined and am familiar with the waste through analysis and testing or through knowledge of the waste

and that the lab pack contains only organic waste specified in 35 Ill. Adm. Code 728. Appendix E or solid wastes not subject to regulation under 35 Ill. Adm. Code 721. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine or imprisonment.

- 10) Small quantity generators with tolling agreements pursuant to 35 Ill. Adm. Code 722.120(e) shall comply with the applicable notification and certification requirements of subsection (a) above for the initial shipment of the waste subject to the agreement. Such generators shall retain on-site a copy of the notification and certification, together with the tolling agreement, for at least three years after termination or expiration of the agreement. The three-year record retention period is automatically extended following notification pursuant to Section 31(d) of the Environmental Protection Act, until either any subsequent enforcement action is resolved, or the Agency notifies the generator documents need no be retained.
- b) Treatment facilities shall test their wastes according to the frequency specified in their waste analysis plans as required by 35 Ill. Adm. Code 724.113 or 725.113. Such testing must be performed as provided in subsections (b)(1), (b)(2) and (b)(3) below.
- 1) For wastes with treatment standards expressed as concentrations in the waste extract (Section 728.141), the owner or operator of the treatment facility shall test the treatment residues or an extract of such residues developed using the test method described in Section 728. Appendix A to assure that the treatment residues or extract meet the applicable treatment standards.
 - 2) For wastes prohibited under Section 728.132 or 728.139 ~~which that~~ are not subject to any treatment standards under Subpart D of this Part, the owner or operator of the treatment facility shall test the treatment residues according to the generator testing requirements specified in Section 728.132 to assure that the treatment residues comply with the applicable prohibitions.
 - 3) For wastes with treatment standards expressed as concentrations in the waste (Section 728.143), the owner or operator of the treatment facility shall test the treatment residues (not an extract of such residues) to assure that the treatment residues meet the applicable treatment standards.
 - 4) A notice must be sent with each waste shipment to the land disposal facility ~~which that~~ includes the following information, except that debris excluded from the definition of the hazardous waste under Section 728.103(f)(2) (i.e., debris treated by an extraction or destruction technology provided by Section 728. Table F, and debris that is delisted) is subject to the notification and certification requirements of subsection (d) below rather than these notification requirements:
 - A) U.S. EPA hazardous waste number;

- B) The corresponding treatment standards for wastes F001 through F005, F039, wastes prohibited pursuant to Section 728.132 or Section 3004(d) of the Resource Conservation and Recovery Act, referenced in Section 728.139, and for underlying hazardous constituents (as defined in Section 728.102 of this Part), in D001 and D002 wastes if those wastes are prohibited under Section 728.137 of this Part. Treatment standards for all other restricted wastes must either be included, or be referenced by including on the notification the applicable wastewater (as defined in Section 728.102(f)) or nonwastewater (as defined in Section 728.102(d)) category, the applicable subdivisions made within a waste code based on waste-specific criteria (such as D003 reactive cyanides), and the Sections and subsections where the applicable treatment standard appears. Where the applicable treatment standards are expressed as specified technologies in Section 728.142, the applicable five-letter treatment code found in Section 728.Table C (e.g., INCIN, WETOX) also must be listed on the notification.
- C) The manifest number associated with the shipment of waste; and
- D) Waste analysis data, where available.
- 5) The treatment facility shall submit a certification with each shipment of waste or treatment residue of a restricted waste to the land disposal facility stating that the waste or treatment residue has been treated in compliance with the treatment standards specified in Subpart D of this Part and the applicable prohibitions set forth in Section 728.132 or 728.139. Debris excluded from the definition of hazardous waste under Section 728.103(f)(2) (i.e., debris treated by an extraction or destruction technology provided by Section 728.Table F, and debris that is delisted), however, is subject to the notification and certification requirements of subsection (d) below rather than the certification requirements of subsection (b)(5).
- A) For wastes with treatment standards expressed as concentrations in the waste extract or in the waste (Sections 728.141 or 728.143), or for wastes prohibited under Section 728.132 or 728.139 ~~which that~~ are not subject to any treatment standards under Subpart D of this Part, the certification must be signed by an authorized representative and must state the following:

I certify under penalty of law that I have personally examined and am familiar with the treatment technology and operation of the treatment process used to support this certification and that, based on my inquiry of those individuals immediately responsible for obtaining this information, I believe that the treatment process has been operated and maintained properly so as to comply with the performance levels specified in 35 Ill. Adm. Code 728.Subpart D and all applicable prohibitions set forth in 35 Ill. Adm. Code

728.132 or 728.139 or Section 3004(d) of the Resource Conservation and Recovery Act without impermissible dilution of the prohibited waste. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine and imprisonment.

- B) For wastes with treatment standards expressed as technologies (Section 728.142), the certification must be signed by an authorized representative and must state the following:

I certify under penalty of law that the waste has been treated in accordance with the requirements of 35 Ill. Adm. Code 728.142. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine and imprisonment.

- C) For wastes with treatment standards expressed as concentrations in the waste pursuant to Section 728.143, if compliance with the treatment standards in Subpart D of this Part is based in part or in whole on the analytical detection limit alternative specified in Section 728.143(c), the certification also must state the following:

I certify under penalty of law that I have personally examined and am familiar with the treatment technology and operation of the treatment process used to support this certification and that, based on my inquiry of those individuals immediately responsible for obtaining this information, I believe that the nonwastewater organic constituents have been treated by incineration in units operated in accordance with 35 Ill. Adm. Code 724.Subpart O or 35 Ill. Adm. Code 725.Subpart O, or by combustion in fuel substitution units operating in accordance with applicable technical requirements, and I have been unable to detect the nonwastewater organic constituents despite having used best good faith efforts to analyze for such constituents. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine and imprisonment.

- 6) If the waste or treatment residue will be further managed at a different treatment or storage facility, the treatment, storage or disposal facility sending the waste or treatment residue off-site must comply with the notice and certification requirements applicable to generators under this Section.
- 7) Where the wastes are recyclable materials used in a manner constituting disposal subject to the provisions of 35 Ill. Adm. Code 726.120(b), regarding treatment standards and prohibition levels, the owner or operator of a treatment facility (i.e. the recycler) is not required to notify the receiving facility pursuant to subsection (b)(4) above. With each shipment of such wastes the owner or operator of

the recycling facility shall submit a certification described in subsection (b)(5) above, and a notice ~~which~~that includes the information listed in subsection (b)(4) above (except the manifest number) to the Agency. The recycling facility also shall keep records of the name and location of each entity receiving the hazardous waste-derived product.

- c) Except where the owner or operator is disposing of any waste that is a recyclable material used in a manner constituting disposal pursuant to 35 Ill. Adm. Code 726.120(b), the owner or operator of any land disposal facility disposing any waste subject to restrictions under this Part shall:
- 1) Have copies of the notice and certification specified in subsection (a) or (b) above, and the certification specified in Section 728.108 if applicable.
 - 2) Test the waste, or an extract of the waste or treatment residue developed using the test method described in Section 728. Appendix A or using any methods required by generators under Section 728.132, to assure that the wastes or treatment residues are in compliance with the applicable treatment standards set forth in Subpart D of this Part and all applicable prohibitions set forth in Sections 728.132 or 728.139. Such testing must be performed according to the frequency specified in the facility's waste analysis plan as required by 35 Ill. Adm. Code 724.113 or 725.113.
 - 3) Where the owner or operator is disposing of any waste that is subject to the prohibitions under Section 728.133(f) but not subject to the prohibitions set forth in Section 728.132, the owner or operator shall ensure that such waste is the subject of a certification according to the requirements of Section 728.108 prior to disposal in a landfill or surface impoundment unit, and that such disposal is in accordance with the requirements of Section 728.105(h)(2). The same requirement applies to any waste that is subject to the prohibitions under Section 728.133(f) and also is subject to the statutory prohibitions in the codified prohibitions in Section 728.139 or Section 728.132.
 - 4) Where the owner or operator is disposing of any waste that is a recyclable material used in a manner constituting disposal subject to the provisions of 35 Ill. Adm. Code 726.120(b), the owner or operator is not subject to subsections (c)(1) through (c)(3) above with respect to such waste.
- d) Generators or treaters ~~who~~that first claim that hazardous debris is excluded from the definition of hazardous waste under 35 Ill. Adm. Code 728.103(f)(2) (i.e., debris treated by an extraction or destruction technology provided by Section 728. Table F, and debris that has been delisted) are subject to the following notification and certification requirements:
- 1) A one-time notification must be submitted to the Agency including the following information:
 - A) The name and address of the RCRA Subtitle D facility receiving the treated debris;

- B) A description of the hazardous debris as initially generated, including the applicable U.S. EPA hazardous waste numbers; and
 - C) For debris excluded under 35 Ill. Adm. Code 728.103(f)(2), the technology from Section 728.Table F, used to treat the debris.
- 2) The notification must be updated if the debris is shipped to a different facility, and, for debris excluded 35 Ill. Adm. Code 721.2(d)(1), if a different type of debris is treated or if a different technology is used to treat the debris.
 - 3) For debris excluded under 35 Ill. Adm. Code 728.103(f)(2), the owner or operator of the treatment facility shall document and certify compliance with the treatment standards of Section 728.Table F, as follows:
 - A) Records must be kept of all inspections, evaluations, and analyses of treated debris that are made to determine compliance with the treatment standards;
 - B) Records must be kept of any data or information the treater obtains during treatment of the debris that identifies key operating parameters of the treatment unit; and
 - C) For each shipment of treated debris, a certification of compliance with the treatment standards must be signed by an authorized representative and placed in the facility's files. The certification must state the following: "I certify under penalty of law that the debris has been treated in accordance with the requirements of 35 Ill. Adm. Code 728.145. I am aware that there are significant penalties for making a false certification, including the possibility of fine and imprisonment."

(Source: Amended at 18 Ill. Reg. _____, effective _____)

SUBPART D: TREATMENT STANDARDS

Section 728.140 Applicability of Treatment Standards

- a) A restricted waste identified in Section 728.141 may be land disposed only if an extract of the waste or of the treatment residue of the waste developed using ~~the test method 35 Ill. Adm. Code 721. Appendix B Method 1311~~, the Toxicity Characteristic Leaching Procedure, does not exceed the value shown in Section 728.Table A for any hazardous constituent listed in Section 728.Table A for that waste, with the following exceptions: D004, D008, K031, K084, K101, K102, P010, P011, P012, P036, P038 and U136. These wastes may be land disposed only if an extract of the waste or of the treatment residue of the waste developed using ~~either the test method in 35 Ill. Adm. Code 721. Appendix B Method 1310, the Extraction Procedure Toxicity Test, or Method 1311, the Toxicity Characteristic Leaching Procedure~~, or the test method in Section 728. Appendix A does not exceed the value concentration shown in Section 728.Table B for any hazardous constituent listed in Section 728.Table A for that waste. Methods 1310 and 1311 are both found in "Test Methods for Evaluating Solid Waste, Physical/

Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111.

- b) A restricted waste for which a treatment technology is specified under Section 728.142(a) or hazardous debris for which a treatment technology is specified under Section 728.145 may be land disposed after it is treated using that specified technology or an equivalent treatment method approved by the Agency under the procedures set forth in Section 728.142(b). For waste displaying the characteristic of ignitability (D001) and reactivity (D003), that are diluted to meet the deactivation treatment standard in Section 728.Tables C and D (DEACT), the treater shall comply with the precautionary measures specified in 35 Ill. Adm. Code 724.117(b) and 35 Ill. Adm. Code 725.117(b).
- c) Except as otherwise specified in Section 728.143(c), a restricted waste identified in Section 728.143 may be land disposed only if the constituent concentrations in the waste or treatment residue of the waste do not exceed the value shown in Section 728.Table B for any hazardous constituent listed in Section 728.Table B for that waste.
- d) If a treatment standard has been established in Sections 728.141 through 728.143 for a hazardous waste that is itself subject to those standards rather than the standards for hazardous debris under Section 728.145.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 728.141 Treatment Standards Expressed as Concentrations in Waste Extract

- a) Section 728.Table A identifies the restricted wastes and the concentrations of their associated constituents ~~which~~that may not be exceeded by the extract of a waste or waste treatment residual ~~developed~~extracted using the test method in Section 728.Appendix ~~A~~Method 1311, the Toxicity Characteristic Leaching Procedure, for the allowable land disposal of such wastes. Compliance with these concentrations is required based upon grab samples, unless otherwise noted in Section 728.Table A. Method 1311 is found in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111.
- b) When wastes with differing treatment standards for a constituent of concern are combined for purposes of treatment, the treatment residue must meet the lowest treatment standard for the constituent of concern, except that mixtures of high and low zinc nonwastewater K061 are subject to the treatment standard for high zinc K061.
- c) The treatment standards for the constituents in F001 through F005 ~~which~~that are listed in Section 728.Table A only apply to wastes which contain one, two, or all three of these constituents. If the waste contains any of these three constituents along with any of the other 26 constituents found in F001 through F005, then only the treatments standards in Section 728.Table A are required.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 728.142 Treatment Standards Expressed as Specified Technologies

- a) The following wastes in subsections (a)(1) and (2) below and Sections 728.Table D and 728.Table E must be treated using the technology or technologies specified in subsections (a)(1) and (2) and Section 728.Table C.
- 1) Liquid hazardous wastes containing PCBs at concentrations greater than or equal to 50 ppm but less than 500 ppm must be incinerated in accordance with technical requirements at 40 CFR 761.70, incorporated by reference in 35 Ill. Adm. Code 720.111, or burned in high efficiency boilers in accordance with the technical requirements of 40 CFR 761.60. Liquid hazardous wastes containing PCBs at concentrations greater than or equal to 500 ppm must be incinerated in accordance with the technical requirements of 40 CFR 761.70. Thermal treatment in accordance with this Section must be in compliance with applicable regulations in 35 Ill. Adm. Code 724, 725 and 726.
 - 2) Nonliquid hazardous wastes containing halogenated organic compounds (HOCs) in total concentrations greater than or equal to 1000 mg/kg and liquid HOC-containing wastes that are prohibited under Section 728.132(e)(1) must be incinerated in accordance with the requirements of 35 Ill. Adm. Code 724.Subpart O or 35 Ill. Adm. Code 725.Subpart O. These treatment standards do not apply where the waste is subject to a Subpart C of this Part treatment standard for a specific HOC (such as a hazardous waste chlorinated solvent for which a treatment standard is established under Section 728.141(a)).
 - 3) A mixture consisting of wastewater, the discharge of which is subject to regulation under 35 Ill. Adm. Code 309 or 310, and de minimis losses of materials from manufacturing operations in which these materials are used as raw materials or are produced as products in the manufacturing process, and that meet the criteria of the D001 ignitable liquids containing greater than 10% total organic constituents (TOC) subcategory, is subject to the DEACT treatment standard described in Table C. For purposes of this subsection, "de minimis losses" include:
 - A) Those from normal material handling operations (e.g., spills from the unloading or transfer of materials from bins or other containers, leaks from pipes, valves or other devices used to transfer materials);
 - B) Minor leaks from process equipment, storage tanks, or containers;
 - C) Leaks from well-maintained pump packings and seals;
 - D) Sample purgings; and
 - E) Relief device discharges.
- b) Any person may submit an application to the Agency demonstrating that an alternative treatment method can achieve a level of performance equivalent to that achievable by methods specified in subsections (a) above and (c) and (d) below for wastes or specified in ~~ef~~ Section 728.Table F for hazardous debris. The applicant shall submit information demonstrating that the applicant's treatment method is in compliance with federal and

state requirements, including this Part, 35 Ill. Adm. Code 709, 724, 725, 726 and 729 and Sections 22.6 and 39(h) of the Environmental Protection Act (Ill. Rev. Stat. 1987, ch. 111 $\frac{1}{2}$, pars. 1022.6 and 1039(h) [415 ILCS 5/22.6 and 5/39(h)]), and is protective of human health or the environment. On the basis of such information and any other available information, the Agency shall approve the use of the alternative treatment method if the Agency finds that the alternative treatment method provides a measure of performance equivalent to that achieved by methods specified in subsections (a) above and (c) and (d) below and in Section 728.Table F, for hazardous debris. Any approval must be stated in writing and may contain such provisions and conditions as the Agency determines to be appropriate. The person to whom such approval is issued shall comply with all limitations contained in such determination.

- c) As an alternative to the otherwise applicable treatment standards of Subpart D of this Part, lab packs are eligible for land disposal provided the following requirements are met:
- 1) The lab packs comply with the applicable provisions of 35 Ill. Adm. Code 724.416 and 725.416;
BOARD NOTE: 35 Ill. Adm. Code 729.301 and 729.312 include additional restrictions on the use of lab packs.
 - 2) All hazardous wastes contained in such lab packs are specified in Section 728.Appendix D or Section 728.Appendix E;
 - 3) The lab packs are incinerated in accordance with the requirements of 35 Ill. Adm. Code 724.Subpart O or 35 Ill. Adm. Code 725.Subpart O; and
 - 4) Any incinerator residues from lab packs containing D004, D005, D006, D007, D008, D010 and D011 are treated in compliance with the applicable treatment standards specified for such wastes in Subpart D.
- d) Radioactive hazardous mixed wastes with treatment standards specified in Section 728.Table E are not subject to any treatment standards specified in Section 728.141, Section 728.143 or Section 728.Table D. Radioactive hazardous mixed wastes not subject to treatment standards in Section 728.Table E remain subject to all applicable treatment standards specified in Section 728.141, Section 728.143 and Section 728.Table D. Hazardous debris containing radioactive waste is not subject to the treatment standards specified in Section 728.Table F but is subject to the treatment standards specified in Section 728.145.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 728.Appendix A Toxicity Characteristic Leaching Procedure (TCLP)

~~The Board incorporates by reference 40 CFR 268, Appendix I (1988). This incorporation includes no future editions or amendments.~~

Note: The TCLP (Method 1311) is published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 728. Appendix I EP Toxicity Test Method and Structural Integrity Test

~~The Board incorporates by reference 40 CFR 268, Appendix IX, adopted at 56 Fed. Reg. 3876, January 31, 1991. This Section incorporates no future amendments or editions.~~

Note: The EP (Method 1310) is published in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods", U.S. EPA Publication SW-846, as incorporated by reference in 35 Ill. Adm. Code 720.111.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 728. Table B Constituent Concentrations in Wastes (CCW)

D, F and K Listed Wastes

Waste Code	See Also	Regulated Hazardous Constituent	CAS No. for Regulated Hazardous Constituent	Concentration (mg/L) Wastewaters	Concentration (mg/L) Nonwastewaters
D003	(Reactive NA)	cyanides (Total) Cyanides (Amenable)	57-12-5 57-12-5	Res. 0.86	Adm. Code 721.123(a)(5) # 590. C 30.
D004	Table A	Arsenic	7440-38-2	5.0	NA
D005	Table A	Barium	7440-39-3	100.	NA
D006	Table A	Cadmium	7440-43-9	1.0	NA
D007	Table A	Chromium (Total)	7440-47-32	5.0	NA
D008	Table A	Lead	7439-92-1	5.0	NA
D009	Table A	Mercury	7439-97-6	0.20	NA
D010	Table A	Selenium	7782-49-2	1.0	NA
D011	Table A	Silver	7440-22-4	5.0	NA
D012	Table D	Endrin	720-20-8	NA	0.13 A
D013	Table D	Lindane	58-89-9	NA	0.066 A
D014	Table D	Methoxychlor	72-43-5	NA	0.18 A
D015	Table D	Toxaphene	8001-35-1	NA	1.3 A
D016	Table D	2,4-D	94-75-7	NA	10.0 A
D017	Table D	2,4,5-TP Silvex	93-76-5	NA	7.9 A
F001-F005	spent solvents				
		Acetone	67-64-1	0.28	160.
		Benzene	71-43-2	0.070	3.7 A
		n-Butyl alcohol	71-36-3	5.6	2.6
		Carbon tetrachloride	56-23-5	0.057	5.6
		Chlorobenzene	108-90-7	0.057	5.7
		Cresol (m- and p-isomers)		0.77	3.2
		o-cresol		0.11	5.6
		o-Dichlorobenzene	95-50-1	0.088	6.2
		Ethyl acetate	141-7-6	0.34	33.

		Ethyl benzene	100-41-4	0.057	6.0
		Ethyl ether	60-29-7	0.12	160.
		Isobutyl alcohol	78-83-1	5.6	170.
		Methylene chloride	75-9-2	0.089	33.
		Methyl ethyl ketone	78-93-3	0.28	36.
		Methyl isobutyl ketone	108-10-1	0.14	33.
		Nitrobenzene	98-95-3	0.068	14.
		Pyridine	110-86-1	0.014	16.
		Tetrachloroethylene	127-18-4	0.056	5.6
		Toluene	108-88-3	0.08	28.
		1,1,1-Trichloroethane	71-55-6	0.054	5.6
		1,1,2-Trichloroethane	79-00-5	0.030	7.6 A
		Trichloroethylene	79-01-6	0.054	5.6
		1,1,2-Trichloro-1,2,2-trifluoromethane	76-13-1	0.057	28.
		Trichloromono-fluoromethane	75-69-4	0.02	33.
		Xylenes (total)		0.32	28.
F006	Table A	Cyanides (Total)	57-12-5	1.2	590.
		Cyanides (Amenable)	57-12-5	0.86	30.
		Cadmium	7440-43-9	1.6	NA
		Chromium	7440-47-32	0.32	NA
		Lead	7439-92-1	0.040	NA
		Nickel	7440-02-0	0.44	NA
F007	Table A	Cyanides (Total)	57-12-5	1.9	590.
		Cyanides (Amenable)	57-12-5	0.1	30.
		Chromium (Total)	7440-47-32	0.32	NA
		Lead	7439-92-1	0.04	NA
		Nickel	7440-02-0	0.44	NA
F008	Table A	Cyanides (Total)	57-12-5	1.9	590.
		Cyanides (Amenable)	57-12-5	0.13	30.
		Chromium	7440-47-32	0.32	NA
		Lead	7439-92-1	0.04	NA
		Nickel	7440-02-0	0.44	NA
F009	Table A	Cyanides (Total)	57-12-5	1.9	590.
		Cyanides (Amenable)	57-12-5	0.1	30.
		Chromium	7440-47-32	0.32	NA
		Lead	7439-92-1	0.04	NA
		Nickel	7440-02-0	0.44	NA
F010	NA	Cyanides (Total)	57-12-5	1.9	1.5
		Cyanides (Amenable)	57-12-5	0.1	NA
F011	Table A	Cyanides (Total)	57-12-5	1.9	110.
		Cyanides (Amenable)	57-12-5	0.1	9.1
		Chromium (Total)	7440-47-32	0.32	NA
		Lead	7439-92-1	0.04	NA
		Nickel	7440-02-0	0.44	NA
F012	Table A	Cyanides (Total)	57-12-5	1.9	110.
		Cyanides (Amenable)	57-12-5	0.1	9.1
		Chromium (Total)	7440-47-32	0.32	NA
		Lead	7439-92-1	0.04	NA
		Nickel	7440-02-0	0.44	NA
F019	Table A	Cyanides (Total)	57-12-5	1.2	590. C
		Cyanides (Amenable)	57-12-5	0.86	30. C
		Chromium (Total)	7440-47-32	0.32	NA

F024	(Note: F024 organic standards must be treated via incineration (INCIN))			
Tables A & D	2-Chloro-1,3-butadiene	126-99-8	0.28 A	0.28 A
	3-Chloropropene	107-05-1	0.28 A	0.28 A
	1,1-Dichloroethane	75-34-3	0.014 A	0.014 A
	1,2-Dichloroethane	107-06-2	0.014 A	0.014 A
	1,2-Dichloropropane	78-87-5	0.014 A	0.014 A
	cis-1,3-Dichloropropene	10061-01-5	0.014 A	0.014 A
	trans-1,3-Dichloropropene	10061-02-6	0.014 A	0.014 A
	Bis(2-ethylhexyl)phthalate	117-81-7	0.036 A	1.8 A
	Hexachloroethane	67-72-1	0.036 A	1.8 A
	Chromium (Total)	7440-47-32	0.35	NA
	Nickel	7440-02-0	0.47	NA
F025	(Light ends subcategory)			
NA	Chloroform	67-66-3	0.046 B	6.2 A
	1,2-Dichloroethane	107-06-2	0.21 B	6.2 A
	1,1-Dichloroethylene	75-35-4	0.025 B	6.2 A
	Methylene chloride	75-9-2	0.089 B	31. A
	Carbon tetrachloride	56-23-5	0.057 B	6.2 A
	1,1,2-Trichloroethane	79-00-5	0.054 B	6.2 A
	Trichloroethylene	79-01-6	0.054 B	5.6 A
	Vinyl chloride	75-01-4	0.27 B	33. A
F025	(Spent filters or aids and desiccants subcategory)			
NA	Chloroform	67-66-3	0.046 B	6.2 A
	Methylene chloride	75-9-2	0.089 B	31. A
	Carbon tetrachloride	56-23-5	0.057 B	6.2 A
	1,1,2-Trichloroethane	79-00-5	0.054 B	6.2 A
	Trichloroethylene	79-01-6	0.054 B	5.6 A
	Vinyl chloride	75-01-4	0.27 B	33. A
	Hexachlorobenzene	118-74-1	0.055 B	37. A
	Hexachlorobutadiene	87-68-3	0.055 B	28. A
	Hexachloroethane	67-72-1	0.055 B	30. A
F037	Table A			
	Acenaphthene	208-96-8	0.059 B	NA
	Anthracene	120-12-7	0.059 B	28. A
	Benzene	71-43-2	0.14 B	14. A
	Benzo(a)anthracene	50-32-8	0.059 B	20. A
	Benzo(a)pyrene	117-81-7	0.061 B	12. A
	Bis(2-ethylhexyl)phthalate	75-15-0	0.28 B	7.3 A
	Chrysene	218-01-9	0.059 B	15. A
	Di-n-butyl phthalate	105-67-9	0.057 B	3.6 A
	Ethylbenzene	100-41-4	0.057 B	14. A
	Fluorene	86-73-7	0.059 B	NA
	Naphthalene	91-20-3	0.059 B	42. A
	Phenanthrene	85-01-8	0.059 B	34. A
	Phenol	108-95-2	0.039 B	3.6 A
	Pyrene	129-00-0	0.067 B	36. A
	Toluene	108-88-3	0.08 B	14. A
	Xylene(s)		0.32 B	22. A
	Cyanides (Total)	57-12-5	0.028 A	1.8 A
	Chromium (Total)	7440-47-32	0.2	NA
	Lead	7439-92-1	0.037	NA
F038	Table A			
	Benzene	71-43-2	0.14 B	14. A
	Benzo(a)pyrene	50-32-8	0.061 B	12. A
	Bis(2-ethylhexyl)phthalate	117-81-7	0.28 B	7.3 A
	Chrysene	218-01-9	0.059 B	15. A
	Di-n-butyl phthalate	84-74-2	0.057 B	3.6 A

	Ethylbenzene	100-41-4	0.057 B	14. A
	Fluorene	86-73-7	0.059 B	NA
	Naphthalene	91-20-3	0.059 B	42. A
	Phenanthrene	85-01-8	0.059 B	34. A
	Phenol	108-95-2	0.039 B	3.6 A
	Pyrene	129-00-0	0.067 B	36. A
	Toluene	108-88-3	0.080 B	14. A
	Xylene(s)		0.32 B	22. A
	Cyanides (Total)	57-12-5	0.028 A	1.8 A
	Chromium (Total)	7440-47-32	0.2	NA
	Lead	7439-92-1	0.037	NA
F039 (and D001 and D002 wastes prohibited under Section 728.137)				
Tables A & D	Acetone	67-64-1	0.28 B	160. A
	Acenaphthalene	208-96-8	0.059 B	3.4 A
	Acenaphthene	83-32-9	0.059 B	4.0 A
	Acetonitrile	75-05-8	0.17 B	NA
	Acetophenone	96-86-2	0.010 B	9.7 A
	2-Acetylaminofluorene	53-96-3	0.059 B	140. A
	<u>Acrolien</u>	<u>107-02-8</u>	<u>0.29 B</u>	<u>NA</u>
	Acrylonitrile	107-13-1	0.24 B	84. A
	Acrolien	107-02-8	0.29 B	NA
	Aldrin	309-00-2	0.021 B	0.068 A
	4-Aminobiphenyl	92-67-1	0.13 B	NA
	Aniline	62-53-3	0.81 B	14. A
	Anthracene	120-12-7	0.059 B	4.0 A
	Aramite	140-57-8	0.36 B	NA
	Aroclor 1016	12674-11-2	0.013 B	0.92 A
	Aroclor 1221	11104-28-2	0.014 B	0.92 A
	Aroclor 1232	11141-16-5	0.013 B	0.92 A
	Aroclor 1242	53469-21-9	0.017 B	0.92 A
	Aroclor 1248	12672-29-6	0.013 B	0.92 A
	Aroclor 1254	11097-69-1	0.014 B	1.8 A
	Aroclor 1260	11096-82-5	0.014 B	1.8 A
	alpha-BHC	319-84-6	0.00014	0.066 A
	beta-BHC	319-85-7	B 0.00014	0.066 A
	delta-BHC	319-86-8	B 0.023 B	0.066 A
	gamma-BHC	58-89-9	0.0017 B	0.066 A
	Benzene	71-43-2	0.14 B	36. A
	Benzo(a)anthracene	56-55-3	0.059 B	8.2 A
	Benzo(b)fluoranthene	205-99-2	0.055 B	3.4 A
	Benzo(k)fluoranthene	207-08-9	0.059 B	3.4 A
	Benzo(g,h,i)perylene	191-24-2	0.0055 B	1.5 A
	Benzo(a)pyrene	50-32-8	0.061 B	8.2 A
	Bromodichloromethane	75-27-4	0.35 B	15. A
	Bromoform (Tribromo- methane)	75-25-2	0.63 B	15. A
	Bromomethane (methyl bromide)	74-63-9	0.11 B	15. A
	4-Bromophenyl phenyl ether	101-55-3	0.055 B	15. A
	n-Butyl alcohol	71-36-3	5.6 B	2.6 A
	Butyl benzyl phthalate	85-68-7	0.017 B	7.9 A
	2-sec-Butyl-4,6-dinitro- phenol	88-85-7	0.066 B	2.5 A
	Carbon tetrachloride	56-23-5	0.057 B	5.6 A
	Carbon disulfide	75-15-0	0.014 B	NA
	Chlordane	57-74-9	0.0033 B	0.13 A
	p-Chloroaniline	106-47-8	0.46 B	16. A
	Chlorobenzene	108-90-7	0.057 B	5.7 A

Chlorobenzilate	510-15-6	0.10 B	NA
2-Chloro-1,3-butadiene	126-99-8	0.057 B	NA
Chlorodibromomethane	124-48-1	0.057 B	16. A
Chloroethane	75-00-3	0.27 B	6.0 A
bis(2-Chloroethoxy)methane	111-91-1	0.036 B	7.2 A
bis(2-Chloroethyl) ether	111-44-4	0.033 B	7.2 A
Chloroform	67-66-3	0.046 B	5.6 A
bis(2-Chloroisopropyl) ether	39638-32-9	0.055 B	7.2 A
p-Chloro-m-cresol	59-50-7	0.018 B	14. A
Chloromethane (Methyl chloride)	74-87-3	0.19 B	33. A
2-Chloronaphthalene	91-8-7	0.055 B	5.6 A
2-Chlorophenol	95-57-8	0.044 B	5.7 A
3-Chloropropene	107-05-1	0.036 B	28. A
Chrysene	218-01-9	0.059 B	8.2 A
o-Cresol	95-48-7	0.11 B	5.6 A
Cresol (m- and p-isomers)		0.77 B	3.2 A
Cyclohexanone	108-94-1	0.36 B	NA
1,2-Dibromo-3-chloro-propane	96-12-8	0.11 B	15. A
1,2-Dibromoethane (Ethylene dibromide)	106-93-4	0.028 B	15. A
Dibromomethane	74-95-3	0.11 B	15. A
2,4-Dichlorophenoxyacetic acid (2,4-D)	94-75-7	0.72 B	10. A
o,p'-DDD	53-19-0	0.023 B	0.087 A
p,p'-DDD	72-54-8	0.023 B	0.087 A
o,p'-DDE	3424-82-6	0.031 B	0.087 A
p,p'-DDE	72-55-9	0.031 B	0.087 A
o,p'-DDT	789-02-6	0.0039 B	0.087 A
p,p'-DDT	50-29-3	0.0039 B	0.087 A
Dibenzo(a,h)anthracene	53-70-3	0.055 B	8.2 A
Dibenzo(a,e)pyrene	192-65-4	0.061 A	NA
m-Dichlorobenzene	541-73-1	0.036 B	6.2 A
o-Dichlorobenzene	95-50-1	0.088 B	6.2 A
p-Dichlorobenzene	106-46-7	0.090 B	6.2 A
Dichlorodifluoromethane	75-71-8	0.23 B	7.2 A
1,1-Dichloroethane	75-34-3	0.059 B	7.2 A
1,2-Dichloroethane	107-06-2	0.21 B	7.2 A
1,1-Dichloroethylene	75-35-4	0.025 B	33. A
trans-1,2-Dichloroethylene		0.054 B	33. A
2,4-Dichlorophenol	120-83-2	0.044 B	14. A
2,6-Dichlorophenol	87-65-0	0.044 B	14. A
1,2-Dichloropropane	78-87-5	0.85 B	18. A
cis-1,3-Dichloropropene	10061-01-5	0.036 B	18. A
trans-1,3-Dichloropropene	10061-02-6	0.036 B	18. A
Dieldrin	60-57-1	0.017 B	0.13 A
Diethyl phthalate	84-66-2	0.20 B	28. A
2,4-Dimethyl phenol	105-67-9	0.036 B	14. A
Dimethyl phthalate	131-11-3	0.047 B	28. A
Di-n-butyl phthalate	84-74-2	0.057 B	28. A
1,4-Dinitrobenzene	100-25-4	0.32 B	2.3 A
4,6-Dinitro-o-cresol	534-52-1	0.28 B	160. A
2,4-Dinitrophenol	51-28-5	0.12 B	160. A
2,4-Dinitrotoluene	121-14-2	0.32 B	140. A
2,6-Dinitrotoluene	606-20-2	0.55 B	28. A
Di-n-octyl phthalate	117-84-0	0.017 B	28. A
Di-n-propylnitrosoamine	621-64-7	0.40 B	14. A
Diphenylamine	122-39-4	0.52 B	NA
1,2-Diphenyl hydrazine	122-66-7	0.087 B	NA

Diphenylnitrosoamine	621-64-7	0.40 B	NA
1,4-Dioxane	123-91-1	0.12 B	170. A
Disulfoton	298-04-4	0.017 B	6.2 A
Endosulfan I	939-98-8	0.023 B	0.066 A
Endosulfan II	33213-6-5	0.029 B	0.13 A
Endosulfan sulfate	1031-07-8	0.029 B	0.13 A
Endrin	72-20-8	0.0028 B	0.13 A
Endrin aldehyde	7421-93-4	0.025 B	0.13 A
Ethyl acetate	141-78-6	0.34 B	33. A
Ethyl cyanide	107-12-0	0.24 B	360. A
Ethyl benzene	100-41-4	0.057 B	6.0 A
Ethyl ether	60-29-7	0.12 B	160. A
bis(2-Ethylhexyl) phthalate	117-81-7	0.28 B	28. A
Ethyl methacrylate	97-63-2	0.14 B	160. A
Ethylene oxide	75-21-8	0.12 B	NA
Famphur	52-85-7	0.017 B	15. A
Fluoranthene	206-44-0	0.068 B	8.2 A
Fluorene	86-73-7	0.059 B	4.0 A
Fluorotrichloromethane	75-69-4	0.020 B	33. A
Heptachlor	76-44-8	0.0012 B	0.066 A
Heptachlor epoxide	1024-57-3	0.016 B	0.066 A
Hexachlorobenzene	118-74-1	0.055 B	37. A
Hexachlorobutadiene	87-68-3	0.055 B	28. A
Hexachlorocyclopentadiene	77-47-4	0.057 B	3.6 A
Hexachlorodibenzofurans		0.000063	0.001 A
		B	
Hexachlorodibenzo-p- dioxins		0.000063	0.001 A
		B	
Hexachloroethane	67-72-1	0.055 B	28. A
Hexachloropropene	1888-71-7	0.035 B	28. A
Indeno(1,2,3,-c,d)pyrene	193-39-5	0.0055 B	8.2 A
Iodomethane	74-88-4	0.019 B	65. A
Isobutanol	78-83-1	5.6 B	170. A
Isodrin	465-73-6	0.021 B	0.066 A
Isosafrole	120-58-1	0.081 B	2.6 A
Kepone	143-50-8	0.0011 B	0.13 A
Methacrylonitrile	126-98-7	0.24 B	84. A
<u>Methanol</u>	<u>67-56-1</u>	<u>5.6 B</u>	<u>NA</u>
Methapyrilene	91-80-5	0.081 B	1.5 A
Methanol	67-56-1	5.6 B	NA
Methoxychlor	72-43-5	0.25 B	0.18 A
3-Methylcholanthrene	56-49-5	0.0055 B	15. A
4,4-Methylene-bis-(2- chloroaniline)	101-14-4	0.50 B	35. A
Methylene chloride	75-09-2	0.089 B	33. A
Methyl ethyl ketone	78-93-3	0.28 B	36. A
Methyl isobutyl ketone	108-10-1	0.14 B	33. A
Methyl methacrylate	80-62-6	0.14 B	160. A
Methyl methansulfonate	66-27-3	0.018 B	NA
Methyl parathion	298-00-1	0.014 B	4.6 BA
Naphthalene	91-20-3	0.059 B	3.1 A
2-Naphthylamine	91-59-8	0.52 B	NA
p-Nitroaniline	100-01-6	0.028 B	28. A
Nitrobenzene	98-95-3	0.068 B	14. A
5-Nitro-o-toluidine	99-55-8	0.32 B	28. A
4-Nitrophenol	100-02-7	0.12 B	29. A
N-Nitrosodiethylamine	55-18-5	0.40 B	28. A
N-Nitrosodimethylamine	62-75-9	0.40 B	NA
N-Nitroso-di-n-butylamine	924-16-3	0.40 B	17. A
N-Nitrosomethylethylamine	105-95-6	0.40 B	2.3 A
N-Nitrosomorpholine	59-89-2	0.40 B	2.3 A

N-Nitrosopiperidine	100-75-4	0.013 B	35. A
N-Nitrosopyrrolidine	930-55-2	0.013 B	35. A
Parathion	56-38-2	0.014 B	4.6 A
Pentachlorobenzene	608-93-5	0.055 B	37. A
Pentachlorodibenzo-furans		0.000063	0.001 A
		B	
Pentachlorodibenzo-p-dioxins		0.000063	0.001 A
		B	
Pentachloronitrobenzene	82-68-8	0.055 B	4.8 A
Pentachlorophenol	87-86-5	0.089 B	7.4 A
Phenacetin	62-44-2	0.081 B	16. A
Phenanthrene	85-01-8	0.059 B	3.1 A
Phenol	108-95-2	0.039 B	6.2 A
Phorate	298-02-2	0.021 B	4.6 A
Phthalic anhydride	85-44-9	0.69 B	NA
Pronamide	23950-58-5	0.093 B	1.5 A
Pyrene	129-00-0	0.067 B	8.2 A
Pyridine	110-86-1	0.014 B	16. A
Safrole	94-59-7	0.081 B	22. A
Silvex (2,4,5-TP)	93-72-1	0.72 B	7.9 A
2,4,5-T	93-76-5	0.72 B	7.9 A
1,2,4,5-Tetrachlorobenzene	95-94-3	0.055 B	19. A
Tetrachlorodibenzofurans		0.000063	0.001 A
		B	
Tetrachlorodibenzo-p-dioxins		0.000063	0.001 A
		B	
1,1,1,2-Tetrachloroethane	630-20-6	0.057 B	42. A
1,1,2,2-Tetrachloroethane	79-34-6	0.057 B	42. A
Tetrachloroethylene	127-18-4	0.056 B	5.6 A
2,3,4,6-Tetrachlorophenol	58-90-2	0.030 B	37. A
Toluene	108-88-3	0.080 B	28. A
Toxaphene	8001-35-1	0.0095 B	1.3 A
1,2,4-Trichlorobenzene	120-82-1	0.055 B	19. A
1,1,1-Trichloroethane	71-55-6	0.054 B	5.6 A
1,1,2-Trichloroethane	79-00-5	0.054 B	5.6 A
Trichloroethylene	79-01-6	0.054 B	5.6 A
2,4,5-Trichlorophenol	95-95-4	0.18 B	37. A
2,4,6-Trichlorophenol	88-06-2	0.035 B	37. A
1,2,3-Trichloropropane	96-18-4	0.85 B	28. A
1,1,2-Trichloro-1,2,2-trifluoroethane	76-13-1	0.057 B	28. A
Tris(2,3-dibromopropyl)-phosphate	126-72-7	0.11 B	NA
Vinyl chloride	75-01-4	0.27 B	33. A
Xylene(s)		0.32 B	28. A
Cyanides (Total)	57-12-5	1.2 B	1.8 A
Fluoride	16964-48-8	35. B	NA
Sulfide	8496-25-8	14. B	NA
Antimony	7440-36-0	1.9 B	NA
Arsenic	7440-38-2	1.4 B	NA
Barium	7440-39-3	1.2 B	NA
Beryllium	7440-41-7	0.82 B	NA
Cadmium	7440-43-9	0.20 B	NA
Chromium (Total)	7440-47-32	0.37 B	NA
Copper	7440-50-8	1.3 B	NA
Lead	7439-92-1	0.28 B	NA
Mercury	7439-97-6	0.15 B	NA
Nickel	7440-02-2	0.55 B	NA
Selenium	7782-49-2	0.82 B	NA
Silver	7440-22-4	0.29 B	NA

		Thallium	7440-28-0	1.4 B	NA
		Vanadium	7440-62-2	0.042 B	NA
		Zinc	7440-66-0	1.0 B	NA
K001	Table A	Naphthalene	91-20-3	0.031 A	1.5 A
		Pentachlorophenol	87-86-5	0.031 A	1.5 A
		Phenanthrene	85-01-8	0.18 A	7.4 A
		Pyrene	129-00-0	0.028 A	1.5 A
		Toluene	108-88-3	0.028 A	28. A
		Xylenes (Total)		0.032 A	33. A
		Lead	7439-92-1	0.037 A	NA
K002	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA
K003	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA
K004	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA
K005	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA
		Cyanides (Total)	57-12-5	0.74 B	D
K006	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA
K007	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA D
		Cyanides (Total)	57-12-5	0.74 B	
K008	Table A	Chromium (Total)	7440-47-32	0.9 B	NA
		Lead	7439-92-1	3.4 B	NA
K009	NA	Chloroform	67-66-3	0.1	6.0 A
K010	NA	Chloroform	67-66-3	0.1	6.0
K011	NA	Acetonitrile	75-05-8	38.	1.8
		Acrylonitrile	107-13-1	0.06	1.4
		Acrylamide	79-06-1	19.	23.
		Benzene	71-43-2	0.02	0.03
		Cyanide (Total)	57-12-5	21.	57.
K013	NA	Acetonitrile	75-05-8	38.	1.8 A
		Acrylonitrile	107-13-1	0.06	1.4 A
		Acrylamide	79-06-1	19.	23. A
		Benzene	71-43-2	0.02	0.03 A
		Cyanide (Total)	57-12-5	21.	57.
K014	NA	Acetonitrile	75-05-8	38.	1.8 A
		Acrylonitrile	107-13-1	0.06	1.4 A
		Acrylamide	79-06-1	19.	23. A
		Benzene	71-43-2	0.02	0.03 A
		Cyanide (Total)	57-12-5	21.	57.
K015	Table A	Anthracene	120-12-7	0.059	3.4 A
		Benzal Chloride	98-87-3	0.28	6.2 A
		Sum of Benzo(b)fluoranthene and Benzo(k)fluoranthene	207-08-9	0.055	3.4

		Phenanthrene	85-01-8	0.059	3.4 A
		Toluene	108-88-3	0.08	6.0 A
		Chromium (Total)	7440-47-32	0.32	NA
		Nickel	7440-02-0	0.44	NA
K016	NA	Hexachlorobenzene	118-74-1	0.055	28. A
		Hexachlorobutadiene	87-68-3	0.055	5.6 A
		Hexachlorocyclopentadiene	77-47-4	0.057	5.6 A
		Hexachloroethane	67-72-1	0.055	28. A
		Tetrachloroethene	127-18-4	0.056	6.0 A
K017	NA	1,2-Dichloropropane	78-87-5	0.85 A B	18. A
		1,2,3-Trichloropropane	96-18-4	0.85 A B	28. A
		Bis(2-chloroethyl)ether	111-44-4	0.033 A	7.2 A
				B	
K018	NA	Chloroethane	76-00-3	0.27	6.0 A
		Chloromethane	74-87-3	0.19	NA
		1,1-Dichloroethane	75-34-3	0.059	6.0 A
		1,2-Dichloroethane	107-06-2	0.21	6.0 A
		Hexachlorobenzene	118-74-1	0.055	28. A
		Hexachlorobutadiene	87-68-3	0.055	5.6 A
		Pentachloroethane	76-01-7	NA	5.6
		1,1,1-Trichloroethane	71-55-6	0.054	6.0
		Hexachloroethane	67-72-1	0.055	28. A
K019	NA	Bis(2-chloroethyl) ether	111-44-4	0.033	5.6 A
		Chlorobenzene	108-90-7	0.057	6.0 A
		Chloroform	67-66-3	0.046	6.0 A
		p-Dichlorobenzene	106-46-7	0.09	NA
		1,2-Dichloroethane	107-06-2	0.21	6.0 A
		Fluorene	86-73-7	0.059	NA
		Hexachloroethane	67-72-1	0.055	28. A
		Naphthalene	91-20-3	0.059	5.6 A
		Phenanthrene	85-01-8	0.059	5.6 A
		1,2,4,5-Tetrachlorobenzene	95-94-3	0.055	NA
		Tetrachloroethene	127-18-4	0.056	6.0 A
		1,2,4-Trichlorobenzene	120-82-1	0.055	19. A
		1,1,1-Trichloroethane	71-55-6	0.054	6.0 A
K020	NA	1,2-Dichloroethane	106-93-4	0.21	6.0 A
		1,1,2,2-Tetrachloroethane	79-34-6	0.057	5.6 A
		Tetrachloroethene	127-18-4	0.056	6.0 A
K021	Table A	Chloroform	67-66-3	0.046 B	6.2 A
		Carbon tetrachloride	58-23-5	0.057 B	6.2 A
		Antimony	7440-36-0	0.60 B	6.2 A
K022	Table A	Toluene	108-88-3	0.080 B	0.034 A
		Acetophenone	96-86-2	0.010	19. A
		Diphenylamine	22-39-4	0.52 B	NA
		Diphenylnitrosamine	86-30-6	0.40 B	NA
		Sum of Diphenylamine and Diphenylnitrosamine		NA	13. A
		Phenol	108-95-2	0.039	12. A
		Chromium (Total)	7440-47-32	0.35	NA
		Nickel	7440-02-0	0.47	NA
K023	NA	Phthalic anhydride (measured as Phthalic acid)	85-44-9	0.069	28. A

K024	NA	Phthalic anhydride (measured as Phthalic acid)	85-44-9	0.069	28. A
K028	Table A	1,1-Dichloroethane trans- 1,2- Dichloroethane	75-34-3	0.059	6.0 A
		Hexachlorobutadiene	87-68-3	0.054	6.0 A
		Hexachloroethane	67-72-1	0.055	5.6 A
		Pentachloroethane	76-01-7	NA	28. A
		1,1,1,2-Tetrachloroethane	630-20-6	0.057	5.6 A
		1,1,2,2-Tetrachloroethane	79-34-6	0.057	5.6 A
		1,1,1,-Trichloroethane	71-55-6	0.054	6.0 A
		1,1,2-Trichloroethane	79-00-5	0.054	6.0 A
		Tetrachloroethylene	127-18-4	0.056	6.0 A
		Cadmium	7440-43-9	6.4	NA
		Chromium (Total)	7440-47-32	0.35	NA
		Lead	7439-92-1	0.037	NA
		Nickel	7440-02-0	0.47	NA
K029	NA	Chloroform	67-66-3	0.46	6.0 A
		1,2-Dichloroethane	107-06-2	0.21	6.0 A
		1,1-Dichloroethylene	75-35-4	0.025	6.0 A
		1,1,1-Trichloroethane	71-55-6	0.054	6.0 A
		Vinyl chloride	75-01-4	0.27	6.0 A
K030	NA	o-Dichlorobenzene	95-50-1	0.088	NA
		p-Dichlorobenzene	106-46-7	0.09	NA
		Hexachlorobutadiene	87-68-3	0.055	5.6 A
		Hexachloroethane	67-72-1	0.055	28. A
		Hexachloropropene	1888-71-7	NA	19. A
		Pentachlorobenzene	608-93-5	NA	28. A
		Pentachloroethane	76-01-7	NA	5.6 A
		1,2,4,5-Tetrachlorobenzene	95-94-3	0.055	14. A
		Tetrachloroethene	127-18-4	0.056	6.0 A
		1,2,4-Trichlorobenzene	120-82-1	0.055	19. A
K031	Table A	Arsenic	7440-38-2	0.79	NA
K032	NA	Hexachlorocyclopentadiene	77-47-4	0.057 B	24. A
		Chlordane	57-74-9	0.0033 B	0.26 A
		Heptachlor	76-44-8	0.0012 B	0.066 A
		Heptachlor epoxide	1024-57-3	0.016 B	0.066 A
K033	NA	Hexachlorocyclopentadiene	77-47-4	0.057 B	2.4 A
K034	NA	Hexachlorocyclopentadiene	77-47-4	0.057 B	2.4 A
K035	NA	Acenaphthene	83-32-9	NA	3.4 A
		Anthracene	120-12-7	NA	3.4 A
		Benz(a)anthracene	56-55-3	0.59 B	3.4 A
		Benzo(a)pyrene	50-32-8	NA	3.4 A
		Chrysene	218-01-9	0.059 B	3.4 A
		Dibenz(a,h)anthracene	53-70-3	NA	3.4 A
		Fluoranthene	206-44-0	0.068 B	3.4 A
		Fluorene	86-73-7	NA	3.4 A
		Indeno(1,2,3-cd)pyrene	193-39-5	NA	3.4 A
		Cresols (m- and p-isomers)		0.77 B	NA
		Naphthalene	91-20-3	0.059 B	3.4 A
		o-Cresol	95-48-7	0.11 B	NA
		Phenanthrene	85-01-8	0.059 B	3.4 A
		Phenol	108-95-2	0.039	NA

		Pyrene	129-00-0	0.067 B	8.2 A
K036	NA	Disulfoton	298-04-4	0.025 B	0.1 A
K037	NA	Disulfoton	298-04-4	0.025 B	0.1 A
		Toluene	108-88-3	0.080 B	28. A
K038	NA	Phorate	298-02-2	0.025	0.1 A
K040	NA	Phorate	298-02-2	0.025	0.1 A
K041	NA	Toxaphene	8001-35-1	0.0095 B	2.6 A
K042	NA	1,2,4,5-Tetrachlorobenzene	95-94-3	0.055 B	4.4 A
		o-Dichlorobenzene	95-50-1	0.088 B	4.4 A
		p-Dichlorobenzene	106-46-7	0.090 B	4.4 A
		Pentachlorobenzene	608-93-5	0.055 B	4.4 A
		1,2,4-Trichlorobenzene	120-82-1	0.055 B	4.4 A
K043	NA	2,4-Dichlorophenol	120-83-2	0.044	0.38 A
		2,6-Dichloropheno	187-65-0	0.044	0.34 A
		2,4,5-Trichlorophenol	95-95-4	0.18	8.2 A
		2,4,6-Trichlorophenol	88-06-2	0.035	7.6 A
		Tetrachlorophenols (Total)		NA	0.68 A
		Pentachlorophenol	87-86-5	0.089	1.9 A
		Tetrachloroethene	79-01-6	0.056	1.7 A
		Hexachlorodibenzo-p-dioxins		0.000063	0.001 A
		Hexachlorodibenzofurans		0.000063	0.001 A
		Pentachlorodibenzo-p-dioxins		0.000063	0.001 A
		Pentachlorodibenzo furans		0.000063	0.001 A
		Tetrachlorodibenzo-p-dioxins		0.000063	0.001 A
		Tetrachlorodibenzo furans		0.000063	0.001 A
K046	Table A	Lead	7439-92-1	0.037	NA
K048	Table A	Benzene	71-43-2	0.14 B	14. A
		Benzo(a)pyrene	50-32-8	0.061 B	12. A
		Bis(2-ethylhexyl) phthalate	117-81-7	0.28 B	7.3 A
		Chrysene	218-01-9	0.059 B	15. A
		Di-n-butylphthalate	84-74-2	0.057 B	3.6 A
		Ethylbenzene	100-41-4	0.057 B	14. A
		Fluorene	86-73-7	0.059 B	NA
		Naphthalene	91-20-3	0.059 B	42. A
		Phenanthrene	85-01-8	0.059 B	34. A
		Phenol	108-95-2	0.039 B	3.6 A
		Pyrene	129-00-0	0.067 B	36. A
		Toluene	108-88-3	0.080 B	14. A
		Xylene(s)		0.32 B	22. A
		Cyanides (Total)	57-12-5	0.028 A	1.8 A
		Chromium (Total)	7440-47-32	0.2	NA
		Lead	7439-92-1	0.037	NA
K049	Table A	Anthracene	120-12-7	0.059 B	28. A
		Benzene	71-43-2	0.14 B	14. A
		Benzo(a)pyrene	117-81-7	0.061 B	12. A
		Bis(2-ethylhexyl) phthalate	75-150-0	0.28 B	7.3 A
		Carbon disulfide	75-15-0	0.014 B	NA

		Chrysene	2218-01-9	0.059 B	15. A
		2,4-Dimethyl phenol	105-67-9	0.036 B	NA
		Ethylbenzene	100-41-4	0.057 B	14. A
		Naphthalene	91-20-3	0.059 B	42. A
		Phenanthrene	85-01-8	0.059 B	34. A
		Phenol	108-95-2	0.039 B	3.6 A
		Pyrene	129-00-0	0.067 B	36. A
		Toluene	108-88-3	0.08 B	14. A
		Xylene(s)		0.32 B	22. A
		Cyanides (Total)	56-12-5	0.028 A	1.8 A
		Chromium (Total)	7440-47-32	0.2	NA
K050	Table A	Lead	7439-92-1	0.037	NA
		Benzo(a)pyrene	50-32-8	0.061 B	12. A
		Phenol	108-95-2	0.039 B	3.6 A
		Cyanides (Total)	57-12-5	0.028 A	1.8 A
		Chromium (Total)	7440-47-32	0.2	NA
		Lead	7439-29-1	0.037	NA
K051	Table A	Acenaphthene	208-96-8	0.059 B	NA
		Anthracene	120-12-7	0.059 B	28. A
		Benzene	71-43-2	0.14 B	14. A
		Benzo(a) anthracene	117-81-7	0.059 B	20. A
		Benzo(a)pyrene	117-81-7	0.061 B	12. A
		Bis(2-ethylhexyl) phthalate	75-15-0	0.28 B	7.3 A
		Chrysene	2218-01-9	0.059 B	15. A
		Di-n-butyl phthalate	105-67-9	0.057 B	3.6 A
		Ethylbenzene	100-41-4	0.057 B	14. A
		Fluorene	86-73-7	0.059 B	NA
		Naphthalene	91-20-3	0.059 B	42. A
		Phenanthrene	85-01-8	0.059 B	34. A
		Phenol	108-95-2	0.039 B	3.6 A
		Pyrene	129-00-0	0.067 B	36. A
		Toluene	108-88-3	0.08 B	14. A
		Xylene(s)		0.32 B	22. A
		Cyanides (Total)	57-12-5	0.028 A	1.8 A
		Chromium (Total)	7440-47-32	0.2	NA
		Lead	7439-29-1	0.037	NA
		Benzene	71-43-2	0.14 B	14. A
		Benzo(a)pyrene	50-32-8	0.061 B	12. A
K052	Table A	o-Cresol	95-48-7	0.11 B	6.2 A
		p-Cresol	106-44-5	0.77 B	6.2 A
		2,4-Dimethylphenol	105-67-9	0.036 B	NA
		Ethylbenzene	100-41-4	0.057 B	14. A
		Naphthalene	91-20-3	0.059 B	42. A
		Phenanthrene	85-01-8	0.059 B	34. A
		Phenol	108-95-2	0.039 B	3.6 A
		Toluene	108-88-3	0.08 B	14. A
		Xylenes		0.32 B	22. A
		Cyanides (Total)	56-12-5	0.028 A	1.8 A
		Chromium (Total)	7440-47-32	0.2	NA
		Lead	7439-92-1	0.037	NA
K060	NA	Benzene	71-43-2	0.17 B	0.071 A
		Benzo(a)pyrene	50-32-8	0.035 B	3.6 A
		Naphthalene	91-20-3	0.028 B	3.4 A
		Phenol	108-95-2	0.042 B	3.4 A
		Cyanides (Total)	57-12-5	1.9	1.2
K061	Table A	Cadmium	7440-43-9	1.61	NA

		Chromium (Total)	7440-47-32	0.32	NA
		Lead	7439-92-1	0.51	NA
		Nickel	7440-02-0	0.44	NA
K062	Table A	Chromium (Total)	7440-47-32	0.32	NA
		Lead	7439-92-1	0.04	NA
		Nickel	7440-02-0	0.44	NA
K069	Tables A & D	Cadmium	7440-43-9	1.6	NA
		Lead	7439-92-1	0.51	NA
K071	Table A	Mercury	7439-97-6	0.030	NA
K073	NA	Carbon tetrachloride	58-23-5	0.057 B	6.2 A
		Chloroform	67-66-3	0.046 B	6.2 A
		Hexachloroethane	67-72-1	0.055 B	30. A
		Tetrachloroethene	127-18-4	0.056 B	6.2 A
		1,1,1-Trichloroethane	71-55-6	0.054 B	6.2 A
K083	Table A	Benzene	71-43-2	0.14 B	6.6 A
		Aniline	62-53-3	0.81 B	14. A
		Diphenylamine	22-39-4	0.52 B	NA
		Diphenylnitrosamine	86-30-6	0.40 B	NA
		Sum of Diphenylamine and Diphenylnitrosamine		NA	14. A
		Nitrobenzene	98-95-3	0.068 B	14. A
		Phenol	108-95-2	0.039	5.6 A
		Cyclohexanone	108-94-1	0.36	30. A
		Nickel	7440-02-0	0.47	NA
K084	NA	Arsenic	7440-38-2	0.79	NA
K085	NA	Benzene	71-43-2	0.14 B	4.4 A
		Chlorobenzene	108-90-7	0.057 B	4.4 A
		o-Dichlorobenzene	95-50-1	0.088 B	4.4 A
		m-Dichlorobenzene	541-73-1	0.036 B	4.4 A
		p-Dichlorobenzene	106-46-7	0.090 B	4.4 A
		1,2,4-Trichlorobenzene	120-82-1	0.055 B	4.4 A
		1,2,4,5-Tetrachlorobenzene	95-94-3	0.055 B	4.4 A
		Pentachlorobenzene	608-93-5	0.055	4.4 A
		Hexachlorobenzene	118-74-1	0.055 B	4.4 A
		Aroclor 1016	12674-11-2	0.013 B	0.9 A
		Aroclor 1221	11104-28-2	0.014 B	0.92 A
		Aroclor 1232	11141-16-5	0.013 B	0.92 A
		Aroclor 1242	53469-21-9	0.017 B	0.92 A
		Aroclor 1248	12672-29-6	0.013 B	0.92 A
		Aroclor 1254	11097-69-1	0.014 B	1.8 A
		Aroclor 1260	11096-82-5	0.014 B	1.8 A
K086	Table A	Acetone	67-64-1	0.28	160. A
		Acetophenone	96-86-2	0.010	9.7 A
		Bis(2-ethylhexyl)phthalate	117-81-7	0.28 B	28. A
		n-Butyl alcohol	71-36-3	5.6	2.6 A
		Butylbenzylphthalate	85-68-7	0.017 B	7.9 A
		cyclohexanone	108-94-1	0.36	NA
		1,2-Dichlorobenzene	95-50-1	0.088	6.0 A
		Diethyl phthalate	84-66-2	0.20 B	28. A
		Dimethyl phthalate	131-11-3	0.047 B	28. A
		Di-n-butyl phthalate	84-74-2	0.057 B	28. A
		Di-n-octyl phthalate	117-84-0	0.017 B	28. A
		Ethyl acetate	141-78-6	0.34 B	33. A

	Ethylbenzene	100-41-4	0.057 B	6.0 A
	Methanol	67-56-1	5.6 B	NA
	Methyl isobutyl ketone	108-10-1	0.14	33. A
	Methyl ethyl ketone	78-93-3	0.28	36. A
	Methylene chloride	75-09-2	0.089 B	33. A
	Naphthalene	91-20-3	0.059 B	3.1 A
	Nitrobenzene	98-95-3	0.068 B	14. A
	Toluene	108-88-3	e -0.080 <u>B</u>	a -28. <u>A</u>
	1,1,1-Trichloroethane	71-55-6	e -0.054 <u>B</u>	a -5.6 <u>A</u>
	Trichloroethylene	79-01-6	e -0.054 <u>B</u>	a -5.6 <u>A</u>
	Xylene(s) <u>(Total)</u>	(Total)	e -0.32 <u>B</u>	a -28. <u>A</u>
	Cyanides (Total)	57-12-5	1.9	1.5
	Chromium (Total)	7440-47-32	0.32	NA
	Lead	7439-92-1	0.037	NA
K087	<u>Table A</u> Acenaphthalene	208-96-8	e -0.059 <u>B</u>	3.4
	Benzene	71-43-2	e -0.14 <u>B</u>	a -0.071 <u>A</u>
	Chrysene	218-01-9	e -0.059 <u>B</u>	a -3.4 <u>A</u>
	Fluoranthene	206-44-0	e -0.068 <u>B</u>	a -3.4 <u>A</u>
	Indeno (1,2,3-cd) pyrene	193-39-5	e -0.0055 <u>B</u>	a -3.4 <u>A</u>
	Naphthalene	91-20-3	e -0.059 <u>B</u>	a -3.4 <u>A</u>
	Phenanthrene	85-01-8	e -0.059 <u>B</u>	a -3.4 <u>A</u>
	Toluene	108-88-3	e -0.08 <u>B</u>	a -0.65 <u>A</u>
	Xylenes		e -0.32 <u>B</u>	a -0.07 <u>A</u>
	Lead	7439-92-1	0.037	NA
K093	<u>NA</u> Phthalic anhydride (measured as Phthalic acid)	85-44-9	0.069	a -28. <u>A</u>
K094	<u>NA</u> Phthalic anhydride (measured as Phthalic acid)	85-44-9	0.069	a -28. <u>A</u>
K095	<u>NA</u> 1,1,1,2-Tetrachloroethane	630-20-6	0.057	a -5.6 <u>A</u>
	1,1,2,2-Tetrachloroethane	79-34-6	0.057	a -5.6 <u>A</u>
	Tetrachloroethene	127-18-4	0.056	a -6.0 <u>A</u>
	1,1,2-Trichloroethane	79-00-5	0.054	a -6.0 <u>A</u>
	Trichloroethylene	79-01-6	0.054	a -5.6 <u>A</u>
	Hexachloroethane	67-72-1	0.055	a -28. <u>A</u>
	Pentachloroethane	76-01-7	0.055	a -5.6 <u>A</u>
K096	<u>NA</u> 1,1,1,2-Tetrachloroethane	630-20-6	0.057	a -5.6 <u>A</u>
	1,1,2,2-Tetrachloroethane	79-34-6	0.057	a -5.6 <u>A</u>
	Tetrachloroethene	127-18-4	0.056	a -6.0 <u>A</u>
	1,1,2-Trichloroethane	79-00-5	0.054	a -6.0 <u>A</u>
	Trichloroethene <u>(Tri-</u> <u>chloroethylene)</u>	79-01-6	0.054	a -5.6 <u>A</u>
	1,3-Dichlorobenzene	541-73-1	0.036	a -5.6 <u>A</u>
	Pentachloroethane	76-01-7	0.055	a -5.6 <u>A</u>
	1,2,4-Trichlorobenzene	120-82-1	0.055	a -19. <u>A</u>
K097	<u>NA</u> Hexachlorocyclopentadiene	77-47-4	e -0.057 <u>B</u>	2.4
	Chlordane	57-74-9	e -0.0033 <u>B</u>	a -0.26 <u>A</u>
	Heptachlor	76-44-8	e -0.0012 <u>B</u>	a -0.066 <u>A</u>
	Heptachlor epoxide	1024-57-3	e -0.016 <u>B</u>	a -0.066 <u>A</u>
K098	<u>NA</u> Toxaphene	8001-35-1	e -0.0095 <u>B</u>	a -2.6 <u>A</u>
K099	<u>NA</u> 2,4-Dichlorophenoxyacetic acid	94-75-7	a -1.0 <u>A</u>	a -1.0 <u>A</u>
	Hexachlorodibenzo-p-		a -0.001 <u>A</u>	a -0.001 <u>A</u>

		dioxins			
		Hexachlorodibenzofurans		a-0.001 <u>A</u>	a-0.001 <u>A</u>
		Pentachlorodibenzo-p-dioxins		a-0.001 <u>A</u>	a-0.001 <u>A</u>
		Pentachlorodibenzofurans		a-0.001 <u>A</u>	a-0.001 <u>A</u>
		Tetrachlorodibenzo-p-dioxins		a-0.001 <u>A</u>	a-0.001 <u>A</u>
		Tetrachlorodibenzofurans		a-0.001 <u>A</u>	a-0.001 <u>A</u>
K100	Table A	Cadmium	7440-43-9	1.6	NA
		Chromium (Total)	7440-47-32	0.32	NA
		Lead	7439-92-1	0.51	NA
K101	<u>NA</u>	o-Nitroaniline		a-0.27 <u>A</u>	a-14. <u>A</u>
		Arsenic	7440-38-2	0.79	NA
		Cadmium	7440-43-9	0.24	NA
		Lead	7439-92-1	0.17	NA
		Mercury	7439-97-6	0.082	NA
K102	Table A	o-Nitrophenol		a-0.028 <u>A</u>	a-13. <u>A</u>
		Arsenic	7440-38-2	0.79	NA
		Cadmium	7440-43-9	0.24	NA
		Lead	7439-92-1	0.17	NA
		Mercury	7439-97-6	0.082	NA
K103	<u>NA</u>	Aniline	62-53-3	a-4.5 <u>A</u>	5.6
		Benzene	71-43-2	a-0.15 <u>A</u>	a-6.0 <u>A</u>
		2,4-Dinitrophenol	51-28-5	a-0.61 <u>A</u>	a-5.6 <u>A</u>
		Nitrobenzene	98-95-3	a-0.073 <u>A</u>	a-5.6 <u>A</u>
		Phenol	108-95-2	a-1.4 <u>A</u>	a-5.6 <u>A</u>
K104	<u>NA</u>	Aniline	62-53-3	a-4.5 <u>A</u>	a-5.6 <u>A</u>
		Benzene	71-43-2	a-0.15 <u>A</u>	a-6.0 <u>A</u>
		2,4-Dinitrophenol	51-28-5	a-0.61 <u>A</u>	a-5.6 <u>A</u>
		Nitrobenzene	98-95-3	a-0.073 <u>A</u>	a-5.6 <u>A</u>
		Phenol	108-95-2	a-1.4 <u>A</u>	a-5.6 <u>A</u>
		Cyanides (Total)	57-12-5	2.7	a-1.8 <u>A</u>
K105	<u>NA</u>	Benzene	71-43-2	0.14	a-4.4 <u>A</u>
		Chlorobenzene	108-90-7	0.057	a-4.4 <u>A</u>
		o-Dichlorobenzene	95-50-1	0.088	a-4.4 <u>A</u>
		p-Dichlorobenzene	106-46-7	0.090	a-4.4 <u>A</u>
		2,4,5-Trichlorophenol	95-95-4	0.18	a-4.4 <u>A</u>
		2,4,6-Trichlorophenol	88-06-2	0.035	a-4.4 <u>A</u>
		2-Chlorophenol	95-57-8	0.044	a-4.4 <u>A</u>
		Phenol	108-95-2	0.039	a-4.4 <u>A</u>
K106	Tables A & D	Mercury	7439-97-6	0.030	NA
K115	Table A	Nickel	7440-02-20	0.47	NA
K111	<u>NA</u>	2,4-Dinitrotoluene	121-14-2	0.32	a-140. <u>A</u>
		2,6-Dinitrotoluene	606-20-2	0.55	a-28. <u>A</u>
K117	<u>NA</u>	Ethylene dibromide	106-93-4	0.028	a-15. <u>A</u>
		Methyl bromide	74-83-9	0.11	a-15. <u>A</u>
		Chloroform	67-66-3	0.046	a-5.6 <u>A</u>
K118	<u>NA</u>	Ethylene dibromide	106-93-4	0.028	a-15. <u>A</u>
		Methyl bromide	74-83-9	0.11	a-15. <u>A</u>
		Chloroform	67-66-3	0.046	a-5.6 <u>A</u>

K131	<u>NA</u>	Methyl bromide	74-83-9	0.11	a-15. <u>A</u>
K132	<u>NA</u>	Methyl bromide	74-83-9	0.11	a-15. <u>A</u>
K136	<u>NA</u>	Ethylene dibromide	106-93-4	0.028	a-15. <u>A</u>
		Methyl bromide	74-83-9	0.11	a-15. <u>A</u>
		Chloroform	67-66-3	0.046	a-5.6 <u>A</u>

~~a Treatment standards for this organic constituent were established based upon incineration in units operated in accordance with the technical requirements of 35 Ill. Adm. Code 724. Subpart 0 or 725. Subpart 0, or based upon combustion in fuel substitution units operating in accordance with applicable technical requirements. A facility may certify compliance with these treatment standards according to provisions in Section 728.107.~~

~~s Based on analysis of composite samples.~~

~~R As analyzed using SW 846 Method 9010, sample size: 0.5-10, distillation time: one hour to one hour and fifteen minutes.~~

~~NA Not Applicable.~~

TABLE B (CCW): P AND U LISTED WASTES

Waste Code	Commercial Chemical Name	See Also	Regulated Hazardous Constituent	CAS No. for Regulated Hazardous Constituent	Concentration (mg/L) Wastewaters	Concentration (mg/L) Nonwastewaters
P004	Aldrin	<u>NA</u>	Aldrin	309-00-2	0.21 <u>B</u>	0.066 <u>A</u>
P010	Arsenic acid	Table A	Arsenic	7440-38-2	0.79	NA
P011	Arsenic pentoxide	Table A	Arsenic	7440-38-2	0.79	NA
P012	Arsenic trioxide	Table A	Arsenic	7440-38-2	0.79	NA
P013	Barium cyanide	Table A	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.1	9.1
P020	2-sec-Butyl-4,6-dinitrophenol (Dinoseb)	<u>NA</u>	2-sec-Butyl-4,6-dinitrophenol (Dinoseb)	88-85-7	0.066	* 2.5 <u>A</u>
P021	Calcium cyanide	<u>NA</u>	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.1	9.1
P022	Carbon disulfide	Table D	Carbon disulfide	75-15-0	0.014	NA
P024	p-Chloroaniline	<u>NA</u>	p-Chloroaniline	106-47-8	0.46	* 16. <u>A</u>

P029	Copper cyanide	<u>NA</u>	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.1	9.1
P030	Cyanides (soluble salts and complexes)	<u>NA</u>	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.1	9.1
P036	Dichloro-phenylarsine	Table A	Arsenic	7440-38-2	0.79	NA
P037	Dieldrin	<u>NA</u>	Dieldrin	60-57-1	* 0.017 <u>B</u>	* 0.13 <u>A</u>
P038	Diethyl-arsine	Table A	Arsenic	7440-38-2	0.79	NA
P039	Disulfoton	NA	Disulfoton	298-04-4	0.017	0.1 A
P047	4,6-Dinitro-o-cresol	NA	4,6-Dinitro-o-cresol	534-52-4	0.28 B	160. A
P048	2,4-Dinitro-phenol	NA	2,4-Dinitro-phenol	51-28-5	0.12 B	160. A
P050	Endosulfan	NA	Endosulfan I	939-98-8	0.023 B	0.066 A
			Endosulfan II	33213-6-5	0.029 B	0.13 A
			Endosulfan sulfate	1031-07-8	0.029 B	0.13 A
P051	Endrin	NA	Endrin	72-20-8	0.0028 B	0.13 A
			Endrin aldehyde	7421-93-4	0.025 B	0.13 A
P056	Fluoride	Table D	Fluoride	18694-48-8	35.	NA
P059	Heptachlor	NA	Heptachlor	76-44-8	0.0012 B	0.066 A
			Heptachlor epoxide	1024-57-3	0.016 B	0.066 A
P060	Isodrin	NA	Isodrin	465-73-6	0.021 B	0.066 A
P063	Hydrogen cyanide	NA	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.10	9.1
P065	Mercury fulminate	Tables A & D	Mercury	7439-97-6	0.030	NA
P071	Methyl parathion	NA	Methyl parathion	298-00-0	0.025	0.1 A
P073	Nickel carbonyl	Table A	Nickel	7440-02-0	0.32	NA
P074	Nickel cyanide	Table A	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides	57-12-5	0.10	9.1

			(Amenable) Nickel	7440-02-0	0.44	NA
P077	p-Nitro-aniline	NA	p-Nitro-aniline	100-01-6	0.028 B	28. A
P082	N-Nitrosodi-methylamine	Table D	N-Nitrosodi-methylamine	62-75-9	0.40 B	NA
P089	Parathion	NA	Parathion	56-38-2	0.025	0.1 A
P092	Phenylmer-cury acetate	Tables A & D	Mercury	7439-97-6	0.030	NA
P094	Phorate	NA	Phorate	298-02-2	0.025	0.1 A
P097	Famphur	NA	Famphur	52-85-7	0.025	0.1 A
P098	Potassium cyanide	NA	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.10	9.1
P099	Potassium silver cyanide	Table A	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.1	9.1
			Silver	7440-22-4	0.29	NA
P101	Ethyl cyanide (Propanenitrile)	NA	Ethyl cyanide (Propanenitrile)	107-12-0	0.24 B	360. A
P103	Selenourea	Table A	Selenium	7782-49-2	1.0 B	NA
P104	Silver cyanide	Table A	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.10	9.1
			Silver	7440-22-4	0.29	NA
P106	Sodium cyanide	NA	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.10	9.1
P110	Tetraethyl lead	Tables A & D	Lead	7439-92-1	0.040	NA
P113	Thallic oxide	Table D	Thallium	7440-28-0	0.14 B	NA
P114	Thallium selenite	Table A	Selenium	7782-49-2	1.0	NA
P115	Thallium(I) sulfate	Table D	Thallium	7440-28-0	0.14 B	NA
P119	Ammonia vanadate	Table D	Vanadium	7440-62-2	28. B	NA

P120	Vanadium pentoxide	Table D	Vanadium	7440-62-2	28. B	NA
P121	Zinc cyanide	NA	Cyanides (Total)	57-12-5	1.9	110.
			Cyanides (Amenable)	57-12-5	0.10	9.1
P123	Toxaphene	NA	Toxaphene	8001-35-1	0.0095 B	1.3 A
U002	Acetone	NA	Acetone	67-64-1	0.28	160. A
U003	Acetonitrile	Table D	Acetonitrile	75-05-8	0.17	0.17
U004	Acetophenone	NA	Acetophenone	98-86-2	0.010 A	9.7 A
U005	2-Acetylaminofluorene	NA	2-Acetylaminofluorene	53-96-3	0.059 B	140. A
U009	Acrylonitrile	NA	Acrylonitrile	107-13-1	0.24 A	84. A
U012	Aniline	NA	Aniline	62-53-3	0.81	14. A
U018	Benz(a)-anthracene	NA	Benz(a)-anthracene	56-55-3	0.059 B	8.2 A
U019	Benzene	NA	Benzene	71-43-2	0.14 B	36. A
U022	Benzo(a)-pyrene	NA	Benzo(a)-pyrene	50-32-8	0.061 B	8.2 A
U024	Bis(2-chloroethoxy)methane	NA	Bis(2-chloroethoxy)methane	111-91-1	0.036	7.2 A
U025	Bis(2-chloroethyl) ether	NA	Bis(2-chloroethyl) ether	111-44-4	0.033	7.2 A
U027	Bis(2-chloroisopropyl) ether	NA	Bis(2-chloroisopropyl) ether	39638-32-9	0.055	7.2 A
U028	Bis(2-ethylhexyl)-phthalate	NA	Bis(2-ethylhexyl)-phthalate	117-81-7	0.28 A	28. A
U029	Bromomethane (Methyl bromide)	NA	Bromomethane (Methyl bromide)	74-83-9	0.11 A	15. A
U030	4-Bromophenyl phenyl ether	NA	4-Bromophenyl phenyl ether	101-55-3	0.055 A	15. A
U031	n-Butyl alcohol	NA	n-Butyl alcohol	71-36-3	5.6	2.6 A
U032	Calcium chromate	Table A	Chromium (Total)	7440-47-32	0.32	NA

U036	Chlordane (alpha and gamma)	NA	Chlordane (alpha and gamma)	57-74-9	B	0.00033	0.13 A
U037	Chlorobenzene	NA	Chlorobenzene	108-90-7		0.057 B	5.7 A
U038	Chlorobenzilate	Table D	Chlorobenzilate	510-15-6		0.10 B	NA
U039	p-Chloro-m-cresol	NA	p-Chloro-m-cresol	59-50-7		0.018 B	14. A
U043	Vinyl chloride	NA	Vinyl chloride	75-01-4		0.27 B	33. A
U044	Chloroform	NA	Chloroform	67-66-3		0.046 B	5.6 A
U045	Chloromethane (Methyl chloride)	NA	Chloromethane (Methyl chloride)	74-87-3		0.19 B	33. A
U047	2-Chloronaphthalene	NA	2-Chloronaphthalene	91-58-7	B	0.055 B	5.6 A
U048	2-Chlorophenol	NA	2-Chlorophenol	95-57-8		0.044 B	5.7 A
U050	Chrysene	NA	Chrysene	218-01-9		0.059 B	8.2 A
U051	Creosote	Table A	Naphthalene	91-20-3		0.031	1.5 A
			Pentachlorophenol	87-86-5		0.18	7.4 A
			Phenanthrene	85-01-8		0.031	1.5 A
			Pyrene	129-00-0		0.028	28. A
			Toluene	108-88-3		0.028	33. A
			Xylenes (Total)			0.032	NA
			Lead	7439-92-1		0.037	NA
U052	Cresols (Cresylic acid)	NA	o-Cresol	95-48-7		0.11 B	5.6 A
			Cresols (m- and p-isomers)			0.77 B	3.2 A
U057	Cyclohexanone	Table D	Cyclohexanone	108-94-1		0.36	NA
U060	DDD	NA	o,p'-DDD	53-19-0		0.023 B	0.087 A
			p,p'-DDD	72-54-8		0.023 B	0.087 A
U061	DDT	NA	o,p'-DDT	789-02-6		0.0039 B	0.087 A
			p,p'-DDT	50-29-3		0.0039 B	0.087 A
			o,p'-DDD	53-19-0		0.023 B	0.087 A
			p,p'-DDD	72-54-8		0.023 B	0.087 A
			o,p'-DDE	3424-82-6		0.031 B	0.087 A
			p,p'-DDE	72-55-9		0.031 B	0.087 A
U063	Dibenzo(a,h)anthracene	NA	Dibenzo(a,h)-anthracene	53-70-3		0.055 B	8.2 A

U066	1,2-Dibromo-3-chloro-propane	NA	1,2-Dibromo-3-chloro-propane	96-12-8	0.11 B	15. A
U067	1,2-Dibromoethane (Ethylene dibromide)	NA	1,2-Dibromoethane (Ethylene dibromide)	106-93-4	0.028 B	15. A
U068	Dibromoethane	NA	Dibromoethane	74-95-3	0.11 B	15. A
U069	Di-n-butyl phthalate	NA	Di-n-butyl phthalate	84-74-2	0.057 A	28. A
U070	o-Dichlorobenzene	NA	o-Dichlorobenzene	95-50-1	0.088 B	6.2 A
U071	m-Dichlorobenzene	NA	m-Dichlorobenzene	541-73-1	0.036	6.2 A
U072	p-Dichlorobenzene	NA	p-Dichlorobenzene	104-46-7	0.090 B	6.2 A
U075	Dichlorodifluoromethane	NA	Dichlorodifluoromethane	75-71-8	0.23 B	7.2 A
U076	1,1-Dichloroethane	NA	1,1-Dichloroethane	75-34-3	0.059 B	7.2 A
U077	1,2-Dichloroethane	NA	1,2-Dichloroethane	107-06-2	0.21 B	7.2 A
U078	1,1-Dichloroethylene	NA	1,1-Dichloroethylene	75-35-4	0.025 B	33. A
U079	1,2-Dichloroethylene	NA	trans-1,2-Dichloroethylene	156-60-5	0.054 B	33. A
U080	Methylene chloride	NA	Methylene chloride	75-08-2	0.089 B	33. A
U081	2,4-Dichlorophenol	NA	2,4-Dichlorophenol	120-83-2	0.044 B	14. A
U082	2,6-Dichlorophenol	NA	2,6-Dichlorophenol	87-65-0	0.044 B	14. A
U083	1,2-Dichloropropane	NA	1,2-Dichloropropane	78-87-5	0.85 B	18. A
U084	1,3-Dichloropropene	NA	cis-1,3-Dichloropropene	10061-01-5	0.036 B	18. A
			trans-1,3-Dichloropropene	10061-02-6	0.036 B	18. A
U088	Diethyl phthalate	NA	Diethyl phthalate	84-66-2	0.2	28. A

U093	p-Dimethyl- aminoazoben- zene	Table D	p-Dimethyl- aminoazo- benzene	60-11-7	0.13 B	NA	
U101	2,4-Di- methylphenol	NA	2,4-Dimethyl- phenol	105-67-9	0.036 B	14. A	
U102	Dimethyl phthalate	NA	Dimethyl phthalate	131-11-3	0.047	28. A	
U105	2,4-Dinitro- toluene	NA	2,4-Dinitro- toluene	121-14-2	0.32 B	140. A	
U106	2,6-Dinitro- toluene	NA	2,6-Dinitro- toluene	606-20-2	0.55 B	28. A	
U107	Di-n-octyl phthalate	NA	Di-n-octyl phthalate	117-84-0	0.017	28. A	
U108	1,4-Dioxane	NA	1,4-Dioxane	123-91-1	0.12 B	170. A	
U111	Di-n-propyl- nitrosoamine	NA	Di-n-propyl- nitrosoamine	621-64-7	0.40 B	14. A	
U112	Ethyl acetate	NA	Ethyl acetate	141-78-6	0.34 B	33. A	
U117	Ethyl ether	NA	Ethyl ether	60-29-7	0.12 B	160. A	
U118	Ethyl meth- acrylate	NA	Ethyl methac- rylate	97-63-2	0.14 B	160. A	
U120	Fluoranthene	NA	Fluoranthene	206-44-0	0.068 B	8.2 A	
U121	Trichloro- monofluoro- methane	NA	Trichloro- monofluoro- methane	75-69-4	0.020 B	33. A	
U127	Hexachloro- benzene	NA	Hexachloro- benzene	118-74-1	0.055 B	37. A	
U128	Hexachloro- butadiene	NA	Hexachloro- butadiene	87-68-3	0.055 B	28. A	
U129	Lindane	NA	alpha-BHC	319-84-6	B B	0.00014	0.66 A
			beta-BHC	319-85-7		0.00014	0.66 A
			Delta-BHC	319-86-8		0.023 B	0.66 A
			gamma-BHC (Lindane)	58-89-9		0.0017 B	0.66 A
U130	Hexachloro- cyclopenta- diene	NA	Hexachloro- cyclopenta- diene	77-47-7	0.057 B	3.6 A	
U131	Hexachloro- ethane	NA	Hexachloro- ethane	67-72-1	0.055 B	28. A	
U134	Hydrogen fluoride	Table D	Fluoride	16964-48-8	35.	NA	

U136	Cacodylic acid	Table A	Arsenic	7440-38-2	0.79	NA
U137	Indeno-(1,2,3-c,d)-pyrene	NA	Indeno(1,2,3-c,d)pyrene	193-39-5	0.0055 B	8.2 A
U138	Iodomethane	NA	Iodomethane	74-88-4	0.19 B	65. A
U140	Isobutyl alcohol	NA	Isobutyl alcohol	78-83-1	5.6	170. A
U141	Isosafrole	NA	Isosafrole	120-58-1	0.081	2.6 A
U142	Kepone	NA	Kepone	143-50-8	0.0011	0.13 A
U144	Lead acetate	Table A	Lead	7439-92-1	0.040	NA
U145	Lead phosphate	Table A	Lead	7439-92-1	0.040	NA
U146	Lead subacetate	Table A	Lead	7439-92-1	0.040	NA
U151	Mercury	Tables A & D	Mercury	7439-97-6	0.030	NA
U152	Methacrylonitrile	NA	Methacrylonitrile	126-98-7	0.24 B	84. A
U154	Methanol	NA	Methanol	67-56-1	5.6	NA
U155	Methapyrilene	NA	Methapyrilene	91-80-5	0.081	1.5 A
U157	3-Methylcholanthrene	NA	3-Methylcholanthrene	56-49-5	0.0055 B	15. A
U158	4,4'-Methylenebis(2-chloroaniline)	NA	Methylenebis(2-chloroaniline)	101-14-4	0.50 B	35. A
U159	Methyl ethyl ketone	NA	Methyl ethyl ketone	78-93-3	0.28	36. A
U161	Methyl isobutyl ketone	NA	Methyl isobutyl ketone	108-10-1	0.14	33. A
U162	Methyl methacrylate	NA	Methyl methacrylate	80-62-6	0.14	160. A
U165	Naphthalene	NA	Naphthalene	91-20-3	0.059 B	3.1 A
U168	2-Naphthylamine	Table D	2-Naphthylamine	91-59-8	0.52 B	NA
U169	Nitrobenzene	NA	Nitrobenzene	98-95-3	0.068 B	14. A
U170	4-Nitrophenol	NA	4-Nitrophenol	100-02-7	0.12 B	29. A

U172	N-Nitrosodi- n-butylamine	NA	N-Nitrosodi- n-butylamine	924-16-3	0.40 B	17. A
U174	N-Nitrosodi- ethylamine	NA	N-Nitrosodi- ethylamine	55-18-5	0.40 B	28. A
U179	N-Nitroso- piperidine	NA	N-Nitroso- piperidine	100-75-4	0.013 B	35. A
U180	N-Nitroso- pyrrolidine	NA	N-Nitroso- pyrrolidine	930-55-2	0.013 B	35. A
U181	5-Nitro-o- toluidine	NA	5-Nitro-o- toluidine	99-55-8	0.32 B	28. A
U183	Pentachloro- benzene	NA	Pentachloro- benzene	608-93-5	0.055 B	37. A
U185	Pentachloro- nitrobenzene	NA	Pentachloro- nitrobenzene	82-68-8	0.055 B	4.8 A
U187	Phenacetin	NA	Phenacetin	62-44-2	0.081	16. A
U188	Phenol	NA	Phenol	108-95-2	0.039	6.2 A
U190	Phthalic anhydride (measured as Phthalic acid)	NA	Phthalic anhydride (measured as Phthalic acid)	85-44-9	0.069	28. A
U192	Pronamide	NA	Pronamide	23950-58-5	0.093	1.5 A
U196	Pyridine	NA	Pyridine	110-86-1	0.014 B	16. A
U203	Safrole	NA	Safrole	94-59-7	0.081	22. A
U204	Selenium dioxide	Table A	Selenium	7782-49-2	1.0	NA
U205	Selenium sulfide	Table A	Selenium	7782-49-2	1.0	NA
U207	1,2,4,5- Tetrachloro- benzene	NA	1,2,4,5- Tetrachloro- benzene	95-94-3	0.055 B	19. A
U208	1,1,1,2- Tetrachloro- ethane	NA	1,1,1,2- Tetrachloro- ethane	630-20-6	0.057	42. A
U209	1,1,2,2- Tetrachloro- ethane	NA	1,1,2,2- Tetrachloro- ethane	79-34-5	0.057 B	42. A
U210	Tetrachloro- ethylene	NA	Tetrachloro- ethylene	127-18-4	0.056 B	5.6 A
U211	Carbon tet- rachloride	NA	Carbon tetra- chloride	56-23-5	0.057 B	5.6 A

U214	Thallium(I) acetate	Table D	Thallium	7440-28-0	0.14 B	NA
U215	Thallium(I) carbonate	Table D	Thallium	7440-28-0	0.14 B	NA
U216	Thallium(I) chloride	Table D	Thallium	7440-28-0	0.14 B	NA
U217	Thallium(I) nitrate	Table D	Thallium	7440-28-0	0.14 B	NA
U220	Toluene	NA	Toluene	108-88-3	0.080 B	28. A
U225	Tribromo-methane (Bromoform)	NA	Tribromo-methane (Bromoform)	75-25-2	0.63 B	15. A
U226	1,1,1-Tri-chloroethane	NA	1,1,1-Tri-chloroethane	71-55-6	0.054 B	5.6 A
U227	1,1,2-Tri-chloroethane	NA	1,1,2-Tri-chloroethane	79-00-5	0.054 B	5.6 A
U228	Trichloro-ethylene	NA	Trichloro-ethylene	79-01-6	0.054 B	5.6 A
U235	tris-(2,3-Dibromoprop-yl)-phosphate	NA	tris-(2,3-Di-bromopropyl)-phosphate	126-72-7	0.025	0.10 A
U239	Xylenes	NA	Xylene		0.32 B-B	28. A
U240	2,4-Dichloro-phenoxyacetic acid	NA	2,4-Dichloro-phenoxyacetic acid	94-75-7	0.72	10. A
U243	Hexachloro-propene	NA	Hexachloro-propene	1888-71-7	0.035 B	28.
U247	Methoxychlor	NA	Methoxychlor	72-43-5	0.25 B	0.18 A

A Treatment standards for this organic constituent were established based upon incineration in units operated in accordance with the technical requirements of 35 Ill. Adm. Code 724.Subpart Q or 725.Subpart Q, or based upon combustion in fuel substitution units operating in accordance with applicable technical requirements. A facility may certify compliance with these treatment standards according to provisions in Section 728.107.

B Based on analysis of composite samples.

C As analyzed using SW-846 Method 9010 or 9012; sample size: 10g; distillation time: one hour and fifteen minutes.

R Reserved.

NA Not Applicable.

(Source: Amended at 18 Ill. Reg. _____, effective _____)

Section 728. Table D Technology-Based Standards by RCRA Waste Code

Waste Codes	See Also	CAS No.	Technology Code, Waste-waters	Technology Code, Non-waste-waters	Waste Descriptions and/or Treatment Subcategory
D001	Tables A & B	NA	DEACT, and meet F039; or FSUBS; RORGS; or INCIN	DEACT, and meet F039; or FSUBS; RORGS; or INCIN	All descriptions based on 35 Ill. Adm. Code 721.121, except for the Section 721.121(a)(1) High TOC subcategory, managed in non-CWA/non-CWA-equivalent/non-Class I SDWA systems
D001	NA	NA	DEACT	DEACT	All descriptions based on 35 Ill. Adm. Code 721.121, except for the Section 261.121(a)(1) High TOC subcategory, managed in CWA, CWA-equivalent, or Class I SDWA systems
D001	NA	NA	NA	FSUBS; RORGS; or INCIN	All descriptions based on 35 Ill. Adm. Code 721.121(a)(1)-High TOC Ignitable Liquids Subcategory--Greater than or equal to 10% total organic carbon
D002	Tables A & B	NA	DEACT and meet F039	DEACT and meet F039	Acid, alkaline, and other subcategory based on 35 Ill. Adm. Code 721.122 managed in non-CWA/non-CWA-equivalent/non-Class I SDWA systems
D002	NA	NA	DEACT	DEACT	Acid, alkaline, and other subcategory based on 35 Ill. Adm. Code 721.122 managed in CWA, CWA-equivalent, or Class I SDWA systems
D003	NA	NA	DEACT (but not including dilution as a substitute for adequate treatment)	DEACT (but not including dilution as a substitute for adequate treatment)	Reactive sulfides based on 35 Ill. Adm. Code 721.123(a)(5)
D003	NA	NA	DEACT	DEACT	Explosives based on 35 Ill. Adm. Code 721.123(a)(6), (7) and (8)

D003	NA	NA	NA	DEACT	Water reactives based on 35 Ill. Adm. Code 721.123(a)(2), (3) and (4)
D003	NA	NA	DEACT	DEACT	Other reactives based on 35 Ill. Adm. Code 721.123(a)(1)
D006	NA	7440-43-9	NA	R THERM	Cadmium-containing batteries
D008	NA	7439-92-1	NA	R LEAD	Lead acid batteries (Note: This standard only applies to lead acid batteries that are identified as RCRA hazardous wastes and that are not excluded elsewhere from regulation under the land disposal restrictions of this Part or exempted under other regulations (see 35 Ill. Adm. Code 726.180).)
D009	Tables A & B	7439-97-6	NA	IMERC; or RMERC	Mercury: (High Mercury Subcategory--greater than or equal to 260 mg/kg total Mercury--contains mercury and organics (and are not incinerator residues))
D009	Tables A & B	7439-97-6	NA	RMERC	Mercury: (High Mercury Subcategory--greater than or equal to 260 mg/kg total Mercury--inorganics (including incinerator residues and residues from RMERC))
D012	Table B	72-20-8	BIODG; or INCIN	NA	Endrin
D013	Table B	58-89-9	CARBN; or INCIN	NA	Lindane
D014	Table B	72-43-5	WETOX; or INCIN	NA	Methoxychlor
D015	Table B	8001-35-1	BIODG; or INCIN	NA	Toxaphene
D016	Table B	94-75-7	CHOXD; BIODG; or INCIN	NA	2,4-D
D017	Table B	93-72-1	CHOXD; or INCIN	NA	2,4,5-TP

F005	Tables A & B	79-46-9	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2-Nitropropane
F005	Tables A & B	110-80-5	BIODG; or INCIN	INCIN	2-Ethoxyethanol
F024	Tables A & B	NA	INCIN	INCIN	-----
K025	NA	NA	LLEXT fb SSTRIP fb CARBN; or INCIN	INCIN	Distillation bottoms from the production of nitrobenzene by the nitration of benzene
K026	NA	NA	INCIN	INCIN	Stripping still tails from the production of methyl ethyl pyridines
K027	NA	NA	CARBN; or INCIN	FSUBS; or INCIN	Centrifuge and distillation residues from toluene diisocyanate production
K039	NA	NA	CARBN; or INCIN	FSUBS; or INCIN	Filter cake from the filtration of diethylphosphorodithioc acid in the production of phosphate
K044	NA	NA	DEACT	DEACT	Wastewater treatment sludges from the manufacturing and processing of explosives
K045	NA	NA	DEACT	DEACT	Spent carbon from the treatment of wastewater containing explosives
K047	NA	NA	DEACT	DEACT	Pink/red water from TNT operations
K069	Tables A & B	NA	NA	RLEAD	Emission control dust/sludge from secondary lead smelting: Non-Calcium Sulfate Subcategory
K106	Tables A & B	NA	NA	RMERC	Wastewater treatment sludge from the mercury cell process in chlorine production: (High Mercury Subcategory-greater than or equal to 260 mg/kg total mercury)

K107	NA	NA	INCIN; or CHOXD fb, CARBN; or BIODG fb CARBN	INCIN.	Column bottoms from product separation from the production of 1,1- dimethylhydrazine (UDMH) from carboxylic acid hydrazides
K108	NA	NA	INCIN; or CHOXD fb, CARBN; or BIODG fb CARBN	INCIN.	Condensed column overheads from product separation and condensed reactor vent gases from the production of 1,1- dimethylhydrazine (UDMH) from carboxylic acid hydrazides
K109	NA	NA	INCIN; or CHOXD fb, CARBN; or BIODG fb CARBN	INCIN.	Spent filter cartridges from product purification from the production of 1,1- dimethylhydrazine (UDMH) from carboxylic acid hydrazides
K110	NA	NA	INCIN; or CHOXD fb, CARBN; or BIODG fb CARBN	INCIN.	Condensed column overheads from intermediate separation from the production of 1,1-dimethylhydrazine (UDMH) from carboxylic acid hydrazides
K112	NA	NA	INCIN; or CHOXD fb, CARBN; or BIODG fb CARBN	INCIN.	Reaction by-product water from the drying column in the production of toluenediamine via hydrogenation of dinitrotoluene
K113	NA	NA	CARBN; or INCIN	FSUBS; or INCIN	Condensed liquid light ends from the purification of toluenediamine in the production of toluenediamine via hydrogenation of di- nitrotoluene
K114	NA	NA	CARBN; or INCIN	FSUBS; or INCIN	Vicinals from the purification of tol- uenediamine in the production of toluenedi- amine via hydrogenation of dinitrotoluene
K115	NA	NA	CARBN; or INCIN	FSUBS; or INCIN	Heavy ends from the purification of toluenediamine in the production of tol- uenediamine via hydrogenation of di- nitrotoluene

K116	NA	NA	CARBN; or INCIN	FSUBS; or INCIN	Organic condensate from the solvent recovery column in the production of toluene diisocyanate via phosgenation of toluenediamine
K123	NA	NA	INCIN; or CHOXD fb (BIODG or CARBN)	INCIN.	Process wastewater (including supernates, filtrates, and washwaters) from the production of ethylenebis-dithiocarbamic acid and its salts
K124	NA	NA	INCIN; or CHOXD fb (BIODG or CARBN)	INCIN.	Reactor vent scrubber water from the production of ethylenebisdi-thiocarbamic acid and its salts
K125	NA	NA	INCIN; or CHOXD fb (BIODG or CARBN)	INCIN.	Filtration, evaporation, and centrifugation solids from the production of ethylenebisdi-thiocarbamic acid and its salts
K126	NA	NA	INCIN; or CHOXD fb (BIODG or CARBN)	INCIN.	Baghouse dust and floor sweepings in milling and packaging operations from the production or formulation of ethylene bisdithiocarbamic acid and its salts
P001	NA	81-81-2	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Warfarin (>0.3%)
P002	NA	591-08-2	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	1-Acetyl-2-thiourea
P003	NA	107-02-8	NA	FSUBS; or INCIN	Acrolein
P005	NA	107-18-6	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Allyl alcohol
P006	NA	20859-73-8	CHOXD; CHRED; or INCIN	CHOXD; CHRED; or INCIN	Aluminum phosphide

P007	NA	2763-96-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	5-Aminoethyl 3- isoxazolol
P008	NA	504-24-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	4-Aminopyridine
P009	NA	131-74-8	CHOXD; CHRED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	Ammonium picrate
P014	NA	108-95-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Thiophenol (Benzene thiol)
P015	NA	7440-41-7	RMETL or RTHRM	RMETL; or RTHRM	Beryllium dust
P016	NA	542-88-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Bis(chloromethyl)ether
P017	NA	598-31-2	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Bromoacetone
P018	NA	357-57-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Brucine
P022	Table B	75-15-0	NA	INCIN	Carbon disulfide
P023	NA	107-20-0	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Chloroacetaldehyde
P026	NA	5344-82-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	1-(o-Chlorophenyl)thio- urea
P027	NA	542-76-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	3-Chloropropionitrile
P028	NA	100-44-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Benzyl chloride

P031	NA	460-19-5	CHOXD; WETOX; or INCIN	CHOXD; WETOX; or INCIN	Cyanogen
P033	NA	506-77-4	CHOXD; WETOX; or INCIN	CHOXD; WETOX; or INCIN	Cyanogen chloride
P034	NA	131-89-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2-Cyclohexyl-4,6-di- nitrophenol
P040	NA	297-97-2	CARBN; or INCIN	FSUBS; or INCIN	O,O-Diethyl O-pyrazinyl phosphorothioate
P041	NA	311-45-5	CARBN; or INCIN	FSUBS; or INCIN	Diethyl-p-nitrophenyl phosphate
P042	NA	51-43-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Epinephrine
P043	NA	55-91-4	CARBN; or INCIN	FSUBS; or INCIN	Diisopropylfluorophos- phate (DFP)
P044	NA	60-51-5	CARBN; or INCIN	FSUBS; or INCIN	Dimethoate
P045	NA	39196-18-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Thiofanox
P046	NA	122-09-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	alpha,alpha-Dimethyl- phenethylamine
P047	NA	534-52-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	4,6-Dinitro-o-cresol salts
P049	NA	541-53-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2,4-Dithiobiuret
P054	NA	151-56-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Aziridine
P056	Table B	7782-41-4	NA	ADGAS fb NEUTR	Fluorine
P057	NA	640-19-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Fluoroacetamide

P058	NA	62-74-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Fluoroacetic acid, sodium salt
P062	NA	757-58-4	CARBN; or INCIN	FSUBS or INCIN	Hexaethyltetraphosphate
P064	NA	624-83-9	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Isocyanic acid, ethyl ester
P065	Tables A & B	628-86-4	NA	RMERC	Mercury fulminate: (High Mercury Sub- category--greater than or equal to 260 mg/kg total Mercury--either incinerator residues or residues from RMERC)
P065	Tables A & B	628-86-4	NA	IMERC	Mercury fulminate: (All nonwastewaters that are not incinerator residues or are not residues from RMERC; regardless of Mercury Content)
P066	NA	16752-77-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Methomyl
P067	NA	75-55-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2-Methylaziridine
P068	NA	60-34-4	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; OR INCIN	Methyl hydrazine
P069	NA	75-86-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Methylactonitrile
P070	NA	116-06-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Aldicarb
P072	NA	86-88-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	1-Naphthyl-2-thiourea

P075	NA	54-11-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Nicotine and salts
P076	NA	10102-43-9	ADGAS	ADGAS	Nitric oxide
P078	NA	10102-44-0	ADGAS	ADGAS	Nitrogen dioxide
P081	NA	55-63-0	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	Nitroglycerin
P082	Table B	62-75-9	NA	INCIN	N-Nitrosodimethylamine
P084	NA	4549-40-0	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	N-Nitrosomethylvinyl- amine
P085	NA	152-16-9	CARBN; or INCIN	FSUBS; or INCIN	Octamethylpyrophosphor- amide
P087	NA	20816-12-0	RMETL; or RTHM	RMETL; or RTHRM	Osmium tetroxide
P088	NA	145-73-3	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Endothall
P092	Tables A & B	62-38-4	NA	RMERC	Phenyl mercury acetate: (High Mercury Sub- category--greater than or equal to 260 mg/kg total Mercury--either incinerator residues or residues from RMERC)
P092	Tables A & B	62-38-4	NA	IMERC; or RMERC	Phenyl mercury acetate: (All nonwastewaters that are not incinerator residues and are not residues from RMERC: regardless of Mercury Content)
P093	NA	103-85-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Phenylthiourea
P095	NA	75-44-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Phosgene
P096	NA	7803-51-2	CHOXD; CH- RED; or INCIN	CHOXD; CH- RED; or INCIN	Phosphine

P102	NA	107-19-7	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Propargyl alcohol
P105	NA	26628-22-8	CHOXD; CH- RED; CARBN BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	Sodium azide
P108	NA	57-24-9 A	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Strychnine and salts
P109	NA	3689-24-5	CARBN; or INCIN	FSUBS; or INCIN	Tetraethyldithiopyro- phosphate
P112	NA	509-14-8	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	Tetranitromethane
P113	Table B	1314-32-5	NA	RTHRM; or STABL	Thallic oxide
P115	Table B	7446-18-6	NA	RTHRM; or STABL	Thallium (I) sulfate
P116	NA	79-19-6	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Thiosemicarbazide
P118	NA	75-70-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Trichloromethanethiol
P119	Table B	7803-55-6	NA	STABL	Ammonium vanadate
P120	Table B	1314-62-1	NA	STABL	Vanadium pentoxide
P122	NA	1314-84-7	CHOXD; CH- RED; or INCIN	CHOXD; CH- RED; or INCIN	Zinc Phosphide (≥10%)
U001	NA	75-07-0	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Acetaldehyde
U003	Table B	75-05-8	NA	INCIN	Acetonitrile
U006	NA	75-36-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Acetyl chloride

U007	NA	79-06-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Acrylamide
U008	NA	79-10-7	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Acrylic acid
U010	NA	50-07-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Mitomycin C
U011	NA	61-82-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Amitrole
U014	NA	492-80-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Auramine
U015	NA	115-02-6	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Azaserine
U016	NA	225-51-4	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Benz(c)acridine
U017	NA	98-87-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Benzal chloride
U020	NA	98-09-9	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Benzenesulfonyl chloride
U021	NA	92-87-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Benzidine
U023	NA	98-07-7	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	Benzotrichloride
U026	NA	494-03-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Chlornaphazin

U033	NA	353-50-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Carbonyl fluoride
U034	NA	75-87-6	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Trichloroacetaldehyde (Chloral)
U035	NA	305-03-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Chlorambucil
U038	Table B	510-15-6	NA	INCIN	Chlorobenzilate
U041	NA	106-89-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	1-Chloro-2,3-epoxy- propane (Epichloro- hydrin)
U042	Table B	110-75-8	NA	INCIN	2-Chloroethyl vinyl ether
U046	NA	107-30-2	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Chloromethyl methyl ether
U049	NA	3165-93-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	4-Chloro-o-toluidine hydrochloride
U053	NA	4170-30-3	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Crotonaldehyde
U055	NA	98-82-8	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Cumene
U056	NA	110-82-7	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Cyclohexane
U057	Table B	108-94-1	NA	FSUBS; or INCIN	Cyclohexanone
U058	NA	50-18-0	CARBN; or INCIN	FSUBS; or INCIN	Cyclophosphamide
U059	NA	20830-81-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Daunomycin

U062	NA	2303-16-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Diallate
U064	NA	189-55-9	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	1,2,7,8-Dibenzopyrene
U073	NA	91-94-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	3,3'-Dichlorobenzidine
U074	NA	1476-11-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	cis-1,4-Dichloro-2-butene; trans-1,4-Dichloro-2-butene
U085	NA	1464-53-5	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	1,2:3,4-Diepoxybutane
U086	NA	1615-80-1	CHOXD; CHRED; CARBN; BIODG; or INCIN	FSUBS; CHOXD; CHRED; or INCIN	N,N-Diethylhydrazine
U087	NA	3288-58-2	CARBN; or INCIN	FSUBS; or INCIN	O,O-Diethyl S-methyldithiophosphate
U089	NA	56-53-1	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Diethyl stilbestrol
U090	NA	94-58-6	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Dihydrosafrole
U091	NA	119-90-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	3,3'-Dimethoxybenzidine
U092	NA	124-40-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Dimethylamine
U093	Table B	621-90-9	NA	INCIN	p-Dimethylaminoazobenzene
U094	NA	57-97-6	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	7,12-Dimethylbenz(a)-anthracene

U095	NA	119-93-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	3,3'-Dimethylbenzidine
U096	NA	80-15-9	CHOXD; CHRED; CARBN; BIODG; or INCIN	FSUBS; CHOXD; CHRED; or INCIN	alpha,alpha-Dimethyl- benzyl hydroperoxide
U097	NA	79-44-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Dimethylcarbamoyl chlor- ide
U098	NA	57-14-7	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	1,1-Dimethylhydrazine
U099	NA	540-73-8	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	1,2-Dimethylhydrazine
U103	NA	77-78-1	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	Dimethyl sulfate
U109	NA	122-66-7	CHOXD; CH- RED; CARBN; BIODG; or INCIN	FSUBS; CH- OXD; CHRED; or INCIN	1,2-Diphenylhydrazine
U110	NA	142-84-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Dipropylamine
U113	NA	140-88-5	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Ethyl acrylate
U114	NA	111-54-6	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Ethylenebisdithio- carbamic acid
U115	NA	75-21-8	(WETOX or CHOXD) fb CARBN; or INCIN	CHOXD; or INCIN	Ethylene oxide

U116	NA	96-45-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Ethylene thiourea
U119	NA	62-50-0	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Ethyl methanesulfonate
U122	NA	50-00-0	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Formaldehyde
U123	NA	64-18-6	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Formic acid
U124	NA	110-00-9	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Furan
U125	NA	98-01-1	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Furfural
U126	NA	765-34-4	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Glycidaldehyde
U132	NA	70-30-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Hexachlorophene
U133	NA	302-01-2	CHOXD; CHRED; CARBN; BIODG; or INCIN	FSUBS; CHOXD; CHRED; or INCIN	Hydrazine
U134	Table B	7664-39-3	NA	ADGAS fb NEUTR; or NEUTR	Hydrogen Fluoride
U135	NA	7783-06-4	CHOXD; CH- RED; or INCIN	CHOXD; CH- RED; or INCIN	Hydrogen Sulfide
U143	NA	303-34-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Lasiocarpine

U147	NA	108-31-6	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Maleic anhydride
U148	NA	123-33-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Maleic hydrazide
U149	NA	109-77-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Malononitrile
U150	NA	148-82-3	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Melphalan
U151	Tables A & B	7439-97-6	NA	RMERC	Mercury: (High Mercury Subcategory--greater than or equal to 260 mg/kg total Mercury)
U153	NA	74-93-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Methanethiol
U154	NA	67-56-1	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Methanol
U156	NA	79-22-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Methyl chlorocarbonate
U160	NA	1338-23-4	CHOXD; CHRED; CARBN; BIODG; or INCIN	FSUBS; CHOXD; CHRED; or INCIN	Methyl ethyl ketone per- oxide
U163	NA	70-25-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	N-Methyl-N'-nitro-N- Nitrosoguanidine
U164	NA	56-04-2	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Methylthiouracil
U166	NA	130-15-4	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	1,4-Naphthoquinone

U167	NA	134-32-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	1-Naphthylamine
U168	Table B	91-59-8	NA	INCIN	2-Naphthylamine
U171	NA	79-46-9	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2-Nitropropane
U173	NA	1116-54-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	N-Nitroso-diethanolamine
U176	NA	759-73-9	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	N-Nitroso-N-ethylurea
U177	NA	684-93-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	N-Nitroso-N-methylurea
U178	NA	615-53-2	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	N-Nitroso-N-methyl- urethane
U182	NA	123-63-7	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Paraldehyde
U184	NA	76-01-7	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Pentachloroethane
U186	NA	504-60-9	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	1,3-Pentadiene
U189	NA	1314-80-3	CHOXD; CH- RED; or INCIN	CHOXD; CH- RED; or INCIN	Phosphorus sulfide
U191	NA	109-06-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2-Picoline
U193	NA	1120-71-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	1,3-Propane sultone

U194	NA	107-10-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	n-Propylamine
U197	NA	106-51-4	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	p-Benzoquinone
U200	NA	50-55-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Reserpine
U201	NA	108-46-3	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Resorcinol
U202	NA	81-07-2 A	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Saccharin and salts
U206	NA	18883-66-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Streptozatocin
U213	NA	109-99-9	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Tetrahydrofuran
U214	Table B	563-68-8	NA	RTHRM; or STABL	Thallium (I) acetate
U215	Table B	6533-73-9	NA	RTHRM; or STABL	Thallium (I) carbonate
U216	Table B	7791-12-0	NA	RTHRM; or STABL	Thallium (I) chloride
U217	Table B	10102-45-1	NA	RTHRM; or STABL	Thallium (I) nitrate
U218	NA	62-55-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Thioacetamide
U219	NA	62-56-6	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Thiourea
U221	NA	25376-45-8	CARBN; or INCIN	FSUBS; or INCIN	Toluenediamine

U222	NA	636-21-5	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	o-Toluidine hydro- chloride
U223	NA	26471-62-5	CARBN; or INCIN	FSUBS; or INCIN	Toluene diisocyanate
U234	NA	99-35-4	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	sym-Trinitrobenzene
U236	NA	72-57-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Trypan Blue
U237	NA	66-75-1	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Uracil mustard
U238	NA	51-79-6	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Ethyl carbamate
U240	NA	94-75-7* <u>A</u>	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	2,4-Dichlorophenoxy- acetic acid (salts and esters)
U244	NA	137-26-8	(WETOX or CHOXD) fb CARBN; or INCIN	INCIN	Thiram
U246	NA	506-68-3	CHOXD; WETOX; or INCIN	CHOXD; WETOX; or INCIN	Cyanogen bromide
U248	NA	81-81-2	(WETOX or CHOXD) fb CARBN; or INCIN	FSUBS; or INCIN	Warfarin (0.3% or less)
U249	NA	1314-84-7	CHOXD; CH- RED; or INCIN	CHOXD; CH- RED; or INCIN	Zinc Phosphide (<10%)
U328	NA	95-53-4	INCIN; or CHOXD fb, (BIODG or CARBN); or BIODG fb CARBN	INCIN; or Thermal Destructio n.	o-toluidine

U353	NA	106-49-0	INCIN; or CHOXD fb, (BIODG or CARN); or BIODG fb CARN	INCIN; or Thermal Destructio n.	p-toluidine
U359	NA	110-80-5	INCIN; or CHOXD fb, (BIODG or CARN); or BIODG fb CARN	INCIN; or FSUBS.	2-ethoxy-ethanol

A CAS Number given for parent compound only.

B This waste code exists in gaseous form and is not categorized as wastewater or nonwastewater forms.

NA Not Applicable.

BOARD NOTE: When a combination of these technologies (i.e., a treatment train) is specified as a single treatment standard, the order of application is specified in this Table by indicating the five letter technology code that must be applied first, then the designation "fb" (an abbreviation for "Followed by"), then the five letter technology code for the technology that must be applied next, and so on. When more than one technology (or treatment train) are specified as alternative treatment standards, the five letter technology codes (or the treatment trains) are separated by a semicolon (;) with the last technology preceded by the word "or". This indicates that any one of these BDAT technologies or treatment trains can be used for compliance with the standard. See Section 728. Table C for a listing of the technology codes and technology-based treatment standards. Derived from 40 CFR 268.42, Table 2 (1992), as amended at 57 Fed. Reg. 37273 (Aug. 18, 1992).

(Source: Amended at 18 Ill. Reg. _____, effective _____)