

ILLINOIS POLLUTION CONTROL BOARD
May 10, 1990

IN THE MATTER OF:)
)
PHARMACEUTICAL MANUFACTURING,)
VOLATILE ORGANIC EMISSIONS AND) R88-14
LIMITATIONS, 35 ILL. ADM. CODE) (Rulemaking)
211 AND 215 (ON PETITION OF)
ABBOTT LABORATORIES))

PROPOSED RULE. SECOND FIRST NOTICE.

PROPOSED ORDER OF THE BOARD (by J. Dumelle):

This matter is before the Board on a Joint Motion for Leave to File the Fourth Amended Proposal filed May 8, 1990 by Abbott Laboratories. Abbott represents that this Fourth Amended Proposal is filed as a result of the ongoing discussions between Abbott, the Agency and the U.S. Environmental Protection Agency. Abbott represents that the Agency joins in the motion. That motion is hereby granted and leave to file is allowed.

The Board has held three public hearings in this matter to date. Two additional hearings are scheduled for June 27, 1990, in Chicago, and June 28, 1990, in Waukegan.


The Board hereby proposes the text of the Fourth Amended Proposal for First Notice without passing on the merits of the proposed amendments. However, the Board has revised the text of the amendments to comply with the Illinois Administrative Code format requirements, as set forth in 1 Ill. Adm. Code 100. The Board has also added amendments to 35 Ill. Adm. Code 215.105: incorporations by reference included in the Fourth Amended Proposal in Sections 215.108 and 215.480. Section 215.105 is the Board's central listing of incorporations by reference in Part 215. The Board attempts to maintain all incorporations by reference in such a single location to facilitate finding and updating those references. The Board has not otherwise altered the text.

ORDER

The Board hereby directs the Clerk to cause the following text to be published in the Illinois Register for First Notice pursuant to 1 Ill. Adm. Code 100.Subpart D:

IT IS SO ORDERED.

I, Dorothy M. Gunn, Clerk of the Illinois Pollution Control Board, do hereby certify that the above Order was adopted on the 10th day of May, 1990, by a vote of 7-0.


 Dorothy M. Gunn, Clerk
 Illinois Pollution Control Board

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE B: AIR POLLUTION
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER c: EMISSION STANDARDS AND LIMITATIONS
 FOR STATIONARY SOURCES

PART 211
 DEFINITIONS AND GENERAL PROVISIONS

SUBPART A: GENERAL PROVISIONS

Section
 211.101 Incorporations by Reference
 211.102 Abbreviations and Units

SUBPART B: DEFINITIONS

Section
 211.121 Other Definitions
 211.122 Definitions

Appendix A Rule into Section Table
 Appendix B Section into Rule Table

AUTHORITY: Implementing Sections 9, 9.1 and 10 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1987, ch. 111 $\frac{1}{2}$, pars. 1009, 1010 and 1027, as amended by P.A. 86-366, effective January 1, 1990).

SOURCE: Adopted as Chapter 2: Air Pollution, Rule 201: Definitions, R71-23, 4 PCB 191, filed and effective April 14, 1972; amended in R74-2 and R75-5, 32 PCB 295, at 3 Ill. Reg. 5, p. 777, effective February 3, 1979; amended in R78-3 and 4, 35 PCB 75 and 243, at 3 Ill. Reg. 30, p. 124, effective July 28, 1979; amended in R80-5, at 7 Ill. Reg. 1244, effective January 21, 1983; codified at 7 Ill. Reg. 13590; amended in R82-1 (Docket A) at 10 Ill. Reg. 12624, effective July 7, 1986; amended in R85-21(A) at 11 Ill. Reg. 11747, effective June 29, 1987; amended in R86-34 at 11 Ill. Reg. 12267, effective July 10, 1987; amended in R86-39 at 11 Ill. Reg. 20804, effective December 14, 1987; amended in R82-14 and R86-37 at 12 Ill. Reg. 787, effective December 24, 1987; amended in R86-18 at 12 Ill. Reg. 7284, effective April 8, 1988; amended in R86-10 at 12 Ill. Reg. 7621,

effective April 11, 1988; amended in R88-23 at 13 Ill. Reg. 10862, effective June 27, 1989; amended in R89-8 at 13 Ill. Reg. 17457, effective January 1, 1990; amended in R88-14 at 14 Ill. Reg. , effective

SUBPART B: DEFINITIONS

Section 211.122 Definitions

"Accelacota": a pharmaceutical coating operation which consists of a horizontally rotating perforated drum in which tablets are placed, a coating is applied by spraying and the coating is dried by the flow of air across the drum through the perforations.

"Accumulator": The reservoir of a condensing unit receiving the condensate from a surface condenser.

"Acid Gases": For the purposes of Section 9.4 of the Environmental Protection Act (the Act) (Ill. Rev. Stat. 1987, ch. 111 $\frac{1}{2}$, par. 1009.4), hydrogen chloride, hydrogen fluoride and hydrogen bromide, which exist as gases, liquid mist, or any combination thereof.

"Actual Heat Input": The quantity of heat produced by the combustion of fuel using the gross heating value of the fuel.

"Aeration": The practice of forcing air through bulk stored grain to maintain the condition of the grain.

"Afterburner": A device in which materials in gaseous effluents are combusted.

"Air Dried Coating": Coatings that dry by the use of air or forced air at temperatures up to 363.15° K (194° F).

"Air suspension coater/dryer": a pharmaceutical coating operation which consists of vertical chambers in which tablets or particles are placed, and a coating is applied and then dried while the tablets or particles are kept in a fluidized state by the passage of air upward through the chambers.

"Annual Grain Through-Put": Unless otherwise shown by the owner or operator, annual grain through-put for grain-handling operations, which have been in operation for three consecutive years prior to June 30, 1975, shall be determined by adding grain receipts and shipments for the three previous fiscal years and

dividing the total by 6. The annual grain through-put for grain-handling operations in operation for less than three consecutive years prior to June 30, 1975, shall be determined by a reasonable three-year estimate; the owner or operator shall document the reasonableness of his three-year estimate.

"Architectural Coating": Any coating used for residential or commercial buildings or their appurtenances, or for industrial buildings which is site applied.

"Asphalt": The dark-brown to black cementitious material (solid, semisolid or liquid in consistency) of which the main constituents are bitumens which occur naturally or as a residue of petroleum refining.

"Asphalt Prime Coat": A low-viscosity liquid asphalt applied to an absorbent surface as the first of more than one asphalt coat.

"Automobile": Any first division motor vehicle as that term is defined in the Illinois Vehicle Code (Ill. Rev. Stat. 1987, ch. 95½, pars 1-100 et seq.).

"Automobile or Light-Duty Truck Manufacturing Plant": A facility where parts are manufactured or finished for eventual inclusion into a finished automobile or light-duty truck ready for sale to vehicle dealers, but not including customizers, body shops and other repainters.

"Batch Loading": The process of loading a number of individual parts at the same time for degreasing.

"Bead-Dipping": The dipping of an assembled tire bead into a solvent-based cement.

"British Thermal Unit": The quantity of heat required to raise one pound of water from 60° F to 61° F (abbreviated btu).

"Bulk Gasoline Plant": Any gasoline storage and distribution facility that receives gasoline from bulk gasoline terminals by delivery vessels and distributes gasoline to gasoline dispensing facilities.

"Bulk Gasoline Terminal": Any gasoline storage and distribution facility that receives gasoline by pipeline, ship or barge, and distributes gasoline to bulk gasoline plants or gasoline dispensing facilities.

"Can Coating": The application of a coating material to a single walled container that is manufactured from metal sheets thinner than 29 gauge (0.0141 in).

"Certified Investigation": A report signed by Illinois Environmental Protection Agency (Agency) personnel certifying whether a grain-handling operation (or portion thereof) or grain-drying operation is causing or tending to cause air pollution. Such report must describe the signatory's investigation, including a summary of those facts on which he relies to certify whether the grain-handling or grain-drying operation is causing or threatening or allowing the discharge or emission of any contaminant into the environment so as to cause or tend to cause air pollution in Illinois, either alone or in combination with contaminants from other sources, or so as to violate regulations or standards adopted by the Pollution Control Board (Board) under the Environmental Protection Act (Act). The certified investigation shall be open to a reasonable public inspection and may be copied upon payment of the actual cost of reproducing the original.

"Choke Loading": That method of transferring grain from the grain-handling operation to any vehicle for shipment or delivery which precludes a free fall velocity of grain from a discharge spout into the receiving container.

"Cleaning and Separating Operation": That operation where foreign and undesired substances are removed from the grain.

"Clear Coating": Coatings that lack color and opacity or are transparent using the undercoat as a reflectant base or undertone color.

"Closed Purge System": A system that is not open to the atmosphere and that is composed of piping, connections, and, if necessary, flow inducing devices that transport liquid or vapor from a piece or pieces of equipment to a control device, or return the liquid or vapor to the process line.

"Closed Vent System": A system that is not open to the atmosphere and that is composed of piping, connections, and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a control device, or return the gas or vapor to the process line.

"Coal Refuse": Waste products of coal mining, cleaning and coal preparation operations containing coal, matrix material, clay and other organic and inorganic material.

"Coating Applicator": Equipment used to apply a surface coating.

"Coating Line": An operation where a surface coating is applied to a material and subsequently the coating is dried and/or cured.

"Coating Plant": Any building, structure or installation that contains a coating line and which is located on one or more contiguous or adjacent properties and which is owned or operated by the same person (or by persons under common control).

"Coil Coating": The application of a coating material to any flat metal sheet or strip that comes in rolls or coils.

"Cold Cleaning": The process of cleaning and removing soils from surfaces by spraying, brushing, flushing or immersion while maintaining the organic solvent below its boiling point. Wipe cleaning is not included in this definition.

"Complete Combustion": A process in which all carbon contained in a fuel or gas stream is converted to carbon dioxide.

"Component": Any piece of equipment which has the potential to leak volatile organic material including, but not limited to, pump seals, compressor seals, seal oil degassing vents, pipeline valves, pressure relief devices, process drains and open ended valves. This definition excludes valves which are not externally regulated, flanges, and equipment in heavy liquid service. For purposes of 35 Ill. Adm. Code 215. Subpart Q, this definition also excludes bleed ports of gear pumps in polymer service.

"Concentrated Nitric Acid Manufacturing Process": Any acid producing facility manufacturing nitric acid with a concentration equal to or greater than 70 percent by weight.

"Condensate": Hydrocarbon liquid separated from its associated gasses which condenses due to changes in the temperature or pressure and remains liquid at standard conditions.

"Control device": Equipment, such as an afterburner, adsorber, scrubber, condenser, cyclone or baghouse used to remove or prevent the emission of air pollutants from a contaminated exhaust stream. For purposes of 35 Ill. Adm. Code 215.Subpart Q, an enclosed combustion device, vapor recovery system, flare, or closed container.

"Conveyorized Degreasing": The continuous process of cleaning and removing soils from surfaces utilizing either cold or vaporized solvents.

"Crude Oil": A naturally occurring mixture which consists of hydrocarbons and sulfur, nitrogen or oxygen derivatives of hydrocarbons and which is a liquid at standard conditions.

"Crude Oil Gathering": The transportation of crude oil or condensate after custody transfer between a production facility and a reception point.

"Custody Transfer": The transfer of produced petroleum and/or condensate after processing and/or treating in the producing operations, from storage tanks or automatic transfer facilities to pipelines or any other forms of transportation.

"Cutback Asphalt": Any asphalt which has been liquified by blending with petroleum solvents other than residual fuel oil and has not been emulsified with water.

"Degreaser": Any equipment or system used in solvent cleaning.

"Delivery Vessel": Any tank truck or trailer equipped with a storage tank that is used for the transport of gasoline to a stationary storage tank at a gasoline dispensing facility, bulk gasoline plant or bulk gasoline terminal.

"Distillate Fuel Oil": Fuel oils of grade No. 1 or 2 as specified in detailed requirements for fuel oil A.S.T.M. D-369-69 (1971).

"Dry Cleaning Facility": A facility engaged in the cleaning of fabrics using an essentially nonaqueous solvent by means of one or more solvent washes, extraction of excess solvent by spinning and drying by tumbling in an airstream. The facility includes, but is not limited to, washers, dryers, filter and

purification systems, waste disposal systems, holding tanks, pumps and attendant piping and valves.

"Dump-Pit Area": Any area where grain is received at a grain-handling or grain-drying operation.

"Effective Grate Area": That area of a dump-pit grate through which air passes, or would pass, when aspirated.

"Effluent Water Separator": Any tank, box, sump or other apparatus in which any organic material floating on or entrained or contained in water entering such tank, box, sump or other apparatus is physically separated and removed from such water prior to outfall, drainage or recovery of such water.

"Emission Rate": Total quantity of any air contaminant discharge into the atmosphere in any one-hour period.

"Enclose": with respect to Subpart T, to cover any volatile organic liquid surface that is exposed to the atmosphere.

"End Sealing Compound Coat": A compound applied to can ends which functions as a gasket when the end is assembled on the can.

"Excess Air": Air supplied in addition to the theoretical quantity necessary for complete combustion of all fuel and/or combustible waste material.

"Excessive Release": A discharge of more than 295g (0.65 pounds) of mercaptans and/or hydrogen sulfide into the atmosphere in any five minute period.

"Existing Grain-Drying Operation": Any grain-drying operation the construction or modification of which was commenced prior to June 30, 1975.

"Existing Grain-Handling Operation": Any grain-handling operation the construction or modification of which was commenced prior to June 30, 1975.

"Exterior Base Coat": An initial coating applied to the exterior of a can after the can body has been formed.

"Exterior End Coat": A coating applied by rollers or spraying to the exterior end of a can.

"External Floating Roof": A storage vessel cover in an open top tank consisting of a double deck or pontoon single deck which is supported by the petroleum liquid being contained and is equipped with a closure seal between the deck edge and tank wall.

"Extreme Performance Coating": Coatings designed for exposure to any of the following: the ambient weather conditions, temperatures above 368.15° K (203° F), detergents, abrasive and scouring agents, solvents, corrosive atmospheres, or other similar extreme environmental conditions.

"Fabric Coating": The coating of a textile substrate.

"Final Repair Coat": The repainting of any coating which is damaged during vehicle assembly.

"Firebox": The chamber or compartment of a boiler or furnace in which materials are burned, but not the combustion chamber or afterburner of an incinerator.

"Flexographic Printing": The application of words, designs and pictures to a substrate by means of a roll printing technique in which the pattern to be applied is raised above the printing roll and the image carrier is made of elastomeric materials.

"Floating Roof": A roof on a stationary tank, reservoir or other container which moves vertically upon change in volume of the stored material.

"Freeboard Height": For open top vapor degreasers, the distance from the top of the vapor zone to the top of the degreaser tank. For cold cleaning degreasers, the distance from the solvent to the top of the degreaser tank.

"Fuel Combustion Emission Source": Any furnace, boiler or similar equipment used for the primary purpose of producing heat or power by indirect heat transfer.

"Fuel Gas System": A system for collection of refinery fuel gas including, but not limited to, piping for collecting tail gas from various process units, mixing drums and controls and distribution piping.

"Fugitive Particulate Matter": Any particulate matter emitted into the atmosphere other than through a stack, provided that nothing in this definition or in 35 Ill. Adm. Code 212.Subpart K shall exempt any source from compliance with other provisions of 35 Ill. Adm. Code

212 otherwise applicable merely because of the absence of a stack.

"Gas Service": Means that the component contains process fluid that is in the gaseous state at operating conditions.

"Gasoline": Any petroleum distillate having a Reid vapor pressure of 4 pounds or greater.

"Gasoline Dispensing Facility": Any site where gasoline is transferred from a stationary storage tank to a motor vehicle gasoline tank used to provide fuel to the engine of that motor vehicle.

"Grain": The whole kernel or seed of corn, wheat, oats, soybeans and any other cereal or oil seed plant; and the normal fines, dust and foreign matter which results from harvesting, handling or conditioning. The grain shall be unaltered by grinding or processing.

"Grain-Drying Operation": Any operation, excluding aeration, by which moisture is removed from grain and which typically uses forced ventilation with the addition of heat.

"Grain-Handling and Conditioning Operation": A grain storage facility and its associate grain transfer, cleaning, drying, grinding and mixing operations.

"Grain-Handling Operation": Any operation where one or more of the following grain-related processes (other than grain-drying operation, portable grain-handling equipment, one-turn storage space, and excluding flour mills and feed mills) are performed: receiving, shipping, transferring, storing, mixing or treating of grain or other processes pursuant to normal grain operations.

"Green Tire Spraying": The spraying of green tires, both inside and outside, with release compounds which help remove air from the tire during molding and prevent the tire from sticking to the mold after curing.

"Green Tires": Assembled tires before molding and curing have occurred.

"Gross Heating Value": Amount of heat produced when a unit quantity of fuel is burned to carbon dioxide and water vapor, and the water vapor condensed as described

in A.S.T.M. D-2015-66, D-900-55, D-1826-64 and D-240-64.

"Heavy Liquid": Liquid with a true vapor pressure of less than 0.3 kPa (0.04 psi) at 294.3° K (70° F) or 0.1 Reid Vapor Pressure as determined by A.S.T.M. method D-323; or which when distilled requires a temperature of 300° F or greater to recover 10% of the liquid as determined by A.S.T.M. method D-86.

"Heavy Metals": For the purposes of Section 9.4 of the Act, elemental, ionic, or combined forms of arsenic, cadmium, mercury, chromium, nickel and lead.

"Heavy, Off-Highway Vehicle Products": For the purposes of Section 215.204(k), heavy off-highway vehicle products shall include: heavy construction, mining, farming or material handling equipment; heavy industrial engines; diesel-electric locomotives and associated power generation equipment; and the components of such equipment or engines.

"Hot Well": The reservoir of a condensing unit receiving the condensate from a barometric condenser.

"Housekeeping Practices": Those activities specifically defined in the list of housekeeping practices developed by the Joint EPA - Industry Task Force and included herein under 35 Ill. Adm. Code 212.461.

"Incinerator": Combustion apparatus in which refuse is burned.

"Indirect Heat Transfer": Transfer of heat in such a way that the source of heat does not come into direct contact with process materials.

"In-Process Tank": A container used for mixing, blending, heating, reacting, holding, crystallizing, evaporating, or cleaning operations in the manufacture of pharmaceuticals.

"In-situ Sampling Systems": Nonextractive samplers or in-line samplers.

"Interior Body Spray Coat": A coating applied by spray to the interior of a can after the can body has been formed.

"Internal Transferring Area": Areas and associated equipment used for conveying grain among the various grain operations.

"Large Appliance Coating": The application of a coating material to the component metal parts (including but not limited to doors, cases, lids, panels and interior support parts) of residential and commercial washers, dryers, ranges, refrigerators, freezers, water heaters, dishwashers, trash compactors, air conditioners and other similar products.

"Light-Duty Truck": Any second division motor vehicle, as that term is defined in the Illinois Vehicle Code, (Ill. Rev. Stat. 1987, ch. 95½, pars. 1-100 et seq.) weighing less than 3854 kilograms (8500 pounds) gross.

"Liquid-Mounted Seal": A primary seal mounted in continuous contact with the liquid between the tank wall and the floating roof edge around the circumference of the roof.

"Liquid Service": Means that the equipment or component contains process fluid that is in a liquid state at operating conditions.

"Liquids Dripping": Any visible leaking from a seal including spraying, misting, clouding and ice formation.

"Load-Out Area": Any area where grain is transferred from the grain-handling operation to any vehicle for shipment or delivery.

"Low Solvent Coating": A coating which contains less organic solvent than the conventional coatings used by the industry. Low solvent coatings include water-borne, higher solids, electro-deposition and powder coatings.

"Magnet Wire Coating": The application of a coating of electrically insulating varnish or enamel to conducting wire to be used in electrical machinery.

"Major Dump Pit": Any dump pit with an annual grain through-put of more than 300,000 bushels, or which receives more than 40% of the annual grain through-put of the grain-handling operation.

"Major Metropolitan Area (MMA)": Any county or group of counties which is defined by the following Table:

MAJOR METROPOLITAN AREAS IN ILLINOIS (MMA's)

MMA	COUNTIES INCLUDED IN MMA
Champaign-Urbana	Champaign
Chicago	Cook, Lake; Will, DuPage, McHenry, Kane, Grundy, Kendall, Kankakee
Decatur	Macon
Peoria	Peoria, Tazewell
Rockford	Winnebago
Rock Island -- Moline	Rock Island
Springfield	Sangamon
St. Louis (Illinois)	St. Clair, Madison
Bloomington -- Normal	McLean

"Major Population Area (MPA)": Areas of major population concentration in Illinois, as described below:

The area within the counties of Cook; Lake; DuPage; Will; the townships of Burton, Richmond, McHenry, Greenwood, Nunda, Door, Algonquin, Grafton and the municipality of Woodstock, plus a zone extending two miles beyond the boundary of said municipality located in McHenry County; the townships of Dundee, Rutland, Elgin, Plato, St. Charles, Campton, Geneva, Blackberry, Batavia, Sugar Creek and Aurora located in Kane County; and the municipalities of Kankakee, Bradley and Bourbonnais, plus a zone extending two miles beyond the boundaries of said municipalities in Kankakee County.

The area within the municipalities of Rockford and Loves Park, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Rock Island, Moline, East Moline, Carbon Cliff, Milan, Oak Grove, Silvis, Hampton, Greenwood and Coal Valley, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Galesburg and East Galesburg, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Bartonville, Peoria and Peoria Heights, plus a zone extending

two miles beyond the boundaries of said municipalities.

The area within the municipalities of Pekin, North Pekin, Marquette Heights, Creve Coeur and East Peoria, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Bloomington and Normal, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Champaign, Urbana and Savoy, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Decatur, Mt. Zion, Harristown and Forsyth, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the municipalities of Springfield, Leland Grove, Jerome, Southern View, Grandview, Sherman and Chatham, plus a zone extending two miles beyond the boundaries of said municipalities.

The area within the townships of Godfrey, Foster, Wood River, Fort Russell, Chouteau, Edwardsville, Venice, Nameoki, Alton, Granite City and Collinsville located in Madison County; and the townships of Stites, Canteen, Centreville, Caseyville, St. Clair, Sugar Loaf and Stookey located in St. Clair County.

"Manufacturing Process": A process emission source or series of process emission sources used to convert raw materials, feed stocks, subassemblies or other components into a product, either for sale or for use as a component in a subsequent manufacturing process.

"Metal Furniture Coating": The application of a coating material to any furniture piece made of metal or any metal part which is or will be assembled with other metal, wood, fabric, plastic or glass parts to form a furniture piece including, but not limited to, tables, chairs, wastebaskets, beds, desks, lockers, benches, shelving, file cabinets, lamps and room dividers. This definition shall not apply to any coating line coating metal parts or products that is identified under the Standard Industrial Classification

Code for Major Groups 33, 34, 35, 36, 37, 38, 39, 40 or 41.

"Miscellaneous Fabricated Product Manufacturing Process":

A manufacturing process involving one or more of the following applications, including any drying and curing of formulations, and capable of emitting volatile organic material:

Adhesives to fabricate or assemble non-furniture components or products

Asphalt solutions to paper or fiberboard

Asphalt to paper or felt

Coatings or dye to leather

Coatings to plastic

Coatings to rubber or glass

Curing of furniture adhesives in an oven which would emit in excess of 10 tons of volatile organic material per year if no air pollution control equipment were used

Disinfectant material to manufactured items

Plastic foam scrap or "fluff" from the manufacture of foam containers and packaging material to form resin pellets

Resin solutions to fiber substances

Rubber solutions to molds

Viscose solutions for food casings

The storage and handling of formulations associated with the process described above.

The use and handling of organic liquids and other substances for clean-up operations associated with the process described above.

"Miscellaneous Formulation Manufacturing Process":

A manufacturing process which compounds one or more of the following and is capable of emitting volatile organic material:

Adhesives

Asphalt solutions

Caulks, sealants or waterproofing agents

Coatings, other than paint and ink

Concrete curing compounds

Dyes

Friction materials and compounds

Resin solutions

Rubber solutions

Viscose solutions

The storage and handling of formulations associated with the process described above.

The use and handling of organic liquids and other substances for clean-up operations associated with the process described above.

"Miscellaneous Metal Parts and Products": For the purpose of 35 Ill. Adm. Code 215.204, miscellaneous metal parts and products shall include farm machinery, garden machinery, small appliances, commercial machinery, industrial machinery, fabricated metal products and any other industrial category which coats metal parts or products under the Standard Industrial Classification Code for Major Groups 33, 34, 35, 36, 37, 38 or 39 with the exception of the following: coating lines subject to 35 Ill. Adm. Code 215.204(a)-(i) and (k), automobile or light-duty truck refinishing, the exterior of marine vessels and the customized top coating of automobiles and trucks if production is less than thirty-five vehicles per day.

"Miscellaneous Organic Chemical Manufacturing Process":

A manufacturing process which produces by chemical reaction, one or more of the following organic compounds or mixtures of organic compounds and

which is capable of emitting volatile organic materials:

Chemicals listed in 35 Ill. Adm. Code 215. Appendix D.

Chlorinated and sulfonated compounds

Cosmetic, detergent, soap or surfactant intermediaries or specialties and products

Disinfectants

Food additives

Oil and petroleum product additives

Plasticizers

Resins or polymers

Rubber additives

Sweeteners

Varnishes

The storage and handling of formulations associated with the process described above.

The use and handling of organic liquids and other substances for clean-up operations associated with the process described above.

"Mixing Operation": The operation of combining two or more ingredients, of which at least one is a grain.

"New Grain-Drying Operation": Any grain-drying operation the construction or modification of which is commenced on or after June 30, 1975.

"New Grain-Handling Operation": Any grain-handling operation the construction or modification of which is commenced on or after June 30, 1975.

"No Detectable Volatile Organic Material Emissions": A discharge of volatile organic material into the atmosphere as indicated by an instrument reading of less than 500 ppm above background as determined in accordance with 40 CFR 60.485(c).

"One Hundred Percent Acid": Acid with a specific gravity of 1.8205 at 30° C in the case of sulfuric acid and 1.4952 at 30° C in the case of nitric acid.

"One-Turn Storage Space": That space used to store grain with a total annual through-put not in excess of the total bushel storage of that space.

"Opacity": A condition which renders material partially or wholly impervious to transmittance of light and causes obstruction of an observer's view. For the purposes of these regulations, the following equivalence between opacity and Ringelmann shall be employed:

Opacity Percent	Ringelmann
10	0.5
20	1.
30	1.5
40	2.
60	3.
80	4.
100	5.

"Open Top Vapor Degreasing": The batch process of cleaning and removing soils from surfaces by condensing hot solvent vapor on the colder metal parts.

"Operator of Gasoline Dispensing Facility": Any person who is the lessee of or operates, controls or supervises a gasoline dispensing facility.

"Organic Material": Any chemical compound of carbon including diluents and thinners which are liquids at standard conditions and which are used as dissolvers, viscosity reducers or cleaning agents, but excluding methane, carbon monoxide, carbon dioxide, carbonic acid, metallic carbonic acid, metallic carbide, metallic carbonates and ammonium carbonate.

"Organic Materials": For the purposes of Section 9.4 of the Act, any chemical compound of, carbon including diluents and thinners which are liquids at standard conditions and which are used as dissolvers, viscosity reducers or cleaning agents, and polychlorinated dibenzo-p-dioxins, polychlorinated dibenzofurans and polynuclear aromatic hydrocarbons are organic materials, while methane, carbon monoxide, carbon dioxide, carbonic acid, metallic carbonic acid, metallic carbide, metallic carbonates and ammonium carbonate are organic materials.

"Organic Vapor": Gaseous phase of an organic material or a mixture of organic materials present in the atmosphere.

"Overvarnish": A coating applied directly over ink or printing.

"Owner of Gasoline Dispensing Facility": Any person who has legal or equitable title to a stationary storage tank at a gasoline dispensing facility.

"Packaging Rotogravure Printing": Rotogravure printing upon paper, paper board, metal foil, plastic film and other substrates, which are, in subsequent operations, formed into packaging products or labels for articles to be sold.

"Paint Manufacturing Plant": A plant that mixes, blends, or compounds enamels, lacquers, sealers, shellacs, stains, varnishes or pigmented surface coatings.

"Paper Coating": The application of a coating material to paper or pressure sensitive tapes, regardless of substrate, including web coating on plastic fibers and decorative coatings on metal foil.

"Particulate Matter": Any solid or liquid material, other than water, which exists in finely divided form.

"Petroleum Liquid": Crude oil, condensate or any finished or intermediate product manufactured at a petroleum refinery, but not including Number 2 through Number 6 fuel oils as specified in A.S.T.M. D-396-69, gas turbine fuel oils Numbers 2-GT through 4-GT as specified in A.S.T.M. D-2880-71 or diesel fuel oils Numbers 2-D and 4-D, as specified in A.S.T.M. D-975-68.

"Petroleum Refinery": Any facility engaged in producing gasoline, kerosene, distillate fuel oils, residual fuel oils, lubricants, or other products through distillation, cracking, extraction or reforming of unfinished petroleum derivatives.

"Pharmaceutical": Any compound or mixture, other than food, used in the prevention, diagnosis, alleviation, treatment or cure of disease in man and animal.

"Pharmaceutical Coating Operation": a device in which a coating is applied to a pharmaceutical, including any drying or curing of the coating.

"Photochemically Reactive Material": Any organic material with an aggregate of more than 20 percent of its total volume composed of the chemical compounds classified below or the composition of which exceeds any of the following individual percentage composition limitations. Whenever any photochemically reactive material or any constituent of any organic material may be classified from its chemical structure into more than one of the above groups of organic materials it shall be considered as a member of the most reactive group, that is, the group having the least allowable percent of the total organic materials.

A combination of hydrocarbons, alcohols, aldehydes, esters, ethers or ketones having an olefinic or cyclo-olefinic types of unsaturation: 5 percent. This definition does not apply to perchlorethylene or trichloroethylene.

A combination of aromatic compounds with eight or more carbon atoms to the molecule except ethylbenzene: 8 percent.

A combination of ethylbenzene, ketones having branched hydrocarbon structures or toluene: 20 percent.

"Plant": all of the pollutant-emitting activities which belong to the same industrial grouping, are located on one or more contiguous or adjacent properties, and are under the control of the same person (or persons under common control), except the activities of any marine vessel. Pollutant-emitting activities shall be considered as part of the same industrial grouping if they belong to the same major group (i.e., which have the same two-digit code) as described in the "Standard Industrial Classification Manual", 1987.

"Pneumatic Rubber Tire Manufacture": The production of pneumatic rubber tires with a bead diameter up to but not including 20.0 inches and cross section dimension up to 12.8 inches, but not including specialty tires for antique or other vehicles when produced on equipment separate from normal production lines for passenger or truck type tires.

"Polybasic Organic Acid Partial Oxidation Manufacturing Process": Any process involving partial oxidation of hydrocarbons with air to manufacture polybasic acids or their anhydrides, such as maleic anhydride, phthalic

anhydride, terephthalic acid, isophthalic acid, trimellitic anhydride.

"Portable Grain-Handling Equipment": Any equipment (excluding portable grain dryers) that is designed and maintained to be movable primarily for use in a non-continuous operation for loading and unloading one-turn storage space, and is not physically connected to the grain elevator, provided that the manufacturer's rated capacity of the equipment does not exceed 10,000 bushels per hour.

"Portland Cement Process": Any facility manufacturing portland cement by either the wet or dry process.

"Power Driven Fastener Coating": The coating of nail, staple, brad and finish nail fasteners where such fasteners are fabricated from wire or rod of 0.0254 inch diameter or greater, where such fasteners are bonded into coils or strips, such coils and strips containing a number of such fasteners, which fasteners are manufactured for use in power tools, and which fasteners must conform with formal standards for specific uses established by various federal and national organizations including Federal Specification FF-N-105b of the General Services Administration dated August 23, 1977 (does not include any later amendments or editions; U.S. Army Armament Research and Development Command, Attn: DRDAR-TST, Rock Island, IL 61201), Bulletin UM-25d of the U.S. Department of Housing and Urban Development - Federal Housing Administration dated September 5, 1973 (does not include any later amendments or editions; Department of HUD, 547 W. Jackson Blvd., Room 1005, Chicago, IL 60606), and the Model Building Code of the Council of American Building Officials, and similar standards. For the purposes of this definition, the terms "brad" and "finish nail" refer to single leg fasteners fabricated in the same manner as staples. The application of coatings to staple, brad, and finish nail fasteners may be associated with the incremental forming of such fasteners in a cyclic or repetitious manner (incremental fabrication) or with the forming of strips of such fasteners as a unit from a band of wires (unit fabrication).

"PPM (Vol) - (Parts per Million) (Volume)": A volume/volume ratio which expresses the volumetric concentration of gaseous air contaminant in a million unit volumes of gas.

"Pressure Release": The emission of materials resulting from system pressure being greater than set pressure of the pressure relief device.

"Pressure Tank": A tank in which fluids are stored at a pressure greater than atmospheric pressure.

"Prime Coat": The first film of coating material applied in a multiple coat operation.

"Prime Surfacer Coat": A film of coating material that touches up areas on the surface not adequately covered by the prime coat before application of the top coat.

"Process": Any stationary emission source other than a fuel combustion emission source or an incinerator.

"Process Unit": Components assembled to produce, as intermediate or final products, one or more of the chemicals listed in 35 Ill. Adm. Code 215. Appendix D. A process unit can operate independently if supplied with sufficient feed or raw materials and sufficient storage facilities for the product.

"Process Unit Shutdown": A work practice or operational procedure that stops production from a process unit or part of a process unit. An unscheduled work practice or operational procedure that stops production from a process unit or part of a process unit for less than 24 hours is not a process unit shutdown. The use of spare components and technically feasible bypassing of components without stopping production is not a process unit shutdown.

"Process Weight Rate": The actual weight or engineering approximation thereof of all materials except liquid and gaseous fuels and combustion air, introduced into any process per hour. For a cyclical or batch operation, the process weight rate shall be determined by dividing such actual weight or engineering approximation thereof by the number of hours of operation excluding any time during which the equipment is idle. For continuous processes, the process weight rate shall be determined by dividing such actual weight or engineering approximation thereof by the number of hours in one complete operation, excluding any time during which the equipment is idle.

"Production Equipment Exhaust System": A system for collecting and directing into the atmosphere emissions of volatile organic material from reactors, centrifuges and other process emission sources.

"Publication Rotogravure Printing": Rotogravure printing upon paper which is subsequently formed into books, magazines, catalogues, brochures, directories, newspaper supplements or other types of non-packaging printed materials.

"Purged Process Fluid": Liquid or vapor from a process unit that contains volatile organic material and that results from flushing or cleaning the sample line(s) of a process unit so that an uncontaminated sample may then be taken for testing or analysis.

"Reactor": A vat, vessel or other device in which chemical reactions take place.

"Reasonably Available Control Technology (RACT)": The lowest emission limitation that an emission source is capable of meeting by the application of control technology that is reasonably available considering technological and economic feasibility.

"Refinery Fuel Gas": Any gas which is generated by a petroleum refinery process unit and which is combusted at the refinery, including any gaseous mixture of natural gas and fuel gas.

"Refinery Unit, Process Unit or Unit": A set of components which are a part of a basic process operation such as distillation, hydrotreating, cracking or reforming of hydrocarbons.

"Refrigerated condenser": a surface condenser in which the coolant supplied to the condenser has been cooled by a mechanical device, other than by a cooling tower or evaporative spray cooling, such as a refrigeration unit or steam chiller unit.

"Residual Fuel Oil": Fuel oils of grade No. 4, 5 and 6 as specified in detailed requirements for fuel oils A.S.T.M. D-396-69 (1971).

"Restricted Area": The area within the boundaries of any "municipality" as defined in the Illinois Municipal Code, plus a zone extending one mile beyond the boundaries of any such municipality having a population of 1000 or more according to the latest federal census.

"Ringelmann Chart": The chart published and described in the Bureau of Mines, U.S. Department of Interior, Information Circular 8333 (Revision of IC7718) May 1,

1967, or any adaptation thereof which has been approved by the Agency.

"Roadway": Any street, highway, road, alley, sidewalk, parking lot, airport, rail bed or terminal, bikeway, pedestrian mall or other structure used for transportation purposes.

"Roll Printing": The application of words, designs and pictures to a substrate usually by means of a series of hard rubber or metal rolls each with only partial coverage.

"Rotogravure Printing": The application of words, designs and pictures to a substrate by means of a roll printing technique in which the pattern to be applied is recessed relative to the non-image area.

"Safety Relief Valve": A valve which is normally closed and which is designed to open in order to relieve excessive pressures within a vessel or pipe.

"Sandblasting": The use of a mixture of sand and air at high pressures for cleaning and/or polishing any type of surface.

"Sensor": A device that measures a physical quantity or the change in a physical quantity such as temperature, pressure, flow rate, pH, or liquid level.

"Set of Safety Relief Valves": One or more safety relief valves designed to open in order to relieve excessive pressures in the same vessel or pipe.

"Sheet Basecoat": A coating applied to metal when the metal is in sheet form to serve as either the exterior or interior of a can for either two-piece or three-piece cans.

"Shotblasting": The use of a mixture of any metallic or non-metallic substance and air at high pressures for cleaning and/or polishing any type of surface.

"Side-Seam Spray Coat": A coating applied to the seam of a three-piece can.

"Smoke": Small gas-borne particles resulting from incomplete combustion, consisting predominately but not exclusively of carbon, ash and other combustible material, that form a visible plume in the air.

"Smokeless Flare": A combustion unit and the stack to which it is affixed in which organic material achieves combustion by burning in the atmosphere such that the smoke or other particulate matter emitted to the atmosphere from such combustion does not have an appearance density or shade darker than No. 1 of the Ringlemann Chart.

"Solvent Cleaning": The process of cleaning soils from surfaces by cold cleaning, open top vapor degreasing or conveyORIZED degreasing.

"Specialty High Gloss Catalyzed Coating": Commercial contract finishing of material prepared for printers and lithographers where the finishing process uses a solvent-borne coating, formulated with a catalyst, in a quantity of no more than 12,000 gallons/year as supplied, where the coating machines are sheet fed and the coated sheets are brought to a minimum surface temperature of 190° F, and where the coated sheets are to achieve the minimum specular reflectance index of 65 measured at a 60 degree angle with a gloss meter.

"Splash Loading": A method of loading a tank, railroad tank car, tank truck or trailer by use of other than a submerged loading pipe.

"Stack": A flue or conduit, free-standing or with exhaust port above the roof of the building on which it is mounted, by which air contaminants are emitted into the atmosphere.

"Standard Conditions": A temperature of 70° F and a pressure of 14.7 pounds per square inch absolute (psia).

"Standard Cubic Foot (scf)": The volume of one cubic foot of gas at standard conditions.

"Startup": The setting in operation of an emission source for any purpose.

"Stationary Emission Source": An emission source which is not self-propelled.

"Stationary Storage Tank": Any container of liquid or gas which is designed and constructed to remain at one site.

"Submerged Loading Pipe": Any loading pipe the discharge opening of which is entirely submerged when the liquid level is 6 inches above the bottom of the

tank. When applied to a tank which is loaded from the side, any loading pipe the discharge of which is entirely submerged when the liquid level is 18 inches or two times the loading pipe diameter, whichever is greater, above the bottom of the tank. The definition shall also apply to any loading pipe which is continuously submerged during loading operations.

"Sulfuric Acid Mist": Sulfuric acid mist as measured according to the method specified in 35 Ill. Adm. Code 214.101(b).

"Surface Condenser": A device which removes a substance from a gas stream by reducing the temperature of the stream, without direct contact between the coolant and the stream.

"Synthetic Organic Chemical or Polymer Manufacturing Plant": A plant that produces, as intermediates or final products, one or more of the chemicals or polymers listed in 35 Ill. Adm. Code 215.Appendix D.

"Tablet coating operation": a pharmaceutical coating operation in which tablets are coated.

"Top Coat": A film of coating material applied in a multiple coat operation other than the prime coat, final repair coat or prime surfacer coat.

"Transfer Efficiency": The weight or volume of coating adhering to the material being coated divided by the weight or volume of coating delivered to the coating applicator and multiplied by 100 to equal a percentage.

"Tread End Cementing": The application of a solvent-based cement to the tire tread ends.

"True Vapor Pressure": The equilibrium partial pressure exerted by a petroleum liquid as determined in accordance with methods described in American Petroleum Institute Bulletin 2517, "Evaporation Loss From Floating Roof Tanks" (1962).

"Turnaround": The procedure of shutting down an operating refinery unit, emptying gaseous and liquid contents to do inspection, maintenance and repair work, and putting the unit back into production.

"Undertread Cementing": The application of a solvent-based cement to the underside of a tire tread.

"Unregulated Safety Relief Valve": A safety relief valve which cannot be actuated by a means other than high pressure in the pipe or vessel which it protects.

"Vacuum Producing System": Any reciprocating, rotary or centrifugal blower or compressor, or any jet ejector or device that creates suction from a pressure below atmospheric and discharges against a greater pressure.

"Valves Not Externally Regulated": Valves that have no external controls, such as in-line check valves.

"Vapor Balance System": Any combination of pipes or hoses which creates a closed system between the vapor spaces of an unloading tank and a receiving tank such that vapors displaced from the receiving tank are transferred to the tank being unloaded.

"Vapor Collection System": All piping, seals, hoses, connections, pressure-vacuum vents, and other possible sources between the gasoline delivery vessel and the vapor processing unit and/or the storage tanks and vapor holder.

"Vapor Control System": Any system that prevents release to the atmosphere of organic material in the vapors displaced from a tank during the transfer of gasoline.

"Vapor-Mounted Primary Seal": A primary seal mounted with an air space bounded by the bottom of the primary seal, the tank wall, the liquid surface and the floating roof.

"Vinyl Coating": The application of a topcoat or printing to vinyl coated fabric or vinyl sheets.

"Volatile Organic Liquid": Any liquid which contains volatile organic material.

"Volatile Organic Material":

Any organic material which participates in atmospheric photochemical reactions unless specifically exempted from this definition. Volatile organic material emissions shall be measured by the reference methods specified under 40 CFR 60, Appendix A (1986) (no future amendments or editions are included), or, if no reference method is applicable, may be determined by mass balance calculations.

For purposes of this definition, the following are not volatile organic materials:

Chlorodifluoroethane (HCFC-142b)
 Chlorodifluoromethane (CFC-22)
 Chloropentafluoroethane (CFC-115)
 Dichlorodifluoromethane (CFC-12)
 Dichlorofluoroethane (HCFC-141b)
 Dichlorotetrafluoroethane (CFC-114)
 Dichlorotrifluoroethane (HCFC-123)
 Ethane
 Methane
 Dichloromethane (Methylene chloride)
 Tetrafluoroethane (HFC-134a)
 Trichloroethane (Methyl chloroform)
 Trichlorofluoromethane (CFC-11)
 Trichlorotrifluoroethane (CFC-113)
 Trifluoromethane (FC-23)

"Volatile Petroleum Liquid": Any petroleum liquid with a true vapor pressure that is greater than 1.5 psia (78 millimeters of mercury) at standard conditions.

"Wastewater (Oil/Water) Separator": Any device or piece of equipment which utilizes the difference in density between oil and water to remove oil and associated chemicals of water, or any device, such as a flocculation tank or a clarifier, which removes petroleum derived compounds from waste water.

"Weak Nitric Acid Manufacturing Process": Any acid producing facility manufacturing nitric acid with a concentration of less than 70 percent by weight.

"Woodworking": The shaping, sawing, grinding, smoothing, polishing and making into products of any form or shape of wood.

(Source: Amended at 14 Ill. Reg. , effective

TITLE 35: ENVIRONMENTAL PROTECTION
 SUBTITLE B: AIR POLLUTION
 CHAPTER I: POLLUTION CONTROL BOARD
 SUBCHAPTER c: EMISSIONS STANDARDS AND LIMITATIONS FOR
 STATIONARY SOURCES

PART 215
 ORGANIC MATERIAL EMISSION STANDARDS AND LIMITATIONS

SUBPART A: GENERAL PROVISIONS

Section	
215.100	Introduction
215.101	Clean-up and Disposal Operations
215.102	Testing Methods
215.103	Abbreviations and Conversion Factors
215.104	Definitions
215.105	Incorporation by Reference
215.106	Afterburners
215.107	Determination of Applicability

SUBPART B: ORGANIC EMISSIONS FROM STORAGE AND LOADING OPERATIONS

Section	
215.121	Storage Containers
215.122	Loading Operations
215.123	Petroleum Liquid Storage Tanks
215.124	External Floating Roofs
215.125	Compliance Dates and Geographical Areas
215.126	Compliance Plan

SUBPART C: ORGANIC EMISSIONS FROM MISCELLANEOUS EQUIPMENT

Section	
215.141	Separation Operations
215.142	Pumps and Compressors
215.143	Vapor Blowdown
215.144	Safety Relief Valves

SUBPART E: SOLVENT CLEANING

Section	
215.181	Solvent Cleaning in General
215.182	Cold Cleaning
215.183	Open Top Vapor Degreasing
215.184	Conveyorized Degreasing
215.185	Compliance Plan

SUBPART F: COATING OPERATIONS

Section	
215.202	Compliance Schedules
215.204	Emission Limitations for Manufacturing Plants
215.205	Alternative Emission Limitations
215.206	Exemptions from Emission Limitations
215.207	Compliance by Aggregation of Emission Sources
215.208	Testing Methods for Solvent Content
215.209	Exemption from General Rule on Use of Organic Material
215.210	Alternative Compliance Schedule
215.211	Compliance Dates and Geographical Areas
215.212	Compliance Plan
215.213	Special Requirements for Compliance Plan

SUBPART H: SPECIAL LIMITATIONS FOR SOURCES IN MAJOR URBANIZED
AREAS WHICH ARE NONATTAINMENT FOR OZONE

Section
215.240 Applicability
215.241 External Floating Roofs
215.245 Flexographic and Rotogravure Printing
215.249 Compliance Dates

SUBPART I: ADJUSTED RACT EMISSIONS LIMITATIONS

Section
215.260 Applicability
215.261 Petition
215.263 Public Hearing
215.264 Board Action
215.267 Agency Petition

SUBPART K: USE OF ORGANIC MATERIAL

Section
215.301 Use of Organic Material
215.302 Alternative Standard
215.303 Fuel Combustion Emission Sources
215.304 Operations with Compliance Program
215.305 Viscose Exemption (Repealed)

SUBPART N: VEGETABLE OIL PROCESSING

Section
215.340 Hexane Extraction Soybean Crushing
215.342 Hexane Extraction Corn Oil Processing
215.344 Recordkeeping For Vegetable Oil Processes
215.345 Compliance Determination
215.346 Compliance Dates and Geographical Areas
215.347 Compliance Plan

SUBPART P: PRINTING AND PUBLISHING

Section
215.401 Flexographic and Rotogravure Printing
215.402 Exemptions
215.403 Applicability of Subpart K
215.404 Testing and Monitoring
215.405 Compliance Dates and Geographical Areas
215.406 Alternative Compliance Plan
215.407 Compliance Plan
215.408 Heatset Web Offset Lithographic Printing

SUBPART Q: LEAKS FROM SYNTHETIC ORGANIC CHEMICAL AND
POLYMER MANUFACTURING EQUIPMENT

Section
215.420 Applicability
215.421 General Requirements
215.422 Inspection Program Plan for Leaks
215.423 Inspection Program for Leaks
215.424 Repairing Leaks

215.425 Recordkeeping for Leaks
 215.426 Reporting for Leaks
 215.427 Alternative Program for Leaks
 215.428 Compliance Dates
 215.429 Compliance Plan
 215.430 General Requirements
 215.431 Inspection Program Plan for Leaks
 215.432 Inspection Program for Leaks
 215.433 Repairing Leaks
 215.434 Recordkeeping for Leaks
 215.435 Report for Leaks
 215.436 Alternative Program for Leaks
 215.437 Open-Ended Valves
 215.438 Standards for Control Devices
 215.439 Compliance Plan

SUBPART R: PETROLEUM REFINING AND RELATED INDUSTRIES; ASPHALT
 MATERIALS

Section

215.441 Petroleum Refinery Waste Gas Disposal
 215.442 Vacuum Producing Systems
 215.443 Wastewater (Oil/Water) Separator
 215.444 Process Unit Turnarounds
 215.445 Leaks: General Requirements
 215.446 Monitoring Program Plan for Leaks
 215.447 Monitoring Program for Leaks
 215.448 Recordkeeping for Leaks
 215.449 Reporting for Leaks
 215.450 Alternative Program for Leaks
 215.451 Sealing Device Requirements
 215.452 Compliance Schedule for Leaks
 215.453 Compliance Dates and Geographical Areas

SUBPART S: RUBBER AND MISCELLANEOUS PLASTIC PRODUCTS

Section

215.461 Manufacture of Pneumatic Rubber Tires
 215.462 Green Tire Spraying Operations
 215.463 Alternative Emission Reduction Systems
 215.464 Testing and Monitoring
 215.465 Compliance Dates and Geographical Areas
 215.466 Compliance Plan

SUBPART T: PHARMACEUTICAL MANUFACTURING

Section

215.480 Applicability of Subpart T
 215.481 Control of Reactors, Distillation Units, Crystallizers,
 Centrifuges and Vacuum Dryers
 215.482 Control of Air Dryers, Production Equipment Exhaust
 Systems and Filters
 215.483 Material Storage and Transfer
 215.484 In-Process Tanks
 215.485 Leaks

215.486 Other Emission Sources
 215.487 Testing
 215.488 Monitors for Air Pollution Control Equipment
~~215.489 Compliance Schedule~~
215.489 Recordkeeping
~~215.489~~215.490 Compliance Schedule

SUBPART U: COKE MANUFACTURING AND BY-PRODUCT RECOVERY

Section
 215.500 Exceptions
 215.510 Coke By-Product Recovery Plants
 215.512 Coke By-Product Recovery Plant Leaks
 215.513 Inspection Program
 215.514 Recordkeeping Requirements
 215.515 Reporting Requirements
 215.516 Compliance Dates
 215.517 Compliance Plan

SUBPART V: AIR OXIDATION PROCESSES

Section
 215.520 Applicability
 215.521 Definitions
 215.525 Emission Limitations for Air Oxidation Processes
 215.526 Testing and Monitoring
 215.527 Compliance Date

SUBPART W: AGRICULTURE

Section
 215.541 Pesticide Exception

SUBPART X: CONSTRUCTION

Section
 215.561 Architectural Coatings
 215.562 Paving Operations
 215.563 Cutback Asphalt

SUBPART Y: GASOLINE DISTRIBUTION

Section
 215.581 Bulk Gasoline Plants
 215.582 Bulk Gasoline Terminals
 215.583 Gasoline Dispensing Facilities
 215.584 Gasoline Delivery Vessels
 215.585 Gasoline Volatility Standards

EMERGENCY

SUBPART Z: DRY CLEANERS

Section
 215.601 Perchloroethylene Dry Cleaners
 215.602 Exemptions
 215.603 Testing and Monitoring
 215.604 Compliance Dates and Geographical Areas
 215.605 Compliance Plan

215.606 Exception to Compliance Plan
 215.607 Standards for Petroleum Solvent Dry Cleaners
 215.608 Operating Practices for Petroleum Solvent Dry Cleaners
 215.609 Program for Inspection and Repair of Leaks
 215.610 Testing and Monitoring
 215.611 Exemption for Petroleum Solvent Dry Cleaners
 215.612 Compliance Dates and Geographical Areas
 215.613 Compliance Plan

SUBPART AA: PAINT AND INK MANUFACTURING

Section
 215.620 Applicability
 215.621 Exemption for Waterbase Material and Heatset Offset Ink
 215.623 Permit Conditions
 215.624 Open-top Mills, Tanks, Vats or Vessels
 215.625 Grinding Mills
 215.628 Leaks
 215.630 Clean Up
 215.636 Compliance Date

SUBPART BB: POLYSTYRENE PLANTS

Section
 215.875 Applicability of Subpart BB
 215.877 Emissions Limitation at Polystyrene Plants
 215.879 Compliance Date
 215.881 Compliance Plan
 215.883 Special Requirements for Compliance Plan
 215.886 Testing and Monitoring

SUBPART PP: MISCELLANEOUS FABRICATED PRODUCT MANUFACTURING PROCESSES

Section
 215.920 Applicability
 215.923 Permit Conditions
 215.926 Control Requirements

SUBPART QQ: MISCELLANEOUS FORMULATION MANUFACTURING PROCESSES

Section
 215.940 Applicability
 215.943 Permit Conditions
 215.946 Control Requirements

SUBPART RR: MISCELLANEOUS ORGANIC CHEMICAL MANUFACTURING PROCESSES

Section
 215.960 Applicability
 215.963 Permit Conditions
 215.966 Control Requirements

Appendix A Rule Into Section Table
 Appendix B Section Into Rule Table
 Appendix C Past Compliance Dates

Appendix D	List of Chemicals Defining Synthetic Organic Chemical and Polymer Manufacturing
Appendix E	Reference Methods and Procedures
Appendix F	Coefficients for the Total Resource Effectiveness Index (TRE) Equation

AUTHORITY: Implementing Section 22 and authorized by Section 27 of the Environmental Protection Act (Ill. Rev. Stat. 1985, ch. 111-1/2, pars. 1022 and 1027).

SOURCE: Adopted as Chapter 2: Air Pollution, Rule 205: Organic Material Emission Standards and Limitations, R71-23, 4 PCB 191, filed and effective April 14, 1972; amended in R77-3, 33 PCB 357, at 3 Ill. Reg. 18, p. 41, effective May 3, 1979; amended in R78-3 and R78-4, 35 PCB 75, at 3 Ill. Reg. 30, p. 124, effective July 28, 1979; amended in R80-5 at 7 Ill. Reg. 1244, effective January 21, 1983; codified at 7 Ill. Reg. 13601; Notice of Corrections at 7 Ill. Reg. 14575; amended in R82-14 at 8 Ill. Reg. 13254, effective July 12, 1984; amended in R83-36 at 9 Ill. Reg. 9114, effective May 30, 1985; amended in R82-14 at 9 Ill. Reg. 13960, effective August 28, 1985; amended in R85-28 at 11 Ill. Reg. 3127, effective February 3, 1987; amended in R82-14 at 11 Ill. Reg. 7296, effective April 3, 1987; amended in R85-21(A) at 11 Ill. Reg. 11770, effective June 29, 1987; recodified in R86-39 at 11 Ill. Reg. 13541; amended in R82-14 and R86-12 at 11 Ill. Reg. 16706, effective September 30, 1987; amended in R85-21(B) at 11 Ill. Reg. 19117, effective November 9, 1987; amended in R86-36, R86-39, R86-40 at 11 Ill. Reg. 20829, effective December 14, 1987; amended in R82-14 and R86-37 at 12 Ill. Reg. 815, effective December 24, 1987; amended in R86-18 at 12 Ill. Reg. 7311, effective April 8, 1988; amended in R86-10 at 12 Ill. Reg. 7650, effective April 11, 1988; amended in R88-23 at 13 Ill. Reg. 10893, effective June 27, 1989.; amended in R88-30(A) at 14 Ill. Reg. 3555, effective February 27, 1990; emergency amendments adopted in R88-30(A) at 14 Ill. Reg. effective 6421, effective April 11, 1990 for a maximum of 150 days; amended in R88-14, effective 14 Ill.Reg. , effective

SUBPART A: GENERAL PROVISIONS

Section 215.102 Testing Methods

- a) ~~The total organic material concentrations in an effluent stream shall be measured by a flame ionization detector, or by other methods approved by the Illinois Environmental Protection Agency (Agency), according to the provisions of 35 Ill. Adm. Code 201.~~
- b) ~~Measurement of Vapor Pressures~~

~~1) For a single component, the actual vapor pressure shall be determined by ASTM (American Society of Testing and Materials) Method D 2879-83 (Approved 1983), incorporated by reference in Section 215.105, or the vapor pressure may be obtained from a published source such as Boublik, F., v. Fried and E. Hala, "The Vapor Pressure of Pure Substances," Elsevier Scientific Publishing Co., New York (1973), Perry's Chemical Engineer's Handbook, McGraw Hill Book Company (1984), CRC Handbook of Chemistry and Physics, Chemical Rubber Publishing Company (1968-87), Lange's Handbook of Chemistry, John A. Dean, editor, McGraw Hill Book Company (1985).~~

~~2) For a mixture, the actual vapor pressure shall be determined by ASTM (American Society of Testing and Materials) Method D 2879-83 (Approved 1983), incorporated by reference in Section 215.105, or the vapor pressure may be taken as either:~~

~~A) If the vapor pressure of the volatile organic liquid is specified in the applicable rule, the lesser of the sum of the actual vapor pressure of each component or each volatile organic material component, as determined above weighted by its mole fraction; or~~

~~B) If the vapor pressure of the organic material or volatile organic material is specified in the applicable rule, the sum of the actual vapor pressure of each such component as determined above weighted by its mole fraction.~~

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.105 Incorporation by Reference

The following materials are incorporated by reference:

- a) American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103:
 - 1) ASTM D 1644-59 Method A
 - 2) ASTM D 1475-60
 - 3) ASTM D 2369-73
 - 4) ASTM D 2879-83 (Approved 1983); ASTM D 2879-86 (Approved 1986)

- 5) ASTM D 323-82 (Approved 1982)
 - 6) ASTM D 86-82 (Approved 1982)
 - 7) ASTM E 260-73 (Approved 1973), E 168-67 (Reapproved 1977), E 169-63 (Reapproved 1981), E 20 (Approved 1985)
 - 8) ASTM D 97-66
 - 9) ASTM D 1946-67
 - 10) ASTM D 2382-76
 - 11) ASTM D 2504-83
 - 12) ASTM D 2382-83
 - 13) ASTM D 4057-81 (Approved 1981)
 - 14) ASTM D 4177-82 (Approved 1982)
 - 15) ASTM D 4953-89
- b) Federal Standard 141a, Method 4082.1.
 - c) National Fire Codes, National Fire Prevention Association, Battery March Park, Quincy, Massachusetts 02269 (1979).
 - d) United States Environmental Protection Agency, Washington, D.C., EPA-450/2-77-026, Appendix A (October 1977).
 - e) United States Environmental Protection Agency, Washington, D.C., EPA-450/2-78-051 Appendix A and Appendix B (December 1978).
 - f) Standard Industrial Classification Manual, published by Executive Office of the President, Office of Management and Budget, Washington, D.C., 1972
 - g) 40 CFR 60, Appendix A (1986).
 - h) United States Environmental Protection Agency, Washington D.C., EPA-450/2-78-041.
 - i) 40 CFR 80, Appendices D, E, and F, ~~adopted March 22, 1989~~ ~~at 54 Fed. Reg. 11897.~~

- j) Elsevier Scientific Publishing Co., New York, "The Vapor Pressure of Pure Substances" (1973), Boublik, T., V. Fried and E. Hala.
- k) McGraw-Hill Book Company, "Perry's Chemical Engineer's Handbook" (1984).
- l) Chemical Rubber Publishing Company, "CRC Handbook of Chemistry and Physics" (1968-87).
- m) McGraw-Hill Book Company, "Lange's Handbook of Chemistry" (1985) John A. Dean, editor.
- n) United States Environmental Protection Agency, Washington D.C., "Control of Volatile Organic Emissions from Manufacture of Synthesized Pharmaceutical Products", (EPA-450/2-78-029).

BOARD NOTE: The incorporations by reference listed above contain no later amendments or editions.)

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.108 Measurement of Vapor Pressures

a) Vapor Pressure of Volatile Organic Liquids

- 1) If the volatile organic liquid consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86, or the vapor pressure may be obtained from a published source such as "The Vapor Pressure of Pure Substances," "Perry's Chemical Engineer's Handbook," "CRC Handbook of Chemistry and Physics," or "Lange's Handbook of Chemistry," each source incorporated by reference at Section 215.105.
- 2) If the volatile organic liquid is a mixture, the vapor pressure shall be determined by ASTM Method D2879-86 or by the following equation:

$$P_{vol} = \sum_{i=1}^n P_i X_i$$

where:

P_{vol} = Total vapor pressure of the mixture.

n = Number of components in the mixture.

i = Subscript denoting an individual component.

P_i = Vapor pressure of a component determined in accordance with subsection (a)(1).

X_i = Mole fraction of the component in the total mixture.

b) Vapor Pressure of Organic Material or Solvent

- 1) If the organic material or solvent consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86, or the vapor pressure may be obtained from a published source such as "The Vapor Pressure of Pure Substances," "Perry's Chemical Engineer's Handbook," "CRC Handbook of Chemistry and Physics," or "Lange's Handbook of Chemistry," each source incorporated by reference at Section 215.105.
- 2) If the organic material or solvent is a mixture made up of both organic material compounds and compounds which are not organic material, the vapor pressure shall be determined by the following equation:

$$P_{om} = \frac{\sum_{i=1}^n P_i X_i}{\sum_{i=1}^n X_i}$$

where:

P_{om} = Total vapor pressure of the portion of the mixture which is composed of organic material.

n = Number of organic material components in the mixture.

i = Subscript denoting an individual component.

P_i = Vapor pressure of an organic material component determined in accordance with subsection (b)(1).

X_i = Mole fraction of the organic material component of the total mixture.

- 3) If the organic material or solvent is a mixture made up of only organic material compounds, the vapor pressure shall be determined by ASTM Method D2879-86 or by the above equation.

c) Vapor Pressure of Volatile Organic Material

- 1) If the volatile organic material consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86, or the vapor pressure may be obtained from a published source such as "The Vapor Pressure of Pure Substances," "Perry's Chemical Engineer's Handbook," "CRC Handbook of Chemistry and Physics," or "Lange's Handbook of Chemistry," each source incorporated by reference at Section 215.105.
- (2) If the volatile organic material is a mixture made up of both volatile organic material compounds and compounds which are not volatile organic material, the vapor pressure shall be determined by the following equation:

$$P_{\text{vom}} = \frac{\sum_{i=1}^n P_i X_i}{\sum_{i=1}^n X_i}$$

where:

P_{vom} = Total vapor pressure of the portion of the mixture which is composed of volatile organic material.

n = Number of volatile organic material components in the mixture.

i = Subscript denoting an individual component.

P_i = Vapor pressure of a volatile organic material component determined in accordance with subsection (c)(1).

X_i = Mole fraction of the volatile organic material component of the total mixture.

- 3) If the volatile organic material is a mixture made up of only volatile organic material compounds, the vapor pressure shall be determined by ASTM Method D2879-86 or by the above equation.

(Source: Added at 14 Ill. Reg. , effective)

SUBPART T: PHARMACEUTICAL MANUFACTURING

Section 215.480 Applicability of Subpart T

- a) The rules of this Subpart, except for Sections 215.483 through 215.485, apply to all emission sources of volatile organic material, including but not limited to reactors, distillation units, dryers, storage tanks for volatile organic liquids, equipment for the transfer of volatile organic liquids, filters, crystallizers, washers, laboratory hoods, pharmaceutical coating operations, mixing operations and centrifuges used in manufacturing, including packaging, of pharmaceuticals, and emitting more than 6.8 kg/day (15 lbs/day) of volatile organic material and more than 2268 kg/year (2.5 tons/year) of volatile organic material, or, ~~i.~~ If an emission source emits less than 2,268 kg/year (2.5 tons/year) of volatile organic material, the requirements of these sections this Subpart, except for Sections 215.483 through 215.485, still apply to the emission source if volatile organic material emissions from any single the emission source exceed 45.4 kg/day (100 lbs/day).
- b) ~~The following emissions shall be excluded from a determination of what constitutes more than 2268 kg/year (2.5 tons/year) of volatile organic material for the purposes of subsection (a) above: not more than 4535 kg/year (5.0 tons/year) of volatile organic material from each fluid bed drier or each tunnel drier, and not more than 6803 kg/year (7.5 ton/year) of volatile organic material from each Accelacota. This subsection shall apply only to fluid bed driers, tunnel driers and Accelacotas located in Libertyville Township, Lake County, Illinois, and only when such~~

~~emissions are not vented to air pollution control equipment~~ Notwithstanding subsection (a), the air suspension coater/dryer, fluid bed dryers, tunnel dryers and Accelacotas located in Libertyville Township, Lake County, Illinois shall be exempt from the rules of this Subpart, except for Sections 215.483 through 215.485, if emissions of volatile organic material not vented to air pollution control equipment do not exceed the following levels: for the air suspension coater/dryer: 2268 kg/year (2.5 tons per year); for each fluid bed dryer: 4535 kg per year (5.0 tons per year); for each tunnel dryer: 6803 kg per year (7.5 tons per year); and for each Accelacota: 6803 kg per year (7.5 tons per year).

- c) Sections 215.483 through 215.485 apply to a plant having one or more emissions sources that:
 - 1) are used to manufacture pharmaceuticals; and
 - 2) emit more than 6.8 kg/day (15 lbs/day) of volatile organic material and more than 2268 kg/year (2.5 tons/year) of volatile organic material, or, if less than 2.5 tons/year, these sections still apply if emissions from one or more emission sources exceed 45.4 kg/day (100 lbs/day).
- d) No person shall violate any condition in a permit when the condition results in exclusion of an emission source from this Subpart ~~¶~~.
- e) Emissions subject to this Subpart shall be controlled at all times, consistent with the requirements set forth in this Subpart.
- f) Control devices required pursuant to Section 215.483 shall be operated at all times.
- g) If a pharmaceutical manufacturing emission source becomes subject to the provisions of Sections 215.481, 215.482 or 215.486 on or after the compliance date specified in Section 215.490(a), the requirements of such section shall continue to apply to the emission source even if there is a reduction in emissions as to be below the applicability criteria of this Section.
- h) Determinations of daily and/or annual emissions
 - 1) Determinations of daily and/or annual emissions for purposes of this Section shall be made using:

- (A) data on the hourly emission rate or the emission per unit of throughput, and
 - (B) appropriate daily and annual data from records of emission source operation or material throughput, or material consumption.
- 2) In the absence of representative test data pursuant to Section 215.487 for the hourly emission rate or emission rate per unit of throughput, such items shall be determined using engineering calculations, including the methods described in Appendix B of "Control of Volatile Organic Emissions from Manufacture of Synthesized Pharmaceutical Products", incorporated by reference at Section 215.105.
- 3) This subsection shall not affect the Agency's authority to require emissions tests to be performed pursuant to Section 215.487.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.481 Control of Reactors, Distillation Units, Crystallizers, Centrifuges and Vacuum Dryers

- a) The owner or operator shall control all reactors, distillation units, crystallizers, centrifuges and vacuum dryers that are used to manufacture pharmaceuticals with surface condensers ~~operated such that the condenser outlet gas temperature does not exceed~~ or other air pollution control equipment listed in subsection (a)(2).
- 1) If a surface condenser is used, it shall be operated such that the condenser outlet gas temperature does not exceed:
- ~~1A)~~ 248.2 K (-13 F) when condensing volatile organic material of vapor pressure greater than 40.0 kPa (5.8 psi) at 294.3 K (70 F); or
 - ~~2B)~~ 258.2 K (5 F) when condensing volatile organic material of vapor pressure greater than 20.0 kPa (2.9 psi) at 294.3 K (70 F); or
 - ~~3C)~~ 273.2 K (32 F) when condensing volatile organic material of vapor pressure greater than 10.0 kPa (1.5 psi) at 294.3 K (70 F); or

- 4D) 283.2 K (50 F) when condensing volatile organic material of vapor pressure greater than 7.0 kPa (1.0 psi) at 294.3 K (70 F); or
- 5E) 298.2 K (77 F) when condensing volatile organic material of vapor pressure greater than 3.45 kPa (0.5 psi) at 294.3 K (70 F).

2) If a scrubber, carbon adsorber, thermal incinerator, catalytic incinerator or other air pollution control equipment other than a surface condenser is used, such equipment shall provide a reduction in the emissions of volatile organic material of 90 percent or more.

- b) The owner or operator shall enclose all centrifuges used to manufacture pharmaceuticals and that have an exposed volatile organic liquid surface, where the volatile organic material in the volatile organic liquid has a vapor pressure of 3.45 kPa (0.5 psi) or more at 294.3 K (70 F), except as production, sampling, maintenance or inspection procedures require operator access.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.482 Control of Air Dryers, Production Equipment Exhaust Systems and Filters

- a) The owner or operator of an air dryer or production equipment exhaust system used to manufacture pharmaceuticals shall control the emissions of volatile organic material from such emission sources by air pollution control equipment which reduces by 90 percent or more the volatile organic material that would otherwise be emitted into the atmosphere.
- b) The owner or operator shall enclose all rotary vacuum filters and other filters used to manufacture pharmaceuticals and that have an exposed volatile organic liquid surface, where the volatile organic material in the volatile organic liquid has a vapor pressure of 3.45 kPa (0.5 psi) or more at 294.3 K (70 F), except as production, sampling, maintenance or inspection procedures require operator access.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.483 Material Storage and Transfer

The owner or operator of a pharmaceutical manufacturing plant shall:

- a) Provide a vapor balance system ~~or equivalent control system~~ that is at least 90.0 percent effective in reducing volatile organic material emissions from truck or railcar deliveries to storage tanks with capacities equal to or greater than 7.57m³ (2,000 gallons) that store volatile organic liquids with vapor pressures greater than 28.0 kPa (4.1 psi) at 294.3 K (70 F); and
- b) Install, operate and maintain pressure/vacuum conservation vents set at 0.2 kPa (0.03 psi) or greater on all storage tanks that store volatile organic liquids with vapor pressures greater than 10 kPa (1.5 psi) at 294.3 K (70F), ~~unless a control system that allows less VOM to be emitted is used.~~

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.484 In-Process Tanks

The owner or operator shall install covers on all in-process tanks used to manufacture pharmaceuticals and containing a volatile organic liquid at any time. These covers must remain closed, except ~~when~~as production, sampling, maintenance, or inspection procedures require operator access.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.485 Leaks

The owner or operator of a pharmaceutical manufacturing plant shall repair any component from which a leak of volatile organic liquid can be observed. The repair shall be completed as soon as practicable but no later than 15 days after the leak is found unless the leaking component cannot be repaired until the process unit is shut down, and the leaking component must then be repaired before the unit is restarted.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.486 Other Emission Sources

The owner or operator of a washer, laboratory hood, ~~capsule~~tablet coating operation, mixing operation, or any other process emission source not subject to Section 215.481 through 215.485 of this Subpart, and used to manufacture pharmaceuticals shall control the emissions of volatile organic material from such emission sources by:

- a) Air pollution control equipment which reduces by 81 percent or more the volatile organic material that would otherwise be emitted to the atmosphere, or
- b) A surface condenser which captures all the volatile organic material which would otherwise be emitted to the atmosphere and which meets the requirements of Section 215.481(a) of this Subpart.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.487 Testing

- a) Upon reasonable request by the Agency, the owner or operator of any volatile organic material emission source subject to this Subpart or exempted from this Subpart by provisions of Section 215.480(a), (b) or (c) shall, at his own expense, demonstrate compliance by methods or procedures listed in Section 215.487(c); and
- b) All tests pursuant to Section 215.487(a) shall be performed in conformance with the procedures set forth in 35 Ill. Adm. Code 283A. A person planning to conduct a volatile organic material emissions test to demonstrate compliance with or determine applicability of provisions of this Subpart shall notify the Agency of that intent to test not less than 30 calendar days prior to the planned initiation of the test.
- c) Test procedures to determine operation and maintenance compliance with and applicability of this Subpart are in 40 CFR Part 60, Appendix A, incorporated by reference at Section 215.105, and shall be used as delineated below: shall be consistent with EPA 450/2-78-041, incorporated by reference in Section 215.105. Procedures for testing air pollution control equipment to determine compliance with this Subpart shall use Part 230, Appendix A Method 25 (40 C.F.R. 60, Appendix A Method 25).
 - 1) 40 CFR Part 60, Appendix A, Methods 18, 25 or 25A, as appropriate to the conditions at the site, shall be used to determine VOM concentration. Method selection shall be based on consideration of the diversity of organic species present and their total concentration and on consideration of the potential presence of interfering gases. Except as indicated in subsections (c)(1)(A) and (c)(1)(B), the test shall consist of three separate runs, each lasting a minimum of 60

minutes, unless the Agency determines that process variables dictate shorter sampling times.

- A) When the method is to be used to determine the efficiency of a fixed-bed carbon adsorption system with a common exhaust stack for all the individual adsorber vessels, the test shall consist of three separate runs, each coinciding with one or more complete sequences through the adsorption cycles of all the individual adsorber vessels.
- B) When the method is to be used to determine the efficiency of a fixed-bed carbon adsorption system with individual exhaust stacks for each adsorber vessel, each adsorber vessel shall be tested individually. The test for each adsorber vessel shall consist of three separate runs. Each run shall coincide with one or more complete adsorption cycles.
- 2) 40 CFR Part 60, Appendix A, Method 1 or 1A shall be used for sample and velocity traverses.
- 3) 40 CFR Part 60, Appendix A, Method 2, 2A, 2C or 2D shall be used for velocity and volumetric flow rates.
- 4) 40 CFR Part 60, Appendix A, Method 3 shall be used for gas analysis.
- 5) 40 CFR Part 60, Appendix A, Method 4 shall be used for stack gas moisture.
- 6) 40 CFR Part 60, Appendix A, Methods 2, 2A, 2C, 2D, 3 and 4 shall be performed, as applicable, at least twice during each test run.
- d) This section shall not affect the authority of the U.S. Environmental Protection Agency under Section 114 of the Clean Air Act.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.488 Monitors for Air Pollution Control Equipment

- a) At a minimum, continuous monitors for the following parameters shall be installed on air pollution control equipment subject to this Subpart:
- 1) Destruction device combustion temperature;

- 2) Temperature rise across a catalytic afterburner bed;
 - 3) Breakthrough of volatile organic material on a carbon absorption unit;
 - 4) Outlet gas temperature of a refrigerated condenser;
 - 5) Temperature of a non-refrigerated condenser coolant supply system.
- b) Each monitor shall be equipped with a recording device.
 - c) Each monitor shall be calibrated quarterly.
 - d) Each monitor shall operate at all times while the associated control equipment is operating.

(Source: Amended at 14 Ill. Reg. , effective)

Section 215.489 ~~Compliance Schedule~~Recordkeeping

- a) The owner or operator of a pharmaceutical manufacturing plant shall maintain the following records:
 - 1) The parameters listed in Section 215.488 shall be recorded.
 - 2) For sources subject to Section 215.481, the vapor pressure of the volatile organic material being controlled shall be recorded for every process.
- b) For any leak subject to Section 215.485 which cannot be readily repaired within one hour after detection, the following records shall be kept:
 - 1) The name of the leaking equipment.
 - 2) The date and time the leak is detected.
 - 3) The action taken to repair the leak.
 - 4) The date and time the leak is repaired.
- c) The following records shall be kept for emission sources subject to Section 215.484 which contain volatile organic liquid:
 - 1) For maintenance and inspection:

- A) The date and time each cover is opened.
 - B) The length of time the cover remains open.
 - C) The reason why the cover is opened.
- 2) For production and sampling, written procedures or manufacturing directions specifying the circumstances under which covers may be opened and the procedures for opening covers.
- d) For each emission source used in manufacture of pharmaceuticals for which the owner or operator of a pharmaceutical manufacturing plant claims emission standards are not applicable because the emissions are below the applicability cutoff in Section 215.480(a) or (b), the owner or operator shall:
- 1) Maintain a demonstration, including detailed engineering calculations, of the maximum daily and annual emissions for each such emission source showing that the emissions are below the applicability cutoffs in Section 215.480(a) or (b), as appropriate, for the current and prior calendar years;
 - 2) Maintain operating records for each emission source to identify whether the cutoffs in Section 215.480(a) or (b), as appropriate, are ever exceeded; and
 - 3) Provide written notification to the Agency within 30 days of a determination that such an emissions source has exceeded the applicability cutoff of Section 215.480(a) or (b), as appropriate.
- e) Records required under this section shall be maintained by the owner or operator for a minimum of two years after the date on which they are made.
- f) Copies of the records shall be made available to the Agency upon verbal or written request.
- (Source: Renumbered to Section 215.490 and added at 14 Ill. Reg. , effective)

Section ~~215.489~~215.490 Compliance Schedule

- a) The owner or operator of an emission source subject to this Subpart, the construction or modification of which has commenced prior to April 15, 1988 (the effective date of these amendments), must complete onsite

construction, modification or installation of the emission control and/or process equipment, ~~or both,~~ or complete any necessary production process changes so as to operate in compliance with this Subpart by April ~~130,~~ 1989.

- b) The owner and operator of any emission source subject to this Subpart, the construction or modification of which has not commenced prior to ~~April 15, 1988~~ (the effective date of these amendments), shall construct such source so that it will operate in compliance with this Subpart.

(Source: Renumbered from Section 215.489 and amended at 14 Ill. Reg. , effective)