ILLINOIS POLLUTION CONTROL BOARD December 30, 1982

IN THE MATTER OF:)	
)	
SULFUR DIOXIDE EMISSION)	R80-22
LIMITATIONS: RULE 204)	
OF CHAPTER 2)	

Proposed Opinion. Second Notice.

OPINION OF THE BOARD (by I. G. Goodman):

On December 1, 1980 the Board received the Illinois Environmental Protection Agency's (Agency) proposal to adopt emission limitations for sulfur dioxide from fuel combustion emission sources located within the three Major Metropolitan Areas (MMA) of St. Louis, Peoria, and Chicago. Also proposed was a reduction in the emission limitations for process emission sources located in the St. Louis and Chicago MMAs. The Agency filed its proposal in R77-15 and R78-14, two ongoing regulatory proceedings which had been consolidated for hearings. R77-15 was a site-specific rulemaking proposed by Ashland Chemical Company (now Sherex Chemical Company, Inc.) to amend Rule 204(c)(1)(A) of the Board's Chapter 2: Air Pollution and finalized by Board Order on December 17, 1981. R78-14 was an inquiry concerning Rule 204(c)(1)(A) instituted by the Board and dismissed on January 8, The Agency's proposal was primarily a response to the legislative mandate that it review the sulfur dioxide emission limits for existing fuel combustion emission sources located within these three MMAs and thereafter propose amendments, consistent with the Clean Air Act's National Ambient Air Quality Standards program, which would enhance the use of Illinois coal. (III. Rev. Stat. 1981, ch. 1111/2, par. 1009.2). On December 19, 1980 the Board docketed the Agency's proposal to amend Rules 204(c)(1)(A), 204(d), 204(f), 204(h) and 204(i) of Chapter 2 as R80-22.

The Agency submitted revisions to the R80-22 proposal on February 26, 1981, January 25, 1982 and June 1, 1982. Public merit hearings were held in East St. Louis, Peoria, and Chicago on February 26, March 10 and 12, 1981, respectively, and again on June 1, 1982 in Chicago. The Department of Energy and Natural Resources (ENR) submitted the Economic Impact Study of the proposed sulfur dioxide amendments, ENR Document No. 82/11, on April 26, 1982. Economic impact hearings were held in Chicago and Peoria on June 1 and 22, 1982, respectively.

The record was kept open for public comments until July 14, 1982. The Village of Winnetka (Winnetka) requested an extension on July 12, 1982. That motion is granted and the comments filed

by Winnetka on July 30, 1982 are accepted. The rules proposed by the Board for First Notice were published in the Illinois Register on September 17, 1982. Comments received during the ensuing forty-five day period are discussed below.

On October 1, 1982 Winnetka requested a public hearing pursuant to Ill. Rev. Stat. 1981, ch. 127, par. 1005.01(a). Since such a hearing would inevitably delay the remainder of this rule-making, two dockets were established by the Board on October 14, 1982. Winnetka's request for a site specific rule was designated as Docket B and hearings held on November 3, 1982 and December 15, 1982. The rules proposed for First Notice were assigned to Docket A, and it alone is the subject of this Opinion and Order.

On November 1, 1982 Granite City Steel Division of National Steel Corporation likewise requested an additional hearing under the Illinois Administrative Procedure Act. Id. This request was untimely and no hearing was held. However, Granite City Steel has since agreed to waive its hearing request, if the amendatory language submitted by the Agency on December 3, 1982 is incorporated into the rules proposed for Second Notice.

Emission limitations for sulfur emitting sources were among the first air regulations promulgated by the Board in 1972. Since then the rules for fuel combustion emission sources have been contested and are even now remanded to the Board. these ten years the original national ambient air quality standards for sulfur dioxide have remained substantially unchanged; the primary annual standard has been attained statewide in Illinois; the control technologies originally considered have proven feasible; and compliance with the original Board emission limits widely achieved. Two new concerns impacting control of sulfur dioxide have developed over the ten year span. The need to utilize more domestic fuel has become apparent for a healthy economy. This realization is especially important considering Illinois' reserves of high sulfur coal. However, it is also probable that further reductions in sulfur dioxide emissions are necessary for a healthy environment. Cognizant of these conflicting developments, it is the Board's intent to reconcile them as much as possible in establishing sulfur dioxide emission limits to replace those voided by the Courts. These limits should also provide for the attainment and maintenance of the air quality in Illinois for sulfur dioxide. As noted, the history of the Board's regulations for sulfur dioxide is lengthy. Therefore, a brief summary precedes the analysis of the rules.

HISTORY

As stated before, the emission limitations for sulfur dioxide produced by solid fuel combustion and process emission sources were among the first air pollution regulations promulgated by the Board, including those for the St. Louis, Peoria and Chicago MMA.

In the Matter of Emission Standards, 4 PCB 298 April 13, 1972. Rule 204, as adopted, provided future compliance dates for both types of emission source: May, 1975 for solid fuel combustion sources and December, 1973 for the process emission sources. In so doing, the Board acknowledged that the control technologies envisioned by these limits were only then rapidly developing. For this reason and because compliance alternatives included switching from high sulfur coal to limited reserves of low sulfur coal, oil, or gas, these emission limits were not uniform statewide, but instead geographic and source determinative. It should be noted that Rule 202: Visual Emissions and Rule 203: Particulate Emissions were adopted concurrently with Rule 204: Sulfur Limitations.

The adoption of Rules 203(g)(1), 204(a)(1) and 204(c)(1)(A)was successfully appealed at the appellate and supreme court level. Commonwealth Edison Company v. Pollution Control Board, 25 Ill. App. 3d 241, 323 N.E.2d 84 (1st Dist. 1974), 62 Ill. 2d 494, 343 N.E.2d 959 (1976). These specific rules pertained to the particulate and sulfur dioxide emissions for sources located within the three largest MMA. In its remand, the appellate court instructed the Board "either to validate [these rules] in accordance with Section 27 of the Act or to prepare proper rules as substitutes." Id. at 96. In affirming the Appellate Court, the Supreme Court introduced the notion that the Board's record was insufficient as to whether simultaneous compliance with Rules 203 and 204 was technically feasible and economically reasonable. The higher Court's decision also cited the fact that "a weight of new evidence" had become available, presumably a reference to the Board's inquiry hearings into sulfur dioxide rules (R74-2) and the Agency's proposal for sulfur dioxide rules (R75-5), and like the appellate decision, directed that the contested rules be validated or appropriate new rules adopted.

Thereafter the Board consolidated the records in R71-23, R74-2 and R75-5 and held two additional public hearings. should be noted that just prior to the Supreme Court's decision the Environmental Protection Act was amended to require 1) economic impact studies (EcIS) and hearings in future rulemakings and 2) adoption of regulations by the Board prescribing conditions for sulfur emission sources to use intermittent control systems The Supreme Court's decision acknowledged the ICS amendment, but was silent on the EcIS amendment. Consideration of ICS was deferred until final rulemaking in R74-2 and R75-5 to avoid introducing a new rulemaking in the validation process. No economic impact statement was prepared or hearings held. An abstract of the consolidated record with its "wealth of information" was prepared by Marder & Associates. On July 7, 1977 the Board validated the remanded rules, after reviewing the pertinent information in the record and considering the issues identified by the Courts. 27 PCB 57. Therein the Board decided that an economic impact study was not necessary for validation, and relied instead on the economic evidence already in the record. Furthermore, the opinion stated that the "Marder report" served only as an aid,

and not an analysis of the merits of the information. Nevertheless, the validation of the rules was vacated. Ashland Chemical Company v. Pollution Control Board, 64 Ill. App. 3d 169, 381 N.E. 2d 56 (3d Dist. 1978) and Illinois State Chamber v. Pollution Control Board, 67 Ill. App. 3d 839, 384 N.E.2d 922 (1st Dist. 1978). Both courts declined ruling on the substantive validity of the R71-23 regulations and instead voided the Board's validation on procedural grounds. Among other things, both Courts found that the Board's use of the Marder report without public hearings on the same violated due process rights and that Section 6 of the Act, requiring an economic impact study and accompanying public hearings had not been complied with.

Validation having failed, the Board instituted inquiry proceedings into the remanded sulfur dioxide rules (R78-14) and the particulate rule (R78-16). On December 14, 1978, these regulatory proceedings were consolidated with R77-15 (the Ashland sitespecific proposal) and R78-15 (Rochelle site-specific proposal) for hearing purposes. Final action on R77-15 was taken on December 17, 1982 and is still pending on R78-15. On February 15, 1979, the issues outstanding from the combined hearing record in R71-23, R74-2, and R75-5 were resolved. Sulfur dioxide emission limits for rural fuel combustion sources including an adjudicatory procedure and formulas for site-specific limits were adopted in the consolidated order for R74-2 and R75-5. ICS rules were not adopted, having been subsequently barred by amendment to the Clean Air Act as a dispersion enhancement technique. As stated above, the Agency's proposal for emission limits in the MMAs was separately docketed as R80-22. R78-14 (sulfur dioxide inquiry) was shortly thereafter dismissed. R78-16 (particulate rule inquiry) was also dismissed with leave to reopen should simultaneous compliance with the particulate and sulfur dioxide emission limitations become an issue in R80-22. It should be noted that R82-1, another Board proceeding concerning Rule 203(g)(1), has been instituted, with further action dependent on submittal of the economic impact study. Therefore, resolution of the issues involved in this rulemaking (R80-22) will hopefully conclude the entangled regulatory history of sulfur dioxide since the Commonwealth Edison appeal.

ANALYSIS OF THE REGULATIONS

Fuel Combustion Emission Sources

The limit for sulfur dioxide emissions for existing sources in the three MMAs was originally adopted at 1.8 pounds per million British thermal units (lb/mBtu). 4 PCB 298. Compliance with this and the other limitations concurrently adopted anticipated that air quality statewide would be better than the national levels established in 1971. The National Ambient Air Quality Standard (NAAQS) for sulfur dioxide includes two primary standards: an annual standard of 0.03 ppm (80 ug/m³) and a 24 hour standard

of 0.14 ppm (365 ug/ m_3^3); and a secondary standard based on 3 hours of 0.5 ppm (1300 ug/ m_3). Since 1975 no violations of the annual primary standard have been recorded in any of the three MMAs. The short-term primary standard has been violated in all three MMAs, but not since 1977 in Chicago and Peoria. Violations of the secondary standard have occurred in East St. Louis and Peoria.

Monitoring alone neither can provide a plan to achieve air quality in the St. Louis MMA, nor determine the extent the limit may be relaxed in the other two MMAs and the NAAQS still be maintained. Forecasting of this type must be developed through air quality analysis. Therefore, regional air quality analyses, including base and strategy analyses, were prepared for each of the three MMAs. The modeling format used for each of the three MMAs was basically the same, as were the data requirements. The data information, on the other hand, were geographically specific. Each base analysis involved the RAM, a modeling program having both a rural and urban version. The rural version was modified to conform with a second model, the CRSTER, which was used to account for isolated emission sources.

It should be noted that modeling is intended to demonstrate that should the worst meteorological circumstances and periods of maximum emissions coincide, the NAAQS would not be exceeded. Except for the St. Louis MMA, modeling was done only to evaluate the short-term standards, i.e., the 24 hour and 3 hour standards. This was considered sufficient since the short-term standards are considered more stringent than the primary annual standard. It should be noted that attainment of the annual standard has already been demonstrated through monitoring.

The emission inventories contained the location, magnitude, frequency, duration and relative contributions of the fuel combustion emission sources in each area. Generally, only point sources emitting more than 100 tons of sulfur dioxide per year (T/yr) were included, and other area sources were accounted for in the background levels. The point sources were identified in the Agency's total air system (TAS), which was compiled initially in 1974 and has since been continuously updated. In calculating the sources' impacts on the model's receptors, all sources were assumed to operate at their maximum allowable rate, which was based on the remanded emission limits.

To determine the appropriate background levels for each area studied, localized monitoring data was matched with localized meteorological data for the same base year. As it turned out, the base year and the number of monitors used for each area varied. Since the sulfur dioxide monitors operate continuously, hourly averages were achieved by averaging the data collected. Lastly, to accurately complete the air quality data, exclusion angles were uniformly calculated to eliminate sources upwind from monitors from the background totals.

Emission Limits for Fuel Combustion Emission Sources

St. Louis MMA

Analysis of the annual air quality standards for the East St. Louis area was performed using the Climatological Dispersion Model (CDM). The meteorological data consisted of data collected between 1973 and 1978 at Lambert Field and compiled by the National Climatic Center, and upper air observations were obtained from the National Weather Service at Salem, Illinois. Even after potential growth was considered, no violations of the annual sulfur dioxide standard were predicted. However, violations of the short-term standards were predicted.

Like the other two MMAs, an analysis of the short-term standards was programmed. The hourly meteorological data for 1973-1977 was gathered from the same sources used for the annual The RAM (urban) was used in those areas which are basically urban in nature, and a modified version of RAM (rural) was used for the rural areas. The CRSTER model, which does not have the capability to model several sources at separate locations, was used for the isolated power plant, Illinois Power Baldwin. The maximum allowable emission rates of all major sources in Madison, St. Clair, and Monroe Counties were used in the model. Individual Missouri emission sources were not used because the maximum allowable emission rates and stack parameters were not available. These emissions were, however, reflected in the background determination. Emissions due to growth were not explicitly modeled in this analysis. It was instead assumed that any additional emissions would be minor, and readily absorbed since the model was already conservative in that all existing sources are presumed to operate at maximum allowable rates. Furthermore, any new major sources would be required to show no significant impact on air quality pursuant to the Prevention of Significant Deterioration (PSD) or New Source Review (NSR) programs.

The short-term modeling predicted widespread violations of the primary 24 hour standard and the secondary 3 hour standard primarily in the industrial areas of East St. Louis (Ex. 3, pp. 85-86). Consequently, a culpability assessment was made, using the "worst case" days of the five year period modeled. The results, which included background concentrations, and Illinois urban and rural sources of sulfur dioxide, found the sources in the Alton Wood River Area to be varied; whereas in East St. Louis and Granite City, the elevated sulfur dioxide levels were more localized and source-oriented. The two sources identified, however, were process sources as opposed to fuel combustion sources.

Due to the number of violations predicted, no relaxation of the emission limitation for fuel combustion sources in the St. Louis MMA is proposed. Sulfur dioxide emissions from residential and commercial sources are predicted to increase in the next decade, but fuel combustion emission to remain constant from industrial sources. In an effort to achieve attainment in this MMA, more stringent limitations for process sources were proposed by the Agency. These will be discussed later in this Opinion.

Peoria Major Metropolitan Area

Neither the modeling done in 1978 nor recent monitoring indicates violation of the annual standards in the Peoria MMA. Thus, only short-term analyses were considered, on the assumption that short-term standards are more restrictive than the annual standards and, therefore, any subsequent relaxation could not jeopardize the annual attainment status. Furthermore, local air quality monitoring indicated annual sulfur dioxide concentrations well below the national annual standard. (R. 41.) A five year base analysis, using the RAM (urban and modified rural) and CRSTER model, was developed to determine if the 1.8 lb/mBtu limitation could be relaxed. Five years (1973-1977) of meteorological data from the Peoria National Weather Service Station was used in the analysis. Again, maximum allowable emissions based on the 1.8 lb/ mBtu standard were used along with appropriate background concen-Terrain effects were not considered. The results of the base analysis predicted violations of the primary 24 hour standard, which were isolated to two small areas, and none for the secondary 3 hour standard (Ex. 3, pp. 25-26.)

A culpability analysis was then developed, focusing on the two receptors which had indicated violations in the short-term base analysis. This analysis associated these violations with sources located at the Caterpillar Mossville Plant and Caterpillar East Peoria Plant. (R. 45.) Both of these Caterpillar plants are already equipped with flue gas desulfurization equipment (FGD). Therefore, if the actual emissions were used in the base analysis, it is possible that violations of the primary short-term standard would not be predicted. Furthermore, if these limitations were in place and enforceable, the base analysis would no longer indicate violations of any standards, so relaxation of the 1.8 lb/mBtu limit can be considered for some of the area's remaining existing sources.

Two strategy analyses were conducted by the Agency to determine the extent relaxation would be possible without creating violations of the NAAQS. The first strategy analysis focused on the violations predicted for the two Caterpillar plants as discussed above. While it took into account the control provided by the FGDs, this analysis considered two twenty-four hour periods, one for the Mossvile plant and one for the East Peoria plant. The probability of violations occurring was confirmed. (Ex. 3, p. 29.)

The second strategy analysis studied relaxations of the emission limit for small sources in the Peoria MMA. (R. 192.) The RAM (urban) and the MPTER models were used. The MPTER is a dispersion model which can simulate the dispersion of several sources' pollutants in a moderate terrain. Applying a data base consisting of the relaxed emission inventory based on a 5.5 lb/mBtu emission limit, a modified receptor network, and five years of meteorological data, the modeled impacts for all urban and rural sources, and background concentrations to the MPTER, air quality was assessed. It should be noted that the two Caterpillar sources already modeled were not included in the inventory, but its other two Peoria plant sources with capacities greater than 250 mBtu (R. 192.) Violations of the short-term standards were predicted. (R. 194.) Yet another culpability analysis was performed. Caterpillar's Mapleton Plant, despite an emission limit of 1.8 lb/mBtu, and the Sherex Chemical Company were identified as the sources of violation.

After considering these analyses together, the following conclusions were made by the Agency:

- (1) The cause of Caterpillar Mapleton and Sherex's predicted violations were the Mapleton bluffs;
- (2) using roll back methodology, emission limits of 1.0 lb/ mBtu for the Caterpillar East Peoria Plant and 1.6 lb/ mBtu for the Caterpillar Mossville plant would be sufficient to maintain NAAQS;
- (3) again using roll back methodology, Sherex's emission limit could be relaxed from 1.8 lb/mBtu to 3.3 lb/mBtu without jeopardizing the NAAQS; and
- (4) with the exceptions of the Caterpillar and Sherex facilities, the emission limit could be relaxed from 1.8 lb/mBtu to 5.5 lb/mBtu for industrial boilers with a generating capacity of less than 250 mBtu. (R. 195-196.)

It should be noted that the industrial facilities with a generating capacity of greater than 250 mBtu still subject to the 1.8 lb/mBtu limitation were CPC International (now Pekin Energy, Inc.), and Caterpillar sources already equipped with FGDs.

During the merit segment of the June 1, 1982 hearing, a third strategy analysis was presented. The emissions inventory for the modeling was revised to include the Caterpillar plants emitting at their actual limit of 1.8 lb/mBtu, small industrial boilers (less than 250 mBtu) emitting at 5.5 lb/mBtu, and CPC International boiler (rated at 330 mBtu) assessed at 5.5 lb/mBtu. The Sherex boiler was modeled at an assumed stack height of 200 feet, which would allow Sherex to emit up to 5.5 lb/mBtu without causing NAAQS violations due to the Mapleton bluffs. This

analysis indicated that emission limits for the Caterpillar Mapleton and East Peoria facilities must be further reduced to assure compliance with the NAAQS. An emission limit of 0.8 1b/mBtu at the Mapleton facility and 1.1 lb/mBtu at the East Peoria facility would eliminate any possibility of air quality violations.

Throughout the proceedings, the four Peoria Caterpillar sources were a subject of controversy. At first a limit for the Mapleton sources was proposed. It was later rescinded because they were considered to be new sources and subject to regulation for the same not yet proposed by the Agency. (R. 98.) Furthermore, boilers 4 and 5 at this facility were initially neither included in the TAS inventory because they were under construction during this rulemaking (R. 176), nor part of the modeling until the final analysis. Boilers 4 and 5 of the Mossville facility, although also new sources, were included in the inventory and in the modeling (R. 176, pg. 12, Ex. 3). Initially, a limit of 1.6 lbs/mBtu was proposed for this facility, but later modeling indicated that emissions up to 1.8 lbs/mBtu would not jeopardize air (R. 570.) The Morton facility was modeled at 1.8 lbs/ quality. mBtu and no violations predicted. The Agency even said that a limit somewhere between 1.8 and 5.5 lbs/mBtu was possible without causing problems, assuming no new sources were constructed in the (R. 125.) As for the East Peoria facility's sources, vicinity. 1.0 lbs/mBtu was originally proposed and later rolled back to 1.1 lbs/mBtu. (R. 208, 571.) Throughout the rulemaking the Agency argued that the limits proposed for the Caterpillar sources were its actual emissions after control with the FGDs and that Caterpillar was already using Illinois coal. Based on this, sitespecific limits were proposed for three of Caterpillar's Peoria facilities; Mapleton was excluded as being a new source. sources, Mossville and Morton, were limited to 1.8 lbs/mBtu, and the East Peoria facility was limited to 1.1 lbs/mBtu. limitations were intended to maintain compliance with the NAAQ standards for sulfur dioxide.

During the First Notice period, Caterpillar renewed its objections (1) that it was being singled out for site-specific rulemaking, and (2) that its sources should be considered existing sources. Caterpillar also objected that as rules were proposed, it was excluded from the exception procedure proposed in Rule 204(c)(4).

Upon reconsideration, these specific limits are deleted from the proposed rules. The Mossville and Morton sources are still restricted to the 1.8 lbs/mBtu emission limit, but now pursuant to proposed Rule 204(d). Secondly, limiting the East Peoria sources to 1.1 lbs/mBtu is deemed unnecessary. If necessary, this limit can be imposed and enforced pursuant to the Agency's permitting authority, as can an emission limit of less than 1.8 lbs/mBtu for the Mapleton sources. In addition, Caterpillar's sources are no

longer classified as new and existing sources. While R80-22 was under consideration, relaxed limits for total suspended particulates emissions were granted for all sources equipped with FGDs. (Amendments to Chapter 2: Rule 203(q), R79-11, October 8, 1981.) Such relief was necessary due to the difficulties these controlled sources have in achieving simultaneous compliance with Rules 203(g) Therein sources were not distinguished between existing and new, other than sources equipped with scrubbers as of the effective date of that Order. Caution was noted that such industrial sources may become subject to USEPA's new source performance standard when and if promulgated (Opinion at 9). The same caution However, to now regulate these sources as other is again offered. than existing would be incongruous. Lastly, since site-specific limits are not being imposed, Caterpillar is free to exercise the exception procedure, if in the future it deems it desirable. The proposed rules have been accordingly restructured.

Chicago Major Metropolitan Area

The air quality analyses for the Chicago MMA were prepared late in 1981 and presented at the June 1, 1982 merit hearing (Ex. 11). The base analysis utilized the RAM (urban) for those areas identified as urban, the MPTER model for those areas identified as rural, and the CRSTER model was later used to demonstrate the air quality near two isolated areas. The meteorological data for the models was provided by the Chicago Midway National Weather Service and the Peoria National Weather Service provided the upper air soundings. The meteorological effects due to Lake Michigan were not considered since (1) no meteorological sites continuously operate near the Lake, and (2) no readily available dispersion modeling is available to take the Lake effects into account. The emission inventory included point sources considered to have significant impacts, that is greater than 100 T/year, located in Cook, Lake, Will, McHenry, Kane and DuPage Counties. The maximum allowable emission rate was used throughout; this way the possible violations of the NAAOS could be identified, with the additional benefit that growth need not be specifically considered.

Unlike the analyses for the other two MMAs, the background areas to be included in the Chicago study had to be limited because of the size and complexity of the geographic locale. Four areas were identified as needing background value determination: Will County, Lake County, southern Cook County and northern Cook County. In estimating these background levels, actual data gathered at nine continuous sulfur dioxide monitors, as recorded in 1976 and 1977, was coupled with the hourly meteorological data for 1976 and 1977. Downwind monitors were discounted through the use of "exclusion angles."

The base analysis identified violations of both short-term standards. For the 24 hour standard, four were predicted in Cook County, and one in Will County. For the 3 hour standard, three violations were predicted in Cook County. (R. 562.)

The Chicago MMA culpability analysis predicted that throughout the Chicago area the 24 hour and the 3 hour standards would be exceeded. In Cook County ten sources were identified as significantly contributing for five days studied in 1975. One source was identified in Will County, which has been mothballed; therefore, its actual emissions have been eliminated. Similarly, the remaining sources identified may not actually be contributing emissions near the maximum allowable emission limits used in the model. Therefore, rather than making a blanket determination that relaxation is not permissible in these areas, it should be realized that individually these sources may be able to prove that increased emission rates may not jeopardize the NAAQS in the surrounding vicinity.

In addition to the base and culpability analyses, four strategy analyses were conducted to determine which sources could be granted relaxed emission limits. Two of the four analyses were site-specific, and two looked initially to the geographic areas to determine if any sources located therein could profit from relaxed limitations.

The first strategy evaluated the emission sources in Kankakee and McHenry Counties to determine if the limitation could be relaxed from 1.8 lb/mBtu to 6.8 lb/mBtu without jeopardizing the attainment status. Each county has one coal burning facility and one oil and/or gas burning facility which is unaffected by any relaxation. Nevertheless, these facilities had to be included in the modeling since they each contribute more than two-thirds of the total sulfur dioxide emissions per year in their respective county. The CRSTER model indicated that the coal burning sources could emit up to 6.8 lbs/mBtu without jeopardizing the air quality in these attainment areas.

The Shapiro facility in Kankakee County was individually modeled. It had not been included in the Kankakee study since its boilers are equipped to operate on natural gas. It does have a single coal-fired boiler which, if utilized with the relaxed emission limit of 6.8 lb/mBtu, would not adversely impact air quality in Kankakee. Furthermore, should Shapiro decide to switch to Illinois coal, results of the CRSTER model indicate that the other coal-fired facility in Kankakee would not be affected, and the attainment status would not be jeopardized.

The second geographic area considered was the areas of the Chicago MMA which were outside the areas designated non-attainment for the short-term standards. Only five sources, which are currently burning non-Illinois coal, were modeled as potential

candidates for a relaxed emission limit of 5.5 lbs/mBtu. These emission sources, meteorological data from 1973 (the "worst case" year), and previously identified receptor locations were input into the RAM (urban) and MPTER model. Background data for Lake, Will and Cook Counties were also programmed. Only two sources were identified as not causing violations of the short-term standards if allowed to emit up to 5.5 lbs/mBtu. However, as was the case for two sources in the Peoria MMA, modeling to determine possible terrain and downwash problems is necessary before a relaxation could be granted to these sources. They therefore are potential candidates for the site-specific adjudicatory procedure also proposed in this rulemaking.

Lastly, the Caterpillar facility in Kendall County was modeled to determine if the emission limitation could be relaxed to 6.8 lbs/mBtu. Kendall County is currently an attainment area for sulfur dioxide. Should the emission limit be relaxed, however, the CRSTER model predicts significant violations of the short-term standards, but no violation of the annual primary standard. Relaxation is denied at this time because the CRSTER model did not take into account background levels, terrain, or building downwash effects. During the First Notice, Caterpillar argued that these same effects were not considered for sources in Kankakee and McHenry Counties, and therefore should not be considered in evaluating Kendall County. However, modeling of McHenry and Kankakee sources did not predict violations of any air quality standards, whereas modeling for the Kendall County facility did. Although denied relaxation at this time, this facility, like many others, can utilize the proposed exemption procedure.

The overall effect of the relaxations proposed is that an additional 220,000 tons of Illinois coal can be burned annually in addition to the 120,000 tons burned annually by Sherex, Bemis and Celotex pursuant to R77-15. Conversions by sources in the Peoria MMA and Kankakee and McHenry Counties from oil or natural gas will also increase Illinois coal usage. At this time, however, the amount is not certain (R.648). The increased usage of high-sulfur coal has been adequately demonstrated, primarily on a source-by-source basis, not to jeopardize current air quality.

In addition to the specific limitations adopted for fuel combustion emission sources in the three MMAs, an exemption procedure is proposed much like that available to rural sources pursuant to Rule 204(g) (former Rule 204(e)). Adopting the adjudicatory format, petitioning sources are required to demonstrate that the relaxed emission limit sought will not jeopardize air quality. This procedure should be readily available to sources since they can merely premise air quality modeling on that already completed by the Agency for each of the MMAs.

At the June 1, 1982 hearing, Winnetka sought a relaxed emission limit for its utility company. It submitted modeling

studies premised on the Agency's studies, to demonstrate that air quality would not be jeopardized if it was allowed to emit up to 6.8 lbs/mBtu. At First Notice, site-specific rulemaking was denied Winnetka because the public had been insufficiently notified of such a possibility. The Opinion noted that Winnetka's source was a likely candidate for the proposed exemption procedure. Nevertheless, Winnetka sought a public hearing pursuant to the Administrative Procedures Act. Docket B was therefore established by Board Order on October 14, 1982 to ensure that adoption of the remainder would not be delayed. As mentioned above, two hearings have been held. Docket B will be concluded as soon as transcripts of the same are received and the record is closed.

Aside from amending the rules for fuel combustion sources burning solid fuel exclusively, the formula for those burning combination of fuels is amended and a new formula for steel mills is proposed. (Rule 204(i).) The numerical limitation for distillate oil sulfur dioxide emissions is eliminated as a specific component in the present formula. The new formula regulating combustion of combination fuels at steel mills is self-explanatory. At First Notice, the definition for the formula's component $H_{\mathcal{G}}$ included a reference to catalyst regenerators at petroleum refineries. Since this formula is applicable only to steel mills, that language has been deleted.

Process Emission Sources

Sulfur compounds are emitted into the atmosphere from fuel burned at process sources or from the process itself. As noted in the St. Louis MMA discussion, the process sources' emissions in that area contribute significantly to the non-attainment demonstration. Consequently, revised and new emission limits are proposed which reflect these sources' current actual emissions and control capabilities. These regulations, which impose no immediate obligations on the regulated facilities, will not necessarily improve air quality. Instead these revisions will enhance the air quality demonstration, which will in turn reflect a larger margin for health and growth purposes. The amendment will also insure that localized atmospheric sulfuric loading is not inadvertently increased by area sources. It should be noted at the outset that the rules for process sources are reorganized and amended into two subparts: process emission sources and fuel burning process sources.

The present general emission limit for process emission sources is 2000 parts per million (ppm). This limit represents a concentration standard as opposed to a mass limitation standard. Although the concentration standard is appropriate for a general limit, it has its drawbacks. For instance, correction factors necessary to compensate for excess air introduced into the exhaust flow are difficult to develop. Therefore, wherever possible a mass limitation standard is proposed.

Three processes are already exempted from the 2000 ppm limit: processes designed to remove sulfur compounds from fuel combustion emission sources' flue gas, i.e., FGDs; existing processes designed to remove sulfur compounds from petroleum and petrochemical processes' flue gas; and qualified existing hydrogen sulfide flares at chemical manufacturing plants. Five additional sources are proposed for exemption from the general concentration limit: (1) sodium aluminum sulfate manufacturing process; (2) sodium sulfite manufacturing process; (3) secondary lead smelting process; (4) glass melting furnaces; and (5) glass heat treating with sulfur dioxide process. Of these five categories only two, secondary lead smelting and glass melting furnaces, are found to significantly contribute to the Chicago MMA non-attainment status for sulfur dioxide (R.635). This is reflected in that the rules proposed are geographically specific.

The differences between the emissions allowed, based on the 2000 ppm standard, and the actual emissions contributed are significant. Review of the processes themselves makes it evident that these differences are inappropriate and unneeded by the process facilities. For example, under the general rule, the glass heat treating with sulfur dioxide process could emit up to 21 pounds of sulfur dioxide per ton of product. Yet, the raw materials as a whole used in this process can only generate one pound of sulfur dioxide per ton of product produced.

Instead of the process-specific emission limits, these five categories are exempted from the general concentration standard. Exemption, as opposed to specific limits, will allow the individual sources emission limits for sulfur dioxide that are appropriate and readily achievable at the individual facility. It should be noted that none of these sources use control equipment for sulfur dioxide. The Agency has requested this regulatory format in an amended proposal.

A specific emission limit is proposed for <u>new</u> process emission sources in the St. Louis MMA which are designed to remove sulfur compounds from the flue gases of petroleum and petrochemical process, commonly known as the Claus process. This process is a recovery unit intended to recapture sulfur from the acid or sour gases at petroleum refineries. The sulfur dioxide emissions from this recovery process are usually more than 9000 ppm, much greater than the 2000 ppm limit. Therefore, secondary recovery is required to control the tail gas emissions of sulfur dioxide. In-plant studies indicate that secondary recovery units can reduce sulfur dioxide emissions to 11-13.9 pounds of sulfur dioxide produced. This corresponds to 646 ppm to 834 ppm, which is far below the 2000 ppm allowed by the general rule.

Shell Oil Company objected to this reduced emission limitation for two reasons. It had just recently installed a SCOT (Shell Claus Off Gas Treating) process at its sulfur recovery

plant in St. Louis. It stated that the 1979 stack test results obtained there and relied on by the Agency in developing the revised limit could not be generalized since design and installation at other facilities might produce different results. Secondly, due to increased recovery efficiency of the SCOT unit, the primary recovery unit is subjected to increased sulfur loadings which result in increased emissions (R.108).

The second fear would seem unjustified based on the 1979 stack tests. These were taken at the Claus plant, and therefore reflect these increased emissions. As for the first, the revised limit is intended to encourage the use of a secondary recovery process as efficient as the SCOT unit at new sulfur recovery facilities as opposed to low temperature Claus processes. In proposing this limit, it is understood that individual facilities might experience problems due to design, installation or other facility specifications. However, as is the case in adopting all regulations solutions to these possible quirks must be remedied as needed. An emission limit of 14 pounds of sulfur dioxide per ton of sulfur for new sulfur recovery processes is proposed.

A 500 ppm limit is proposed for sulfuric acid manufacturing plants in the City of Chicago. The one such plant affected is equipped with a Wellman-Lord sulfur dioxide recovery system with 96.3 percent efficiency. This control equipment was designed to meet the City of Chicago's 500 ppm limit for sulfur dioxide. (R.636). Based on this, the Board finds that the technology to achieve this reduction is feasible and economically reasonable. This limit is therefore proposed to achieve and maintain the NAAQS for sulfur dioxide in the Chicago MMA.

As stated earlier, emission limits based on the fuel combustion capabilities of process sources are proposed. Three categories of such sources are affected. One is source specific; the second involves a type of process source; and the third is an exemption.

The source specific limitation is applicable to a process source located in the St. Louis MMA which burns tea leaves as a solid fuel. The proposed emission limit of 0.70 lb/mBtu will not require any additional control equipment or investments by the affected source, and will allow it to utilize its waste product -- tea leaves -- in a manner more resourceful than landfilling.

Secondly, lime kilns as a fuel burning process source are exempted from both the 2000 ppm limit for process sources and the 1.8 lb/mBtu limit for solid fuel combustion sources. Lime kilns are only located in the Chicago MMA and rural areas and primarily burn high-sulfur coal. Subsequently, it should be subject to the 1.8 lb/mBtu applicable to other similarly located sources burning coal. However, the lime involved in the process itself reacts with the sulfur to reduce the sulfur dioxide emissions to levels below the 1.8 lb/mBtu and therefore well below the 2000 ppm.

In exempting these kilms as a fuel combustion source and a process emission source, the emission attributed to these sources will be their actual emissions, as opposed to their allowable under a Board rule.

An exemption is provided for those sources which can be classified as either fuel burning process sources or fuel combustion emission sources. The slab furnaces at the Granite City Steel Corporation are the only known such sources since the furnaces are directly fired. The oil burned there is too high in sulfur content to meet the limits applicable to fuel combustion sources. However, it does meet the 2000 ppm limitation. The exemption proposed in Rule 204(j)(l) allows these sources to meet either limitation without switching to fuel oil with lower sulfur content.

At First Notice, the rule was phrased in general terms which limited emissions to the maximum amount emitted by a fuel-burning process emission source between March, 1981 and March, 1982. It was only intended that the rule be applicable to slab reheat furnaces, and the proposed limit was not intended to cause any fuel switching. Granite City Steel commented that the limit was inappropriate and the Illinois Petroleum Council commented that as phrased the rule was possibly applicable to petroleum refineries.

The rule has been changed in response to these comments. Rule 204(j)(l) now specifically names slab reheat furnaces—eliminating the Petroleum Council's concern. Furthermore, the emission limit is now a specified amount, 730 lbs/hr, eliminating Granite City Steel's concerns. The mass emission limit was calculated based on the total fuel burning capacity of three of four slab reheat furnaces—since only three of four currently permitted can be operated at one time—and multiplying the percentage of total heat input obtained from the fuel oil by the sulfur content and the emission factor for residual fuel oil. This calculation was agreeable to both the Agency and Granite City Steel. (Public Comments received December 3 and 13, 1982, respectively.)

Before concluding the discussion of the individual segments of proposed Rule 204, the reader should note that the Rule has again been reorganized. This was done with the hope that additional lettered subsections would facilitate understanding. For instance, the formulas found in the Rule entitled Fuel Combustion Emission Sources Located Outside the Chicago, St. Louis (Illinois) and Peoria Major Metropolitan Area has been returned to subsection (e). In so doing it follows directly after the rules containing the emission limits for such sources. This also means that any site-specific limits already granted pursuant to this subsection remain in effect. This reorganization also means that the exemption procedure (Rule 204(g)) proposed in this rulemaking now follows the specific limits set out for fuel combustion sources. In this way it should be clear that the procedure is available to fuel combustion emission sources regulated by Rule 204(c)-(f).

Economic Evaluation

At the March 12, 1981 hearing, an economist with the Agency discussed the possible compliance costs should the emission limits then proposed for fuel combustion sources be adopted. The Agency's permit files identified 113 coal burning facilities to which these limitations would apply. Only one of these, Sherex, was out of compliance with the limits proposed. Therefore, the cost of compliance would be only the amount Sherex would be required to expend to achieve the 3.3 lb/mBtu then proposed for its source.

Having concluded that adoption of the proposed regulations would result in little or no economic effects on the capital investment of the affected facilities, the Agency then considered the economic ramifications should the proposed regulations not be adopted. Fuel switching from low-sulfur coal to high-sulfur Illinois coal has obvious economic benefits, but only for a limited number of facilities. Forty-eight Peoria sources were already burning high-sulfur coal. The permitted coal consumption for the remaining sixty-five facilities is primarily attributable to electric utility companies. Since these facilities are committed to long-term western coal contracts, fuel switching is not a viable alternative. The economic benefits available by switching from liquid or combination fuel to Illinois coal are similarly attractive, but only if the conversion costs can be amortized over a long period.

The ENR economic impact study (Exhibit 17) reviewed separately the relaxed limits for fuel combustion emission sources and the reduced limits for process emission sources. Since cost of compliance was not at issue for either coal combustion sources or process sources, the study assessed the cost savings for the first and the economic consequences of the second. It also examined the probable economic impact on the Illinois fuel markets, which along with cost savings, could be expressed in real dollars. The study considered the consequences to the health and welfare of the affected public and property. Assigning dollar values to this proved difficult.

Five industrial facilities equipped with coal combustion boilers were identified in the Peoria MMA which could benefit from the adoption of a 5.5 lb/mBtu limitation. It should be noted that three of the five, Celotex, Bemis, and Sherex, have already obtained this relief pursuant to R77-15. All five facilities, however, are briefly discussed here.

The Westinghouse Airbrake Company (WABCO) currently utilizes 4,500 tons of Kentucky low-sulfur coal per year at an approximate cost of \$55.15 per ton (1981 dollars). Converting to Illinois coal, costing approximately \$31.42 per ton, should save WABCO nearly \$108,450 per year in fuel costs. Additionally, WABCO indicated that conversion costs would be negligible.

Pursuant to R77-15, Celotex currently burns approximately 45,000 tons of Illinois coal. Therefore, no cost savings is attributable to reaffirmation of the 5.5 lb/mBtu limit. However, if forced to use blended coal, costs would increase by \$727,000 per year. Sherex, the original proponent in R77-15, is operating with the same relief. It currently burns only Illinois coal in its boilers which have two stacks. If forced to instead use blended coal, fuel costs could increase by \$708,000 per year, or as much as \$1,060,000 per year if low-sulfur Kentucky coal is required. These increased cost figures do not include any equipment costs associated with converting to blended coal because Sherex claims that would not be technologically feasible. In allowing a maximum emission limit of 5.5 lb/mBtu, aerodynamic downwash from its facility posed a problem. Sherex has corrected this by heightening its stack at an approximate cost of \$235,000. The same situation holds true for Bemis Corporation which burns an estimated 31,000 tons of Illinois coal per year at a fuel cost savings of \$499,000 per year. Bemis incurred no significant conversion costs.

In 1980 Pekin Energy Company, formerly CPC International, consumed 63,000 tons of Illinois coal and 123,000 tons of western coal for a blend costing an average of \$45.40 per ton, or \$8,380,000. Pekin Energy testified that, if permitted, it could instead consume 191,000 tons of Illinois coal at a total cost of \$5,600,000 and thereby save \$2,830,000. These savings, however, are partially offset by the estimated annualized cost of \$125,000 for a fifty foot stack extension. Without such an extension, emissions ranging up to the 5.5 lb/mBtu limit could have caused aerodynamic downwash, which would result in air quality violations.

Based on the proposed relaxation in McHenry and Kankakee Counties in the Chicago MMA, cost savings were found to be available to one Kankakee facility. Other facilities were not studied since they indicated they would not utilize a relaxed emission limit of 6.8 lb/mBtu. The Kankakee facility, Roper Company, indicated that it could switch from using natural gas to Illinois coal, saving approximately \$134,000 per year.

No relaxed limit is proposed for existing fuel combustion sources located in the St. Louis MMA, so no economic consequences were considered by the ENR study.

In adopting the two relaxed standards, total cost fuel savings for the facilities considered is estimated at \$4,972,000. If the conversion costs, i.e., the stack extension costs, are considered, the net savings is estimated at \$4,612,000. As noted above, relaxing the emission limits will only moderately increase usage of Illinois coal by approximately 0.35% of the current annual production. Consequently, secondary impacts on the Illinois coal industry were determined to be modest. An additional \$6 to \$7.4 million per annum will be generated, and seventy to ninety

Pursuant to R77-15, Celotex currently burns approximately 45,000 tons of Illinois coal. Therefore, no cost savings is attributable to reaffirmation of the 5.5 lb/mBtu limit. if forced to use blended coal, costs would increase by \$727,000 Sherex, the original proponent in R77-15, is operating with the same relief. It currently burns only Illinois coal in its If forced to instead use blended boilers which have two stacks. coal, fuel costs could increase by \$708,000 per year, or as much as \$1,060,000 per year if low-sulfur Kentucky coal is required. These increased cost figures do not include any equipment costs associated with converting to blended coal because Sherex claims that would not be technologically feasible. In allowing a maximum emission limit of 5.5 lb/mBtu, aerodynamic downwash from its facility posed a problem. Sherex has corrected this by heightening its stack at an approximate cost of \$235,000. The same situation holds true for Bemis Corporation which burns an estimated 31,000 tons of Illinois coal per year at a fuel cost savings of \$499,000 per year. Bemis incurred no significant conversion costs.

In 1980 Pekin Energy Company, formerly CPC International, consumed 63,000 tons of Illinois coal and 123,000 tons of western coal for a blend costing an average of \$45.40 per ton, or \$8,380,000. Pekin Energy testified that, if permitted, it could instead consume 191,000 tons of Illinois coal at a total cost of \$5,600,000 and thereby save \$2,830,000. These savings, however, are partially offset by the estimated annualized cost of \$125,000 for a fifty foot stack extension. Without such an extension, emissions ranging up to the 5.5 lb/mBtu limit could have caused aerodynamic downwash, which would result in air quality violations.

Based on the proposed relaxation in McHenry and Kankakee Counties in the Chicago MMA, cost savings were found to be available to one Kankakee facility. Other facilities were not studied since they indicated they would not utilize a relaxed emission limit of 6.8 lb/mBtu. The Kankakee facility, Roper Company, indicated that it could switch from using natural gas to Illinois coal, saving approximately \$134,000 per year.

No relaxed limit is proposed for existing fuel combustion sources located in the St. Louis MMA, so no economic consequences were considered by the ENR study.

In adopting the two relaxed standards, total cost fuel savings for the facilities considered is estimated at \$4,972,000. If the conversion costs, i.e., the stack extension costs, are considered, the net savings is estimated at \$4,612,000. As noted above, relaxing the emission limits will only moderately increase usage of Illinois coal by approximately 0.35% of the current annual production. Consequently, secondary impacts on the Illinois coal industry were determined to be modest. An additional \$6 to \$7.4 million per annum will be generated, and seventy to ninety additional new jobs created. Using a regional economic theory previously developed by ENR, the authors extrapolated the effect of the estimated annual increase to determine the overall effect

on the State's gross product. Assuming that an income multiplier of two was reasonable for small regions, the \$6 to \$7.4 million generated could possibly boost income in Illinois by \$12 to \$14.8 million.

The study considered whether increased use of Illinois coal could disrupt the residual fuel oil market. It concluded that such a possibility was unlikely. Not only is the number of sources switching from out-of-state coal to domestic coal few, but since the supply of Illinois coal is subject to the same uncertainty as out-of-state coal, it is likely that they will have to continue maintaining reserves of fuel oil. Even if such an impact was to occur, the economic ramification would be minimal since it would be a transfer of income rather than a direct loss.

In studying the effects of the proposal for the process emission sources, estimates for control costs or cost savings were not developed. The revisions of the present standard are intended only to more accurately reflect what is actually being emitted; no additional control is envisioned by the amendments. The study did note that in modifying the existing rules, the margin of operating error at the affected facilities is reduced, which has possible economic ramifications. The study also concluded that offsetting credits possibly envisioned by the affected facilities were eliminated.

The economic impact study also examined the costs to the health and welfare of persons and property. A cost of \$1.032 to \$2.434 million per year was estimated. In proposing these amendments, the Board recognizes that a certain segment of the public is rendered less protection from sulfur dioxide, and that property is possibly subjected to increased deterioration from sulfur dioxide. However, the relaxations proposed are limited primarily to the Peoria MMA, and modeling for that locality has adequately demonstrated that downwash and atmospheric loading problems should not occur.

The remaining amendments should not cause any increase in sulfur dioxide emissions, but rather more accurately reflect the actual emissions from process sources. These should therefore not cause any impact on the health and welfare of the people of Illinois. Hopefully, the proposed amendments suffice to enhance the use of Illinois coal to the greatest extent possible, while attainment of the NAAQS for sulfur dioxide is furthered statewide.

This Opinion supports the rules proposed for Second Notice in the Attached Order.

Board Chairman Dumelle and Board Member Werner concurred.

I, Christan L. Moffett, Clerk of the Illinois Pollution Control Board, hereby certify that the above Opinion was adopted on the 30 day of Adams (1982 by a vote of 1982).

Christan L. Moffett/ Clerk
Illinois Pollution Control Board