

ILLINOIS POLLUTION CONTROL BOARD
March 21, 1996

IN THE MATTER OF:)
)
15% ROP PLAN:)
CLEAN-UP PART II:) R96-13
AMENDMENTS TO 35 ILL. ADM.) (Rulemaking-Air)
CODE PARTS 218 AND 219)

Proposed Rule. Second Notice.

OPINION AND ORDER OF THE BOARD (by J. Theodore Meyer):

This proposal for rulemaking before the Board was initiated on December 13, 1995 by the Illinois Environmental Protection Agency (Agency) pursuant to Section 28.5 of the Illinois Environmental Protection Act (Act) (415 ILCS 5/1 *et seq.* (1994)). The proposal seeks to make minor amendments to 35 Ill. Adm. Code Parts 218 and 219.

The Board's responsibility in this matter arises from the Act (415 ILCS 5/1 *et seq.*). The Board is charged therein to "determine, define and implement the environmental control standards applicable in the State of Illinois". (415 ILCS 5/5(b).) More generally, the Board's rulemaking charge is based upon the system of checks and balances integral to Illinois environmental governance: the Board bears responsibility for the rulemaking and principal adjudicatory functions; the Agency has primary responsibility for administration of the Act and the Board's regulations, including today's proposed regulation.

By today's action, the Board finds that the proposal is economically reasonable and technically feasible and is adopting the proposed amendments for the purpose of second notice, pursuant to the Illinois Administrative Procedure Act (5 ILCS 100/1-1 *et seq.*). The Board will direct this matter to be filed with the Joint Committee on Administrative Rules (JCAR) for consideration.

PROCEDURAL HISTORY AND BACKGROUND

Section 182(b) (1) of the Clean Air Act (42 U.S.C. 7511(b) (1)) required Illinois to submit a plan by November 15, 1993, for achieving a 15% reduction of volatile organic material (VOM) emissions in the Chicago and Metro-East ozone nonattainment areas (15% Rate-of-Progress (ROP) Plan). Section 182(b) of the CAA also required Illinois to submit fully adopted measures to implement the ROP Plan. Illinois submitted its 15% ROP plan November 13, 1993, and thereafter proposed regulations to implement the ROP Plan.

In its December 13, 1995 proposal, the Agency submitted seven (7) minor amendments to the ROP Plan which are detailed below. The Agency also filed a motion to waive certain filing requirements of 35 Ill. Adm. Code 102 which the Board granted at its December 20, 1995 meeting.

This proposal was filed pursuant to Section 28.5 of the Act. (415 ILCS 5/27 and 28.5.) As such, the Board is required to proceed within set time frames toward the adoption of this regulation. The Board has no discretion to adjust these time frames under any circumstances. Therefore, the Board adopted the first notice opinion and order on December 20, 1995, without commenting on the merits of the proposal.

The proposal was published for first notice under the Illinois Administrative Procedure Act (5 ILCS 100/1-1 *et seq.*) on January 5, 1996 at 20 Ill.Reg. 122 (Part 218) and 20 Ill.Reg. 155 (Part 219). In response to the first notice publication, the Board received two comments from JCAR regarding additional minor changes to the proposed rulemaking.

A public hearing was held in this rulemaking docket before hearing officer K.C. Poulos in Chicago on February 6, 1996. The Agency presented the pre-filed testimony of Gary E. Beckstead, an Environmental Protection Engineer in the Air Quality Planning Section of the Division of Air Pollution Control in the Agency's Bureau of Air (Exhibit No. 1). During the hearing the Agency offered clarifications to the proposed language. All testimony supports the adoption of the language as set forth in the Board's December 20, 1995 order and as amended by the Agency.

Having received no requests for another hearing, the second and third hearings in this matter were cancelled by hearing officer order dated February 23, 1996. A public comment period was established at the first hearing which expired February 27, 1996. No public comments were received and the record was closed on February 27, 1996.

PROPOSAL

In its proposal, the Agency recommended seven minor amendments in 35 Ill. Adm. Code Parts 218 and 219:

- 1) Add identical language found in Section 218.208(b) regarding "equivalent alternative control plans" to Section 219.108(b);
- 2) Revise certain equations for vapor pressure in Subpart A of both sections;
- 3) Clarify the applicable recordkeeping and reporting requirements for coating operations using touch-up and repair coatings in Subpart F of both sections;
- 4) Correct a Federal Register citation regarding Synthetic

- Organic Chemical and Polymer Manufacturing Plants (SOCMI) and correct typographical errors in Subpart Q of both sections;
- 5) Reflect the Illinois General Assembly's repeal in Public Law 89-79 of the bakery oven rules in Subpart FF of both sections;
 - 6) Amend the exemption for polyethylene manufacturing operations in Subpart TT of both sections; and,
 - 7) Correct a typographical error in Appendix G of both sections.

The Board also received minor editorial revisions from JCAR which will be reflected in this order. One revision is a correction that appeared in a prior rulemaking, but was not reflected in the final printing of that rulemaking. (15% ROP Plan: Amendments to 35 Ill. Adm. Code 219.585(a) and 219. Appendix E, R96-2, PCB (February 1, 1996).) In R96-2 the words "Leaks from" were removed from the title of Subpart Q so that it reads "Synthetic Organic Chemical and Polymer Manufacturing Plant". This order reflects that correction.

DISCUSSION

The Board has carefully considered the testimony and exhibit in this matter. Having received no public comments regarding the minor amendments proposed by the Agency, the Board will amend the proposal as suggested. The Board will also amend the proposal as suggested by JCAR.

CONCLUSION

The Board finds that the proposed amendments are technically feasible and economically reasonable, and the rules are necessary to meet the requirements of the Clean Air Act. We find that the record supports proceeding with the proposed rules, as amended, to second notice.

ORDER

The Board hereby directs that second notice of the following proposed amendments be submitted to the Joint Committee on Administrative Rules (JCAR). The proposed language is indicated by underlining and the proposed deletions are indicated by striking out the previous rule.

TITLE 35: ENVIRONMENTAL PROTECTION
SUBTITLE B: AIR POLLUTION
CHAPTER I: POLLUTION CONTROL BOARD
SUBCHAPTER C: EMISSIONS STANDARDS AND
LIMITATIONS FOR STATIONARY SOURCES

PART 218
ORGANIC MATERIAL EMISSION STANDARDS AND
LIMITATIONS FOR THE CHICAGO AREA

SUBPART A: GENERAL PROVISIONS

Section	
218.100	Introduction
218.101	Savings Clause
218.102	Abbreviations and Conversion Factors
218.103	Applicability
218.104	Definitions
218.105	Test Methods and Procedures
218.106	Compliance Dates
218.107	Operation of Afterburners
218.108	Exemptions, Variations, and Alternative Means of Control or Compliance Determinations
218.109	Vapor Pressure of Volatile Organic Liquids
218.110	Vapor Pressure of Organic Material or Solvents
218.111	Vapor Pressure of Volatile Organic Material
218.112	Incorporations by Reference
218.113	Monitoring for Negligibly-Reactive Compounds
218.114	Compliance with Permit Conditions

SUBPART B: ORGANIC EMISSIONS FROM STORAGE
AND LOADING OPERATIONS

Section	
218.119	Applicability for VOL
218.120	Control Requirements for Storage Containers of VOL
218.121	Storage Containers of VPL
218.122	Loading Operations
218.123	Petroleum Liquid Storage Tanks
218.124	External Floating Roofs
218.125	Compliance Dates
218.126	Compliance Plan (Repealed)
218.127	Testing VOL Operations
218.128	Monitoring VOL Operations
218.129	Recordkeeping and Reporting for VOL Operations

SUBPART C: ORGANIC EMISSIONS FROM
MISCELLANEOUS EQUIPMENT

Section
218.141 Separation Operations
218.142 Pumps and Compressors
218.143 Vapor Blowdown
218.144 Safety Relief Valves

SUBPART E: SOLVENT CLEANING

Section
218.181 Solvent Cleaning in General
218.182 Cold Cleaning
218.183 Open Top Vapor Degreasing
218.184 Conveyorized Degreasing
218.185 Compliance Schedule (Repealed)
218.186 Test Methods

SUBPART F: COATING OPERATIONS

Section
218.204 Emission Limitations
218.205 Daily-Weighted Average Limitations
218.206 Solids Basis Calculation
218.207 Alternative Emission Limitations
218.208 Exemptions from Emission Limitations
218.209 Exemption from General Rule on Use of Organic Material
218.210 Compliance Schedule
218.211 Recordkeeping and Reporting
218.212 Cross-Line Averaging to Establish Compliance for
Coating Lines
218.213 Recordkeeping and Reporting for Cross-Line Averaging
Participating Coating Lines
218.214 Changing Compliance Methods

SUBPART G: USE OF ORGANIC MATERIAL

Section
218.301 Use of Organic Material
218.302 Alternative Standard
218.303 Fuel Combustion Emission Units
218.304 Operations with Compliance Program

SUBPART H: PRINTING AND PUBLISHING

Section
218.401 Flexographic and Rotogravure Printing
218.402 Applicability
218.403 Compliance Schedule
218.404 Recordkeeping and Reporting
218.405 Lithographic Printing: Applicability
218.406 Provisions Applying to Heatset Web Offset Lithographic
Printing Prior to March 15, 1996

- 218.407 Emission Limitations and Control Requirements for Lithographic Printing Lines On and After March 15, 1996
- 218.408 Compliance Schedule for Lithographic Printing on and After March 15, 1996
- 218.409 Testing for Lithographic Printing On and After March 15, 1996
- 218.410 Monitoring Requirements for Lithographic Printing
- 218.411 Recordkeeping and Reporting for Lithographic Printing

SUBPART Q: SYNTHETIC ORGANIC CHEMICAL
AND POLYMER MANUFACTURING PLANT

Section

- 218.421 General Requirements
- 218.422 Inspection Program Plan for Leaks
- 218.423 Inspection Program for Leaks
- 218.424 Repairing Leaks
- 218.425 Recordkeeping for Leaks
- 218.426 Report for Leaks
- 218.427 Alternative Program for Leaks
- 218.428 Open-Ended Valves
- 218.429 Standards for Control Devices
- 218.430 Compliance Date (Repealed)
- 218.431 Applicability
- 218.432 Control Requirements
- 218.433 Performance and Testing Requirements
- 218.434 Monitoring Requirements
- 218.435 Recordkeeping and Reporting Requirements
- 218.436 Compliance Date

SUBPART R: PETROLEUM REFINING AND
RELATED INDUSTRIES; ASPHALT MATERIALS

Section

- 218.441 Petroleum Refinery Waste Gas Disposal
- 218.442 Vacuum Producing Systems
- 218.443 Wastewater (Oil/Water) Separator
- 218.444 Process Unit Turnarounds
- 218.445 Leaks: General Requirements
- 218.446 Monitoring Program Plan for Leaks
- 218.447 Monitoring Program for Leaks
- 218.448 Recordkeeping for Leaks
- 218.449 Reporting for Leaks
- 218.450 Alternative Program for Leaks
- 218.451 Sealing Device Requirements
- 218.452 Compliance Schedule for Leaks
- 218.453 Compliance Dates (Repealed)

SUBPART S: RUBBER AND MISCELLANEOUS
PLASTIC PRODUCTS

Section

218.461 Manufacture of Pneumatic Rubber Tires
218.462 Green Tire Spraying Operations
218.463 Alternative Emission Reduction Systems
218.464 Emission Testing
218.465 Compliance Dates (Repealed)
218.466 Compliance Plan (Repealed)

SUBPART T: PHARMACEUTICAL MANUFACTURING

Section
218.480 Applicability
218.481 Control of Reactors, Distillation Units, Crystallizers,
Centrifuges and Vacuum Dryers
218.482 Control of Air Dryers, Production Equipment Exhaust
Systems and Filters
218.483 Material Storage and Transfer
218.484 In-Process Tanks
218.485 Leaks
218.486 Other Emission Units
218.487 Testing
218.488 Monitoring for Air Pollution Control Equipment
218.489 Recordkeeping for Air Pollution Control Equipment

SUBPART V: BATCH OPERATIONS AND AIR
OXIDATION PROCESSES

Section
218.500 Applicability for Batch Operations
218.501 Control Requirements for Batch Operations
218.502 Determination of Uncontrolled Total Annual Mass
Emissions and Average Flow Rate Values for Batch
Operations
218.503 Performance and Testing Requirements for Batch
Operations
218.504 Monitoring Requirements for Batch Operations
218.505 Reporting and Recordkeeping for Batch Operations
218.506 Compliance Date
218.520 Emission Limitations for Air Oxidation Processes
218.521 Definitions (Repealed)
218.522 Savings Clause
218.523 Compliance
218.524 Determination of Applicability
218.525 Emission Limitations for Air Oxidation Processes
(Renumbered)
218.526 Testing and Monitoring
218.527 Compliance Date (Repealed)

SUBPART W: AGRICULTURE

Section
218.541 Pesticide Exception

SUBPART X: CONSTRUCTION

Section
218.561 Architectural Coatings
218.562 Paving Operations
218.563 Cutback Asphalt

SUBPART Y: GASOLINE DISTRIBUTION

Section
218.581 Bulk Gasoline Plants
218.582 Bulk Gasoline Terminals
218.583 Gasoline Dispensing Operations - Storage Tank Filling
Operations
218.584 Gasoline Delivery Vessels
218.585 Gasoline Volatility Standards
218.586 Gasoline Dispensing Operations - Motor Vehicle Fueling
Operations

SUBPART Z: DRY CLEANERS

Section
218.601 Perchloroethylene Dry Cleaners
218.602 Applicability
218.603 Leaks
218.604 Compliance Dates (Repealed)
218.605 Compliance Plan (Repealed)
218.606 Exception to Compliance Plan (Repealed)
218.607 Standards for Petroleum Solvent Dry Cleaners
218.608 Operating Practices for Petroleum Solvent Dry Cleaners
218.609 Program for Inspection and Repair of Leaks
218.610 Testing and Monitoring
218.611 Applicability for Petroleum Solvent Dry Cleaners
218.612 Compliance Dates (Repealed)
218.613 Compliance Plan (Repealed)

SUBPART AA: PAINT AND INK MANUFACTURING

Section
218.620 Applicability
218.621 Exemption for Waterbase Material and Heatset-Offset Ink
218.623 Permit Conditions (Repealed)
218.624 Open Top Mills, Tanks, Vats or Vessels
218.625 Grinding Mills
218.626 Storage Tanks
218.628 Leaks
218.630 Clean Up
218.636 Compliance Schedule
218.637 Recordkeeping and Reporting

SUBPART BB: POLYSTYRENE PLANTS

Section
218.640 Applicability
218.642 Emissions Limitation at Polystyrene Plants
218.644 Emissions Testing

SUBPART CC: POLYESTER RESIN PRODUCT
MANUFACTURING PROCESS

Section
218.660 Applicability
218.666 Control Requirements
218.667 Compliance Schedule
218.668 Testing
218.670 Recordkeeping and Reporting for Exempt Emission Units
218.672 Recordkeeping and Reporting for Subject Emission Units

SUBPART DD: AEROSOL CAN FILLING

Section
218.680 Applicability
218.686 Control Requirements
218.688 Testing
218.690 Recordkeeping and Reporting for Exempt Emission Units
218.692 Recordkeeping and Reporting for Subject Emission Units

SUBPART FF: BAKERY OVENS (Repealed)

Section
218.720 Applicability (Repealed)
218.722 Control Requirements (Repealed)
218.726 Testing (Repealed)
218.727 Monitoring (Repealed)
218.728 Recordkeeping and Reporting (Repealed)
218.729 Compliance Date (Repealed)
218.730 Certification (Repealed)

SUBPART GG: MARINE TERMINALS

Section
218.760 Applicability
218.762 Control Requirements
218.764 Compliance Certification
218.766 Leaks
218.768 Testing and Monitoring
218.770 Recordkeeping and Reporting

SUBPART HH: MOTOR VEHICLE REFINISHING

Section
218.780 Emission Limitations
218.782 Alternative Control Requirements
218.784 Equipment Specifications

218.786 Surface Preparation Materials
218.787 Work Practices
218.788 Testing
218.789 Monitoring and Recordkeeping for Control Devices
218.790 General Recordkeeping and Reporting
218.791 Compliance Date
218.792 Registration
218.875 Applicability of Subpart BB (Renumbered)
218.877 Emissions Limitation at Polystyrene Plants (Renumbered)
218.879 Compliance Date (Repealed)
218.881 Compliance Plan (Repealed)
218.883 Special Requirements for Compliance Plan (Repealed)
218.886 Emissions Testing (Renumbered)

SUBPART PP: MISCELLANEOUS FABRICATED
PRODUCT MANUFACTURING PROCESSES

Section
218.920 Applicability
218.923 Permit Conditions (Repealed)
218.926 Control Requirements
218.927 Compliance Schedule
218.928 Testing

SUBPART QQ: MISCELLANEOUS FORMULATION
MANUFACTURING PROCESSES

Section
218.940 Applicability
218.943 Permit Conditions (Repealed)
218.946 Control Requirements
218.947 Compliance Schedule
218.948 Testing

SUBPART RR: MISCELLANEOUS ORGANIC
CHEMICAL MANUFACTURING PROCESSES

Section
218.960 Applicability
218.963 Permit Conditions (Repealed)
218.966 Control Requirements
218.967 Compliance Schedule
218.968 Testing

SUBPART TT: OTHER EMISSION UNITS

Section
218.980 Applicability
218.983 Permit Conditions (Repealed)
218.986 Control Requirements
218.987 Compliance Schedule
218.988 Testing

SUBPART UU: RECORDKEEPING AND REPORTING

Section
218.990 Exempt Emission Units
218.991 Subject Emission Units

Section 218.Appendix A: List of Chemicals Defining Synthetic Organic Chemical and Polymer Manufacturing
Section 218.Appendix B: VOM Measurement Techniques for Capture Efficiency
Section 218.Appendix C: Reference Methods and Procedures
Section 218.Appendix D: Coefficients for the Total Resource Effectiveness Index (TRE) Equation
Section 218.Appendix E: List of Affected Marine Terminals
Section 218.Appendix G: TRE Index Measurements for SOCOMI Reactors and Distillation Units
Section 218.Appendix H: Baseline VOM Content Limitations for Subpart F, Section 218.212 Cross-Line Averaging

AUTHORITY: Implementing Section 10 and authorized by Section 28.5 of the Environmental Protection Act [415 ILCS 5/10 and 28.5].

SOURCE: Adopted at R91-7 at 15 Ill. Reg. 12231, effective August 16, 1991; amended in R91-24 at 16 Ill. Reg. 13564, effective August 24, 1992; amended in R91-28 and R91-30 at 16 Ill. Reg. 13864, effective August 24, 1992; amended in R93-9 at 17 Ill. Reg. 16636, effective September 27, 1993; amended in R93-14 at 18 Ill. Reg. at 1945, effective January 24, 1994; amended in R94-12 at 18 Ill. Reg. at 14973, effective September 21, 1994; amended in R94-15 at 18 Ill. Reg. 16392, effective October 25, 1994; amended in R94-16 at 18 Ill. Reg. 16950, effective November 15, 1994; amended in R94-21, R94-31 and R94-32 at 19 Ill. Reg. 6848, effective May 9, 1995; amended in R94-33 at 19 Ill. Reg. 7359, effective May 22, 1995; amended at _____ Ill. Reg. _____, effective _____.

BOARD NOTE: This Part implements the Environmental Protection Act as of July 1, 1994.

SUBPART A: GENERAL PROVISIONS

Section 218.110 Vapor Pressure of Organic Material or Solvent

- a) If the organic material or solvent consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 218.112 of this Part) or the vapor pressure may be obtained from a publication such as: Boublik, T., V. Fried and E. Hala, "The Vapor Pressure of Pure

Substances," Elsevier Scientific Publishing Co., New York (1973); Perry's Chemical Engineer's Handbook, McGraw-Hill Book Company (1984); CRC Handbook of Chemistry and Physics, Chemical Rubber Publishing Company (1986-87); and Lange's Handbook of Chemistry, John A. Dean, editor, McGraw-Hill Book Company (1985).

- b) If the organic material or solvent is in a mixture made up of both organic material compounds and compounds which are not organic material, the vapor pressure shall be determined by the following equation:

$$\frac{P_{\text{vom}}}{P_{\text{om}}} = \frac{\sum_{i=1}^n P_i X_i}{\sum_{i=1}^n X_i}$$

where:

- P_{om} = Total vapor pressure of the portion of the mixture which is composed of organic material;
- n = Number of organic material components in the mixture;
- i = Subscript denoting an individual component;
- P_i = Vapor pressure of an organic material component determined in accordance with subsection (a) of this Section;
- X_i = Mole fraction of the organic material component of the total organic mixture.

- c) If the organic material or solvent is in a mixture made up of only organic material compounds, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 218.112 of this Part) or by the above equation.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

Section 218.111 Vapor Pressure of Volatile Organic Material

- a) If the VOM consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 218.112

of this Part) or the vapor pressure may be obtained from a publication such as: Boublik, T., V. Fried and E. Hala, "The Vapor Pressure of Pure Substances," Elsevier Scientific Publishing Co., New York (1973); Perry's Chemical Engineer's Handbook, McGraw-Hill Book Company (1984); CRC Handbook of Chemistry and Physics, Chemical Rubber Publishing Company (1986-87); and Lange's Handbook of Chemistry, John A. Dean, editor, McGraw-Hill Book Company (1985).

- b) If the VOM is in a mixture made up of both VOM compounds and compounds which are not VOM, the vapor pressure shall be determined by the following equation:

$$P_{\text{vom}} = \frac{\sum_{i=1}^n P_i X_i}{\sum_{i=1}^n X_i}$$

where:

- P_{vom} = Total vapor pressure of the portion of the mixture which is composed of VOM;
- n = Number of VOM components in the mixture;
- i = Subscript denoting an individual component;
- P_i = Vapor pressure of a VOM component determined in accordance with subsection (a) of this Section;
- X_i = Mole fraction of the VOM component of the total organic mixture.

- c) If the VOM is in a mixture made up of only VOM compounds, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 218.112 of this Part) or by the above equation.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

SUBPART F: COATING OPERATIONS

Section 218.208 Exemptions ~~F~~rom Emission Limitations

- a) Exemptions for all coating categories except wood furniture coating. The limitations of this Subpart

shall not apply to coating lines within a source, that otherwise would be subject to the same subsection of Section 218.204 (because they belong to the same coating category, e.g. can coating), provided that combined actual emissions of VOM from all lines at the source subject to that subsection never exceed 6.8 kg/day [15 lbs/day] before the application of capture systems and control devices. (For example, can coating lines within a source would not be subject to the limitations of Section 218.204(b) of this Subpart if the combined actual emissions of VOM from the can coating lines never exceed 6.8 kg/day [15 lbs/day] before the application of capture systems and control devices.) Volatile organic material emissions from heavy off-highway vehicle products coating lines must be combined with VOM emissions from miscellaneous metal parts and products coating lines to determine applicability. Any owner or operator of a coating source shall comply with the applicable coating analysis test methods and procedures specified in Section 218.105(a) of this Part and the recordkeeping and reporting requirements specified in Section 218.211(a) of this Subpart if total VOM emissions from the subject coating lines are always less than or equal to 6.8 kg/day [15 lbs/day] before the application of capture systems and control devices and, therefore, are not subject to the limitations of Section 218.204 of this Subpart. Once a category of coating lines at a source is subject to the limitations in Section 218.204 of this Subpart the coating lines are always subject to the limitations in Section 218.204 of this Subpart.

b) Applicability for wood furniture coating

- 1) The limitations of this Subpart shall apply to a source's wood furniture coating lines if the source contains process emission units, not regulated by Subparts B, E, F (excluding Section 218.204(l) of this Subpart), H (excluding Section 218.405 of this Part), Q, R, S, T (excluding Section 218.486 of this Part), V, X, Y, or BB of this Part, which as a group both:
 - A) Have a maximum theoretical emissions of 91 Mg (100 tons) or more per calendar year of VOM if no air pollution control equipment were used, and
 - B) Are not limited to less than 91 Mg (100 tons) of VOM per calendar year if no air pollution control equipment were used, through production or capacity limitations contained

in a federally enforceable permit or SIP revision.

- 2) The limitations of this Subpart shall apply to a source's wood furniture coating lines, on and after March 15, 1996, if the source contains process emission units, which as a group, have a potential to emit 22.7 Mg (25 tons) or more of VOM per calendar year and have not limited emissions to less than 22.7 Mg (25 tons) of VOM per calendar year through production or capacity limitations contained in a federally enforceable operating permit or SIP revision, and which:
 - A) Are not regulated by Subparts B, E, F (excluding Section 218.204(l) of this Subpart), H, Q, R, S, T (excluding Section 218.486 of this Part), V, X, Y, Z or BB of this Part; and
 - B) Are not included in any of the following categories: synthetic organic chemical manufacturing industry (SOCMI) distillation, SOCMI reactors, plastic parts coating (business machines), plastic parts coating (other), offset lithography, industrial wastewater, autobody refinishing, SOCMI batch processing, volatile organic liquid storage tanks and clean-up solvents operations.
- 3) If a source ceases to fulfill the criteria of subsection (b) (1) or (b) (2) of this Section, the limitations of Section 218.204(l) of this Subpart shall continue to apply to any wood furniture coating line which was ever subject to the limitations of Section 218.204(l) of this Subpart.
- 4) For the purposes of subsection (b) of this Section, an emission unit shall be considered to be regulated by a Subpart if it is subject to the limitations of that Subpart. An emission unit is not considered regulated by a Subpart if it is not subject to the limits of that Subpart, e.g., the emission unit is covered by an exemption in the Subpart or the applicability criteria of the Subpart are not met.
- 5) Any owner or operator of a wood furniture coating line to which the limitations of this Subpart are not applicable due to the criteria in subsection (b) of this Section shall, upon request by the Agency or the USEPA, submit records to the Agency

and the USEPA within 30 calendar days from the date of the request that document that the coating line is exempt from the limitations of this Subpart.

- c) On and after March 15, 1996, the limitations of this Subpart shall not apply to touch-up and repair coatings used by a coating source described by subsections 218.204(b), (d), (f), (g), (i), (j), (n) and (o) of this Subpart; provided that the source-wide volume of such coatings used does not exceed 0.95 l (1 quart) per eight-hour period or exceed 209 l/yr [55 gal/yr] for any rolling twelve month period. Recordkeeping and reporting for touch-up and repair coatings shall be consistent with Section 218.211(b)(4) of this Subpart subsection (d) of this Section.
- d) On and after March 15, 1996, the owner or operator of a coating line or a group of coating lines using touch-up and repair coatings that are exempted from the limitations of Section 218.204(b), (d), (f), (g), (i), (j), (n) and (o) of this Subpart because of the provisions of Section 218.208(c) of this Subpart shall:
- 1) Collect and record the name, identification number, and volume used of each touch-up and repair coating, as applied on each coating line, per eight-hour period and per month;
 - 2) Perform calculations on a daily basis, and maintain at the source records of such calculations, of the combined volume of touch-up and repair coatings used source-wide for each eight-hour period;
 - 3) Perform calculations on a monthly basis, and maintain at the source records of such calculations, of the combined volume of touch-up and repair coatings used source-wide for the month and the rolling twelve month period;
 - 4) Prepare and maintain at the source an annual summary of the information required to be compiled pursuant to subsections ~~(e)(4)(A) and (e)(4)(B)~~ (d)(1) and (d)(2) of this Section on or before January 31 of the following year;
 - 5) Maintain at the source for a minimum period of three years all records required to be kept under this subsection and make such records available to the Agency upon request;

- 6) Notify the Agency in writing if the use of touch-up and repair coatings at the source ever exceeds a volume of 0.95 l (1 quart) per eight-hour period or exceeds 209 l/yr ~~+(55 gal/yr)~~ for any rolling twelve month period within 30 days after any such exceedance. Such notification shall include a copy of any records of such exceedance; and
- 7) "Touch-up and repair coatings" means, for purposes of 35 Ill. Adm. Code 218.208, any coating used to cover minor scratches and nicks that occur during manufacturing and assembly processes.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

SUBPART Q: ~~LEAKS FROM~~ SYNTHETIC ORGANIC CHEMICAL
AND POLYMER MANUFACTURING PLANT

Section 218.431 Applicability

- a) The provisions of Sections 218.431 through 218.436 of this Subpart shall apply to:
 - 1) Every owner or operator of any chemical manufacturing process unit that manufactures, as a primary product, one or more of the chemicals listed in Appendix A of this Part and that chemical manufacturing process unit causes or allows any reactor or distillation unit, either individually or in tandem, to discharge one or more process vent streams either directly to the atmosphere or to a recovery system.
 - 2) All continuous distillation and reactor process emission units not subject to Section 218.520 through 218.527 of this Part, and located within Stepan Company's Millsdale manufacturing facility, Elwood, Illinois.
- b) Notwithstanding subsection (a) of this Section, the control requirements set forth within Section 218.432 of this Subpart shall not apply to the following:
 - 1) Any process vent stream with a total resource effectiveness (TRE) index value greater than 1.0. However, such process vent stream remains subject to the performance testing requirements contained in Section 218.433 of this Subpart and the reporting and recordkeeping requirements contained in Section 218.435 of this Subpart;

- 2) Any reactor or distillation unit that is designed and operated as a batch operation;
- 3) Any reactor or distillation unit that is part of a polymer manufacturing operation;
- 4) Any reactor or distillation unit that is part of the chemical manufacturing process unit with a total design capacity of less than 1 gigagram (1,100 tons) per year for all chemicals produced, as a primary product, within that process unit. However, such operations remain subject to the reporting and recordkeeping requirements contained in Section 218.435(d) of this Subpart;
- 5) Any vent stream with a flow rate less than 0.0085 scm/min or a total VOM concentration of less than 500 ppmv, less methane and ethane, as measured by Method 18, or a concentration of VOM of less than 250 ppmv as measured by Method 25A. However, such operations remain subject to the performance testing requirement listed in Section 218.433 of this Subpart, as well as the reporting and recordkeeping requirements contained in Section 218.435 of this Subpart; or
- 6) Any reactor or distillation unit included within an Early Reduction Program, as specified in 40 CFR 63, and published in 57 Fed. Reg. 61970 ~~(October 22, 1993)~~ (December 29, 1992), evidenced by a timely enforceable commitment approved by USEPA.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

Section 218.434 Monitoring Requirements

- a) The owner or operator of a source subject to the control requirements in Section 218.432 of this Subpart that uses an incinerator to comply with the VOM emission limitation specified in Section 218.432(a)(1) shall install, calibrate, maintain, and operate, according to manufacturer's specifications, a temperature monitoring device equipped with a continuous recorder and having an accuracy of ± 1 percent of the temperature measured expressed in degrees Celsius, or $\pm 0.5^{\circ}\text{C}$, whichever is greater.
 - 1) Where an incinerator other than a catalytic incinerator is used, a temperature monitoring device shall be installed in the firebox.
 - 2) Where a catalytic incinerator is used, temperature

monitoring devices shall be installed in the gas stream immediately before and after the catalyst bed.

- b) The owner or operator of a source that uses a flare to comply with Section 218.432(a)(2) of this Subpart shall install, calibrate, maintain and operate, according to manufacturer's specifications, a heat-sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light to indicate continuous presence of a flame.
- c) The owner or operator of a source that uses a boiler or process heater with a design heat input capacity less than 44 megawatts to comply with Section 218.432(a)(1) of this Subpart shall install, calibrate, maintain and operate, according to the manufacturer's specifications, a temperature monitoring device in the firebox. The monitoring device shall be equipped with a continuous recorder with an accuracy of ± 1 percent of the temperature being measured expressed in degrees Celsius or $\pm 0.5^{\circ}\text{C}$, whichever is greater. Any boiler or process heater in which all vent streams are introduced with primary fuel is exempt from this requirement.
- d) The owner or operator of a process vent with a TRE index value of 4.0 or less that uses one or more product recovery devices shall install either an organic monitoring device equipped with a continuous recorder or the monitoring equipment specified in subsections (d)(1), (d)(2), (d)(3) or (d)(4) of this Section, depending on the type of recovery device used. All monitoring equipment shall be installed, calibrated and maintained according to the manufacturer's specifications.
 - 1) Where an absorber is the final recovery device in the recovery system, a scrubbing liquid temperature monitoring device and a specific gravity monitoring device, each equipped with a continuous recorder, shall be used.
 - 2) Where a condenser is the final recovery device in the recovery system, a condenser exit (product side) temperature monitoring device equipped with a continuous recorder and having an accuracy of ± 1 percent of the temperature being monitored expressed in degrees Celsius or $\pm 0.5^{\circ}\text{C}$, whichever is greater.
 - 3) Where a carbon adsorber is the final recovery device in the recovery system, an integrating regeneration ~~stream~~ steam flow monitoring device having an accuracy of ± 10 percent, capable of recording the total regeneration ~~stream~~ steam mass flow for each regeneration cycle; and a carbon bed temperature monitoring device having an

accuracy of ± 1 percent of the temperature being monitored expressed in degrees Celsius of $\pm 0.5^{\circ}\text{C}$, capable of recording the carbon bed temperature after each regeneration and within 15 minutes of completing any cooling cycle.

- 4) Where a scrubber is used with an incinerator, boiler, or, in the case of halogenated vent streams, a process heater, the following monitoring equipment is required for the scrubber:
 - A) A pH monitoring device equipped with a continuous recorder to monitor the pH of the scrubber effluent; and
 - B) Flow meters equipped with a continuous recorder at the scrubber influent for liquid flow and the scrubber inlet for gas stream flow.
- e) The owner or operator of a process vent using a vent system that contains bypass lines capable of diverting a vent stream away from the control device associated with a process vent shall comply with either (e) (1) or (e) (2) of this Section. Equipment needed for safety purposes, including, but not limited to, pressure relief devices, are not subject to this subsection.
 - 1) The owner or operator shall install, calibrate, maintain and operate a flow indicator that provides a record of vent stream flow at least once every 15 minutes. The flow indicator shall be installed at the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.
 - 2) The owner or operator shall secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism shall be performed at least once every month to ensure that the valve is maintained in the closed position and the vent stream is not diverted through the bypass line.
- f) The owner or operator of a process vent may monitor by an equivalent alternative means or parameters other than those listed in subsections (a) through (d) of this Section. Any equivalent alternative shall be approved by the Agency and USEPA, and contained in the source's operating permit as federally enforceable permit conditions.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

Section 218.435 Recordkeeping and Reporting Requirements

- a) Every owner or operator of a reactor or distillation unit with a TRE index value of 4.0 or less shall keep records, for a minimum of 3 years, of the following parameters measured during a performance test or TRE determination required under Section 218.433 of this Subpart, and required to be monitored under Section 218.434 of this Subpart.
 - 1) Every owner or operator of a source that seeks to demonstrate compliance with Section 218.432(a)(1) of this Subpart through the use of either a thermal or catalytic incinerator shall maintain records of the following:
 - A) The average firebox temperature of the incinerator (or the average temperature upstream and downstream of the catalyst bed for a catalytic incinerator), measured at least every 15 minutes and averaged over the same time period of the performance testing; and
 - B) The percent reduction of VOM determined as specified in Section 218.433(c) of this Subpart achieved by the incinerator, or the concentration of VOM (ppmv, by compound) determined as specified in Section 218.433(c) of this Subpart at the outlet of the control device, on a dry basis, corrected to 3 percent oxygen.
 - 2) Every owner or operator of a source that seeks to demonstrate compliance with Section 218.432(a)(1) of this Subpart through the use of a boiler or process heater shall maintain the records described below. Any boiler or process heater in which all vent streams are introduced with primary fuel are exempt from these requirements.
 - A) A description of the location at which the vent stream is introduced into the boiler or process heater; and
 - B) The average combustion temperature of the boiler or process heater with a design heat input capacity of less than 44 megawatt measured at least every 15 minutes and averaged over the same time period of the performance testing.
 - 3) Every owner or operator of a source that seeks to demonstrate compliance with Section 218.432(a)(2) of this Subpart through use of a smokeless flare, or flare design (i.e., steam-assisted, air-assisted, or

nonassisted), shall maintain records of all visible emission readings, heat content determinations, flow rate measurements, and exit velocity determinations made during the performance test, continuous records of the flare pilot flame monitoring, and records of all periods of operations during which the pilot flame is absent.

- 4) Every owner or operator of a source that seeks to demonstrate compliance with Section 218.432(b) of this Subpart shall maintain records of the following:
 - A) Where an absorber is the final recovery device in the recovery system, the exit specific gravity (or alternative parameter which is a measure of the degree of absorbing liquid saturation, if approved by the Agency and USEPA, and average exit temperature of the absorbing liquid measured at least every 15 minutes and averaged over the same time period as the performance testing (both measured while the vent stream is normally routed and constituted);
 - B) Where a condenser is the final recovery device in the recovery system, the average exit (product side) temperature measured at least every 15 minutes and averaged over the same time period as the performance testing while the vent stream is normally routed and constituted;
 - C) Where a carbon absorber is the final recovery device in the recovery system, the total ~~stream~~ steam mass or volumetric flow measured at least every 15 minutes and averaged over the same time period as the performance testing (full carbon bed cycle), the temperature of the carbon bed after regeneration (and within 15 minutes of completion of any cooling cycle(s)), and duration of the carbon bed steaming cycle (all measured while the vent stream is normally routed and constituted);
 - D) As an alternative to subsection (a) (4) (A), (a) (4) (B) or (a) (4) (C) of this Section, the concentration level or reading indicated by the organic monitoring device at the outlet of the absorber, condenser, or carbon absorber, measured at least every 15 minutes and averaged over the same time period as the performance testing (measured while the vent stream is normally routed and constituted); or
 - E) All measurements and calculations performed to

determine the flow rate, VOM concentration, heating value, and TRE index value of the vent stream.

- b) Every owner or operator of a reactor or distillation unit with a TRE index value of less than 4.0 shall be subject to the exceedance reporting requirements of the draft Enhanced Monitoring Guidelines as published at 58 Fed. Reg. 54648 (October 22, 1993).
- c) Every owner or operator of a source seeking to comply with Section 218.432(b) of this Subpart shall maintain records of the following:
 - 1) Any changes in production capacity, feedstock type, catalyst type, or of any replacement, removal, or addition of recovery equipment or reactors and distillation units; and
 - 2) Any recalculation of the flow rate, VOM concentration, or TRE index value calculated according to ~~Section~~ Subsection (c) of Appendix G of this Part.
- d) Every owner or operator of a source claiming a design capacity of less than 1 gigagram (1,100 tons) per year, as contained in Section 218.431(b) of this Subpart, shall maintain records of the design capacity or any changes in equipment or operations that may affect the design capacity.
- e) Every owner or operator of a source claiming a vent stream flow rate or vent stream concentration exemption level, as contained in Section 218.431(b) (5) of this Subpart, shall maintain records to indicate that the stream flow rate is less than 0.0085 scm/min or the vent stream concentration is less than 500 ppmv.

(Source: Amended at _____ Ill. Reg. _____ , effective _____)

SUBPART FF: BAKERY OVENS (Repealed)

Section 218.720 Applicability (Repealed)

- ~~a) The provisions of this Subpart shall apply to every owner or operator of a source which operates a bakery oven, as defined at 35 Ill. Admin. Code 211.680, unless the source bakes products only for on site human consumption or on site retail sale.~~
- ~~b) Notwithstanding subsection (a) of this Section, a source is required to comply with the control~~

~~requirements of this Subpart only if the source has the potential to emit 22.7 Mg (25 tons) or more of VOM per year, in the aggregate, from all emission units at the source, excluding:~~

- ~~1) Emission units regulated by Subparts B, E, F, H, Q, R, S, T (excluding Section 218.486 of this Part), V, X, Y, Z or BB of this Part; and~~
- ~~2) Emission units that are included in any of the following categories: synthetic organic chemical manufacturing industry (SOCMI) distillation, SOCMI reactors, wood furniture coating, plastic parts coating (business machines), plastic parts coating (other), offset lithography, industrial wastewater, autobody refinishing, SOCMI batch processing, volatile organic liquid storage tanks and clean up solvents operations.~~
- ~~e) Every owner or operator of a source which has limited its potential to emit below 22.7 Mg (25 tons) of VOM per year, as specified in subsection (b) of this Section, through federally enforceable permit conditions is not required to comply with this Subpart.~~
- ~~d) Every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria in subsection (b) of this Section remains subject to the recordkeeping and reporting requirements of Section 218.728(b) of this Subpart and the certification requirements in Section 218.730(d) of this Subpart.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 218.722 Control Requirements (Repealed)

- ~~a) Every owner or operator of a source subject to the control requirements of this Subpart shall comply with the requirements of subsection (a) (1) or (a) (2) of this Section for each bakery oven with a rated heat input capacity of at least 2 mmbtu/hr or at least 586 kW:~~
 - ~~1) Operate emissions capture and control equipment which achieves an overall reduction in uncontrolled VOM emissions of at least 81 percent from each such bakery oven; or~~
 - ~~2) Provide an equivalent alternative control plan for such bakery ovens at the source which has been~~

approved by the Agency and USEPA through federally enforceable permit conditions or as a SIP revision.

~~b) An owner or operator of a source subject to the control requirements of this Subpart may elect to exempt from the control requirements in subsections (a) (1) or (a) (2) and (c) (1) or (c) (2) of this Section any bakery oven with actual VOM emissions less than or equal to 15 TPY, provided that the total actual VOM emissions from all such exempt bakery ovens never exceed 25 TPY.~~

~~e) Notwithstanding the requirements in subsection (a) of this Section, until March 15, 1998, only, a source may elect to comply with the control requirements in subsection (c) (1) or (c) (2) of this Section, rather than the control requirements in subsection (a) (1) or (a) (2) of this Section, if all emission units at the source, in the aggregate, excluding emission units regulated by Subparts B, E, F, H (excluding Section 218.405 of this Subpart), Q, R, S, T (excluding Section 218.486 of this Subpart), V, X, Y, Z or BB of this Part, have maximum theoretical emissions of less than 90.7 Mg (100 tons) of VOM per year or are limited to less than 90.7 Mg (100 tons) of VOM emissions per calendar year in the absence of air pollution control equipment through production or capacity limitations contained in federally enforceable permit conditions or in a SIP revision:~~

~~1) Operate emissions capture and control equipment which achieves an overall reduction in uncontrolled VOM emissions of at least 60 percent from each bakery oven with a rated heat input capacity of at least 2 mmbtu/hr or at least 586 KW; or~~

~~2) Provide an equivalent alternative control plan for such bakery ovens at the source which has been approved by the Agency and USEPA through federally enforceable permit conditions or as a SIP revision.~~

~~d) Any bakery oven that becomes subject to the requirements of this Subpart at any time shall remain subject to the requirements of this Subpart at all times thereafter.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 218.726 Testing (Repealed)

- ~~a) Upon request by the Agency, the owner or operator of a bakery oven shall, at its own expense, conduct such tests in accordance with the applicable test methods and procedures specified in Section 218.105(f) of this Part to demonstrate compliance with the control requirements of this Subpart and shall:~~
- ~~1) Notify the Agency 30 days prior to conducting such tests; and~~
 - ~~2) Submit all test results to the Agency within 30 days of conducting such tests.~~
- ~~b) Nothing in this Section shall limit the authority of USEPA pursuant to the Clean Air Act (CAA) to require testing, or shall affect the authority of USEPA under Section 114 of the CAA (42 U.S.C. 7414 (1990)).~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 218.727 Monitoring (Repealed)

- ~~a) Every owner or operator of a bakery oven subject to the control requirements of this Subpart shall install and operate at all times a device to continuously monitor the following parameters for each type of control device as follows:~~
- ~~1) For catalytic oxidizers, the inlet and outlet temperatures of the oxidizer;~~
 - ~~2) For regenerative oxidizers, the temperature in the combustion chamber; or~~
 - ~~3) For thermal incinerators, the temperature in the combustion chamber.~~
- ~~b) The owner or operator may monitor with an alternative method or monitor other parameters if approved by the Agency and USEPA through federally enforceable permit conditions or as a SIP revision.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 218.728 Recordkeeping and Reporting (Repealed)

- ~~a) Every owner or operator of a bakery oven shall maintain the following records for the most recent consecutive 3 year period for all bakery ovens subject to the control requirements of this Subpart. Such records shall be made available to the Agency immediately upon request.~~
- ~~1) Parameters for control devices as monitored pursuant to Section 218.727 of this Subpart;~~
 - ~~2) Hrs/day of operation of each bakery oven;~~
 - ~~3) Factors necessary to calculate VOM emissions for all bakery ovens including, but not limited to, type of dough used for each yeast leavened baked product, initial yeast percentage for each product, total fermentation time for each product, any additional percentage of yeast added, and the fermentation time of any additional yeast;~~
 - ~~4) Calculated daily VOM emissions of each bakery oven expressed as lbs/day;~~
 - ~~5) Total amount of each type of yeast leavened bread product produced by each bakery oven expressed as lbs/day.~~
- ~~b) Every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria in Section 218.720(b) of this Subpart shall maintain records necessary to demonstrate that its potential to emit is less than 22.7 Mg (25 tons) of VOM per year, as specified in Section 218.720(b). Such records shall be maintained for the most recent consecutive 3 year period and shall be made available to the Agency immediately upon request.~~
- ~~c) Every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria specified in Section 218.722(b) of this Subpart shall:~~
- ~~1) Maintain records necessary to demonstrate that the actual VOM emissions from exempt bakery ovens are less than or equal to 15 TPY for each bakery oven and less than or equal to 25 TPY from all exempt bakery ovens combined. Such records shall be maintained for the most recent consecutive 3 year period and shall be made available to the Agency immediately upon request; and~~
 - ~~2) Notify the Agency in writing if the actual VOM emissions from an exempt bakery oven ever exceed~~

~~15 TPY or the actual VOM emissions from a combination of exempt bakery ovens ever exceed 25 TPY, within 30 days after the exceedance occurs. Such notice shall include a copy of all records of the exceedance.~~

- ~~d) Every owner or operator of a bakery oven which is controlling emissions as provided in Section 218.722(e) of this Subpart until March 15, 1998, shall maintain records necessary to demonstrate that its maximum theoretical emissions as specified in Section 218.722(e) are less than 90.7 Mg (100 tons) of VOM per year. Such records shall be maintained for the most recent consecutive 3 year period and shall be made available to the Agency immediately upon request.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 218.729 Compliance Date (Repealed)

~~On and after March 15, 1996, upon initial startup or upon modification, every owner or operator of a source subject to this Subpart shall comply with the requirements of this Subpart.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 218.730 Certification (Repealed)

- ~~a) Every owner or operator of a source subject to the control requirements of this Subpart shall certify compliance with this Subpart on or before a date consistent with Section 218.729 of this Subpart.~~
- ~~b) If an owner or operator of a bakery oven subject to the control requirements of this Subpart changes the method of compliance, the owner or operator shall certify compliance with the requirements of this Subpart for the alternative method upon changing the method of compliance.~~
- ~~e) All certifications of compliance with this Subpart shall include the results of all tests and the calculations performed to demonstrate that each oven at the source is in compliance with, or is exempt from, the control requirements of this Subpart. The certification shall include the following:~~
- ~~1) The name and identification number of each oven~~

- ~~and any associated capture and control device;~~
- ~~2) The maximum rated heat input of each oven;~~
 - ~~3) A classification of each oven as either a "bakery oven" as defined in 35 Ill. Admin. Code 211.680 or an oven used exclusively to bake non yeast-leavened products;~~
 - ~~4) The capture and control efficiency of each bakery oven control device;~~
 - ~~5) Test reports, calculations, and other data necessary to demonstrate that the capture and control efficiency of each bakery oven control device achieves an overall reduction in uncontrolled VOM emissions of at least 81 percent, and~~
 - ~~6) The date each bakery oven control device was installed and operating.~~
- ~~d) On or before March 15, 1996, or upon initial startup, every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria in Section 218.720(b) of this Subpart shall certify that its potential to emit is less than 22.7 Mg (25 tons) of VOM per year, as specified in Section 218.720(b).~~
- ~~e) On or before March 15, 1996, or upon initial startup, every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria specified in Section 218.722(b) of this Subpart shall certify that actual VOM emissions from any individual exempt bakery oven never exceed 15 TPY and that VOM emissions from all exempt bakery ovens, in the aggregate, never exceed 25 TPY.~~
- ~~f) On or before March 15, 1996, or upon initial startup if prior to March 15, 1998, every owner or operator of a bakery oven which is controlling emissions as provided by Section 218.722(e) of this Subpart shall certify that its maximum theoretical emissions as specified in Section 218.722(e) are less than 90.7 Mg (100 tons) of VOM per year.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

SUBPART TT: OTHER EMISSION UNITS

Section 218.980 Applicability

a) Maximum theoretical emissions:

1) A source is subject to this Subpart if it contains process emission units not regulated by Subparts B, E, F (excluding Section 218.204(1) of this Part), H (excluding Section 218.405 of this Part), Q, R, S, T (excluding Section 218.486 of this Part), V, X, Y, Z or BB of this Part, which as a group both:

A) Have maximum theoretical emissions of 90.7 Mg (100 tons) or more per calendar year of VOM, and

B) Are not limited to less than 90.7 Mg (100 tons) of VOM emissions per calendar year in the absence of air pollution control equipment through production or capacity limitations contained in a federally enforceable permit or a SIP revision.

2) If a source is subject to this Subpart as provided in this Subpart, the requirements of this Subpart shall apply to a source's VOM emission units which are not included within any of the categories specified in Subparts B, E, F, H, Q, R, S, T, V, X, Y, Z, AA, BB, PP, QQ, or RR of this Part or which are not exempted from permitting requirements pursuant to 35 Ill. Adm. Code 201.146.

b) Potential to emit:

1) A source is subject to this Subpart if it has the potential to emit 22.7 Mg (25 tons) or more of VOM per year, in aggregate, from emission units, other than furnaces at glass container manufacturing sources and VOM leaks from components, that are:

A) Not regulated by Subparts B, E, F, H, Q, R, S, T, (excluding Section 218.486 of this Part), V, X, Y, Z, or BB of this Part, or

B) Not included in any of the following categories: synthetic organic chemical manufacturing industry (SOCMI) distillation, SOCMI reactors, wood furniture, plastic parts coating (business machines), plastic parts coating (other), offset lithography, industrial wastewater, autobody refinishing,

SOCMI batch processing, volatile organic liquid storage tanks and clean-up solvents operations.

- 2) If a source is subject to this Subpart as provided above, the requirements of this Subpart shall apply to a source's VOM emission units, which are:
 - A) Not included within any of the categories specified in Subparts B, E, F, H, Q, R, S, T, V, X, Y, Z, AA, BB, CC, DD, PP, QQ or RR of this Part, or which are not exempted from permitting requirements pursuant to 35 Ill. Adm. Code 201.146 (excluding Section 201.146(o) and (p)), or
 - B) Not included in any of the following categories: synthetic organic chemical manufacturing industry (SOCMI) distillation, SOCMI reactors, wood furniture, plastic parts coating (business machines), plastic parts coating (other), offset lithography, industrial wastewater, autobody refinishing, SOCMI batch processing, volatile organic liquid storage tanks and clean-up solvents operations.
- c) If a source ceases to fulfill the criteria of subsections (a) and/or (b) of this Section, the requirements of this Subpart shall continue to apply to an emission unit which was ever subject to the control requirements of Section 219.986 of this Part.
- d) No limits under this Subpart shall apply to emission units with emissions of VOM to the atmosphere less than or equal to 2.3 Mg (2.5 tons) per calendar year if the total emissions from such emission units not complying with Section 219.986 of this Part does not exceed 4.5 Mg (5.0 tons) per calendar year.
- e) For the purposes of this Subpart, an emission unit shall be considered regulated by a Subpart, if it is subject to the limits of that Subpart. An emission unit is considered not regulated by a Subpart if it is not subject to the limits of that Subpart, e.g., the emission unit is covered by an exemption in the Subpart or the applicability criteria of the Subpart are not met.
- f) The control requirements in Subpart TT shall not apply to sewage treatment plants; vegetable oil extraction and processing; coke ovens (including by-product

recovery plants); fuel combustion units; bakeries; barge loading facilities; jet engine test cells; production of polystyrene foam insulation board including storage and extrusion of scrap where blowing agent is added to the polystyrene resin at the source, but not including blending and preliminary expansion of resin prior to molding where blowing agent is incorporated into the polystyrene resin by the producer of the resin; production of polystyrene or polyethylene foam packaging not including blending and preliminary expansion of resin prior to molding where blowing agent is incorporated into the polystyrene or polyethylene resin by the producer of the resin, and not including storage and extrusion of scrap where blowing agent is added to the polystyrene or polyethylene resin at the source; and iron and steel production; and furnaces at glass container manufacturing sources.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

Section 218.Appendix G TRE Index Measurements for SOCOMI Reactors and Distillation Units

For purposes of Subpart Q, Sections 218.431 through 218.435, the following apply:

- a) The following test methods shall be used to determine compliance with the total resource effectiveness ("TRE") index value:
 - 1) Method 1 or 1A, incorporated by reference at Section 218.112 of this Part, as appropriate, for selection of the sampling site.
 - A) The sampling site for the vent stream molar composition determination and flow rate prescribed in subsections (a)(2) and (a)(3) of this Appendix shall be, except for the situations outlined in subsection (a)(1)(B), after the final recovery device, if a recovery system is present, prior to the inlet of any control device, and prior to any post-reactor or post-distillation unit introduction of halogenated compounds into the vent stream. No traverse site selection method is needed for vents smaller than 10 cm in diameter.
 - B) If any gas stream other than the reactor or distillation unit vent stream is normally conducted through the final recovery device:

- i) The sampling site for vent stream flow rate and molar composition shall be prior to the final recovery device and prior to the point at which any nonreactor or nondistillation unit vent stream or stream from a nonaffected reactor or distillation unit is introduced. Method 18 incorporated by reference at Section 218.112 of this Part, shall be used to measure organic compound concentrations at this site.
 - ii) The efficiency of the final recovery device is determined by measuring the organic compound concentrations using Method 18, incorporated by reference at Section 218.112 of this Part, at the inlet to the final recovery device after the introduction of all vent streams and at the outlet of the final recovery device.
 - iii) The efficiency of the final recovery device determined according to subsection (a) (1) (B) (ii) of this Appendix shall be applied to the organic compound concentrations measured according to subsection (a) (1) (B) (i) of this Appendix to determine the concentrations of organic compounds from the final recovery device attributable to the reactor or distillation unit vent stream. The resulting organic compound concentrations are then used to perform the calculations outlined in subsection (a) (4) of this Appendix.
- 2) The molar composition of the vent stream shall be determined as follows:
 - A) Method 18, incorporated by reference at Section 218.112 of this Part, to measure the concentration of organic compounds including those containing halogens;
 - B) ASTM D1946-77, incorporated by reference at Section 218.112 of this Part, to measure the concentration of carbon monoxide and hydrogen; and
 - C) Method 4, incorporated by reference at Section 218.112 of this Part, to measure the content of water vapor.
 - 3) The volumetric flow rate shall be determined using Method 2, 2A, 2C, or 2D, incorporated by reference at

Section 218.112 of this Part, as appropriate.

- 4) The emission rate of VOM (minus methane and ethane) (E_{VOM}) in the vent stream shall be calculated using the following formula:

$$E_{VOM} = K_2 \sum_{j=1}^n C_j M_j Q_s$$

where:

E_{VOM} = Emission rate of VOM (minus methane and ethane) in the sample, kg/hr.

K_2 = Constant, 2.494×10^{-6} (l/ppmv) (g-mole/scm) (kg/g) (min/hr), where standard temperature for (g-mole/scm) is 20°C.

C_j = Concentration of compound j, on a dry basis, in ppmv as measured by Method 18, incorporated by reference at Section 218.112 of this Part, as indicated in Section 218.433(c) (3) of this Part.

M_j = Molecular weight of sample j, g/g-mole.

Q_s = Vent stream flow rate (scm) at a temperature of 20°C.

- 5) The total vent stream concentration (by volume) of compounds containing halogens (ppmv, by compound) shall be summed from the individual concentrations of compounds containing halogens which were measured by Method 18, incorporated by reference at Section 218.112 of this Part.
- 6) The net heating value of the vent stream shall be calculated using the following:

$$H_T = K_1 \sum_{j=1}^n C_j H_j (1 - B_{ws})$$

where:

H_T = Net heating value of the sample (MJ/scm), where the net enthalpy per mole of vent stream is based on combustion of 25°C and 760 mmHG, but the standard temperature for determining the volume corresponding to one mole is 25°C 20°C, as in the definition of Q_s (vent

stream flow rate).

- K_1 = Constant, 1.740×10^{-7} (ppmv)⁻¹ (g-mole/scm), (MJ/KCal), where standard temperature for (g-mole/scm) is 20°C.
- E_{ws} = Water vapor content of the vent stream, proportion by volume; except that if the vent stream passes through a final stream jet and is not condensed, it shall be assumed that $E_{ws} = 0.023$ in order to correct to 2.3 percent moisture.
- C_j = Concentration on a dry basis of compound j in ppmv, as measured for all organic compounds by Method 18, incorporated by reference at Section 218.112 of this Part, and measured for hydrogen and carbon monoxide by using ASTM D1946-77, incorporated by reference at Section 218.112 of this Part.
- H_j = Net heat of combustion of compound j, kCal/g-mole, based on combustion at 25°C and 760 mmHG. The heats of combustion of vent stream components shall be determined using ASTM D2382-83, incorporated by reference at Section 218.112 of this Part, if published values are not available or cannot be calculated.

- b) 1) The TRE index value of the vent shall be calculated using the following:

$$TRE = \frac{1}{E_{VOM}} [a + b (Q_s) + c (H_T) + d (E_{VOM})]$$

where:

TRE = TRE index value.

E_{VOM} = Hourly emission rate of VOM (kg/hr) as calculated in subsection (a) (4) of this Appendix.

Q_s = Vent stream flow rate scm/min at a standard temperature of 20°C.

H_T = Vent stream net heating value (MJ/scm), as calculated in subsection (a) (6) of this Appendix.

E_{VOM} = Hourly emission rate of VOM (minus methane and ethane), (kg/hr) as calculated in subsection (a) (4) of this Appendix.

a,b, c,d = Value of coefficients presented below are:

Type of Stream	Control Device Basis	Value of Coefficients			
		a	b	c	d
Nonhalogenated	Flare	2.129	0.183	-0.005	0.359
Thermal incinerator zero (0) Percent heat Recovery		3.075	0.021	-0.037	0.018
Thermal incinerator 70 Percent heat Recovery		3.803	0.032	-0.042	0.007
Halogenated	Thermal incinerator and scrubber	5.470	0.181	-0.040	0.004

- 2) Every owner or operator of a vent stream shall use the applicable coefficients identified for values a, b, c and d in subsection (b) (1) of this Appendix to calculate the TRE index value based on a flare, a thermal incinerator with zero percent heat recovery, and a thermal incinerator with 70 percent heat recovery, and shall select the lowest TRE index value.
 - 3) Every owner or operator of a reactor or distillation unit with a halogenated vent stream, determined as any stream with a total concentration of halogen atoms contained in organic compounds of 200 ppmv or greater, shall use the applicable coefficients identified for values a, b, c and d in subsection (b) (1) of this Appendix to calculate the TRE index value based on a thermal incinerator and scrubber.
- c) Every owner or operator of a source seeking to comply with Section 218.432(b) of this Part shall recalculate the flow rate and VOM concentration for each affected vent stream whenever process changes are made. Examples of process changes include, but are not limited to, changes in production capacity, feedstock type, or catalyst type, or

whenever there is replacement, removal, or addition of recovery equipment. The flow rate and VOM concentration shall be recalculated based on test data, or on best engineering estimates of the effects of the change to the recovery system.

- d) Whenever a process change, as defined in Section 218.435(c) of this Subpart, yields a TRE index value of 1.0 or less, the owner or operator shall notify and submit a report to the Agency according to the requirements specified in Section 218.435(c) of this Subpart, within 180 calendar days after the process change and shall conduct a performance test according to the methods and procedures required by Section 218.433 of this Part.
- e) For the purpose of demonstrating that a process vent stream has a VOM concentration below 500 ppmv, the following shall be used:
 - 1) The sampling site shall be selected as specified in Section 218.433(c)(1) of this Part.
 - 2) Method 18 or Method 25A of 40 CFR Part 60, Appendix A, incorporated by reference at Section 218.112 of this Part, shall be used to measure concentration; alternatively, any other method or data that has been validated according to the protocol in Method 301 of 40 CFR Part 63, Appendix A, incorporated by reference at Section 218.112 of this Part, may be used.
 - 3) Where Method 18 is used, the following procedures shall be used to calculate ppmv concentration:
 - i) The minimum sampling time for each run shall be 1 hour in which either an integrated sample or four grab samples shall be taken. If grab sampling is used, then the samples shall be taken at approximately equal intervals in time, such as 15 minute intervals during the run.
 - ii) The concentration of VOM shall be calculated using Method 18 according to Section 218.433(c)(4) of this Part.
 - 4) Where Method 25A is used, the following procedures shall be used to calculate ppmv VOM concentration:
 - A) Method 25A shall be used only if a single VOM is greater than 50 percent of total VOM, by volume, in the process vent stream.
 - B) The vent stream composition may be determined by

either process knowledge, test data collected using an appropriate Reference Method or a method of data collection validated according to the protocol in Method 301 of 40 CFR Part 63, Appendix A, incorporated by reference at Section 218.112 of this Part. Examples of information that constitute process knowledge include calculations based on material balances, process stoichiometry, or previous test results provided the results are still relevant to the current process vent stream conditions.

- C) The VOM used as the calibration gas for Method 25A shall be the single VOM present at greater than 50 percent of the total VOM by volume.
 - D) The span value for Method 25A shall be 50 ppmv.
 - E) Use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.
 - F) The concentration of VOM shall be corrected to 3 percent oxygen using the procedures and equation in Section 218.433(c)(3) of this Part.
- 5) The owner or operator shall demonstrate that the concentration of VOM, including methane and ethane, measured by Method 25A is below 250 ppmv to qualify for the low concentration exclusion in Section 218.431 of this Part.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

TITLE 35: ENVIRONMENTAL PROTECTION
SUBTITLE B: AIR POLLUTION
CHAPTER I: POLLUTION CONTROL BOARD
SUBCHAPTER c: EMISSIONS STANDARDS AND
LIMITATIONS FOR STATIONARY SOURCES

PART 219
ORGANIC MATERIAL EMISSION STANDARDS AND
LIMITATIONS FOR THE METRO EAST AREA

SUBPART A: GENERAL PROVISIONS

Section
219.100 Introduction
219.101 Savings Clause

- 219.102 Abbreviations and Conversion Factors
- 219.103 Applicability
- 219.104 Definitions
- 219.105 Test Methods and Procedures
- 219.106 Compliance Dates
- 219.107 Operation of Afterburners
- 219.108 Exemptions, Variations, and Alternative Means of Control or Compliance Determinations
- 219.109 Vapor Pressure of Volatile Organic Liquids
- 219.110 Vapor Pressure of Organic Material or Solvents
- 219.111 Vapor Pressure of Volatile Organic Material
- 219.112 Incorporations by Reference
- 219.113 Monitoring for Negligibly-Reactive Compounds

SUBPART B: ORGANIC EMISSIONS FROM STORAGE
AND LOADING OPERATIONS

- Section
- 219.119 Applicability for VOL
- 219.120 Control Requirements for Storage Containers of VOL
- 219.121 Storage Containers of VPL
- 219.122 Loading Operations
- 219.123 Petroleum Liquid Storage Tanks
- 219.124 External Floating Roofs
- 219.125 Compliance Dates
- 219.126 Compliance Plan (Repealed)
- 219.127 Testing VOL Operations
- 219.128 Monitoring VOL Operations
- 219.129 Recordkeeping and Reporting for VOL Operations

SUBPART C: ORGANIC EMISSIONS FROM
MISCELLANEOUS EQUIPMENT

- Section
- 219.141 Separation Operations
- 219.142 Pumps and Compressors
- 219.143 Vapor Blowdown
- 219.144 Safety Relief Valves

SUBPART E: SOLVENT CLEANING

- Section
- 219.181 Solvent Cleaning in General
- 219.182 Cold Cleaning
- 219.183 Open Top Vapor Degreasing
- 219.184 Conveyorized Degreasing
- 219.185 Compliance Schedule (Repealed)
- 219.186 Test Methods

SUBPART F: COATING OPERATIONS

Section

- 219.204 Emission Limitations
- 219.205 Daily-Weighted Average Limitations
- 219.206 Solids Basis Calculation
- 219.207 Alternative Emission Limitations
- 219.208 Exemptions From Emission Limitations
- 219.209 Exemption From General Rule on Use of Organic Material
- 219.210 Compliance Schedule
- 219.211 Recordkeeping and Reporting
- 219.212 Cross-Line Averaging to Establish Compliance for Coating Lines
- 219.213 Recordkeeping and Reporting for Cross-Line Averaging Participating Coating Lines
- 219.214 Changing Compliance Methods

SUBPART G: USE OF ORGANIC MATERIAL

Section

- 219.301 Use of Organic Material
- 219.302 Alternative Standard
- 219.303 Fuel Combustion Emission Units
- 219.304 Operations with Compliance Program

SUBPART H: PRINTING AND PUBLISHING

Section

- 219.401 Flexographic and Rotogravure Printing
- 219.402 Applicability
- 219.403 Compliance Schedule
- 219.404 Recordkeeping and Reporting
- 219.405 Lithographic Printing: Applicability
- 219.406 Provisions Applying to Heatset Web Offset Lithographic Printing Prior to March 15, 1996
- 219.407 Emission Limitations and Control Requirements for Lithographic Printing Lines On and After March 15, 1996
- 219.408 Compliance Schedule for Lithographic Printing on and After March 15, 1996
- 219.409 Testing for Lithographic Printing On and After March 15, 1996
- 219.410 Monitoring Requirements for Lithographic Printing
- 219.411 Recordkeeping and Reporting for Lithographic Printing

SUBPART Q: SYNTHETIC ORGANIC CHEMICAL AND POLYMER MANUFACTURING PLANT

Section

- 219.421 General Requirements
- 219.422 Inspection Program Plan for Leaks
- 219.423 Inspection Program for Leaks
- 219.424 Repairing Leaks
- 219.425 Recordkeeping for Leaks
- 219.426 Report for Leaks
- 219.427 Alternative Program for Leaks

219.428 Open-Ended Valves
219.429 Standards for Control Devices
219.430 Compliance Date (Repealed)
219.431 Applicability
219.432 Control Requirements
219.433 Performance and Testing Requirements
219.434 Monitoring Requirements
219.435 Recordkeeping and Reporting Requirements
219.436 Compliance Date

SUBPART R: PETROLEUM REFINING AND
RELATED INDUSTRIES; ASPHALT MATERIALS

Section

219.441 Petroleum Refinery Waste Gas Disposal
219.442 Vacuum Producing Systems
219.443 Wastewater (Oil/Water) Separator
219.444 Process Unit Turnarounds
219.445 Leaks: General Requirements
219.446 Monitoring Program Plan for Leaks
219.447 Monitoring Program for Leaks
219.448 Recordkeeping for Leaks
219.449 Reporting for Leaks
219.450 Alternative Program for Leaks
219.451 Sealing Device Requirements
219.452 Compliance Schedule for Leaks
219.453 Compliance Dates (Repealed)

SUBPART S: RUBBER AND MISCELLANEOUS
PLASTIC PRODUCTS

Section

219.461 Manufacture of Pneumatic Rubber Tires
219.462 Green Tire Spraying Operations
219.463 Alternative Emission Reduction Systems
219.464 Emission Testing
219.465 Compliance Dates (Repealed)
219.466 Compliance Plan (Repealed)

SUBPART T: PHARMACEUTICAL MANUFACTURING

Section

219.480 Applicability
219.481 Control of Reactors, Distillation Units, Crystallizers,
Centrifuges and Vacuum Dryers
219.482 Control of Air Dryers, Production Equipment Exhaust
Systems and Filters
219.483 Material Storage and Transfer
219.484 In-Process Tanks
219.485 Leaks
219.486 Other Emission Units
219.487 Testing

- 219.488 Monitoring for Air Pollution Control Equipment
- 219.489 Recordkeeping for Air Pollution Control Equipment

SUBPART V: BATCH OPERATIONS AND AIR OXIDATION PROCESSES

- Section
- 219.500 Applicability for Batch Operations
- 219.501 Control Requirements for Batch Operations
- 219.502 Determination of Uncontrolled Total Annual Mass Emissions and Actual Weighted Average Flow Rate Values for Batch Operations
- 219.503 Performance and Testing Requirements for Batch Operations
- 219.504 Monitoring Requirements for Batch Operations
- 219.505 Reporting and Recordkeeping for Batch Operations
- 219.506 Compliance Date
- 219.520 Emission Limitations for Air Oxidation Processes
- 219.521 Definitions (Repealed)
- 219.522 Savings Clause
- 219.523 Compliance
- 219.524 Determination of Applicability
- 219.525 Emission Limitations for Air Oxidation Processes (Renumbered)
- 219.526 Testing and Monitoring
- 219.527 Compliance Date (Repealed)

SUBPART W: AGRICULTURE

- Section
- 219.541 Pesticide Exception

SUBPART X: CONSTRUCTION

- Section
- 219.561 Architectural Coatings
- 219.562 Paving Operations
- 219.563 Cutback Asphalt

SUBPART Y: GASOLINE DISTRIBUTION

- Section
- 219.581 Bulk Gasoline Plants
- 219.582 Bulk Gasoline Terminals
- 219.583 Gasoline Dispensing Operations - Storage Tank Filling Operations
- 219.584 Gasoline Delivery Vessels
- 219.585 Gasoline Volatility Standards
- 219.586 Gasoline Dispensing Operations - Motor Vehicle Fueling Operations (Repealed)

SUBPART Z: DRY CLEANERS

Section
219.601 Perchloroethylene Dry Cleaners
219.602 Exemptions
219.603 Leaks
219.604 Compliance Dates (Repealed)
219.605 Compliance Plan (Repealed)
219.606 Exception to Compliance Plan (Repealed)
219.607 Standards for Petroleum Solvent Dry Cleaners
219.608 Operating Practices for Petroleum Solvent Dry Cleaners
219.609 Program for Inspection and Repair of Leaks
219.610 Testing and Monitoring
219.611 Exemption for Petroleum Solvent Dry Cleaners
219.612 Compliance Dates (Repealed)
219.613 Compliance Plan (Repealed)

SUBPART AA: PAINT AND INK MANUFACTURING

Section
219.620 Applicability
219.621 Exemption for Waterbase Material and Heatset-Offset Ink
219.622 Permit Conditions
219.624 Open-Top Mills, Tanks, Vats or Vessels
219.625 Grinding Mills
219.626 Storage Tanks
219.628 Leaks
219.630 Clean Up
219.636 Compliance Schedule
219.637 Recordkeeping and Reporting

SUBPART BB: POLYSTYRENE PLANTS

Section
219.640 Applicability
219.642 Emissions Limitation at Polystyrene Plants
219.644 Emissions Testing

SUBPART FF: BAKERY OVENS (Repealed)

Section
219.720 Applicability (Repealed)
219.722 Control Requirements (Repealed)
219.726 Testing (Repealed)
219.727 Monitoring (Repealed)
219.728 Recordkeeping and Reporting (Repealed)
219.729 Compliance Date (Repealed)
219.730 Certification (Repealed)

SUBPART GG: MARINE TERMINALS

Section
219.760 Applicability
219.762 Control Requirements

219.764 Compliance Certification
219.766 Leaks
219.768 Testing and Monitoring
219.770 Recordkeeping and Reporting

SUBPART HH: MOTOR VEHICLE REFINISHING

Section
219.780 Emission Limitations
219.782 Alternative Control Requirements
219.784 Equipment Specifications
219.786 Surface Preparation Materials
219.787 Work Practices
219.788 Testing
219.789 Monitoring and Recordkeeping for Control Devices
219.790 General Recordkeeping and Reporting
219.791 Compliance Date
219.792 Registration
219.875 Applicability of Subpart BB (Renumbered)
219.877 Emissions Limitation at Polystyrene Plants (Renumbered)
219.879 Compliance Date (Repealed)
219.881 Compliance Plan (Repealed)
219.883 Special Requirements for Compliance Plan (Repealed)
219.886 Emissions Testing (Renumbered)

SUBPART PP: MISCELLANEOUS FABRICATED
PRODUCT MANUFACTURING PROCESSES

Section
219.920 Applicability
219.923 Permit Conditions
219.926 Control Requirements
219.927 Compliance Schedule
219.928 Testing

SUBPART QQ: MISCELLANEOUS FORMULATION
MANUFACTURING PROCESSES

Section
219.940 Applicability
219.943 Permit Conditions
219.946 Control Requirements
219.947 Compliance Schedule
219.948 Testing

SUBPART RR: MISCELLANEOUS ORGANIC
CHEMICAL MANUFACTURING PROCESSES

Section
219.960 Applicability
219.963 Permit Conditions
219.966 Control Requirements

219.967 Compliance Schedule
219.968 Testing

SUBPART TT: OTHER EMISSION UNITS

Section
219.980 Applicability
219.983 Permit Conditions
219.986 Control Requirements
219.987 Compliance Schedule
219.988 Testing

SUBPART UU: RECORDKEEPING AND REPORTING

Section
219.990 Exempt Emission Units
219.991 Subject Emission Units

Section 219.Appendix A: List of Chemicals Defining Synthetic Organic Chemical and Polymer Manufacturing
Section 219.Appendix B: VOM Measurement Techniques for Capture Efficiency
Section 219.Appendix C: Reference Methods And Procedures
Section 219.Appendix D: Coefficients for the Total Resource Effectiveness Index (TRE) Equation
Section 219.Appendix E: List of Affected Marine Terminals
Section 219.Appendix G: TRE Index Measurements for SOCOMI Reactors and Distillation Units
Section 219.Appendix H: Baseline VOM Content Limitations for Subpart F, Section 219.212 Cross-Line Averaging

AUTHORITY: Implementing Section 10 and authorized by Section 28.5 of the Environmental Protection Act [415 ILCS 5/10 and 28.5].

SOURCE: Adopted at R91-8 at 15 Ill. Reg. 12491, effective August 16, 1991; amended in ~~R91-24~~ at 16 Ill. Reg. 13597, effective August 24, 1992; amended in R91-30 at 16 Ill. Reg. 13883, effective August 24, 1992; emergency amendment in R93-12 at 17 Ill. Reg. 8295, effective May 24, 1993, for a maximum of 150 days, amended in R93-9 at 17 Ill. Reg. 16918, effective September 27, 1993 and October 21, 1993; amended in R93-28 at 18 Ill. Reg. 4242, effective March 3, 1994; amended in R94-12 at 18 Ill. Reg. 14987, effective September 21, 1994; amended in R94-15 at 18 Ill. Reg. 16415, effective October 25, 1994; amended in R94-16 at 18 Ill. Reg. 16980, effective November 15, 1994; emergency amendment in R95-10 at 19 Ill. Reg. 3059, effective February 28, 1995, for a maximum of 150 days; amended in R94-21, R94-31 and R94-32 at 19 Ill. Reg. 6958, effective May 9, 1995; amended in R94-33 at 19 Ill. Reg. 7385, effective May 22, 1995; ~~amended in R96-2 at _____~~

Ill. Reg. _____, effective _____,
amended in R96____ at _____ Ill. Reg. _____, effective _____
_____.

BOARD NOTE: This Part implements the Illinois Environmental Protection Act as of July 1, 1994.

SUBPART A: GENERAL PROVISIONS

Section 219.108 Exemptions, Variations, and Alternative Means of Control or Compliance Determinations

Notwithstanding the provisions of any other Sections of this Part, :

- a) ~~a~~Any exemptions, variations or alternatives to the control requirements, emission limitations, or test methods set forth in this Part shall be effective only when approved by the Agency and approved by the USEPA as a SIP revision.
- b) Any equivalent alternative control plans, equivalent device, or other equivalent alternative practice authorized by the Agency where this Part provides for such alternative or equivalent practice or equivalent variations or alterations to test methods approved by the Agency shall be effective only when included in a federally enforceable permit or approved as a SIP revision.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

Section 219.110 Vapor Pressure of Organic Material or Solvent

- a) If the organic material or solvent consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 219.112 of this Part) or the vapor pressure may be obtained from a publication such as: Boublik, T., V. Fried and E. Hala, "The Vapor Pressure of Pure Substances," Elsevier Scientific Publishing Co., New York (1973); Perry's Chemical Engineer's Handbook, McGraw-Hill Book Company (1984); CRC Handbook of Chemistry and Physics, Chemical Rubber Publishing Company (1986-87); and Lange's Handbook of Chemistry, John A. Dean, editor, McGraw-Hill Book Company (1985).
- b) If the organic material or solvent is in a mixture made up of both organic material compounds and compounds which are not organic material, the vapor pressure shall be determined by the following equation:

$$P_{\text{om}} = \frac{\sum_{i=1}^n P_i X_i}{\sum_{i=1}^n X_i}$$

where:

P_{om} = Total vapor pressure of the portion of the mixture which is composed of organic material;

n = Number of organic material components in the mixture;

i = Subscript denoting an individual component;

P_i = Vapor pressure of an organic material component determined in accordance with subsection (a) of this Section;

X_i = Mole fraction of the organic material component of the total organic mixture.

- c) If the organic material or solvent is in a mixture made up of only organic material compounds, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 219.112 of this Part) or by the above equation.

(Source: Amended at ____ Ill. Reg. _____, effective ____
_____)

Section 219.111 Vapor Pressure of Volatile Organic Material

- a) If the VOM consists of only a single compound, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 219.112 of this Part) or the vapor pressure may be obtained from a publication such as: Boublik, T., V. Fried and E. Hala, "The Vapor Pressure of Pure Substances," Elsevier Scientific Publishing Co., New York (1973); Perry's Chemical Engineer's Handbook, McGraw-Hill Book Company (1984); CRC Handbook of Chemistry and Physics, Chemical Rubber Publishing Company (1986-87); and Lange's Handbook of Chemistry, John A. Dean, editor, McGraw-Hill Book Company (1985).
- b) If the VOM is in a mixture made up of both VOM compounds and compounds which are not VOM, the vapor

pressure shall be determined by the following equation:

$$P_{\text{vom}} = \frac{\sum_{i=1}^n P_i X_i}{\sum_{i=1}^n X_i}$$

where:

P_{vom} = Total vapor pressure of the portion of the mixture which is composed of VOM;

n = Number of VOM components in the mixture;

i = Subscript denoting an individual component;

P_i = Vapor pressure of a VOM component determined in accordance with subsection (a) of this Section;

X_i = Mole fraction of the VOM component of the total organic mixture.

- c) If the VOM is in a mixture made up of only VOM compounds, the vapor pressure shall be determined by ASTM Method D2879-86 (incorporated by reference in Section 219.112 of this Part) or by the above equation.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

SUBPART F: COATING OPERATIONS

Section 219.208 Exemptions From Emission Limitations

- a) Exemptions for all coating categories except wood furniture coating. The limitations of this Subpart shall not apply to coating lines within a source, that otherwise would be subject to the same subsection of Section 219.204 (because they belong to the same coating category, e.g. can coating), provided that combined actual emissions of VOM from all lines at the source subject to that subsection never exceed 6.8 kg/day (15 lbs/day) before the application of capture systems and control devices. (For example, can coating lines within a source would not be subject to the limitations of Section 219.204(b) of this Subpart if the combined actual emissions of VOM from the can coating lines never exceed 6.8 kg/day (15 lbs/day))

before the application of capture systems and control devices.) Volatile organic material emissions from heavy off-highway vehicle products coating lines must be combined with VOM emissions from miscellaneous metal parts and products coating lines to determine applicability. Any owner or operator of a coating source shall comply with the applicable coating analysis test methods and procedures specified in Section 219.105(a) of this Part and the recordkeeping and reporting requirements specified in Section 219.211(a) of this Subpart if total VOM emissions from the subject coating lines are always less than or equal to 6.8 kg/day (15 lbs/day) before the application of capture systems and control devices and, therefore, are not subject to the limitations of Section 219.204 of this Subpart. Once a category of coating lines at a source is subject to the limitations in Section 219.204 of this Subpart the coating lines are always subject to the limitations in Section 219.204 of this Subpart.

b) Applicability for wood furniture coating

- 1) The limitations of this Subpart shall apply to a source's wood furniture coating lines if the source contains process emission units, not regulated by Subparts B, E, F (excluding Section 219.204(l) of this Subpart), H (excluding Section 219.405 of this Part), Q, R, S, T (excluding Section 219.486 of this Part), V, X, Y, Z or BB of this Part, which as a group both:
 - A) Have a maximum theoretical emissions of 91 Mg (100 tons) or more per calendar year of VOM if no air pollution control equipment were used; and
 - B) Are not limited to less than 91 Mg (100 tons) of VOM per calendar year if no air pollution control equipment were used, through production or capacity limitations contained in a federally enforceable permit or SIP revision.
- 2) The limitations of this Subpart shall apply to a source's wood furniture coating lines, on and after March 15, 1996, if the source contains process emission units, which as a group have a potential to emit 22.7 Mg (25 tons) or more of VOM per calendar year and have not limited emissions to less than 22.7 Mg (25 tons) of VOM per calendar year through production or capacity limitations contained in a federally enforceable operating

permit or SIP revision, and which:

- A) Are not regulated by Subparts B, E, F (excluding Section 219.204(1) of this Subpart), H, Q, R, S, T (excluding Section 219.486 of this Part), V, X, Y, Z or BB of this Part; and
 - B) Are not included in any of the following categories: synthetic organic chemical manufacturing industry (SOCMI) distillation, SOCMI reactors, plastic parts coating (business machines), plastic parts coating (other), offset lithography, industrial wastewater, autobody refinishing, SOCMI batch processing, volatile organic liquid storage tanks and clean-up solvents operations.
- 3) If a source ceases to fulfill the criteria of subsection (b) (1) or (b) (2) of this Section, the limitations of Section 219.204(1) of this Subpart shall continue to apply to any wood furniture coating line which was ever subject to the limitations of Section 219.204(1) of this Subpart.
 - 4) For the purposes of subsection (b) of this Section, an emission unit shall be considered to be regulated by a Subpart if it is subject to the limitations of that Subpart. An emission unit is not considered regulated by a Subpart if it is not subject to the limits of that Subpart, e.g., the emission unit is covered by an exemption in the Subpart or the applicability criteria of the Subpart are not met.
 - 5) Any owner or operator of a wood furniture coating line to which the limitations of this Subpart are not applicable due to the criteria in subsection (b) of this Section shall, upon request by the Agency or the USEPA, submit records to the Agency and the USEPA within 30 calendar days from the date of the request that document that the coating line is exempt from the limitations of this Subpart.
- c) On and after March 15, 1996, the limitations of this Subpart shall not apply to touch-up and repair coatings used by a coating source described by subsections 219.204(b), (d), (f), (g), (i), (j), (m) and (n) of this Subpart; provided that the source-wide volume of such coatings used does not exceed 0.95 l (1 quart) per eight-hour period or exceed 209 l/yr (55 gal/yr) for

any rolling twelve month period. Recordkeeping and reporting for touch-up and repair coatings shall be consistent with Section 219.211(b) (4) of this Subpart subsection (d) of this Section.

- d) On and after March 15, 1996, the owner or operator of a coating line or a group of coating lines using touch-up and repair coatings that are exempted from the limitations of Section 219.204(b), (d), (f), (g), (i), (j), (m) and (n) of this Subpart because of the provisions of Section 219.208(c) of this Subpart shall:
- 1) Collect and record the name, identification number, and volume used of each touch-up and repair coating, as applied on each coating line, per eight-hour period and per month;
 - 2) Perform calculations on a daily basis, and maintain at the source records of such calculations of the combined volume of touch-up and repair coatings used source-wide for each eight-hour period;
 - 3) Perform calculations on a monthly basis, and maintain at the source records of such calculations of the combined volume of touch-up and repair coatings used source-wide for the month and the rolling twelve month period;
 - 4) Prepare and maintain at the source an annual summary of the information required to be compiled pursuant to subsections ~~(e) (4) (A) and (e) (4) (B)~~ (d) (1) and (d) (2) of this Section on or before January 31 of the following year;
 - 5) Maintain at the source for a minimum period of three years all records required to be kept under this subsection and make such records available to the Agency upon request;
 - 6) Notify the Agency in writing if the use of touch-up and repair coatings at the source ever exceeds a volume of 0.95 l (1 quart) per eight-hour period or exceeds 209 l/yr (55 gal/yr) for any rolling twelve month period within 30 days after any such exceedance. Such notification shall include a copy of any records of such exceedance; and
 - 7) "Touch-up and repair coatings" means, for purposes of 35 Ill. Adm. Code 219.208, any coating used to cover minor scratches and nicks that occur during manufacturing and assembly processes.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

SUBPART Q: SYNTHETIC ORGANIC CHEMICAL
AND POLYMER MANUFACTURING PLANT

Section 219.431 Applicability

- a) The provisions of Sections 219.431 through 219.436 of this Subpart shall apply to every owner or operator of any chemical manufacturing process unit that manufactures, as a primary product, one or more of the chemicals listed in Appendix A of this Part and that chemical manufacturing process unit causes or allows any reactor or distillation unit, either individually or in tandem, to discharge one or more process vent streams either directly to the atmosphere or to a recovery system.
- b) Notwithstanding subsection (a) of this Section, the control requirements set forth within Section 219.432 of this Subpart shall not apply to the following:
 - 1) Any process vent stream with a total resource effectiveness (TRE) index value greater than 1.0. However, such process vent stream remains subject to the performance testing requirements contained in Section 219.433 of this Subpart and the reporting and recordkeeping requirements contained in Section 219.435 of this Subpart;
 - 2) Any reactor or distillation unit that is designed and operated as a batch operation;
 - 3) Any reactor or distillation unit that is part of a polymer manufacturing operation;
 - 4) Any reactor or distillation unit that is part of the chemical manufacturing process unit with a total design capacity of less than 1 gigagram (1,100 tons) per year for all chemicals produced, as a primary product, within that process unit. However, such operations remain subject to the reporting and recordkeeping requirements contained in Section 219.435(d) of this Subpart; ~~ex~~
 - 5) Any vent stream with a flow rate less than 0.0085 scm/min or a total VOM concentration of less than 500 ppmv, less methane and ethane, as measured by Method 18, or a concentration of VOM of less than 250 ppmv as measured by Method 25A. However, such

operations remain subject to the performance testing requirement listed in Section 219.433 of this Subpart, as well as the reporting and recordkeeping requirements contained in Section 219.435 of this Subpart-; or

- 6) Any reactor or distillation unit included within an Early Reduction Program, as specified in 40 CFR 63, and published in 57 Fed. Reg. 61970 (~~October 22, 1993~~) (December 29, 1992), evidenced by a timely enforceable commitment approved by USEPA.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

Section 219.434 Monitoring Requirements

- a) The owner or operator of a source subject to the control requirements in Section 219.432 of this Subpart that uses an incinerator to comply with the VOM emission limitation specified in Section 219.432(a)(1) shall install, calibrate, maintain, and operate, according to manufacturer's specifications, a temperature monitoring device equipped with a continuous recorder and having an accuracy of ± 1 percent of the temperature measured expressed in degrees Celsius, or $\pm 0.5^{\circ}\text{C}$, whichever is greater.
 - 1) Where an incinerator other than a catalytic incinerator is used, a temperature monitoring device shall be installed in the firebox.
 - 2) Where a catalytic incinerator is used, temperature monitoring devices shall be installed in the gas stream immediately before and after the catalyst bed.
- b) The owner or operator of a source that uses a flare to comply with Section 219.432(a)(2) of this Subpart shall install, calibrate, maintain and operate, according to manufacturer's specifications, a heat-sensing device, such as an ultraviolet beam sensor or thermocouple, at the pilot light to indicate continuous presence of a flame.
- c) The owner or operator of a source that uses a boiler or process heater with a design heat input capacity less than 44 megawatts to comply with Section 219.432(a)(1) of this Subpart shall install, calibrate, maintain and operate, according to the manufacturer's specifications, a temperature monitoring device in the firebox. The monitoring device shall be equipped with a continuous recorder with an accuracy of ± 1 percent of the temperature being measured expressed in degrees Celsius or $\pm 0.5^{\circ}\text{C}$, whichever is greater. Any boiler or process heater in which

all vent streams are introduced with primary fuel is exempt from this requirement.

- d) The owner or operator of a process vent with a TRE index value of 4.0 or less that uses one or more product recovery devices shall install either an organic monitoring device equipped with a continuous recorder or the monitoring equipment specified in subsections (d) (1), (d) (2), (d) (3) or (d) (4) of this Section, depending on the type of recovery device used. All monitoring equipment shall be installed, calibrated and maintained according to the manufacturer's specifications.
- 1) Where an absorber is the final recovery device in the recovery system, a scrubbing liquid temperature monitoring device and a specific gravity monitoring device, each equipped with a continuous recorder, shall be used.
 - 2) Where a condenser is the final recovery device in the recovery system, a condenser exit (product side) temperature monitoring device equipped with a continuous recorder and having an accuracy of ± 1 percent of the temperature being monitored expressed in degrees Celsius or $\pm 0.5^{\circ}\text{C}$, whichever is greater.
 - 3) Where a carbon adsorber is the final recovery device in the recovery system, an integrating regeneration ~~stream~~ steam flow monitoring device having an accuracy of ± 10 percent, capable of recording the total regeneration ~~stream~~ steam mass flow for each regeneration cycle; and a carbon bed temperature monitoring device having an accuracy of ± 1 percent of the temperature being monitored expressed in degrees Celsius of $\pm 0.5^{\circ}\text{C}$, capable of recording the carbon bed temperature after each regeneration and within 15 minutes of completing any cooling cycle.
 - 4) Where a scrubber is used with an incinerator, boiler, or, in the case of halogenated vent streams, a process heater, the following monitoring equipment is required for the scrubber:
 - A) A pH monitoring device equipped with a continuous recorder to monitor the pH of the scrubber effluent; and
 - B) Flow meters equipped with a continuous recorder at the scrubber influent for liquid flow and the scrubber inlet for gas stream flow.
- e) The owner or operator of a process vent using a vent system

that contains bypass lines capable of diverting a vent stream away from the control device associated with a process vent shall comply with either (e) (1) or (e) (2) of this Section. Equipment needed for safety purposes, including, but not limited to, pressure relief devices, are not subject to this subsection.

- 1) The owner or operator shall install, calibrate, maintain and operate a flow indicator that provides a record of vent stream flow at least once every 15 minutes. The flow indicator shall be installed at the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.
 - 2) The owner or operator shall secure the bypass line valve in the closed position with a car-seal or a lock-and-key type configuration. A visual inspection of the seal or closure mechanism shall be performed at least once every month to ensure that the valve is maintained in the closed position and the vent stream is not diverted through the bypass line.
- f) The owner or operator of a process vent may monitor by an equivalent alternative means or parameters other than those listed in subsections (a) through (d) of this Section. Any equivalent alternative shall be approved by the Agency and USEPA, and contained in the source's operating permit as federally enforceable permit conditions.

(Source: Amended at ____ Ill. Reg. _____, effective ____
_____)

Section 219.435 Recordkeeping and Reporting Requirements

- a) Every owner or operator of a reactor or distillation unit with a TRE index value of 4.0 or less shall keep records, for a minimum of 3 years, of the following parameters measured during a performance test or TRE determination required under Section 219.433 of this Subpart, and required to be monitored under Section 219.434 of this Subpart.
 - 1) Every owner or operator of a source that seeks to demonstrate compliance with Section 219.432(a) (1) of this Subpart through the use of either a thermal or catalytic incinerator shall maintain records of the following:
 - A) The average firebox temperature of the incinerator (or the average temperature upstream and downstream of the catalyst bed for a catalytic incinerator), measured at least every 15 minutes and averaged over the same time period of the

performance testing; and

- B) The percent reduction of VOM determined as specified in Section 219.433(c) of this Subpart achieved by the incinerator, or the concentration of VOM (ppmv, by compound) determined as specified in Section 219.433(c) of this Subpart at the outlet of the control device, on a dry basis, corrected to 3 percent oxygen.
- 2) Every owner or operator of a source that seeks to demonstrate compliance with Section 219.432(a)(1) of this Subpart through the use of a boiler or process heater shall maintain the records described below. Any boiler or process heater in which all vent streams are introduced with primary fuel are exempt from these requirements.
- A) A description of the location at which the vent stream is introduced into the boiler or process heater; and
 - B) The average combustion temperature of the boiler or process heater with a design heat input capacity of less than 44 megawatt measured at least every 15 minutes and averaged over the same time period of the performance testing.
- 3) Every owner or operator of a source that seeks to demonstrate compliance with Section 219.432(a)(2) of this Subpart through use of a smokeless flare, or flare design (i.e., steam-assisted, air-assisted, or nonassisted), shall maintain records of all visible emission readings, heat content determinations, flow rate measurements, and exit velocity determinations made during the performance test, continuous records of the flare pilot flame monitoring, and records of all periods of operations during which the pilot flame is absent.
- 4) Every owner or operator of a source that seeks to demonstrate compliance with Section 219.432(b) of this Subpart shall maintain records of the following:
- A) Where an absorber is the final recovery device in the recovery system, the exit specific gravity (or alternative parameter) which is a measure of the degree of absorbing liquid saturation, if approved by the Agency and USEPA, and average exit temperature of the absorbing liquid measured at least every 15 minutes and averaged over the same time period as the performance testing (both

measured while the vent stream is normally routed and constituted);

- B) Where a condenser is the final recovery device in the recovery system, the average exit (product side) temperature measured at least every 15 minutes and averaged over the same time period as the performance testing while the vent stream is normally routed and constituted;
 - C) Where a carbon absorber is the final recovery device in the recovery system, the total stream steam mass or volumetric flow measured at least every 15 minutes and averaged over the same time period as the performance testing (full carbon bed cycle), the temperature of the carbon bed after regeneration (and within 15 minutes of completion of any cooling cycle(s)), and duration of the carbon bed steaming cycle (all measured while the vent stream is normally routed and constituted);
 - D) As an alternative to subsection (a) (4) (A), (a) (4) (B) or (a) (4) (C) of this Section, the concentration level or reading indicated by the organic monitoring device at the outlet of the absorber, condenser, or carbon absorber, measured at least every 15 minutes and averaged over the same time period as the performance testing (measured while the vent stream is normally routed and constituted); or
 - E) All measurements and calculations performed to determine the flow rate, VOM concentration, heating value, and TRE index value of the vent stream.
- b) Every owner or operator of a reactor or distillation unit with a TRE index value of less than 4.0 shall be subject to the exceedance reporting requirements of the draft Enhanced Monitoring Guidelines as published at 58 Fed. Reg. 54648 (October 22, 1993).
 - c) Every owner or operator of a source seeking to comply with Section 219.432(b) of this Subpart shall maintain records of the following:
 - 1) Any changes in production capacity, feedstock type, catalyst type, or of any replacement, removal, or addition of recovery equipment or reactors and distillation units; and
 - 2) Any recalculation of the flow rate, VOM concentration,

or TRE index value calculated according to subsection Section (c) of Appendix G of this Part.

- d) Every owner or operator of a source claiming a design capacity of less than 1 gigagram (1,100 tons) per year, as contained in Section 219.431(b) of this Subpart, shall maintain records of the design capacity or any changes in equipment or operations that may affect the design capacity.
- e) Every owner or operator of a source claiming a vent stream flow rate or vent stream concentration exemption level, as contained in Section 219.431(b) (5) of this Subpart, shall maintain records to indicate that the stream flow rate is less than 0.0085 scm/min or the vent stream concentration is less than 500 ppmv.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

SUBPART FF: BAKERY OVENS (Repealed)

Section 219.720 Applicability (Repealed)

- ~~a) The provisions of this Subpart shall apply to every owner or operator of a source which operates a bakery oven, as defined at 35 Ill. Adm. Code 211.680, unless the source bakes products only for on-site human consumption or on-site retail sale.~~
- ~~b) Notwithstanding subsection (a) of this Section, a source is required to comply with the control requirements of this Subpart only if the source has the potential to emit 22.7 Mg (25 tons) or more of VOM per year, in the aggregate, from all emission units at the source, excluding:~~
 - ~~1) Emission units regulated by Subparts B, E, F, H, Q, R, S, T (excluding Section 219.486 of this Part), V, X, Y, Z or BB of this Part; and~~
 - ~~2) Emission units that are included in any of the following categories: synthetic organic chemical manufacturing industry (SOCMI) distillation, SOCMI reactors, wood furniture coating, plastic parts coating (business machines), plastic parts coating (other), offset lithography, industrial wastewater, autobody refinishing, SOCMI batch processing, volatile organic liquid storage tanks and clean up solvents operations.~~
- ~~c) Every owner or operator of a source which has limited~~

~~its potential to emit below 22.7 Mg (25 tons) of VOM per year, as specified in subsection (b) of this Section, through federally enforceable permit conditions is not required to comply with this Subpart.~~

- ~~d) Every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria in subsection (b) of this Section remains subject to the recordkeeping and reporting requirements of Section 219.728(b) of this Subpart and the certification requirements in Section 219.730(d) of this Subpart.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.722 Control Requirements (Repealed)

- ~~a) Every owner or operator of a source subject to the control requirements of this Subpart shall comply with the requirements of subsection (a) (1) or (a) (2) of this Section for each bakery oven with a rated heat input capacity of at least 2 mmBtu/hr or at least 586 kW:~~
- ~~1) Operate emissions capture and control equipment which achieves an overall reduction in uncontrolled VOM emissions of at least 81 percent from each such bakery oven; or~~
 - ~~2) Provide an equivalent alternative control plan for such bakery ovens at the source which has been approved by the Agency and USEPA through federally enforceable permit conditions or as a SIP revision.~~
- ~~b) An owner or operator of a source subject to the control requirements of this Subpart may elect to exempt from the control requirements in subsections (a) (1) or (a) (2) and (c) (1) or (c) (2) of this Section any bakery oven with actual VOM emissions less than or equal to 15 TPY; provided that the total actual VOM emissions from all such exempt bakery ovens never exceed 25 TPY.~~
- ~~c) Notwithstanding the requirements in subsection (a) of this Section, until March 15, 1998, only, a source may elect to comply with the control requirements in subsection (c) (1) or (c) (2) of this Section, rather than the control requirements in subsection (a) (1) or (a) (2) of this Section, if all emission units at the source, in the aggregate, excluding emission units~~

~~regulated by Subparts B, E, F, H (excluding Section 219.405 of this Subpart), Q, R, S, T (excluding Section 219.486 of this Subpart), V, X, Y, Z or BB of this Subpart, have maximum theoretical emissions of less than 90.7 Mg (100 tons) of VOM per year or are limited to less than 90.7 Mg (100 tons) of VOM emissions per calendar year in the absence of air pollution control equipment through production or capacity limitations contained in federally enforceable permit conditions or in a SIP revision.~~

- ~~1) Operate emissions capture and control equipment which achieves an overall reduction in uncontrolled VOM emissions of at least 60 percent from each bakery oven with a rated heat input capacity of at least 2 mmbtu/hr or at least 586 KW, or~~
- ~~2) Provide an equivalent alternative control plan for such bakery ovens at the source which has been approved by the Agency and USEPA through federally enforceable permit conditions or as a SIP revision.~~

~~d) Any bakery oven that becomes subject to the requirements of this Subpart at any time shall remain subject to the requirements of this Subpart at all times thereafter.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.726 Testing (Repealed)

- ~~a) Upon request by the Agency, the owner or operator of a bakery oven shall, at its own expense, conduct such tests in accordance with the applicable test methods and procedures specified in Section 219.105(f) of this Part to demonstrate compliance with the control requirements of this Subpart and shall:~~
 - ~~1) Notify the Agency 30 days prior to conducting such tests, and~~
 - ~~2) Submit all test results to the Agency within 30 days of conducting such tests.~~
- ~~b) Nothing in this Section shall limit the authority of USEPA pursuant to the Clean Air Act (CAA) to require testing, or shall affect the authority of USEPA under Section 114 of the CAA (42 U.S.C. 7414 (1990)).~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.727 Monitoring (Repealed)

- ~~a) Every owner or operator of a bakery oven subject to the control requirements of this Subpart shall install and operate at all times a device to continuously monitor the following parameters for each type of control device as follows:~~
- ~~1) For catalytic oxidizers, the inlet and outlet temperatures of the oxidizer;~~
 - ~~2) For regenerative oxidizers, the temperature in the combustion chamber; or~~
 - ~~3) For thermal incinerators, the temperature in the combustion chamber.~~
- ~~b) The owner or operator may monitor with an alternative method or monitor other parameters if approved by the Agency and USEPA through federally enforceable permit conditions or as a SIP revision.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.728 Recordkeeping and Reporting (Repealed)

- ~~a) Every owner or operator of a bakery oven shall maintain the following records for the most recent consecutive 3 year period for all bakery ovens subject to the control requirements of this Subpart. Such records shall be made available to the Agency immediately upon request.~~
- ~~1) Parameters for control devices as monitored pursuant to Section 219.727 of this Subpart;~~
 - ~~2) Hrs/day of operation of each bakery oven;~~
 - ~~3) Factors necessary to calculate VOM emissions for all bakery ovens including, but not limited to, type of dough used for each yeast leavened baked product, initial yeast percentage for each product, total fermentation time for each product, any additional percentage of yeast added, and the fermentation time of any additional yeast;~~

- 4) ~~Calculated daily VOM emissions of each bakery oven expressed as lbs/day;~~
 - 5) ~~Total amount of each type of yeast leavened bread product produced by each bakery oven expressed as lbs/day.~~
- b) ~~Every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria in Section 219.720(b) of this Subpart shall maintain records necessary to demonstrate that its potential to emit is less than 22.7 Mg (25 tons) of VOM per year, as specified in Section 219.720(b). Such records shall be maintained for the most recent consecutive 3 year period and shall be made available to the Agency immediately upon request.~~
- e) ~~Every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria specified in Section 219.722(b) of this Subpart shall:~~
- 1) ~~Maintain records necessary to demonstrate that the actual VOM emissions from exempt bakery ovens are less than or equal to 15 TPY for each bakery oven and less than or equal to 25 TPY from all exempt bakery ovens combined. Such records shall be maintained for the most recent consecutive 3 year period and shall be made available to the Agency immediately upon request; and~~
 - 2) ~~Notify the Agency in writing if the actual VOM emissions from an exempt bakery oven ever exceed 15 TPY or the actual VOM emissions from a combination of exempt bakery ovens ever exceed 25 TPY, within 30 days after the exceedance occurs. Such notice shall include a copy of all records of the exceedance.~~
- d) ~~Every owner or operator of a bakery oven which is controlling emissions as provided in Section 219.722(c) of this Subpart until March 15, 1998, shall maintain records necessary to demonstrate that its maximum theoretical emissions as specified in Section 219.722(c) are less than 90.7 Mg (100 tons) of VOM per year. Such records shall be maintained for the most recent consecutive 3 year period and shall be made available to the Agency immediately upon request.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.729 Compliance Date (Repealed)

~~On and after March 15, 1996, upon initial startup or upon modification, every owner or operator of a source subject to this Subpart shall comply with the requirements of this Subpart.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.730 Certification (Repealed)

- ~~a) Every owner or operator of a source subject to the control requirements of this Subpart shall certify compliance with this Subpart on or before a date consistent with Section 219.729 of this Subpart.~~
- ~~b) If an owner or operator of a bakery oven subject to the control requirements of this Subpart changes the method of compliance, the owner or operator shall certify compliance with the requirements of this Subpart for the alternative method upon changing the method of compliance.~~
- ~~c) All certifications of compliance with this Subpart shall include the results of all tests and the calculations performed to demonstrate that each oven at the source is in compliance with, or is exempt from, the control requirements of this Subpart. The certification shall include the following:
 - ~~1) The name and identification number of each oven and any associated capture and control device;~~
 - ~~2) The maximum rated heat input of each oven;~~
 - ~~3) A classification of each oven as either a "bakery oven" as defined in 35 Ill. Admin. Code 211.680 or an oven used exclusively to bake non yeast-leavened products;~~
 - ~~4) The capture and control efficiency of each bakery oven control device;~~
 - ~~5) Test reports, calculations, and other data necessary to demonstrate that the capture and control efficiency of each bakery oven control device achieves an overall reduction in uncontrolled VOC emissions of at least 81 percent;~~~~

and

- ~~6) The date each bakery oven control device was installed and operating.~~
- ~~d) On or before March 15, 1996, or upon initial startup, every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria in Section 219.720(b) of this Subpart shall certify that its potential to emit is less than 22.7 Mg (25 tons) of VOM per year, as specified in Section 219.720(b).~~
- ~~e) On or before March 15, 1996, or upon initial startup, every owner or operator of a bakery oven which is exempt from the control requirements of this Subpart because of the criteria specified in Section 219.722(b) of this Subpart shall certify that actual VOM emissions from any individual exempt bakery oven never exceed 15 TPY and that VOM emissions from all exempt bakery ovens, in the aggregate, never exceed 25 TPY.~~
- ~~f) On or before March 15, 1996, or upon initial startup if prior to March 15, 1998, every owner or operator of a bakery oven which is controlling emissions as provided by Section 219.722(c) of this Subpart, shall certify that its maximum theoretical emissions as specified in Section 219.722(c) are less than 90.7 Mg (100 tons) of VOM per year.~~

(Source: Repealed at _____ Ill. Reg. _____, effective _____)

Section 219.Appendix G TRE Index Measurements for SOGMI Reactors and Distillation Units

For purposes of Subpart Q, Sections 219.431 through 219.435, the following apply:

- a) The following test methods shall be used to determine compliance with the total resource effectiveness ("TRE") index value:
- 1) Method 1 or 1A, incorporated by reference at Section 219.112 of this Part, as appropriate, for selection of the sampling site.
 - A) The sampling site for the vent stream molar composition determination and flow rate prescribed in subsections (a) (2) and (a) (3) of this Appendix

shall be, except for the situations outlined in subsection (a) (1) (B), after the final recovery device, if a recovery system is present, prior to the inlet of any control device, and prior to any post-reactor or post-distillation unit introduction of halogenated compounds into the vent stream. No traverse site selection method is needed for vents smaller than 10 cm in diameter.

- B) If any gas stream other than the reactor or distillation unit vent stream is normally conducted through the final recovery device:
- i) The sampling site for vent stream flow rate and molar composition shall be prior to the final recovery device and prior to the point at which any nonreactor or nondistillation unit vent stream or stream from a nonaffected reactor or distillation unit is introduced. Method 18 incorporated by reference at Section 219.112 of this Part, shall be used to measure organic compound concentrations at this site.
 - ii) The efficiency of the final recovery device is determined by measuring the organic compound concentrations using Method 18, incorporated by reference at Section 219.112 of this Part, at the inlet to the final recovery device after the introduction of all vent streams and at the outlet of the final recovery device.
 - iii) The efficiency of the final recovery device determined according to subsection (a) (1) (B) (ii) of this Appendix shall be applied to the organic compound concentrations measured according to subsection (a) (1) (B) (i) of this Appendix to determine the concentrations of organic compounds from the final recovery device attributable to the reactor or distillation unit vent stream. The resulting organic compound concentrations are then used to perform the calculations outlined in subsection (a) (4) of this Appendix.
- 2) The molar composition of the vent stream shall be determined as follows:
- A) Method 18, incorporated by reference at Section 219.112 of this Part, to measure the concentration

of organic compounds including those containing halogens;

- B) ASTM D1946-77, incorporated by reference at Section 219.112 of this Part, to measure the concentration of carbon monoxide and hydrogen; and
 - C) Method 4, incorporated by reference at Section 219.112 of this Part, to measure the content of water vapor.
- 3) The volumetric flow rate shall be determined using Method 2, 2A, 2C, or 2D, incorporated by reference at Section 219.112 of this Part, as appropriate.
- 4) The emission rate of VOM (minus methane and ethane) (E_{VOM}) in the vent stream shall be calculated using the following formula:

$$E_{VOM} = K_2 \sum_{j=1}^n C_j M_j Q_s$$

where:

E_{VOM} = Emission rate of VOM (minus methane and ethane) in the sample, kg/hr.

K_2 = Constant, 2.494×10^{-6} (1/ppmv) (g-mole/scm) (kg/g) (min/hr), where standard temperature for (g-mole/scm) is 20°C.

C_j = Concentration of compound j, on a dry basis, in ppmv as measured by Method 18, incorporated by reference at Section 219.112 of this Part, as indicated in Section 219.433(c) (3) of this Part.

M_j = Molecular weight of sample j, g/g-mole.

Q_s = Vent stream flow rate (scm) at a temperature of 20°C.

- 5) The total vent stream concentration (by volume) of compounds containing halogens (ppmv, by compound) shall be summed from the individual concentrations of compounds containing halogens which were measured by Method 18, incorporated by reference at Section 219.112 of this Part.
- 6) The net heating value of the vent stream shall be calculated using the following:

$$H_T = K_1 \sum_{j=1}^n C_j H_j (1 - B_{ws})$$

where:

H_T = Net heating value of the sample (MJ/scm), where the net enthalpy per mole of vent stream is based on combustion of 25°C and 760 mmHG, but the standard temperature for determining the volume corresponding to one mole is 25°C 20°C as in the definition of Q_s (vent stream flow rate).

K_1 = Constant, 1.740×10^{-7} (ppmv)⁻¹ (g-mole/scm), (MJ/KCal), where standard temperature for (g-mole/scm) is 20°C.

B_{ws} = Water vapor content of the vent stream, proportion by volume; except that if the vent stream passes through a final stream jet and is not condensed, it shall be assumed that $B_{ws} = 0.023$ in order to correct to 2.3 percent moisture.

C_j = Concentration on a dry basis of compound j in ppmv, as measured for all organic compounds by Method 18, incorporated by reference at Section 219.112 of this Part, and measured for hydrogen and carbon monoxide by using ASTM D1946-77, incorporated by reference at Section 219.112 of this Part.

H_j = Net heat of combustion of compound j , kCal/g-mole, based on combustion at 25°C and 760 mmHG. The heats of combustion of vent stream components shall be determined using ASTM D2382-83, incorporated by reference at Section 219.112 of this Part, if published values are not available or cannot be calculated.

- b) 1) The TRE index value of the vent shall be calculated using the following:

$$TRE = \frac{1}{E_{VOM}} [a + b (Q_s) + c (H_T) + d (E_{VOM})]$$

where:

TRE = TRE index value.

- E_{VOM} = Hourly emission rate of VOM (kg/hr) as calculated in subsection (a) (4) of this Appendix.
- Q_s = Vent stream flow rate scm/min at a standard temperature of 20°C.
- H_T = Vent stream net heating value (MJ/scm), as calculated in subsection (a) (6) of this Appendix.
- E_{VOM} = Hourly emission rate of VOM (minus methane and ethane), (kg/hr) as calculated in subsection (a) (4) of this Appendix.
- a,b,
c,d = Value of coefficients presented below are:

Type of Stream	Control Device Basis	Value of Coefficients			
		a	b	c	d
Nonhalogenated	Flare	2.129	0.183	-0.005	0.359
	Thermal incinerator zero (0) Percent heat Recovery	3.075	0.021	-0.037	0.018
	Thermal incinerator 70 Percent heat Recovery	3.803	0.032	-0.042	0.007
Halogenated	Thermal incinerator and scrubber	5.470	0.181	-0.040	0.004

- 2) Every owner or operator of a vent stream shall use the applicable coefficients identified for values a, b, c and d in subsection (b) (1) of this Appendix to calculate the TRE index value based on a flare, a thermal incinerator with zero percent heat recovery, and a thermal incinerator with 70 percent heat recovery, and shall select the lowest TRE index value.
- 3) Every owner or operator of a reactor or distillation unit with a halogenated vent stream, determined as any stream with a total concentration of halogen atoms contained in organic compounds of 200 ppmv or greater, shall use the applicable coefficients identified for values a, b, c and d in subsection (b) (1) of this Appendix to calculate the TRE index value based on a thermal incinerator and scrubber.


- c) Every owner or operator of a source seeking to comply with Section 219.432(b) of this Part shall recalculate the flow rate and VOM concentration for each affected vent stream whenever process changes are made. Examples of process changes include, but are not limited to, changes in production capacity, feedstock type, or catalyst type, or whenever there is replacement, removal, or addition of recovery equipment. The flow rate and VOM concentration shall be recalculated based on test data, or on best engineering estimates of the effects of the change to the recovery system.
- d) Whenever a process change, as defined in Section 219.435(c) of this Subpart, yields a TRE index value of 1.0 or less, the owner or operator shall notify and submit a report to the Agency according to the requirements specified in Section 219.435(c) of this Subpart, within 180 calendar days after the process change and shall conduct a performance test according to the methods and procedures required by Section 219.433 of this Part.
- e) For the purpose of demonstrating that a process vent stream has a VOM concentration below 500 ppmv, the following shall be used:
 - 1) The sampling site shall be selected as specified in Section 219.433(c)(1) of this Part.
 - 2) Method 18 or Method 25A of 40 CFR Part 60, Appendix A, incorporated by reference at Section 219.112 of this Part, shall be used to measure concentration; alternatively, any other method or data that has been validated according to the protocol in Method 301 of 40 CFR Part 63, Appendix A, incorporated by reference at Section 219.112 of this Part, may be used.
 - 3) Where Method 18 is used, the following procedures shall be used to calculate ppmv concentration:
 - i) The minimum sampling time for each run shall be 1 hour in which either an integrated sample or four grab samples shall be taken. If grab sampling is used, then the samples shall be taken at approximately equal intervals in time, such as 15 minute intervals during the run.
 - ii) The concentration of VOM shall be calculated using Method 18 according to Section 219.433(c)(4) of this Part.
 - 4) Where Method 25A is used, the following procedures shall be used to calculate ppmv VOM concentration:

- A) Method 25A shall be used only if a single VOM is greater than 50 percent of total VOM, by volume, in the process vent stream.
 - B) The vent stream composition may be determined by either process knowledge, test data collected using an appropriate Reference Method or a method of data collection validated according to the protocol in Method 301 of 40 CFR Part 63, Appendix A, incorporated by reference at Section 219.112 of this Part. Examples of information that constitute process knowledge include calculations based on material balances, process stoichiometry, or previous test results provided the results are still relevant to the current process vent stream conditions.
 - C) The VOM used as the calibration gas for Method 25A shall be the single VOM present at greater than 50 percent of the total VOM by volume.
 - D) The span value for Method 25A shall be 50 ppmv.
 - E) Use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.
 - F) The concentration of VOM shall be corrected to 3 percent oxygen using the procedures and equation in Section 219.433(c) (3) of this Part.
- 5) The owner or operator shall demonstrate that the concentration of VOM, including methane and ethane, measured by Method 25A is below 250 ppmv to qualify for the low concentration exclusion in Section 219.431 of this Part.

(Source: Amended at _____ Ill. Reg. _____, effective _____)

IT IS SO ORDERED.

I, Dorothy M. Gunn, Clerk of the Illinois Pollution Control Board, hereby certify that the above opinion and order was adopted on the 21st day of March, 1996, by a vote of 7-0.



Dorothy M. Gunn, Clerk
Illinois Pollution Control Board